

WSEP 2026: External Systems API

The external payment and ticket issuance systems are accessible by sending an HTTP POST request to the following web address:

<https://damp-lynnna-wsep-1984852e.koyeb.app/>

In order to specify which service to request from these systems, the content of the post message must contain an **action_type**. In addition, any parameter required by the desired action type should also appear in the content of the message. The **action_types** supported by the external systems are: **handshake**, **pay**, **refund**, **issue_ticket**, and **cancel_ticket**.

Actions

handshake:

This action type is used for checking the availability of the external systems.

- **action_type:** handshake
- **Additional Parameters:** none
- **Output:** “OK” message to signify that the handshake has been successful.

pay:

This action type is used for charging a payment for purchases.

- **action_type:** pay
- **Additional Parameters:** amount, currency, card_number, month, year, holder, cvv, id
- **Output:** transaction id - an integer in the range [10000, 100000] which indicates a transaction number if the transaction succeeds, or -1 if the transaction has failed.

refund:

This action type is used for cancelling a payment transaction and automatically crediting the customer.

- **action_type:** refund
- **Additional Parameters:** transaction_id - the id of the transaction to be refunded.
- **Output:** 1 if the refund has been successful or -1 if the refund has failed.

issue_ticket:

This action type is used for generating a secure digital barcode/ticket code for a customer.

- **action_type:** issue_ticket

- **Additional Parameters:** `customer_id`, `event_id`, `zone`.
 - For general admission/standing zones: `quantity`
 - For assigned seating zones: `is_seating` (true) and `seats` (accepted as either a JSON-serialized string OR a structured array containing row and seat identifiers).
- **Output:** A ticket identifier/secure code string (e.g., `TIx-1a2b-3456`) if the transaction succeeds, or -1 if the transaction has failed.

cancel_ticket:

This action type is used for cancelling an issued ticket (e.g., during system-initiated rollbacks).

- **action_type:** `cancel_ticket`
- **Additional Parameters:** `ticket_id` - the id of the ticket to be canceled.
- **Output:** 1 if the cancellation has been successful or -1 if the cancellation has failed.

Usage Examples

Java Examples

An example of the content of the respective POST request in a map format for each of the supported actions:

```

1 import java.util.Map;
2 import java.util.HashMap;
3
4 // handshake:
5 Map<String, String> handshake = Map.of(
6     "action_type", "handshake"
7 );
8
9 // pay:
10 Map<String, String> pay = new HashMap<>();
11 pay.put("action_type", "pay");
12 pay.put("amount", "1000");
13 pay.put("currency", "USD");
14 pay.put("card_number", "2222333344445555");
15 pay.put("month", "4");
16 pay.put("year", "2021");
17 pay.put("holder", "Israel Israelovice");
18 pay.put("cvv", "262");
19 pay.put("id", "20444444");
20
21 // refund:
22 Map<String, String> refund = Map.of(

```

```

23     "action_type", "refund",
24     "transaction_id", "20123"
25 );
26
27 // issue_ticket (Standing / General Admission):
28 Map<String, String> issueTicketStanding = Map.of(
29     "action_type", "issue_ticket",
30     "customer_id", "849302",
31     "event_id", "EVT-9923",
32     "zone", "Golden Ring",
33     "quantity", "2"
34 );
35
36 // issue_ticket (Assigned Seating - JSON String format):
37 Map<String, String> issueTicketSeating = Map.of(
38     "action_type", "issue_ticket",
39     "customer_id", "849302",
40     "event_id", "EVT-9923",
41     "zone", "VIP Balcony",
42     "is_seating", "true",
43     "seats", "[{\"row\": 4, \"seat\": 12}, {\"row\": 4, \"
44         seat\": 13}]"
45 );
46
47 // cancel_ticket:
48 Map<String, String> cancelTicket = Map.of(
49     "action_type", "cancel_ticket",
50     "ticket_id", "TIX-1a2b-3456"
51 );

```

Command Line Examples (cURL & PowerShell)

You can test the API using standard command-line tools. Below are examples of triggering the `pay` and `issue_ticket` actions.

Windows (PowerShell):

```

1 # Example 1: Processing a payment
2 Invoke-WebRequest -Uri "https://damp-lynna-wsep-1984852e.
3     koyeb.app/" '
4     -Method POST '
5     -Body @{
6         action_type="pay";
7         amount="1000";
8         currency="USD";
9         card_number="2222333344445555";
10        month=4;
11        year=2021;
12        holder="israel";
13        cvv=262;

```

```

13         id=20444444
14     }
15
16 # Example 2: Issuing a ticket (General Admission)
17 Invoke-WebRequest -Uri "https://damp-lynna-wsep-1984852e.
    koyeb.app/" '
18     -Method POST '
19     -Body @{
20         action_type="issue_ticket";
21         customer_id="849302";
22         event_id="EVT-9923";
23         zone="Golden Ring";
24         quantity=2
25     }

```

Linux / macOS (cURL):

```

1 # Example 1: Processing a payment
2 curl -X POST https://damp-lynna-wsep-1984852e.koyeb.app/ \
3     -d "action_type=pay" \
4     -d "amount=1000" \
5     -d "currency=USD" \
6     -d "card_number=2222333344445555" \
7     -d "month=4" \
8     -d "year=2021" \
9     -d "holder=israel" \
10    -d "cvv=262" \
11    -d "id=20444444"
12
13 # Example 2: Issuing a ticket (Assigned Seating - JSON
    String format)
14 curl -X POST https://damp-lynna-wsep-1984852e.koyeb.app/ \
15     -d "action_type=issue_ticket" \
16     -d "customer_id=849302" \
17     -d "event_id=EVT-9923" \
18     -d "zone=VIP Balcony" \
19     -d "is_seating=true" \
20     --data-urlencode 'seats=[{"row": 4, "seat": 12}, {"row":
    4, "seat": 13}]'
21
22 # Example 3: Issuing a ticket (Assigned Seating - Structured
    Array format)
23 curl -X POST https://damp-lynna-wsep-1984852e.koyeb.app/ \
24     -d "action_type=issue_ticket" \
25     -d "customer_id=849302" \
26     -d "event_id=EVT-9923" \
27     -d "zone=VIP Balcony" \
28     -d "is_seating=true" \
29     -d "seats[0][row]=4" \
30     -d "seats[0][seat]=12" \

```

```
31     -d "seats[1][row]=4" \  
32     -d "seats[1][seat]=13"
```