
# UNIVERSITY OF ASIA PACIFIC

**Department of Computer Science & Engineering**

## LAB ASSIGNMENT-01

**Course Title** : Microprocessors and Assembly Language Lab

**Course Code** : CSE 312

**Date of Submission:** 14/09/2022

**Submitted by:**

**Name** : Sheikh Nafez Sadnan

**Reg. No.** : 20101106

**Roll No.** : 106

**Section** : B (2)

**Submitted To:**

Faria Zarin Subah

Lecturer

Department of CSE

University of Asia Pacific

# Problem Statement 1:

Perform the following operations using emu8086:

a) Declare the following variables assigning the stated values:

**Table1:**

| Variable_name | Variable_size | Value_assigned |
|---|---|---|
| NUMB | DB | 01111000B |
| NUMD | DB | 120D |
| NUMO | DB | 170O |
| NUMH | DB | 78H |
| CHAR | DB | '3' |
| CHARASC | DB | 3 |
| STR | DB | "HELLO WORLD" |
| UNKNOWN | DB | ? |

b) Take any character as input and assign that character as the value of the UNKNOWN variable.

c) Print the values of all 8 variables with a newline between each print statement. Provide a screenshot of your output screen.

d) Provide a screenshot showing the status of the variables after emulating your code.

e) State the reason why each output shown on the output screen of emu8086 is different from that of **Table1** ? Provide justification for each of the 8 variables.

# Screenshot of the assembly code:

## Line (1-34)




## Line (34-67)



# Line (67-100)




# Line (100-133)



# Line (121-140)




# Assembly Code Screen Shot (While Emulating):



## Status of all 8 variables after assigning values:

**NUMB DB 01111000B:**
After, assigning  NUMB DB 01111000B,
AH got 02 (Calling the output subroutine)
DL got 78H (Equivalent to 01111000B)

Output is x which is different from Table-1
Because, in ASCII table **120:x** (01111000B/78H equivalent to 120 in decimal.)






**NUMD DB 120D:**
After, assigning NUMD DB 120D,
AH got 02 (Calling the output subroutine)
DL got 78H (Equivalent to 120D)

Output is x which is different from Table-1
Because, in ASCII table **120:x** (78H equivalent to 120 in decimal.)


variables
size: byte
elements: 1
edit
show as: hex
NUMB 'x'
NUMD 78h
NUMO 78h
NUMH 78h
CHAR 33h
CHARASC 03h
STR 48h
UNKNOWN 41h


variables
size: byte
elements: 1
edit
show as: ascii
NUMB 'x'
NUMD 'x'
NUMO 78h
NUMH 78h
CHAR 33h
CHARASC 03h
STR 48h
UNKNOWN 41h

**NUMO DB 170O:**
After, assigning  NUMO DB 170O,
AH got 02 (Calling the output subroutine)
DL got 78H (Equivalent to 170O)

Output is x which is different from Table-1
Because, in ASCII table **120:x** (170O/78H equivalent to 120 in decimal.)






**NUMH DB 78H:**
After, assigning NUMH DB 78H,
AH got 02 (Calling the output subroutine)
DL got 78H

Output is x which is different from Table-1
Because, in ASCII table **120:x** (78H equivalent to 120 in decimal.)


variables
size: byte
elements: 1
edit
show as: hex
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 78h
CHAR 33h
CHARASC 03h
STR 48h
UNKNOWN 41h


variables
size: byte
elements: 1
edit
show as: ascii
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 'x'
CHAR 33h
CHARASC 03h
STR 48h
UNKNOWN 41h

**CHAR DB '3':**
After, assigning  CHAR DB ‘3’,
AH got 02 (Calling the output subroutine)
DL got 33H

Output is 3 which is different from Table-1
Because, in ASCII table **051:3** (33H equivalent to 051 in decimal.)






**CHARASC DB 3:**
After, assigning  CHARASC DB 3,
AH got 02 (Calling the output subroutine)
DL got 03H

Output is a heart shape emoji which is different from Table-1
Because, in ASCII table **003:** ♥ (03H equivalent to 003 in decimal.)


variables
size: byte
elements: 1
edit
show as: hex
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 'x'
CHAR '3'
CHARASC 03h
STR 48h
UNKNOWN 41h


variables
size: byte
elements: 1
edit
show as: ascii
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 'x'
CHAR '3'
CHARASC '♥'
STR 48h
UNKNOWN 41h

**STR DB "HELLO WORLD":**
Input needs a dollar ($) sign after the string.
Input- STR DB "HELLO WORLD$"
After, assigning STR DB “HELLO WORLD$”,
AH got 09 (Display string function)

Output is HELLO WORLD which is different from Table-1
Because, LEA DX, STR receives the string and INT 21H displays it.






**UNKNOWN DB ? :**
After, assigning UNKNOWN DB ?,
AH got 02 (Calling the output subroutine)
DL got 41H

Output is A which was given as input, which is different from Table-1
Because, in ASCII table **065:A** (41H equivalent to 065 in decimal.)


variables
size: byte
elements: 1
edit
show as: hex
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 'x'
CHAR '3'
CHARASC '♥'
STR 'H'
UNKNOWN 41h


variables
size: byte
elements: 1
edit
show as: ascii
NUMB 'x'
NUMD 'x'
NUMO 'x'
NUMH 'x'
CHAR '3'
CHARASC '♥'
STR 'H'
UNKNOWN 'A'

## A screenshot of the output screen:

After all values are assigned, output displays on screen:


Here,

A (Given Input)

x (Output of 01111000B)

x (Output of 120D)

x (Output of 170O)

x (Output of 78H)

3 (Output of '3')

♥ (Output of 3)

HELLO WORLD (Output of ‘HELLO WORLD’)

A (Output of given Input)

**Reference:** The ASCII code table-