Digital Image Processing

Lecture #8

Ming-Sui (Amy) Lee

Course Information

- **Following Schedule**

03/28	Lecture 4	05/16	Proposal
04/04	溫書假	05/23	Lecture 9
04/11	Lecture 5	05/30	Lecture 10
04/18	Lecture 6	06/06	Lecture 11
04/25	Midterm	06/13	Demo
05/02	Lecture 7	06/20	Demo
05/09	Lecture 8	06/27	Final Package Due

Announcement

- Proposal
  - May 16, 2018
  - Check the list announced on CEIBA
  - Oral presentation (PPT) AND Written report (PDF)
    - Paper title
    - Motivation
    - Problem definition
    - Algorithm
    - Expected results
    - Reference

Image Sampling & Transforms

Image Sampling & Transforms

- **Image sampling**
  - **A/D conversion**
    - **Usually deals with arrays of numbers obtained by spatially sampling points of a physical image**
    - $F_I(x,y)$ **: continuous, infinite-extent, ideal image field**
    - $F_P(x,y)$ **: the sampled image**

$$S(x,y) = \sum_{j=-\infty}^{\infty} \sum_{k=-\infty}^{\infty} \delta(x - j\Delta x, y - k\Delta y)$$

Dirac delta function

Image Sampling & Transforms

- **Image sampling**
  - **Sampling function** $S(x,y) = \sum_{j=-\infty}^{\infty} \sum_{k=-\infty}^{\infty} \delta(x - j\Delta x, y - k\Delta y)$
    - **An infinite array of the Dirac delta functions arranged in a grid of spacing,** $(\Delta x, \Delta y)$
  - **Space domain**

$$F_P(x,y) = F_I(x,y)S(x,y) = \sum_{j=-\infty}^{\infty} \sum_{k=-\infty}^{\infty} F_I(j\Delta x, k\Delta y)\delta(x - j\Delta x, y - k\Delta y)$$

  - **Transform domain (Fourier transform)**

(Convolution Theorem)

$$\mathcal{F}_P(\omega_x,\omega_y) = \int_{-\infty}^{\infty}\int_{-\infty}^{\infty} F_P(x,y)\exp\{-i(\omega_x x + \omega_y y)\}dxdy = \frac{1}{4\pi^2}\mathcal{F}_I(\omega_x,\omega_y) \otimes S(\omega_x,\omega_y)$$

Sampling frequency

where $S(\omega_x,\omega_y) = \frac{4\pi^2}{\Delta x \Delta y} \sum_{j=-\infty}^{\infty} \sum_{k=-\infty}^{\infty} \delta(\omega_x - j\omega_{xs}, \omega_y - k\omega_{ys})$

and $\omega_{xs} = 2\pi / \Delta x \quad and \quad \omega_{ys} = 2\pi / \Delta y$

Image Sampling & Transforms

- **Image sampling**
  - **Transform domain (Fourier transform)**
    - **Assume the spectrum of the ideal image is band-limited**

$$\mathcal{F}_P(\omega_x,\omega_y)=\int_{-\infty}^{\infty}\int_{-\infty}^{\infty}F_P(x,y)\exp\{-i(\omega_x x+\omega_y y)\}dxdy=\frac{1}{4\pi^2}\mathcal{F}_I(\omega_x,\omega_y)\otimes S(\omega_x,\omega_y)$$

$$=\frac{1}{\Delta x\Delta y}\int_{-\infty}^{\infty}\int_{-\infty}^{\infty}\mathcal{F}_I(\omega_x-\alpha,\omega_y-\beta)\times\sum_{j=-\infty}^{\infty}\sum_{k=-\infty}^{\infty}\delta(\alpha-j\omega_{xs},\beta-k\omega_{ys})d\alpha d\beta$$

$$=\frac{1}{\Delta x\Delta y}\sum_{j=-\infty}^{\infty}\sum_{k=-\infty}^{\infty}\mathcal{F}_I(\omega_x-j\omega_{xs},\omega_y-k\omega_{ys})$$

where $\omega_{xs}=2\pi/\Delta x \quad and \quad \omega_{ys}=2\pi/\Delta y$

(a) Original image

(b) Sampled image

Overlapping?

Image Sampling & Transforms

- **Image sampling**
  - **Transform domain (Fourier transform)**
    - **Assume the spectrum of the ideal image is limited and suppose that the cutoff frequency is $(\omega_{xc}, \omega_{yc})$**
      i.e. $\mathcal{F}_I(\omega_x, \omega_y)$ is non-zero only in the region bounded

      by $|\omega_x| \le \omega_{xc}$ $|\omega_y| \le \omega_{yc}$

(a) Original image

Image Sampling & Transforms

- **Image sampling**
  - **Transform domain (Fourier transform)**
    - **If** $\omega_{xc} \le \frac{\omega_{xs}}{2}, \quad \omega_{yc} \le \frac{\omega_{ys}}{2}$,

      there is no overlapping (no aliasing) between adjacent shifted waveforms of $\mathcal{F}_P(\omega_x, \omega_y)$
  - **Sampling Theorem**
    - **To sample a band-limited signal, the sampling period must be no longer than one-half of the period of the finest details within the image to avoid aliasing**
    - **Generalization of the 1D Nyquist Theorem to the 2D case**

Image Sampling & Transforms

- **Sampling Theorem**
  - **To sample a band-limited signal, the sampling period must be no longer than one-half of the period of the finest details within the image to avoid aliasing**

Original image

Sampled image

Image Sampling & Transforms

- Image Transform
  - Why image transform?
    - Feature extraction
    - Energy compaction
  - We are able to concentrate energy distribution over a small number of transform coefficients
    - Can be exploited for compression purpose
      - DCT – Discrete Cosine Transform
      - Block-based transform – 8x8

Image Sampling & Transforms

- **General 2D transform**
  - **Forward**

$$F(j,k) \longrightarrow \boxed{\begin{array}{c}\text{Transform}\\ \text{Kernel}\\ \text{A(j,k;u,v)}\end{array}} \longrightarrow \tilde{F}(u,v)$$

$$0 \le j,k \le N-1 \qquad\qquad 0 \le u,v \le N-1$$

  - **Backward**

$$\tilde{F}(u,v) \longrightarrow \boxed{\begin{array}{c}\text{Inverse Transform}\\ \text{Kernel}\\ \text{B(u,v;j,k)}\end{array}} \longrightarrow F(j,k)$$

$$0 \le u,v \le N-1 \qquad\qquad 0 \le j,k \le N-1$$

Image Sampling & Transforms

- **2D separable transform**
  - **General 2D transform**
    - **Forward**

$$\widetilde{F}(u,v) = \sum_{j=0}^{N-1}\sum_{k=0}^{N-1} F(j,k)A(j,k;u,v)$$

    - **Backward**

$$F(j,k) = \sum_{u=0}^{N-1}\sum_{v=0}^{N-1} \widetilde{F}(u,v)B(u,v;j,k)$$

    - **If A and B are separable, we have**

$$A(j,k;u,v) = A_X(j,u)A_Y(k,v)$$

$$B(u,v;j,k) = \underbrace{B_X(u,j)}_{\text{x-direction}}\underbrace{B_Y(v,k)}_{\text{y-direction}}$$

Image Sampling & Transforms

- **2D separable transform**
  - **The real advantage is the low computational cost of the separable transform**
    - **General 2D transform**

$$\widetilde{F}(u,v) = \sum_{j=0}^{N-1}\sum_{k=0}^{N-1} F(j,k)A(j,k;u,v)$$

$O(N^2)$ **per (u,v)** **&** $O(N^4)$ **for all (u,v)**

    - **Separable 2D transform**

$$\widetilde{F}(u,v) = \sum_{k=0}^{N-1}\left(\sum_{j=0}^{N-1} F(j,k)A_X(j,u)\right)A_Y(k,v)$$

$2N$ **per (u,v)** **&** $2N^3$ **for all (u,v)**

Image Sampling & Transforms

- **Unitary Transform**
  - **Consider 1D transform**

$$\tilde{F}(u) = \sum_{j=0}^{N-1} F(j) A(j,u)$$

$$\underline{f} = \begin{bmatrix} F(0) \\ F(1) \\ \vdots \\ F(N-1) \end{bmatrix} \quad \underline{\tilde{f}} = \begin{bmatrix} \tilde{F}(0) \\ \tilde{F}(1) \\ \vdots \\ \tilde{F}(N-1) \end{bmatrix} \quad A = \begin{bmatrix} A(0,0) & \cdots & A(N-1,0) \\ \vdots & \ddots & \vdots \\ A(0,N-1) & \cdots & A(N-1,N-1) \end{bmatrix}$$

  - **Forward** $\underline{\tilde{f}} = A\underline{f}$ $\Rightarrow B = A^{-1}$
  - **Backward** $\underline{f} = B\underline{\tilde{f}}$ **Gaussian elimination** $\Rightarrow O(N^3)$

Image Sampling & Transforms

- **Unitary Transform**
  - The inverse is easy to compute

$$A^H A = AA^H = I \quad \Rightarrow A^{-1} = A^H$$

$$A^H = (A^*)^T = (A^T)^*$$

- **Karhunen Loeve Transform (KLT)**
  - Hotelling transform / Eigenvector transform
  - Linear transform
  - Ideal for energy compaction
  - Principal component analysis (PCA)/Singular Value Decomposition (SVD)
  - Basis functions are image dependent
  - High computation cost for obtaining basis images

Image Sampling & Transforms

- **Karhunen Loeve Transform (KLT)**
  - Hotelling transform / Eigenvector transform
  - Linear transform
  - Ideal for energy compaction
  - Principal component analysis (PCA)/ Singular Value Decomposition (SVD)
  - Basis functions are image dependent
  - High computation cost for obtaining basis images

Image Sampling & Transforms

- **Karhunen Loeve Transform (KLT)**
  - **Mean and covariance matrix**

$$\underline{m}_x = E\{\underline{x}\} = [m_1 \quad m_2 \quad \ldots \quad m_n]^T = [E\{x_1\} \quad E\{x_2\} \quad \ldots \quad E\{x_n\}]^T$$

$$C = E\{(\underline{x} - \underline{m}_x)(\underline{x} - \underline{m}_x)^T\}$$

  - Let *A* be a matrix whose rows are formed from the eigenvectors of the covariance matrix *C*
  - *A* is ordered so that the first row is the eigenvector corresponding to the largest eigenvalue, and the last row is the eigenvector corresponding to the smallest eigenvalue
  - The following transform is called the Karhunen-Loeve transform

$$\underline{y} = A(\underline{x} - \underline{m}_x)$$

Image Sampling & Transforms

- **Example**

Original images (channels)

Six principal components after KL transform

Image Sampling & Transforms

- **Discrete Fourier Transform (DFT)**
  - **Idea**
    - **Any function that periodically repeats itself can be expressed as a sum of sine and cosine of different frequencies.**

Image Sampling & Transforms

- **Discrete Fourier Transform (DFT)**
  - **Transform**

$$F(u,v) = \frac{1}{n}\sum_{j=0}^{n-1}\sum_{k=0}^{n-1} f(j,k)\exp\{-\frac{2\pi i(uj+vk)}{n}\}$$

  - **Inverse DFT**

$$f(j,k) = \frac{1}{n}\sum_{u=0}^{n-1}\sum_{v=0}^{n-1} F(u,v)\exp\{\frac{2\pi i(uj+vk)}{n}\}$$

$i = \sqrt{-1}$ **and** $f(j,k)$ **is the input sequence**

Image Sampling & Transforms

- **Discrete Fourier Transform (DFT)**
  - **Fast Fourier Transform (FFT)**
    - $O(n \log n)$
  - **Not so popular in image compression**
    - **performance is not good enough**
    - **computational cost for complex number is expensive**

Image Sampling & Transforms

- **Discrete Fourier Transform (DFT)**
  - **Example**

original

log magnitude

Image Sampling & Transforms

- **Discrete Fourier Transform (DFT)**
  - **Application – Noise reduction**

Image Sampling & Transforms

- Discrete Fourier Transform (DFT)
  - Application– Low Pass Filter

Image Sampling & Transforms

- Discrete Fourier Transform (DFT)
  - Application– Low Pass Filter

Original image

After low pass filter

Image Sampling & Transforms

- **Discrete Cosine Transform (DCT)**
  - **1D DCT basis functions**

n=8

Image Sampling & Transforms

- **Discrete Cosine Transform (DCT)**
  - **Transform**

$$F(u,v) = \frac{C(u)C(v)}{4}\sum_{j=0}^{n-1}\sum_{k=0}^{n-1} f(j,k)cos\left[\frac{(2j+1)u\pi}{2n}\right]cos\left[\frac{(2k+1)v\pi}{2n}\right]$$

  - **Inverse DCT**

$$f(j,k) = \sum_{v=0}^{n-1}\sum_{u=0}^{n-1} C(u)C(v)F(u,v)cos\left[\frac{(2j+1)u\pi}{2n}\right]cos\left[\frac{(2k+1)v\pi}{2n}\right]$$

$$C(w) = \begin{cases} 1/\sqrt{2} & \text{if } w = 0 \\ 1 & \text{if } w = 1,2,\ldots,n\text{-}1 \end{cases}$$

Image Sampling & Transforms

- **Discrete Cosine Transform (DCT)**
  - **Transform**

$$F(u,v) = \frac{C(u)C(v)}{4}\sum_{j=0}^{n-1}\sum_{k=0}^{n-1} f(j,k)cos\left[\frac{(2j+1)u\pi}{2n}\right]cos\left[\frac{(2k+1)v\pi}{2n}\right]$$

$$F_{10} = \frac{c_1 c_0}{4}\left[\cos\frac{\pi}{16}\left(\sum_{i=0}^{7} f(0,j) - \sum_{i=0}^{7} f(7,j)\right) + \cos\frac{3\pi}{16}\left(\sum_{i=0}^{7} f(1,j) - \sum_{i=0}^{7} f(6,j)\right) + \right.$$

$$\left. \cos\frac{5\pi}{16}\left(\sum_{i=0}^{7} f(2,j) - \sum_{i=0}^{7} f(5,j)\right) + \cos\frac{7\pi}{16}\left(\sum_{i=0}^{7} f(3,j) - \sum_{i=0}^{7} f(4,j)\right)\right]$$

Image Sampling & Transforms

- **2D DCT basis functions (8x8)**

Image Sampling & Transforms

- The Meaning of DCT Coefficients
  - Represent the spatial frequency content within an 8x8 image block
  - The (0,0) coefficient is called DC coefficient
    - The average of the 64 image pixel values in the block
  - The rest of 63 coefficients are called AC coefficients
  - Move to the right of the block

    → the energy in higher horizontal frequencies
  - Move down the block

    → the energy in higher vertical frequencies

Image Sampling & Transforms

- Examples of 8x8 DCT Coefficients

Image Sampling & Transforms

- **Discrete Cosine Transform (DCT)**

Vertical-dominant	section 1	$\lvert F01\rvert > \lvert F10\rvert$	$F01 \le 0$	$F10 > 0$	
				$F10 < 0$	
	section 2		$F01 \ge 0$	$F10 > 0$	
				$F10 < 0$	
Horizontal-dominant	section 3	$\lvert F01\rvert < \lvert F10\rvert$	$F10 \le 0$	$F01 > 0$	
				$F01 < 0$	
	section 4		$F10 \ge 0$	$F01 > 0$	
				$F01 < 0$	

Vertical	$F10 = 0$	$F01 > 0$	
		$F01 < 0$	
Horizontal	$F01 = 0$	$F10 > 0$	
		$F10 < 0$	
Diagonal	$\lvert F01\rvert = \lvert F10\rvert$	$F01 < 0,$ $F10 > 0$	
		$F01 > 0,$ $F10 < 0$	
		$F01 > 0,$ $F10 > 0$	
		$F01 < 0,$ $F10 < 0$	

Bo Shen and Ishwar K. Sethi, "Direct feature extraction from compressed images,"1996

Image Sampling & Transforms

- **Discrete Cosine Transform (DCT)**
  - Use cosine function as its basis function
  - Performance similar to KLT
  - Fast algorithm available
  - Most popular in image compression
  - JPEG (Joint Photographic Experts Group)
  - The periodicity implied by DCT implies that less blocking artifact will be introduced than DFT

Image Sampling & Transforms

- **Hadamard transform**
  - **Based on Hadamard matrix**
    - **A square array with elements of plus and minus 1's**
    - **Rows and columns are orthogonal**
    - **A normalized Hadamard matrix satisfies** $HH^T = I$
    - **The general form:**

$$H_{2N} = \frac{1}{\sqrt{2}} \begin{bmatrix} H_N & H_N \\ H_N & -H_N \end{bmatrix}$$

$$\mathbf{H}_2 = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix}$$

$$\mathbf{H}_4 = \frac{1}{2} \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & -1 \\ 1 & 1 & -1 & -1 \\ 1 & -1 & -1 & 1 \end{bmatrix} \quad \begin{matrix} \text{Sign Changes} \\ 0 \\ 3 \\ 1 \\ 2 \end{matrix}$$

$$\mathbf{H}_8 = \frac{1}{2\sqrt{2}} \left[\begin{array}{cccc|cccc} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & -1 & 1 & -1 & 1 & -1 \\ 1 & 1 & -1 & -1 & 1 & 1 & -1 & -1 \\ 1 & -1 & -1 & 1 & 1 & -1 & -1 & 1 \\ \hline 1 & 1 & 1 & 1 & -1 & -1 & -1 & -1 \\ 1 & -1 & 1 & -1 & -1 & 1 & -1 & 1 \\ 1 & 1 & -1 & -1 & -1 & -1 & 1 & 1 \\ 1 & -1 & -1 & 1 & -1 & 1 & 1 & -1 \end{array}\right] \quad \begin{matrix} \text{Sign Changes} \\ 0 \\ 7 \\ 3 \\ 4 \\ 1 \\ 6 \\ 2 \\ 5 \end{matrix}$$

Image Sampling & Transforms

- **Hadamard transform**

e.g. N=16

e.g. N=4

$$\mathbf{H}_8 = \frac{1}{2\sqrt{2}} \left[\begin{array}{cccc|cccc} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & -1 & 1 & -1 & 1 & -1 & 1 & -1 \\ 1 & 1 & -1 & -1 & 1 & 1 & -1 & -1 \\ 1 & -1 & -1 & 1 & 1 & -1 & -1 & 1 \\ \hline 1 & 1 & 1 & 1 & -1 & -1 & -1 & -1 \\ 1 & -1 & 1 & -1 & -1 & 1 & -1 & 1 \\ 1 & 1 & -1 & -1 & -1 & -1 & 1 & 1 \\ 1 & -1 & -1 & 1 & -1 & 1 & 1 & -1 \end{array}\right] \begin{array}{c} \text{Sign Changes} \\ 0 \\ 7 \\ 3 \\ 4 \\ 1 \\ 6 \\ 2 \\ 5 \end{array}$$

- **Applications**
  - data encryption and signal processing
  - data compression algorithms
    - HD Photo and MPEG-4 AVC
    - video compression
      - the sum of absolute transformed differences

Image Sampling & Transforms

- **Haar transform**
  - **Derived from the Haar matrix**

$$R_N = \begin{bmatrix} V_N \\ W_N \end{bmatrix}_{NxN}$$

$$\mathbf{V}_N = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1 & 0 & 0 & 0 & 0 & \cdots & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 1 & 0 & 0 & \cdots & 0 & 0 & 0 & 0 \\ & & & & & & & & & & \\ 0 & 0 & 0 & 0 & 0 & 0 & \cdots & 1 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & \cdots & 0 & 0 & 1 & 1 \end{bmatrix}$$

Scaling matrix

$$\mathbf{W}_N = \frac{1}{\sqrt{2}} \begin{bmatrix} 1 & -1 & 0 & 0 & 0 & 0 & \dots & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & -1 & 0 & 0 & \dots & 0 & 0 & 0 & 0 \\ & & \vdots & & & & & & \vdots & & \\ 0 & 0 & 0 & 0 & 0 & 0 & \dots & 1 & -1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & \dots & 0 & 0 & 1 & -1 \end{bmatrix}$$

Wavelet matrix

e.g.

$$\mathbf{H}_4 = \frac{1}{2} \begin{bmatrix} 1 & 1 & 1 & 1 \\ 1 & 1 & -1 & -1 \\ \sqrt{2} & -\sqrt{2} & 0 & 0 \\ 0 & 0 & \sqrt{2} & -\sqrt{2} \end{bmatrix}$$

$$\mathbf{H}_8 = \frac{1}{\sqrt{8}} \begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 & -1 & -1 & -1 & -1 \\ \sqrt{2} & \sqrt{2} & -\sqrt{2} & -\sqrt{2} & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & \sqrt{2} & \sqrt{2} & -\sqrt{2} & -\sqrt{2} \\ 2 & -2 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 2 & -2 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 2 & -2 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 2 & -2 \end{bmatrix}$$

Image Sampling & Transforms

- **Haar transform**
  - **1st-level Haar transform of a Nx1 vector f**

$$f_1 = R_N f = [a_1 \mid d_1]^T \quad where \quad \underbrace{a_1 = V_N f;}_{\text{trend}} \quad \underbrace{d_1 = W_N f}_{\text{fluctuation}}$$

  - **2nd-level Haar transform of a Nx1 vector f**

$$f_2 = [a_2 \mid d_2 \mid d_1]^T \quad where \quad a_2 = V_{N/2} a_1; \quad d_2 = W_{N/2} a_1$$

  - **The process continues till the full transformation**

$$\Rightarrow f_n = [a_n \mid d_n \mid d_{n-1} \mid \cdots \mid d_1]^T$$

Image Sampling & Transforms

- **Haar transform**
  - E.g. basis functions with N=16
  - Sample an input data sequence with finer and finer resolution increasing at the power of 2
  - Provide a transform domain in which type of differential energy is concentrated in localized regions

Image Sampling & Transforms

- **Hadamard transform and Haar transform**
  - **Example**

Hadamard transform

Haar transform

Image Sampling & Transforms

- **Hough transform**
  - An edge is not a line…
  - How to detect lines in an image?

Image Sampling & Transforms

- Hough transform
  - How to detect lines in an image?
    - Search for the lines at every position with possible orientations
    - Voting scheme: <u>Hough transform</u>
  - Performed after edge detection
  - Can locate straight lines, circles, parabolas, ellipses, etc
    - As the curve can be specified in a parametric form
  - Advantages
    - Tolerate gaps between edges
    - Relatively unaffected by noise
    - Can deal with occlusion

Image Sampling & Transforms

- **Hough transform**
  - **A straight line can be represented as** $y = mx + b$
    - Vertical lines?
  - **Another representation is**

$$\rho = x\cos\theta + y\sin\theta, \qquad -\frac{\pi}{2} \le \theta \le \frac{\pi}{2}$$

(a) Parametric line

(b)Hough transform

Image Sampling & Transforms

- **Hough transform**

(c) Family of lines, common point

(d) Hough transform of (c)

(e) Colinear points

(f) Hough transform of (e)

Image Sampling & Transforms

- **Hough transform for line detection**
  - Quantize the Hough Transform space
    - Identify the maximum and minimum values of ρ and θ
  - Generate an accumulator array $A(\rho,\theta)$
  - For all edge points (x_i, y_i) in the image
    - Use gradient direction as θ
    - Compute ρ from the equation
    - Increment $A(\rho,\theta)$ by one
  - For all cells in $A(\rho,\theta)$
    - Search for the maximum value
    - Calculate the equation of the line

Image Sampling & Transforms

- **Hough transform for line detection**