

Fichiers de Configuration (Compte-rendu)

Switch C2 :

```
Current configuration : 930 bytes
!
version 12.2
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname Switch
!
boot-start-marker
boot-end-marker
!
!
!
!
no aaa new-model
system mtu routing 1500
!
```

```
spanning-tree mode pvst
spanning-tree extend system-id
!
vlan internal allocation policy ascending
!
!
interface FastEthernet0/1
!
interface FastEthernet0/2
switchport access vlan 20
switchport mode access
spanning-tree portfast
!
interface FastEthernet0/3
!
interface FastEthernet0/4
!
interface FastEthernet0/5
!
interface FastEthernet0/6
!
interface FastEthernet0/7
switchport trunk allowed vlan 10 20
!
```

Switch C1 :

```

spanning-tree mode pvst
spanning-tree extend system-id

vlan internal allocation policy ascending

interface FastEthernet0/1
description LIEN_VERS_R1_ROUTAGE
switchport access vlan 10
switchport trunk allowed vlan 10,20
switchport mode trunk

interface FastEthernet0/2
switchport access vlan 20
switchport mode access

```

```

interface FastEthernet0/3
interface FastEthernet0/4
interface FastEthernet0/5
interface FastEthernet0/6
interface FastEthernet0/7
description LIEN_VERS_C2
switchport trunk allowed vlan 10,20
switchport mode trunk

interface FastEthernet0/8
switchport trunk allowed vlan 10,20
switchport mode trunk

interface GigabitEthernet0/1
interface Vlan1
no ip address
no ip route-cache

```

```

interface FastEthernet0/6
interface FastEthernet0/7
switchport trunk allowed vlan 10,20
switchport mode trunk

interface FastEthernet0/8
switchport access vlan 10
switchport mode access

interface GigabitEthernet0/1

interface Vlan1
no ip address
no ip route-cache

ip http server
ip http secure-server
vstack

line con 0
line vty 5 15
end

```

```

interface FastEthernet0/8
switchport trunk allowed vlan 10,20
switchport mode trunk

interface GigabitEthernet0/1

interface Vlan1
no ip address
no ip route-cache

ip http server
ip http secure-server
vstack

line con 0
line vty 0 4
login
line vty 5 15
login

end

```

Routeur :

```

speed auto

interface FastEthernet0/1.10
encapsulation dot1Q 10
ip address 192.168.10.254 255.255.255.0
no snmp trap link-status

interface FastEthernet0/1.20
encapsulation dot1Q 20
ip address 192.168.20.254 255.255.255.0
no snmp trap link-status

ip classless

ip http server
no ip http secure-server

control-plane

```

```

ip http server
no ip http secure-server

control-plane

line con 0
line aux 0
line vty 0 4

end

```