

Towards an omnilingual model for solving morphological analogies

Safa AlSaidi, Amandine Decker, Stephanie Monteiro

M2 — Software Project



- 1 Reminder
- 2 Issues
- 3 New objective
- 4 Regression task
- 5 Our approach
- 6 Preliminary results
- 7 Future work

Reminder of our aim

- Apply decoder to the regression task (solving analogies)

$$A : B :: C : X \xrightarrow{X=?} A : B :: C : D$$

e.g. *star : stars :: cat : X* \rightarrow *cats*

- Current output: vectors (\neq word)
- Aim: transform these vectors into words

- 1 Reminder
- 2 Issues**
- 3 New objective
- 4 Regression task
- 5 Our approach
- 6 Preliminary results
- 7 Future work

Results

A	:	B	::	C	:	expected D	output D
schieben	:	schiebend	::	vergeben	:	vergebend	antisemitischer
schieben	:	vergeben	::	schiebend	:	vergebend	beschäftigter
schiebend	:	vergebend	::	schieben	:	vergeben	antisemitischer
schiebend	:	schieben	::	vergebend	:	vergeben	antisemitischer
vergebend	:	vergeben	::	schiebend	:	schieben	erschienen
vergebend	:	schiebend	::	vergeben	:	schieben	angeregterem
vergeben	:	schieben	::	vergebend	:	schiebend	antisemitischer

Output:

- 30 different words for German
- 22 for Arabic

Discussion

- ❶ Redundant outputs: decoder stuck on a few words
- ❷ Possible solution to implement: VAE
- ❸ Lack of time

- 1 Reminder
- 2 Issues
- 3 New objective**
- 4 Regression task
- 5 Our approach
- 6 Preliminary results
- 7 Future work

New objective

- Regression task based on transfer

$$A : B :: C : X \xrightarrow{X=?} A : B :: C : D$$

e.g. dog : dogs :: chat : X \rightarrow chats

- Input: A and B in language 1, C in language 2
- Output: D in language 2
- Same transformation for A, B and C, D

- 1 Reminder
- 2 Issues
- 3 New objective
- 4 Regression task**
- 5 Our approach
- 6 Preliminary results
- 7 Future work

Regression method





Figure: Structure of the analogy solver model

$\text{word}_D \leftarrow \text{word with closest embedding to } D$

Previous results



Results from [Alsaïdi et al., 2021]

- 1 Reminder
- 2 Issues
- 3 New objective
- 4 Regression task
- 5 Our approach**
- 6 Preliminary results
- 7 Future work

Our approach

- ❶ Find good pairs of languages
 - ▶ languages that have same transformations (i.e. same features)
 - ▶ languages that transfer well from one to another (based on previous experiments)
- ❷ Build analogies only when A,B in language 1 and C,D in language 2 have the same features
- ❸ The unknown word is either C or D

Language pairs




Figure: Number of possible analogies per language pair

Language pairs

Source language	Target language	Nb different features	Transfer accuracy (%)	(source, target) nb features
Hungarian	German	3	90	(86, 98)
Hungarian	Finnish	19	84	(86, 95)
Turkish	Finnish	6	81	(187, 95)
German	Hungarian	3	74	(98, 86)
Hungarian	Spanish	4	72	(86, 84)
Finnish	Turkish	6	70	(95, 187)

Table: Information on the language pairs (ranked by transfer accuracy).

- 1 Reminder
- 2 Issues
- 3 New objective
- 4 Regression task
- 5 Our approach
- 6 Preliminary results**
- 7 Future work

First trial

	hungarian, german	turkish, finnish	hungarian, finnish
Cosine similarity	58.9	39.5	18.9
Euclidean distance	57.7	39.1	16.8

Table: Accuracy for the regression task on the three (source, target) language pairs.

Discussion

- Few common features
- Performance seems to decrease when number of features increases (to confirm)
- Fine-tuning the embeddings

- 1 Reminder
- 2 Issues
- 3 New objective
- 4 Regression task
- 5 Our approach
- 6 Preliminary results
- 7 Future work**

Future work

- ~~22 Nov - Regression model + decoder / Variational auto-encoder~~
- ~~10 Dec - Qualitative analysis / Regression model + decoder~~
- 14 Jan - Application docker & webpage
- 3 Feb - Report

Future work

- ~~22 Nov - Regression model + decoder / Variational auto-encoder~~
- ~~10 Dec - Qualitative analysis / Regression model + decoder~~
- 14 Jan - Regression + Application docker & webpage
- 3 Feb - Report

شكرا جزيلا

Thank you

Merci

អរគុណ

Obrigado

References I



Alsaidi, S., Decker, A., Marquer, E., Murena, P.-A., and Couceiro, M. (2021). Tackling morphological analogies using deep learning – extended version.



Lim, S., Prade, H., and Richard, G. (2019).

Solving word analogies: A machine learning perspective.

In Kern-Isberner, G. and Ognjanovic, Z., editors, *Symbolic and Quantitative Approaches to Reasoning with Uncertainty, 15th European Conference, ECSQARU 2019, Belgrade, Serbia, September 18-20, 2019, Proceedings*, volume 11726 of *Lecture Notes in Computer Science*, pages 238–250.

Springer.