

Estimate

VAISHNAVI UPVC WINDOWS AND DOORS

GSTIN: 36CSPPV7053P1ZJ

SY NO 21 AND 22, Near Kharmanghat, Hanuman Temple, Gayatri Nagar X Roads, Jillelaguda, Hyderabad, Rangareddy, Telangana, 50007

Ph: 9640000825 Email: ecotexupvc@gmail.com
Prop: kiran chary

Estimate No: 322

Date: 13-08-2026

Estimate For

Santhosh kumar

#	Item Name	Windows QTY	Windows SQ FEET	MESH	Glass	Quantity	Unit	Price/Unit	GST	Amount
1	1828 mm x 1828 mm 2.5 track sliding window	46	36	Nylon	Clear	1656	Sqf	Rs. 355.93	18.0%	Rs. 1,06,096.27
2	1036 mm x 1828 mm 2.5 track sliding window	6	20	Nylon	Clear	122	Sqf	Rs. 355.93	18.0%	Rs. 7,841.90
3	1525 mm x 1463 mm 2.5 track sliding window	24	24	Nylon	Clear	576	Sqf	Rs. 355.93	18.0%	Rs. 36,903.05
4	1525 mm x 1828 mm 2.5 track sliding window	11	30	Nylon	Clear	330	Sqf	Rs. 355.93	18.0%	Rs. 21,142.37
5	1220 mm x 1828 mm 2.5 track sliding window	5	24	Nylon	Clear	120	Sqf	Rs. 355.93	18.0%	Rs. 7,688.14
6	915 mm x 1828 mm 2.5 track sliding window	5	18	Nylon	Clear	90	Sqf	Rs. 355.93	18.0%	Rs. 5,766.10
7	1828 mm x 1828 mm casement fixed window	8	36	No	Clear	288	Sqf	Rs. 355.93	18.0%	Rs. 18,451.53

Sub Total	Rs. 11,32,718.64
SGST @ 9.0%	Rs. 1,01,944.69
CGST @ 9.0%	Rs. 1,01,944.69
Grand Total	Rs. 13,36,608.00

Amount in Words: Thirteen Lakh Thirty Six Thousand Six Hundred and Eight Rupees only

Pay To:

Bank Name	Yes Bank, Lb Nagar, Hyderabad
Account No	11352700000045
IFSC	YESB0001135

Account Holder: VAISHNAVI UPVC WINDOWS AND DOORS

Description

product: " OASIS "

Supplying and fixing of Unplasticised Poly Vinyl Chloride (UPVC) 3 track sliding windows with mesh shutter - (2-glass shutters and 1-mesh shutter) duly manufactured using UPVC reinforced profiles (Composition of profile shall consists a minimum of 5.5 PHR of TiO2 and not more than 12 PHR of CaCo3 for every 100 parts of PVC resin) of (94mm x 45 mm)/(80 mm x 52 mm) x 2.20 mm for outer frames, (58 mm x 39 mm)/(54 mm x 38 mm) x 2.20mm for sliding shutter frames capable of mounting single glazing ally reinforced with system structurally reinforced with hot dip galvanized up to 50 microns of minimum thickness of 1.0/1.2 mm prefabricated & welded through fusion welding. The window sash shall be fitted with 5 mm thick clear float glass of reputed make and mesh shutter frame shall be (42 mm x 25mm)/(52 mm x 21.5 mm) x 2.0 mm fitted with Vinyl Coated Fiber mesh- on rollers/ pulley duly fitted with Grey colour TPV Gasket for sash & Glazing bead shall be co- extruded with Grey colour soft PVC. System shall have single point locking with Touch Lock and the system is to be installed at the site using anchor fasteners, silicon rubber sealant, easy glazing/deglazing at site etc., including cost and conveyance of all materials, accessories, labour charges for transportation, erection at site including overheads and contractors profit etc., complete for finished item of work

Thank you for your business!

