HARRY POTTER

THE MAGIC BEGINS | HTML + CSS LEARNING GUIDE

Corrected beginner-friendly website and detailed line-by-line explanations, organized in the exact order of the finished page.

What we corrected from your screenshot

• **Missing character images:** the earlier code expected files named harry.jpg, hermione.jpg and ron.jpg that were not included. This version includes actual local SVG illustration files in the images folder.

• **Missing hero poster:** the earlier hero pointed to an image that was not supplied. This version includes a Hogwarts-inspired illustrated castle background.

• **Blue links and unstyled buttons:** browser-default blue links suggest some link/button rules were missing, unsaved or mismatched. This version explicitly styles nav links and the trailer button.

• **Stacked character cards:** the original screenshot looked like the grid rules were not taking effect. This version matches the HTML class names to .card-grid and .character-card and provides responsive columns.

• **Consistency:** the movie title, headings, navigation, character images, dark fantasy palette and trailer now follow the same visual system.

Important: the screenshot cannot prove exactly why each style failed. The fixes above address the visible symptoms, and the checks later in this guide will help you diagnose the actual cause in VS Code.

Your files

index.html = website structure. **style.css** = layout and visual style. **images/** = image assets. The HTML and CSS must remain next to each other so the stylesheet link works.

Folder structure:

```
harry_potter_learning_site/
  index.html
  style.css
  images/
    hogwarts-hero.svg
    harry.svg
    hermione.svg
    ron.svg
```

How to study this guide

Each page section includes the exact code and an explanation for **every nonblank source line**. CSS explanations name the property, its value, and why it contributes to that section. Start with HTML, then revisit the matching CSS.

HTML = structure: the order your visitor reads. CSS = presentation: how that structure looks. SVG = a local image file (you may replace it later).

PART A - HTML: WHAT GOES ON THE PAGE

HTML 1 | Document setup

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01 <!DOCTYPE html>
```

Tells the browser to use modern HTML5 rules. Without it, browsers can use older rendering behavior.

```
02 <html lang="en">
```

Starts the HTML document; lang="en" tells screen readers and browsers the page language.

```
03 <head>
```

Begins document settings that help the browser; this section is not displayed as page content.

```
04   <meta charset="UTF-8">
```

Allows letters, punctuation and special symbols to display correctly.

```
05   <meta name="viewport" content="width=device-width, initial-scale=1.0">
```

Makes the layout fit the actual phone width, which is essential for responsive design.

```
06   <meta name="description" content="Explore the story and characters of Harry Potter.">
```

Describes the page for search engines and sharing previews.

```
07   <title>Harry Potter | The Magic Begins</title>
```

Sets the text shown in the browser tab.

```
08   <link rel="stylesheet" href="style.css">
```

Connects this HTML file to style.css in the same folder. If this path is wrong, most styling will not appear.

```
09 </head>
```

Closes the head; visible site content follows in the body.

```
10 <body>
```

Begins the visible webpage.

HTML 2 | Header and navigation

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01   <!-- SECTION 1: HEADER / NAVIGATION -->
```

A developer comment naming this section. The browser does not display comments.

```
02   <header class="site-header">
```

Starts the site header. The class lets .site-header in CSS style its background and border.

```
03     <div class="container nav-layout">
```

Groups the header content and assigns reusable width and horizontal Flexbox layout styles.

```
04       <a class="brand" href="#home">HARRY POTTER</a>
```

Makes the movie-name brand clickable; #home jumps to the element whose id is home.

```
05        <nav aria-label="Main navigation">
```

Marks these links as the site navigation; the label helps screen-reader users.

```
06          <a href="#story">Story</a>
```

Jumps to the synopsis section whose id="story".

```
07          <a href="#characters">Characters</a>
```

Jumps directly to the character cards.

```
08          <a href="#trailer">Trailer</a>
```

Jumps to the trailer call-to-action section.

```
09        </nav>
```

Ends the navigation group.

```
10      </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
11    </header>
```

Ends the top header section.

HTML 3 | Hero / movie poster

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01    <main>
```

Identifies the primary content; useful for accessibility and document structure.

```
02      <!-- SECTION 2: HERO -->
```

A developer comment naming this section. The browser does not display comments.

```
03      <section class="hero" id="home" aria-labelledby="movie-title">
```

Creates the visual movie-poster area, sets its anchor id, and links it to its heading for accessibility.

```
04        <div class="hero-shade"></div>
```

Places a semi-transparent dark overlay on the background so title text stays legible.

```
05        <div class="container hero-content">
```

Limits content width and keeps the hero text above the dark overlay.

```
06          <p class="eyebrow">A FANTASY MOVIE EXPERIENCE</p>
```

Adds a small label that signals the website genre.

```
07          <h1 id="movie-title">HARRY POTTER</h1>
```

The most important page heading; it clearly names the movie being promoted.

```
08          <h2>THE MAGIC BEGINS</h2>
```

A secondary headline gives the campaign its tagline.

```
09          <p>Discover the magic. Meet the legends. Experience the adventure.</p>
```

Short promotional copy that tells visitors what the site offers.

```
10          <a class="button" href="#trailer">WATCH THE TRAILER</a>
```

A call-to-action link styled as a button, leading straight to the trailer.

```
11        </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
12      </section>
```

Ends this named website section so the next section begins separately.

HTML 4 | Synopsis / story

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01      <!-- SECTION 3: SYNOPSIS -->
```

A developer comment naming this section. The browser does not display comments.

```
02      <section class="section story" id="story" aria-labelledby="story-title">
```

Starts synopsis; its id makes the Story nav link work.

```
03        <div class="container narrow">
```

Keeps the story paragraph from stretching too wide to read comfortably.

```
04          <p class="section-number">01 / THE STORY</p>
```

Adds visual chapter numbering to make the website feel cinematic.

```
05          <h2 id="story-title">The Story Begins</h2>
```

Names the synopsis and gives its section a heading reference.

```
06          <p>Harry discovers that he is a wizard and arrives at Hogwarts,
```

Begins a paragraph; the following lines continue its text until .

```
07            a school filled with magic and secrets. With new friends
```

Continues the element or text opened on the previous line; it belongs inside this named section.

```
08            Hermione and Ron, he faces a mystery that tests their courage,
```

Continues the element or text opened on the previous line; it belongs inside this named section.

```
09            knowledge, and loyalty.</p>
```

Finishes the paragraph begun above.

```
10        </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
11      </section>
```

Ends this named website section so the next section begins separately.

HTML 5 | Character cards

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01      <!-- SECTION 4: CHARACTER CARDS -->
```

A developer comment naming this section. The browser does not display comments.

```
02      <section class="section characters" id="characters" aria-labelledby="cast-title">
```

Creates the cast area and a link target for Characters navigation.

```
03        <div class="container">
```

Opens a group so related content can share CSS layout or spacing.

```
04          <p class="section-number">02 / THE CHARACTERS</p>
```

Creates a consistent chapter label for the cast section.

```
05          <h2 id="cast-title">Meet the Legends</h2>
```

Introduces the required character showcase.

```
06          <p class="intro">Three friends. Three strengths. One adventure.</p>
```

Ties the card collection to the story and the group presentation theme.

```
07          <div class="card-grid">
```

Groups the cards. .card-grid in CSS will place them in columns.

```
08            <article class="character-card">
```

Creates a self-contained character card that can be understood independently.

```
09              <img src="images/harry.svg" alt="Illustrated Harry Potter character card">
```

Displays an image from images/harry.svg. The matching file is included in the images folder; alt describes it if the image cannot load.

```
10              <div class="card-details">
```

Groups each card’s name, actor, strength and description for padding and styling.

```
11                <h3>Harry Potter</h3>
```

Names the first character; heading level 3 sits under the section heading.

```
12                <p class="actor">Played by Daniel Radcliffe</p>
```

Lists the actor, satisfying the cast information requirement.

```
13                <p class="trait">COURAGE</p>
```

Adds a collectible-card strength for Harry.

```
14                <p>A young wizard learning to face the unknown.</p>
```

Adds the visible descriptive sentence in this section, helping explain the movie or character.

```
15              </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
16            </article>
```

Finishes this individual character card.

```
17            <article class="character-card">
```

Creates a self-contained character card that can be understood independently.

```
18              <img src="images/hermione.svg" alt="Illustrated Hermione Granger character card">
```

Displays an image from images/hermione.svg. The matching file is included in the images folder; alt describes it if the image cannot load.

```
19              <div class="card-details">
```

Groups each card’s name, actor, strength and description for padding and styling.

```
20                <h3>Hermione Granger</h3>
```

Names the second character.

```
21                <p class="actor">Played by Emma Watson</p>
```

Lists the actor playing Hermione.

```
22                <p class="trait">KNOWLEDGE</p>
```

Adds a collectible-card strength for Hermione.

```
23                <p>A clever friend who finds answers when they matter most.</p>
```

Adds the visible descriptive sentence in this section, helping explain the movie or character.

```
24              </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
25            </article>
```

Finishes this individual character card.

```
26            <article class="character-card">
```

Creates a self-contained character card that can be understood independently.

```
27              <img src="images/ron.svg" alt="Illustrated Ron Weasley character card">
```

Displays an image from images/ron.svg. The matching file is included in the images folder; alt describes it if the image cannot load.

```
28              <div class="card-details">
```

Groups each card’s name, actor, strength and description for padding and styling.

```
29                <h3>Ron Weasley</h3>
```

Names the third character.

```
30                <p class="actor">Played by Rupert Grint</p>
```

Lists the actor playing Ron.

```
31                <p class="trait">LOYALTY</p>
```

Adds a collectible-card strength for Ron.

```
32                <p>A dependable friend who stands with his team.</p>
```

Adds the visible descriptive sentence in this section, helping explain the movie or character.

```
33              </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
34            </article>
```

Finishes this individual character card.

```
35          </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
36        </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
37      </section>
```

Ends this named website section so the next section begins separately.

HTML 6 | Trailer / call to action

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01      <!-- SECTION 5: TRAILER / CALL TO ACTION -->
```

A developer comment naming this section. The browser does not display comments.

```
02      <section class="section trailer" id="trailer" aria-labelledby="trailer-title">
```

Starts the required trailer/call-to-action area, accessible via #trailer.

```
03        <div class="container narrow">
```

Keeps the story paragraph from stretching too wide to read comfortably.

```
04          <p class="section-number">03 / OFFICIAL TRAILER</p>
```

Labels the final story chapter consistently.

```
05          <h2 id="trailer-title">Experience the Magic</h2>
```

Makes the call to watch the movie clear.

```
06          <div class="video-frame">
```

Wraps the embedded video so CSS can give it a widescreen ratio.

```
07            <iframe src="https://www.youtube.com/embed/VyHV0BRtdxo"
```

Loads an embedded YouTube player. This needs internet access and permission from the video owner.

```
08              title="Harry Potter movie trailer" loading="lazy"
```

Sets a property of the embedded YouTube player: description, playback capabilities or link privacy settings.

```
09              allow="accelerometer; autoplay; clipboard-write; encrypted-media; gyroscope; picture-in-picture;
web-share"
```

Sets a property of the embedded YouTube player: description, playback capabilities or link privacy settings.

```
10              referrerpolicy="strict-origin-when-cross-origin"
```

Sets a property of the embedded YouTube player: description, playback capabilities or link privacy settings.

```
11              allowfullscreen></iframe>
```

Ends the video player and allows fullscreen viewing.

```
12          </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
13          <p class="trailer-note">Your adventure starts here.</p>
```

Adds a final line encouraging visitors to watch.

```
14        </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
15      </section>
```

Ends this named website section so the next section begins separately.

```
16    </main>
```

Ends the main content before the footer.

HTML 7 | Footer and close document

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01    <!-- SECTION 6: FOOTER -->
```

A developer comment naming this section. The browser does not display comments.

```
02    <footer class="site-footer">
```

Starts the closing area; the footer holds project credits.

```
03      <div class="container">
```

Opens a group so related content can share CSS layout or spacing.

```
04        <p>Fantasy Movie Website | Per Scholas Team Project</p>
```

Credits the group's educational project.

```
05        <p class="credit">Educational fan concept; not an official movie website.</p>
```

Clearly distinguishes this classroom fan project from an official studio website.

```
06      </div>
```

Closes the most recently opened div group; correct nesting keeps CSS layouts predictable.

```
07    </footer>
```

Ends the footer.

```
08  </body>
```

Ends the visible webpage body.

```
09  </html>
```

Ends the HTML document.

PART B - CSS: HOW EACH PAGE SECTION LOOKS

CSS 1 | CSS foundation and reusable colors

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 1: GLOBAL STYLES */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  :root {
```

Starts shared site-wide color variables, so changing one value updates many sections.

```
03    --night: #101827;
```

Stores the base deep-navy color in one reusable place; var(--night) retrieves it.

```
04    --navy: #172239;
```

Stores a second navy tone for header, cards and footer.

```
05    --gold: #e2be77;
```

Stores the shared gold accent that gives the fantasy film identity.

```
06    --paper: #e7e9ee;
```

Stores the light text color for dark backgrounds.

```
07    --muted: #bdc5d2;
```

Stores a softer text color for supporting descriptions.

```
08  }
```

Closes the current CSS rule; all properties above it apply to :root.

```
10  * {
```

Selects every element for a consistent box-sizing rule.

```
11    box-sizing: border-box;
```

Includes padding and borders inside an element’s calculated width, preventing accidental overflow. Here the value is border-box.

```
12  }
```

Closes the current CSS rule; all properties above it apply to *.

```
14  html {
```

Starts the CSS rule for html; it will style HTML elements matching this selector.

```
15    scroll-behavior: smooth;
```

Makes internal navigation slide smoothly to each section instead of jumping abruptly. Here the value is smooth.

```
16  }
```

Closes the current CSS rule; all properties above it apply to html.

```
18  body {
```

Starts the CSS rule for body; it will style HTML elements matching this selector.

```
19    margin: 0;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 0.

```
20    background: var(--night);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--night).

```
21    color: var(--paper);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--paper).

```
22    font-family: Arial, Helvetica, sans-serif;
```

Chooses the fonts used for text. Arial and Helvetica are widely available fallbacks. Here the value is Arial, Helvetica, sans-serif.

```
23    line-height: 1.6;
```

Sets comfortable distance between lines of text. Here the value is 1.6.

```
24  }
```

Closes the current CSS rule; all properties above it apply to body.

```
26  .container {
```

Starts the CSS rule for .container; it will style HTML elements matching this selector.

```
27    width: 90%;
```

Sets element width; using percentages makes it adapt to screen size. Here the value is 90%.

```
28    max-width: 1100px;
```

Stops content from becoming too wide on desktop. Here the value is 1100px.

```
29    margin: 0 auto;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 0 auto.

```
30  }
```

Closes the current CSS rule; all properties above it apply to .container.

```
32  a {
```

Starts the CSS rule for a; it will style HTML elements matching this selector.

```
33    color: inherit;
```

Sets text or border color, often using one of the shared custom variables. Here the value is inherit.

```
34  }
```

Closes the current CSS rule; all properties above it apply to a.

```
36  .section {
```

Starts the CSS rule for .section; it will style HTML elements matching this selector.

```
37    padding: 65px 0;
```

Adds space inside a box, away from its edges. Here the value is 65px 0.

```
38  }
```

Closes the current CSS rule; all properties above it apply to .section.

```
40  .section h2 {
```

Starts the CSS rule for .section h2; it will style HTML elements matching this selector.

```
41    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
42    font-size: 2rem;
```

Controls how large or small the text appears. Here the value is 2rem.

```
43    margin: 8px 0 18px;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 8px 0 18px.

```
44  }
```

Closes the current CSS rule; all properties above it apply to .section h2.

```
46  .section-number {
```

Starts the CSS rule for .section-number; it will style HTML elements matching this selector.

```
47    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
48    font-size: 0.8rem;
```

Controls how large or small the text appears. Here the value is 0.8rem.

```
49    letter-spacing: 2px;
```

Adds space between letters for a cinematic title or eyebrow label. Here the value is 2px.

```
50    font-weight: bold;
```

Controls text thickness, making important elements bold. Here the value is bold.

```
51  }
```

Closes the current CSS rule; all properties above it apply to .section-number.

```
53  .narrow {
```

Starts the CSS rule for .narrow; it will style HTML elements matching this selector.

```
54    max-width: 800px;
```

Stops content from becoming too wide on desktop. Here the value is 800px.

```
55  }
```

Closes the current CSS rule; all properties above it apply to .narrow.

CSS 2 | CSS header and navigation

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 2: HEADER / NAVIGATION */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  .site-header {
```

Starts the CSS rule for .site-header; it will style HTML elements matching this selector.

```
03    background: var(--navy);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--navy).

```
04    border-bottom: 1px solid var(--gold);
```

Draws a line below the header, visually separating navigation from the movie content. Here the value is 1px solid var(--gold).

```
05  }
```

Closes the current CSS rule; all properties above it apply to .site-header.

```
07  .nav-layout {
```

Starts the CSS rule for .nav-layout; it will style HTML elements matching this selector.

```
08    display: flex;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is flex.

```
09    justify-content: space-between;
```

Controls how items distribute horizontally inside a Flexbox row. Here the value is space-between.

```
10    align-items: center;
```

Vertically aligns elements in Flexbox. Here the value is center.

```
11    gap: 20px;
```

Adds consistent spacing between Flexbox or Grid children. Here the value is 20px.

```
12    padding: 18px 0;
```

Adds space inside a box, away from its edges. Here the value is 18px 0.

```
13  }
```

Closes the current CSS rule; all properties above it apply to .nav-layout.

```
15  .brand {
```

Starts the CSS rule for .brand; it will style HTML elements matching this selector.

```
16    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
17    font-size: 1.4rem;
```

Controls how large or small the text appears. Here the value is 1.4rem.

```
18    font-weight: bold;
```

Controls text thickness, making important elements bold. Here the value is bold.

```
19    text-decoration: none;
```

Removes or adds underlines on navigation links. Here the value is none.

```
20  }
```

Closes the current CSS rule; all properties above it apply to .brand.

```
22  nav {
```

Starts the CSS rule for nav; it will style HTML elements matching this selector.

```
23    display: flex;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is flex.

```
24    flex-wrap: wrap;
```

Allows menu links to wrap on small screens instead of overflowing. Here the value is wrap.

```
25    gap: 22px;
```

Adds consistent spacing between Flexbox or Grid children. Here the value is 22px.

```
26  }
```

Closes the current CSS rule; all properties above it apply to nav.

```
28  nav a {
```

Starts the CSS rule for nav a; it will style HTML elements matching this selector.

```
29    color: var(--paper);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--paper).

```
30    text-decoration: none;
```

Removes or adds underlines on navigation links. Here the value is none.

```
31  }
```

Closes the current CSS rule; all properties above it apply to nav a.

```
33  nav a:hover,
```

Adds another selector to the same style rule; both selectors will receive identical properties.

```
34  nav a:focus-visible {
```

Starts the CSS rule for nav a:focus-visible; it will style HTML elements matching this selector.

```
35    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
36    text-decoration: underline;
```

Removes or adds underlines on navigation links. Here the value is underline.

```
37  }
```

Closes the current CSS rule; all properties above it apply to nav a:focus-visible.

CSS 3 | CSS hero image and call-to-action button

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 3: HERO */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  .hero {
```

Starts the CSS rule for .hero; it will style HTML elements matching this selector.

```
03    position: relative;
```

Controls positioning behavior; relative creates a reference for absolutely positioned children. Here the value is relative.

```
04    min-height: 520px;
```

Keeps the hero tall enough for a cinematic first impression. Here the value is 520px.

```
05    background: var(--night) url("images/hogwarts-hero.svg") center / cover no-repeat;
```

Sets a background color, gradient or image depending on the value. Here the value is var(--night) url("images/hogwarts-hero.svg") center / cover no-repeat.

```
06    display: flex;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is flex.

```
07    align-items: center;
```

Vertically aligns elements in Flexbox. Here the value is center.

```
08    text-align: center;
```

Controls alignment of text; center gives a movie-poster feel. Here the value is center.

```
09  }
```

Closes the current CSS rule; all properties above it apply to .hero.

```
11  .hero-shade {
```

Starts the CSS rule for .hero-shade; it will style HTML elements matching this selector.

```
12    position: absolute;
```

Controls positioning behavior; relative creates a reference for absolutely positioned children. Here the value is absolute.

```
13    inset: 0;
```

Pins the overlay to all four edges of its positioned parent. Here the value is 0.

```
14    background: rgba(5, 10, 20, 0.45);
```

Sets a background color, gradient or image depending on the value. Here the value is rgba(5, 10, 20, 0.45).

```
15  }
```

Closes the current CSS rule; all properties above it apply to .hero-shade.

```
17  .hero-content {
```

Starts the CSS rule for .hero-content; it will style HTML elements matching this selector.

```
18    position: relative;
```

Controls positioning behavior; relative creates a reference for absolutely positioned children. Here the value is relative.

```
19    z-index: 1;
```

Places the hero text visually above the shaded overlay. Here the value is 1.

```
20    padding: 80px 0;
```

Adds space inside a box, away from its edges. Here the value is 80px 0.

```
21  }
```

Closes the current CSS rule; all properties above it apply to .hero-content.

```
23  .eyebrow {
```

Starts the CSS rule for .eyebrow; it will style HTML elements matching this selector.

```
24    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
25    font-size: 0.8rem;
```

Controls how large or small the text appears. Here the value is 0.8rem.

```
26    letter-spacing: 3px;
```

Adds space between letters for a cinematic title or eyebrow label. Here the value is 3px.

```
27  }
```

Closes the current CSS rule; all properties above it apply to .eyebrow.

```
29  .hero h1 {
```

Starts the CSS rule for .hero h1; it will style HTML elements matching this selector.

```
30    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
31    font-size: 3.5rem;
```

Controls how large or small the text appears. Here the value is 3.5rem.

```
32    margin: 8px 0 0;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 8px 0 0.

```
33    letter-spacing: 2px;
```

Adds space between letters for a cinematic title or eyebrow label. Here the value is 2px.

```
34  }
```

Closes the current CSS rule; all properties above it apply to .hero h1.

```
36  .hero h2 {
```

Starts the CSS rule for .hero h2; it will style HTML elements matching this selector.

```
37    font-size: 1.6rem;
```

Controls how large or small the text appears. Here the value is 1.6rem.

```
38    margin: 0 0 12px;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 0 0 12px.

```
39  }
```

Closes the current CSS rule; all properties above it apply to .hero h2.

```
41  .hero-content > p:not(.eyebrow) {
```

Starts the CSS rule for .hero-content > p:not(.eyebrow); it will style HTML elements matching this selector.

```
42    max-width: 650px;
```

Stops content from becoming too wide on desktop. Here the value is 650px.

```
43    margin: 0 auto 24px;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 0 auto 24px.

```
44  }
```

Closes the current CSS rule; all properties above it apply to .hero-content > p:not(.eyebrow).

```
46  .button {
```

Starts the CSS rule for .button; it will style HTML elements matching this selector.

```
47    display: inline-block;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is inline-block.

```
48    background: var(--gold);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--gold).

```
49    color: #161514;
```

Sets text or border color, often using one of the shared custom variables. Here the value is #161514.

```
50    padding: 12px 24px;
```

Adds space inside a box, away from its edges. Here the value is 12px 24px.

```
51    border-radius: 5px;
```

Rounds box corners for modern poster-like cards and buttons. Here the value is 5px.

```
52    text-decoration: none;
```

Removes or adds underlines on navigation links. Here the value is none.

```
53    font-weight: bold;
```

Controls text thickness, making important elements bold. Here the value is bold.

```
54  }
```

Closes the current CSS rule; all properties above it apply to .button.

```
56  .button:hover,
```

Adds another selector to the same style rule; both selectors will receive identical properties.

```
57  .button:focus-visible {
```

Starts the CSS rule for .button:focus-visible; it will style HTML elements matching this selector.

```
58    background: #f6d89c;
```

Sets a background color, gradient or image depending on the value. Here the value is #f6d89c.

```
59  }
```

Closes the current CSS rule; all properties above it apply to .button:focus-visible.

CSS 4 | CSS synopsis

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 4: SYNOPSIS */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  .story {
```

Starts the CSS rule for .story; it will style HTML elements matching this selector.

```
03    background: var(--night);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--night).

```
04  }
```

Closes the current CSS rule; all properties above it apply to .story.

```
06  .story p:last-child {
```

Starts the CSS rule for .story p:last-child; it will style HTML elements matching this selector.

```
07    max-width: 720px;
```

Stops content from becoming too wide on desktop. Here the value is 720px.

```
08  }
```

Closes the current CSS rule; all properties above it apply to .story p:last-child.

CSS 5 | CSS character-card grid

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 5: CHARACTER CARDS */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  .characters {
```

Starts the CSS rule for .characters; it will style HTML elements matching this selector.

```
03    background: var(--navy);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--navy).

```
04  }
```

Closes the current CSS rule; all properties above it apply to .characters.

```
06  .intro {
```

Starts the CSS rule for .intro; it will style HTML elements matching this selector.

```
07    color: var(--muted);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--muted).

```
08  }
```

Closes the current CSS rule; all properties above it apply to .intro.

```
10  .card-grid {
```

Starts the CSS rule for .card-grid; it will style HTML elements matching this selector.

```
11    display: grid;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is grid.

```
12    grid-template-columns: repeat(3, 1fr);
```

Defines the number and widths of Grid columns; three on desktop, fewer on mobile. Here the value is repeat(3, 1fr).

```
13    gap: 22px;
```

Adds consistent spacing between Flexbox or Grid children. Here the value is 22px.

```
14    margin-top: 30px;
```

Sets a CSS visual or layout property for the current selector. Here the value is 30px.

```
15  }
```

Closes the current CSS rule; all properties above it apply to .card-grid.

```
17  .character-card {
```

Starts the CSS rule for .character-card; it will style HTML elements matching this selector.

```
18    background: #1f2b42;
```

Sets a background color, gradient or image depending on the value. Here the value is #1f2b42.

```
19    border: 1px solid var(--gold);
```

Draws the gold decorative edge around each character card. Here the value is 1px solid var(--gold).

```
20    border-radius: 8px;
```

Rounds box corners for modern poster-like cards and buttons. Here the value is 8px.

```
21    overflow: hidden;
```

Hides artwork that extends beyond the rounded card boundary. Here the value is hidden.

```
22    transition: transform 0.2s ease;
```

Makes changes from normal to hover state smooth. Here the value is transform 0.2s ease.

```
23  }
```

Closes the current CSS rule; all properties above it apply to .character-card.

```
25  .character-card:hover {
```

Starts the CSS rule for .character-card:hover; it will style HTML elements matching this selector.

```
26    transform: translateY(-6px);
```

Moves the hovered card slightly upward for a subtle interactive effect. Here the value is translateY(-6px).

```
27  }
```

Closes the current CSS rule; all properties above it apply to .character-card:hover.

```
29  .character-card img {
```

Starts the CSS rule for .character-card img; it will style HTML elements matching this selector.

```
30    display: block;
```

Defines how elements are laid out. flex handles rows; grid handles columns; block creates normal boxes. Here the value is block.

```
31    width: 100%;
```

Sets element width; using percentages makes it adapt to screen size. Here the value is 100%.

```
32    height: 260px;
```

Sets display height; fixed card images align in a neat row. Here the value is 260px.

```
33    object-fit: cover;
```

Crops images proportionally to fill cards without stretching them. Here the value is cover.

```
34  }
```

Closes the current CSS rule; all properties above it apply to .character-card img.

```
36  .card-details {
```

Starts the CSS rule for .card-details; it will style HTML elements matching this selector.

```
37    padding: 18px;
```

Adds space inside a box, away from its edges. Here the value is 18px.

```
38  }
```

Closes the current CSS rule; all properties above it apply to .card-details.

```
40  .card-details h3 {
```

Starts the CSS rule for .card-details h3; it will style HTML elements matching this selector.

```
41    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
42    margin: 0;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 0.

```
43  }
```

Closes the current CSS rule; all properties above it apply to .card-details h3.

```
45  .actor {
```

Starts the CSS rule for .actor; it will style HTML elements matching this selector.

```
46    color: var(--muted);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--muted).

```
47    font-size: 0.9rem;
```

Controls how large or small the text appears. Here the value is 0.9rem.

```
48  }
```

Closes the current CSS rule; all properties above it apply to .actor.

```
50  .trait {
```

Starts the CSS rule for .trait; it will style HTML elements matching this selector.

```
51    color: var(--gold);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--gold).

```
52    font-weight: bold;
```

Controls text thickness, making important elements bold. Here the value is bold.

```
53    letter-spacing: 1px;
```

Adds space between letters for a cinematic title or eyebrow label. Here the value is 1px.

```
54  }
```

Closes the current CSS rule; all properties above it apply to .trait.

CSS 6 | CSS trailer and footer

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 6: TRAILER + FOOTER */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  .trailer {
```

Starts the CSS rule for .trailer; it will style HTML elements matching this selector.

```
03    text-align: center;
```

Controls alignment of text; center gives a movie-poster feel. Here the value is center.

```
04  }
```

Closes the current CSS rule; all properties above it apply to .trailer.

```
06  .video-frame {
```

Starts the CSS rule for .video-frame; it will style HTML elements matching this selector.

```
07    aspect-ratio: 16 / 9;
```

Preserves a 16:9 video frame on any screen size. Here the value is 16 / 9.

```
08    max-width: 900px;
```

Stops content from becoming too wide on desktop. Here the value is 900px.

```
09    margin: 28px auto 14px;
```

Controls empty space outside an element; value 0 removes unwanted browser default spacing. Here the value is 28px auto 14px.

```
10  }
```

Closes the current CSS rule; all properties above it apply to .video-frame.

```
12  .video-frame iframe {
```

Starts the CSS rule for .video-frame iframe; it will style HTML elements matching this selector.

```
13    width: 100%;
```

Sets element width; using percentages makes it adapt to screen size. Here the value is 100%.

```
14    height: 100%;
```

Sets display height; fixed card images align in a neat row. Here the value is 100%.

```
15    border: 0;
```

Draws the gold decorative edge around each character card. Here the value is 0.

```
16  }
```

Closes the current CSS rule; all properties above it apply to .video-frame iframe.

```
18  .trailer-note {
```

Starts the CSS rule for .trailer-note; it will style HTML elements matching this selector.

```
19    color: var(--muted);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--muted).

```
20  }
```

Closes the current CSS rule; all properties above it apply to .trailer-note.

```
22  .site-footer {
```

Starts the CSS rule for .site-footer; it will style HTML elements matching this selector.

```
23    background: var(--navy);
```

Sets a background color, gradient or image depending on the value. Here the value is var(--navy).

```
24    border-top: 1px solid var(--gold);
```

Draws a line above the footer. Here the value is 1px solid var(--gold).

```
25    padding: 25px 0;
```

Adds space inside a box, away from its edges. Here the value is 25px 0.

```
26    text-align: center;
```

Controls alignment of text; center gives a movie-poster feel. Here the value is center.

```
27  }
```

Closes the current CSS rule; all properties above it apply to .site-footer.

```
29  .credit {
```

Starts the CSS rule for .credit; it will style HTML elements matching this selector.

```
30    color: var(--muted);
```

Sets text or border color, often using one of the shared custom variables. Here the value is var(--muted).

```
31    font-size: 0.85rem;
```

Controls how large or small the text appears. Here the value is 0.85rem.

```
32  }
```

Closes the current CSS rule; all properties above it apply to .credit.

CSS 7 | CSS responsive mobile and tablet layout

Read each code line, then its explanation below. The line numbers restart for each learning section.

```
01  /* SECTION 7: RESPONSIVE DESIGN */
```

Comment marks the CSS section. Browsers ignore comments; teammates use them to find code.

```
02  @media (max-width: 850px) {
```

Starts a responsive breakpoint: the rules inside it apply only when the screen width meets this condition.

```
03    .card-grid {
```

Starts the CSS rule for .card-grid; it will style HTML elements matching this selector.

```
04      grid-template-columns: repeat(2, 1fr);
```

Defines the number and widths of Grid columns; three on desktop, fewer on mobile. Here the value is repeat(2, 1fr).

```
05    }
```

Closes the current CSS rule; all properties above it apply to .card-grid.

```
06  }
```

Closes the current CSS rule; all properties above it apply to .card-grid.

```
08  @media (max-width: 600px) {
```

Starts a responsive breakpoint: the rules inside it apply only when the screen width meets this condition.

```
09    .nav-layout {
```

Starts the CSS rule for .nav-layout; it will style HTML elements matching this selector.

```
10      flex-direction: column;
```

Changes a Flexbox row into a column for mobile. Here the value is column.

```
11      text-align: center;
```

Controls alignment of text; center gives a movie-poster feel. Here the value is center.

```
12    }
```

Closes the current CSS rule; all properties above it apply to .nav-layout.

```
14    .hero {
```

Starts the CSS rule for .hero; it will style HTML elements matching this selector.

```
15      min-height: 430px;
```

Keeps the hero tall enough for a cinematic first impression. Here the value is 430px.

```
16    }
```

Closes the current CSS rule; all properties above it apply to .hero.

```
18    .hero h1 {
```

Starts the CSS rule for .hero h1; it will style HTML elements matching this selector.

```
19      font-size: 2.3rem;
```

Controls how large or small the text appears. Here the value is 2.3rem.

```
20    }
```

Closes the current CSS rule; all properties above it apply to .hero h1.

```
22    .section {
```

Starts the CSS rule for .section; it will style HTML elements matching this selector.

```
23      padding: 45px 0;
```

Adds space inside a box, away from its edges. Here the value is 45px 0.

```
24    }
```

Closes the current CSS rule; all properties above it apply to .section.

```
26    .card-grid {
```

Starts the CSS rule for .card-grid; it will style HTML elements matching this selector.

```
27      grid-template-columns: 1fr;
```

Defines the number and widths of Grid columns; three on desktop, fewer on mobile. Here the value is 1fr.

```
28    }
```

Closes the current CSS rule; all properties above it apply to .card-grid.

```
29  }
```

Closes the current CSS rule; all properties above it apply to .card-grid.

PART C - TROUBLESHOOTING THE SCREENSHOT

1. Images show a broken-image icon

Why it happens: The browser cannot find the picture at the src path.

How to test: Check that images/harry.svg, images/hermione.svg and images/ron.svg are spelled exactly and stored in the images folder. Do not put images in a different folder without updating src.

2. Hero image is missing

Why it happens: The CSS background image may point to a filename that does not exist.

How to test: Open style.css and confirm the file path inside background: url("images/hogwarts-hero.svg"). The SVG is included in this project.

3. Links are blue

Why it happens: The link style may not be applied, even though other CSS works.

How to test: Look for nav a { color: var(--paper); text-decoration: none; }. Also check whether your HTML uses the same nav element and class names.

4. Character cards stack on desktop

Why it happens: The .card-grid style may be missing, or the HTML class does not match.

How to test: Confirm the wrapper is and the CSS includes display: grid and grid-template-columns: repeat(3, 1fr). On phones, the one-column layout is intentional.

5. Some CSS works but some does not

Why it happens: A stylesheet can load while later selectors fail due to a typo, unmatched brace, or unsaved file.

How to test: Save style.css (Ctrl+S). Inspect the browser developer tools if needed; compare class spellings character by character and confirm every { has a matching }.

6. YouTube player appears blank

Why it happens: A YouTube embed can be blocked by privacy settings, video restrictions, extensions, or lack of internet.

How to test: Confirm you are online and that the chosen video allows embedding. The HTML structure is valid even if a particular YouTube video is unavailable.

PART D - PRACTICE QUESTIONS

1. If you change href="#characters" to href="#trailer", what happens when you click the link?

2. Why is the CSS .card-grid selector different from the HTML class="card-grid" syntax?

3. What would happen if you changed grid-template-columns from repeat(3, 1fr) to 1fr?

4. Why is the hero dark overlay helpful when the background contains bright details?

5. Which @media rule makes your character cards a single column on phones?

6. How would you replace one SVG placeholder with a movie still without changing the card layout?

PART E - SAFE TEAM WORKFLOW

This is a standalone learning example. Your class project is in a shared GitHub repository. Do not replace teammates' HTML or CSS with these files. Instead, study the ideas, discuss them with your team, and add only agreed sections through your normal branches and pull requests.

Your instructor requires HTML structure, CSS styling, responsiveness, a prominent title/hero, synopsis, at least three cast members, and a trailer. The example satisfies those structural goals; verify the actual trailer video before presenting.

OPTIONAL NEXT LESSON

Begin with the Document Setup section. Once you understand the seven opening lines, move to Header and Navigation. You do not have to memorize everything at once.