Site Safety Assessment

Report Title:

Assessment ID:

Date:

Location:

Assessor Name:

Point of Contact:

Operational Scope:

Review Status:

Category: 01 - Confined Space

01.01.001: Has a workplace evaluation been conducted to identify all confined spaces and determine if they are permit-required?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(c)(1): The employer shall evaluate the workplace to determine if any spaces are permit-required confined spaces. Note: Proper application of the decision flow chart in Appendix A to Sec. 1910.146 would facilitate compliance with this requirement.

Aligned Standard:

Findings:

Recommendations:

01.01.002: Are exposed employees informed of the existence and location of permit spaces via posted danger signs or other equally effective means?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(c)(2): If the workplace contains permit spaces, the employer shall inform exposed employees, by posting danger signs or by any other equally effective means, of the existence and location of and the danger posed by the permit spaces.

Note: A sign reading "DANGER - PERMIT-REQUIRED CONFINED SPACE, DO NOT ENTER" or using other similar language would satisfy the requirement for a sign.

Aligned Standard:

Findings:

Recommendations:

01.02.001: If the employer has decided that employees will not enter permit spaces, have effective measures been taken to prevent employees from entering?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(c)(3): If the employer decides that its employees will not enter permit spaces, the employer shall take effective measures to prevent its employees from entering the permit spaces and shall comply with paragraphs (c)(1), (c)(2), (c)(6), and (c)(8) of this section.

Aligned Standard:

Findings:

Recommendations:

01.03.001: If the employer has decided that employees will enter permit spaces, has a written permit space program been developed and implemented?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(c)(4): If the employer decides that its employees will enter permit spaces, the employer shall develop and implement a written permit space program that complies with this section. The written program shall be available for inspection by employees and their authorized representatives.

Aligned Standard:

Findings:

Recommendations:

01.04.001: Does the written program include specific procedures for summoning rescue and emergency services, preventing unauthorized rescue, and rescuing entrants?"

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(d)(9): Develop and implement procedures for summoning rescue and emergency services, for rescuing entrants from permit spaces, for providing necessary emergency services to rescued employees, and for preventing unauthorized personnel from attempting a rescue.

Aligned Standard:

Findings:

Recommendations:

01.04.002: Has the employer evaluated and verified that the designated rescue service is capable of responding in a timely manner and is equipped to handle the specific hazards of the space?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.146(k)(1): An employer who designates rescue and emergency services pursuant to paragraph (d)(9) of this section shall:
(k)(1)(i) evaluate a prospective rescuer's ability to respond to a rescue summons in a timely manner, considering the hazard(s) identified
Note to paragraph (k)(1)(i): What will be considered timely will vary according to the specific hazards involved in each entry. For example, Sec. 1910.134, Respiratory Protection, requires that employers provide a standby person or persons capable of immediate action to rescue employee(s) wearing respiratory protection while in work areas defined as IDLH atmospheres.
29 CFR 1910.146(k)(1)(ii): Evaluate a prospective rescue service's ability, in terms of proficiency with rescue-related tasks and equipment, to function appropriately while rescuing entrants from the particular permit space or types of permit spaces identified.
29 CFR 1910.146(k)(1)(iv): The employer shall Inform each rescue team or service of the hazards they may confront when called on to perform rescue at the site.

Aligned Standard:

Findings:

Recommendations:

Category: 02 - Electrical

02.01.001: Has an arc flash risk assessment been completed for this facility in the last five years?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.335(a)(1)(i): Employees working in areas where there are potential electrical hazards shall be provided with, and shall use, electrical protective equipment that is appropriate for the specific parts of the body to be protected and for the work to be performed. Note: Personal protective equipment requirements are contained in Subpart I of this part.

(Note: OSHA 29 CFR 1910 Subpart S is fundamentally a performance-based standard that defines the required level of electrical safety and protection outcomes, without prescribing a specific method for achieving them. In contrast, NFPA 70E functions as the detailed "how-to" standard, providing prescriptive methodologies, including incident energy calculations and other quantitative approaches, for determining appropriate arc flash personal protective equipment and demonstrating compliance with OSHA's performance requirements.)

Aligned Standard:

Findings:

Recommendations:

02.02.001: Is absence-of-voltage testing being performed prior to work on or near exposed conductors?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.333(b)(2)(iv)(B): A qualified person shall use test equipment to test the circuit elements and electrical parts of equipment to which employees will be exposed and shall verify that the circuit elements and electrical parts of equipment are deenergized. The test shall also determine if any energized condition exists as a result of inadvertently induced voltage or unrelated voltage back feed, even though specific parts of the circuit have been deenergized and presumed to be safe. If the circuit is to be tested for the absence of voltage, the tester shall be checked for proper operation immediately before and immediately after this test.

Aligned Standard:

Findings:

Recommendations:

02.03.001: Are all unused openings in cabinets, boxes, and fittings closed?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.305(b)(1)(ii): Unused openings in cabinets, boxes, and fittings shall be effectively closed.

Aligned Standard:

Findings:

Recommendations:

02.03.002: Is all electrical equipment in use labeled and listed?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.303(a): The conductors and equipment required or permitted by this subpart shall be acceptable only if approved.
29 CFR 1910.303(f)(1) (Labeled): Each disconnecting means shall be legibly marked to indicate its purpose, unless located and arranged so the purpose is evident.
29 CFR 1910.303(f)(2) (Listed): Each service, feeder, and branch circuit, at its disconnecting means or overcurrent device, shall be legibly marked to indicate its purpose, unless it is located and arranged so the purpose is evident.
29 CFR 1910.399: installation or equipment is acceptable to the Assistant Secretary of Labor, and approved within the meaning of subpart S: (1) If it is accepted, certified, listed, labeled, or otherwise determined to be safe by a nationally recognized testing laboratory recognized pursuant to 1910.7 or (2) With respect to an installation or equipment of a kind that no nationally recognized testing laboratory accepts, certifies, lists, labels, or determines to be safe, if it is inspected or tested by another Federal agency, or by a State, municipal, or other local authority responsible for enforcing occupational safety provisions of the National Electrical Code, and found in compliance with the provisions of the National Electrical Code as applied in this subpart or (3) With respect to custom-made equipment or related installations that are designed, fabricated for, and intended for use by a particular customer, if it is determined to be safe for its intended use by its manufacturer on the basis of test data which the employer keeps and makes available for inspection to the Assistant Secretary and his authorized representatives.
29 CFR 1910.399 (Labeled): Labeled. Equipment is "labeled" if there is attached to it a label, symbol, or other identifying mark of a nationally recognized testing laboratory: (1) That makes periodic inspections of the production of such equipment, and (2) whose labeling indicates compliance with nationally recognized standards or tests to determine safe use in a specified manner.
29 CFR 1910.399 (Listed): Equipment is "listed" if it is of a kind mentioned in a list that: (1) Is published by a nationally recognized laboratory that makes periodic inspections of the production of such equipment, and (2) States that such equipment meets nationally recognized standards or has been tested and found safe for use in a specified manner.

Aligned Standard:

Findings:

Recommendations:

02.03.003: Is all electrical equipment in use adequately maintained in accordance with the manufacturer's instructions and applicable codes and standards? NFPA 70B 2023

Answer: **Risk:**

Reference Standards:

29 CFR 1910.303(b)(2): Listed or labeled equipment shall be installed and used in accordance with any instructions included in the listing or labeling.
29 CFR 1910.303(b)(1): Examination. Electric equipment shall be free from recognized hazards that are likely to cause death or serious physical harm to employees.
Note: OSHA 1910.303(b)(1) mandates equipment be free from recognized hazards, and 1910.303(b)(2) requires adherence to manufacturer instructions. While OSHA does not directly adopt NFPA 70B, failure to perform maintenance defined by NFPA 70B can be cited as a violation of 1910.303(b)(1) if it results in a recognized hazard, or 1910.303(b)(2) if the manufacturer's listing requires such maintenance.)

Aligned Standard:

Findings:

Recommendations:

02.03.004: Is the electrical equipment clearly marked with the manufacturer's identification and electrical ratings, and are appropriate safety signs or tags visible to warn employees of electrical hazards?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.303(e)(1): Electrical equipment may not be used unless the following markings have been placed on the equipment: (i) The manufacturer's name, trademark, or other descriptive marking by which the organization responsible for the product may be identified and (ii) Other markings giving voltage, current, wattage, or other ratings as necessary.

29 CFR 1910.335(b)(1): Safety signs and tags. Safety signs, safety symbols, or accident prevention tags shall be used where necessary to warn employees about electrical hazards which may endanger them, as required by Sec. 1910.145.

Aligned Standard:

Findings:

Recommendations:

02.04.001: Is sufficient space and access maintained by electrical equipment 600 volts or less?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.303(g)(1): Sufficient access and working space shall be provided and maintained about all electric equipment to permit ready and safe operation and maintenance of such equipment.

29 CFR1910.303(g)(1)(i)(B): The width of working space in front of the electric equipment shall be the width of the equipment or 762 mm (30 in.), whichever is greater. In all cases, the working space shall permit at least a 90-degree opening of equipment doors or hinged panels

29 CFR 1910.303(g)(1)(i)(A): The depth of the working space in the direction of access to live parts may not be less than indicated in Table S-1. Distances shall be measured from the live parts if they are exposed or from the enclosure front or opening if they are enclosed. The minimum distance is 36", depending on the condition, and can be referenced in Table S-1.

Aligned Standard:

Findings:

Recommendations:

02.05.001: Are all flexible power cords used as a temporary wiring means and NOT permanent wiring?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.305(a)(2)(ii): Temporary wiring shall be removed immediately upon completion of the project or the purpose for which the wiring was installed.

29 CFR 1910.305(a)(2)(i): Temporary electrical power and lighting installations of 600 volts, nominal, or less may be used only as follows: (A): During and for remodeling, maintenance, or repair of buildings, structures, or equipment, and similar activities, (B): For a period not to exceed 90 days for Christmas decorative lighting, carnivals, and similar purposes

(Note): The 90-day limit is ONLY applicable to the purposes identified in 1910.305(a)(2)(i)(B) and does not apply to any other circumstances. All other circumstances require temporary wiring to be removed upon completion of the project or work, (C): For experimental or development work, and during emergencies.

Aligned Standard:

Findings:

Recommendations:

02.06.001: Are all employees performing electrical work properly trained and qualified?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.332(b)(1): Employees shall be trained in and familiar with the safety-related work practices required by Sec. Sec. 1910.331 through 1910.335 that pertain to their respective job assignments.

29 CFR 1910.332(b)(2): Employees who are covered by paragraph (a) of this section but who are not qualified persons shall also be trained in and familiar with any electrically related safety practices not specifically addressed by Sec. Sec. 1910.331 through 1910.335 but which are necessary for their safety.

29 CFR 1910.332(b)(3): Qualified persons (i.e., those permitted to work on or near exposed energized parts) shall, at a minimum, be trained in and familiar with the following: (b)(3)(i): The skills and techniques necessary to distinguish exposed live parts from other parts of electric equipment, (b)(3)(ii): The skills and techniques necessary to determine the nominal voltage of exposed live parts, (b)(3)(iii): The clearance distances specified in Sec. 1910.333(c) and the corresponding voltages to which the qualified person will be exposed.

Note 1: For the purposes of Sec. Sec. 1910.331 through 1910.335, a person must have the training required by paragraph (b)(3) of this section to be considered a qualified person.

Note 2: Qualified persons whose work on energized equipment involves either direct contact or contact by means of tools or materials must also have the training needed to meet Sec. 1910.333(c)(2).

Aligned Standard:

Findings:

Recommendations:

Category: 03 - Employee Temperature Stress

03.01.001: Do you have practices, products, or procedures in place to minimize employee exposure to extreme hot temperatures?

Answer: **Risk:**

Reference Standards:

review the

Aligned Standard:

Findings:

Recommendations:

03.01.002: Do you have a written Heat Stress Prevention Program?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as air conditioning with cooled air or increased air flow, keep body temperatures down by making changes to workload and schedules, provide employees with hydrating fluids, and train employees on how to prevent and recognize heat stress illnesses and injuries, how to apply first aid treatment, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Temperature Stress

Aligned Standard:

Findings:

Recommendations:

03.02.001: Do you have practices, products, or procedures in place to minimize employee exposure to extreme cold temperatures?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as air conditioning with cooled air or increased air flow, keep body temperatures down by making changes to workload and schedules, provide employees with hydrating fluids, and train employees on how to prevent and recognize heat stress illnesses and injuries, how to apply first aid treatment, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Temperature Stress

Aligned Standard:

Findings:

Recommendations:

03.02.002: Do you have a written Cold Stress Prevention Program?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as air conditioning with cooled air or increased air flow, keep body temperatures down by making changes to workload and schedules, provide employees with hydrating fluids, and train employees on how to prevent and recognize heat stress illnesses and injuries, how to apply first aid treatment, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Temperature Stress

Aligned Standard:

Findings:

Recommendations:

03.03.001: Do you currently monitor employees for temperature stress?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970:Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as air conditioning with cooled air or increased air flow, keep body temperatures down by making changes to workload and schedules, provide employees with hydrating fluids, and train employees on how to prevent and recognize heat stress illnesses and injuries, how to apply first aid treatment, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Temperature Stress

Aligned Standard:

Findings:

Recommendations:

Category: 04 - Ergonomics

04.01.001: Do employees at all levels of the organization understand what ergonomics is and can identify ergonomic risk factors (awkward postures, forces, repetitive motion, etc.)?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: Because there is no specific OSHA standard for ergonomics, compliance is assessed under the General Duty Clause. To demonstrate compliance, an employer must show they have implemented feasible means of abatement; this includes training employees to recognize early signs of MSDs and identify risk factors such as repetition, force, and awkward postures before injuries occur.

Aligned Standard:

Findings:

Recommendations:

04.02.001: Do you have a formal process for quantifying risk across workstations and tasks?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: Subjective observation is often insufficient to establish a "recognized hazard" under the General Duty Clause. Employers should utilize validated ergonomic assessment tools (such as the NIOSH Lifting Equation, RULA, REBA, or Strain Index) to objectively quantify risk levels. This data provides the necessary evidence to justify capital expenditures for engineering controls.

Aligned Standard:

Findings:

Recommendations:

04.02.002: Do you have a quantitative measure for all physical demands within each job (e.g., push forces are 50 lbs, horizontal reach in front of the body is 18 inches?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: To determine if a specific task exceeds the physical capabilities of the workforce, and thus constitutes a recognized hazard, accurate data is required. Documenting specific force, frequency, and geometry measurements is essential for comparing job demands against known ergonomic thresholds (such as Snook Tables or Liberty Mutual Tables) and designing appropriate abatements..

Aligned Standard:

Findings:

Recommendations:

04.03.001: Do you have a formal process in place for procurement or design of equipment, workstations, hand tools, etc., to ensure ergonomic design specifications are being considered?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: While OSHA does not explicitly mandate pre-purchase ergonomic evaluations, "Prevention through Design" is considered the most effective and feasible means of abatement. Integrating ergonomic specifications into the procurement process eliminates hazards before they enter the facility, avoiding the higher costs and compliance risks associated with retrofitting equipment later.

Aligned Standard:

Findings:

Recommendations:

04.04.001: Do you have a formal ergonomics process with roles and responsibilities clearly defined at all levels of the organization?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: For an ergonomics program to be considered "effective" during an OSHA inspection, it must be more than a written policy; it must be operational. Clearly defining roles ensures that hazard identification, reporting, and abatement are not ad-hoc activities but are integrated into the daily management system, satisfying the employer's ongoing duty to provide a safe workplace.

Aligned Standard:

Findings:

Recommendations:

04.04.002: Can you prioritize corrective actions within your ergonomics program based on cost, ease of implementation, and overall risk?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: Section 5(a)(1) requires employers to use "feasible" means to abate hazards. By maintaining a prioritized list of corrective actions based on risk severity and implementation difficulty, an employer demonstrates a good-faith effort to systematically address hazards, even if immediate resolution of all issues is not financially or operationally possible simultaneously.

Aligned Standard:

Findings:

Recommendations:

04.05.001: Can you demonstrate the collection of ergonomic solutions that have been put in place that have a proven record of risk reduction or benefits to productivity or quality?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: Mere implementation of a change is not sufficient to satisfy an abatement requirement; the change must actually reduce the hazard. Documenting "after" assessments or case studies serves as proof that the engineering or administrative controls implemented were effective in removing or reducing the recognized hazard to an acceptable level.

Aligned Standard:

Findings:

Recommendations:

04.06.001: Have you identified the light-duty task within each job?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: implement engineering controls, such as mechanical lifting devices, adjustable workstations, or conveyor systems, reduce physical exertion and repetitive motion by making changes to task design and job rotation, provide employees with ergonomically designed tools and anti-fatigue matting, and train employees on how to prevent and recognize signs of Musculoskeletal Disorders (MSDs), how to apply proper body mechanics, and appropriate engineering controls, and personal protective equipment and work practices to reduce the risk of Ergonomic hazards.

Note: Identifying light-duty or restricted-work options proactively is a key component of Medical Management. While not a direct engineering control, this administrative strategy prevents the aggravation of existing MSDs (ensuring they do not progress to "serious physical harm") and supports the employer's obligation to minimize the severity of workplace injuries.

Aligned Standard:

Findings:

Recommendations:

Category: 05 - Exits and Fire Protection

05.01.001: Does this facility have a current emergency action plan?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.38(a): An employer must have an emergency action plan whenever an OSHA standard in this part requires one. The requirements in this section apply to each such emergency action plan.

These standards require a written Emergency Action Plan:

i. 29 CFR 1910.119: Process Safety Management (PSM)
ii. 29 CFR 1910.120: HAZWOPER
iii. 29 CFR 1910.157: Portable Fire Extinguishers
iv. 29 CFR 1910.160 Fixed Extinguishing Systems
v. 29 CFR 1910.164 Fire Detection Systems
vi. 29 CFR 1910.272 Grain Handling Facilities
vii. 29 CFR 1910.1047 Ethylene Oxide (EtO)
viii. 29 CFR 1910.1050 Methylenedianiline (MDA)
ix. 29 CFR 1910.1051 1,3-Butadiene

29 CFR 1910.38(b): An emergency action plan must be in writing, kept in the workplace, and available to employees for review. However, an employer with 10 or fewer employees may communicate the plan orally to employees.

Aligned Standard:

Findings:

Recommendations:

05.01.002: Does this facility have a current fire prevention plan?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.39(a): An employer must have a fire prevention plan when an OSHA standard in this part requires one.

29 CFR 1910.39(b): A fire prevention plan must be in writing, be kept in the workplace, and be made available to employees for review. However, an employer with 10 or fewer employees may communicate the plan orally to employees.

Aligned Standard:

Findings:

Recommendations:

05.02.001: Are all exits clearly visible and marked with an Exit sign?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.37(b)(2): Each exit must be clearly visible and marked by a sign reading "Exit."
29 CFR 1910.37(b)(4): If the direction of travel to the exit or exit discharge is not immediately apparent, signs must be posted along the exit access indicating the direction of travel to the nearest exit and exit discharge. Additionally, the line of sight to an exit sign must clearly be visible at all times.

Aligned Standard:

Findings:

Recommendations:

05.02.002: Are evacuation alarms serviced and tested to ensure reliable and safe operation?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.165(d)(1): The employer shall assure that all employee alarm systems are maintained in operating condition except when undergoing repairs or maintenance.
29 CFR 1910.165(d)(2): The employer shall assure that a test of the reliability and adequacy of non-supervised employee alarm systems is made every two months. A different actuation device shall be used in each test of a multi-actuation device system so that no individual device is used for two consecutive tests.
29 CFR 1910.165(d)(4): The employer shall assure that employee alarm circuitry installed after January 1, 1981, which is capable of being supervised, is supervised and that it will provide positive notification to assigned personnel whenever a deficiency exists in the system. The employer shall ensure that all supervised employee alarm systems are tested at least annually for reliability and adequacy.
29 CFR 1910.165(d)(5): The employer shall assure that the servicing, maintenance, and testing of employee alarms are done by persons trained in the designed operation and functions necessary for reliable and safe operation of the system.

Aligned Standard:

Findings:

Recommendations:

05.03.001: Are adequate fire extinguishers provided in the workplace?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.157(c)(1): The employer shall provide portable fire extinguishers and shall mount, locate, and identify them so that they are readily accessible to employees without subjecting the employees to possible injury.
29 CFR 1910.157(d)(1): Portable fire extinguishers shall be provided for employee use and selected and distributed based on the classes of anticipated workplace fires and on the size and degree of hazard which would affect their use.
29 CFR 1910.157(d)(2): The employer shall distribute portable fire extinguishers for use by employees on Class A fires so that the travel distance for employees to any extinguisher is 75 feet (22.9 m) or less.
29 CFR 1910.157(d)(4): The employer shall distribute portable fire extinguishers for use by employees on Class B fires so that the travel distance from the Class B hazard area to any extinguisher is 50 feet (15.2 m) or less.
29 CFR 1910.157(d)(5): The employer shall distribute portable fire extinguishers used for Class C hazards on the basis of the appropriate pattern for the existing Class A or Class B hazards.

Aligned Standard:

Findings:

Recommendations:

05.03.002: Are all portable fire extinguishers visually tagged to show they have received an annual maintenance check within the last 12 months?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.157(e)(3): The employer shall ensure that portable fire extinguishers are subjected to an annual maintenance check. The employer shall record the annual maintenance date and the initials of the person performing the maintenance.
29 CFR 1910.157(e)(1): The employer shall be responsible for the inspection, maintenance, and testing of all portable fire extinguishers in the workplace.

Aligned Standard:

Findings:

Recommendations:

Category: 06 - Hand Tools

06.01.001: Are hand tools inspected and maintained regularly to ensure safe operation?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.242(a): Each employer shall be responsible for the safe condition of tools and equipment used by employees, including tools and equipment which may be furnished by employees.

Aligned Standard:

Findings:

Recommendations:

06.01.002: Are power tools equipped with the necessary guards and safety features to prevent injuries?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.242(a): Each employer shall be responsible for the safe condition of tools and equipment used by employees, including tools and equipment which may be furnished by employees.

29 CFR 1910.243: Guarding of portable powered tools. The paragraphs within this standard provide guarding requirements for portable power tools, including portable circular saws, switches and controls, portable belt sanders, pneumatic-powered tools, portable abrasive wheels and grinders, high-velocity tools, and power lawn mowers.

Aligned Standard:

Findings:

Recommendations:

06.01.003: Are lithium batteries stored safely in accordance with fire safety and hazardous materials regulations?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970, which mandates that: 'Each employer shall furnish to each of his employees' employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. While OSHA has not yet enacted a specific standard within 29 CFR 1910 governing the storage and charging of lithium-ion batteries in General Industry, the catastrophic failure of these units (thermal runaway) is a growing trend and a universally recognized hazard in the industrial sector; consequently, this hazard is enforceable under the General Duty Clause.

While OSHA has not enacted a specific standard exclusively governing lithium-ion batteries, the hazards associated with their storage, charging, and maintenance are regulated under the General Duty Clause (Section 5(a)(1) of the OSH Act) and a broad range of existing General Industry standards. To ensure compliance, the facility must align its practices with 1910 Subpart L (Fire Protection), 1910.39 (Fire Prevention Plans), and 1910.120 (Hazardous Waste Operation and Emergency Response) to address fire and emergency risks. Operational and handling hazards must be managed through 1910 Subpart S (Electrical), 1910.147 (The Control of Hazardous Energy - Lockout/Tagout), and 1910.178 (Powered Industrial Trucks). Furthermore, employee protection and chemical safety requirements are enforceable under 1910.119 (Process Safety Management), 1910.132 (Personal Protective Equipment), 1910.134 (Respiratory Protection), 1910.151 (Medical Services and First Aid), 1910.1000 (Air Contaminants), 1910.1020 (Access to Employee Exposure and Medical Records), and 1910.1200 (Hazard Communication).

Aligned Standard:

Findings:

Recommendations:

06.02.001: Are tools stored and handled correctly to prevent damage to the tools and ensure safe access?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.242 (a): Each employer shall be responsible for the safe condition of tools and equipment used by employees, including tools and equipment which may be furnished by employees.

29 CFR 1910.176(b): Storage of material shall not create a hazard. Bags, containers, bundles, etc., stored in tiers shall be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

Aligned Standard:

Findings:

Recommendations:

06.03.001: Are employees trained on the proper selection and use of the correct tool for each task?

Answer: **Risk:**

Reference Standards:

General hand tools, OSHA enforces training under the General Duty Clause: Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees' employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees.

Electrical tools, OSHA enforces training under 29 CFR 1910.332(b)(1): Employees shall be trained in and familiar with the safety-related work practices required by Sec. Sec. 1910.331 through 1910.335 that pertain to their respective job assignments.

Aligned Standard:

Findings:

Recommendations:

06.03.002: Are appropriate PPE and safety protocols followed when using higher potential risk tools, such as portable grinders or saws?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(a): Protective equipment, including personal protective equipment for eyes, face, head, and extremities, protective clothing, respiratory devices, and protective shields and barriers, shall be provided, used, and maintained in a sanitary and reliable condition wherever it is necessary by reason of hazards of processes or environment, chemical hazards, radiological hazards, or mechanical irritants encountered in a manner capable of causing injury or impairment in the function of any part of the body through absorption, inhalation or physical contact.
29 CFR 1910.132(d)(1): The employer shall assess the workplace to determine if hazards are present, or are likely to be present, which necessitate the use of personal protective equipment. If such hazards are present, or likely to be present, the employer shall: (i) Select, and have each affected employee use, the types of personal protective equipment that will protect the affected employee from the hazards identified in the hazard assessment; (ii) Communicate selection decisions to each affected employee; and (iii) Select personal protective equipment that properly fits each affected employee.

Aligned Standard:

Findings:

Recommendations:

06.03.003: Are corded tools managed and used in a way that minimizes slip, trip, and fall hazards?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.22(a)(1): All places of employment, passageways, storerooms, and service rooms shall be kept clean, orderly, and in a sanitary condition.
29 CFR 1910.305(g)(1)(iii): Flexible cords and cables shall not be used for the following: (A) As a substitute for the fixed wiring of a structure; (B) Where run through holes in walls, ceilings, or floors; (C) Where run through doorways, windows, or similar openings; (D) Where attached to building surfaces; or (E) Where concealed behind building walls, ceilings, or floors.

Aligned Standard:

Findings:

Recommendations:

Category: 07 - Hazardous Substances

07.01.001: Have you done a hazard assessment to ensure hazardous substances are being stored properly?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.120(b)(4)(i): General. The site safety and health plan, which must be kept on site, shall address the safety and health hazards of each phase of site operation and include the requirements and procedures for employee protection.
29 CFR 1910.1200(b)(1): "This section requires chemical manufacturers or importers to classify the hazards of chemicals which they produce or import, and all employers to provide information to their employees about the hazardous chemicals to which they are exposed, by means of a hazard communication program, labels and other forms of warning, safety data sheets, and information and training.
29 CFR 1910.132(d)(1): The employer shall assess the workplace to determine if hazards are present, or are likely to be present, which necessitate the use of personal protective equipment (PPE). If such hazards are present, or likely to be present, the employer shall: (i) Select and have each affected employee use the types of PPE that will protect the affected employee from the hazards identified in the hazard assessment, (ii) Communicate selection decisions to each affected employee, and (iii) Select PPE that properly fits each affected employee.

Aligned Standard:

Findings:

Recommendations:

07.01.002: Do you currently store chemicals in an approved container, cabinet, or room?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.106(a)(35): Approved unless otherwise indicated, approved, or listed by a nationally recognized testing laboratory. Refer to Sec. 1910.7 for the definition of nationally recognized testing laboratory.
29 CFR 1910.106(d)(2)(i): General. Only approved containers and portable tanks shall be used. Metal containers and portable tanks meeting the requirements of and containing products authorized by chapter I, title 49 of the Code of Federal Regulations (regulations issued by the Hazardous Materials Regulations Board, Department of Transportation), shall be deemed to be acceptable.
29 CFR 1910.106(d)(3)(i): Maximum capacity. Not more than 60 gallons of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons of Category 4 flammable liquids, may be stored in a storage cabinet.
29 CFR 1910.106(d)(3)(ii)(a): Metal cabinets constructed in the following manner shall be deemed to be in compliance. The bottom, top, door, and sides of the cabinet shall be at least No. 18-gauge sheet iron and double-walled with 1-inch air space. Joints shall be riveted, welded, or made tight by some equally effective means. The door shall be provided with a three-point lock, and the door sill shall be raised at least 2 inches above the bottom of the cabinet.
29 CFR 1910.106(d)(4)(i): Construction. Inside storage rooms shall be constructed to meet the required fire-resistive rating for their use. Such construction shall comply with the test specifications set forth in Standard Methods of Fire Tests of Building Construction and Materials, NFPA 251-1969. Where an automatic sprinkler system is provided, the system shall be designed and installed in an acceptable manner. Openings to other rooms or buildings shall be provided with noncombustible liquid-tight raised sills or ramps at least 4 inches in height, or the floor in the storage area shall be at least 4 inches below the surrounding floor. Openings shall be provided with approved self-closing fire doors. The room shall be liquid-tight at the wall-floor junctions. A permissible alternative to the sill or ramp is an open-grated trench inside the room, which drains to a safe location. Where other portions of the building or other properties are exposed, windows shall be protected as set forth in the Standard for Fire Doors and Windows, NFPA No. 80-1968, which is incorporated by reference as specified in Sec. 1910.6, for Class E or F openings. Wood at least 1 inch nominal thickness may be used for shelving, racks, dunnage, scuffboards, floor overlay, and similar installations.
29 CFR 1910.106(d)(4)(iv): Ventilation. Every inside storage room shall be provided with either a gravity or a mechanical exhaust ventilation system. Such a system shall be designed to provide for a complete change of air within the room at least six times per hour. If a mechanical exhaust system is used, it shall be controlled by a switch located outside the door. The ventilating equipment and any lighting fixtures shall be operated by the same switch. A pilot light shall be installed adjacent to the switch if Category 1 or 2 flammable liquids, or Category 3 flammable liquids with a flashpoint below 100 degF (37.8 degC), are dispensed within the room. Where gravity ventilation is provided, the fresh air intake, as well as the exhaust outlet from the room, shall be on the exterior of the building in which the room is located.

Aligned Standard:

Findings:

Recommendations:

07.02.001: Is secondary containment in use where hazardous chemicals are transferred or stored?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1450(h)(1): Employers shall ensure that special precautions are taken in the handling of particularly hazardous substances.
29 CFR 1910.120(j)(1)(viii): Where major spills may occur, a spill containment program, which is part of the employer's safety and health program required in paragraph (b) of this section, shall be implemented to contain and isolate the entire volume of the hazardous substance being transferred.

Aligned Standard:

Findings:

Recommendations:

07.02.002: Are adequate means, such as spill or neutralization kits, provided for clean-up in the event of a hazardous chemical spill?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.120(j)(1)(vii): U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbent shall be kept available and used in areas where spills, leaks, or ruptures may occur.
29 CFR 1910.120(j)(1)(viii): Where major spills may occur, a spill containment program, which is part of the employer's safety and health program required in paragraph (b) of this section, shall be implemented to contain and isolate the entire volume of the hazardous substance being transferred.
29 CFR 1910.120(j)(1)(xii): Fire extinguishing equipment meeting the requirements of 29 CFR part 1910, subpart L, shall be on hand and ready for use to control incipient fires.
29 CFR1910.120(q)(1): Emergency response plan. An emergency response plan shall be developed and implemented to handle anticipated emergencies prior to the commencement of emergency response operations. The plan shall be in writing and available for inspection and copying by employees, their representatives and OSHA personnel. Employers who will evacuate their employees from the danger area when an emergency occurs, and who do not permit any of their employees to assist in handling the emergency, are exempt from the requirements of this paragraph if they provide an emergency action plan in accordance with 29 CFR 1910.38.

Aligned Standard:

Findings:

Recommendations:

07.03.001: Do you have engineering or administrative controls in place to prevent dust accumulations that could pose a fire or explosion hazard?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.176(c): Storage areas shall be kept free from accumulation of materials that constitute hazards from tripping, fire, explosion, or pest harborage

29 CFR 1910.22(a)(1): All places of employment, passageways, storerooms, service rooms, and walking-working surfaces are kept in a clean, orderly, and sanitary condition.

29 CFR 1910.176(c): Housekeeping. Storage areas shall be kept free from accumulation of materials that constitute hazards from tripping, fire, explosion, or pest harborage. Vegetation control will be exercised when necessary

Aligned Standard:

Findings:

Recommendations:

07.03.002: Is exposure to silica dust prevented?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1053(c): The employer shall ensure that no employee is exposed to an airborne concentration of respirable crystalline silica in excess of 50 ug/m3, calculated as an 8-hour TWA.

29 CFR 1910.1053(f)(1): The employer shall use engineering and work practice controls to reduce and maintain employee exposure to respirable crystalline silica to or below the PEL, unless the employer can demonstrate that such controls are not feasible. Wherever such feasible engineering and work practice controls are not sufficient to reduce employee exposure to or below the PEL, the employer shall nonetheless use them to reduce employee exposure to the lowest feasible level and shall supplement them with the use of respiratory protection that complies with the requirements of paragraph (g) of this section.

29 CFR 1910.1053(f)(2)(i): The employer shall establish and implement a written exposure control plan that contains at least the following elements: (A) A description of the tasks in the workplace that involve exposure to respirable crystalline silica; (B) A description of the engineering controls, work practices, and respiratory protection used to limit employee exposure to respirable crystalline silica for each task; (C) A description of the housekeeping measures used to limit employee exposure to respirable crystalline silica; and (D) A description of the procedures used to restrict access to work areas, when necessary, to minimize the number of employees exposed to respirable crystalline silica and their level of exposure, including exposures generated by other employers or sole proprietors.

29 CFR 1910.1053(h)(1) "The employer shall not allow dry sweeping or dry brushing where such activity could contribute to employee exposure to respirable crystalline silica unless wet sweeping, HEPA-filtered vacuuming or other methods that minimize the likelihood of exposure are not feasible.

Aligned Standard:

Findings:

Recommendations:

Category: 08 - HazCom

08.01.001: Does your organization have a written hazard communication program?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(e)(1): Employers shall develop, implement, and maintain at each workplace, a written hazard communication program which at least describes how the criteria specified in paragraphs (f), (g), and (h) of this section for labels and other forms of warning, safety data
sheets, and employee information and training will be met, and which also includes the following, which are defined in the following regulations: (e)(1)(i), (e)(1)(ii) of this section.
29 CFR 1910.1200(e)(1)(i): A list of the hazardous chemicals known to be present using a product identifier that is referenced on the appropriate safety data sheet (the list may be compiled for the workplace as a whole or for individual work areas) and,
29 CFR 1910.1200(e)(1)(ii): The methods the employer will use to inform employees of the hazards of non-routine tasks (for example, the cleaning of reactor vessels), and the hazards associated with chemicals contained in unlabeled pipes in their work areas.

Aligned Standard:

Findings:

Recommendations:

08.02.001: Are all hazardous chemical containers labeled with either shipped container labels or in-plant workplace labels?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(f)(1): Labels on shipped containers. The chemical manufacturer, importer, or distributor shall ensure that each container of hazardous chemicals leaving the workplace is labeled, tagged or marked.
29 CFR 1910.1200(f)(6): Workplace labeling. Except as provided in paragraphs (f)(7) and (f)(8) of this section, the employer shall ensure that each container of hazardous chemicals in the workplace is labeled, tagged or marked with either: (i) The information specified under paragraphs (f)(1)(i) through (v) of this section for labels on shipped containers; or, (ii) Product identifier and words, pictures, symbols, or combination thereof, which provide at least general information regarding the hazards of the chemicals, and which, in conjunction with the other information immediately available to employees under the hazard communication program, will provide employees with the specific information regarding the physical and health hazards of the hazardous chemical.

Aligned Standard:

Findings:

Recommendations:

08.02.002: Are you currently meeting the requirements of the Global Harmonized System (GHS) under the OSHA HAZCOM standard?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(a)(1): The purpose of this section is to ensure that the hazards of all chemicals produced or imported are classified, and that information cncerning the classified hazards is transmitted to employers and employees. The requirements of this section are intended to be consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS), Revision 3.

29 CFR 1910.1200(j)(2): Hazard communication programs and specific training for new physical or health hazards (no later than June 1, 2016). Employers shall have updated the hazard communication programs required by paragraph (e) of this section as necessary, and shall have provided additional employee training for newly identified physical or health hazards.

Aligned Standard:

Findings:

Recommendations:

08.03.001: Do you conduct training for your employees on hazardous chemicals used in their work area?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(h)(1): Employers shall provide employees with effective information and training on hazardous chemicals in their work area at the time of their initial assignment, and whenever a new chemical hazard the employees have not previously been trained about is introduced into their work area. Information and training may be designed to cover categories of hazards (e.g., flammability, carcinogenicity) or specific chemicals. Chemical-specific information must always be available through labels and safety data sheets.

Aligned Standard:

Findings:

Recommendations:

08.04.001: Are the most current Safety Data Sheets (SDS) maintained (hard copy or electronic) for each hazardous chemical on-site?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(g)(1): Chemical manufacturers and importers shall obtain or develop a safety data sheet for each hazardous chemical they produce or import. Employers shall have a safety data sheet in the workplace for each hazardous chemical which they use.
29 CFR 1910.1200(g)(8): The employer shall maintain in the workplace copies of the required safety data sheets for each hazardous chemical, and shall ensure that they are readily accessible during each work shift to employees when they are in their work area(s). (Electronic access and other alternatives to maintaining paper copies of the safety data sheets are permitted as long as no barriers to immediate employee access in each workplace are created by such options.)

Aligned Standard:

Findings:

Recommendations:

Category: 09 - Lockout / Tagout

09.01.001: Do you have a comprehensive written LO/TO program established at this facility?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.147(c)(1): Energy control program. The employer shall establish a program consisting of energy control procedures, employee training and periodic inspections to ensure that before any employee performs any servicing or maintenance on a machine or equipment where the unexpected energizing, startup or release of stored energy could occur and cause injury, the machine or equipment shall be isolated from the energy source and rendered inoperative.

Aligned Standard:

Findings:

Recommendations:

09.02.001: Are written procedures developed, documented, and utilized for all equipment at this facility that requires procedures to isolate and control the energy?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.147(c)(4)(i): Procedures shall be developed, documented, and utilized for the control of potentially hazardous energy when employees are engaged in the activities covered by this section.

Aligned Standard:

Findings:

Recommendations:

09.02.002: Has a periodic inspection of your LO/TO procedures, including the application of the procedures by authorized persons, been performed within the last year?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.147(c)(6)(i): The employer shall conduct a periodic inspection of the energy control procedure at least annually to ensure that the procedure and the requirements of this standard are being followed.

29 CFR 1910.147(c)(6)(i)(A): The periodic inspection shall be performed by an authorized employee other than the one(s) utilizing the energy control procedure being inspected.

29 CFR 1910.147(c)(6)(i)(C): The periodic inspection shall be conducted to correct any deviations or inadequacies identified.

Aligned Standard:

Findings:

Recommendations:

09.03.001: Are all necessary LO/TO devices available for use?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.147(c)(5)(i): Materials and hardware. The employer shall provide locks, tags, chains, wedges, key blocks, adapter pins, self-locking fasteners, or other hardware for isolating, securing, or blocking machines or equipment from energy sources.

Aligned Standard:

Findings:

Recommendations:

09.04.001: Have all affected employees been adequately trained on LOTO programs and procedures?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.147(c)(7)(i): The employer shall provide training to ensure that the purpose and function of the energy control program are understood by employees and that the knowledge and skills required for the safe application, usage, and removal of the energy controls are acquired by employees.

29 CFR 1910.147(c)(7)(i)(B): Each affected employee shall be instructed in the purpose and use of the energy control procedure.

Aligned Standard:

Findings:

Recommendations:

Category: 10 - Machine Safety

10.01.001: Do you have practices... in place to minimize employee exposure to nip points, rotating parts, flying chips, and sparks...?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.212(a)(1): Types of guarding. One or more methods of machine guarding shall be provided to protect the operator and other employees in the machine area from hazards such as those created by the point of operation, ingoing nip points, rotating parts, flying chips, and sparks. Examples of guarding methods are: barrier guards, two-hand tripping devices, electronic safety devices, etc.

Aligned Standard:

Findings:

Recommendations:

10.01.002: Have machine guards been provided to protect the operator and other employees...?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.212(a)(1): Types of guarding. One or more methods of machine guarding shall be provided to protect the operator and other employees in the machine area from hazards such as those created by the point of operation, ingoing nip points, rotating parts, flying chips, and sparks. Examples of guarding methods are: barrier guards, two-hand tripping devices, electronic safety devices, etc.

Aligned Standard:

Findings:

Recommendations:

10.02.001: Are all machines that are designed for a fixed location securely anchored?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.212(b): Anchoring fixed machinery. Machines designed for a fixed location shall be securely anchored to prevent walking or moving.

Aligned Standard:

Findings:

Recommendations:

10.03.001: Are adequate measures in place to provide safe operation of pneumatic tools and compressed air?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.242(b): Compressed air used for cleaning. Compressed air shall not be used for cleaning purposes except where reduced to less than 30 p.s.i. and then only with effective chip guarding and personal protective equipment.

29 CFR 1910.243(b)(1): Tool retainer. A tool retainer shall be installed on each piece of utilization equipment which, without such a retainer, may eject the tool.

29 CFR 1910.243(b)(2): Airhose. Hose and hose connections used for conducting compressed air to utilization equipment shall be designed for the pressure and service to which they are subjected.

Aligned Standard:

Findings:

Recommendations:

Category: 11 - Material Handling

11.01.001: Are sufficient safe clearances allowed for aisles, at loading docks, through doorways, and wherever turns or passages must be made where mechanical handling equipment is used?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.176(a): Use of mechanical equipment. Where mechanical handling equipment is used, sufficient safe clearances shall be allowed for aisles, at loading docks, through doorways, and wherever turns or passages must be made.

Aligned Standard:

Findings:

Recommendations:

11.01.002: Is the material stored in such a way that it does not create a hazard?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.176(b): Secure storage. Storage of material shall not create a hazard. Bags, containers, bundles, etc., stored in tiers shall be stacked, blocked, interlocked, and limited in height so that they are stable and secure against sliding or collapse.

Aligned Standard:

Findings:

Recommendations:

11.02.001: Has each powered industrial truck operator been properly trained?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.178(l)(1)(i): The employer shall ensure that each powered industrial truck operator is competent to operate a powered industrial truck safely, as demonstrated by the successful completion of the training and evaluation specified in this paragraph (l).

29 CFR 1910.178(l)(6): Certification. The employer shall certify that each operator has been trained and evaluated as required by this paragraph (l).

Aligned Standard:

Findings:

Recommendations:

11.03.001: Are all powered industrial trucks operated in a safe manner?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.178(n): All traffic regulations shall be observed, including authorized plant speed limits. A safe distance shall be maintained approximately three truck lengths from the truck ahead, and the truck shall be kept under control at all times.

29 CFR 1910.178(n)(15): While negotiating turns, speed shall be reduced to a safe level by means of turning the hand steering wheel in a smooth, sweeping motion. Except when maneuvering at a very low speed, the hand steering wheel shall be turned at a moderate, even rate.

Aligned Standard:

Findings:

Recommendations:

11.03.002: Are inspections of powered industrial trucks performed and documented at an adequate frequency?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.178(q)(7): Industrial trucks shall be examined before being placed in service, and shall not be placed in service if the examination shows any condition adversely affecting the safety of the vehicle. Such examination shall be made at least daily.

Where industrial trucks are used on a round-the-clock basis, they shall be examined after each shift. Defects when found shall be immediately reported and corrected.

Aligned Standard:

Findings:

Recommendations:

11.04.001: Has the facility conducted an assessment of potential hazards resulting from PIT and pedestrian interactions?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as physical barriers (guardrails/bollards) separating walkways from vehicle lanes, designated pedestrian crosswalks, convex mirrors at blind intersections, or sensor-based collision avoidance systems reduce struck-by hazards and traffic congestion by making changes to facility layout, aisle design, and traffic flow patterns provide employees with clearly marked designated paths and high-visibility vests and train employees on how to prevent and recognize situational hazards involving mobile equipment, how to apply pedestrian right-of-way rules, and appropriate engineering controls and work practices to reduce the risk of Powered Industrial Truck (PIT) hazards.

Note: Mere implementation of a change (e.g., painting a line on the floor) is not sufficient to satisfy an abatement requirement; the change must actually reduce the hazard. Documenting "after" assessments or traffic-flow observations provides evidence that the engineering or administrative controls implemented were effective in eliminating or reducing the recognized hazard to an acceptable level.

Aligned Standard:

Findings:

Recommendations:

11.04.002: Is the facility designed to minimize interaction between PITs and pedestrians?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as physical barriers (guardrails/bollards) separating walkways from vehicle lanes, designated pedestrian crosswalks, convex mirrors at blind intersections, or sensor-based collision avoidance systems reduce struck-by hazards and traffic congestion by making changes to facility layout, aisle design, and traffic flow patterns provide employees with clearly marked designated paths and high-visibility vests and train employees on how to prevent and recognize situational hazards involving mobile equipment, how to apply pedestrian right-of-way rules, and appropriate engineering controls and work practices to reduce the risk of Powered Industrial Truck (PIT) hazards.

Note: Mere implementation of a change (e.g., painting a line on the floor) is not sufficient to satisfy an abatement requirement; the change must actually reduce the hazard. Documenting "after" assessments or traffic-flow observations provides evidence that the engineering or administrative controls implemented were effective in eliminating or reducing the recognized hazard to an acceptable level.

Aligned Standard:

Findings:

Recommendations:

11.04.003: Are designated paths provided and clearly marked for pedestrians where PIT traffic is present?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.22(b)(2): The employer must ensure: Permanent aisles and passageways are appropriately marked.

29 CFR 1910.176(a): Use of mechanical equipment. Where mechanical handling equipment is used, sufficient safe clearances shall be allowed for aisles, at loading docks, through doorways and wherever turns or passage must be made. Aisles and passageways shall be kept clear and in good repair, with no obstruction across or in aisles that could create a hazard. Permanent aisles and passageways shall be appropriately marked.

29 CFR 1910.144(a)(3): Yellow shall be the basic color for designating caution and for marking physical hazards such as: Striking against, stumbling, falling, tripping, and "caught in between."

Aligned Standard:

Findings:

Recommendations:

11.04.004: Are designated crosswalks provided and clearly marked where pedestrian and PIT traffic intersections are present?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as physical barriers (guardrails/bollards) separating walkways from vehicle lanes, designated pedestrian crosswalks, convex mirrors at blind intersections, or sensor-based collision avoidance systems reduce struck-by hazards and traffic congestion by making changes to facility layout, aisle design, and traffic flow patterns provide employees with clearly marked designated paths and high-visibility vests and train employees on how to prevent and recognize situational hazards involving mobile equipment, how to apply pedestrian right-of-way rules, and appropriate engineering controls and work practices to reduce the risk of Powered Industrial Truck (PIT) hazards.

Note: Mere implementation of a change (e.g., painting a line on the floor) is not sufficient to satisfy an abatement requirement; the change must actually reduce the hazard. Documenting "after" assessments or traffic-flow observations provides evidence that the engineering or administrative controls implemented were effective in eliminating or reducing the recognized hazard to an acceptable level.

Aligned Standard:

Findings:

Recommendations:

11.04.005: Are doorways that open directly into designated PIT traffic routes protected?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as physical barriers (guardrails/bollards) separating walkways from vehicle lanes, designated pedestrian crosswalks, convex mirrors at blind intersections, or sensor-based collision avoidance systems reduce struck-by hazards and traffic congestion by making changes to facility layout, aisle design, and traffic flow patterns provide employees with clearly marked designated paths and high-visibility vests and train employees on how to prevent and recognize situational hazards involving mobile equipment, how to apply pedestrian right-of-way rules, and appropriate engineering controls and work practices to reduce the risk of Powered Industrial Truck (PIT) hazards.

Note: Mere implementation of a change (e.g., painting a line on the floor) is not sufficient to satisfy an abatement requirement the change must actually reduce the hazard. Documenting "after" assessments or traffic-flow observations provides evidence that the engineering or administrative controls implemented were effective in eliminating or reducing the recognized hazard to an acceptable level.

Aligned Standard:

Findings:

Recommendations:

11.04.006: Are cranes and hoists inspected at an adequate frequency?

Answer: **Risk:**

Reference Standards:

29 CFR OSHA 1910.178(n)(4): the driver shall be required to slow down and sound the horn at cross aisles and other locations where vision is obstructed. If the load being carried obstructs the forward view, the driver shall be required to travel with the load trailing.

Aligned Standard:

Findings:

Recommendations:

11.05.001: Are all slings inspected at an adequate frequency?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.179(j)(1)(i): Prior to initial use all new and altered cranes shall be inspected to insure compliance with the provisions of this section.

29 CFR 1910.179(j)(1)(ii): Inspection procedure for cranes in regular service is divided into two general classifications based upon the intervals at which inspection should be performed. The intervals, in turn, are dependent upon the nature of the critical components of the crane and the degree of their exposure to wear, deterioration, or malfunction. The two general classifications are herein designated as "frequent" and "periodic" with respective intervals between inspections as defined below: (a) Frequent inspection - Daily to monthly intervals. (b) Periodic inspection - 1 to 12-month intervals.

Aligned Standard:

Findings:

Recommendations:

Category: 12 - Medical First Aid

12.01.001: Is there a hospital, clinic, or infirmary for medical care near your workplace, or is at least one employee on each shift currently qualified to render first aid?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.151(b): In the absence of an infirmary, clinic, or hospital in near proximity to the workplace which is used for the treatment of all injured employees, a person or persons shall be adequately trained to render first aid. Adequate first aid supplies shall be readily available.

Aligned Standard:

Findings:

Recommendations:

12.01.002: Are your first aid kits or supplies adequate, easily accessible, periodically inspected, and replenished as needed?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.151(b): In the absence of an infirmary, clinic, or hospital in near proximity to the workplace which is used for the treatment of all injured employees, a person or persons shall be adequately trained to render first aid. Adequate first aid supplies shall be readily available.

Note: While OSHA requires that adequate first aid supplies be readily available to employees, ANSI/ISEA Z308.1 serves as the "how-to" guide for specific kit contents, inspection, and replenishment. Although this consensus standard contains specific requirements for inspection and replenishment lists, it is not incorporated by reference into 29 CFR 1910 as a mandatory standard.

Aligned Standard:

Findings:

Recommendations:

12.02.001: Do you have adequate AEDs present at this facility?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement a Medical Emergency Response Plan that includes the placement of Automated External Defibrillators (AEDs) in accessible locations to address the hazard of sudden cardiac arrest ensure AEDs are available within a timeframe that optimizes survival rates (typically 3-5 minutes from collapse to shock) conduct regular maintenance and inspection of units to ensure functionality (checking pads and batteries) and provide training to designated employees on CPR and the proper use of AEDs to reduce the risk of fatality associated with medical emergencies.

Note: Mere installation of a device (e.g., mounting a cabinet on the wall) is not sufficient to satisfy an abatement requirement; the equipment must be functional and accessible. Documenting regular monthly inspections (verifying battery/pad expiration) and maintaining active training records provides evidence that the administrative controls and emergency equipment implemented are effective in reducing the recognized hazard.

Aligned Standard:

Findings:

Recommendations:

12.03.001: Are all employees who may be exposed to blood or other infectious bodily fluids included in your exposure control plan?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1030(b): Definition of Occupational Exposure: Occupational Exposure means reasonably anticipated skin, eye, mucous membrane, or parenteral contact with blood or other potentially infectious materials that may result from the performance of an employee's duties.

29 CFR 1910.1030(c)(1)(i): Each employer having an employee(s) with occupational exposure as defined by paragraph (b) of this section shall establish a written Exposure Control Plan designed to eliminate or minimize employee exposure.

29 CFR 1910.1030(d)(1): Universal precautions shall be observed to prevent contact with blood or other potentially infectious materials. Under circumstances in which differentiation between body fluid types is difficult or impossible, all body fluids shall be considered potentially infectious materials.

Aligned Standard:

Findings:

Recommendations:

12.04.001: Do you have adequate emergency eyewash/showers present at this facility?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.151(c): Where the eyes or body of any person may be exposed to injurious corrosive materials, suitable facilities for quick drenching or flushing of the eyes and body shall be provided within the work area for immediate emergency use.

Note: While OSHA 29 CFR 1910.151(c) mandates that "suitable facilities" for quick drenching be provided where injurious corrosive materials are present, it does not define specific parameters. ANSI/ISEA Z358.1 serves as the "how-to" guide for establishing performance specifications (e.g., flow rate, temperature), though it is not incorporated by reference into the regulation as a mandatory standard.

Aligned Standard:

Findings:

Recommendations:

Category: 13 - Occupational Health Hazards

13.01.001: Has a noise monitoring survey been conducted to identify employees who may be exposed to noise at or above the Action Level of 85 dBA (8-hour TWA)?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.95(d)(1): When information indicates that any employee's exposure may equal or exceed an 8-hour time-weighted average of 85 decibels, the employer shall develop and implement a monitoring program.

Aligned Standard:

Findings:

Recommendations:

13.01.002: If noise exposures equal or exceed the Action Level (85 dBA), has a continuing, effective Hearing Conservation Program been implemented?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.95(c)(1): The employer shall administer a continuing, effective hearing conservation program, as described in paragraphs (c) through (o) of this section, whenever employee noise exposures equal or exceed an 8-hour time-weighted average sound level (TWA) of 85 decibels measured on the A scale (slow response) or, equivalently, a dose of fifty percent. For purposes of the hearing conservation program, employee noise exposures shall be computed in accordance with appendix A and Table G-16a, and without regard to any attenuation provided by the use of personal protective equipment.

Aligned Standard:

Findings:

Recommendations:

13.01.003: Are feasible administrative or engineering controls utilized to reduce sound levels?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.95(b)(1): When employees are subjected to sound exceeding those listed in Table G-16, feasible administrative or engineering controls shall be utilized. If such controls fail to reduce sound levels within the levels of Table G-16, personal protective equipment shall be provided and used to reduce sound levels within the levels of the table.

Aligned Standard:

Findings:

Recommendations:

13.01.004: Where controls fail to reduce exposure, is adequate hearing protection provided and mandatory?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.95(b)(1): When employees are subjected to sound exceeding those listed in Table G-16, feasible administrative or engineering controls shall be utilized. If such controls fail to reduce sound levels within the levels of Table G-16, personal protective equipment shall be provided and used to reduce sound levels within the levels of the table.

Aligned Standard:

Findings:

Recommendations:

13.02.001: Have potential employee exposures to airborne contaminants (dust, fumes, vapors) been evaluated to determine if they exceed permissible limits?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.134(d)(1)(iii): The employer shall identify and evaluate the respiratory hazard(s) in the workplace; this evaluation shall include a reasonable estimate of employee exposures to respiratory hazard(s) and an identification of the contaminant's chemical state and physical form. Where the employer cannot identify or reasonably estimate the employee exposure, the employer shall consider the atmosphere to be immediately dangerous to life or health (IDLH).

Aligned Standard:

Findings:

Recommendations:

13.02.002: Is effective local exhaust or general ventilation maintained in areas where hazardous air contaminants are generated?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.134(a)(1): In the control of those occupational diseases caused by breathing air contaminated with harmful dusts, fogs, fumes, mists, gases, smokes, sprays, or vapors, the primary objective shall be to prevent atmospheric contamination. This shall be accomplished as far as feasible by accepted engineering control measures (for example, enclosure or confinement of the operation, general and local ventilation, and substitution of less toxic materials).

Aligned Standard:

Findings:

Recommendations:

13.02.003: If engineering controls fail to reduce exposure limits, has a written Respiratory Protection Program been implemented in accordance with 29 CFR 1910.134?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.134(d)(1)(iii): The employer shall identify and evaluate the respiratory hazard(s) in the workplace this evaluation shall include a reasonable estimate of employee exposures to respiratory hazard(s) and an identification of the contaminant's chemical state and physical form.

Aligned Standard:

Findings:

Recommendations:

13.03.001: Have indoor air quality assessments for mold been conducted in areas with known moisture intrusion, water damage, or high humidity?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.141(a)(3)(i): All places of employment shall be kept clean to the extent that the nature of the work allows.

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as maintaining building envelopes to prevent water intrusion, ensuring HVAC systems are regularly inspected to keep relative humidity below 60%, and utilizing dehumidifiers or local exhaust ventilation in high-moisture areas reduce biological hazards by identifying and eliminating the source of moisture within 24-48 hours of a water event and removing water-damaged porous materials that cannot be effectively cleaned provide employees involved in remediation with appropriate Personal Protective Equipment (PPE) (e.g., N95 respirators, gloves, and eye protection) as determined by a hazard assessment and train employees on how to recognize and report water intrusion or mold growth, the potential health effects of exposure, and the appropriate work practices to maintain a dry working environment.

Aligned Standard:

Findings:

Recommendations:

13.04.001: Has an exposure determination been conducted for other regulated hazards present in the facility (e.g., Lead, Asbestos, Silica, Hexavalent Chromium) as required by their specific OSHA standards?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1026(d)(1) Hexavalent Chromium: General. Each employer who has a workplace or work operation covered by this section shall determine the 8-hour TWA exposure for each employee exposed to chromium (VI).

29 CFR 1910.1025(d)(2) Lead: Initial determination. Each employer who has a workplace or work operation covered by this standard shall determine if any employee may be exposed to lead at or above the action level.

29 CFR 1910.1025(d)(3)(i): Basis of initial determination. (A) The employer shall monitor employee exposures and shall base initial determinations on the employee exposure monitoring results and any of the following, relevant considerations: (1) Any information, observations, or calculations which would indicate employee exposure to lead (2) Any previous measurements of airborne lead and (3) Any employee complaints of symptoms which may be attributable to exposure to lead.

29 CFR 1910.1001(d)(2)(i): Asbestos: Initial monitoring. Each employer who has a workplace or work operation covered by this standard shall perform monitoring to determine accurately the airborne concentrations of asbestos to which employees may be exposed

29 CFR 1910.1053(d)(1): Silica: The employer shall assess the exposure of each employee who is or may reasonably be expected to be exposed to respirable crystalline silica at or above the action level in accordance with either the performance option in paragraph (d)(2) or the scheduled monitoring option in paragraph (d)(3) of this section.

29 CFR 1910.1053(d)(2): Silica: Performance option. The employer shall assess the 8-hour TWA exposure for each employee on the basis of any combination of air monitoring data or objective data sufficient to accurately characterize employee exposures to respirable crystalline silica.

29 CFR 1910.1053(d)(3)(i): Silica: Scheduled monitoring option. The employer shall perform initial monitoring to assess the 8-hour TWA exposure for each employee on the basis of one or more personal breathing zone air samples that reflect the exposures of employees on each shift, for each job classification, in each work area.

Aligned Standard:

Findings:

Recommendations:

Category: 14 - Personal Protective Equipment

14.01.001: Are employees using the required PPE for this facility?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(a): Protective equipment, including personal protective equipment for eyes, face, head, and extremities, protective clothing, respiratory devices, and protective shields and barriers, shall be provided, used, and maintained in a sanitary and reliable condition wherever it is necessary by reason of hazards of processes or environment, chemical hazards, radiological hazards, or mechanical irritants encountered in a manner capable of causing injury or impairment in the function of any part of the body through absorption, inhalation or physical contact.

29 CFR 1910.132(d)(1): The employer shall assess the workplace to determine if hazards are present, or are likely to be present, which necessitate the use of personal protective equipment (PPE). If such hazards are present, the employer must select the types of PPE that will protect the affected employee, communicate selection decisions to each affected employee, and select PPE that properly fits each affected employee.

Aligned Standard:

Findings:

Recommendations:

14.01.002: Do you have a current workplace hazard assessment to determine the required PPE for each job in this facility?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(d)(1): The employer shall assess the workplace to determine if hazards are present, or are likely to be present, which necessitate the use of personal protective equipment (PPE). If such hazards are present, the employer must select the types of PPE that will protect the affected employee, communicate selection decisions to each affected employee, and select PPE that properly fits each affected employee.

29 CFR 1910.132(d)(2): The employer shall verify that the required workplace hazard assessment has been performed through a written certification that identifies the workplace evaluated; the person certifying that the evaluation has been performed; the date(s) of the hazard assessment; and, which identifies the document as a certification of hazard assessment.

Aligned Standard:

Findings:

Recommendations:

14.02.001: Do employees receive training on the selection and use of PPE?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(f)(1): The employer shall provide training to each employee who is required by this section to use PPE. Each such employee shall be trained to know at least the following: (i) When PPE is necessary; (ii) What PPE is necessary; (iii) How to properly don, doff, adjust, and wear PPE; (iv) The limitations of the PPE; and, (v) The proper care, maintenance, useful life and disposal of the PPE.

Aligned Standard:

Findings:

Recommendations:

14.03.001: Is PPE of safe design or construction for the work to be performed?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(c): Design. All personal protective equipment shall be of safe design and construction for the work to be performed.

Aligned Standard:

Findings:

Recommendations:

14.04.001: Is the required PPE properly fitted?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(d)(1)(iii): Select PPE that properly fits each affected employee.

Aligned Standard:

Findings:

Recommendations:

14.04.002: Are simultaneously worn PPE items compatible and effective together?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.134(g)(1)(i)(B): States: "Do not interfere with the seal of the facepiece." (Specific to respirators, not general PPE).

Aligned Standard:

Findings:

Recommendations:

14.05.001: Is all PPE maintained in a sanitary condition and ready for use?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(a): Protective equipment, including personal protective equipment for eyes, face, head, and extremities, protective clothing, respiratory devices, and protective shields and barriers, shall be provided, used, and maintained in a sanitary and reliable condition wherever it is necessary by reason of hazards of processes or environment, chemical hazards, radiological hazards, or mechanical irritants encountered in a manner capable of causing injury or impairment in the function of any part of the body through absorption, inhalation or physical contact.

Aligned Standard:

Findings:

Recommendations:

14.06.001: Have you conducted a workplace hazard assessment to determine which jobs and areas in this facility require protective footwear?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(d)(1): The employer shall assess the workplace to determine if hazards are present, or are likely to be present, which necessitate the use of personal protective equipment (PPE). If such hazards are present, the employer must select the types of PPE that will protect the affected employee, communicate selection decisions to each affected employee, and select PPE that properly fits each affected employee.

29 CFR 1910.136(a): The employer shall ensure that each affected employee uses protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, or when the use of protective footwear will protect the affected employee from an electrical hazard, such as a static-discharge or electric-shock hazard, that remains after the employer takes other necessary protective measures.

Aligned Standard:

Findings:

Recommendations:

14.06.002: Are employees wearing protective safety footwear in areas where applicable hazards exist? (e.g., impact, compression, electrical, static, and puncture hazards)

Answer: **Risk:**

Reference Standards:

29 CFR 1910.136(a): General requirements. The employer shall ensure that each affected employee uses protective footwear when working in areas where there is a danger of foot injuries due to falling or rolling objects, or objects piercing the sole, or when the use of protective footwear will protect the affected employee from an electrical hazard, such as a static-discharge or electric-shock hazard, that remains after the employer takes other necessary protective measures.

Aligned Standard:

Findings:

Recommendations:

14.06.003: Do you provide protective footwear to each affected employee through a subsidy, stipend, or other footwear program?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.132(h)(1): Except as provided by paragraphs (h)(2) through (h)(6) of this section, the protective equipment, including personal protective equipment (PPE), used to comply with this part, shall be provided by the employer at no cost to employees.

29 CFR 1910.132(h)(2): The employer is not required to pay for non-specialty safety-toe protective footwear (including steel-toe shoes or steel-toe boots) and non-specialty prescription safety eyewear, provided that the employer permits such items to be worn off the job-site.

Aligned Standard:

Findings:

Recommendations:

Category: 15 - Safety and Health Programs and Recordkeeping

15.01.001: Does your written safety and health program address all of the following: management commitment, employee involvement, worksite analyses, hazard prevention and control, and training?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1200(e)(1): HazCom: Employers shall develop, implement, and maintain at each workplace, a written hazard communication program which at least describes how the criteria specified in paragraphs (f), (g), and (h) of this section for labels and other forms of warning, safety data sheets, and employee information and training will be met, and which also includes the following: A list of the hazardous chemicals known to be present using a product identifier that is referenced on the appropriate safety data sheet (the list may be compiled for the workplace as a whole or for individual work areas) and, The methods the employer will use to inform employees of the hazards of non-routine tasks (for example, the cleaning of reactor vessels), and the hazards associated with chemicals contained in unlabeled pipes in their work areas.

29 CFR 1910.134(c)(1): Respiratory Protection: In any workplace where respirators are necessary to protect the health of the employee or whenever respirators are required by the employer, the employer shall establish and implement a written respiratory protection program with worksite-specific procedures.

29 CFR 1910.1030(c)(1)(i): Bloodborne Pathogens: Each employer having an employee(s) with occupational exposure as defined by paragraph (b) of this section shall establish a written Exposure Control Plan designed to eliminate or minimize employee exposure

29 CFR 1910.38(b): Emergency Action Plans: Written and oral emergency action plans. An emergency action plan must be in writing, kept in the workplace, and available to employees for review. However, an employer with 10 or fewer employees may communicate the plan orally to employees.

29 CFR 1910.39(b): Fire Prevention Plans: Written and oral fire prevention plans. A fire prevention plan must be in writing, be kept in the workplace, and be made available to employees for review. However, an employer with 10 or fewer employees may communicate the plan orally to employees.

29 CFR 1910.146(c)(4): Permit-Required Confined Spaces: If the employer decides that its employees will enter permit spaces, the employer shall develop and implement a written permit space program that complies with this section.

29 CFR 1910.147(c)(4)(i): Lockout/Tagout: Procedures. Procedures shall be developed, documented, and utilized for the control of potentially hazardous energy when employees are engaged in the activities covered by this section.

29 CFR 1910.119(f)(1): Process Safety Management: The employer shall develop and implement written operating procedures that provide clear instructions for safely conducting activities involved in each covered process consistent with the process safety information and shall address at least the following elements.

Aligned Standard:

Findings:

Recommendations:

15.02.001: Does your recordkeeping process ensure all of the following: Obtaining a report on every injury or job-related illness requiring medical treatment Recording each injury or job-related illness on the OSHA Form 300 Preparing a supplementary record for recordable cases on an OSHA Form 301 or other equivalent forms Preparing an annual summary using OSHA Form 300 Posting the OSHA Form 300A from February 1 - May 1 If required, electronically submitting the Form 300A to OSHA Retaining these records for at least five years?

Answer: **Risk:**

Reference Standards:

29 CFR 1904.7(a): Basic requirement. You must consider an injury or illness to be recordable, and therefore enter it on the OSHA 300 Log, if it results in any of the following: death, days away from work, restricted work or transfer to another job, medical treatment beyond first aid, or loss of consciousness.
29 CFR 1904.29(a): Basic requirement. You must use OSHA 300, 300-A, and 301 forms, or equivalent forms, for recordable injuries and illnesses. The OSHA 300 form is called the Log of Work-Related Injuries and Illnesses, the OSHA 300-A is the Summary of Work-Related Injuries and Illnesses, and the OSHA 301 form is the Injury and Illness Incident Report.
29 CFR 1904.32(b)(6): When do I have to post the annual summary? You must post the annual summary no later than February 1 of the year following the year covered by the records and keep the posting in place until April 30.
29 CFR 1904.33(a): Basic requirement. You must save the OSHA 300 Log, the privacy case list (if one exists), the annual summary, and the OSHA 301 Incident Report forms for five (5) years following the end of the calendar year that these records cover.
29 CFR 1904.41(a)(1)(i): If your establishment had 20-249 employees at any time during the previous calendar year, and your establishment is classified in an industry listed in appendix A to subpart E of this part, then you must electronically submit information from OSHA Form 300A Summary of WorkRelated Injuries and Illnesses to OSHA or OSHA's designee. You must submit the information once a year, no later than the date listed in paragraph (c) of this section of the year after the calendar year covered by the form.
29 CFR 1904.41(a)(1)(ii): If your establishment had 250 or more employees at any time during the previous calendar year, and this part requires your establishment to keep records, then you must electronically submit information from OSHA Form 300A Summary of Work-Related Injuries and Illnesses to OSHA or OSHA's designee. You must submit the information once a year, no later than the date listed in paragraph (c) of this section of the year after the calendar year covered by the form.

Aligned Standard:

Findings:

Recommendations:

15.02.002: If required, are records on the exposure of employees to toxic substances and hazardous exposures, physical examination reports, and employment records maintained?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.1020(d)(1): Employee Medical Records: Unless a specific occupational safety and health standard provides a different period of time, each employer shall assure the preservation and retention of records as follows: The medical record for each employee shall be preserved and maintained for at least the duration of employment plus thirty (30) years, except that the following types of records need not be retained for any specified period: (A) Health insurance claims records maintained separately from the employer's medical program and its records, (B) First aid records (not including medical histories) of one-time treatment and subsequent observation of minor scratches, cuts, burns, splinters, and the like which do not involve medical treatment, loss of consciousness, restriction of work or motion, or transfer to another job, if made on-site by a non-physician and if maintained separately from the employer's medical program and its records, and (C) The medical records of employees who have worked for less than (1) year for the employer need not be retained beyond the term of employment if they are provided to the employee upon the termination of employment.
29 CFR 1910.1020(d)(1)(ii): Employee Exposure Records: Each employee exposure record shall be preserved and maintained for at least thirty (30) years, except that: (A) Background data to environmental (workplace) monitoring or measuring, such as laboratory reports and worksheets, need only be retained for one (1) year as long as the sampling results, the collection methodology (sampling plan), a description of the analytical and mathematical methods used, and a summary of other background data relevant to interpretation of the results obtained, are retained for at least thirty (30) years and (B) Safety data sheets and paragraph (c)(5)(iv) records concerning the identity of a substance or agent need not be retained for any specified period as long as some record of the identity (chemical name if known) of the substance or agent, where it was used, and when it was used is retained for at least thirty (30) years and (C) Biological monitoring results designated as exposure records by specific occupational safety and health standards shall be preserved and maintained as required by the specific standard.

Aligned Standard:

Findings:

Recommendations:

Category: 16 - Safety Communication

16.01.001: Are all hazards or dangerous conditions adequately communicated using signs, lights, alarms, or other methods at this facility?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.145(a)(1): These specifications apply to the design, application, and use of signs or symbols (as included in paragraphs (c) through (e) of this section) intended to indicate and, insofar as possible, to define specific hazards of a nature such that failure to designate them may lead to accidental injury to workers or the public, or both, or to property damage.
29 CFR 1910.145(f)(3): Use. Tags shall be used as a means to prevent accidental injury or illness to employees who are exposed to hazardous or potentially hazardous conditions, equipment or operations which are out of the ordinary, unexpected or not readily apparent. Tags shall be used until such time as the identified hazard is eliminated or the hazardous operation is completed.
29 CFR 1910.165(b)(1): The employee alarm system shall provide warning for necessary emergency action as called for in the emergency action plan, or for reaction time for safe escape of employees from the workplace or the immediate work area, or both.
29 CFR 1910.144(a)(1): Red. Red shall be the basic color for the identification of: Fire protection equipment and apparatus.
29 CFR 1910.144(a)(3): Yellow. Yellow shall be the basic color for designating caution and for marking physical hazards such as: Striking against, stumbling, falling, tripping, and "caught in between."

Aligned Standard:

Findings:

Recommendations:

Category: 17 - Security

17.01.001: Are there written security policies for your facility?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as closed-circuit television (CCTV) cameras to monitor high-risk areas, physical access control systems (keycards/badge readers) at employee entrances, and adequate exterior lighting in parking lots and walkways; reduce security risks by developing and implementing a written workplace security policy that outlines "Zero Tolerance" for violence and procedures for unauthorized visitors; provide employees with clear communication channels for reporting security concerns without fear of reprisal; and train employees on the specific facility security policies, how to recognize behavioral indicators of potential violence, and the emergency response procedures for security breaches or active threats.

Aligned Standard:

Findings:

Recommendations:

17.01.002: Are adequate security measures in place to address potential issues?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as closed-circuit television (CCTV) cameras to monitor high-risk areas, physical access control systems (keycards/badge readers) at employee entrances, and adequate exterior lighting in parking lots and walkways; reduce security risks by developing and implementing a written workplace security policy that outlines "Zero Tolerance" for violence and procedures for unauthorized visitors; provide employees with clear communication channels for reporting security concerns without fear of reprisal; and train employees on the specific facility security policies, how to recognize behavioral indicators of potential violence, and the emergency response procedures for security breaches or active threats.

Aligned Standard:

Findings:

Recommendations:

17.02.001: Is there adequate illumination in all areas of the building and exterior grounds?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.37(b)(1): Each exit route must be adequately lighted so that an employee with normal vision can see along the exit route.
29 CFR 1910.305(a)(2)(ix): All lamps for general illumination shall be protected from accidental contact or breakage by a suitable fixture or lampholder with a guard. Brass shell, paper-lined sockets, or other metal-cased sockets may not be used unless the shell is grounded.

Aligned Standard:

Findings:

Recommendations:

17.02.002: Have adequate measures been taken, such as installing security cameras, to deter theft and/or monitor activities?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as closed-circuit television (CCTV) cameras to monitor high-risk areas, physical access control systems (keycards/badge readers) at employee entrances, and adequate exterior lighting in parking lots and walkways; reduce security risks by developing and implementing a written workplace security policy that outlines "Zero Tolerance" for violence and procedures for unauthorized visitors; provide employees with clear communication channels for reporting security concerns without fear of reprisal; and train employees on the specific facility security policies, how to recognize behavioral indicators of potential violence, and the emergency response procedures for security breaches or active threats.

Aligned Standard:

Findings:

Recommendations:

17.03.001: Is there adequate signage to communicate security policies to employees and visitors throughout the facility?

Answer: **Risk:**

Reference Standards:

Section 5(a)(1) of the Occupational Safety and Health Act of 1970: Each employer shall furnish to each of his employees employment and a place of employment which are free from recognized hazards that are causing or are likely to cause death or serious physical harm to his employees. Employers should, therefore: Implement engineering controls, such as closed-circuit television (CCTV) cameras to monitor high-risk areas, physical access control systems (keycards/badge readers) at employee entrances, and adequate exterior lighting in parking lots and walkways; reduce security risks by developing and implementing a written workplace security policy that outlines "Zero Tolerance" for violence and procedures for unauthorized visitors; provide employees with clear communication channels for reporting security concerns without fear of reprisal; and train employees on the specific facility security policies, how to recognize behavioral indicators of potential violence, and the emergency response procedures for security breaches or active threats.

Aligned Standard:

Findings:

Recommendations:

Category: 18 - Slips, Trips, and Falls

18.01.001: Do you have practices, products, or procedures in place to minimize slips, trips, and falls?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.22(a)(1): All places of employment, passageways, storerooms, service rooms, and walking-working surfaces are kept in a clean, orderly, and sanitary condition.
29 CFR 1910.22(a)(2): The floor of each workroom is maintained in a clean and, so far as possible, a dry condition. When wet processes are used, drainage must be maintained and, to the extent feasible, dry standing places, such as false floors, platforms, and mats must be provided.
29 CFR 1910.22(a)(3): Walking-working surfaces are maintained free of hazards such as sharp or protruding objects, loose boards, corrosion, leaks, spills, snow, and ice.

Aligned Standard:

Findings:

Recommendations:

18.02.001: When working at elevated heights, is fall protection equipment being used?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.28(b)(1)(i): Unprotected sides and edges. (i) Except as provided elsewhere in this section, the employer must ensure that each employee on a walking-working surface with an unprotected side or edge that is 4 feet (1.2 m) or more above a lower level is protected from falling by one or more of the following: (A) Guardrail systems (B) Safety net systems or (C) Personal fall protection systems, such as personal fall arrest, travel restraint, or positioning systems.

Aligned Standard:

Findings:

Recommendations:

18.03.001: Are all employees who use personal fall protection systems... trained on fall and equipment hazards?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.30(a)(1): Fall hazards. Before any employee is exposed to a fall hazard, the employer must provide training for each employee who uses personal fall protection systems or who is required to be trained as specified elsewhere in this subpart. Employers must ensure employees are trained in the requirements of this paragraph on or before May 17, 2017.

29 CFR 1910.30(a)(2): The employer must ensure that each employee is trained by a qualified person.

Aligned Standard:

Findings:

Recommendations:

18.04.001: Do you have a process for inspecting portable ladders?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.23(b)(9): Ladders are inspected before initial use in each work shift, and more frequently as necessary, to identify any visible defects that could cause employee injury.

Aligned Standard:

Findings:

Recommendations:

18.04.002: Do your fixed ladders meet the requirements of the latest walking working surfaces standard (i.e., self-closing safety gates, ladder safety systems as required)?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.29(b)(13): When guardrail systems are used around holes which are used as points of access (such as ladderways), they shall be provided with a self-closing gate that slides or swings away from the hole, and is equipped with a top rail and midrail or equivalent intermediate member that meets the requirements in paragraph (b) of this section, or is offset so that a person cannot walk directly into the hole.

29 CFR 1910.28(b)(9)(i): For fixed ladders that extend more than 24 feet (7.3 m) above a lower level, the employer must ensure: (A) Existing fixed ladders. Each fixed ladder installed before November 19, 2018 is equipped with a personal fall arrest system, ladder safety system, cage, or well (B) New fixed ladders. Each fixed ladder installed on and after November 19, 2018, is equipped with a personal fall arrest system or a ladder safety system (C) Replacement. When a fixed ladder, cage, or well, or any portion of a section thereof, is replaced, a personal fall arrest system or ladder safety system is installed in at least that section of the fixed ladder, cage, or well where the replacement is located and (D) Final deadline. On and after November 18, 2036, all fixed ladders are equipped with a personal fall arrest system or a ladder safety system.

Aligned Standard:

Findings:

Recommendations:

18.05.001: Are all walking and working surfaces inspected regularly and maintained in a safe condition?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.22(d)(1): Inspection, maintenance, and repair. The employer must ensure: (i) Walking-working surfaces are inspected, regularly and as necessary, and maintained in a safe condition (ii) Hazardous conditions on walking-working surfaces are corrected or repaired before an employee uses the walking-working surface again.

Aligned Standard:

Findings:

Recommendations:

18.06.001: Are employees adequately protected from exposure to falling objects?

Answer: **Risk:**

Reference Standards:

29 CFR 1910.28(c)(1): Protection from falling objects. When an employee is exposed to falling objects, the employer must ensure that each employee wears head protection that meets the requirements of subpart I of this part. In addition, the employer must protect employees from falling objects by implementing one or more of the following: (1) Erecting toeboards, screens, or guardrail systems to prevent objects from falling to a lower level (2) Erecting canopy structures and keeping potential falling objects far enough from an edge, hole, or opening to prevent them from falling to a lower level or (3) Barricading the area into which objects could fall, prohibiting employees from entering the barricaded area, and keeping objects far enough from an edge or opening to prevent them from falling to a lower level.

Aligned Standard:

Findings:

Recommendations: