

Frontend API Change Guide

Receptionist / Nurse / Doctor Bug Fixes

Date: 13 July 2026 | Audience: Frontend developers | Purpose: Exact UI/API changes after backend fixes REC-1, REC-2, REC-3, NURSE-1, DOC-1.

This document tells you WHAT changed, WHICH endpoints to call, request/response shapes, and WHAT to stop doing in the UI.

1. Change Overview

Ticket	Module	Frontend impact
REC-1	Receptionist	Dashboard counts are now accurate
REC-2	Receptionist	Queue has no duplicate patients; pagination fixe
REC-3	Receptionist	Queue returns scheduled_at - show time, not dash
NURSE-1	Nurse	IPD vitals/notes via patient_id (no OPD appointm
DOC-1	Doctor	One Save API completes consult + optional Rx ato

Auth note

All endpoints still require Bearer JWT. Permissions unchanged unless noted.

2. Receptionist Module

2.1 REC-1 - Dashboard counts

Endpoint (unchanged): GET /receptionist/dashboard

Optional query: doctor_id

Backend now counts DISTINCT appointments. Do not invent client-side totals from joined/queue lists. Trust data.total_patients, data.completed, data.todays_paid_appointments, data.todays_unpaid_appointments, data.todays_cancelled.

```
{
  "success": true,
  "data": {
    "total_patients": 47,
    "completed": 12,
    "todays_paid_appointments": 30,
    "todays_unpaid_appointments": 17,
    "todays_cancelled": 2
  }
}
```

- UI: bind dashboard cards directly to these fields.
- UI: expected Scheduled/Total card uses total_patients (now correct).

2.2 REC-2 - Queue duplicates and pagination

Endpoints (unchanged paths):

- GET /receptionist/today-queue
- GET /receptionist/doctor-queue/{doctor_id}
- GET /receptionist/queue-history

Backend guarantees one queue row per selected appointment. On same-day boards (today-queue / doctor-queue), if

the same patient has multiple appointments, backend keeps ONE canonical appointment using this priority:

- 1. Paid appointment
- 2. Linked visit exists
- 3. Latest scheduled_at
- 4. Highest appointment id

total / page / limit now match unique rows after dedupe. Use server pagination; do not re-count duplicates on the client.

Frontend action

Remove any client-side unique-by-patient hacks. Rely on API total for pager labels (e.g. Showing 1-20 of {total}).

2.3 REC-3 - scheduled_at on queue items

Every queue item now includes scheduled_at (ISO datetime with timezone). Previously UI showed '-' because the field was missing.

```
{
  "appointment_id": 42,
  "appointment_uid": "AP-0042",
  "patient_id": 10,
  "patient_name": "Nilesh Patil",
  "patient_uid": "P-1001",
  "patient_phone": "98XXXXXXX",
  "doctor_id": 5,
  "doctor_name": "Dr. Sharma",
  "status": "scheduled",
  "payment_status": "paid",
  "scheduled_at": "2026-07-13T13:00:00+05:30",
  "checked_in_at": null,
  "called_at": null,
  "consultation_started_at": null,
  "consultation_completed_at": null,
  "queue_date": "2026-07-13"
}
```

- Display: format scheduled_at in Asia/Kolkata, e.g. 1:00 PM.
- Fallback only if scheduled_at is null (should be rare).
- Applies to today-queue, doctor-queue, and queue-history rows.

2.4 Receptionist TypeScript types (suggested)

```
type ReceptionistQueueItem = {
  appointment_id: number;
  appointment_uid?: string | null;
  patient_id: number;
  patient_name: string;
  patient_uid: string;
  patient_phone?: string | null;
  doctor_id: number;
  doctor_name?: string | null;
  status: "scheduled" | "completed";
  payment_status?: string | null;
  scheduled_at?: string | null; // NEW - ISO string
  checked_in_at?: string | null;
  called_at?: string | null;
  consultation_started_at?: string | null;
  consultation_completed_at?: string | null;
  queue_date?: string | null;
};
```

3. Nurse Module (NURSE-1)

3.1 Problem solved

IPD patients on occupied beds often have no OPD appointment. Vitals and nursing notes no longer require appointment_id only.

3.2 Create vitals

Endpoint: POST /nurse/vitals

Send EITHER appointment_id (OPD) OR patient_id (IPD occupied bed).

```
// OPD (existing)
POST /nurse/vitals
{ "appointment_id": 42, "temperature": 98.6, "heart_rate": 78 }

// IPD (NEW)
POST /nurse/vitals
{ "patient_id": 10, "temperature": 98.6, "heart_rate": 78, "mark_critical": false }
```

Rules:

- At least one of appointment_id or patient_id is required.
- patient_id alone is allowed only if patient currently occupies a bed.
- If both are sent, patient_id must match the appointment patient.
- Response appointment_id may be null for pure IPD records.

3.3 Create nursing notes

Endpoint: POST /nurse/notes

```
// OPD
{ "appointment_id": 42, "symptoms": "...", "additional_notes": "..." }

// IPD (NEW)
{ "patient_id": 10, "symptoms": "...", "treatment_response": "...", "additional_notes": "..." }
```

3.4 Response shape changes

```
{
  "id": 101,
  "appointment_id": null,    // can be null for IPD
  "patient_id": 10,
  "patient_uid": "P-1001",
  "patient_name": "Nilesh Patil",
  "bed_number": "B-12",
  "recorded_by": 8,
  "temperature": 98.6,
  "heart_rate": 78,
  "status": "recorded",
  "recorded_at": "2026-07-13T14:10:00+05:30"
}
```

Frontend action - IPD screens

On bed/IPD patient detail, call create vitals/notes with patient_id from the bed record. Do not block the form waiting for an OPD appointment_id.

Frontend action - OPD screens

Keep using appointment_id as before. No breaking change if you already send it.

Errors to handle in UI:

- 400: Provide appointment_id or patient_id
- 400: patient_id only allowed for occupied-bed patients
- 400: Vitals already recorded for this appointment / today for IPD
- 404: Appointment not found / Patient not found

3.5 Suggested TypeScript

```
type VitalCreatePayload = {
  appointment_id?: number;
  patient_id?: number;
  temperature?: number;
  blood_pressure?: string;
  heart_rate?: number;
  respiratory_rate?: number;
  oxygen_saturation?: number;
  blood_sugar?: number;
  weight?: number;
  pain_level?: number;
  observation_notes?: string;
  mark_critical?: boolean;
};

type VitalResponse = {
  id: number;
  appointment_id?: number | null;
  patient_id: number;
  patient_uid?: string | null;
  patient_name?: string | null;
  bed_number?: string | null;
  recorded_by: number;
  // ...vital fields
  status?: string | null;
  recorded_at: string;
};
```

4. Doctor Module (DOC-1)

4.1 Problem solved

Doctors no longer need a multi-step UI flow Scheduled -> Waiting -> In Progress -> Completed with separate prescription create. Partial failures left inconsistent data. Use ONE atomic save.

4.2 Preferred endpoint

POST /consultations/save

Also available: PUT /queue/complete (same SaveConsultationRequest body).

In one DB transaction the backend: ensures queue row, saves clinical fields (symptoms/diagnosis/notes/follow_up_date), optionally creates prescription + items, marks appointment completed, marks queue completed.

4.3 Request body

```
POST /consultations/save
{
  "appointment_id": 42,
  "clinical": {
    "symptoms": "Fever, cough",
    "diagnosis": "Viral fever",
    "notes": "Advise rest and fluids",
    "follow_up_date": "2026-07-20"
  },
  "prescription": {
    "diagnosis": "Viral fever",
    "notes": "After food",
    "items": [
      {
        "medicine_name": "Paracetamol",
        "dosage": "500mg",
        "frequency": "TDS",
        "duration": 3,
        "instructions": "After food"
      }
    ]
  }
}
```

- prescription is OPTIONAL. Omit it if only clinical completion is needed.
- If prescription is sent, diagnosis and non-empty items are required.
- clinical fields are all optional individually, but send what the form collected.

4.4 Success response

```
{
  "success": true,
  "message": "Consultation saved",
  "appointment": { "id": 42, "status": "completed", "...": "..." },
  "queue": { "id": 16, "status": "completed", "appointment_id": 42, "token_number": 7 },
  "prescription": {
    "id": 55,
    "appointment_id": 42,
    "patient_id": 10,
```

```
"diagnosis": "Viral fever",
"status": "pending",
"items": [ { "medicine_name": "Paracetamol", "...": "..." } ]
}
}
```

prescription in response is null when not provided in the request.

4.5 What frontend should STOP doing

- Do NOT manually patch appointment status scheduled -> waiting -> in_progress -> completed.
- Do NOT call create-prescription only after a separate complete call (race/partial failure).
- Do NOT keep local multi-step wizards that require intermediate status success.

Recommended UX: one Save / Complete Consultation button that posts clinical + Rx together.

4.6 Optional still-valid endpoints

- GET /consultations/appointment/{id} - read-only context (appointment, queue, past Rx, labs).
- PATCH /consultations/appointment/{id} - clinical complete without creating prescription.
- Legacy queue start/complete-by-queue-id may exist; prefer POST /consultations/save for finish.

4.7 Errors to handle

- 404 Appointment not found
- 400 Consultation already completed
- 400 Cannot save consultation for cancelled appointment
- 400 prescription.diagnosis required / items must not be empty
- 400 Prescription already exists for this appointment
- 409 Patient already has a queue entry with this doctor today (rare edge)

4.8 Suggested TypeScript

```
type SaveConsultationRequest = {
  appointment_id: number;
  clinical?: {
    symptoms?: string;
    diagnosis?: string;
    notes?: string;
    follow_up_date?: string; // YYYY-MM-DD
  };
  prescription?: {
    diagnosis: string;
    notes?: string;
    items: Array<{
      medicine_name: string;
      dosage: string;
      frequency: string;
      duration: number;
      instructions?: string;
    }>;
  };
};

type SaveConsultationResponse = {
  success: boolean;
  message: string;
  appointment: Record<string, unknown>;
};
```

SaffoCare HMS - Frontend API Changes (Receptionist / Nurse / Doctor)

```
queue: { id: number; status: string; appointment_id: number; token_number?: number };  
prescription?: Record<string, unknown> | null;  
};
```

5. Frontend Implementation Checklist

Receptionist

- [] Dashboard cards use GET /receptionist/dashboard fields only
- [] Queue time column binds to scheduled_at (format local IST)
- [] Pager uses response.total after dedupe (no client unique hacks)
- [] Update QueueItem TypeScript to include scheduled_at

Nurse

- [] IPD bed patient vitals form sends patient_id
- [] IPD nursing notes form sends patient_id
- [] OPD forms continue sending appointment_id
- [] Handle nullable appointment_id in list/detail UI
- [] Show friendly error if patient is not on an occupied bed

Doctor

- [] Replace multi-step complete flow with POST /consultations/save
- [] Include prescription payload in same save when Rx is written
- [] On success, refresh appointment + queue from response (status=completed)
- [] Remove dependency on intermediate waiting/in_progress UI steps for finish

6. Quick Endpoint Map

Method	Path	Change
GET	/receptionist/dashboard	Accurate distinct counts
GET	/receptionist/today-queue	Dedupe + scheduled_at
GET	/receptionist/doctor-queue/{id}	Dedupe + scheduled_at
GET	/receptionist/queue-history	Dedupe + scheduled_at
POST	/nurse/vitals	patient_id OR appointment_id
POST	/nurse/notes	patient_id OR appointment_id
POST	/consultations/save	Atomic clinical + Rx + complete
PUT	/queue/complete	Same save body as above

7. Notes for QA

- Receptionist: create multi-visit/queue join cases; dashboard must not inflate.
- Receptionist: same patient two appointments same day -> one canonical row on today-queue.
- Receptionist: time column shows 1:00 PM style from scheduled_at.
- Nurse IPD: occupied bed patient can save vitals with only patient_id.
- Nurse OPD: appointment_id path unchanged.
- Doctor: one Save completes consult; if Rx included, prescription row exists immediately.
- Doctor: second save on completed appointment returns 400.

Generated for SaffoCare HMS frontend team. Backend source of truth: Services/receptionist_service.py, Schemas/receptionist_schema.py, Schemas/nurse_schema.py, nurse vitals/notes services, Schemas/doctor_consultation_schema.py, Services/doctor_consultation_service.py.