

Doctor Module

OPD / IPD Tabs + Patient History

Frontend Implementation Guide

Audience: Doctor frontend developers | Scope: Doctor UI only | Date: August 2026 | Backend for this work is already shipped

1. Purpose

This document tells frontend what to build after the doctor-module backend update. Doctors must see OPD and IPD separately, with filters and pagination on IPD, and discharged IPD patients in patient history.

IMPORTANT: Do not use GET /ipd/admissions for the doctor screen. That IPD-desk API requires ipd:patients:list, which the doctor role does not have. Use GET /doctor/ipd-admissions (appointments:view).

IMPORTANT: Do not drive the IPD tab from GET /appointments/today. That list has no IPD pagination, no IPD date filter, and no discharged list. Today-list IPD rows also send status=scheduled, which is wrong for Admit/Discharge UI.

2. What Product UI Must Look Like

Doctor Dashboard

- Add two buttons / tabs: OPD | IPD.
- OPD tab: today's OPD appointments only (existing Consult / Cancel / Pending-payment behaviour).
- IPD tab: this doctor's admissions. Columns: Patient name, Patient ID (UHID), Date (admit date), Status (Admit / Discharge).
- IPD filters: search (name / UHID / phone / admission no), date range, status Admit or Discharge. Pagination: page + page_size.
- IPD sort is done by backend (newest admission first). Do not re-sort oldest first.
- Admit list stays until discharge. After discharge the row leaves Admit and appears under Discharge and in Patients history.

Patients / EMR history

- Same search, date (filter_date / month / year), and page / page_size as today.
- List now mixes completed OPD visits + discharged IPD stays (default).
- Show an OPD / IPD badge per row using encounter_type.
- Do not open Consult using an IPD row id.

3. Which API For Which Screen

Screen	Call this API	Do not use
Dashboard OPD tab	GET /appointments/today (existing)	IPD desk /ipd/*
Dashboard IPD tab	GET /doctor/ipd-admissions	GET /appointments/today
Patients list / EMR	GET /patients (+ encounter_type)	GET /ipd/admissions
One patient history	GET /patients/{patient_uid}	Appointment id APIs for IPD

Auth: same doctor JWT. IPD list permission = appointments:view. History permission = patients:view. Do not send doctor_id; backend uses the token.

4. NEW API - GET /doctor/ipd-admissions

This is the IPD tab API. Logged-in doctor only. Newest admitted_at first. Default status is admitted (Admit list).

4.1 Query params

Param	Default	Notes
status	admitted	admitted discharged cancelled all
		Aliases: admit, discharge
from_date	none	YYYY-MM-DD, filters admitted_at
to_date	none	YYYY-MM-DD, filters admitted_at
search	none	name, UHID, phone, admission_no
page	1	1-based
page_size	20	max 100

Examples:

```
GET /doctor/ipd-admissions?status=admitted&page=1&page_size=20
GET /doctor/ipd-admissions?status=admit&page=1
GET /doctor/ipd-admissions?status=discharged&from_date=2026-08-01&to_date=2026-08-17
GET /doctor/ipd-admissions?search=amresh&status=admitted&page=2&page_size=20
```

4.2 Response

```
{
  "success": true,
  "total": 41,
  "page": 1,
  "page_size": 20,
  "items": [ { ...IPD row... } ]
}
```

4.3 IPD row fields (map these)

```
{
  "id": "IPD-1005",
  "appointment_uid": "IPD-1005",
  "patient_id": 205,
  "patient_uid": "P-1205",
  "patient_name": "Amresh",
  "patient_phone": "98xxxxxxxx",
  "patient_age": "32y",
  "patient_gender": "Male",
  "registration_source": "IPD",
  "encounter_type": "IPD",
  "appointment_type": "ipd",
  "admission_id": 5,
  "bed_number": "B-12",
  "ward_name": "General",
  "status": "admitted",
  "scheduled_at": "<admitted_at ISO>",
  "appointment_date": "2026-08-17",
  "appointment_time": "10:15:00",
  "admitted_at": "2026-08-17T10:15:00+05:30",
  "discharged_at": null,
  "diagnosis": "...",
  "notes": "...",
  "doctor_id": 12,
  "department_id": 3
}
```

```
}
```

- id and appointment_uid are STRINGS (admission_no). Not a numeric appointment PK.
- admission_id is the numeric IPD admission PK if you need it later.
- status is real: admitted | discharged | cancelled. Display Admit / Discharge.
- Date column: admitted_at (or appointment_date). After discharge, discharged_at is set.
- If IPD admit left Doctor empty, doctor_id is null and the row never appears here.

4.4 Status mapping for UI

API status	IPD tab label	Query to send
admitted	Admit	status=admitted (or admit)
discharged	Discharge	status=discharged (or discharge)
cancelled	Cancelled	status=cancelled (optional)

Extend apiStatusToUiStatus: admitted -> Admit, discharged -> Discharge. Do not map admitted to Scheduled on the IPD tab.

5. Dashboard OPD Tab - GET /appointments/today

Keep using this for the OPD tab only. Permission: appointments:view. Top-level shape is unchanged.

```
{
  "success": true,
  "message": "Today's appointments fetched successfully",
  "appointment": <count>,
  "appointments": [ ... ]
}
```

- OPD rows: encounter_type=OPD, numeric id, normal appointment status.
- Backend may still append admitted IPD rows on this list (bonus / badge). Those IPD rows use status=scheduled on purpose so old Scheduled filter does not drop them. That is NOT the IPD tab contract.
- OPD tab should show only encounter_type === 'OPD' (or appointment_type !== 'ipd').
- Keep the existing unpaid-OPD Pending filter on the OPD tab. Never run that filter on IPD tab rows.
- If the same patient has OPD today + IPD admit, today-list skips the IPD duplicate. The IPD tab still shows them via /doctor/ipd-admissions.

5.1 OPD row vs leftover today-list IPD row

```
OPD (use on OPD tab):
  id: 42                // numeric appointment PK
  encounter_type: "OPD"
  status: "scheduled" | "completed" | "cancelled"
  admission_id: null

Today-list IPD leftover (ignore on IPD tab):
  id: "IPD-1005"        // STRING
  encounter_type: "IPD"
  status: "scheduled"   // dashboard-only, not Admit
  admission_id: 5
```

6. Patients History - GET /patients

Same filters and pagination as before, plus encounter_type. Default encounter_type=all mixes completed OPD + discharged IPD.

6.1 Query params (unchanged + one new)

Param	Used for	Notes
search	name / UHID / phone	same as OPD history
filter_date	one day	OPD: scheduled_at; IPD: admitted_at
month + year	calendar filter	month is 1-12
year	year only	same as today
page / page_size	pagination	default 20, max 100
encounter_type	NEW	opd ipd all (default all)

```
GET /patients?page=1&page_size=20
GET /patients?encounter_type=all&search=amresh&page=1
GET /patients?encounter_type=opd&filter_date=2026-08-17
GET /patients?encounter_type=ipd&month=8&year=2026
GET /patients/P-1205?encounter_type=all&page=1&page_size=20
```

If a screen must stay OPD-only (old behaviour), send encounter_type=opd. Patients EMR should send all (or omit it) so discharged IPD appears.

6.2 History row

- OPD: id is numeric appointment PK, status=completed, encounter_type=OPD.
- IPD: id is STRING admission_no, status=discharged, encounter_type=IPD, admission_id set, admitted_at / discharged_at set.
- department_id may be null on IPD. Treat it as optional.
- appointmentDbId / Consult must use numeric appointment id only. If encounter_type is IPD, appointmentDbId must be null.

6.3 Current frontend gap

- features/doctor/api/patients.js does not send encounter_type yet. Add it.
- getPatientHistory() currently has no query string. Pass page, page_size, encounter_type when opening one patient.
- doctorPatientMapper.apiToUiPatientVisitRow uses api.id as appointmentDbId. That will treat IPD-1005 as an appointment id. Guard it.

7. registration_source vs encounter_type

- registration_source (OPD | IPD): which desk first created the UHID. Permanent.
- encounter_type (OPD | IPD): this row's visit type. Use this for badges.

Example: UHID created in OPD, later admitted to this doctor. registration_source stays OPD. IPD tab / history IPD row has encounter_type IPD.

8. Frontend Work - What To Change

IMPORTANT: IPD tab will stay empty until you call GET /doctor/ipd-admissions and skip the OPD Pending payment filter on those rows.

8.1 MUST - New IPD API client + query

```
- NEW file: src/features/doctor/api/ipd.js

// GET /doctor/ipd-admissions
export async function getDoctorIpAdmissions(token, params = {}) {
  const qs = new URLSearchParams();
  if (params.page != null) qs.set('page', String(params.page));
  if (params.page_size != null) qs.set('page_size', String(params.page_size));
  if (params.status) qs.set('status', params.status);
```

```
if (params.from_date) qs.set('from_date', params.from_date);
if (params.to_date) qs.set('to_date', params.to_date);
if (params.search?.trim()) qs.set('search', params.search.trim());
const q = qs.toString();
return apiClient(q ? `/doctor/ipd-admissions?${q}` : '/doctor/ipd-admissions', { token });
}
```

- NEW hook: src/features/doctor/hooks/useDoctorIpdQuery.js
- queryKeys.js: add doctor.ipd.admissions(filters) e.g. ['doctor', 'ipd', 'admissions', filters]
- Do not reuse queryKeys.ipd.* (those are the IPD desk module).
- Invalidate doctor IPD keys after discharge if the doctor UI can refresh it.

8.2 MUST - Dashboard OPD | IPD tabs

Files: DashboardSection.jsx, DashboardAppointmentsTable.jsx, DashboardFilterBar.jsx

- Add OPD | IPD toggle. Default OPD so current OPD flow stays.
- OPD: keep useDoctorDashboardTodayAppointmentsQuery. Filter out IPD rows.
- IPD: new query. Table columns Patient ID, Patient Name, Date, Status. No Consult / Cancel columns (or disable them).
- IPD status filter: Admit (status=admitted) vs Discharge (status=discharged). Do not reuse Scheduled / Completed / Cancelled OPD chips for IPD.
- IPD search + date: send search / from_date / to_date to the API (not client-only).
- IPD pagination: use response.total, page, page_size. Do not slice locally.
- Optional: show ward_name / bed_number under the name.

8.3 MUST - Do not treat IPD as unpaid OPD

Files: features/doctor/utills/doctorAppointmentPayment.js (enrichDoctorAppointmentsWithOpdPayment) and appointmentMapper.js

Today OPD tab still drops unpaid scheduled OPD (displayStatus Pending). If an IPD row is ever mapped through that helper, it has no OPD bill and is dropped.

```
const isIpd =
  appt.encounterType === 'IPD' ||
  appt.encounter_type === 'IPD' ||
  appt.type === 'ipd';

if (isIpd) {
  // keep the row; do not set Pending; do not filter out
}
```

- IPD tab must never call enrichDoctorAppointmentsWithOpdPayment.

8.4 MUST - Map new fields

File: shared/api/mappers/appointmentMapper.js (apiToUiAppointment)

- encounterType from encounter_type (default OPD).
- registrationSource from registration_source.
- admissionId, bedNumber, wardName, admittedAt, dischargedAt.
- Keep string id => dbId null for IPD (resolveAppointmentIds).
- Status map: admitted -> Admit, discharged -> Discharge.

File: shared/api/mappers/doctorPatientMapper.js

- Map encounterType, registrationSource, admissionId, admittedAt, dischargedAt.
- appointmentDbId: only if encounter_type is OPD and id is numeric. Never Number('IPD-1005').

- Status: keep discharged as Discharge, not Completed.

8.5 MUST - Guard Consult / Cancel / GET appointment by id

Files: AppointmentRowActions.jsx, DashboardSection.jsx, features/doctor/api/appointments.js

- If encounterType === IPD or dbld == null: hide/disable Consult and Cancel.
- Never call GET /appointments/{id} or PUT /appointments/{id}/status with IPD-1005.
- Patient profile by patientUid / patientDbld still works without appointment id.

8.6 MUST - Patients EMR / history

Files: features/doctor/api/patients.js, hooks/useDoctorPatientQuery.js, PatientsEMRSection.jsx, PatientHistoryProfile.jsx, patientDateFilters.js

- Pass encounter_type=all on the EMR list (or omit; backend default is all).
- Keep sending search, filter_date, month, year, page, page_size as today.
- Optional OPD/IPD filter in EMR: pass encounter_type=opd|ipd|all.
- Show Type badge from encounterType. Date from scheduled_at / admitted_at.
- Opening a history IPD row must not start an OPD consultation.

9. Frontend Files Checklist

Create

- src/features/doctor/api/ipd.js
- src/features/doctor/hooks/useDoctorIpQuery.js
- Optional: src/features/doctor/components/DoctorIpPatientsTable.jsx

Must change

- src/shared/api/queryKeys.js
- src/shared/api/mappers/appointmentMapper.js
- src/shared/api/mappers/doctorPatientMapper.js
- src/features/doctor/Utils/doctorAppointmentPayment.js
- src/features/doctor/components/DashboardSection.jsx
- src/features/doctor/components/DashboardAppointmentsTable.jsx
- src/features/doctor/components/DashboardFilterBar.jsx
- src/features/doctor/components/AppointmentRowActions.jsx
- src/features/doctor/api/patients.js
- src/features/doctor/hooks/useDoctorPatientQuery.js
- src/features/doctor/components/PatientsEMRSection.jsx
- src/features/doctor/components/PatientHistoryProfile.jsx

Should change

- src/features/doctor/Utils/doctorDashboardSelectors.js
- src/features/doctor/Utils/patientDateFilters.js
- src/features/doctor/Utils/patientListFilters.js
- src/features/doctor/components/StatusPill.jsx (Admit / Discharge colours)
- src/shared/api/services/doctorAppointments.js (skip IPD in OPD today map if mixed)
- src/shared/api/services/doctorPatients.js

Do not change for this

- IPD desk frontend (features/ipd/*) and GET /ipd/admissions.
- Nurse, lab, pharmacy, receptionist.
- OPD consult / queue / prescribe flows for real OPD appointments.

10. Suggested Frontend Data Flow

Dashboard

```
[OPD] -> GET /appointments/today
      -> map appointments
      -> drop encounter_type IPD
      -> existing OPD payment Pending filter
      -> Consult / Cancel allowed if dbId is number

[IPD] -> GET /doctor/ipd-admissions?status=&from_date=&to_date=&search=&page=
      -> map items (do NOT run OPD payment filter)
      -> table: name | UHID | date | Admit/Discharge
      -> paginate from total / page / page_size
      -> no Consult / Cancel
```

Patients EMR

```
GET /patients?search=&filter_date=&month=&year=&page=&encounter_type=all
GET /patients/{uid}?encounter_type=all&page=
  -> badge OPD / IPD from encounter_type
  -> IPD rows are discharged stays only
```

11. Doctor notification on IPD admit (backend live)

When IPD desk admits a patient with Doctor selected, that doctor gets an in-app inbox row on the existing GET /doctor/notifications API. Unread count includes it. No new notification endpoint.

- Type: IPD_ADMITTED | source_module: IPD | priority: HIGH
- reference_type: ADMISSION | reference_id: numeric admission_id
- Title: IPD Patient Admitted
- Also sent if an already-admitted stay is later assigned/reassigned to this doctor.
- Not sent if Doctor is empty on admit. Not sent on discharge.

Existing doctor inbox already renders unknown types with the Bell fallback, so the row appears without a frontend code change. Optional later: add an IPD_ADMITTED filter chip and deep-link the click to the IPD tab.

```
{
  "notification_type": "IPD_ADMITTED",
  "source_module": "IPD",
  "reference_type": "ADMISSION",
  "reference_id": 5,
  "priority": "HIGH",
  "title": "IPD Patient Admitted",
  "message": "IPD patient admitted under you.\nPatient: Amresh (P-1205)\nAdmission: IPD-1005\nWard: General Bed: B-12"
}
```

12. How An IPD Patient Reaches The Doctor

```
IPD Register (UHID)    -> registration_source = IPD
    |
IPD Admit (bed + doctor) -> ipd_admissions.doctor_id = that doctor
    |                      status = admitted
    v
```

```
GET /doctor/ipd-admissions?status=admitted
GET /doctor/notifications (IPD_ADMITTED)
    |
    | -> IPD tab Admit list (until discharge)
    | -> doctor inbox bell / unread count
    v
IPD Discharge -> status = discharged
    |
GET /doctor/ipd-admissions?status=discharged
GET /patients (encounter_type=all or ipd)
    |
    | -> Discharge list + Patients history
```

- Doctor on IPD admit is optional. Empty doctor => row never appears for anyone, and no notification.
- User must open the dashboard of the SAME doctor selected at admit.

13. QA Checklist

- OPD tab: paid today patients still show; unpaid OPD still hidden.
- OPD tab: Consult / Cancel still work on numeric appointment ids.
- IPD tab Admit: Amresh admitted to Dr X appears on Dr X, newest first.
- IPD tab still shows Amresh the next day if still admitted (not today-only).
- IPD search by name / UHID hits the API and paginates (total matches pages).
- IPD date from/to filters by admit date.
- After discharge: leaves Admit, appears under Discharge + Patients history.
- History search / month / year / page still work; IPD rows have Type IPD.
- IPD row never calls /appointments/{id} (422/404 would mean a frontend bug).
- IPD admit with no doctor: does not appear (expected).
- Doctor JWT only; 403 if a non-doctor calls the IPD doctor API.
- IPD admit with Doctor = Dr X: Dr X GET /doctor/notifications shows IPD Patient Admitted; unread-count +1.
- IPD admit with no doctor: no notification for any doctor.
- Later assign Doctor on the admission: that doctor then gets IPD_ADMITTED.

14. Out of Scope

- Lab technician module.
- Nurse module.
- IPD consult / prescribe / lab order from an IPD encounter (no API yet).
- Changing IPD desk admit/discharge screens.

End of document. Build IPD tab on GET /doctor/ipd-admissions first, then map history encounter_type so discharged IPD shows in Patients EMR.