

Lab Orders: OPD / IPD, Ward and Bed

Frontend Developer Guide

Date: 17 August 2026 | Audience: Frontend (Lab module) | Scope: Show visit type, ward and bed on lab ordered tests.

IMPORTANT

Backend for these fields is ALREADY DONE. Do not change backend files. Lab screens still hide the data because the mapper and UI were not updated. This PDF is frontend-only work.

1. Status of the original gaps

Earlier, none of this was visible in lab. Backend now returns the visit fields. Frontend still does not map or display them.

Requirement	Backend	Frontend / Lab UI
Lab sees OPD or IPD on ordered test	DONE	MISSING - not mapped, not shown
Lab sees ward	DONE	MISSING - not mapped, not shown
Lab sees bed	DONE	MISSING - not mapped, not shown
Source = this visit (not UHID desk)	DONE	MISSING - use encounter_type

registration_source was already on the lab API before this work. It is still returned. Do NOT use it for the OPD/IPD badge on lab screens. Use encounter_type.

2. What the technician should see

Doctor orders a test. Lab already receives that order on Pending Tests. On that same row, lab must know if the patient is currently OPD or IPD, and if IPD, which ward and bed to collect the sample from.

Patient	Visit	Ward	Bed	Test
Rahul Sharma	IPD	General Ward	G-02	CBC
Priya Nair	OPD	-	-	LFT

- OPD: patient comes to the lab. Ward and bed show as dash (-).
- IPD: patient is admitted. Lab goes to the ward and bed.
- Location is live. If the patient is transferred before collection, the next GET /lab/orders shows the new bed.

3. registration_source vs encounter_type

Both fields are strings: OPD or IPD. They answer different questions. Using the wrong one will send lab to the wrong place.

Field	Meaning	Use on lab UI?
registration_source	Which desk created the UHID. Permanent.	No. Do not badge this.
encounter_type	This visit now. IPD if admitted, else OPD.	YES. This is the badge.
ward_name / bed_number	From active IPD admission.	YES. Empty for OPD.

Why registration_source is wrong for lab

- UHID created in OPD, later admitted: registration_source stays OPD, but encounter_type is IPD with a real ward and bed.
- UHID created in IPD, later discharged, OPD test: registration_source stays IPD, but encounter_type is OPD and ward/bed are null.

RULE

Badge = encounter_type. Ward/bed only when encounter_type is IPD. If ward/bed are null, show dash. Never invent a ward from registration_source.

4. Backend contract (already live)

No new lab routes. Existing responses gained extra fields.

4.1 Endpoints

Method / URL	Where the new fields sit
GET /lab/orders	Each item in items[]
GET /lab/orders/{id}	Top-level order object
GET /lab/reports	Each item in items[]
GET /lab/reports/{id}	Nested object: order

4.2 New / relevant fields

JSON field	Type	Notes
encounter_type	string	OPD or IPD. Default OPD if omitted.
ward_name	string null	Null for OPD. Ward name, not a number.
bed_number	string null	Null for OPD. Example: G-02
admission_id	int null	Null for OPD. Optional for UI.
registration_source	string	Still present. Ignore for badge.

encounter_type: str = "OPD" in the schema is only a fallback when the field is missing. The service sets IPD when an active admission exists.

4.3 Example: OPD patient

```
{
  "id": 184,
  "patient_name": "Priya Nair",
  "patient_uid": "P-1205",
  "registration_source": "OPD",
  "encounter_type": "OPD",
  "admission_id": null,
  "ward_name": null,
  "bed_number": null,
  "test_name": "LFT"
}
```

4.4 Example: IPD patient (UHID may still be OPD)

```
{
  "id": 185,
  "patient_name": "Rahul Sharma",
  "patient_uid": "P-1188",
  "registration_source": "OPD",
  "encounter_type": "IPD",
  "admission_id": 42,
  "ward_name": "General Ward",
  "bed_number": "G-02",
  "test_name": "CBC"
}
```

}

In 4.4 registration_source is OPD (UHID desk) but encounter_type is IPD. Lab must show IPD + General Ward + G-02.

5. What is missing in the Lab frontend

CURRENT STATE

API already sends the fields. labMapper.js drops them. Lab pages never render Source, Ward or Bed. Extra JSON does not break the UI; it is ignored.

5.1 Mapper (must do first)

File	Gap
src/shared/api/mappers/labMapper.js	apiToUiLabOrder ignores the new fields
same file: apiToUiLabReport	Drops encounter_type, ward, bed
same file: apiToUiLabReportDetail	Reads order.* but not visit location

No new API client file is required. GET /lab/orders is already wired.

5.2 Screens that must show the fields

File	What is missing
features/lab/pages/LabOrderListPage.jsx	No Source / Ward / Bed columns
features/lab/components/LabDashboardRemainingTests.jsx	Only name, test, UHID, time
features/lab/pages/LabUploadReportPage.jsx	Info panel has no visit / location

5.3 Screens that should also show them (recommended)

File	What is missing
features/lab/pages/LabCompletedReportsPage.jsx	Archive table has no Source/Ward/Bed
features/lab/components/LabReportDetailModal.jsx	Detail panel has no visit / location
features/lab/utills/labReportUtils.js	Print + CSV omit visit / location

5.4 Do not change

- HM-System-Backend (already shipped)
- Lab routes, hooks, query keys, GET URLs
- Doctor consultation / create-lab-test flow
- IPD admission create/edit screens

6. Frontend implementation

6.1 Mapper - add to apiToUiLabOrder

apiToUiLabOrderDetail already spreads apiToUiLabOrder, so order detail and upload page pick this up automatically after this change.

```
encounterType: row.encounter_type ?? row.encounterType ?? 'OPD',
admissionId: row.admission_id ?? row.admissionId ?? null,
wardName: row.ward_name ?? row.wardName ?? null,
bedNumber: row.bed_number ?? row.bedNumber ?? null,
```

Also add the same four fields in apiToUiLabReport (from the report row) and apiToUiLabReportDetail (from row.order).

DO NOT

Do not map registration_source into the badge. You may keep registrationSource for debugging, but the UI label must be encounterType.

6.2 Display helper (suggested)

```
function visitLocationLabel(order) {
  const visit = order.encounterType === 'IPD' ? 'IPD' : 'OPD';
  if (visit !== 'IPD') return { visit, ward: '-', bed: '-' };
  return {
    visit: 'IPD',
    ward: order.wardName || '-',
    bed: order.bedNumber || '-',
  };
};
}
```

6.3 Pending Tests table (required)

LabOrderListPage.jsx current columns: Request ID, Patient Name, Patient ID, Doctor, Test, Priority, Requested, Status, Action.

Add three columns after Patient ID (or after Patient Name):

- Source -> badge from encounterType (OPD / IPD)
- Ward -> wardName or dash
- Bed -> bedNumber or dash

If the table is too wide, one column 'Ward / Bed' is OK: 'General Ward / G-02' for IPD, dash for OPD.

6.4 Dashboard remaining tests (required)

LabDashboardRemainingTests.jsx: under the patient name or in meta, show OPD, or IPD plus ward and bed. Example: 'IPD · General Ward · G-02'.

6.5 Upload report header (required)

LabUploadReportPage.jsx info panel: add Source, Ward, Bed next to Patient Name / Patient ID. Technicians need location while working the sample.

6.6 Completed reports (recommended)

Add the same fields on LabCompletedReportsPage and LabReportDetailModal. If the patient is already discharged, encounter_type will be OPD and ward/bed null (live join). Show dash. Do not hide the report.

7. UI rules

- Badge text: exactly OPD or IPD (uppercase, from encounter_type).
- OPD: ward and bed must be dash, never 'N/A ward'.
- IPD with missing ward/bed: still show IPD, dash for empty location.
- Do not filter the list by OPD/IPD unless product asks later.
- There is no encounter_type query param on GET /lab/orders yet.
- Do not call IPD or nurse bed APIs from lab. Lab payload is enough.

Suggested badge styling

- OPD: existing lab-badge style, neutral / blue.
- IPD: distinct colour (match IPD patient list chips if possible).
- Ward / bed: match IPD chips on IpdPatientListPage if easy; plain text is fine.

8. Test plan

- OPD-only patient with a lab order: Source=OPD, Ward=-, Bed=-. Pending Tests, dashboard remaining, and upload header all agree.
- Admitted IPD patient with a lab order: Source=IPD and the current ward/bed from IPD (same values nurse/IPD see).
 - Patient registered in OPD then admitted: registration_source may be OPD, but the badge MUST be IPD with ward/bed.
- Transfer bed in IPD, refresh lab list: new ward/bed appear.
- Discharge the patient, refresh lab list: badge becomes OPD, location dash.
- Existing lab actions still work: sample collected, upload, complete.
- Lab dashboard counts and filters are unchanged.

9. Out of scope (do not build in this ticket)

- Doctors ordering tests from an IPD visit (lab orders still require an OPD appointment_id). If the patient is also admitted, lab still sees IPD + bed.
- New lab census / ward board. Stay on the existing order worklist.
- Backend schema, lab_service, or new query filters.
- Using registration_source as the visible Source column.

10. File checklist

Need	File	Change
MUST	shared/api/mappers/labMapper.js	Map encounterType, ward, bed
MUST	features/lab/pages/LabOrderListPage.jsx	Columns: Source, Ward, Bed
MUST	lab/.../LabDashboardRemainingTests.jsx	Show visit + location
MUST	features/lab/pages/LabUploadReportPage.jsx	Info panel location
NICE	features/lab/pages/LabCompletedReportsPage.jsx	Archive columns
NICE	lab/.../LabReportDetailModal.jsx	Detail location fields
NICE	features/lab/utills/labReportUtils.js	Print/CSV columns

DONE WHEN

A lab technician opening Pending Tests can tell, for every ordered test, whether the patient is OPD or IPD, and if IPD, the ward name and bed number, without opening IPD or nurse screens.