

# Statistical Data Analysis

---

Dr. Jana de Wiljes

12. Dezember 2022

Universität Potsdam

# Graph Partitioning and Community Detection

---

# Difference

## Graph Partitioning (GP)

- partition vertices into given number of groups
- sizes of groups are (roughly) fixed
- many edges inside groups, few edges between groups
- goal: dividing network into smaller more manageable pieces
- example:
  - numerical solution of network processes on a parallel computer

## Community Detection (CD)

- partition vertices into groups
- sizes of groups are not fixed
- many edges inside groups, few edges between groups
- goal: understanding structure of a network
- examples:
  - collaboration
  - related web pages

# Why is partitioning hard?

## Problem

Partition vertex set into two parts (*graph bisection*).

$n$  vertices into parts of sizes  $n_1$  and  $n_2$  ( $n_1 + n_2 = n$ ):

- $\frac{n!}{n_1!n_2!}$  possibilities (half of it if order is ignored and  $n_1 = n_2$ )
- using Stirling's formula  $n! \approx \sqrt{2\pi n}(n/e)^n$  we get

$$\frac{n!}{n_1!n_2!} \approx \frac{n^{n+1/2}}{n_1^{n_1+1/2}n_2^{n_2+1/2}}$$

- for a balanced partition ( $n_1 \approx n_2$ ):

$$\text{roughly } \frac{2^{n+1}}{\sqrt{n}} \text{ possibilities}$$

Therefore, exhaustive search is usually unfeasible.

## Arbitrary number of classes

Methods for graph bisection can be generalised (other ways are possible):

- number of vertices:  $n$
- number of classes:  $k$
- define  $l = k - 2^{\lfloor \log_2 k \rfloor}$
- for  $r = 1, \dots, l$  (ascending order) apply graph bisection method with

$$n_1^{(r)} = n - \frac{r \cdot n}{k} \quad \text{and} \quad n_2^{(r)} = \frac{n}{k}$$

- apply (equally sized) graph bisection  $\lfloor \log_2 k \rfloor$  times to the  $n - \frac{l \cdot n}{k}$  vertices in the large class
- results in  $k$  classes of (almost) same size  $\frac{n}{k}$

# Graph cuts

Given a graph  $G = (V, E, \omega)$ .

- for disjoint  $A, B \subset V$  define the *cut size*

$$\text{cut}(A, B) = \sum_{i \in A, j \in B} \omega_{ij}$$

- for a partition  $\mathcal{A} = A_1, A_2, \dots, A_k$  define

$$\text{cut}(A_1, A_2, \dots, A_k) = \sum_{i=1}^k \text{cut}(A_i, \bar{A}_i)$$

- basic problem: find  $\mathcal{A}$  minimizing  $\text{cut}(A_1, A_2, \dots, A_k)$

## Types of methods (usually heuristics)

### Local

- Kernighan-Lin algorithm
- Fiduccia-Mattheyses algorithm
- ...

### Global

- Spectral clustering
- ...

# Kernighan-Lin algorithm

The algorithm (Kernighan and Lin in 1970) works as follows:

---

**Algorithm:** Partition vertex set into two parts (Kernighan & Lin)

---

**Input:** Graph  $G = (V, E)$ , positive integers  $n_1, n_2$

1 Choose random partition  $V_1, V_2$  of  $V$  with  $|V_i| = n_i$ ;

2 **repeat**

3      $\text{minPair} \leftarrow \sum \omega_{ij} + 1$ ;

4     **for** (  $i \in V_1, j \in V_2$ , *neither  $i$  nor  $j$  has been swapped before* )

5         **if**  $\text{cut}((V_1 \setminus \{i\}) \cup \{j\}, (V_2 \setminus \{j\}) \cup \{i\}) \leq \text{minPair}$  **then**

6              $\text{minPair} \leftarrow \text{cut}((V_1 \setminus \{i\}) \cup \{j\}, (V_2 \setminus \{j\}) \cup \{i\})$ ;

7              $i_0 \leftarrow i, j_0 \leftarrow j$ ;

8         **end**

9      $V_1 = (V_1 \setminus \{i_0\}) \cup \{j_0\}, V_2 = (V_2 \setminus \{j_0\}) \cup \{i_0\}$  (swap  $i_0$  and  $j_0$ )

10 **until** *no pair of unused vertices exists*;

11 Pick partition (from the different  $V_1, V_2$ ) with smallest cut size;

**Output:** Partition  $V_1, V_2$  of  $V$

---



# Runtime of Kernighan-Lin algorithm

At first glance we get:

- $0 \leq \min\{n_1, n_2\} \leq \frac{n}{2} \rightsquigarrow \mathcal{O}(n)$  swaps (worst case)
- $\frac{n}{2} \cdot \frac{n}{2}$  of considered pairs per swap (worst case)
- cut size change (swap  $i$  and  $j$ ):

$$\sum_{v \in N(i) \cap V_1} \omega_{iv} + \sum_{v \in N(j) \cap V_2} \omega_{jv} - \sum_{v \in N(i) \cap V_2} \omega_{iv} - \sum_{v \in N(j) \cap V_1} \omega_{jv} + \omega_{ij}$$

- evaluating this expression costs  $\mathcal{O}(m/n)$ , where  $m = |E|$ , if stored in adjacency list
- $\rightsquigarrow$  runtime is  $\mathcal{O}(m \cdot n^2)$  for one (!) round

## Notes on the Kernighan-Lin algorithm

- swapping every round avoids local minima
- usually the algorithm is repeated several times with last output as input
- first partition is random  $\rightsquigarrow$  sometimes algorithm is started more than once to get other (hopefully better) results
- convergence rate unknown
- for larger number of classes (i.e.  $k \geq 3$ ) optimum might not be reached if applied
- Generalisation to hypergraphs: Fiduccia-Mattheyses algorithm

- mathematical foundation by Donath & Hoffman and Fiedler in 1973
- applications in various fields/for various problems
  - image segmentation
  - educational data mining
  - entity resolution
  - speech separation
  - ...

## Laplacian matrix (and another graph definition)

The degree matrix  $D(G)$  is given by

$$d_{ij} = \begin{cases} \sum_{l \in N(i)} w_{il} & \text{if } i = j, \\ 0 & \text{else.} \end{cases}$$

Laplacian matrix:

$$L(G) = D(G) - W(G)$$

We also need:

$$\text{vol}(A) = \sum_{ij \in E, i, j \in A} \omega_{ij} \text{ for } A \subset V \text{ (no double counting!)}$$

# Spectral clustering and graph cuts

Clustering corresponds to finding cuts in graphs (see next slides; other interpretations possible), there are (usually) two types:

- RatioCut (balanced by number of vertices in each cluster)
- NCut (balanced by sum of edge weights in each cluster)

## Formalization of RatioCut and NCut

- $\text{RatioCut}(A_1, A_2, \dots, A_k) = \sum_{i=1}^k \frac{\text{cut}(A_i, \bar{A}_i)}{|A_i|}$ 
  - $\sum_{i=1}^k (1/|A_i|)$  is minimized if all  $A_i$  have the same size
  - hence minimizing RatioCut balances clusters by their number of vertices (as desired)
- $\text{NCut}(A_1, A_2, \dots, A_k) = \sum_{i=1}^k \frac{\text{cut}(A_i, \bar{A}_i)}{\text{vol}(A_i)}$ 
  - $\sum_{i=1}^k (1/\text{vol}(A_i))$  is minimized if all  $\text{vol}(A_i)$  coincide
  - hence minimizing NCut balances clusters by their edge weights (as desired)
- corresponding optimization problems are NP hard
- spectral clustering is a way to solve relaxed versions of those problems

# Useful properties of the Laplacian

**Proposition:** The Laplacian matrix  $L (= D - W)$  satisfies the following properties:

i For every vector  $f \in \mathbb{R}^n$  we have

$$f^T L f = \frac{1}{2} \sum_{i,j=1}^n w_{ij} (f_i - f_j)^2.$$

ii  $L$  is symmetric and positive semi-definite.

iii The smallest eigenvalue of  $L$  is 0, the corresponding eigenvector is the constant one vector.

iv  $L$  has  $n$  non-negative, real-valued eigenvalues

$$0 = \lambda_1 \leq \lambda_2 \leq \dots \leq \lambda_n.$$

# Useful properties of the Laplacian

Proof:


i By the definition of  $d_i$ ,

$$\begin{aligned} f^T L f &= f^T D f - f^T W f = \sum_{i=1}^n d_i f_i^2 - \sum_{i,j=1}^n f_i f_j w_{ij} \\ &= \frac{1}{2} \left( \sum_{i=1}^n d_i f_i^2 - 2 \sum_{i,j=1}^n f_i f_j w_{ij} + \sum_{j=1}^n d_j f_j^2 \right) = \frac{1}{2} \sum_{i,j=1}^n w_{ij} (f_i - f_j)^2. \end{aligned}$$

- ii The symmetry of  $L$  follows directly from the symmetry of  $W$  and  $D$ . The positive semi-definiteness is a direct consequence of Part (i), which shows that  $f^T L f \geq 0$  for all  $f \in \mathbb{R}^n$ .
- iii All eigenvalues are real (symmetric matrix). The rest follows easily from Part (ii) and the defining equation of eigenvalues.
- iv This is a direct consequence of (i)-(iii).



## Graph cuts and spectral clustering



$$f^T L f = \frac{1}{2} \sum_{i,j=1}^n w_{ij} (f_i - f_j)^2$$

**Proposition:** The number of connected components of a graph is equal to the multiplicity of the first eigenvalue (which is 0) of the graph Laplacian matrix.

## Relaxation of RatioCut for $k = 2$

Goal is to solve

$$\min_{A \subset V} \text{RatioCut}(A, \bar{A})$$

Reformulation: for  $A \subset V$  define  $f = (f_1, \dots, f_n) \in \mathbb{R}^n$  (some kind of indicator vector) via

$$f_i = \begin{cases} \sqrt{|\bar{A}|/|A|} & \text{if } v_i \in A, \\ -\sqrt{|A|/|\bar{A}|} & \text{if } v_i \in \bar{A}. \end{cases}$$

It can be shown that

$$f^T L f = |V| \cdot \text{RatioCut}(A, \bar{A})$$

## Relaxation of RatioCut for $k = 2$

Proof:

$$\begin{aligned} 2f^T Lf &= \sum_{i,j=1}^n w_{ij}(f_i - f_j)^2 \\ &= \sum_{i \in A, j \in \bar{A}} w_{i,j} \left( \sqrt{\frac{|\bar{A}|}{|A|}} \right. \\ &\quad \left. + \sqrt{\frac{|A|}{|\bar{A}|}} \right)^2 + \sum_{i \in \bar{A}, j \in A} w_{i,j} \left( -\sqrt{\frac{|\bar{A}|}{|A|}} - \sqrt{\frac{|A|}{|\bar{A}|}} \right)^2 \\ &= 2\text{cut}(A, \bar{A}) \left( \frac{|\bar{A}|}{|A|} + \frac{|A|}{|\bar{A}|} + 2 \right) \\ &= 2\text{cut}(A, \bar{A}) \left( \frac{|A| + |\bar{A}|}{|A|} + \frac{|A| + |\bar{A}|}{|\bar{A}|} \right) \\ &= 2|V| \cdot \text{RatioCut}(A, \bar{A}) \end{aligned}$$

## Relaxation of RatioCut for $k = 2$

Further,  $f$  is orthogonal to 1:

$$\sum_{i=1}^n f_i = \sum_{i \in A} \sqrt{\frac{|\bar{A}|}{|A|}} - \sum_{i \in \bar{A}} \sqrt{\frac{|A|}{|\bar{A}|}} = |A| \sqrt{\frac{|\bar{A}|}{|A|}} - |\bar{A}| \sqrt{\frac{|A|}{|\bar{A}|}} = 0.$$

Finally

$$\|f\|^2 = \sum_{i=1}^n f_i^2 = |A| \frac{|\bar{A}|}{|A|} + |\bar{A}| \frac{|A|}{|\bar{A}|} = |\bar{A}| + |A| = n.$$

Hence the minimization problem is equivalent to

$$\min_{A \subset V} f^T L f$$

subject to the given  $f$ .

## Relaxation of RatioCut for $k = 2$

This problem is NP-hard since the solution vector only takes two particular values.

Relaxing this problem is possible:

$$\min_{f \in \mathbb{R}^n} f^T L f \text{ subject to } f \perp 1, \|f\| = \sqrt{n}$$

The Rayleigh-Ritz theorem (see e.g. Strang - Linear algebra and its applications) gives the solution of this problem via an eigenvector corresponding to the second smallest eigenvalue of  $L$ .

Remark: Solution has to be transformed!

## Special case ( $k = 2$ ) of unnormalized spectral clustering

---

**Algorithm:** Unnormalized spectral clustering ( $k = 2$ )

---

**Input:** Weight matrix (or any similarity matrix)  $S \in \mathbb{R}^{n \times n}$

- 1 Construct similarity graph  $G$ ;
- 2 Compute  $L(G)$ ;
- 3 Compute Eigenvectors  $X_1$  and  $X_2$  of  $L(G)$ ;
- 4 Build  $U \in \mathbb{R}^{n \times 2}$  with  $X_1$  and  $X_2$  as columns;
- 5 Rows of  $U$  are  $y_1, y_2, \dots, y_n \in \mathbb{R}^2$ ;
- 6 Cluster  $y_1, y_2, \dots, y_n$  into Clusters  $C_1$  and  $C_2$  ( $k$ -means);

**Output:** Clusters  $A_1 = \{j : y_j \in C_1\}$  and  $A_2 = \{j : y_j \in C_2\}$

---

## Relaxation of RatioCut for $k > 2$ (sketch)

- Define  $k$  indicator vectors  $h_j = (h_{1,j}, h_{2,j}, \dots, h_{n,j})^T$  via

$$h_{i,j} = \begin{cases} 1/\sqrt{|A_j|} & \text{if } v_i \in A_j, \\ 0 & \text{else} \end{cases}$$

- Matrix  $H \in \mathbb{R}^{n \times k}$  with columns  $h_1, h_2, \dots, h_k$  is orthogonal
- We have  $h_i^T L h_i = \frac{\text{cut}(A_i, \bar{A}_i)}{|A_i|}$  and  $h_i^T L h_i = (H^T L H)_{ii}$
- Together this yields  $\text{RatioCut}(A_1, A_2, \dots, A_k) = \text{tr}(H^T L H)$
- Hence the minimum of  $\text{RatioCut}(A_1, A_2, \dots, A_k)$  can be approximated by solving (the relaxed version)

$$\min_{H \in \mathbb{R}^{n \times k}} \text{tr}(H^T L H) \text{ subject to } H^T H = I$$



# General case of unnormalized spectral clustering

---

**Algorithm:** Unnormalized spectral clustering

---

**Input:** Weight matrix (or any similarity matrix)  $S \in \mathbb{R}^{n \times n}$ , number  $k$  of clusters

- 1 Construct similarity graph  $G$ ;
- 2 Compute  $L(G)$ ;
- 3 Compute Eigenvectors  $X_1, X_2, \dots, X_k$  of  $L(G)$ ;
- 4 Build  $U \in \mathbb{R}^{n \times k}$  with  $X_1, X_2, \dots, X_k$  as columns;
- 5 Rows of  $U$  are  $y_1, y_2, \dots, y_n \in \mathbb{R}^k$ ;
- 6 Cluster  $y_1, y_2, \dots, y_n$  into Clusters  $C_1, C_2, \dots, C_k$  ( $k$ -means);

**Output:** Clusters  $A_1, A_2, \dots, A_k$  with  $A_i = \{j : y_j \in C_i\}$

---