

Terraform

- template

- IAAS

- Automation tool

hashicorp - maintaining the terraform

TERRAFORM WORKFLOW

init -> Validate -> Plan -> Apply -> Destroy

BLOCKS OF TERRAFORM

- fundamental block

- variable block

- online /calling block

Code :

```
terraform {  
  required_providers {  
    aws = {  
      source = "hashicorp/aws"  
      version = "5.92.0"  
    }  
  }  
}
```

```
provider "aws" {  
  region = "us-east-1"  
}
```

```
resource "aws_vpc" "myvpc" {  
  cidr_block = "10.0.0.0/16"
```

```
  tags = {  
    Name = "demovpc"  
  }  
}
```

```
resource "aws_subnet" "pubsub" {  
  vpc_id = aws_vpc.myvpc.id  
  cidr_block = "10.0.1.0/24"  
  availability_zone = "us-east-1a"
```

```
  tags = {  
    Name = "sn1"  
  }  
}
```

```
resource "aws_subnet" "pubsub" {  
  vpc_id = aws_vpc.myvpc.id  
  cidr_block = "10.0.1.1/24"  
  availability_zone = "us-east-1a"
```

```
  tags = {  
    Name = "sn1"  
  }  
}
```

```
}
```

```
resource "aws_subnet" "prisub" {  
  vpc_id   = aws_vpc.myvpc.id  
  cidr_block = "10.0.1.0/24"  
  availability_zone = "us-east-1a"
```

```
  tags = {  
    Name = "sn1"  
  }  
}
```

```
resource "aws_subnet" "prisub" {  
  vpc_id   = aws_vpc.myvpc.id  
  cidr_block = "10.0.1.0/24"  
  availability_zone = "us-east-1a"
```

```
  tags = {  
    Name = "sn1"  
  }  
}
```

```
resource "aws_internet_gateway" "tfigw" {  
  vpc_id = aws_vpc.myvpc.id
```

```
  tags = {  
    Name = "tfigw"  
  }  
}
```

```
resource "aws_route_table" "tfpubrt" {
```

```
vpc_id = aws_vpc.myvpc.id
```

```
route {  
  cidr_block = "0.0.0.0/0"  
  gateway_id = aws_internet_gateway.tfigw.id  
}
```

```
tags = {  
  Name = "tfpublicroute"  
}  
}
```

```
resource "aws_route_table_association" "pubsn1" {  
  subnet_id    = aws_subnet.pubsub.id  
  route_table_id = aws_route_table.tfpubrt.id  
}
```

```
resource "aws_route_table_association" "pubsn2" {  
  subnet_id    = aws_subnet.pub_sub.id  
  route_table_id = aws_route_table.tfpubrt.id  
}
```

```
resource "aws_eip" "tfeip" {  
  domain = "vpc"  
}
```

```
resource "aws_nat_gateway" "tfnat" {  
  allocation_id = aws_eip.tfeip.id  
  subnet_id    = aws_subnet.pub_sub.id  
}
```

```
tags = {  
  Name = "gw NAT"  
}
```

```
}  
}
```

```
resource "aws_route_table" "tfprirt" {  
  vpc_id = aws_vpc.myvpc.id
```

```
  route {  
    cidr_block = "0.0.0.0/0"  
    gateway_id = aws_nat_gateway.tfnat.id  
  }  
}
```

```
  tags = {  
    Name = "tfprivateroute"  
  }  
}
```

```
resource "aws_route_table_association" "prsn3" {  
  subnet_id    = aws_subnet.prisub.id  
  route_table_id = aws_route_table.tfprirt.id  
}
```

```
resource "aws_route_table_association" "prsn4" {  
  subnet_id    = aws_subnet.pri_sub.id  
  route_table_id = aws_route_table.tfprirt.id  
}
```

```
resource "aws_security_group" "allow_tfsg" {  
  name      = "allow_tfsg"  
  description = "Allow TLS inbound traffic"  
  vpc_id    = aws_vpc.myvpc.id
```

```
  ingress {
```

```
description    = "HTTPS "
from_port      = 443
to_port        = 443
protocol       = "tcp"
cidr_blocks    = ["0.0.0.0/0"]
}

ingress {
  description   = "HTTP "
  from_port     = 80
  to_port       = 80
  protocol      = "tcp"
  cidr_blocks   = ["0.0.0.0/0"]
}

ingress {
  description   = "SSH"
  from_port     = 22
  to_port       = 22
  protocol      = "tcp"
  cidr_blocks   = ["0.0.0.0/0"]
}

egress {
  from_port     = 0
  to_port       = 0
  protocol      = "-1"
  cidr_blocks   = ["0.0.0.0/0"]
}

tags = {
  Name = "TfsecurityGroup"
}
```

```
}
```

```
resource "aws_instance" "pub_ins" {  
  ami          = "ami-0fc5d935ebf8bc3bc"  
  instance_type = "t2.micro"  
  subnet_id    = aws_subnet.pub_sub.id  
  vpc_security_group_ids = [aws_security_group.allow_tfsg.id]  
  key_name      = "Safrin"  
  associate_public_ip_address = "true"  
}
```

```
resource "aws_instance" "pri_ins" {  
  ami          = "ami-0fc5d935ebf8bc3bc"  
  instance_type = "t2.micro"  
  subnet_id    = aws_subnet.prisub.id  
  vpc_security_group_ids = [aws_security_group.allow_tfsg.id]  
  key_name      = "Safrin"  
}
```

```
#terraform init
```

```
#terraform validate
```

```
#terraform plan
```

```
#terraform apply
```

```
#terraform destroy
```



the essential Terraform Cheatsheet

by justin o'connor

general commands

get the terraform version
`terraform version`

download and update root modules
`terraform get -update=true`

open up a terraform interactive terminal
terraform console

create a dot diagram of terraform dependencies
`terraform graph | dot -Tpng > graph.png`

format terraform code to HCL standards
`terraform fmt`

validate terraform code syntax
`terraform validate`

enable tab auto-completion in the terminal
`terraform -install-autocomplete`

show information about provider requirements
`terraform providers`

login and logout of terraform cloud
`terraform login` and `terraform logout`

workspaces

list the available workspaces
`terraform workspace list`

create a new workspace
`terraform workspace new development`

select an existing workspace
`terraform workspace select default`

initialize terraform

initialize terraform in the current working directory
`terraform init`

skip plugin installation
`terraform init -get-plugins=false`

force plugin installation from a directory
`terraform init -plugin-dir=PATH`

upgrade modules and plugins at initialization
`terraform init -upgrade`

update backend configuration
`terraform init -migrate-state -force-copy`

skip backend configuration
`terraform init -backend=false`

use a local backend configuration
`terraform init -backend-config=FILE`

change state lock timeout (default is zero seconds)
`terraform init -lock-timeout=120s`

plan terraform

produce a plan with diff between code and state
`terraform plan`

output a plan file for reference during apply
`terraform plan -out current.tfplan`

output a plan to show effect of terraform destroy
`terraform plan -destroy`

target a specific resource for deployment
`terraform plan -target=ADDRESS`

note that the -target option is also available for the terraform apply and terraform destroy commands.

outputs

list available outputs
`terraform output`

output a specific value
`terraform output NAME`

apply terraform

apply the current state of terraform code
`terraform apply`

specify a previously generated plan to apply
`terraform apply current.tfplan`

enable auto-approval or automation
`terraform apply -auto-approve`

destroy terraform

destroy resources managed by terraform state
`terraform destroy`

enable auto-approval or automation
`terraform destroy -auto-approve`

manage terraform state

list all resources in terraform state
`terraform state list`

show details about a specific resource
`terraform state show ADDRESS`

track an existing resource in state under new name
`terraform state mv SOURCE DESTINATION`

import a manually created resource into state
`terraform state import ADDRESS ID`

pull state and save to a local file
`terraform state pull > terraform.tfstate`

push state to a remote location
`terraform state push PATH`

replace a resource provider
`terraform state replace-provider A B`

taint a resource to force redeployment on apply
`terraform taint ADDRESS`

untaint a previously tainted resource
`terraform untaint ADDRESS`

Version 1 <https://justinoconnor.codes>