# Matched data, small gaps: a pre-registered comparison of fine-tuned classifiers, retrieval-prompted language models and a typed-decision model for intent and out-of-scope decisions

**Safwan Kamal**

## Abstract

We compare a fine-tuned 150M classifier and retrieval-prompted 27–31B language models on intent and out-of-scope decisions, each given the same labelled data, in protocols frozen before any request; a hosted typed-decision model is a secondary system. On Banking77 the classifier is 1.4 points behind the primary general model, not significant after correction, and equivalence within 2.5 points is not shown. The one significant pre-registered difference (CLINC150, $-1.9$ points, Holm $p = .007$) splits about equally between scope and intent, and its in-scope part holds on items we had never inspected (post hoc). MASSIVE shows no stable ordering: its result depends on the model and on which domains are held out. A combination suggested by our exploratory data showed no advantage when tested as pre-registered, and two frontier models run with reasoning off were not significantly more accurate on 100 sessions per set, at 17 to 44 times the uncached API cost. For prompted models, the out-of-scope decision moves with what the prompt shows. On BANKING77-OOS, retrieving in-scope examples lowered five models' rejection of unsupported same-domain requests by 19 to 30 points on fresh label-clean items, after we removed a label leak we found in that dataset; for the typed-decision model the drop is at its fixed threshold. Random examples move it much less (1 to 11 points). Labelled out-of-scope examples raise rejection, mainly among the requests that retrieve them. No mitigation met its pre-registered criterion for most models.

## 1 Introduction

Typed-decision models such as Jev (Deußer et al., 2026) prompted this study. Jev returns a probability for each of a fixed set of typed options, which places it between a fine-tuned classifier and a prompted language model. That raised a broader question: given the same labelled data, which kind of system should decide whether an assistant handles a message and what it asks for? Our pre-registered comparison is between classifiers and prompted language models; Jev, added after those protocols were frozen, is a secondary system.

Before an assistant acts on a message it decides whether the message is something it handles (*scope*) and which operation it asks for (*intent*). The usual choices are a small classifier fine-tuned on labelled examples, a prompted general language model, or a cascade from the first to the second. Recent work finds that a cascade can beat both (Chen and Wang, 2025) or approach the general model at lower cost (Zaera et al., 2025; Arora et al., 2024), because the classifier names intents as well or better and the general model recognises out-of-scope requests better (Rodrigues and Vas, 2026). Those comparisons usually equip one side better than the other. The classifier thresholds its softmax, which is weak on same-domain out-of-scope requests (Zhang et al., 2022; Podolskiy et al., 2021), or the general model answers without the labelled examples the classifier was trained on, which retrieval would provide (Milios et al., 2023; Loukas et al., 2023).

Our own exploratory comparison equipped both sides and found the retrieval-prompted model ahead on every semantic intent set. An internal review attributed that lead to three artefacts: a threshold objective that over-rejected in-scope requests; borrowed out-of-scope sets that capitalisation separates; and labelled out-of-scope rows in the model's retrieval pool that the classifier never saw. We therefore froze a confirmatory protocol before any request, with matched data, normalised text, native or held-out-domain out-of-scope data, four pre-registered systems, a clustered test with Holm correction, and the sentence to print for each outcome (section 4). A second frozen protocol tested an observation from the exploratory

data: that retrieving in-scope examples lowers a model's rejection of unsupported same-domain requests (section 5). Jev was added under its own protocol, frozen after the first two had results, and joined two further frozen protocols.

Our contributions are three. First, a matched pre-registered comparison: on Banking77 the classifier and the general model are not significantly different, and equivalence is not shown; the one significant gap, 1.9 points on CLINC150, splits about equally between scope and intent; MASSIVE shows no stable ordering; and a cascade comes within 0.4 points of the model alone at 40% of its API cost, plus hosting the classifier. Second, evidence on what sets a prompted model's out-of-scope decision. Retrieved in-scope examples lower the rejection of unsupported same-domain requests on BANKING77-OOS for four general models and, at its fixed threshold, a typed-decision model, replicated on fresh leak-free items. Random examples move it much less. With ten options, CLINC single-domain shows no drop. Labelled out-of-scope examples raise rejection for the requests that retrieve them. Third, a record of what went wrong, as a checklist for such comparisons. The record covers an exploratory headline that did not survive the confirmatory design, a label leak in a public benchmark, and an item-reuse error in our own freshness rule.

## 2 Related work

**Classifiers, general models and cascades.** With plentiful labels, fine-tuned classifiers match or beat zero- and few-shot general models on intent (Rodrigues and Vas, 2026), while the stronger general models detect out-of-scope requests better (Rodrigues and Vas, 2026; Arora et al., 2024); hybrids combine the two (Castillo-López et al., 2025). Cascades that route a classifier's uncertain cases to a general model beat both on few-shot Banking77, CLINC150 and HWU64 (Chen and Wang, 2025) and approach the general model's accuracy at lower cost (Zaera et al., 2025; Arora et al., 2024); routing between general models is studied by Bouchard (2026) and Li et al. (2026).

**Retrieval and few-shot learning.** Retrieving demonstrations similar to the input helps in-context learning (Liu et al., 2022) and closes much of the intent gap to fine-tuning (Milios et al., 2023; Loukas et al., 2023), and many-shot in-context learning keeps improving with more examples (Bertsch et al., 2025). Fine-tuning breaks even with prompting at about 100 labelled samples on average (Pecher et al., 2025); SetFit is a strong few-shot fine-tuning baseline (Tunstall et al., 2022). Demonstrations shift a model's label prior (Zhao et al., 2021), and what models learn from demonstrations is partly the label space and input distribution rather than the input–label mapping (Min et al., 2022). The effect we report is narrower than a global prior shift (section 5). Contextual calibration (Zhao et al., 2021) corrects a global prior and is untested here. Arora et al. (2024) report that out-of-scope detection by prompted models degrades with more labels, which bears on our option-count test.

**Out-of-scope detection.** Classifier scores include the maximum softmax probability (Hendrycks and Gimpel, 2017), energy (Liu et al., 2020), Mahalanobis distance (Lee et al., 2018; Podolskiy et al., 2021) and nearest-neighbour distance (Sun et al., 2022); trained boundaries include Zhang et al. (2021). Zhang et al. (2022) separate out-of-domain from same-domain out-of-scope (BANKING77-OOS, CLINC single-domain) and show that the second defeats confidence-based detectors. Li et al. (2024) exclude HWU64's catch-all intents when building an out-of-scope benchmark, and Yilmaz and Toraman (2022) attribute weaker out-of-scope detection on HWU64 to its generic utterances. Training with labelled outliers improves detection (Hendrycks et al., 2019).

**Typed-decision models.** Deußer et al. (2026) benchmark Jev on 37 data sets, and Tang and Zheng (2026) audit the early evidence on typed-decision models. Rao and Callison-Burch (2026) find that Jev and language-model rubric judges err on the same items, so a Jev-first cascade gains little. Zhang et al. (2026) and Li and Wagle (2026) read Jev-style option probabilities out of general language models.

## 3 Setup

Figure 1 shows how the experiments connect.

**Decisions and endpoint.** Each turn needs a scope decision and, if in scope, an intent decision; a turn is right when both are. The primary endpoint is weighted turn accuracy, $0.8\times$ the share of in-scope turns kept with the right intent plus $0.2\times$ the share of out-of-scope turns rejected, which





Figure 1: Study design. The upper lane compares systems that are given the same labelled data; the lower lane asks what sets a prompted model's out-of-scope decision. Dashed arrows mark where an observation in one study motivated another: the exploratory drop in same-domain rejection led to run D, and Gemma's 23% rejection on MASSIVE led to the MASSIVE draws. Runs G and H check the confirmatory comparison. Filled boxes are protocols frozen before any of their requests; dashed boxes are audits recorded as dated errata.

| Set | Labels | Turns | Out of scope | Never seen |
|---|---|---|---|---|
| Banking77 | 77 | 1,479 | 184 | 582 |
| MASSIVE | 42 | 1,216 | 243 | 1,215 |
| CLINC150 | 150 | 1,850 | 185 | 1,766 |

Table 1: Confirmatory sets. *Never seen*: turns whose normalised text appears in no session built earlier (section 4). MASSIVE's in-scope turns cover 21 of its 42 labels.

matches a 20% out-of-scope prior and does not depend on the rate in the sessions. Turns form five-turn sessions; session success is secondary.

**Data.** Table 1 lists the confirmatory sets, built from Banking77 (Casanueva et al., 2020), MASSIVE (FitzGerald et al., 2022) and CLINC150 (Larson et al., 2019). CLINC150 uses its native out-of-scope test queries, and Banking77 borrows the same CLINC150 queries. MASSIVE uses utterances from three whole domains held out of its label set (email, iot, play), drawn with a fixed seed from the 16 domains other than *general* and *qa*, which we exclude from the draw as catch-alls, as Li et al. (2024) exclude HWU64's two catch-all intents; their intents remain in scope. Those are sibling domains of retained skills such as music and social. All text is lower-cased, and punctuation other than apostrophes is removed, for every system and pool. The sets were meant to contain only test items no earlier session used; that held for MASSIVE but not for Banking77 and CLINC150 (section 4).

**Systems.**

- **Specialist:** an Ettin 150M encoder (Weller et al., 2026) with a mean-pooled classification head, retrained on the normalised data. It uses three seeds and a learning rate chosen on development data (for MASSIVE, on the earlier 60-label task, not re-swept). Scope comes from a development-selected detector, with a threshold weighted by the 20% prior. The development out-of-scope items are 100 CLINC150 out-of-scope validation queries for Banking77 and CLINC150, and 100 development items from the held-out domains for MASSIVE.
- **General models:** Gemma 4 31B (primary) and Qwen3.5 27B (secondary). Each answers scope and intent at temperature 0 with reasoning off, after 20 BM25-nearest (Robertson and Zaragoza, 2009) in-scope training examples. The pool contains no out-of-scope rows, and labels are shown by name only, without descriptions.
- **Jev 1.13.0** (Deußer et al., 2026): a hosted "typed-decision" model from TypeSafe, pinned to one version, that answers a yes/no question as a probability and a choice question as a distribution over the given labels in one call. Its weights and architecture are not public, and its API bills 113 to 1,259 output tokens per call in our runs. It receives the same 20 neighbours, labelled with intent names, and its scope decision uses a fixed 0.5 threshold; its interface therefore differs from the general models' prompt, and comparisons with them are secondary.
- **Combination** (pre-registered): Gemma's scope, with the specialist's intent when its probability is at least 0.9.

- **Cascade** (pre-registered): the 40% of each test set's turns with the lowest specialist confidence go to Gemma (a batch rule, not a tuned threshold).

*Matched* means the same in-scope training rows for every system; only the specialist calibrates its scope decision, on 100 development out-of-scope items (table 5). *Pre-registered* means that each protocol, its item lists and its analysis code were committed to version control before any request, with no external registry (appendix A). Hosts, precision, prompts and hyperparameters are in appendix B.

**Statistics.** Paired differences are tested by sign flips of cluster sums. Clusters are gold intents; out-of-scope turns have no intent label, so each is its own cluster. The specialist's per-turn correctness is the mean over its three seeds. Intervals are 95% cluster bootstrap, not adjusted for multiplicity. The primary family is specialist against Gemma and combination against Gemma on each set, with Holm correction (Holm, 1979). Banking77 was to be tested for equivalence at $\pm 2.5$ points. Everything else is secondary and unadjusted, or post hoc where labelled.

## 4 Confirmatory comparison

Table 2 and fig. 2 give the results. As pre-registered, the general model is ahead on CLINC150 by 1.9 points (Holm $p = .007$). On Banking77 the 1.4-point gap is not significant after correction. Equivalence within 2.5 points is not shown: the pre-registered 90% interval's lower bound is $-2.53$ (mean over 40 bootstrap seeds $-2.51$, standard deviation 0.03). On MASSIVE the specialist is 4.4 points ahead, but the test cannot detect differences below about 9 points there (clustering its out-of-scope turns by source label, $p = .55$), and Qwen is 2.6 points ahead of the specialist here and 1.9 to 3.4 points ahead on all three further draws (appendix G), so the ranking depends on the model. The combination that looked better on our earlier data is not significantly different from Gemma on any set (Holm $\geq .40$). The cascade is within 0.4 points of Gemma alone at 40% of its API cost. Jev given the same retrieved examples is within 0.9 points of Gemma on Banking77 and CLINC150 (90% intervals; no margin was pre-specified) and 4.0 points ahead on the confirmatory MASSIVE draw ($p = .0001$, secondary), but not on the three further draws ($+0.5$, $-0.8$, $-3.5$). The Jev protocol's gate, Jev's scope with the specialist's intent, is 1.1 points ahead of the specialist on Banking77 ($p = .0005$) and not significantly different on CLINC150 ($+0.9$, $p = .12$) or MASSIVE ($-0.7$, $p = .95$; secondary, unadjusted). With the specialist's threshold set, as pre-registered, for a 10% or 30% out-of-scope rate, the Banking77 gap is $-1.78$ ($p = .008$, unadjusted) or $-1.25$, and the other sets keep their direction (appendix D). These gaps are not artefacts of example order: two further orderings of Gemma's 20 retrieved examples changed its weighted accuracy by at most 0.16 points on CLINC150 and 0.41 on MASSIVE, and left the CLINC150 gap between $-1.75$ and $-1.90$ (appendix H).

**Where the gaps come from.** Splitting each gap as pre-registered, into a scope part (specialist minus a hybrid of the model's scope and the specialist's intent) and an intent part (that hybrid minus the model), the CLINC150 gap divides evenly (0.9 scope, 1.0 intent). Our pre-registered headline rule therefore forbids saying that the difference lies in the out-of-scope decision. MASSIVE's 4.4 points are all scope. Gemma keeps 97% of in-scope turns but rejects only 23% of the held-out-domain requests: 5% of *play* requests, which it maps onto the retained music skills, and 35% of *email* requests. The specialist rejects 78% and 81% of these, with a threshold set, as pre-registered, on development items from the same held-out domains; set from in-scope development data alone, it rejects 24 to 54% and scores 73.9 to 79.3 (post hoc). On three further seeded draws of held-out domains (a sensitivity analysis that reuses MASSIVE test text; appendix G), specialist minus Gemma is $-1.0$, $-1.7$ and $+0.3$ points, none significant, and Gemma rejects 61 to 68% of held-out-domain requests. Two of those draws also held out music, play's sibling; whether this explains the confirmatory result is untested.

**Freshness (post hoc).** After the run, an audit found that 832 of Banking77's 1,295 in-scope turns had been used before. So had 65 of its 184 out-of-scope turns and 78 of CLINC150's 185. They appeared in our exploratory BANKING77-OOS sessions. That set is a lower-cased copy of the Banking77 test split and reuses CLINC out-of-scope queries, and our freshness rule had matched exact text. The models never saw these items before, but we had. On never-seen turns no primary

| | Weighted turn accuracy (%), all turns | | | | | | Specialist − Gemma (Holm $p$) | | |
|---|---|---|---|---|---|---|---|---|---|
| Set | Specialist | Gemma | Qwen 27B | Combination | Cascade 0.4 | Jev + retr. | All turns | Never seen | Gemma $/1k sess. |
| Banking77 | 92.7 | 94.1 | 94.0 | 94.7 | 94.3 | 94.1 | −1.42 (.19) | −1.65 (.94) | 0.73 |
| MASSIVE | 78.3 | 73.8 | 80.8 | 74.4 | 73.5 | 77.8 | +4.42 (.51) | +4.42 (.94) | 0.47 |
| CLINC150 | 93.1 | 95.0 | 95.0 | 95.1 | 95.1 | 95.0 | −1.89 (**.007**) | −0.94 (.94) | 1.06 |

Table 2: Pre-registered comparison. Specialist: mean of three seeds. Combination and cascade use Gemma. Jev and Qwen are secondary. The *never seen* column is a post hoc sensitivity analysis (section 4), with Holm over the same six tests. The cascade calls Gemma on 40% of turns, so its API cost is 40% of the Gemma column, plus hosting the classifier; the combination calls it on every turn. Combination − Gemma: +0.58, +0.60, +0.10 (Holm $\geq$ .40).





Figure 2: Paired differences in weighted turn accuracy with 95% cluster-bootstrap intervals on the confirmatory sessions. Specialist − Gemma is pre-registered; the never-seen row (open marker) is a post hoc sensitivity analysis; the other rows are pre-registered (combination, cascade) or secondary (Jev, Qwen). MASSIVE has almost no reused turns, so its two specialist rows coincide. Intervals are pointwise.

comparison is significant (table 2); CLINC150's gap halves to −0.94 [−2.14, +0.35]. Split by component, the in-scope part of the CLINC150 gap is unchanged on never-seen turns (−2.19 [−3.12, −1.32], $p = .0001$). The change comes from the out-of-scope turns: specialist − Gemma is +4.0 on the 107 never-seen ones and −7.3 on the 78 seen before. Neither out-of-scope subset differs significantly ($p = .17$ and $p = .09$, post hoc); since the models never saw these items, the change reflects which out-of-scope items are compared.

**Frontier models and cost.** Kimi K3 and Claude Opus 5 are never significantly different from Gemma (largest: Opus on CLINC150, +1.8, $p = .065$), though 100 sessions per set cannot exclude gains of 2 to 3 points. Uncached at list prices they cost 17 to 21 and 36 to 44 times as much per session. An earlier Banking77 specialist classified a request in 11 ms at batch size 1 on one consumer GPU (scope detector not timed), against median final-attempt calls of 1.0 to 2.8 s, and hosting it costs less than calling Gemma on every turn above about 47,000 to 106,000 sessions a month for an assumed $50-a-month host (appendices B and C).

## 5 What sets a prompted model's out-of-scope decision

On our exploratory BANKING77-OOS sessions, Gemma rejected 70% of requests for held-out Banking77 intents zero-shot and 38% with retrieved in-scope examples. A second frozen protocol (run D) tested this on items not used in the exploratory sessions (462 BANKING77-OOS and 332 CLINC single-domain items had been confirmatory turns; appendix A), with four general models from four families and two same-domain splits: BANKING77-OOS (Zhang et al., 2022), and CLINC single-domain out-of-scope for banking and for credit cards. There were four arms: zero-shot, retrieval, retrieval with a scope instruction, and retrieval with four fixed off-topic out-of-scope examples. The Jev protocol repeated the first three arms.

**Retrieval moves models towards acceptance on one split.** On BANKING77-OOS, retrieval lowered rejection of held-out requests for all four general models, by 24 to 40 points (Holm $p \leq .0008$ each), and for Jev by 45 points (Holm $p = .0002$; table 3). It also raised in-scope acceptance from

| | BANKING77-OOS: held-out rejected (%) | | | In-scope kept (%) | CLINC single-domain | |
|---|---|---|---|---|---|---|
| Model | As run | Leak-free subset | Instruction (as run) | zero-shot → retrieval | Held-out rejected | Instruction |
| Gemma 4 31B | 59.5 → 30.3 | 67.5 → 42.9 | 33.3 | 91.7 → 98.2 | 42.6 → 47.6 | 70.3 |
| Qwen3.5 27B | 82.2 → 58.5 | 85.4 → 71.2 | 63.5 | 80.9 → 95.2 | 67.0 → 68.9 | 84.1 |
| Llama 3.3 70B | 50.7 → 17.7 | 69.2 → 31.7 | 31.7 | 89.2 → 99.2 | 34.4 → 39.4 | 66.6 |
| DeepSeek V4 Pro | 60.8 → 21.1 | 70.4 → 38.3 | 31.8 | 88.9 → 99.0 | 30.6 → 31.7 | 48.6 |
| Jev 1.13.0 | 70.7 → 25.3 | 79.2 → 50.4 | 25.5 | 88.7 → 98.2 | 55.4 → 56.9 | 61.7 |
| Specialist (reference) | 49.6 (44.5 dev-unseen) | 68.2 | | | 53.7 (37.9 dev-unseen) | |

Table 3: Rejection of held-out same-domain requests, zero-shot → retrieval of 20 in-scope examples. The drop on BANKING77-OOS is pre-registered for each model (Holm $p \leq .0008$). On the post hoc leak-free subset (10 held-out intents that never leak, label-clean items) it is 14 to 38 points, $p \leq .009$ each. On CLINC single-domain, retrieval leaves rejection level or raises it by 1 to 5 points, and no model shows a drop. *Instruction*: the retrieval prompt plus one sentence on scope. Specialist: mean of three seeds (35 to 63% by seed as run); its in-scope accuracy is 85.8% as run and 91.8% on the leak-free subset. Jev's rejection is at a fixed 0.5 threshold.

81–92% to 95–99%. On CLINC single-domain, with each domain's own 10 options, it lowered rejection for no model; with 20 options it did for three (below).

An audit then found that the published BANKING77-OOS training split mislabels 366 of 5,905 rows. 145 of them are utterances of 17 held-out intents filed under in-scope labels, so the retrieval pool leaked held-out intents, and the models copied the leaked labels. On the 10 held-out intents that never leak, the drop is 14 to 38 points for all five models ($p \leq .009$). It survives the leak but is smaller.

**Mechanism (post hoc for the general models, pre-registered for Jev).** Accepted held-out requests go to nearby in-scope labels (D2 items below; appendix E). For the four general models, the chosen label is among the 20 retrieved labels for 92 to 99% of accepted held-out requests; zero-shot, 83 to 94% of accepted requests already go to those labels, so retrieval mainly raises how many requests are accepted rather than where they go. Gemma, for example, maps all 33 identity-verification requests it accepts to *why verify identity*. The drop is larger where the retrieved labels concentrate on one label (for Qwen, 29 points against 8). In signal-detection terms (Macmillan and Creelman, 2005), retrieval moves the general models' criterion towards acceptance by 0.7 to 1.1 standard deviations on run D's leak-free subset (appendix F).

Jev returns probabilities, so its discrimination was measured directly. Its pre-registered readout on the as-run items was an operating-point shift: AUROC unchanged ($+0.003$ [$-0.03$, $+0.04$]), and the mean in-scope probability on held-out requests up by 0.29. On leak-free items its AUROC rises slightly ($+0.03$ [$+0.007$, $+0.068$]) while that mean probability still rises by 0.17. At equal in-scope acceptance its rejection does not fall: on the fresh D2 items, with 95% of in-scope requests kept, retrieval raises it from 61% to 82% (post hoc, with thresholds set on the same items, so a diagnostic). Jev's drop in tables 3 and 4 is therefore at its fixed 0.5 threshold, which retrieval moves most in-scope and many held-out requests past. For the general models, which answer yes or no, no such comparison is possible; in aggregate their change looks like a shift towards acceptance with level or slightly better discrimination.

On CLINC single-domain the shift is smaller (the interval excludes zero for two of four general models), and discrimination improves (Jev: AUROC $+0.11$). Retrieval closeness does not explain the difference between the splits once the leak is removed (AUROC of top-1 similarity 0.90 against 0.91).

**Replication and causes (pre-registered, run D2).** A third frozen protocol (run D2) used validation items. On BANKING77-OOS they were fresh and label-clean: 500 in-scope and 388 held-out items, from 23 intents, with all 366 mislabelled rows removed from the pool. On CLINC single-domain there were 1,000 in-scope items, which had served as run D's specialist development data (never sent to a model; appendix A), and 575 held-out items. The protocol added three arms (table 4 and fig. 3).

- **The drop replicates** for all five models, by 19 to 30 points (Holm $p \leq .0006$).
- **Query-conditioned selection drives most of it.** Twenty random in-scope examples leave rejection 13 to 21 points higher than the 20





Figure 3: Operating points of the scope decision in run D2. Each arrow runs from a model's zero-shot answer (open marker) to its answer with 20 retrieved in-scope examples (filled marker). On BANKING77-OOS every model moves down and to the right: it accepts more in-scope requests and rejects fewer unsupported ones. Random examples ($\times$) move it much less, and repeating the scope rule after the examples ($+$) moves it back for four of five models. On CLINC single-domain the 10-option prompts (solid) barely move the rejection rate, while the 20-option prompts (dashed) move three general models down.

retrieved ones (Holm $p \leq .004$ for all five), within 1 to 11 points of zero-shot.

- **Repeating the rule partly helps.** Repeating the scope rule after the examples, immediately before the request, recovers 7 to 19 points of rejection for Qwen, Llama, DeepSeek and Jev (Holm $p \leq .008$); Gemma does not move ($+1.5$, $p = .13$). By run D's "works" criterion this is a mitigation for Llama only (79% recovered at $-0.6$ in-scope points). The arm repeats the rule rather than moving it.

- **Option count is not established.** Pooling CLINC single-domain's two domains into one 20-option prompt lowers rejection by 14 to 25 points for Gemma, Llama and DeepSeek, but the pooled prompt changes more than the option count (appendix F).

Throughout, the aggregate criterion moves towards acceptance; Jev's AUROC rises from 0.934 to 0.965, so for it discrimination does not fall.

**Labelled unsupported examples move it the other way.** In a paired secondary arm of the confirmatory run, we added 250 labelled out-of-scope rows to Gemma's pool. These rows came from the same three held-out domains as the test requests.

| Model | Zero-shot | Retrieval | Random | Rule after |
|---|---|---|---|---|
| Gemma 4 31B | 74.0 | 50.0 | 69.1 | 51.5 |
| Qwen3.5 27B | 91.5 | 72.7 | 90.2 | 83.2 |
| Llama 3.3 70B | 59.8 | 36.1 | 49.5 | 54.9 |
| DeepSeek V4 Pro | 68.0 | 41.8 | 62.6 | 49.0 |
| Jev 1.13.0 | 78.4 | 48.7 | 67.5 | 57.5 |

Table 4: Run D2: held-out rejection (%) on fresh label-clean BANKING77-OOS items with a clean pool. *Random*: 20 random in-scope examples. *Rule after*: the scope rule repeated after the retrieved examples. In-scope acceptance is 85–94% zero-shot and 97–100% with retrieval.

Gemma's rejection of those requests rose from 23% to 91%, and its weighted accuracy rose by 13.3 points [12.1, 14.6]. On the three further MASSIVE draws, rows from the tested domains again raised accuracy, for Gemma by 5.1 to 6.5 points and for Qwen by 2.3 to 4.0 (Holm $p \leq .0003$ for all six). Rows from three *other* unsupported domains raised weighted accuracy significantly in 1 of 6 tests (Gemma, draw 1, $+2.0$), but raised rejection in all 6 cells (post hoc, $+2.4$ to $+8.8$ points). That gain falls on the requests for which such a row is retrieved ($+5$ to $+16$ points, against about zero for the others). The gain is concentrated among the requests that retrieve such a row (fig. 4), much as outlier exposure helps classifiers





Figure 4: Gemma's rejection of held-out-domain MASSIVE requests on the confirmatory draw and three further draws (sensitivity analysis), with the specialist for reference. Labelled out-of-scope rows from the tested domains raise rejection most; rows from other unsupported domains raise it less, and only for requests that retrieve them.

(Hendrycks et al., 2019).

**Mitigations.** Neither pre-registered mitigation met its criterion, which was to recover half of the lost rejection at a cost of at most 2 points of in-scope accuracy. The instruction recovered 10 to 42% on BANKING77-OOS and none for Jev. On CLINC single-domain it raised rejection by 15 to 27 points for the general models, and by 5 points for Jev. On either split it cost at most 1.8 in-scope points. Off-topic out-of-scope examples did not help. In D2, repeating the scope rule after the examples met the criterion for Llama only. Two post hoc rules on the saved answers also fail it (appendix E).

## 6 Discussion

On our opening question, the pre-registered tests show no consistent advantage for either kind of system, and no equivalence (item 1). Differences between individual models can exceed the difference between kinds. On MASSIVE, Gemma and Qwen, given the same prompts and examples, rejected 23% and 68% of held-out-domain requests (descriptive). For a team choosing a system, the kind of system therefore says less than a check of the out-of-scope decision for the specific model and data. Four observations follow, each tagged with its evidence:

1. **Matched and equipped, neither kind of system holds a consistent advantage.** On Banking77 the 1.4-point gap is not significant and equivalence is not shown; on CLINC150 the general model is 1.9 points ahead; MASSIVE's direction depends on the model (pre-registered). Jev given the same examples is within 0.9 points of Gemma on Banking77 and CLINC150, and two frontier models were not significantly more accurate on 100 sessions per set, though gains of 2 to 3 points are not excluded (secondary).

2. **For a prompted model, the out-of-scope decision moves with what the prompt shows.** Retrieved in-scope examples lower the rejection of unsupported same-domain requests on BANKING77-OOS (pre-registered twice, the second time on fresh label-clean items for five models). Query-conditioned retrieval, not examples as such, accounts for most of it. For the typed-decision model the drop is at its fixed threshold: at equal in-scope acceptance, retrieval raised its rejection (post hoc). Retrieved examples did not lower rejection on CLINC single-domain with 10 options, and we could not establish why. Labelled out-of-scope examples raise rejection, mainly among the requests that retrieve them (MASSIVE, four draws). A fair comparison reports each system's operating point, not only its accuracy.

3. **Comparisons of this kind are fragile.** Our exploratory MASSIVE result (Gemma +5.3) did not survive the confirmatory design. A public benchmark leaked held-out intents, and our freshness rule missed lowercased copies. We suggest reporting, for any classifier-versus-model scope comparison: how out-of-scope data was sourced and whether surface cues separate it, what data each system's scope decision could use, the objective behind every threshold, and a label audit of the benchmark.

4. **The cascade's value is API cost** (pre-registered). It comes within 0.4 points of the general model at 40% of its API cost, but it also needs the classifier hosted, which pays for itself only above about 79,000 to 177,000 sessions a month at $50 a month.

## Limitations

**Data.**

- The confirmatory sets are assembled from single utterances of three English label sets.
- The supply of native out-of-scope data limits their size: the smallest differences detectable with 80% power (post hoc, from the observed sign-flip null, before Holm correction) are 1.9, 8.8 and 1.7 points on Banking77, MASSIVE and CLINC150.
- Banking77 and CLINC150 items overlap our exploratory sessions, and run D's items overlap the confirmatory turns.
- The confirmatory MASSIVE draw held out sibling domains, and three further draws reuse its test text. Its in-scope turns cover half of its labels.
- In the confirmatory run, the labelled out-of-scope rows added to Gemma's pool come from the test domains.
- The two same-domain splits come from one benchmark family. One of them has a label leak, and they differ in option count.
- The base BANKING77-OOS prompt already contains a scope sentence.
- Labels are shown by name only; label descriptions might reduce sibling absorption.
- The option-count arm could reach significance for at most one model and changes more than the number of options.
- The further MASSIVE draws hold out six domains each, which removes sibling skills from the label set.

**Models.**

- General models ran once per prompt at temperature 0 with one retriever; other orders of the retrieved examples changed accuracy by at most 0.4 points.
- Retrieval was BM25 only, which needs no trained component. In an exploratory paired comparison on 400 earlier sessions per set, a dense retriever (all-mpnet-base-v2), a Sentence-Transformers model (Reimers and Gurevych, 2019), changed Gemma's session success by $-2.2$ to $+2.5$ points, none significantly; its effect on the out-of-scope findings, such as how strongly the retrieved labels concentrate on one sibling, is untested.
- Moving one model between two fp8 hosts changed 9.5% of its answers, which is the size of several reported differences.
- The two frontier models were chosen by the author among those accepting reasoning disabled; reasoning-on use was not tested.
- Jev's scope threshold was fixed at 0.5 and not tuned; a threshold set from in-scope data changes its out-of-scope results.
- Jev's per-call price is not reported by its API; all Jev use in the project, including exploratory calls before the frozen runs, cost $4.27 (one $5.00 credit with $0.73 left; billing record in `artifacts/jev-cost/`), so a per-call price cannot be separated. Its interface (a fixed probability threshold, label names) differs from the general models' prompt.

**Analyses.**

- The specialist uses development out-of-scope data, which on MASSIVE came from the held-out test domains; the prompted models use none.
- The signal-detection estimates for the general models are aggregate descriptions; under unequal variances the sign of the discrimination change is not determined for two of four models.
- CLINC150 and Banking77 are public and may be in the models' training data. A completion probe found 0.5% verbatim completions for Gemma (Qwen refused the task), which does not rule contamination out.

## Availability and licences

Protocols, frozen item lists, every saved model reply, analysis code and the record of withdrawn conclusions are in our release (`https://github.com/SafwanKamal/matched-data-small-gaps`, with SHA-256 hashes of every file in `release/SHA256SUMS`). The specialist weights

and cached features for Banking77, CLINC150 and MASSIVE are on the Hugging Face Hub (https://huggingface.co/Safka532/matched-data-small-gaps-specialists) under the same hashes; those trained on BANKING77-OOS, which states no licence, are not redistributed, and the code rebuilds them. Banking77 is CC BY 4.0, CLINC150 CC BY 3.0 and MASSIVE CC BY 4.0. BANKING77-OOS and CLINC single-domain out-of-scope (Zhang et al., 2022) state no licence for their splits; we do not redistribute their files, and the items in our release are verbatim Banking77 and CLINC150 utterances. Our code is released under the MIT License.

## Disclosures

**Jev.** The author has no affiliation with TypeSafe, the provider of Jev, and received no funding or special access from it. Jev was used through its API in the same way as the other hosted models.

**AI assistance.** The author conceived and designed the study, chose the data sets, models and hypotheses, approved every protocol before it ran, directed the analyses and the internal review rounds, and is responsible for all content. AI tools assisted with coding, literature search and editing, and acted as reviewers in the internal review rounds.

## References


Gaurav Arora, Shreya Jain, and Srujana Merugu. 2024. Intent detection in the age of LLMs. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pages 1559–1570. ArXiv:2410.01627.

Amanda Bertsch, Maor Ivgi, Emily Xiao, Uri Alon, Jonathan Berant, Matthew R. Gormley, and Graham Neubig. 2025. In-context learning with long-context models: An in-depth exploration. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics*, pages 12119–12149. ArXiv:2405.00200.

Dylan Bouchard. 2026. Is escalation worth it? on the depth of LLM cascades. *arXiv preprint arXiv:2605.06350*. Version 2.

Iñigo Casanueva, Tadas Temčinas, Daniela Gerz, Matthew Henderson, and Ivan Vulić. 2020. Efficient intent detection with dual sentence encoders. In *Proceedings of the 2nd Workshop on NLP for Conversational AI*. ArXiv:2003.04807.

Galo Castillo-López, Gaël de Chalendar, and Nasredine Semmar. 2025. Intent recognition and out-of-scope detection using LLMs in multi-party conversations. In *Proceedings of the 26th Annual Meeting of the Special Interest Group on Discourse and Dialogue*, pages 504–512.

Peng Chen and Bang Wang. 2025. On collaborating small and large models for few-shot intent detection. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 13937–13953.

Tobias Deußer, Lorenz Sparrenberg, and Rafet Sifa. 2026. Evaluating and benchmarking the System One model Jev. *arXiv preprint arXiv:2609.37647*.

Jack FitzGerald, Christopher Hench, Charith Peris, Scott Mackie, Kay Rottmann, Ana Sanchez, Aaron Nash, Liam Urbach, Vishesh Kakarala, Richa Singh, Swetha Ranganath, Laurie Crist, Misha Britan, Wouter Leeuwis, Gokhan Tur, and Prem Natarajan. 2022. MASSIVE: A 1m-example multilingual natural language understanding dataset with 51 typologically-diverse languages. *arXiv preprint arXiv:2204.08582*.

Dan Hendrycks and Kevin Gimpel. 2017. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *International Conference on Learning Representations*. ArXiv:1610.02136.

Dan Hendrycks, Mantas Mazeika, and Thomas Dietterich. 2019. Deep anomaly detection with outlier exposure. In *International Conference on Learning Representations*.

Sture Holm. 1979. A simple sequentially rejective multiple test procedure. *Scandinavian Journal of Statistics*, 6(2):65–70.

Stefan Larson, Anish Mahendran, Joseph J. Peper, Christopher Clarke, Andrew Lee, Parker Hill, Jonathan K. Kummerfeld, Kevin Leach, Michael A. Laurenzano, Lingjia Tang, and Jason Mars. 2019. An evaluation dataset for intent classification and out-of-scope prediction. In *Proceedings of EMNLP-IJCNLP 2019*. ArXiv:1909.02027.

Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. 2018. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *Advances in Neural Information Processing Systems*. ArXiv:1807.03888.

Hao Li, Yiqun Zhang, Zhaoyan Guo, Chenxu Wang, Shengji Tang, Qiaosheng Zhang, Yang Chen, Biqing Qi, Peng Ye, Lei Bai, Zhen Wang, and Shuyue Hu. 2026. LLMRouterBench: A massive benchmark and unified framework for LLM routing. *arXiv preprint arXiv:2601.07206*.

Yinheng Li and Justin Wagle. 2026. LLM-as-Jev: LLMs are already Jev-style decision models – when and how to fine-tune them. *arXiv preprint arXiv:2610.02076*.

Zhijian Li, Stefan Larson, and Kevin Leach. 2024. Generating hard-negative out-of-scope data with ChatGPT for intent classification. In *Proceedings of LREC-COLING 2024*. ArXiv:2403.05640.

Jiachang Liu, Dinghan Shen, Yizhe Zhang, Bill Dolan, Lawrence Carin, and Weizhu Chen. 2022. What makes good in-context examples for GPT-3? In *Proceedings of Deep Learning Inside Out (DeeLIO 2022): The 3rd Workshop on Knowledge Extraction and Integration for Deep Learning Architectures*, pages 100–114.

Weitang Liu, Xiaoyun Wang, John D. Owens, and Yixuan Li. 2020. Energy-based out-of-distribution detection. In *Advances in Neural Information Processing Systems*. ArXiv:2010.03759.

Lefteris Loukas, Ilias Stogiannidis, Odysseas Diamantopoulos, Prodromos Malakasiotis, and Stavros Vassos. 2023. Making LLMs worth every penny: Resource-limited text classification in banking. In *Proceedings of the Fourth ACM International Conference on AI in Finance (ICAIF)*. ArXiv:2311.06102.

Neil A. Macmillan and C. Douglas Creelman. 2005. *Detection Theory: A User's Guide*, 2 edition. Lawrence Erlbaum Associates.

Aristides Milios, Siva Reddy, and Dzmitry Bahdanau. 2023. In-context learning for text classification with many labels. In *Proceedings of the 1st GenBench Workshop on (Benchmarking) Generalisation in NLP*. ArXiv:2309.10954.

Sewon Min, Xinxi Lyu, Ari Holtzman, Mikel Artetxe, Mike Lewis, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2022. Rethinking the role of demonstrations: What makes in-context learning work? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11048–11064. ArXiv:2202.12837.

Branislav Pecher, Ivan Srba, and Maria Bielikova. 2025. Comparing specialised small and general large language models on text classification: 100 labelled samples to achieve break-even performance. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 165–184. ArXiv:2402.12819.

Denis Peskov, Nancy Clarke, Jason Krone, Brigi Fodor, Yi Zhang, Adel Youssef, and Mona Diab. 2019. Multi-domain goal-oriented dialogues (MultiDoGO): Strategies toward curating and annotating large scale dialogue data. In *Proceedings of EMNLP-IJCNLP 2019*, pages 4526–4536.

Alexander Podolskiy, Dmitry Lipin, Andrey Bout, Ekaterina Artemova, and Irina Piontkovskaya. 2021. Revisiting Mahalanobis distance for transformer-based out-of-domain detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*. ArXiv:2101.03778.

Delip Rao and Chris Callison-Burch. 2026. Decision models vs. LLMs as rubric judges: Cheaper, faster, and wrong in the same places. *arXiv preprint arXiv:2609.29769*. Version 3; version 2 titled "JEV vs. LLMs as Rubric Judges: Cheaper, Faster, and Wrong in the Same Places".

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of EMNLP-IJCNLP*. ArXiv:1908.10084.

Stephen Robertson and Hugo Zaragoza. 2009. The probabilistic relevance framework: BM25 and beyond. *Foundations and Trends in Information Retrieval*, 3(4):333–389.

Carson Rodrigues and Oysturn Vas. 2026. When do LLMs replace fine-tuned NLU? a decision framework for intent detection in production conversational systems. *arXiv preprint arXiv:2608.20371*.

Yiyou Sun, Yifei Ming, Xiaojin Zhu, and Yixuan Li. 2022. Out-of-distribution detection with deep nearest neighbors. In *International Conference on Machine Learning*. ArXiv:2204.06507.

Lijuan Tang and Yuemeng Zheng. 2026. Typed decision models: An early evidence audit and evaluation checklist. *arXiv preprint arXiv:2609.32160*.

Lewis Tunstall, Nils Reimers, Unso Eun Seo Jo, Luke Bates, Daniel Korat, Moshe Wasserblat, and Oren Pereg. 2022. Efficient few-shot learning without prompts. *Preprint*, arXiv:2209.11055.

Orion Weller, Kathryn Ricci, Marc Marone, Antoine Chaffin, Dawn Lawrie, and Benjamin Van Durme. 2026. Seq vs Seq: An open suite of paired encoders and decoders. In *International Conference on Learning Representations*. ArXiv:2507.11412.

Eyup Halit Yilmaz and Cagri Toraman. 2022. D2U: Distance-to-uniform learning for out-of-scope detection. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2093–2108.

Álvaro Zaera, Diana Nicoleta Popa, Ivan Sekulic, and Paolo Rosso. 2025. Efficient out-of-scope detection in dialogue systems via uncertainty-driven LLM routing. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Industry Track)*, pages 328–335. ArXiv:2507.01541.

Hanlei Zhang, Hua Xu, and Ting-En Lin. 2021. Deep open intent classification with adaptive decision boundary. In *Proceedings of the AAAI Conference on Artificial Intelligence*. ArXiv:2012.10209.

Jiamu Zhang, Tianze Yang, Yucheng Shi, Evan Chen, Zixiang Nie, Kelly Wan, Liangjie Hong, Ninghao Liu, and Liang Wu. 2026. AnyJev technical report. *arXiv preprint arXiv:2610.00831*.

Jianguo Zhang, Kazuma Hashimoto, Yao Wan, Zhiwei Liu, Ye Liu, Caiming Xiong, and Philip S. Yu. 2022. Are pretrained transformers robust in intent classification? a missing ingredient in evaluation of out-of-scope intent detection. In *Proceedings of the 4th Workshop on NLP for Conversational AI*. ArXiv:2106.04564.

Tony Z. Zhao, Eric Wallace, Shi Feng, Dan Klein, and Sameer Singh. 2021. Calibrate before use: Improving few-shot performance of language models. In *International Conference on Machine Learning*. ArXiv:2102.09690.

## A Protocols, amendments and withdrawn conclusions

The confirmatory questions were chosen after more than twenty exploratory protocols on the same label sets. Six protocols govern this paper; each was committed before any of its requests, and each carries dated amendments. Their freeze times, their text as frozen and their item-list hashes are listed in `release/FREEZE_TABLE.md`; the times are the author's git commit timestamps. OpenRouter's own request log, exported by the author, dates the first hosted request after each freeze 4 to 17 seconds after it:

- `confirmatory_protocol.json`
- `retrieval_suppression_protocol.json`
- `jev_rerun_protocol.json`
- `retrieval_mechanism_protocol.json`
- `massive_robustness_protocol.json`
- `gh_protocol.json`

Within the confirmatory protocol, run A is Gemma, run B Qwen, run C Gemma with labelled out-of-scope rows in its pool, and run I the frontier models; run D is the retrieval-suppression protocol and run D2 the mechanism protocol. The amendments are:

- the frontier model was changed after Qwen3.8 2.4T refused requests with reasoning disabled;
- a plumbing-check cap was raised;
- DeepSeek V4 Pro was moved between hosts after rate limits;
- errata record the freshness problem (section 4) and the BANKING77-OOS label leak;
- run D's BANKING77-OOS items were fresh with respect to the BANKING77-OOS sessions only: 462 of its 1,077 items had appeared as confirmatory Banking77 turns, and 332 of its 1,700 CLINC single-domain items as confirmatory CLINC150 turns;
- before freezing D2, its CLINC single-domain in-scope items were allowed although they had served as run D's specialist development data (never sent to a model);
- D2 was switched to one process per model about an hour after its requests began (a request-loop change only; its note miscounts the finished cells), and the per-process caps together exceeded the run cap, which spend never approached;
- the cost figure stage of `confirmatory.py` was edited after the run (presentation only).

Two parallel processes briefly sent 76 duplicate requests, and spend was reconciled from saved rows. Every request of every experiment was answered; parse failures were zero in all runs.

Conclusions of our earlier drafts that these runs withdrew or narrowed:

1. that the retrieval-prompted model overtakes the classifier on Banking77, MASSIVE and CLINC150;
2. that the combination of the model's scope and the classifier's intent is significantly better on Banking77;
3. that the difference lies in the out-of-scope decision;
4. that BANKING77-OOS held-out requests resemble the retrieval pool more closely than CLINC single-domain ones (an artefact of the leak);
5. that Jev is a weak scope gate. That came from zero-shot runs on our exploratory sessions; with retrieval it is level with Gemma on two sets;
6. that the systems differ mainly in where they put the out-of-scope threshold (draft 3 abstract; contradicted by the pre-registered headline rule);

7. that restating the scope rule after the examples is a cheap general lever (it met the mitigation criterion for one of five models);

8. that labelled out-of-scope rows help only when they come from the tested domains (rows from other domains raise rejection for the requests that retrieve them);

9. that Gemma's host was slow throughout runs G and H (the saved latencies give medians of about one second).

Studies cut from this paper remain in the release record: typed state against stated decisions, model-to-model handoff, encoder against decoder, a local orchestrator, de-escalation and cascades between two general models.

## B Systems and prompts

**Settings.**

- **Prices and hosts:** prices are OpenRouter listings for the pinned host, 15–16 October 2026, with fallbacks off.
- **Retrieval:** BM25 with $k_1 = 1.5$ and $b = 0.75$ over lower-cased word tokens, top 20, listed least similar first as "message ⇒ code".
- **Specialist training:** learning rate and epochs chosen on development data from $\{2{\cdot}10^{-5}, 5{\cdot}10^{-5}, 10^{-4}, 2 \cdot 10^{-4}\} \times \{3, 6\}$, with seeds 20261007, 20261015 and 20261016.
- **Specialist scope detectors:** softmax, energy, Mahalanobis and tenth-nearest neighbour.
- **Specialist development data:** 400 in-scope and 100 out-of-scope items.
- **Prompts:** reproduced verbatim in the protocol files, together with the session sampler and its seeds.
- **Latency per call** on the confirmatory runs (p50 / p95 / p99, seconds): Gemma 1.0 / 8.8 / 40.0 (including a host slowdown), Qwen 2.3 / 10.7 / 13.3, Kimi K3 2.8 / 5.3 / 7.7, Claude Opus 5 1.2 / 2.0 / 4.2; the specialist 0.011 / 0.013 at batch size 1 on one RTX 5070, for an earlier Banking77 specialist without the scope detector. Saved latencies time the final attempt only: the outer back-off of 3 to 45 s after rate-limit replies is excluded, and retries were not logged. Gemma's 95th percentile on Banking77 was 29 s in run A and 53.5 s in run C, and at most 2.3 s on the other sets (per set in table 7). Jev's latency was not recorded in the frozen runs.

## C Frontier models and cost

Kimi K3 (2.8T parameters, open weights) and Claude Opus 5 answered the first 100 sessions of each set with the same prompt and reasoning off. Both also reject under 10% of MASSIVE *play* requests. The cascade still calls Gemma on 40% of turns, so it pays for hosting the specialist only above about 79,000 to 177,000 sessions a month.

## D Sensitivity analyses

Table 9 gives the pre-registered sensitivity of the specialist's threshold rule and three post hoc analyses requested in review. Gemma leads on Banking77 and CLINC150 under every threshold rule, seed and endpoint weight shown. On MASSIVE the difference favours the specialist for every seed but varies in size, and its sign depends on the weight given to out-of-scope turns: Gemma's point estimate is ahead when that weight is 10% or less, and the specialist is clearly ahead from 30% up, because Gemma rejects only 23% of the held-out-domain requests. The cascade's escalated turns cost 39.6 to 39.9% of Gemma's API cost per set (post hoc, from the billed cost of those turns), so the 40% figure holds. The primary test has 77, 21 and 150 in-scope intent clusters and 184, 243 and 185 single-turn out-of-scope clusters on Banking77, MASSIVE and CLINC150. Code: `src/bakeoff/posthoc_round6.py`.

## E Post hoc analyses

**Mitigation rules.** Accepting only when the specialist also accepts recovers 42 to 96% of the loss at 2.0 to 3.0 in-scope points; a similarity floor costs 11 to 16 points; both fail the criterion on held-out intents that the development items did not cover. The full tables are in `docs/posthoc-round3.md` and `docs/posthoc-round3b.md`. The development out-of-scope items covered 5 of the 27 held-out test intents on BANKING77-OOS, and 2 of 5 per CLINC single-domain domain. The specialist rejects 64.8% of covered-intent requests against 44.5% of uncovered ones. On uncovered intents only:

| Information | Specialist | General models | Jev |
|---|---|---|---|
| In-scope training rows | fine-tuning | 20 BM25-retrieved rows per request | the same 20 rows |
| 400 development in-scope items | temperature and threshold | none | none |
| 100 development out-of-scope items | detector choice and threshold | none | none |
| Labelled out-of-scope rows | only in run C's secondary arm | only in run C (250 rows in the pool) | none |
| Label names | none (class indices) | listed with codes; examples show codes | offered as options |
| Scope decision | prior-weighted threshold on a detector score | yes/no in the reply | fixed 0.5 threshold |

Table 5: Information each system uses in the confirmatory comparison. All systems share the in-scope training rows; only the specialist calibrates its scope decision on out-of-scope development items.

| Model | Host | Precision | Price, $ per million input / output |
|---|---|---|---|
| Gemma 4 31B | Novita | bf16 | 0.14 / 0.40 |
| Qwen3.5 27B | Alibaba | not stated | 0.195 / 1.56 |
| Llama 3.3 70B | DeepInfra | fp8 | 0.10 / 0.32 |
| DeepSeek V4 Pro | StreamLake | fp8 | 0.955 / 1.911 |
| Kimi K3 | Moonshot AI | mxfp4 | 3 / 15 |
| Claude Opus 5 | Anthropic | not stated | 5 / 25 |
| Jev 1.13.0 | TypeSafe | not stated | not reported per call |

Table 6: Hosted systems: the pinned host, the precision it reports and its OpenRouter list price, 15–16 October 2026 (Jev is billed by TypeSafe directly).

- **Classifier veto** (accept only if the specialist also accepts): recovers 42 to 96% of the lost rejection on BANKING77-OOS, at 2.0 to 3.0 points of in-scope accuracy, with every interval extending below $-2$.
- **Similarity floor:** costs 11 to 16 points.
- **Neighbour-label rule:** changes little.

**Sibling labels (D2, BANKING77-OOS, retrieval).** Gemma's accepted held-out requests go mostly to sibling labels: verify my identity and unable to verify identity to *why verify identity* (17 and 16), pin blocked to *change pin* (15), top-up by bank transfer charge to *transfer fee charged* (10). The chosen label is among the 20 retrieved labels for 92 to 99% of accepted held-out requests and is the top-1 neighbour's label for 43 to 58% (four general models). Split at the median concentration of the retrieved labels, rejection falls by 30 against 18 points (Gemma), 29 against 8 (Qwen), 25 against 23 (Llama) and 30 against 22 (DeepSeek).

**Label audit.** BANKING77-OOS was matched to the original Banking77 labels after lowercasing:

- 366 mislabelled training rows, of which 145 are leaked held-out intents;
- 32 in-scope test items with wrong gold intents;
- 36 "held-out" test items that are in-scope intents by their original labels.

Our files are byte-identical to the upstream release.

## F Run D2 details

**Signal detection.** As an aggregate description we treat scope as a detection task (Macmillan and Creelman, 2005), separating discrimination ($d'$) from the criterion ($c$, readiness to accept). On run D's leak-free subset of BANKING77-OOS, retrieval moves the four general models' criterion towards acceptance by 0.7 to 1.1 standard deviations. On the D2 items, allowing unequal variances (zROC slopes 0.6 to 1.25), discrimination improves for Llama and DeepSeek at every slope, while for Gemma and Qwen the sign of the change depends on the slope.

**Option count.** With CLINC single-domain's two domains pooled into one 20-option prompt, retrieval lowers rejection by 14 to 25 points for Gemma (43 to 29%), Llama (45 to 20%) and DeepSeek (34 to 16%), by 5 points for Jev, and not for Qwen. The difference from the 10-option prompts is Holm-significant only for Llama ($-29$

| Latency per call, p50 / p95 (s) | Banking77 | MASSIVE | CLINC150 |
|---|---|---|---|
| Gemma 4 31B, no rows (run A) | 1.01 / 28.9 | 0.88 / 1.79 | 1.01 / 2.29 |
| Gemma 4 31B, with rows (run C) | 1.11 / 53.5 | 0.83 / 1.81 | 0.89 / 1.56 |
| Qwen3.5 27B (run B) | 3.64 / 12.5 | 1.33 / 10.3 | 2.25 / 4.83 |
| Kimi K3 (first 100 sessions) | 2.83 / 6.10 | 2.96 / 5.28 | 2.81 / 4.79 |
| Claude Opus 5 (first 100 sessions) | 1.16 / 2.56 | 1.52 / 1.95 | 1.08 / 1.58 |

Table 7: Latency per call by set on the confirmatory runs. Each figure times the final attempt only; back-off after rate-limit replies is excluded. Gemma's Banking77 tail reflects a host slowdown during those runs.

| Set (first 100 sessions) | Specialist | Gemma 4 31B | Kimi K3 | Claude Opus 5 | Uncached cost, multiple of Gemma (Kimi / Opus) |
|---|---|---|---|---|---|
| Banking77 | 93.0 | 95.0 | 95.9 | 95.9 | 20.5 / 44.1 |
| MASSIVE | 80.4 | 78.5 | 79.0 | 77.2 | 21.3 / 43.0 |
| CLINC150 | 93.2 | 95.9 | 95.1 | 97.6 | 17.4 / 36.1 |

Table 8: Frontier models on the first 100 sessions of each set: weighted turn accuracy (%) of each system on the same turns, and API cost as a multiple of Gemma's. Cost multiples use the mean uncached list-price cost per call (the frontier models on the first 100 sessions, Gemma on its full run A), times the set's mean turns per session.

points, $p = .04$), but with eight held-out-intent clusters and Holm over five models, .04 is the smallest attainable adjusted $p$. The pooled prompt also adds sibling labels from the other domain, mixes the retrieval pools and changes the desk description, and its effect differs in sign between the two domains, so this arm does not isolate option count.

## G MASSIVE robustness (sensitivity analysis)

**Confirmatory draw (post hoc).** Without MASSIVE's catch-all *general quirky* intent, which supplies 2.4 of the specialist's 7.1-point in-scope deficit, the specialist is 6.1 points ahead ($p = .001$). Clustering out-of-scope turns by their source label instead of by turn, the specialist − Gemma difference has $p = .55$. In run C, the same rows offered to the specialist were used by its development-selected rule only on MASSIVE, where the two were level ($-1.8$, $p = .54$); clustering run C's out-of-scope turns by source label, its rows effect has $p = .03$. A one-sentence scope instruction did not help significantly ($+1$ to $+2$ points for Gemma).

**Further draws.** A frozen protocol (`massive_robustness_protocol.json`) drew three further sets of three held-out test domains: alarm, play and social; calendar, iot and play; audio, takeaway and weather. Each draw also held out three domains that supplied labelled out-of-scope rows. Each draw has 1,000 in-scope and 250 out-of-scope test utterances, and the specialist was retrained per draw.

## H Example order and contamination (runs G and H)

A frozen protocol (`gh_protocol.json`) re-ran Gemma on the confirmatory CLINC150 and MASSIVE turns with the 20 retrieved examples most similar first and in a random order, in addition to the original least-similar-first order. Weighted accuracy ranged over 0.16 points on CLINC150 and 0.41 on MASSIVE; 0.6 to 4.5% of answers changed. A contamination probe asked Gemma and Qwen to complete the second half of 200 Banking77 and 200 CLINC150 test utterances. Gemma completed 0.5% verbatim. Its completions resembled their own endings more than other endings of the same intent (token F1 0.18 against 0.08 on Banking77); this probe cannot tell that apart from memorisation. Qwen refused 350 of 400 requests, so its rows say little. The preregistered criterion for memorisation (a significant own-ending advantage and more than 5% verbatim) was not met.

## I Exploratory record

On our earlier sessions, a model retrieving from exactly the rows the specialist was trained on was never significantly behind it at any training-set size. This used one seed, one model, and a pool with out-of-scope rows. At one example per intent no specialist was usable, while nearest-neighbour and centroid classifiers on the same rows got 14% of Banking77 sessions against about 49% for the retrieval-prompted model.

On MultiDoGO support chats (Peskov et al., 2019), the specialist was more accurate on the





Figure 5: Weighted turn accuracy against API cost per 1,000 sessions at uncached list prices; the dashed line is the frontier of systems with an API cost. The specialist has no API cost and is drawn in the shaded off-scale band; its hosting cost is not shown. Jev is not shown because its API does not report a per-call price.

dataset's "out of domain" label and, by under one point, on its dialogue-act labels. Gemma was more accurate on task intents; Qwen 27B's difference there was not significant.

| *(a) Pre-registered: specialist threshold set for an out-of-scope rate of* | | | | | | |
|---|---|---|---|---|---|---|
| Set | 10% | 20% (primary) | 30% | | | |
| Banking77 | $-1.78$ (.008) | $-1.42$ (.037) | $-1.25$ (.064) | | | |
| MASSIVE | $+2.50$ (.046) | $+4.42$ (.171) | $+3.82$ (.417) | | | |
| CLINC150 | $-1.89$ (.001) | $-1.89$ (.001) | $-1.63$ (.011) | | | |
| *(b) Post hoc: each specialist seed against Gemma* | | | | | | |
| Set | Seed 20261007 | Seed 20261015 | Seed 20261016 | Mean of seeds | | |
| Banking77 | $-1.04$ (.131) | $-1.24$ (.119) | $-1.98$ (.012) | $-1.42$ (.037) | | |
| MASSIVE | $+5.85$ (.009) | $+1.33$ (.875) | $+6.10$ (.003) | $+4.42$ (.171) | | |
| CLINC150 | $-2.35$ ($p < .001$) | $-1.85$ (.008) | $-1.47$ (.033) | $-1.89$ (.001) | | |
| *(c) Post hoc: out-of-scope weight $\pi$ in the endpoint $(1-\pi)C + \pi R$* | | | | | | |
| Set | $\pi = 0.05$ | 0.1 | 0.2 (primary) | 0.3 | 0.4 | 0.5 |
| Banking77 | $-0.97$ (.178) | $-1.12$ (.109) | $-1.42$ (.037) | $-1.72$ (.015) | $-2.02$ (.009) | $-2.31$ (.008) |
| MASSIVE | $-5.55$ (.109) | $-2.22$ (.579) | $+4.42$ (.171) | $+11.07$ ($p < .001$) | $+17.72$ ($p < .001$) | $+24.37$ ($p < .001$) |
| CLINC150 | $-2.11$ ($p < .001$) | $-2.04$ ($p < .001$) | $-1.89$ (.001) | $-1.74$ (.019) | $-1.60$ (.095) | $-1.45$ (.216) |

Table 9: Specialist − Gemma in weighted points (unadjusted sign-flip $p$) on the confirmatory sessions. (a) The pre-registered sensitivity of the specialist's threshold rule; Gemma's answers do not change. (b) Each seed's specialist alone; the paper's specialist is the per-turn mean over seeds. (c) The specialist's threshold rule stays at 20%; $C$ is the share of in-scope turns kept with the right intent and $R$ the share of out-of-scope turns rejected.

| Weighted accuracy / held-out rejected (%) | Draw 1 | Draw 2 | Draw 3 | Original |
|---|---|---|---|---|
| Specialist | 83.1 / 80.0 | 83.1 / 72.8 | 82.3 / 90.8 | 78.3 / 80.7 |
| Gemma, no rows | 84.1 / 68.0 | 84.7 / 62.8 | 82.0 / 61.2 | 73.8 / 23.0 |
| Gemma, rows from the tested domains | 89.7 / 94.8 | 89.8 / 90.4 | 88.5 / 95.6 | 87.2 / 90.5 |
| Gemma, rows from other domains | 86.1 / 76.8 | 85.5 / 68.8 | 82.3 / 66.4 | – |
| Gemma, instruction | 85.5 / 82.4 | 85.8 / 78.4 | 84.0 / 80.8 | 75.3 / 42.4 |
| Qwen 27B, no rows | 86.5 / 82.8 | 85.3 / 72.8 | 84.2 / 81.6 | 80.8 / 68.3 |
| Jev, no rows | 84.6 / 70.4 | 83.9 / 56.4 | 78.5 / 47.6 | 77.8 / 44.0 |

Table 10: MASSIVE robustness: weighted turn accuracy and the share of held-out-domain requests rejected (%) for three further draws of held-out domains and the original confirmatory draw. The specialist was retrained per draw; "rows" are labelled out-of-scope rows in Gemma's retrieval pool.