

Improving Group Fairness in Knowledge Distillation via Laplace Approximation of Early Exits

Edvin 24V0074 Sagar 24D0367

CS 769

Optimization in Machine Learning

2 May 2025

1. Recap from Seminar
2. Experiments And Results
3. Analysis And Future Work

Section Overview

1. Recap from Seminar
2. Experiments And Results
3. Analysis And Future Work

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student
- Teacher Provides "Soft Targets"

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student
- Teacher Provides "Soft Targets"
- Loss: kl divergence + cross-entropy

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student
- Teacher Provides "Soft Targets"
- Loss: kl divergence + cross-entropy
- Student model relies on spurious correlations

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student
- Teacher Provides "Soft Targets"
- Loss: kl divergence + cross-entropy
- Student model relies on spurious correlations
- Student's early Layers overconfident on hard instances

Recap from Seminar

- Knowledge Distillation as an effective way to distill knowledge from teacher to student
- Teacher Provides "Soft Targets"
- Loss: kl divergence + cross-entropy
- Student model relies on spurious correlations
- Student's early Layers overconfident on hard instances
- DEDIER loss

$$\mathcal{L}_{student} = \sum_{D_w} (1 - \lambda) \cdot l_{ce} + \lambda \cdot \mathbf{wt} \cdot l_{kd}$$

where $\mathbf{wt} = \exp^{\beta \cdot \mathbf{cm} \cdot \alpha}$ and $\mathbf{cm}(\mathbf{p}) = \mathbf{p}_{\max} - \max_{\mathbf{p}_k \in \mathbf{p} - \mathbf{p}_{\max}} \mathbf{p}_k$

Recap from Seminar

- Two alternate approaches for estimating uncertainty in prediction in early exit layers.

Recap from Seminar

- Two alternate approaches for estimating uncertainty in prediction in early exit layers.
- [Meronen et al., 2023] used Laplace approximation for bayesian posterior at exit layer.

Recap from Seminar


- Two alternate approaches for estimating uncertainty in prediction in early exit layers.
- [Meronen et al., 2023] used Laplace approximation for bayesian posterior at exit layer.
- [Jazbec et al., 2024] used AVCS based on Predictive-likelihood ratio to get confidence intervals for predictions.

Recap from Seminar

- Two alternate approaches for estimating uncertainty in prediction in early exit layers.
- [Meronen et al., 2023] used Laplace approximation for bayesian posterior at exit layer.
- [Jazbec et al., 2024] used AVCS based on Predictive-likelihood ratio to get confidence intervals for predictions.
- Experiment: Laplace Approximation based uncertainty estimate to reweight both the losses.

Recap from Seminar

Figure:




Recap from Seminar

Figure:




Recap from Seminar

Figure:



Recap from Seminar

Figure:



Recap from Seminar

- Bayesian treatment of parameters

$$p(\boldsymbol{\theta} \mid \mathcal{D}_{\text{train}}) = \frac{p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) p(\boldsymbol{\theta})}{\int_{\boldsymbol{\theta}} p(\mathcal{D}_{\text{train}}, \boldsymbol{\theta}) d\boldsymbol{\theta}} = \frac{[\text{likelihood}] \times [\text{prior}]}{[\text{model evidence}]}$$

Recap from Seminar

- Bayesian treatment of parameters

$$p(\boldsymbol{\theta} \mid \mathcal{D}_{\text{train}}) = \frac{p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) p(\boldsymbol{\theta})}{\int_{\boldsymbol{\theta}} p(\mathcal{D}_{\text{train}}, \boldsymbol{\theta}) d\boldsymbol{\theta}} = \frac{[\text{likelihood}] \times [\text{prior}]}{[\text{model evidence}]}$$

- MAP estimate can be found by maximising the unnormalised posterior:

$$\hat{\boldsymbol{\theta}} = \arg \max_{\boldsymbol{\theta}} \log p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) + \log p(\boldsymbol{\theta})$$

Recap from Seminar

- Bayesian treatment of parameters

$$p(\boldsymbol{\theta} \mid \mathcal{D}_{\text{train}}) = \frac{p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) p(\boldsymbol{\theta})}{\int_{\boldsymbol{\theta}} p(\mathcal{D}_{\text{train}}, \boldsymbol{\theta}) d\boldsymbol{\theta}} = \frac{[\text{likelihood}] \times [\text{prior}]}{[\text{model evidence}]}$$

- MAP estimate can be found by maximising the unnormalised posterior:

$$\hat{\boldsymbol{\theta}} = \arg \max_{\boldsymbol{\theta}} \log p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) + \log p(\boldsymbol{\theta})$$

- Gaussian distribution via laplace approximation

$$p(\hat{\mathbf{z}}_i \mid \mathbf{x}_i) = \mathcal{N}(\hat{\mathbf{W}}_{\text{MAP}}^{\top} \hat{\boldsymbol{\phi}}_i, (\hat{\boldsymbol{\phi}}_i^{\top} \mathbf{V} \hat{\boldsymbol{\phi}}_i) \mathbf{U})$$
$$\mathbf{V}^{-1} \otimes \mathbf{U}^{-1} = \mathbf{H}^{-1}$$

Recap from Seminar

- Bayesian treatment of parameters

$$p(\boldsymbol{\theta} \mid \mathcal{D}_{\text{train}}) = \frac{p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) p(\boldsymbol{\theta})}{\int_{\boldsymbol{\theta}} p(\mathcal{D}_{\text{train}}, \boldsymbol{\theta}) d\boldsymbol{\theta}} = \frac{[\text{likelihood}] \times [\text{prior}]}{[\text{model evidence}]}$$

- MAP estimate can be found by maximising the unnormalised posterior:

$$\hat{\boldsymbol{\theta}} = \arg \max_{\boldsymbol{\theta}} \log p(\mathcal{D}_{\text{train}} \mid \boldsymbol{\theta}) + \log p(\boldsymbol{\theta})$$

- Gaussian distribution via laplace approximation

$$p(\hat{\mathbf{z}}_i \mid \mathbf{x}_i) = \mathcal{N}(\hat{\mathbf{W}}_{\text{MAP}}^{\top} \hat{\boldsymbol{\phi}}_i, (\hat{\boldsymbol{\phi}}_i^{\top} \mathbf{V} \hat{\boldsymbol{\phi}}_i) \mathbf{U})$$
$$\mathbf{V}^{-1} \otimes \mathbf{U}^{-1} = \mathbf{H}^{-1}$$

- Samples

$$\hat{\mathbf{z}}_i^{(l)} = \hat{\mathbf{W}}_{\text{MAP}}^{\top} \hat{\boldsymbol{\phi}}_i + (\hat{\boldsymbol{\phi}}_i^{\top} \mathbf{V} \hat{\boldsymbol{\phi}}_i)^{\frac{1}{2}} (\mathbf{L} \mathbf{g}^{(l)})$$

$\mathbf{g}^{(l)} \sim \mathcal{N}(0, \mathbf{I})$ and \mathbf{L} is the Cholesky factor of \mathbf{U}

Section Overview

1. Recap from Seminar
2. Experiments And Results
3. Analysis And Future Work

- The MultiNLI dataset [Williams et al., 2018] was used


Experiments And Results

Figure:




Experiments And Results

Figure:



Experiments And Results

Figure:



Section Overview

1. Recap from Seminar
2. Experiments And Results
3. Analysis And Future Work

References



Jazbec, M., Forré, P., Mandt, S., Zhang, D., and Nalisnick, E. (2024).
Early-Exit Neural Networks with Nested Prediction Sets.
arXiv:2311.05931 [cs, stat].



Meronen, L., Trapp, M., Pilzer, A., Yang, L., and Solin, A. (2023).
Fixing Overconfidence in Dynamic Neural Networks.
Version Number: 4.



Williams, A., Nangia, N., and Bowman, S. R. (2018).
A broad-coverage challenge corpus for sentence understanding through inference.
In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1112–1122. Association for Computational Linguistics.