Hashmaps & Tries - Class 2

Special class

Love Babbar • May 31, 2023

Tries:

D.S

Definition

Multi-way Tree structure

pattern - searching



pattern length

$\propto$ time complexity


RAMESH
root
LOVER
DADA
21
A-2
CARE
strings
LOVE
LOVELY
DAD
CAR
DADDY
DAADI
DAADDI
C
D
V
E
A
A
L
Y
R
D
E
D
Y
A
D
D
I
I
A


node present
to waha chalo
jaao
node observed
create karo
&
chale jao
root
Strings
CODE
CODER
CODEHELP
CODING
LEETCODE
LAXMI
CALLING
BABBAR
INDIA
SUPREME
return
CODEWORD
CODE
Trimmed
INDIA
L-C
Fals


Insertion
node present
node pe
chale jao
node absent
node create
karo
node pr
jao


char data
Node* arr[26]
isTerminal
a
Constructor (characters
false
N



CODER

ODER

DER

ER

R


root
'\0'
root
C
root
O
root
D
E
root->children[index] != NULL
CODING
ODING
DING
ING
NG
G
root
I
root
N
root
G
Terminal


data = 10
a b c
0 1 2 3 — — — 25


data = '10'
0 1 2 3 25
data = 'C'
data = 0
data = 2D
data = L
CODE
CODING
substr(1)
ODING
DING
ING


root
children
data = '\0'
isTerminal
false
char = 'c'
index = 'c' - 'A'
root
data
isTerminal
parent
false
children
TrieNode
root
children
data
isTerminal
false
root
data
'D'
isTerminal
false
(root = '\0', DING)
(root = 'c', DING)
(root = 'o', DING)
(root = 'd', DING)
True
"\0" -> a, 1 -> b, 2 -> c ... 25 -> z



CODE

COBER

CODEMELP


0
1
x
!x
z

W. Layer = L

T.C → O(L)


Deletion
remove(root, "coding")
search coding
but Hierarchy
Terminal
false
H/W