

# Populating column-oriented databases

INTRODUCTION TO NOSQL

SQL

**Jake Roach**  
Data Engineer


# Populating row-oriented vs. column-oriented databases

## Row-oriented:


- Optimized for transactional use-cases
- Best performance when inserting, updating or deleting individual records

## Column-oriented:

- Use for analytics workflows
- Perform well when loading, updating, or deleting data in-bulk



# CREATE TABLE



```
CREATE TABLE books (  
    title VARCHAR(100),  
    author VARCHAR(100),  
    price FLOAT  
);
```

# COPY INTO

```
COPY INTO books
FROM 'file:///data_science_books.csv'
FILE_FORMAT = (
  TYPE = 'CSV'
  FIELD_DELIMITER = ','
  SKIP_HEADER = 1
);
```

COPY INTO

FROM

- Cloud storage location
- URL
- Staged files

FILE\_FORMAT

- Type of file, delimiter, other metadata information

<sup>1</sup> <https://docs.snowflake.com/en/sql-reference/sql/copy-into-table>

# CREATE TABLE ... AS

```
CREATE TABLE premium_books AS
SELECT *
FROM books
WHERE price > 50.00;
```

```
CREATE OR REPLACE TABLE premium_books AS
SELECT *
FROM books
WHERE price > 50.00;
```

CREATE TABLE ... AS

- Provide a table name
- Creates table in the current schema

SELECT ...

- Populates table with data returned by query

OR REPLACE

- If there is an existing table, it is replaced by new table

<sup>1</sup> <https://docs.snowflake.com/en/sql-reference/sql/create-table>

# Let's practice!

INTRODUCTION TO NOSQL

# Advanced column-oriented database techniques

INTRODUCTION TO NOSQL

SQL

Jake Roach  
Data Engineer

# Micro-partitioning data with Snowflake

## Micro-partitioning:

- Creates smaller "chunks" of rows, stored in columnar format
- Stores metadata about each partition

## Allowing for:

- Query pruning to reduce the amount of data accessed
- Efficient execution of DML (data manipulation language)

<sup>1</sup> <https://docs.snowflake.com/en/user-guide/tables-clustering-micropartitions>



# Micro-partitioning data

title	author	pages	price
R for Dummies	de Vries	432	17.99
Data for All	Thompson	230	49.99
Python Cookbook	NULL	704	51.48
The Art of Data Science	Peng	170	20.00
Emotional Data	Jame	24	4.99
Integrating Data	Inmon	134	19.95

metadata	title	author	pages	price
	Integrating Data	Inmon	134	19.95
	Python Cookbook	NULL	704	51.48
	Data for All	Thompson	230	49.99

metadata	title	author	pages	price
	R for Dummies	de Vries	432	17.99
	Emotional Data	Jame	24	4.99
	The Art of Data Science	Peng	170	20.00

# Data clustering with Snowflake

## Data clustering:

- Organizing or grouping similar data points together
- Automatically performed during data load

## Allowing for:

- Decreasing data accessed during execution
- Improved query performance

<sup>1</sup> <https://docs.snowflake.com/en/user-guide/tables-clustering-micropartitions>

# Data clustering

Data is clustered by price column

cluster key

metadata	title	author	pages	price
	Integrating Data	Inmon	134	19.95
	Python Cookbook	NULL	704	51.48
	Data for All	Thompson	230	49.99

metadata	title	author	pages	price
	Integrating Data	Inmon	134	19.95
	Data for All	Thompson	230	49.99
	Python Cookbook	NULL	704	51.48

metadata	title	author	pages	price
	R for Dummies	de Vries	432	17.99
	Emotional Data	Jame	24	4.99
	The Art of Data Science	Peng	170	20.00

metadata	title	author	pages	price
	Emotional Data	Jame	24	4.99
	R for Dummies	de Vries	432	17.99
	The Art of Data Science	Peng	170	20.00

# Query pruning

The query manager first looks in the first cluster, then second. In this case there no rows greater than 25 in second micro partition.  
Supported by columnar database (Clustering).

**SELECT**

title,  
author,  
price

**FROM** books

**WHERE**

price > 25.00;

metadata	title	author	pages	price
	Integrating Data	Inmon	134	19.95
	Data for All	Thompson	230	49.99
	Python Cookbook	NULL	704	51.48

metadata	title	author	pages	price
	Emotional Data	Jame	24	4.99
	R for Dummies	de Vries	432	17.99
	The Art of Data Science	Peng	170	20.00

Micro-partitioning and data clustering allow for:

- Reducing data scanned
- Fast time-to-insights

Second partition of the data doesn't contain value greater than 25, then they are pruned.

Supported by data partitioning.

# Let's practice!

INTRODUCTION TO NOSQL

# Analytics workflows for column-oriented databases

INTRODUCTION TO NOSQL

SQL

Jake Roach  
Data Engineer

# Common table expressions with Snowflake

Name, subqueries, temp tables using with keyword.

## Common table expressions (CTEs):

- Named sub-queries/temporary tables, defined using the `WITH` keyword
- Creates a object that can be later queried
- Reduce the amount of data that is being queried and/or `JOIN` 'ed
- More modular, easier to troubleshoot

```
WITH <cte-name> AS (  
    SELECT  
        . . . .  
    FROM <table-name>  
    [JOIN | WHERE | ...]  
)  
  
SELECT  
    . . .  
FROM <cte-name>;
```

<sup>1</sup> <https://docs.snowflake.com/en/user-guide/queries-cte>

# Writing common table expressions

```
WITH premium_books AS (  
  SELECT  
    title,  
    author,  
    avg_reviews  
  FROM books  
  WHERE price > 25.00  
)  
SELECT  
  author,  
  MIN(avg_reviews) AS min_avg_reviews,  
  MAX(avg_reviews) AS max_avg_reviews  
FROM premium_books  
GROUP BY author;
```

- Creating a `premium_books` temporary object
- Using `premium_books` downstream

Can creating multiple temporary objects:

```
WITH  
  <first-name> AS (...),  
  <second-name> AS (...),  
  ...  
  ...  
;
```



# Views with Snowflake

## Views:

- Allow query results to be accessed like a table
- Non-materialized and materialized

```
CREATE VIEW <view-name> AS
SELECT
    ...
FROM <table-name>
[WHERE | JOIN | ...];
```

# Creating views with Snowflake

```
CREATE VIEW premium_books AS
  SELECT
    title,
    author,
    avg_reviews
  FROM books
  WHERE price >= 25.00;
```

**Non Materialized.**

```
SELECT * FROM premium_books;
```

- Query executes when `premium_books` is called
- "Named definition" of a query

```
CREATE MATERIALIZED VIEW premium_books AS
  SELECT
    title,
    author,
    avg_reviews
  FROM books
  WHERE price >= 25.00;
```

```
SELECT * FROM premium_books;
```

- Results are stored upon execution
- Better query performance, requires refreshing

# Let's practice!

INTRODUCTION TO NOSQL

# Working with semi-structured data in Snowflake

INTRODUCTION TO NOSQL

SQL

Jake Roach  
Data Engineer

# Semi-structured data in Snowflake

```
{  
  "ISBN_13": "978-1685549596",  
  "publisher": "Notion Press Media",  
  "size": {  
    "dimensions": "8.5 x 1.01 x 11 inches",  
    "weight": "2.53 pounds"  
  }  
}
```

- Allows data to be stored in "raw" format
- **VARIANT** type
- Store each object in a single column

# Semi-structured data types in Snowflake

Snowflake also supports the **OBJECT** and **ARRAY** types

- **OBJECT** is similar to dictionaries in Python
- **ARRAY** is similar to lists in Python

## **VARIANT** type

- Stores semi-structured data in a single column

library
<pre>{   "ISBN_13": "978-1685549596",   "publisher": "Notion Press Media",   "size": {     "dimensions": "8.5 x 1.01 x 11 inches",     "weight": "2.53 pounds"   } } {   "ISBN_13": "978-0596153939",   "publisher": "O'Reilly Media",   "size": {     "dimensions": "8 x 0.98 x 9.25 inches",     "weight": "1.96 pounds"   } }</pre>

# Querying semi-structured data with bracket notation

library
<pre>{   "ISBN_13": "978-1685549596",   "publisher": "Notion Press Media",   "size": {     "dimensions": "8.5 x 1.01 x 11 inches",     "weight": "2.53 pounds"   } }</pre>
<pre>{   "ISBN_13": "978-0596153939",   "publisher": "O'Reilly Media",   "size": {     "dimensions": "8 x 0.98 x 9.25 inches",     "weight": "1.96 pounds"   } }</pre>

Query:

```
SELECT  
  library['ISBN_13']  
FROM books;
```

Result:

library['ISBN_13']
"978-1685549596"
"978-0596153939"

# Querying semi-structured data with dot notation

library
<pre>{   "ISBN_13": "978-1685549596",   "publisher": "Notion Press Media",   "size": {     "dimensions": "8.5 x 1.01 x 11 inches",     "weight": "2.53 pounds"   } }</pre>
<pre>{   "ISBN_13": "978-0596153939",   "publisher": "O'Reilly Media",   "size": {     "dimensions": "8 x 0.98 x 9.25 inches",     "weight": "1.96 pounds"   } }</pre>

Query:

```
SELECT
  library:ISBN_13,
  library:publisher
FROM books;
```

Result:

library:ISBN_13	library:publisher
"978-1685549596"	"Notion Press Media"
"978-0596153939"	"O'Reilly Media"



# Querying nested semi-structured data

library

```
{
  "ISBN_13": "978-1685549596",
  "publisher": "Notion Press Media",
  "size": {
    "dimensions": "8.5 x 1.01 x 11 inches",
    "weight": "2.53 pounds"
  }
}
{
  "ISBN_13": "978-0596153939",
  "publisher": "O'Reilly Media",
  "size": {
    "dimensions": "8 x 0.98 x 9.25 inches",
    "weight": "1.96 pounds"
  }
}
```

**SELECT**

```
library:ISBN_13,
library:size.dimensions,
library:size.weight,
```

**FROM** books;

**SELECT**

```
library["ISBN_13"],
library["size"]["dimensions"],
library["size"]["weight"],
```

**FROM** books;

library:ISBN_13	library:size:dimensions	library:size:weight
"978-1685549596"	"8.5 x 1.01 x 11 inches"	"2.53 pounds"
"978-0596153939"	"8 x 0.98 x 9.25 inches"	"1.96 pounds"

# Let's practice!

INTRODUCTION TO NOSQL