

Introducing Classes (Chapter 6 of Schilit)

Object Oriented Programming BS (CS/SE) II

By

Abdul Haseeb

Class Fundamentals

- Core of Java
- Basic foundation of OOP
- Until now you just saw a class which encapsulates main, to demonstrate basics of java
- Class is a template:
 - Defines a data type
 - Create multiple objects using that data type
- Object is an instance of class

General Form of class

```
class classname {  
    type instance-variable1;  
    type instance-variable2;  
    // ...  
    type instance-variableN;  
  
    type methodname1(parameter-list) {  
        // body of method  
    }  
    type methodname2(parameter-list) {  
        // body of method  
    }  
    // ...  
    type methodnameN(parameter-list) {  
        // body of method  
    }  
}
```

Class Basics

- Contains code and data
- Code and data to gather are called members of a class
- Code organized inside methods
- Variables of class are called Instance variables
 - Because each object will have a different copy of these values

A Simple Class — Code

- Box with only data

```
class Box {  
    double width;  
    double height;  
    double depth;  
}
```

A Simple Class — Code

- Two Objects of Box

Use dot operator to access and assign
instance variables and methods

How many .class files will be created?

Task

- Create a student datatype having id and name and create two instances of it

Declaring Objects




Figure 6-1 Declaring an object of type **Box**


New Operator

- Creates object of a class, and allocates memory to it
- Performs dynamic allocation (at run time)
- Here classname() refers to constructor
 - Specify what should happen when object is created
 - If no constructor is provided, java provides default constructor

- Both point to same object
- Changes in one affect the others

```
Box b1 = new Box();  
Box b2 = b1;
```

Object Reference Variables and use of *null*



Unhooking through the use of null

```
Box b1 = new Box();  
Box b2 = b1;  
// ...  
b1 = null;
```

Here, **b1** has been set to **null**, but **b2** still points to the original object.

Introducing Methods

```
type name(parameter-list) {  
    // body of method  
}
```

Inserting the volume method to box class

- Call it with box1
- Call it with box2
- You will notice that when we call instance variables inside a method:
 - No Need to use object reference
- When returning a value:
 - Make sure the return data and method return type are compatible:

Use a method which returns some value