

6. Demonstrate lazy collection in Hibernate

Source Code:

```
DROP TABLE IF EXISTS `colors`;

/*!40101 SET @saved_cs_client    = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `colors` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `color_name` varchar(40) DEFAULT NULL,
  `idx` int(11) DEFAULT NULL,
  `product_id` bigint(20) DEFAULT NULL,
  PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;


LOCK TABLES `colors` WRITE;

/*!40000 ALTER TABLE `colors` DISABLE KEYS */;

INSERT INTO `colors` VALUES
(1,'Red',0,1),(2,'Silver',1,1),(3,'Gray',0,2),(4,'White',1,2),(5,'Maroon',0,3);• /*!40000 ALTER
TABLE `colors` ENABLE KEYS */;

UNLOCK TABLES;


--

-- Table structure for table `eproduct`

--
```

```

DROP TABLE IF EXISTS `eproduct`;

/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `eproduct` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `name` varchar(100) DEFAULT NULL,
  `price` decimal(10,2) DEFAULT NULL,
  `date_added` timestamp NOT NULL DEFAULT CURRENT_TIMESTAMP,
  PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=4 DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

```

```

LOCK TABLES `eproduct` WRITE;

/*!40000 ALTER TABLE `eproduct` DISABLE KEYS */;

INSERT INTO `eproduct` VALUES (1,'HP Laptop ABC',21900.00,'2019-06-04
07:18:57'),(2,'Acer Laptop ABC',23300.00,'2019-06-04 07:19:07'),(3,'Lenovo Laptop
ABC',33322.00,'2019-06-04 07:19:19');

/*!40000 ALTER TABLE `eproduct` ENABLE KEYS */;

UNLOCK TABLES;

```

```

DROP TABLE IF EXISTS `finance`;

/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `finance` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `ftype` varchar(10) DEFAULT NULL,

```

```

`name` varchar(30) DEFAULT NULL,
`product_id` bigint(20) DEFAULT NULL,
PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=latin1;
/*!40101 SET character_set_client = @saved_cs_client */;

```

```

LOCK TABLES `finance` WRITE;

/*!40000 ALTER TABLE `finance` DISABLE KEYS */;

INSERT INTO `finance` VALUES (1,'CREDITCARD','EMI on Citibank Card',1),(3,'BANK','40%
finance from SBI',2),(4,'BANK','60% finance from ICICI',3),(5,'BANK','20% finance from ICICI',1);

/*!40000 ALTER TABLE `finance` ENABLE KEYS */;

UNLOCK TABLES;

```

```

DROP TABLE IF EXISTS `os`;

/*!40101 SET @saved_cs_client = @@character_set_client */;

/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `os` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `name` varchar(30) DEFAULT NULL,
  `product_id` bigint(20) DEFAULT NULL,
  PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=6 DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

```

```

LOCK TABLES `os` WRITE;

/*!40000 ALTER TABLE `os` DISABLE KEYS */;

INSERT INTO `os` VALUES (1,'Windows 10',1),(2,'Windows
10',2),(3,'FreeDOS',2),(4,'RedHat Linux',2),(5,'Windows 10',3);

/*!40000 ALTER TABLE `os` ENABLE KEYS */;

UNLOCK TABLES;

```

```

DROP TABLE IF EXISTS `screensizes`;

/*!40101 SET @saved_cs_client = @@character_set_client */;
/*!40101 SET character_set_client = utf8 */;

CREATE TABLE `screensizes` (
  `ID` bigint(20) NOT NULL AUTO_INCREMENT,
  `size` varchar(10) DEFAULT NULL,
  `product_id` bigint(20) DEFAULT NULL,
  PRIMARY KEY (`ID`)
) ENGINE=InnoDB AUTO_INCREMENT=5 DEFAULT CHARSET=latin1;

/*!40101 SET character_set_client = @saved_cs_client */;

```

```

LOCK TABLES `screensizes` WRITE;

/*!40000 ALTER TABLE `screensizes` DISABLE KEYS */;

INSERT INTO `screensizes` VALUES (1,'12 in',1),(2,'14.5 in',2),(3,'14.9 in',2),(4,'15.5 in',3);

/*!40000 ALTER TABLE `screensizes` ENABLE KEYS */;

UNLOCK TABLES;

```

```
package com.ecommerce;
```

```
public class Color {
```

```
    private long COLORID;
```

```
    private String name;
```

```
    public Color() {
```

```
    }
```

```
    public Color(String name) {
```

```
        this.COLORID = 0;
```

```
        this.name = name;
```

```
    }
```

```
    public long getCOLORID() {return this.COLORID; }
```

```
    public String getName() { return this.name;}
```

```
    public void setCOLORID(long id) { this.COLORID = id;}
```

```
    public void setName(String name) { this.name = name;}
```

```
}
```

```
package com.ecommerce;
```

```
import java.math.BigDecimal;
```

```
import java.util.Collection;
```

```
import java.util.Date;
```

```
import java.util.List;
```

```
import java.util.Set;
```

```
import java.util.Map;
```

```
public class EProduct {
```

```
    private long ID;
```

```
    private String name;
```

```
    private BigDecimal price;
```

```
    private Date dateAdded;
```

```
    private List<Color> colors;
```

```
    private Set<Finance> finance;
```

```
    private PDescription pdescrip;
```

```
    public EProduct() {
```

```
}
```

```
    public long getID() {return this.ID; }
```

```
    public String getName() { return this.name;}
```

```
    public BigDecimal getPrice() { return this.price;}
```

```
    public Date getDateAdded() { return this.dateAdded;}
```

```
public List<Color> getColors() { return this.colors;}
public Set<Finance> getFinance() { return this.finance;}
public PDescription getPdescrip() { return this.pdescrip;}

public void setID(long id) { this.ID = id;}
public void setName(String name) { this.name = name;}
public void setPrice(BigDecimal price) { this.price = price;}
public void setDateAdded(Date date) { this.dateAdded = date;}
public void setColors(List<Color> colors) { this.colors = colors;}
public void setFinance(Set<Finance> finance) { this.finance = finance;}
public void setPdescrip(PDescription pdescrip) { this.pdescrip = pdescrip;}
}
```

```
package com.ecommerce;
```

```
public class Finance {
    private long FINANCEID;
    private String name;
    private String ftype;

    public Finance() {

    }

    public Finance(String name, String ftype) {
```

```
    this.FINANCEID = 0;
    this.name = name;
    this.ftype = ftype;
}
```

```
public long getFINANCEID() {return this.FINANCEID; }
public String getName() { return this.name;}
public String getFtype() { return this.ftype;}
public void setFINANCEID(long id) { this.FINANCEID = id;}
public void setName(String name) { this.name = name;}
public void setFtype(String ftype) { this.ftype= ftype;}
```

```
}
```

```
package com.ecommerce;
```

```
public class OS {
```

```
    private long OSID;
    private String name;
```

```
    public OS() {
```



```
}  
  
public OS(String name) {  
    this.OSID = 0;  
    this.name = name;  
}  
  
public long getOSID() {return this.OSID; }  
public String getName() { return this.name;}  
public void setOSID(long id) { this.OSID = id;}  
public void setName(String name) { this.name= name;}  
  
}
```

```
package com.ecommerce;
```

```
public class ScreenSizes {  
    private long SCREENID;  
    private String size;  
  
    public ScreenSizes() {  
  
    }  
    public ScreenSizes(String size) {
```

```
        this.SCREENID = 0;
        this.size = size;
    }
```

```
    public long getSCREENID() {return this.SCREENID; }
    public String getSize() { return this.size;}
    public void setSCREENID(long id) { this.SCREENID = id;}
    public void setSize(String size) { this.size = size;}

}
```

```
package com.ecommerce;
```

```
import org.hibernate.SessionFactory;
import org.hibernate.boot.Metadata;
import org.hibernate.boot.MetadataSources;
import org.hibernate.boot.registry.StandardServiceRegistry;
import org.hibernate.boot.registry.StandardServiceRegistryBuilder;
```

```
public class HibernateUtil {

    private static final SessionFactory sessionFactory;

    static {
```

```

    try {
        StandardServiceRegistry standardRegistry = new StandardServiceRegistryBuilder()
            .configure("hibernate.cfg.xml").build();

        Metadata metaData = new
MetadataSources(standardRegistry).getMetadataBuilder().build();

        sessionFactory = metaData.getSessionFactoryBuilder().build();
    } catch (Throwable th) {
        throw new ExceptionInInitializerError(th);
    }
}

public static SessionFactory getSessionFactory() {
    return sessionFactory;
}
}

```

```

<?xml version="1.0"?>
<!DOCTYPE hibernate-mapping PUBLIC
"-//Hibernate/Hibernate Mapping DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">
<hibernate-mapping package="com.ecommerce">
    <class name="Color" table="colors">
        <id name="COLORID" type="long" column="ID">
            <generator class="identity"/>
        </id>
        <property name="name" type="string" column="COLOR_NAME"/>
    </class>

```

</hibernate-mapping>

<?xml version="1.0"?>

<!DOCTYPE hibernate-mapping PUBLIC

"-//Hibernate/Hibernate Mapping DTD 3.0//EN"

"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">

<hibernate-mapping package="com.ecommerce">

 <class name="EProduct" table="eproduct">

 <id name="ID" type="long" column="ID">

 <generator class="identity"/>

 </id>

 <property name="name" type="string" column="NAME"/>

 <property name="price" type="big_decimal" column="PRICE"/>

 <property name="dateAdded" type="timestamp" column="DATE_ADDED"/>

 <list name="colors" cascade="all" lazy="true">

 <key column="product_id" />

 <list-index column="idx" />

 <one-to-many class="com.ecommerce.Color" />

 </list>

 <bag name="screensizes" cascade="all" lazy="true">

 <key column="product_id"></key>

 <one-to-many class="com.ecommerce.ScreenSizes"/>

 </bag>

```

        <set name = "os" cascade="all" lazy="true">
        <key column = "product_id"/>
        <one-to-many class="OS"/>
    </set>

    <map name = "finance" cascade="all">
        <key column = "product_id"/>
        <index column = "ftype" type = "string"/>
        <one-to-many class="com.ecommerce.Finance"/>
    </map>
</class>
</hibernate-mapping>

<?xml version="1.0"?>
<!DOCTYPE hibernate-mapping PUBLIC
"-//Hibernate/Hibernate Mapping DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">
<hibernate-mapping package="com.ecommerce">
    <class name="Finance" table="finance">
        <id name="FINANCEID" type="long" column="ID">
            <generator class="identity"/>
        </id>
        <property name="name" type="string" column="NAME"/>
        <property name="ftype" type="string" column="FTYPE"/>
    </class>
</hibernate-mapping>

```

```
<?xml version="1.0"?>
<!DOCTYPE hibernate-mapping PUBLIC
"-//Hibernate/Hibernate Mapping DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">
<hibernate-mapping package="com.ecommerce">
  <class name="OS" table="os">
    <id name="OSID" type="long" column="ID">
      <generator class="identity"/>
    </id>
    <property name="name" type="string" column="NAME"/>
  </class>
</hibernate-mapping>
```

```
<?xml version="1.0"?>
<!DOCTYPE hibernate-mapping PUBLIC
"-//Hibernate/Hibernate Mapping DTD 3.0//EN"
"http://www.hibernate.org/dtd/hibernate-mapping-3.0.dtd">
<hibernate-mapping package="com.ecommerce">
  <class name="ScreenSizes" table="screensizes">
    <id name="SCREENID" type="long" column="ID">
      <generator class="identity"/>
    </id>
    <property name="size" type="string" column="SIZE"/>
  </class>
```

</hibernate-mapping>

<?xml version='1.0' encoding='utf-8'?>

<!DOCTYPE hibernate-configuration PUBLIC

"-//Hibernate/Hibernate Configuration DTD 3.0//EN"

"http://www.hibernate.org/dtd/hibernate-configuration-3.0.dtd">

<hibernate-configuration>

<session-factory>

<!-- Database connection settings -->

<property name="connection.driver_class">com.mysql.jdbc.Driver</property>

<property name="connection.url">jdbc:mysql://localhost:3306/ecommerce</property>

<property name="connection.username">root</property>

<property name="connection.password">master</property>

<mapping resource="com/ecommerce/EProduct.hbm.xml"/>

<mapping resource="com/ecommerce/Color.hbm.xml"/>

<mapping resource="com/ecommerce/ScreenSizes.hbm.xml"/>

<mapping resource="com/ecommerce/Os.hbm.xml"/>

<mapping resource="com/ecommerce/Finance.hbm.xml"/>

</session-factory>

</hibernate-configuration>

<!DOCTYPE html>

<html>

<head>

<meta charset="UTF-8">

<title>Hibernate Collection Mapping With XML</title>

```
</head>
<body>
<a href="details">Product Details</a><br>

</body>
</html>
```

```
import java.io.IOException;
import java.io.PrintWriter;
import javax.servlet.ServletConfig;
import javax.servlet.ServletException;
import javax.servlet.annotation.WebServlet;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.transaction.*;
import javax.xml.bind.*;
import java.io.Serializable;
import java.math.BigDecimal;
import java.util.ArrayList;
import java.util.Calendar;
import java.util.Collection;
import java.util.List;
import java.util.Map;
import java.util.Set;

import org.hibernate.Session;
```



```
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;
import org.hibernate.cfg.Configuration;

import com.ecommerce.Color;
import com.ecommerce.EProduct;
import com.ecommerce.Finance;
import com.ecommerce.HibernateUtil;
import com.ecommerce.PDescription;

/**
 * Servlet implementation class ProductDetails
 */
@WebServlet("/ProductDetails")
public class ProductDetails extends HttpServlet {
    private static final long serialVersionUID = 1L;

    /**
     * @see HttpServlet#HttpServlet()
     */
    public ProductDetails() {
        super();
        // TODO Auto-generated constructor stub
    }

    /**
     * @see HttpServlet#doGet(HttpServletRequest request, HttpServletResponse response)
     */
}
```

```
protected void doGet(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
```

```
    // TODO Auto-generated method stub
```

```
    try {
```

```
        SessionFactory factory = HibernateUtil.getSessionFactory();
```

```
        Session session = factory.openSession();
```

```
        List<EProduct> list = session.createQuery("from EProduct").list();
```

```
        PrintWriter out = response.getWriter();
```

```
        out.println("<html><body>");
```

```
        out.println("<b>One to One Mapping</b><br>");
```

```
        for(EProduct p: list) {
```

```
            out.println("ID: " + String.valueOf(p.getID()) + ", Name: " + p.getName() +
```

```
                ", Price: " + String.valueOf(p.getPrice()) + ", Date Added: " +
p.getDateAdded().toString());
```

```
            PDescription descrip = p.getPdescrip();
```

```
            out.println("<br>Description:" + descrip.getDescrip());
```

```
            out.println("<hr>");
```

```
        }
```

```
        out.println("<b>One to Many and Many to One Mapping</b><br>");
```

```
        for(EProduct p: list) {
```

```
            out.println("ID: " + String.valueOf(p.getID()) + ", Name: " + p.getName() +
```

```
                ", Price: " + String.valueOf(p.getPrice()) + ", Date Added: " +
p.getDateAdded().toString());
```

```
            List<Color> colors = p.getColors();
```

```
            out.println("<br>Colors: <ul>");
```

```
            for(Color c: colors) {
```

```

        out.print("<li>" + c.getName() + "</li>");
    }
    out.println("</ul>");
    out.println("<hr>");

}
out.println("<b>Many to Many Mapping</b><br>");
for(EProduct p: list) {
    out.println("ID: " + String.valueOf(p.getID()) + ", Name: " + p.getName() +
        ", Price: " + String.valueOf(p.getPrice()) + ", Date Added: " +
p.getDateAdded().toString());

    Set<Finance> finances= p.getFinance();
    out.println("<br>Finance Options : <ul>");
    for(Finance f: finances) {
        out.print("<li>" + f.getFtype() + "</li>");
    }
    out.println("</ul>");
    out.println("<hr>");
}

session.close();

out.println("</body></html>");

} catch (Exception ex) {
    throw ex;
}

```

```

    }

    /**
     * @see HttpServlet#doPost(HttpServletRequest request, HttpServletResponse response)
     */
    protected void doPost(HttpServletRequest request, HttpServletResponse response) throws
ServletException, IOException {
        // TODO Auto-generated method stub
        doGet(request, response);
    }
}

```

```

<?xml version="1.0" encoding="UTF-8"?>

<web-app xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://xmlns.jcp.org/xml/ns/javaee"
xsi:schemaLocation="http://xmlns.jcp.org/xml/ns/javaee
http://xmlns.jcp.org/xml/ns/javaee/web-app_4_0.xsd" id="WebApp_ID" version="4.0">

    <display-name>HibernateLazyCollections</display-name>

    <welcome-file-list>

        <welcome-file>index.html</welcome-file>

        <welcome-file>index.htm</welcome-file>

        <welcome-file>index.jsp</welcome-file>

        <welcome-file>default.html</welcome-file>

        <welcome-file>default.htm</welcome-file>

        <welcome-file>default.jsp</welcome-file>

    </welcome-file-list>

```

```
<servlet>
  <servlet-name>ProductDetails</servlet-name>
  <servlet-class>ProductDetails</servlet-class>
</servlet>
<servlet-mapping>
  <servlet-name>ProductDetails</servlet-name>
  <url-pattern>/details</url-pattern>
</servlet-mapping>
</web-app>
```

Output:

