

Publications Reissue Highlights

Manual: *ACI Java Server Framework Reference Guide*

Number: CF-DA000-02-ES

Date: Jun-2008

Software: Release 1.0 Version 08.2

The following table highlights the major changes that have been made in the most recent update to the *ACI Java Server Framework Reference Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes. These changes update the guide to release 1.0, version 08.2 and reflect version 07.4 of the ACI Java Server Framework.

Section/ Appendix	Major Changes
All	Changes the acronym for the ACI Java Server Framework from JSF to AJSF to avoid confusion with Java Server Faces (JSF) presentation technology.
1	Adds the User Security (USEC) application subsystem to the framework layer of the ACI Java Server Framework (AJSF). Adds a discussion of the <code>AJI_isocodes.jar</code> , which consolidates all ISO country codes and currency codes used by AJSF-based applications in the AJSF.
2	Adds a description of the USEC application subsystem, which is now part of the AJSF. This description includes third-party JAAS authentication information previously provided in the “BASE24-eps User Interface (ESWEB)” appendix. Adds support to <i>plug in</i> third-party JAAS authentication from IBM’s Tivoli Access Manager for e-business to the USEC application. Adds support for configuring SSL security between the USEC application and Tivoli Access Manager for e-business using the Tivoli Java SvrSslCf utility. Adds procedures for sharing USEC application context among ACI Payment Framework (APF) products that use the ACI desktop or a browser user interface for access to multiple AJSF-based products. Adds <i>salted</i> SHA-256 hash (SSHA-256) encryption for user passwords. Clarifies third-party authenticator configuration requirements for pluggable authentication in the USEC application.

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|---|--|
| 3 | <p>Adds character encoding options for TCP/IP protocols used by external connections and listeners.</p> <p>Adds a new topic describing how message context is handled in an AJSF-based application.</p> |
| 4 | <p>Adds a discussion of the EVENTTIVOLIAPPENDER appender in the EventConfig.xml file and the associated TivoliConfigFile script file to support the routing of event messages to the Tivoli Enterprise Console (TEC) or Netcool/Omnibus.</p> <p>Adds a discussion of the JMSMQAPPENDER appender in the EventConfig.xml file to consolidate events from the AJSF-based Application Management agent.</p> <p>Adds comments to the example EventConfig.xml and TraceConfig.xml files for additional configuration parameters needed for the IBM System z and Unix platforms.</p> <p>Adds a discussion for integrating the Application Management agent with Tivoli on an IBM System z platform by modifying the TRACE appender definition in the TraceConfig.xml.</p> <p>Adds a “Security Considerations” discussion that was previously located in the “BASE24-eps User Interface (ESWEB)” appendix.</p> |
| 5 | <p>Updates the ConfigPropertyBuilder.class password encryption utility to allow for the encryption of user password property values.</p> <p>Adds the DISK-WITH-CACHE value for the context.type property to allow for the sharing USEC application context among ACI Payment Framework (APF) products and the MEM-OUT-OF-PROCESS-WITH-CACHE value to maintain context in cache by a separate process configured as a Context Manager.</p> <p>Updates the description of the DigestCredAlgorithm property to use the <i>salted</i> SHA-256 algorithm (SSHA-256) as the default to encrypt stored passwords.</p> <p>Adds a description of the isDisableUserOnFailedLogonAttempts property. This property indicates whether the USEC application automatically sets a user’s status to Disabled/System when the user exceeds the allowed number of failed logon attempts.</p> <p>Updates the description of the initialization.function.n.classname property to indicate that beginning with AJSF 07.4, initialization function properties are only loaded from the APPLCNFG and not from the config.properties file.</p> |

Section/ Appendix	Major Changes
6	Adds a new section for extending the ACI Java Server Framework (AJSF) User Security (USEC) authentication and user auditing functions to non-AJSF-based applications. This section describes the USEC and user auditing APIs and how to configure them for non-AJSF-based applications.
7	Adds a new section to describe the Event Adapter bundled with the AJSF for use by any ACI Payments Framework application that has a need to log standardized events.
A	Moves the “Third-Party JAAS Authenticator Configuration Files” topic to section 2. Moves the “Security Considerations” topic to section 4. Adds a description of the <code>db.char.set.ebcdic</code> property. Updates the description of the <code>jsf.jaxb.context.n</code> property for user authentication in non-AJSF-based applications.
C	Adds a new appendix to describe where the AJSF configuration information can be found for the Application Management agent.
D	Adds a new appendix to describe where the AJSF configuration information can be found for the Remote Database Server.

ACI Worldwide, Inc.