

Publications Reissue Highlights

Manual: *ACI Java Server Framework Reference Guide*

Number: CF-DA000-02-ES

Date: Feb-2009

Software: Release 1.0, Version 08.2, Service Pack 3

The following table highlights the major changes that have been made in the most recent update to the *ACI Java Server Framework Reference Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes. These changes update the manual to release 1.0, version 08.2, service pack 3.

Section/ Appendix	Major Changes
All	The naming conventions for the following configuration properties that had to be numbered sequentially prior to AJSF version 07.4 now need only end in a unique text string. • initialization.function<text-string> • jsf.jaxb.context.<text-string> • timertask.function<text-string> • website.xml.menumap.filename<text-string> • xmltranmap.filename<text-string> For example, the initialization.function<text-string> property used to require a naming convention of initialization.function.<i>n</i>.classname, where <i>n</i> was a sequential number starting with 0 and incremented by 1 for each property configured. Under the new naming conventions, all of the following are valid: • initialization.function.0.classname • initialization.function.TransactionMapManager • initialization.function.USECManager References to these properties were changed to reflect the new naming conventions throughout the guide. Because the naming convention has simply been relaxed, the old naming conventions are still valid. As such, the examples in the guide using the old naming conventions remain unchanged and are still valid.

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|---|
| 2 | Adds the cleanup.userauditlog.batch.size property to the list of properties required to implement user auditing in the user interface server process (e.g., ESWEB, PMWEB, or CRUXWEB). |
| 4 | Adds notes for the sample EventConfig.xml and TraceConfig.xml files to indicate that when installed on an IBM System z platform, the encoding meta element in the XML declarations for these files must be either be set to “IBM-1047” instead of "UTF-8" or be removed. |
| 5 | <p>Adds a description of the cleanup.userauditlog.batch.size property. This property limits the number of old rows to to delete in a single batch when cleaning up the User Audit Log data source (USRAULOG).</p> <p>Removes the description of the db.useisolationlevel property because it is no longer used by the ACI Java Server Framework (AJSF). In BASE24-eps version 08.2, which uses version 07.4 of the AJSF, convenience methods were added to database components to enable the application to manipulate the database isolation level as needed. The AJSF uses these methods during user auditing to prevent lock contention for one thread using two database connections.</p> |
| 7 | <p>Adds a note for the sample EventConfig.xml file used by the ACI Event Adapter to indicate that when installed on an IBM System z platform, the encoding meta element in the XML declarations for this file must be either set to “IBM-1047” instead of "UTF-8" or be removed.</p> <p>Adds a note for the sample event message XML schema file used by the ACI Event Adapter to indicate that when installed on an IBM System z platform, the encoding meta element in the XML declarations for this file must be set to “IBM-1047” instead of "UTF-8".</p> <p>Clarifies the procedures for integrating the ACI Event Adapter with the IBM Tivoli Enterprise Console (TEC) and adds procedures for integrating the ACI Event Adapter with Tivoli Netcool/OMNIBus.</p> |
| A | Removes the usec1.0 value from the description of the usec.security.version property. This value can only be used with BASE24-eps versions prior to 07.4. |