

Publications Reissue Highlights

Manual: *BASE24 External Message Manual*

Number: BA-DH011-02

Date: Dec-2009, May-2010, Jul-2010

Software: Release 6.0, Version 10

The following table highlights the major changes that have been made to the *BASE24 External Message Manual* in this edition. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes. This edition updates the manual to release 6.0, version 10.

Section/ Appendix	Major Changes
2	Removes the mention of card verification transactions from the 0100 Authorization Request (BASE24-pos) message description. Card verification transactions are processed as 0200—rather than 0100—external messages, so no 0100-to-0200 message conversion is involved for these transactions. (Dec-2009)
3	Adds BASE24-atm bulk check data elements S-113 through S-117 to the BASE24-atm message defaults. (Dec-2009)
4	Adds BASE24-atm bulk check data elements S-113 through S-117 to the list of variable-length data elements that can be made fixed length using the BASE24-atm fixed-length message option in the Host Configuration File (HCF). (Dec-2009)
5	Updates the P-4 (Transaction Amount) data element description for BASE24-atm. Hosts that authorize BASE24-atm transactions or receive BASE24-atm completion messages must be able to process balance inquiries, PIN change, and PIN unblock transactions where the transaction amount is greater than zero. This situation can occur when acquirers assess access fees on these transactions. Similarly, hosts must be able to support reversals of these same transactions. (Dec-2009)
	Updates the P-39 (Response Code) data element to note the impacts of the ADJ-ADVISE-RC param on outgoing BASE24-pos 0220 adjustment messages. (Dec-2009)

**Section/
Appendix**

Major Changes

Updates the P-52 (Personal Identification Number Data) data element to note the impacts of the PRE-VERIFIED-PIN-PAD-CHAR param on the contents of the data element for BASE24-atm, BASE24-pos, and BASE24-teller. (Dec-2009)

Updates the P-63 (BASE24-pos Additional Data) data element to enlarge its size from ANS ..600 to ANS ..1000. (May-2010)

- 6 Adds the following BASE24-atm data element definitions to support the use of custom-developed Bulk Check device handler functionality. These data element definitions are not used with the BASE24-atm standard product.

- S-113 BASE24-atm Bulk Check Amount Token Data
- S-114 BASE24-atm Bulk Check MICR Token Data—Part 1
- S-115 BASE24-atm Bulk Check MICR Token Data—Part 2
- S-116 BASE24-atm Bulk Check SSBC Token Data
- S-117 BASE24-atm Bulk Check Disposition Token Data

(Dec-2009)

Updates the S-120 BASE24 Key Management data element because the Field Length Indicator field must contain the length of the check digits being exchanged. For the following modules, this value must be set as shown below.

- BIC ISO Interchange Interface must be set to a value of 004 to accommodate TSS at co-networks.
- ISO Host Interface must be set to a value of 006.

(Jul-2010)

- A Modifies the response code mapping tables to include enhanced EMV mapping for BASE24-atm. (Dec-2009)

- C Modifies the response code mapping tables to include enhanced EMV mapping for BASE24-pos. (Dec-2009)

Adds mapping information to the BASE24-pos response code mapping tables for response code 10 (partial approval). For inbound messages, response code 10 maps to 000. For outbound messages, response code 000 maps to response code 10 if the authorized amount differs from the requested amount.

(Dec-2009)