

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Services Processing Guide*

Number: BA-AE000-14

Date: Dec-2009

Software: Release 6.0, Version 10 (TSS Release 09.2)

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Services Processing Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the guide to TSS release 09.2 for BASE24 release 6.0, version 10.

Section/ Appendix	Major Changes
All	Removes references to NCR's enhanced signature remote key loading (RKL) authentication scheme for the BASE24 Automated Key Distribution System (AKDS) add-on product. NCR has no plans to implement this scheme in the near future. Changes all references to the <i>ACI Java Server Framework Reference Guide</i> to <i>ACI Java Infrastructure Java Server Reference Guide</i> throughout.
2	Adds notes indicating that certain fields and tabs displayed on the Channel Security Configuration window and on the Interface Security Configuration window for Thales e-Security HSMs are not used for Transaction Security Services processing. Currently, these fields and tabs are only used in BASE24-eps processing. Updates the description of the Contactless tab of the Authentication Profile Configuration window to indicate that it is supported for Atalla variant NSPs as well as AKB NSPs. Updates all window and tab examples for TSS release 09.2 and indicates which tabs are only applicable to BASE24-eps. Corrects the description of key variant 2 (Data Encryption Key Variant) for the "Data Encryption Working Key Variants" topic. The description incorrectly referred to the PIN key instead of the data encryption key.

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|----|--|
| 3 | <p>Adds a description of the ATALLA_CBC_DATA_FRMT Environment attribute for Canadian POS processing.</p> <p>Adds descriptions of the RAM_MAX_BUF_LGTH and URAM_MAX_BUF_LGTH Environment attributes. These attributes prevent the RAM and URAM process, respectively, from sending data that is too long in DUKPT MAC Generate and DUKPT MAC Verify functions to Thales e-Security HSMs. These functions allow for a maximum of 4096 bytes.</p> |
| 7 | <p>Adds procedures for changing the IP address of the TSS environment and for changing the TSS database access password.</p> |
| 8 | <p>Adds a note to the “Cause, Effect, and Remedy” topic to indicate that Java User Interface servlets (ESWEB) process error events related to the creation and connection with the database pool are not configured on the Event Management window because you cannot access this window when they occur.</p> |
| 10 | <p>Adds the AACR (ACI Collision Resolution) and BAUT (Batch Authorization) process type values for the Process Type field on the Trace Configuration window. These process types are only used with BASE24-eps.</p> <p>Clarifies information about examining trace output using the Trace Viewer utility. It can take considerable time to write extremely large trace records to the system.</p> |
| 12 | <p>Adds Atalla variant NSP support for commands 357 and 359.</p> |
| B | <p>Updates the “Key Generate (KEYGEN) Command” topic to indicate that the host name in the command can be set to the host BASE24 system as configured in the KEY SIGNER field on screen 22 of the BASE24-atm Terminal Data files (ATD) for NCR 5XXX and Diebold 10XX/478X devices as well as devices running Wincor Nixdorf firmware, NCR devices running Diebold signature emulation firmware, Tidel devices, and Triton devices.</p> <p>Using different host names, you can generate multiple BASE24 system public key pairs for a particular device type.</p> |
| C | <p>Adds the DVPND and ZKA_KGK data source values for the Check Digit Validation and Generation Utility. These files are used only on BASE24-eps.</p> <p>Adds support to the Master File Conversion utility for the Dynamic card verification keys (DYN_CARD_VRFCTN) and ZKA Key Generation Keys (ZKA_KGK) data sources when using Atalla AKB NSPs. These files are used only on BASE24-eps.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|---|---|
| C | Adds support to the Master File Conversion utility for the following types of keys stored in the Channel_Security or ICHG_SECURITY for Thales e-Security HSMs. These files are used only on BASE24-eps. <ul style="list-style-type: none">• Terminal Encryption Keys (LMK pair 32–33)• Zone Authentication Keys (LMK pair 26–27)• Zone Encryption Keys (LMK pair 30–31) |
| D | M/Chip 4 cryptogram version number values %h10 and %h11 were missing for MasterCard and have been added. |

ACI Worldwide, Inc.