

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Services Processing Guide*

Number: BA-AE000-14

Date: Dec-2006

Software: Release 6.0, Version 7 (TSS Release 06.4)

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Services Processing Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the guide from TSS release 06.2 to TSS release 06.4 for BASE24 release 6.0, version 7.

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|--|
| 1 | <p>Adds the Atalla Axx150 series of Network Security Processors to the list of supported hardware security devices for BASE24-es.</p> <p>Adds the Dynamic Card Verification File (DYN_CARD_VRFCTN). This file contains keys used to verify the dynamic card verification digits (DCVD) for contactless magnetic stripe cards. The key locator for the DYN_CARD_VRFCTN is configured in the Card Prefix File (CPF).</p> <p>Adds support for the Banksys Data Encryption Peripheral (DEP) range of hardware security modules (HSMs).</p> <p>Adds support for shared Wincor Nixdorf certificate-based ATM devices running in 912 or NDC emulation mode and APACS 30/40 POS devices.</p> <p>Adds a brief discussion of new user auditing tools for the ACI desktop user interface.</p> |
| 2 | <p>Adds notes indicating that the display of key entry fields on ACI desktop user interface windows differs significantly for Banksys DEP HSMs.</p> <p>Adds a description of the Transaction Key Security tab on the Channel Security Configuration window for APACS 30/40 devices.</p> <p>Updates the sample of the Dynamic Key Limits tab and adds a sample of the Message Information tab on the BASE24 KEYF Configuration window for support of full message encryption by the ISO Host Interface process.</p> <p>Adds a description of the Contactless tab of the Authentication Profile Configuration window and how the corresponding Dynamic Card Verification File (DYN_CARD_VRFCTN) is accessed.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|---|---|
| 2 | <p>Adds a description of the Cryptographic Version Number field on the EMV tab of the Authentication Profile Configuration window along with a discussion of how the EMV scheme and cryptogram version number dictate the type of security processing performed by the Transaction Security Services process. The value in the Cryptographic Version Number field is used only if the cryptogram version number is not present in an EMV transaction request.</p> <p>Adds the Dynamic Card Verification external memory table (DYNAMIC_CARD_VERIFICATION_OLTP) and the optional Event external memory table (EVENT_OLTP) to the External Memory Tables (OLTPs) discussion.</p> |
| 3 | <p>Updates the Security Device Configuration window description to support the Atalla Axx150 series of Network Security Processors and Banksys Data Encryption Peripheral (DEP) hardware security modules (HSMs).</p> <p>Adds a description of the DFLT_DAT_FRMT Environment attribute. This attribute specifies the date format used for any reports generated by the BASE24-es product, except for the AKDS Capacity Report, which does not currently use it.</p> <p>Adds a discussion of user interface list retrieval attributes and parameters that limit the number of items that can be returned to a window in a single message.</p> |
| 4 | <p>Adds support for the Atalla Axx150 series of Network Security Processors.</p> <p>Adds a note for the Atalla Generate MAC (98) and Verify MAC (99) commands to indicate that they support the X9.19 method of message authentication, also known as pseudo triple DES, as well as single DES and triple DES message authentication.</p> <p>Adds the Atalla 357 (Visa dCVV Verify) and 359 (MasterCard CVC3 Verify) commands and the Thales e-Security PM (Verify Dynamic CVV) command to support dynamic card verification for contactless magnetic stripe cards. Adds the key encryption requirements for entering the dynamic card verification key into the TSS database.</p> <p>Adds support for the Banksys DEP HSM.</p> <p>Adds a discussion of how the Eracom ProtectHost White Mark II host security module (HSM) handles <i>short</i> PINs (i.e., PINs entered with a length less than the configured minimum PIN length).</p> |
| 6 | <p>Renames the section from “Data Field Encryption” to “Message Data Field Encryption” and adds support for full message data encryption between the BASE24 system and an ISO host using the ISO Host Interface process.</p> |

Section/ Appendix	Major Changes
7	Adds example MDSDEST entries for Banksys DEP HSMs and clarifies the example MDSDEST entries for Thales e-Security HSMs.
8	Adds a step for rebuilding and warmbooting the optional Event_OLTP if you change any data on the Event Message or Event Suppression Information tabs on the Event Configuration and Management window.
9	Clarifies the description of the Info Attribute process control command for the Environment component. This process control command is intended to be used only in a support situation to view the values processes are using for the environment variables they have registered. Adds the Dynamic Card Verification File (DCRDVD) to the syntax of the Convert AKB, Validate Check Digits, and Generate Check Digits process control commands. Updates the description and syntax of the Key Generate process control command for support of shared Wincor Nixdorf certificate devices.
10	Adds the ATBM (ATM Batch Manager process) to the possible values for the Process Type field on the Trace Configuration window; however, this value is not valid for the Transaction Security Services process. Adds an example of the DALCI SELECT command with the INSERTFORM option to the external message trace example for viewing trace output using DALCI.
11	Updates the OLTP Warmboot Management window to display values of Yes or No in the OLTP Rebuild Submitted and OLTP Warmboot Submitted columns. Updates all the procedures for this window to allow for selection of multiple OLTP_Warmboot rows. Clarifies the procedure for deleting OLTP_Warmboot rows.
12	Adds a new section describing support for dynamic card verification. Dynamic card verification is the verification of contactless magnetic stripe cards, or proximity cards.
B	Adds support for Banksys Data Encryption Peripheral (DEP) HSMs. AKDS procedures for the Banksys DEP HSM are the same as those used for Thales e-Security HSMs. Adds support for shared Wincor Nixdorf certificate devices. AKDS procedures for shared Wincor Nixdorf certificate devices are the same as those used for Diebold devices, except you cannot migrate from single-length keys to double-length keys using AKDS due to limitations in Wincor Nixdorf firmware.

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|---|---|
| C | <p>Updates the Check Digit Validation and Generation utility, AKB Conversion utility, and Master File Key Conversion utility to support the Dynamic Card Verification File (DYN_CARD_VRFCTN).</p> <p>Clarifies that the network must be shut down (i.e., transaction processing must be stopped) while keys are converted using the AKB Conversion utility or the Master File Key Conversion utility. OLTPs must be rebuilt and warmbooted following the conversion. The Channel Security File (CHANNEL_SECURITY) and Interface Security File (ICHG_SECURITY) must also be warmbooted if the Transaction Security Services and AKDS processes were not stopped while the keys were converted.</p> |
| D | <p>Updates the discussion on how the EMV cryptogram version number impacts the security processing performed.</p> <p>Adds illustrations to depict the flow of cryptographic functions for authorization request and response cryptogram processing and for secure message processing.</p> <p>Adds support throughout for the EMV Common Core Definitions (CCD) implementation.</p> <p>Clarifies how destination PIN blocks relate to EMV schemes.</p> |