

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Services Processing Guide*

Number: BA-AE000-14

Date: Nov-2007

Software: Release 6.0, Version 8 (TSS Release 07.4)

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Services Processing Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the guide from TSS release 06.4 to TSS release 07.4 for BASE24 release 6.0, version 8.

Section/ Appendix	Major Changes
All	All references to Eracom have been changed to SafeNet (Eracom). SafeNet, Inc. acquired Eracom Technologies AG in 2005. Corrects the name of the SECURE-DEV-ACCESS-TYP LCONF param throughout. Removes references to the Host Public Key Security Secondary File (HOST_PKEY_SCND). Renames the Host Public Key Security Primary File (HOST_PKEY_PRI) to Host Public Key Security File (HOST_PKEY_PRI). Secondary certificates are discarded and no longer stored for the BASE24 Automated Key Distribution System.
Preface	Adds a reference to the ANSI X9.24-2 standard to the prerequisite industry literature recommended for public key cryptography.
1	Adds the Chip Authentication File (Chip_Authentication). Updates the “Configuration” topic to depict how the USEC application can run <i>onboard</i> (i.e., within the ESWEB process) or <i>offboard</i> (i.e., as a separate OSS process) in the TSS environment. Adds a reference to file format descriptions of TSS files provided in a HELP24 solution attachment on InfoLink.
2	Adds discussions of how to store keys in the Channel Security File (Channel_Security) or in the host security module (HSM) for SafeNet (Eracom) ProtectHost White Mark II HSMs. Adds support for accessing the Data Encryption tab on the Channel Security Configuration window for SafeNet (Eracom) ProtectHost White Mark II HSMs.

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|---|--|
| 2 | <p>Adds support for accessing the Data Encr Exch Intf and Data Encr Key Inf tabs on the Interface Security Configuration window for SafeNet (Eracom) ProtectHost White Mark II HSMs.</p> <p>Adds a description of the Chip Authentication tab on the Authentication Profile Configuration window and the fields that appear on this tab.</p> |
| 3 | <p>Corrects references to the SECURE-DEV-ACCESS-TYP LCONF param throughout.</p> <p>Adds a description of the CHAN_DATA_KEY_EXPORT_VARIANT Environment attribute. This attribute is used to generate data encryption keys in an Atalla NSP.</p> <p>Adds a description of the CUSTOMER_NAME Environment attribute. This parameter specifies the name of the customer to be displayed in the header on the AKDS Capacity Report.</p> |
| 4 | <p>Adds support for message authentication of large messages using data chaining in Atalla variant and AKB NSPs, Banksys DEP HSMs, Eracom ProtectHost White Mark II and AMB HSMs, and Thales e-Security HSMs.</p> <p>Adds the Generate Random Number (93) command to the list of commands supported for Atalla AKB NSPs. The 93 command is used in AKDS processing to generate a random nonce when a new master key is generated for a Diebold, NCR certificate emulation, or shared Wincor Nixdorf certificate device. Command 93 is enabled in the AKB NSP's default factory security policy.</p> <p>Adds a discussion of how to store keys in the Channel Security File (Channel_Security) or in the host security module (HSM) for SafeNet (Eracom) ProtectHost White Mark II HSMs.</p> <p>Adds support for message data field encryption, EMV processing, and proof-of-endpoint (interface) processing in SafeNet (Eracom) ProtectHost White Mark II host security modules.</p> <p>Adds the Verify Truncated Application Cryptogram (MasterCard CAP) (K2) command to the list of commands supported for Thales e-Security HSMs.</p> |
| 6 | <p>Adds support for configurable and full message encryption for the ACI Standard POS Device Handler (SPDH) module.</p> <p>Adds message data encryption for SafeNet (Eracom) ProtectHost White Mark II host security modules.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|----|---|
| 7 | <p>Clarifies that MDSDEST entries use symbolic names rather than assign names and adds an example obey file for creating the MDSDEST.</p> <p>Adds the “Metadata External Memory Tables” topic to explain how the CONFCSV and MDBCSV can be accessed from memory rather than from disk in TSS version 07.4 and later.</p> <p>Clarifies the description of the SIMDS_DEST_WARMBOOT_DELTA parameter in the CONFCSV. This parameter enables the MDSDEST to be automatically warmbooted.</p> |
| 8 | <p>Adds a step to the “Configuring Events” topic to indicate that you must stop and restart the ESWEB Server process before the process will start to use the rebuilt Event_OLTP.</p> |
| 9 | <p>Adds a workaround for process control destination conflicts when both Transaction Security Services and BASE24 for Enhanced Authorization are installed on the same system.</p> <p>Modifies the description of the KEYGEN command to refer to the command syntax provided in appendix B.</p> |
| 10 | <p>Adds a topic describing considerations for process tracing in a production environment.</p> <p>Clarifies that trace commands should be sent to a single process of a specified process type.</p> <p>Adds optional TRCIN and TRCOUT runtime parameters for the Trace Viewer utility and procedures for using the TRCVR TACL macro to run the utility.</p> |
| 12 | <p>Adds support for the Dynamic Cardholder Authorization File (CAFD), which allows the ATC value to be maintained in a separate file that is not overwritten during a full-file refresh of the CAF.</p> <p>Adds Cardholder Authentication Program (CAP) token validation impacts for storing and maintaining the ATC for contactless magnetic stripe transactions.</p> |
| B | <p>Renames the appendix from “Automated Key Distribution System” to “Public Key Cryptography” to better describe its contents. Some of the facilities described in this appendix are now used for secure logons to an interchange in addition to securely downloading master keys remotely to ATMs.</p> <p>Adds support for NCR’s enhanced signature remote key loading (RKL) authentication scheme. Although the NCR enhanced RKL authentication scheme has been added in TSS release 07.4, it is not yet available in any BASE24 Device Handler modules in release 6.0v8.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|--|
| B | <p>Adds support for Diebold firmware emulating NCR devices using the basic signature scheme and NCR firmware emulating Diebold devices using certificates.</p> <p>Clarifies the combinations of EPP hardware vendor, ATM firmware vendor, message format, and Device Handler supported for the BASE24 Automated Key Distribution System.</p> <p>Clarifies how the BASE24 Automated Key Distribution System is provided in extensions to the BASE24-atm Diebold 10XX/478X Device Handler and NCR 5XXX Device Handler modules.</p> <p>Adds implementation procedures for secure logons between a BASE24 system Interchange Interface process (i.e., SAMA SPAN2 Interchange Interface process) and an interchange.</p> <p>Updates the syntax of the KEYGEN process control command to support interfaces and to include the modulus size, key option, and effective date.</p> <p>Adds a description of the KEYGEN Command Configuration and Submission window, which is provided to assist you in building, verifying, and submitting the KEYGEN command.</p> <p>Adds support for generating a random nonce for certificate-based PKI.</p> <p>Updates descriptions of the Disable KEYGEN Command, Certificate Management, Host Public Key Perusal, and Channel Public Key Perusal windows for various enhancements.</p> <p>Clarifies that you can enter any of the 05 printable ASCII characters in the Serial Number field on the EPP Serial Number Configuration window, except for the quote (") character.</p> <p>Updates the description of the AKDS Capacity Report to indicate that the value of the CUSTOMER_NAME Environment attribute is printed on the header of the report.</p> |
| C | <p>Removes references to the Host Public Key Security Secondary File (HOST_PKEY_SCND). Renames the Host Public Key Security Primary File (HOST_PKEY_PRI) to Host Public Key Security File (HOST_PKEY_PRI).</p> |
| D | <p>Changes the name of the OFFLINE PIN TRANSPORT KEY on CPF screen 11 to NEW PIN TRANSPORT KEY.</p> <p>Adds EMV 2000 and common session key derivation support for SafeNet (Eracom) ProtectHost White Mark II host security modules.</p> <p>Adds support for chip authentication program (CAP) token validation in Thales e-Security HSMs.</p> |