

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Services Processing Guide*

Number: BA-AE000-14

Date: Jul-2008

Software: Release 6.0, Version 8 (TSS Release 08.2)

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Services Processing Guide*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the guide to TSS release 08.2 for BASE24 release 6.0, version 8.

Section/ Appendix	Major Changes
----------------------	---------------

All	Replaces all references to “Interpay Nederland B.V.” with “Equens N.V.” and all references to “Interpay” with “Equens” throughout the manual because Interpay Nederland B.V. has merged with German processor Transaktionsinstitut to create a new pan-European service provider, Equens.
1	Updates the “Database Relationships” topic to indicate that the Card Prefix File (CPF) also contains a key locator to the Interface Security File (ICHG_SECURITY). Clarifies that large message MAC generation and verification is supported for the Dutch security extensions.
2	Clarifies that the SECURE-DEV-TYP LCONF assign must be set to TSS and the PIN encryption or MAC type field associated with the key field (i.e., PIN ENCRYPT TYP field on device-specific ATD screen 9, PIN ENCRYPTION TYPE and MAC TYPE fields on device-specific PTD screen 7) must also be set to a value indicating encryption or message authentication in a security device when adding a new channel ID record. Clarifies that if the LN-IND LCONF param is set, the value of this param is prepended to the terminal ID key locator value set in the hardware key field when adding a new channel ID record. Updates the “Key Authorization Files” and “Maintaining Authentication Profile Security Data” topics to indicate that the NEW PIN TRANSPORT KEY LOCATOR field on CPF screen 11 contains a key locator to the Interface Security File (ICHG_SECURITY).

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|----|---|
| 4 | Clarifies that the Thales e-Security MAC Generate/Verify (MS) command supports data chaining for message authentication of large messages. |
| 7 | <p>Corrects the -AI start option to indicate the TSS value in the run command syntax and XPNET configuration examples for starting the Metadata EMT Build process.</p> <p>Clarifies that you must always stop and restart the ESWEB process when the CONFEMT or MDBEMT is rebuilt. Because the Java User Interface servlets (ESWEB) process is a Java process, it does not receive SIS broadcast notifications automatically when the CONFEMT or MDBEMT is rebuilt. Only C++ Integrated Servers do.</p> <p>Clarifies that when installing TSS release 07.4 or later, you should also ensure that the location for the BASE24_KEYF assign is correct in the CONFCSV. The value of this assign must match the value of the KEYF/KEY6 assign in the LCONF.</p> |
| 9 | Adds descriptions of the REPORT command for the Event component and the VSP command for the VSP Manager component. The REPORT command generates an event documentation report for all events that can be generated in the TSS system for all subsystems or for a specified subsystem. The VSP command returns the version level and service pack level information installed in a process in the TSS environment, and, if applicable, a list of patches and CSMs. |
| 10 | Clarifies how traces are performed in the TSS environment, including a step-by-step procedure for tracing security device interaction. |
| 12 | For DCVD checking, clarifies that if the track static data length is odd and you are using an Atalla NSP, the Transaction Security Services process pads the track data with an “F” character and adds 1 to the track length. This ensures that an even number of track characters are sent in the 359 command to an Atalla NSP. |