

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Manual*

Number: BA-AE000-13

Date: Dec-2009

Software: Release 6.0, Version 10

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Manual*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the manual to release 6.0, version 10.

Section/ Appendix	Major Changes
5	Adds the Tidel and Triton Device Handler processes to the list of BASE24 processes that use hardware security modules to perform message authentication. Page 5-6.
6	Adds a description of the LCONF param PSEUDO-3DES-CBC-MAC-TYPE. This param specifies whether to use the pseudo 3DES cipher block chaining or 3DES cipher block chaining method for message authentication in the ISO Host Interface process. This param only applies when using Thales e-Security HSMs without the Transaction Security Services process. When using the Transaction Security Services process, you configure the message authentication method used in the TSS database. Page 6-2.
7	Adds a note to the description of the MAC SUPPORT TYPE field on ATD screen 9 to indicate that the field only enables message authentication in the Triton Device Handler process for a device. Once message authentication has been enabled for a Triton device, you must use the MACINGOFF text command to disable message authentication for a Triton device. You can also use the MACINGON text command as an alternative to the MAC SUPPORT TYPE field to enable message authentication for a Triton device. Pages 7-10 and 7-11.
8	Adds the “Preverified PIN Identification” topic to describe how the ISO Host Interface and BIC ISO Interface processes alter the PIN block to indicate that the PIN has already been verified. Pages 8-2 and 8-3.

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|----|--|
| 8 | Updates the “Optional PINs” topic for BASE24-pos PIN verification to include additional values for the PIN PROCESSING FLAG on CPF screen 7 to accommodate the use of contactless cards at attended or unattended terminals. Pages 8-31 and 8-32. |
| 13 | Adds values to the CHECK METHOD field on CPF screen 11 to enable you to inhibit iCVD validation on EMV transactions where the expiration date of the card is prior to the EMV CV DATE on the appropriate CPF record. Page 13-41. |
| 16 | Adds a description of the LCONF param RACAL-ANSI-METHOD. This param specifies whether to use the ANSI X9.17 encryption method for key exchanges instead of the default variant encryption method used by the ISO Host Interface process. This param only applies when using Thales e-Security HSMs without the Transaction Security Services process. When using the Transaction Security Services process, you configure the encryption method used in the TSS database. Page 16-2. |