

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Manual*

Number: BA-AE000-13

Date: Nov-2007

Software: Release 6.0, Version 8

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Manual*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the manual from release 6.0, version 7 to release 6.0, version 8.

Section/ Appendix	Major Changes
All	All references to Eracom have been changed to SafeNet (Eracom). SafeNet, Inc. acquired Eracom Technologies AG in 2005.
Preface	Adds a reference to the ANSI X9.24-1 standard to the prerequisite industry literature recommended for key management.
1	Adds a discussion of Chip Authentication Program (CAP) token validation to the “Chip Authentication” topic.
7	Adds Tidel to the list of BASE24-atm Device Handler processes that support message authentication code (MAC).
13	Adds a note in the overview to indicate that for electronically acquired (i.e., card-read) transactions, BASE24 automatically declines the transaction if the service code is set to 000. No configuration is required. This processing is performed to prevent a fraud scheme where phishers use a stolen PAN, expiration date, and CVD2 to encode a card with track data, using the CVD2 (printed on the card) in place of the CVD1 (encoded on the track), and a service code of zeroes in place of the actual service code. This scheme <i>tricks</i> the payment system into thinking the CVD1 is valid when it is actually the CVD2 that is validated.
15	Adds support for dynamic key management in the BASE24-atm Tidel Device Handler process. Clarifies that the Triton Device Handler module does not use the ATM-DH-DKM-MAC-ERR-LMT and ATM-DH-CONS-MAC-ERR-LMT LCONF params. The Triton Device Handler module loads a new MAC key whenever a MAC verification fails.

Section/ Appendix	Major Changes
------------------------------	----------------------

-
- | | |
|----|--|
| 16 | Adds a note for the CTP and CTR fields in Key Service Messages (KSMs) to indicate that for the BASE24 Interchange (BIC) ISO Interface, the field must contain at least six bytes populated with hexadecimal digits. If the field contains more than six bytes of data, the interface uses only the last six bytes. |
|----|--|