

Publications Reissue Highlights

Manual: *BASE24 Transaction Security Manual*

Number: BA-AE000-13

Date: 11/2004

Software: Release 6.0, Version 5

The following table highlights the major changes that have been made in the most recent update to the *BASE24 Transaction Security Manual*. The first column of the table lists the sections and appendixes in which major changes have been made. The second column of the table describes the major changes for each section or appendix. These changes update the manual to release 6.0, version 5.

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|--|
| 1 | <p>Adds a discussion of PIN verification value (PVV) security and the new MASK-POFST-PVV LCONF param to mask the display of the PVV in the POFST/PVV field on Cardholder Authorization File (CAF) screen 1.</p> <p>Updates the card verification discussion to include support for card verification digits (CVD) obtained from the magnetic stripe on a chip card, which is referred to as the integrated circuit card (ICC) card verification value (iCVV), and from American Express cards, which is referred to as the card security code (CSC).</p> <p>Adds a discussion of EMV 2000 support.</p> |
| 2 | <p>Adds DUKPT PIN encryption support for the BASE24-pos Hypercom Device Handler (HPDH) module.</p> <p>Clarifies the description of how the transaction counter is increased for the key serial number (KSN) in derived unique key per transaction (DUKPT) PIN blocks.</p> |
| 4 | <p>Adds DUKPT PIN encryption support for the BASE24-pos Hypercom Device Handler (HPDH) module.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

-
- | | |
|----|--|
| 8 | <p>Adds additional values to the BASE24-atm Release 5.0 token for Dutch security enhancements.</p> <p>Clarifies how the BASE24-pos Authorization process uses the value carried in the third byte of the PT-SRV-ENTRY-MDE field in the internal message to determine whether the terminal originating the transaction has PIN entry capabilities. This processing only applies when the PIN PROCESSING FLAG on screen 7 of the Card Prefix File (CPF) is set to a value of 2.</p> <p>Adds DUKPT PIN encryption support for the BASE24-pos Hypercom Device Handler (HPDH) module.</p> |
| 13 | <p>Adds support for card verification of the iCVV for chip cards.</p> <p>Adds support for verifying the American Express CSC.</p> <p>Updates the descriptions of the CRD-VRFY-FLG field in the internal message for BASE24-atm and BASE24-pos.</p> <p>Adds a description of the CRD-VRFY-FLG2 field in the internal message for BASE24-pos.</p> <p>Updates the card verification processing steps to indicate that BASE24 checks the CRD-VRFY-FLG to determine whether card verification has already been performed before it verifies the card. If it has, processing continues without verifying the card again.</p> |
| 14 | <p>Adds the POS-SETL-NOTIFY<i>identifier</i> param. This param is required for the ISO Host Interface process because the ACI Commerce Gateway product does not send the posting date in messages sent to the ISO Host Interface process. When this param is configured for the ISO Host Interface process, the Main Settlement process sends a 9502 cutover command to the ISO Host Interface process. When ISO Host Interface process receives this command, it updates a global posting date value that it uses to set the posting date for a transaction when the posting date is not included in the transaction.</p> |
| 15 | <p>Adds the new LCONF SECURE-DEV-xx assign and SECURE-DEV-ACCESS-TYPE param to notes describing how to use the Transaction Security Services process for dynamic key management with the BASE24-atm and BASE24-pos products.</p> |

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|----|---|
| 16 | <p>Corrects the outbound messages only value for the Key Direction field in the Security-Related Control Information (P-53) data element.</p> <p>Adds notes to the descriptions of the PIN KEY VARIANT and MAC KEY VARIANT fields on KEYF screen 3 or KEY6 screen 4. When using the Transaction Security Services process, the PIN KEY VARIANT field is hardcoded to a value of 1, regardless of the hardware security module used by BASE24 or the external processor. The MAC KEY VARIANT field is hardcoded to a value of 3 when using the Transaction Security Services process.</p> |
| 17 | <p>Updates the card verification description to include the integrated circuit card (ICC) card verification value (iCVV) for Europay, MasterCard, and Visa (EMV) chip cards, and the card security code (CSC) for American Express.</p> <p>Updates the authorization request cryptogram verification description to include support for EMV 2000.</p> <p>Adds Eracom to the list of security device vendors supported by BASE24.</p> <p>Adds a discussion of accessing up to 20 Transaction Security Services processes on a round-robin (i.e., rotating) basis. This is a new method of accessing Transaction Security Services processes in addition to the existing access method of a primary and secondary Transaction Security Services process. The new LCONF param SECURE-DEV-ACCESS-TYPE specifies which access method is used by a BASE24 process. Transaction Security Services processes accessed on a round-robin basis are configured in the new LCONF assigns SECURE-DEV-xx, where xx is any two characters.</p> <p>When using the round-robin access method, the security utilities in the BASE24 process use the new LCONF param SECURE-DEV-REINSTATE-TIME to determine the number of minutes a Transaction Security Services process is excluded from the rotation when it is marked down before the security utilities attempt to reopen the Transaction Security Services process.</p> <p>If you are using the Transaction Security Services process with either access method, the BASE24 process will attempt to reopen a failed Transaction Security Services process at the interval specified by the LCONF param SECURE-DEV-FAIL-NOTIFY, in addition to generating a critical event message.</p> |
| B | <p>Adds a discussion of how the Atalla Boxcar interface module uses option 023 to determine the end of an NSP command response when it is greater than 1024 bytes. If you change the setting of option 023 after the Boxcar interface module has been initialized, it may not be able to recognize the end of a response message from the NSP that is greater than 1024 bytes and may wait indefinitely.</p> |

ACI Worldwide Inc.