

Offset[Len] Field Name and Description Data Type

RECORD TLF

0 [474]

0 [76] head [HEAD]

The Transaction Log File (TLF) contains a record of every financial transaction (approved or denied) processed by BASE24-atm during a single processing day. It also contains settlement records for each ATM in the system. This file is an audit record at the transaction level of the system's processing.

The TLF is used by the BASE24-atm report programs to produce their reports and can also be extracted daily to provide detailed transaction data for processing by a host.

Records are written to the TLF sequentially, and each TLF record has two alternate keys which allow for perusal of the file via BASE24-atm file maintenance functions.

A new TLF is created by the Settlement Initiator process at logical network cutover. Once a new TLF is created, the previous TLF is closed and is available for reporting and extract processing.

The following pages describe the fields included in a TLF record. The information below summarizes other information specific to the TLF.

LCONF ASSIGN: TLF

The following fields contain header information for all TLF records.

0 [8] head.dat^tim TYPE BINARY 64 SIGNED.

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time tracking purposes.

8 [2] head.rec^typ.byte[0:1] PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM but the transaction was posted.
 21 = Exception caused by invalid data in the STM and the transaction was not posted.
 22 = Exception (for future use)

In situations where financial transactions cannot be processed because of invalid dates or invalid Track 2 data, the Authorization process logs the transactions to the TLF as exceptions (REC-TYP 20 or 21). Exception transactions are included as details in the BASE24-atm reports but are not included in the BASE24-atm settlement totals.

10	[4]	head.auth^ppd.byte[0:3]	PIC X(4).
----	-----	-------------------------	-----------

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

14	[24]	head.term	
----	------	-----------	--

The values in the following fields identify the terminal where the transaction originated.

14	[4]	head.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the terminal.

18	[4]	head.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the financial institution owning the terminal.

22	[16]	head.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	--	------------

Offset[Len] Field Name and Description Data Type

The terminal ID of the terminal originating the transaction.

38 [30] head.crd

The values in the following fields identify the card issuer and cardholder associated with the transaction.

38 [4] head.crd.ln.byte[0:3]
[LN] PIC X(4).

The logical network associated with the card issuer.

42 [4] head.crd.fiid.byte[0:3]
[FIID] PIC X(4).

The FIID of the card issuer.

46 [19] head.crd.pan [PAN]

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

46 [19] head.crd.pan.num.byte[0:18] PIC X(19).

65 [3] head.crd.mbr^num.byte[0:2]
[MBR-NUM] PIC 9(3).

The member number associated with the cardholder's account number.

68 [4] head.brch^id.byte[0:3]
[BRCH] PIC X(4).

The branch ID associated with the terminal originating the transaction.

```

82      [2]      auth.rte^stat.byte[0:1]      PIC 9(2).

```

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code used to determine the status of a message at the system level. Valid values are:

00 = No error
01 = Processing error
02 = Security device failure
11 = Destination not available
12 = Line down

84	[1]	auth.originator	PIC X(1).
----	-----	-----------------	-----------

An indicator identifying where the transaction originated. Valid values are:

1 = Device controlled by BASE24
2 = Device Handler
3 = Authorization
4 = Host Interface
5 = Host
6 = Interchange Interface
7 = Interchange

85	[1]	auth.responder	PIC X(1).
----	-----	----------------	-----------

An indicator identifying where the response message (0210) was generated. Valid values are:

0 = Default, the response has not been generated yet
1 = Device controlled by BASE24
2 = Device Handler
3 = Authorization
4 = Host Interface
5 = Host
6 = Interchange Interface
7 = Interchange
S = Secondary Authorizer

86	[8]	auth.entry^tim	TYPE BINARY 64 SIGNED.
----	-----	----------------	------------------------

The time the transaction entered the BASE24 system.

94	[8]	auth.exit^tim	TYPE BINARY 64 SIGNED.
----	-----	---------------	------------------------

The time the Host Interface or Interchange Interface transmitted the request to an authorizing entity.

Offset[Len] Field Name and Description Data Type

102 [8] auth.re^entry^tim TYPE BINARY 64 SIGNED.

The time the Host Interface or Interchange Interface received a response to its original request from the authorizing entity.

110 [6] auth.tran^dat [DAT]

The date (YYMMDD) on which the transaction began.

110 [2] auth.tran^dat.yy.byte[0:1] PIC X(2).

112 [2] auth.tran^dat.mm.byte[0:1] PIC X(2).

114 [2] auth.tran^dat.dd.byte[0:1] PIC X(2).

116 [8] auth.tran^tim [TIM]

The time (HHMMSSHH) the transaction entered the BASE24 system from a device, interchange, or acquirer host.

116 [2] auth.tran^tim.hh.byte[0:1] PIC X(2).

118 [2] auth.tran^tim.mm.byte[0:1] PIC X(2).

120 [2] auth.tran^tim.ss.byte[0:1] PIC X(2).

122 [2] auth.tran^tim.tt.byte[0:1] PIC X(2).

124 [6] auth.post^dat [DAT]

The date (YYMMDD) on which the transaction will be settled.

124 [2] auth.post^dat.yy.byte[0:1] PIC X(2).

126 [2] auth.post^dat.mm.byte[0:1] PIC X(2).

128 [2] auth.post^dat.dd.byte[0:1] PIC X(2).

130 [6] auth.acq^ichg^setl^dat
[DAT]

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The date (YYMMDD) this transaction will be settled by the interchange originating the transaction, if the transaction originates through an interchange.

130	[2]	auth.acq^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

132	[2]	auth.acq^ichg^setl^dat.mm.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

134	[2]	auth.acq^ichg^setl^dat.dd.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

136	[6]	auth.iss^ichg^setl^dat [DAT]	
-----	-----	---------------------------------	--

The date (YYMMDD) this transaction will be settled by the interchange authorizing the transaction, if an interchange was involved in processing.

136	[2]	auth.iss^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

138	[2]	auth.iss^ichg^setl^dat.mm.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

140	[2]	auth.iss^ichg^setl^dat.dd.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

142	[12]	auth.seq^num.byte[0:11]	PIC X(12).
-----	------	-------------------------	------------

The sequence number associated with this transaction. If the ATM does not generate a sequence number, the associated process generates one. This field remains unchanged through the life of the transaction. This field is set by the Device Handler, Interchange Interface, or Host Interface process.

154	[2]	auth.term^typ.byte[0:1]	PIC 9(2).
-----	-----	-------------------------	-----------

The type of terminal at which this transaction was initiated. Refer to the ATD and TDF DDL files for a list of valid values for this field

156	[2]	auth.tim^ofst	TYPE BINARY 16 SIGNED.
-----	-----	---------------	------------------------

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

158	[11]	auth.acq^inst^id^num.byte[0:10]	
-----	------	---------------------------------	--

Offset[Len]	Field Name and Description	Data Type
	[ID-NUM]	PIC 9(11).

The routing or transit number of the terminal owner.

169	[11]	auth.rcv^inst^id^num.byte[0:10]	
		[ID-NUM]	PIC 9(11).

The card-issuer routing or identification number.

180	[6]	auth.tran^cde.byte[0:5]	PIC X(6).
-----	-----	-------------------------	-----------

The values in the following fields define the transaction code.

180	[6]	auth.tran^cde^r	
		[REDEFINES TRAN^CDE]	

180	[2]	auth.tran^cde^r.t^cde.byte[0:1]	PIC X(2).
-----	-----	---------------------------------	-----------

The type of transaction. The following codes are supported by BASE24-atm; but be aware that not all of the codes listed are supported by all ATMs.

NOTE 1: The transaction codes of 25 and 26 are only supported with the definitions-based model of BASE24-atm Mobile Top-Up. The BASE24-atm Transaction Context Manager and certain Mobile Operator Interfaces process these transaction codes. BASE24-atm Authorization does not recognize these codes.

Valid values are:

- 03 = Check Guarantee
- 04 = Check Verify
- 10 = Withdrawal
- 11 = Cash Check
- 20 = Deposit
- 24 = Deposit with Cash Back
- 25 = Mobile Top-Up (NOTE 1)
- 26 = Mobile Top-Up with Funds (NOTE 1)
- 30 = Balance Inquiry
- 40 = Transfer
- 41 = Load Value
- 50 = Payment from/to
- 51 = Payment Enclosed
- 60 = Message Enclosed to Financial Institution
- 61 = Log Only

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

	62 = Card Review	
	70 = Statement print	
	81 = PIN change	
	82 = EMV PIN Unblock	
	U1 = SVC Balance Inquiry	

182	[2]	auth.tran^cde^r.t^from.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

The type of from account. Values are:

01 = Checking
11 = Savings
31 = Credit
70 = Electronic purse

184	[2]	auth.tran^cde^r.t^to.byte[0:1]	PIC X(2).
-----	-----	--------------------------------	-----------

The type of to account. Values are:

01 = Checking
11 = Savings
31 = Credit
70 = Electronic purse

186	[19]	auth.from^acct [ACCT]	
-----	------	-----------------------	--

The account number of the from account for the transaction. If the from account is not needed or known, this field contains zeros.

186	[19]	auth.from^acct.acct^num.byte[0:18]	PIC X(19).
-----	------	------------------------------------	------------

205	[1]	auth.user^fld1	PIC X(1).
-----	-----	----------------	-----------

This field is not used.

206	[19]	auth.to^acct [ACCT]	
-----	------	---------------------	--

The account number of the to account for the transaction. If the to account is not needed or known, this field contains zeros.

206	[19]	auth.to^acct.acct^num.byte[0:18]	PIC X(19).
-----	------	----------------------------------	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

225 [1]	auth.mult^acct	PIC 9(1).
---------	----------------	-----------

An indicator used to determine whether the transaction is a primary-account transaction, a multiple-account transaction, or a fast cash transaction. Valid values are:

- 0 = A primary-account transaction--the ATM where the transaction originated does not support multiple account selection.
- 1 = A multiple-account transaction--the ATM where the transaction originated does support multiple account selection.
- 2 = A fast cash transaction.

226 [8]	auth.amt^1	TYPE BINARY 64 SIGNED.
---------	------------	------------------------

The transaction amount requested. In the case of force post (0220) or reversal (0420) messages, this field contains the amount originally requested. For Adjustment (5400) messages, this field indicates the original completion amount. Note that for deposit with cash back transactions, this field contains the deposit amount. For split desposit transactions, this field contains the deposit amount for the first account involved in the transaction.

234 [8]	auth.amt^2	TYPE BINARY 64 SIGNED.
---------	------------	------------------------

For most reversal (0420) messages, this field contains the actual completion amount of the transaction. For reversal messages for deposit with cash-back transactions, this field contains the cash-back amount. For reversal messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For most response (0210) messages, this field contains a balance amount. This is the credit balance, for credit accounts; and it is the ledger balance for non-credit accounts. For response messages for deposit with cash back transactions, this field contains the cash-back amount. For reponse messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For most request (0200) messages, this field contains

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

zeros. For request messages for deposit with cash-back transactions, this field contains the cash-back amount. For request messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For adjustment (5400) messages, this field indicates the updated completion amount.

242	[8]	auth.amt^3	TYPE BINARY 64 SIGNED.
-----	-----	------------	------------------------

For most response (0210) messages, this field contains a balance amount. This is the available balance for non-credit accounts; and it is the available credit for credit accounts. For response messages for deposit with cash-back transactions and split deposit transactions this field contains zeroes.

For a reversal (0420) message which is the result of a deposit with cash back transaction, this field contains the deposit amount if the deposit part of the transaction did not complete successfully, and it contains the completed amount of the cash back part of the transaction if the deposit completed, but the cash back did not complete successfully. This is the only type of reversal that utilizes this field.

250	[4]	auth.dep^bal^cr	TYPE BINARY 32 SIGNED.
-----	-----	-----------------	------------------------

The amount of credit given on a deposit.

For a split deposit transaction, this field contains the amount of credit given to the first account involved in the transaction.

254	[1]	auth.dep^typ	PIC 9(1).
-----	-----	--------------	-----------

An indicator used to determine the type of depository used at the terminal. Valid values are:

0 = Normal envelope depository
1 = Commercial depository (e.g., Securomatic)
3 = Check depository
4 = BNA depository (Cash depository)

255	[3]	auth.resp^cde.byte[0:2]	PIC X(3).
-----	-----	-------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The values in the following fields define the response code assigned by the transaction authorizer.

255	[3]	auth.resp^cde^r [REDEFINES RESP^CDE]	
-----	-----	---	--

255	[1]	auth.resp^cde^r.resp^byte^1	PIC X(1).
-----	-----	-----------------------------	-----------

An indicator used to determine whether the card was returned or retained. Values are:

0 = Card was returned
1 = Card was retained

256	[2]	auth.resp^cde^r.resp^byte^2.byte[0:1]	PIC X(2).
-----	-----	---------------------------------------	-----------

A code identifying the reason the transaction was approved or denied. For a listing of the BASE24 transaction response codes, please refer to the BASE24-atm Transaction Processing Manual.

258	[25]	auth.term^name^loc.byte[0:24]	PIC X(25).
-----	------	-------------------------------	------------

The terminal name and location of the terminal that acquired the transaction.

283	[22]	auth.term^owner^name.byte[0:21]	PIC X(22).
-----	------	---------------------------------	------------

The name of the financial institution that owns the terminal that acquired the transaction.

305	[13]	auth.term^city.byte[0:12]	PIC X(13).
-----	------	---------------------------	------------

The city in which the terminal that acquired the transaction is located.

318	[3]	auth.term^st^x.byte[0:2]	PIC X(3).
-----	-----	--------------------------	-----------

The state in which the terminal that acquired the transaction is located.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

321	[2]	auth.term^cntry^x.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

A code indicating the country in which the terminal that acquired the transaction is located.

323	[28]	auth.orig	
-----	------	-----------	--

The original data elements apply to transaction reversals (0420) and adjustments (5400) only. If this transaction is a reversal or adjustment, these fields contain information on the original transaction.

323	[12]	auth.orig.oseq^num.byte[0:11]	PIC X(12).
-----	------	-------------------------------	------------

The sequence number that identifies the original transaction.

335	[4]	auth.orig.otran^dat.byte[0:3]	PIC X(4).
-----	-----	-------------------------------	-----------

The date of the original transaction.

339	[8]	auth.orig.otran^tim.byte[0:7]	PIC X(8).
-----	-----	-------------------------------	-----------

The time of the original transaction.

347	[4]	auth.orig.b24^post^dat.byte[0:3]	PIC X(4).
-----	-----	----------------------------------	-----------

The BASE24 posting date of the original transaction.

351	[3]	auth.orig^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

The type of currency involved in the original transaction.

354	[30]	auth.user^fld2.byte[0:29]	PIC X(30).
-----	------	---------------------------	------------

This field is not used.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

354	[30]	auth.mult^crncy [REDEFINES USER^FLD2]	
-----	------	--	--

The following fields are defined for multiple currency support, but they are not currently used by BASE24-atm.

354	[3]	auth.mult^crncy.auth^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code identifying the type of currency used in the authorization response.

357	[8]	auth.mult^crncy.auth^conv^rate.byte[0:7]	PIC 9(8).
-----	-----	--	-----------

The exchange rate of the authorizing institution. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

365	[3]	auth.mult^crncy.setl^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code identifying the type of currency used by the settlement entity.

368	[8]	auth.mult^crncy.setl^conv^rate.byte[0:7]	PIC 9(8).
-----	-----	--	-----------

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

376	[8]	auth.mult^crncy.conv^dat^tim	TYPE BINARY 64 SIGNED.
-----	-----	------------------------------	------------------------

The day and time when the exchange rate was applied. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time

Offset[Len]	Field Name and Description	Data Type
	tracking purposes.	

384	[2]	auth.rvsl^rsn.byte[0:1]	PIC 9(2).
-----	-----	-------------------------	-----------

An indicator used to identify the reason for a reversal (0420) or adjustment (5400) message type.

Valid values for a reversal message (0420) are:

- 01 = Time-out
- 02 = Command reject
- 03 = Destination not available
- 08 = Transaction canceled
- 10 = Hardware error
- 20 = Suspect transaction
- 30 = Funds side of stored value tran failed
- 31 = SVC side of stored value tran failed
- 40 = Split Routing Enabled; Secondary Service Not Approved

Valid values for an adjustment message (5400) are:

- 12 = Original amount incorrect
- 13 = ATM malfunction
- 14 = Suspicious reversal override
- 15 = Misdispense reversal override
- 16 = Duplicate transaction
- 17 = Reconciliation error
- 18 = PLUS add cash withdrawal or advance
- 21 = Message Authentication Code (MAC) failure
- 22 = MAC key synchronization error
- 23 = Message replay error
- 24 = Invalid MAC

386	[16]	auth.pin^ofst.byte[0:15]	PIC X(16).
-----	------	--------------------------	------------

The PIN offset value.

This is calculated by the Authorization process when the institution allows its cardholders to select or change their PINs.

402	[1]	auth.shrg^grp	PIC X(1).
-----	-----	---------------	-----------

An indicator used to identify the sharing group used to allow the transaction, if it was a not-on-us transaction; otherwise, this field contains a zero.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

403 [1]	auth.dest^order	PIC X(1).
------------	-----------------	-----------

An indicator used to determine which destination performed the final authorization. Valid values are:

A = Alternate destination
P = Primary destination

404 [6]	auth.auth^id^resp.byte[0:5]	PIC X(6).
------------	-----------------------------	-----------

The host-generated transaction sequence number used for logging and extract purposes only.

410 [9]	auth.refr	
------------	-----------	--

The values in the following fields indicate to Refresh when to impact the PBF and how to impact the balances when impacting is required. All are set by Authorization according to the transaction type.

410 [1]	auth.refr.imp^ind	PIC X(1).
------------	-------------------	-----------

An indicator used to determine whether this record should be considered when impacting a newly refreshed set of account records. Valid values are:

0 = Do not use this record for impacting.
1 = Use this record for impacting.

411 [2]	auth.refr.avail^imp[0:1]	PIC X(1).
------------	--------------------------	-----------

An indicator used to define how the value in the AVAIL-BAL field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

413 [2]	auth.refr.ledg^imp[0:1]	PIC X(1).
------------	-------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

An indicator used to define how the value in the LEDG-BAL field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
 1 = Add to balance
 2 = Subtract from balance

415	[2]	auth.refr.hld^amt^imp[0:1]	PIC X(1).
-----	-----	----------------------------	-----------

An indicator used to define how the value in the AMT-ON-HLD field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
 1 = Add to balance
 2 = Subtract from balance

417	[1]	auth.refr.caf^refr^ind	PIC X(1).
-----	-----	------------------------	-----------

An indicator used to determine when transaction impacting can be terminated. The value in this field is set by Authorization from a corresponding field in the IDF.

When Refresh finishes refreshing the CAF, it begins impacting the file with new transactions being added to the TLF. At that time, it increments the value in the CAF1 field in the IDF (A to B, B to C, C to D, etc.) and sends a message to Authorization containing the refreshed CAF file name and the new value in the CAF1 field. Thus, when transactions begin appearing in the TLF with the new value in the CAF-REFR-IND field, refresh knows that Authorization is using the refreshed CAF and that it can stop impacting the CAF.

418	[1]	auth.refr.user^fld3	PIC X(1).
-----	-----	---------------------	-----------

This field is not used.

419	[1]	auth.dep^set1^imp^flg	PIC X(1).
-----	-----	-----------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

An indicator identifying how deposits at an ATM impact settlement. Valid values are:

0 = Deposits do not impact settlement.
 1 = Envelope deposits do impact settlement.
 2 = Commercial deposits do impact settlement.
 3 = Both envelope and commercial deposits do impact settlement.

420	[1]	auth.adj^setl^imp^flg	PIC X(1).
-----	-----	-----------------------	-----------

An indicator used to determine whether adjustments impact settlement. Valid values are:

0 = Adjustments do not impact settlement.
 1 = Adjustments impact settlement.

421	[4]	auth.refr^ind	
-----	-----	---------------	--

An indicator used to determine when transaction impacting can be terminated. The value in this field is set by Authorization from a corresponding field in the IDF.

When Refresh finishes refreshing the PBF, it begins impacting the file with new transactions being added to the TLF. At that time, it increments the value in the REFR-IND field in the IDF (A to B, B to C, C to D, etc.) and sends a message to Authorization containing the refreshed PBF file name and the new value in the REFR-IND field. Thus, when transactions begin appearing in the TLF with the new value in the REFR-IND field, Refresh knows that Authorization is using the refreshed PBF and that it can stop impacting the PBF.

The first three settings (PBF1, PBF2, and PBF3) are present because an institution may have three separate PBFs used for BASE24-atm and, therefore, multiple refresh schedules: one for checking accounts (PBF1), one for savings accounts (PBF2), and one for credit accounts (PBF3). If only one PBF is maintained, only the PBF1 field is used. The PBF4 field is used in situations when a CPBF (used in conjunction with BASE24-cash manager) is used instead of a PBF.

421	[1]	auth.refr^ind.pbf1	PIC X(1).
-----	-----	--------------------	-----------

422	[1]	auth.refr^ind.pbf2	PIC X(1).
-----	-----	--------------------	-----------

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

423	[1]	auth.refr^ind.pbf3	PIC X(1).
-----	-----	--------------------	-----------

424	[1]	auth.refr^ind.pbf4	PIC X(1).
-----	-----	--------------------	-----------

425	[16]	auth.user^fld4.byte[0:15]	PIC X(16).
-----	------	---------------------------	------------

Taken from the RQST.USER-FLD5 in the STM. (The RQST.USER-FLD5 field in the STM is not used by BASE24-atm; but, it is routinely moved into the TLF record.)

441	[11]	auth.frwd^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

An identification number used to identify the forwarding institution.

452	[11]	auth.crd^acct^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

An identification number used to identify the card acceptor for a request message (0200) originating from an acquirer host.

463	[11]	auth.crd^iss^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

An identification number used to identify the card issuer for a response message (0210) originating from an authorizing host.

END [size 474]

Offset[Len] Field Name and Description Data Type

DEF TLF-TERM-SETL

0 [442]

0 [76] head [HEAD]

The Transaction Log File (TLF) contains a record of every financial transaction (approved or denied) processed by BASE24-atm during a single processing day. It also contains settlement records for each ATM in the system. This file is an audit record at the transaction level of the system's processing.

The TLF is used by the BASE24-atm report programs to produce their reports and can also be extracted daily to provide detailed transaction data for processing by a host.

Records are written to the TLF sequentially, and each TLF record has two alternate keys which allow for perusal of the file via BASE24-atm file maintenance functions.

A new TLF is created by the Settlement Initiator process at logical network cutover. Once a new TLF is created, the previous TLF is closed and is available for reporting and extract processing.

The following pages describe the fields included in a TLF record. The information below summarizes other information specific to the TLF.

LCONF ASSIGN: TLF

The following fields contain header information for all TLF records.

0 [8] head.dat^tim TYPE BINARY 64 SIGNED.

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time tracking purposes.

8 [2] head.rec^typ.byte[0:1] PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM but the transaction was posted.
 21 = Exception caused by invalid data in the STM and the transaction was not posted.
 22 = Exception (for future use)

In situations where financial transactions cannot be processed because of invalid dates or invalid Track 2 data, the Authorization process logs the transactions to the TLF as exceptions (REC-TYP 20 or 21). Exception transactions are included as details in the BASE24-atm reports but are not included in the BASE24-atm settlement totals.

10	[4]	head.auth^ppd.byte[0:3]	PIC X(4).
----	-----	-------------------------	-----------

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

14	[24]	head.term	
----	------	-----------	--

The values in the following fields identify the terminal where the transaction originated.

14	[4]	head.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the terminal.

18	[4]	head.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the financial institution owning the terminal.

22	[16]	head.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	--	------------

The branch ID associated with the terminal originating the transaction.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

72 [4]	head.regn^id.byte[0:3] [REGN]	PIC X(4).
--------	----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

76 [366]	term^setl	
----------	-----------	--

The following fields are included in terminal balancing records logged to the TLF. Terminal balancing records are identified by a value of 04 in the REC-TYP field in the TLF header. These records are further identified by values of 05, 06, or 09 in the TERM-SETL.ADMIN-CDE field.

76 [6]	term^setl.admin^dat [DAT]	
--------	------------------------------	--

The date (YYMMDD) the administrative transaction occurred.

76 [2]	term^setl.admin^dat.yy.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

78 [2]	term^setl.admin^dat.mm.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

80 [2]	term^setl.admin^dat.dd.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

82 [8]	term^setl.admin^tim [TIM]	
--------	------------------------------	--

The time (HHMMSSST) the administrative transaction occurred.

82 [2]	term^setl.admin^tim.hh.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

84 [2]	term^setl.admin^tim.mm.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

86 [2]	term^setl.admin^tim.ss.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

88 [2]	term^setl.admin^tim.tt.byte[0:1]	PIC X(2).
--------	----------------------------------	-----------

90 [2]	term^setl.admin^cde.byte[0:1]	PIC 9(2).
--------	-------------------------------	-----------

An indicator used to determine how the terminal was cut over. Values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

05 = Terminal cutover via the Device Handler.
 06 = Terminal cutover via CRT.
 09 = Forced cutover via Settlement Initiator.

92	[276]	term^setl.hopr[0:5]	
----	-------	---------------------	--

The following fields contain the hopper values from the TDF just prior to the terminal being balanced.

92	[2]	term^setl.hopr[0:5].contents.byte[0:1]	PIC X(2).
----	-----	--	-----------

A code used to identify the contents of the hopper.
 Valid values are:

00 = Cash
 01 = Coin

94	[8]	term^setl.hopr[0:5].beg^cash	TYPE BINARY 64 SIGNED.
----	-----	------------------------------	------------------------

The amount of currency in the hopper at the start of the current balancing period.

102	[8]	term^setl.hopr[0:5].cash^incr	TYPE BINARY 64 SIGNED.
-----	-----	-------------------------------	------------------------

The amount of currency added to the hopper during the current balancing period.

110	[8]	term^setl.hopr[0:5].cash^decr	TYPE BINARY 64 SIGNED.
-----	-----	-------------------------------	------------------------

The amount of currency removed from the hopper during the current balancing period.

118	[8]	term^setl.hopr[0:5].cash^out	TYPE BINARY 64 SIGNED.
-----	-----	------------------------------	------------------------

The amount of currency dispensed from the hopper through customer withdrawals between terminal balancing periods.

126	[8]	term^setl.hopr[0:5].end^cash	TYPE BINARY 64 SIGNED.
-----	-----	------------------------------	------------------------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The amount of currency remaining in the hopper at the end of the balancing period.

134	[3]	term^setl.hopr[0:5].crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code identifying the currency in the hopper. Valid values are listed in the booklet "Codes for the Representation of Currencies and Funds", ISO 4217:1990.

137	[1]	term^setl.hopr[0:5].user^fld5	PIC X(1).
-----	-----	-------------------------------	-----------

This field is not used.

368	[2]	term^setl.num^dep	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The number of envelope deposits accepted at the terminal since the last terminal balancing transaction.

370	[8]	term^setl.amt^dep	TYPE BINARY 64 SIGNED.
-----	-----	-------------------	------------------------

The unverified amount of the deposits accepted at the terminal since the last terminal balancing transaction.

378	[2]	term^setl.num^cmrcl^dep	TYPE BINARY 16 SIGNED.
-----	-----	-------------------------	------------------------

The number of envelope deposits accepted in the commercial (e.g., Securomatic) depository since the last terminal balancing transaction.

380	[8]	term^setl.amt^cmrcl^dep	TYPE BINARY 64 SIGNED.
-----	-----	-------------------------	------------------------

The unverified amount of the deposits accepted in the commercial (e.g., Securomatic) depository since the last terminal balancing transaction.

388	[2]	term^setl.num^pay	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The number of envelope payments accepted at the

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

terminal since the last terminal balancing transaction.

390	[8]	term^setl.amt^pay	TYPE BINARY 64 SIGNED.
-----	-----	-------------------	------------------------

The unverified amount of payments accepted at the terminal since the last terminal balancing transaction.

398	[2]	term^setl.num^msg	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The number of messages-to-institution transaction envelopes accepted since the last terminal balancing transaction.

400	[2]	term^setl.num^chk	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The total number of checks received (i.e. cashed or deposited) since the terminal was last balanced.

402	[8]	term^setl.amt^chk	TYPE BINARY 64 SIGNED.
-----	-----	-------------------	------------------------

The unverified total amount of checks received (i.e. cashed or deposited) since the terminal was last balanced. terminal balancing transaction.

410	[2]	term^setl.num^logonly	TYPE BINARY 16 SIGNED.
-----	-----	-----------------------	------------------------

The number of log-only transactions performed since the last terminal balancing transaction.

412	[2]	term^setl.ttl^env	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The estimated number of envelopes deposited at the terminal. This number is computed by the process creating the terminal settlement record by adding the values from the following fields in the TDF: NUM-DEP, NUM-PAY, NUM-MSG and NUM-CHK.

414	[2]	term^setl.crd^ret	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The number of cards retained since the last terminal

Offset[Len] Field Name and Description Data Type

balancing transaction.

416 [3] term^setl.setl^crncy^cde.byte[0:2]
[CRNCY-CDE] PIC 9(3).

A code indicating the type of currency used to represent the terminal's amount fields (i.e., the nation that printed the currency). Valid values are listed in the "ISO Codes for the Representation of Currencies and Funds", 4217-1990.

419 [1] term^setl.user^fld7 PIC X(1).

This field is not used.

420 [2] term^setl.tim^ofst TYPE BINARY 16 SIGNED.

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

422 [20] term^setl.setl^area.byte[0:19] PIC X(20).

This field is not used.

END [size 442]

Offset[Len] Field Name and Description Data Type

DEF TLF-TERM-CASH

0 [132]

0 [76] head [HEAD]

The Transaction Log File (TLF) contains a record of every financial transaction (approved or denied) processed by BASE24-atm during a single processing day. It also contains settlement records for each ATM in the system. This file is an audit record at the transaction level of the system's processing.

The TLF is used by the BASE24-atm report programs to produce their reports and can also be extracted daily to provide detailed transaction data for processing by a host.

Records are written to the TLF sequentially, and each TLF record has two alternate keys which allow for perusal of the file via BASE24-atm file maintenance functions.

A new TLF is created by the Settlement Initiator process at logical network cutover. Once a new TLF is created, the previous TLF is closed and is available for reporting and extract processing.

The following pages describe the fields included in a TLF record. The information below summarizes other information specific to the TLF.

LCONF ASSIGN: TLF

The following fields contain header information for all TLF records.

0 [8] head.dat^tim TYPE BINARY 64 SIGNED.

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time tracking purposes.

8 [2] head.rec^typ.byte[0:1] PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM but the transaction was posted.
 21 = Exception caused by invalid data in the STM and the transaction was not posted.
 22 = Exception (for future use)

In situations where financial transactions cannot be processed because of invalid dates or invalid Track 2 data, the Authorization process logs the transactions to the TLF as exceptions (REC-TYP 20 or 21). Exception transactions are included as details in the BASE24-atm reports but are not included in the BASE24-atm settlement totals.

10	[4]	head.auth^ppd.byte[0:3]	PIC X(4).
----	-----	-------------------------	-----------

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

14	[24]	head.term	
----	------	-----------	--

The values in the following fields identify the terminal where the transaction originated.

14	[4]	head.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the terminal.

18	[4]	head.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the financial institution owning the terminal.

22	[16]	head.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	--	------------

Offset[Len] Field Name and Description Data Type

The terminal ID of the terminal originating the transaction.

38 [30] head.crd

The values in the following fields identify the card issuer and cardholder associated with the transaction.

38 [4] head.crd.ln.byte[0:3]
[LN] PIC X(4).

The logical network associated with the card issuer.

42 [4] head.crd.fiid.byte[0:3]
[FIID] PIC X(4).

The FIID of the card issuer.

46 [19] head.crd.pan [PAN]

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

46 [19] head.crd.pan.num.byte[0:18] PIC X(19).

65 [3] head.crd.mbr^num.byte[0:2]
[MBR-NUM] PIC 9(3).

The member number associated with the cardholder's account number.

68 [4] head.brch^id.byte[0:3]
[BRCH] PIC X(4).

The branch ID associated with the terminal originating the transaction.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

72	[4]	head.regn^id.byte[0:3] [REGN]	PIC X(4).
----	-----	----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

76	[56]	term^cash	
----	------	-----------	--

The following fields are included in Terminal Cash Adjustment records logged to the TLF. Terminal Cash Adjustment records are identified by a value of 04 in the REC-TYP field in the TLF header. These records are further identified by values of 01, 02, 03, 04, 07, and 08 in the TERM-CASH.ADMIN-CDE field.

76	[6]	term^cash.admin^dat [DAT]	
----	-----	------------------------------	--

The date (YYMMDD) the administrative transaction occurred.

76	[2]	term^cash.admin^dat.yy.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

78	[2]	term^cash.admin^dat.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

80	[2]	term^cash.admin^dat.dd.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

82	[8]	term^cash.admin^tim [TIM]	
----	-----	------------------------------	--

The time (HHMMSSTT) the administrative transaction occurred.

82	[2]	term^cash.admin^tim.hh.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

84	[2]	term^cash.admin^tim.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

86	[2]	term^cash.admin^tim.ss.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

88	[2]	term^cash.admin^tim.tt.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

90	[2]	term^cash.admin^cde.byte[0:1]	PIC 9(2).
----	-----	-------------------------------	-----------

A code indicating a transaction type that involves increases and decreases of currency. This code also

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

identifies whether the transaction was performed by a Device Handler or at a CRT. Valid values are:

01 = Initialize cash, hopper #n (Device Handler).
 02 = Initialize cash, hopper #n (CRT).
 03 = Increase cash, hopper #n (Device Handler).
 04 = Increase cash, hopper #n (CRT).
 07 = Decrease cash, hopper #n (Device Handler).
 08 = Decrease cash, hopper #n (CRT).

92	[1]	term^cash.hopr^num	PIC X(1).
----	-----	--------------------	-----------

The number of the hopper being affected by the administrative transaction.

93	[2]	term^cash.hopr^contents.byte[0:1]	PIC X(2).
----	-----	-----------------------------------	-----------

The contents contained in the hopper. Valid values are:

00 = Cash
 01 = Coin

95	[12]	term^cash.amt.byte[0:11]	PIC 9(12).
----	------	--------------------------	------------

The amount of increase or decrease to the hopper because of the administrative transaction.

107	[3]	term^cash.crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code identifying the type of currency used for the administrative transaction. Valid values are listed in the "ISO Codes for the Representation of Currencies and Funds", 4217-1990.

110	[2]	term^cash.tim^ofst	TYPE BINARY 16 SIGNED.
-----	-----	--------------------	------------------------

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

112	[20]	term^cash.cash^area.byte[0:19]	PIC X(20).
-----	------	--------------------------------	------------

MM/DD/YY HH:MM	\$VOLUME AT60DDL	TLF-TERM-CASH	PAGE: 33
Offset[Len]	Field Name and Description		Data Type

This field is not used.

END [size 132]

Offset[Len] Field Name and Description Data Type

DEF TLF-SETL-TTL

0 [166]

0 [76] head [HEAD]

The Transaction Log File (TLF) contains a record of every financial transaction (approved or denied) processed by BASE24-atm during a single processing day. It also contains settlement records for each ATM in the system. This file is an audit record at the transaction level of the system's processing.

The TLF is used by the BASE24-atm report programs to produce their reports and can also be extracted daily to provide detailed transaction data for processing by a host.

Records are written to the TLF sequentially, and each TLF record has two alternate keys which allow for perusal of the file via BASE24-atm file maintenance functions.

A new TLF is created by the Settlement Initiator process at logical network cutover. Once a new TLF is created, the previous TLF is closed and is available for reporting and extract processing.

The following pages describe the fields included in a TLF record. The information below summarizes other information specific to the TLF.

LCONF ASSIGN: TLF

The following fields contain header information for all TLF records.

0 [8] head.dat^tim TYPE BINARY 64 SIGNED.

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time tracking purposes.

8 [2] head.rec^typ.byte[0:1] PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM but the transaction was posted.
 21 = Exception caused by invalid data in the STM and the transaction was not posted.
 22 = Exception (for future use)

In situations where financial transactions cannot be processed because of invalid dates or invalid Track 2 data, the Authorization process logs the transactions to the TLF as exceptions (REC-TYP 20 or 21). Exception transactions are included as details in the BASE24-atm reports but are not included in the BASE24-atm settlement totals.

10	[4]	head.auth^ppd.byte[0:3]	PIC X(4).
----	-----	-------------------------	-----------

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

14	[24]	head.term	
----	------	-----------	--

The values in the following fields identify the terminal where the transaction originated.

14	[4]	head.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the terminal.

18	[4]	head.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the financial institution owning the terminal.

22	[16]	head.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	--	------------

The branch ID associated with the terminal originating the transaction.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

72	[4]	head.regn^id.byte[0:3] [REGN]	PIC X(4).
----	-----	----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

76	[90]	setl^ttl	
----	------	----------	--

The following fields are included in Terminal Settlement records logged to the TLF. Terminal Settlement records are identified by a value of 04 in the REC-TYP field in the TLF header. These records are further identified by values of 20, 21, and 22 in the SETL-TTL.ADMIN-CDE field.

76	[6]	setl^ttl.admin^dat [DAT]	
----	-----	-----------------------------	--

The date (YYMMDD) the administrative transaction occurred.

76	[2]	setl^ttl.admin^dat.yy.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

78	[2]	setl^ttl.admin^dat.mm.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

80	[2]	setl^ttl.admin^dat.dd.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

82	[8]	setl^ttl.admin^tim [TIM]	
----	-----	-----------------------------	--

The time (HHMMSSST) the administrative transaction occurred.

82	[2]	setl^ttl.admin^tim.hh.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

84	[2]	setl^ttl.admin^tim.mm.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

86	[2]	setl^ttl.admin^tim.ss.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

88	[2]	setl^ttl.admin^tim.tt.byte[0:1]	PIC X(2).
----	-----	---------------------------------	-----------

90	[2]	setl^ttl.admin^cde.byte[0:1]	PIC 9(2).
----	-----	------------------------------	-----------

An indicator used to determine the type of settlement transaction and originator of the transaction. Valid

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

values are:

20 = Terminal totals sent by the CRT

21 = Terminal totals sent by the Device Handler

22 = Terminal totals sent by the Settlement Initiator

92	[12]	setl^ttl.term^db.byte[0:11]	PIC 9(12).
----	------	-----------------------------	------------

The unverified amount of terminal debits since the terminal was last balanced. The amount in this field consists of debits from the institution's point of view. Transaction amounts are added to the balance in this field for:

- o On-us and not-on-us deposits. This includes all types of deposit transactions (i.e. deposit transactions, split deposit transactions and deposit with cash back transactions). Note that these transactions are supported for envelop, commercial and check deposit types.
- o On-us and not-on-us payment-enclosed transactions
- o On-us and not-on-us transfers
- o On-us and not-on-us payments between accounts

104	[12]	setl^ttl.term^cr.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The total amount of terminal credits since the terminal was last balanced. The amount in this field consists of credits from the institution's point of view. Transaction amounts are added to the balance in this field for:

- o On-us and not-on-us withdrawals
- o On-us and not-on-us cash checks
- o On-us and not-on-us deposits with cash back. Note that only the cash back amount is included in the TERM-CR amount.
- o On-us and not-on-us transfers
- o On-us and not-on-us payments between accounts

116	[12]	setl^ttl.on^us^db.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The total amount of on-us debits since the terminal was last balanced. The amount in this field consists of debits from the customer's point of view. Transaction amounts are added to the balance in this field for:

- o On-us withdrawals
- o On-us cash checks
- o On-us and not-on-us deposits with cash back. Note that only the cash back amount is included in the ON-US-DB amount.
- o On-us transfers
- o On-us payments between accounts

128	[12]	setl^ttl.on^us^cr.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The total amount of on-us credits since the terminal was last balanced. The amount in this field consists of credits from the customer's point of view. Transaction amounts are added to the balance in this field for:

- o On-us deposits. This includes all types of deposit transactions (i.e. deposit transactions, split deposit transactions and deposit with cash back transactions). Note that these transactions are supported for envelop, commercial and check deposit types.
- o On-us payment enclosed transactions
- o On-us transfers
- o On-us payments between accounts

140	[3]	setl^ttl.crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used during settlement. Valid values are listed in the "ISO Codes for the Representation of Currencies and Funds", 4217-1990.

143	[1]	setl^ttl.user^fld9	PIC X(1).
-----	-----	--------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

This field is not used.

144	[2]	setl^ttl.tim^ofst	TYPE BINARY 16 SIGNED.
-----	-----	-------------------	------------------------

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

146	[20]	setl^ttl.ttl^area.byte[0:19]	PIC X(20).
-----	------	------------------------------	------------

This field is not used.

END [size 166]