

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

DEF TLFX

0 [574]

0 [89] headx [HEADX]

The following pages describe the fields included in the TLF extract record format.

The following fields contain header information for all TLF extract records.

0 [19] headx.dat^tim.byte[0:18] PIC 9(19).

The date and time the record was logged.

19 [2] headx.rec^typ.byte[0:1] PIC X(2).

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM,
 but the transaction was posted.
 21 = Exception caused by invalid data in the STM
 and the transaction was not posted.
 22 = Exception (for future use)

21 [4] headx.auth^ppd.byte[0:3] PIC X(4).

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

25 [24] headx.term

The values in the following fields identify the terminal where the transaction originated.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

25	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	---------------------------------	-----------

The logical network associated with the terminal.

29	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------------	-----------

The FIID of the financial institution owning the terminal.

33	[16]	headx.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	---	------------

The terminal ID of the terminal originating the transaction.

49	[30]	headx.crd	
----	------	-----------	--

The values in the following fields identify the card issuer and cardholder associated with the transaction.

49	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the card issuer.

53	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the card issuer.

57	[19]	headx.crd.pan.byte[0:18]	PIC X(19).
----	------	--------------------------	------------

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

76 [3]	headx.crd.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
-------------	--	-----------

The member number associated with the cardholder's account number.

79 [4]	headx.brch^id.byte[0:3] [BRCH]	PIC X(4).
-------------	-----------------------------------	-----------

The branch ID associated with the terminal originating the transaction.

83 [4]	headx.regn^id.byte[0:3] [REGN]	PIC X(4).
-------------	-----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

87 [2]	headx.user^fldlx.byte[0:1]	PIC X(2).
-------------	----------------------------	-----------

This field is not used.

89 [485]	authx [AUTHX]
---------------	------------------------------------

The following fields are included in financial transaction records logged to the TLF in ASCII-only format. Financial transaction records are identified by values of 01, 20, 21, or 22 in the REC-TYP field in the TLF header.

89 [2]	authx.typ^cde.byte[0:1]	PIC X(2).
-------------	-------------------------	-----------

A code used to determine whether an envelope or a check was involved in the transaction. The value in this field is set by Authorization at the time the record is logged. Valid values are:

30 = An envelope was used.
31 = An envelope was not used.
32 = A check was used.

If a check was used in the transaction, Authorization

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

will set this field to 32. If a check was not used in the transaction and the transaction is a deposit, split deposit, deposit with cash back, payment enclosed, or message to financial institution, Authorization will set the value in this field to 30. Otherwise, it will set the value in this field to 31.

91	[4]	authx.typ.byte[0:3]	PIC 9(4).
----	-----	---------------------	-----------

The type of message associated with this record. Valid values are:

0210 = Authorization response
0220 = Authorization advice (force post)
0420 = Reversal
5400 = Transaction adjustment
9980 = Information--money in drawer
9991 = Log request

95	[2]	authx.rte^stat.byte[0:1]	PIC 9(2).
----	-----	--------------------------	-----------

A code used to determine the status of a message at the system level. Valid values are:

00 = No error
01 = Processing error
02 = Security device failure
11 = Destination not available
12 = Line down

97	[1]	authx.originator	PIC X(1).
----	-----	------------------	-----------

An indicator identifying where the transaction originated. Valid values are:

1 = Device controlled by BASE24
2 = Device Handler
3 = Authorization
4 = Host Interface
5 = Host
6 = Interchange Interface
7 = Interchange

98	[1]	authx.responder	PIC X(1).
----	-----	-----------------	-----------

An indicator identifying where the response message

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

(0210) was generated. Valid values are:

0 = Default, the response has not been generated yet
 1 = Device controlled by BASE24
 2 = Device Handler
 3 = Authorization
 4 = Host Interface
 5 = Host
 6 = Interchange Interface
 7 = Interchange

99	[19]	authx.entry^tim.byte[0:18]	PIC 9(19).
----	------	----------------------------	------------

The time the transaction entered the BASE24 system.

118	[19]	authx.exit^tim.byte[0:18]	PIC 9(19).
-----	------	---------------------------	------------

The time the Host Interface or Interchange Interface transmitted the request to the authorizing entity.

137	[19]	authx.re^entry^tim.byte[0:18]	PIC 9(19).
-----	------	-------------------------------	------------

The time the Host Interface or Interchange Interface received a response to its original request from the authorizing entity.

156	[6]	authx.tran^dat [DAT]	
-----	-----	----------------------	--

The date (YYMMDD) on which the transaction began.

156	[2]	authx.tran^dat.yy.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

158	[2]	authx.tran^dat.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

160	[2]	authx.tran^dat.dd.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

162	[8]	authx.tran^tim [TIM]	
-----	-----	----------------------	--

The time (HHMMSSHH) the transaction entered the BASE24 system from a device, interchange, or acquirer host.

162	[2]	authx.tran^tim.hh.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

164	[2]	authx.tran^tim.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

166	[2]	authx.tran^tim.ss.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

168	[2]	authx.tran^tim.tt.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

170	[6]	authx.post^dat [DAT]	
-----	-----	----------------------	--

The date (YYMMDD) on which the transaction will be settled.

170	[2]	authx.post^dat.yy.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

172	[2]	authx.post^dat.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

174	[2]	authx.post^dat.dd.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

176	[6]	authx.acq^ichg^setl^dat [DAT]	
-----	-----	----------------------------------	--

The date (YYMMDD) this transaction will be settled by the interchange originating the transaction, if the transaction originates through an interchange.

176	[2]	authx.acq^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

178	[2]	authx.acq^ichg^setl^dat.mm.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

180	[2]	authx.acq^ichg^setl^dat.dd.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

182	[6]	authx.iss^ichg^setl^dat [DAT]	
-----	-----	----------------------------------	--

The date (YYMMDD) this transaction will be settled by the interchange authorizing the transaction, if an interchange was involved in processing.

182	[2]	authx.iss^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

184	[2]	authx.iss^ichg^setl^dat.mm.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

186	[2]	authx.iss^ichg^setl^dat.dd.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

188	[12]	authx.seq^num.byte[0:11]	PIC X(12).
-----	------	--------------------------	------------

The sequence number associated with this transaction.
If the ATM does not generate a sequence number, the

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

associated process generates one. This field remains unchanged through the life of the transaction. This field is set by the Device Handler, Interchange Interface, or Host Interface process.

200	[2]	authx.term^typ.byte[0:1]	PIC 9(2).
-----	-----	--------------------------	-----------

The type of terminal at which this transaction initiated. Valid values are:

- 01 = Diebold 910
- 02 = IBM 3624 Version 8--dual cartridge
- 03 = Docutel 2300
- 04 = Burroughs RT650/750
- 05 = Diebold 600
- 06 = NCR 1770/1780
- 09 = Diebold 911 outside device
- 10 = Diebold 911 lobby device
- 11 = Docutel 5100
- 14 = IBM 3624 Version 7 - single cartridge
- 15 = IBM 3624 Version 7 - dual cartridge
- 16 = IBM 3614 Version 6 - single cartridge
- 17 = IBM 3614 Version 6 - dual cartridge
- 18 = IBM 3624 Version 8 - single cartridge
- 20 = Diebold 912
- 22 = NCR 5070/5080
- 26 = IBM 4730 single console
- 27 = IBM 4730 dual console
- 28 = Omron ATM
- 29 = Omron RCD
- 30 = Diebold 1000
- 32 = Mirror
- 40 = Diebold 906
- 45 = IBM 3614 Version 5 - single cartridge
- 46 = IBM 3614 Version 5 - dual cartridge
- 48 = IBM 3624 Version 8 - single cartridge D01
- 49 = IBM 3624 Version 8 - dual cartridge D02

202	[5]	authx.tim^ofst.byte[0:4]	PIC 9(5).
-----	-----	--------------------------	-----------

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

207	[11]	authx.acq^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

The routing or transit number of the terminal owner.

Offset[Len] Field Name and Description Data Type

218 [11] authx.rcv^inst^id^num.byte[0:10]
[ID-NUM] PIC 9(11).

The card-issuer routing or identification number.

229 [6] authx.tran^cde.byte[0:5] PIC X(6).

The values in the following fields define the transaction code.

229 [6] authx.tran^cde^r
[REDEFINES TRAN^CDE]

229 [2] authx.tran^cde^r.t^cde.byte[0:1] PIC X(2).

The type of transaction. The following codes are supported by BASE24-atm; but be aware that not all of the codes listed are supported by all ATMs. Values are:

03 = Check Guarantee
04 = Check Verify
10 = Withdrawal
11 = Cash Check
20 = Deposit
24 = Deposit with Cash Back
30 = Balance Inquiry
40 = Transfer
41 = Load Value
50 = Payment from/to
51 = Payment Enclosed
60 = Message Enclosed to Financial Institution
61 = Log Only
62 = Card Review
70 = Statement printon.
81 = PIN change
82 = EMV PIN Unblock
U1 = SVC Balance Inquiry

231 [2] authx.tran^cde^r.t^from.byte[0:1] PIC X(2).

The type of from account. Values are:

01 = Checking
11 = Savings

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

31 = Credit
70 = Electronic purse

233	[2]	authx.tran^cde^r.t^to.byte[0:1]	PIC X(2).
-----	-----	---------------------------------	-----------

The type of to account. Values are:

01 = Checking
11 = Savings
31 = Credit
70 = Electronic purse

235	[19]	authx.from^acct.byte[0:18]	PIC X(19).
-----	------	----------------------------	------------

The account number of the from account for the transaction. If the from account is not needed or known, this field contains zeros.

254	[1]	authx.user^fld1	PIC X(1).
-----	-----	-----------------	-----------

This field is not used.

255	[19]	authx.to^acct.byte[0:18]	PIC X(19).
-----	------	--------------------------	------------

The account number of the to account of the transaction. If the to account is not needed or known, this field contains zeros.

274	[1]	authx.mult^acct	PIC 9(1).
-----	-----	-----------------	-----------

An indicator used to determine whether the transaction is a primary-account transaction, a multiple-account transaction, or a fast cash transaction. Valid values are:

0 = A primary-account transaction--the ATM where the transaction originated does not support multiple account selection.
1 = A multiple-account transaction--the ATM where the transaction originated does support multiple account selection.
2 = A fast cash transaction.

Offset[Len]	Field Name and Description	Data Type
275 [19]	authx.amt^1.byte[0:18]	PIC 9(19).

The transaction amount requested. In the case of force post (0220) or reversal (0420) messages, this field contains the amount originally requested. For Adjustment (5400) messages, this field indicates the original completion amount. Note that for deposit with cash back transactions, this field contains the deposit amount. For split desposit transactions, this field contains the deposit amount for the first account involved in the transaction.

294 [19]	authx.amt^2.byte[0:18]	PIC 9(19).
----------	------------------------	------------

For most reversal (0420) messages this field contains the actual completion amount of the transaction. For reversal messages for deposit with cash-back transactions, this field contains the cash-back amount. For reversal messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For most response (0210) messages, this field contains a balance amount. This is the credit balance, for credit accounts; and it is the ledger balance for non-credit accounts. For response messages for deposit with cash back transactions, this field contains the cash-back amount. For reponse messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For most request (0200) messages, this field contains zeros. For request messages for deposit with cash-back transactions, this field contains the cash-back amount. For request messages for split deposit transactions, this field contains the deposit amount for the second account involved in the transaction.

For adjustment (5400) messages, this field indicates the updated completion amount.

313 [19]	authx.amt^3.byte[0:18]	PIC 9(19).
----------	------------------------	------------

For most response (0210) messages, this field contains a balance amount. This is the available balance for non-credit accounts; and it is the available credit for credit accounts. For response messages for deposit with cash-back transactions and split deposit

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

transactions this field contains zeroes.

For a reversal (0420) message which is the result of a deposit with cash back transaction, this field contains the deposit amount if the deposit part of the transaction did not complete successfully, and it contains the completed amount of the cash back part of the transaction if the deposit completed, but the cash back did not complete successfully. This is the only type of reversal that utilizes this field.

332	[10]	authx.dep^bal^cr.byte[0:9]	PIC 9(10).
-----	------	----------------------------	------------

The amount of credit given on a deposit.

For a split deposit transaction, this field contains the amount of credit given to the first account involved in the transaction.

342	[1]	authx.dep^typ	PIC 9(1).
-----	-----	---------------	-----------

An indicator used to determine the type of depository used at the terminal. Valid values are:

0 = Normal envelope depository
 1 = Commercial depository (e.g., Securomatic)
 3 = Check depository
 4 = BNA depository (Cash depository)

343	[3]	authx.resp^cde.byte[0:2]	PIC X(3).
-----	-----	--------------------------	-----------

The values in the following fields define the response code assigned by the transaction authorizer.

343	[3]	authx.resp^cde^r	[REDEFINES RESP^CDE]
-----	-----	------------------	----------------------

343	[1]	authx.resp^cde^r.resp^byte^1	PIC X(1).
-----	-----	------------------------------	-----------

An indicator used to determine whether the card was returned or retained. Values are:

0 = Card was returned
 1 = Card was retained

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

344 [2]	authx.resp^cde^r.resp^byte^2.byte[0:1]	PIC X(2).
---------	--	-----------

A code identifying the reason the transaction was approved or denied. For a listing of the BASE24 transaction response codes, please refer to the BASE24-atm Transaction Processing Manual.

346 [25]	authx.term^name^loc.byte[0:24]	PIC X(25).
----------	--------------------------------	------------

The terminal name and location of the terminal that acquired the transaction.

371 [22]	authx.term^owner^name.byte[0:21]	PIC X(22).
----------	----------------------------------	------------

The name of the financial institution that owns the terminal that acquired the transaction.

393 [13]	authx.term^city.byte[0:12]	PIC X(13).
----------	----------------------------	------------

The city in which the terminal that acquired the transaction is located.

406 [3]	authx.term^st^x.byte[0:2]	PIC X(3).
---------	---------------------------	-----------

The state in which the terminal that acquired the transaction is located.

409 [2]	authx.term^cntry^x.byte[0:1]	PIC X(2).
---------	------------------------------	-----------

A code indicating the country in which the terminal that acquired the transaction is located.

411 [28]	authx.orig	
----------	------------	--

The original data elements apply to transaction reversals (0420) and adjustments (5400) only. If this transaction is a reversal or adjustment, these fields contain information on the original transaction.

411 [12]	authx.orig.oseq^num.byte[0:11]	PIC X(12).
----------	--------------------------------	------------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The sequence number that identifies the original transaction.

423	[4]	authx.orig.otran^dat.byte[0:3]	PIC X(4).
-----	-----	--------------------------------	-----------

The date of the original transaction.

427	[8]	authx.orig.otran^tim.byte[0:7]	PIC X(8).
-----	-----	--------------------------------	-----------

The time of the original transaction.

435	[4]	authx.orig.b24^post^dat.byte[0:3]	PIC X(4).
-----	-----	-----------------------------------	-----------

The BASE24 posting date of the original transaction.

439	[3]	authx.orig^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

The type of currency involved in the original transaction.

442	[41]	authx.user^fld2.byte[0:40]	PIC X(41).
-----	------	----------------------------	------------

This field is not used.

442	[41]	authx.mult^crncy [REDEFINES USER^FLD2]	
-----	------	---	--

The following fields are defined for multiple currency support, but they are not currently used by BASE24-atm.

442	[3]	authx.mult^crncy.auth^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code identifying the type of currency used in the authorization response.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

445 [8]	authx.mult^crncy.auth^conv^rate.byte[0:7]	PIC 9(8).
------------	---	-----------

The exchange rate of the authorizing institution. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

453 [3]	authx.mult^crncy.setl^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
------------	--	-----------

A code identifying the type of currency used by the settlement entity.

456 [8]	authx.mult^crncy.setl^conv^rate.byte[0:7]	PIC 9(8).
------------	---	-----------

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

464 [19]	authx.mult^crncy.conv^dat^tim.byte[0:18]	PIC 9(19).
-------------	--	------------

The day and time when the exchange rate was applied. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility. It is used for time tracking purposes.

483 [2]	authx.rvsl^rsn.byte[0:1]	PIC 9(2).
------------	--------------------------	-----------

An indicator used to identify the reason for a reversal (0420) or adjustment (5400) message type.

Valid values for a reversal message (0420) are:

- 01 = Time-out
- 02 = Command reject
- 03 = Destination not available
- 08 = Transaction canceled
- 10 = Hardware error
- 20 = Suspect transaction
- 30 = Funds side of stored value tran failed

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

31 = SVC side of stored value tran failed

Valid values for an adjustment message (5400) are:

12 = Original amount incorrect

13 = ATM malfunction

14 = Suspicious reversal override

15 = Misdispense reversal override

16 = Duplicate transaction

17 = Reconciliation error

18 = PLUS add cash withdrawal or advance

21 = Message Authentication Code (MAC) failure

22 = MAC key synchronization error

23 = Message replay error

24 = Invalid MAC

485	[16]	authx.pin^ofst.byte[0:15]	PIC X(16).
-----	------	---------------------------	------------

The PIN offset value for the PIN.

501	[1]	authx.shrg^grp	PIC X(1).
-----	-----	----------------	-----------

An indicator used to identify the sharing group used to allow the transaction, if it was a not-on-us transaction; otherwise, this field contains a zero.

502	[1]	authx.dest^order	PIC X(1).
-----	-----	------------------	-----------

An indicator used to determine which destination performed the final authorization. Valid values are:

A = Alternate destination

P = Primary destination

503	[6]	authx.auth^id^resp.byte[0:5]	PIC X(6).
-----	-----	------------------------------	-----------

The host-generated transaction sequence number used for logging and extract purposes only.

509	[9]	authx.refr	
-----	-----	------------	--

The values in the following fields indicate to Refresh when to impact the PBF and how to impact the balances when impacting is required. All are set by

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

Authorization according to the transaction type.

509	[1]	authx.refr.imp^ind	PIC X(1).
-----	-----	--------------------	-----------

An indicator used to determine whether this record should be considered when impacting a newly refreshed set of account records. Valid values are:

0 = Do not use this record for impacting.
1 = Use this record for impacting.

510	[2]	authx.refr.avail^imp[0:1]	PIC X(1).
-----	-----	---------------------------	-----------

An indicator used to define how the value in the AVAIL-BAL field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

512	[2]	authx.refr.ledg^imp[0:1]	PIC X(1).
-----	-----	--------------------------	-----------

An indicator used to define how the value in the LEDG-BAL field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

514	[2]	authx.refr.hld^amt^imp[0:1]	PIC X(1).
-----	-----	-----------------------------	-----------

An indicator used to define how the value in the AMT-ON-HLD field is impacted in the PBF account records. The first occurrence defines impacting on the from account and the second occurrence defines impacting on the to account. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

516 [1]	authx.refr.caf^refr^ind	PIC X(1).
---------	-------------------------	-----------

An indicator used to determine when transaction impacting can be terminated. The value in this field is set by Authorization from a corresponding field in the IDF.

When Refresh finishes refreshing the CAF, it begins impacting the file with new transactions being added to the TLF. At that time, it increments the value in the CAF1 field in the IDF (A to B, B to C, C to D, etc.) and sends a message to Authorization containing the refreshed CAF file name and the new value in the CAF1 field. Thus, when transactions begin appearing in the TLF with the new value in the CAF-REFR-IND field, refresh knows that Authorization is using the refreshed CAF and that it can stop impacting the CAF.

517 [1]	authx.refr.user^fld3	PIC X(1).
---------	----------------------	-----------

This field is not used.

518 [1]	authx.dep^setl^imp^flg	PIC X(1).
---------	------------------------	-----------

An indicator identifying how deposits at an ATM impact settlement. Valid values are:

- 0 = Deposits do not impact settlement.
- 1 = Envelope deposits do impact settlement.
- 2 = Commercial deposits do impact settlement.
- 3 = Both envelope and commercial deposits do impact settlement.

519 [1]	authx.adj^setl^imp^flg	PIC X(1).
---------	------------------------	-----------

An indicator used to determine whether adjustments impact settlement. Valid values are:

- 0 = Adjustments do not impact settlement.
- 1 = Adjustments impact settlement.

520 [4]	authx.refr^ind	
---------	----------------	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

An indicator used to determine when transaction impacting can be terminated. The value in this field is set by Authorization from a corresponding field in the IDF.

When Refresh finishes refreshing the PBF, it begins impacting the file with new transactions being added to the TLF. At that time, it increments the value in the REFR-IND field in the IDF (A to B, B to C, C to D, etc.) and sends a message to Authorization containing the refreshed PBF file name and the new value in the REFR-IND field. Thus, when transactions begin appearing in the TLF with the new value in the REFR-IND field, Refresh knows that Authorization is using the refreshed PBF and that it can stop impacting the PBF.

The first three settings (PBF1, PBF2, and PBF3) are here because an institution may have three separate PBFs used for BASE24-atm and, therefore, multiple refresh schedules: one for checking accounts (PBF1), one for savings accounts (PBF2), and one for credit accounts (PBF3). If only one PBF is maintained, only the PBF1 field is used. The PBF4 field is used in situations when a CPBF (used in conjunction with BASE24-cash manager) is used instead of a PBF.

520	[1]	authx.refr^ind.pbf1	PIC X(1).
521	[1]	authx.refr^ind.pbf2	PIC X(1).
522	[1]	authx.refr^ind.pbf3	PIC X(1).
523	[1]	authx.refr^ind.pbf4	PIC X(1).
524	[16]	authx.user^fld4.byte[0:15]	PIC X(16).
540	[11]	authx.frwd^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).

An identification number used to identify the forwarding institution.

551	[11]	authx.crd^acct^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

An identification number used to identify the card acceptor for a request message (0200) originating from an acquirer host.

MM/DD/YY HH:MM \$VOLUME AT60DDL TLFX PAGE: 19

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

```

562      [11]      authx.crd^iss^id^num.byte[0:10]
                        [ID-NUM]                                PIC 9(11).

```

An identification number used to identify the card issuer for a response message (0210) originating from an authorizing host.

```
573      [1]      authx.user^fld6                                PIC X(1).
```

This field is not used.

```
END      [size      574]
```

Offset[Len] Field Name and Description Data Type

DEF TLFX-TERM-SETL

0 [856]

0 [89] headx [HEADX]

The following pages describe the fields included in the TLF extract record format.

The following fields contain header information for all TLF extract records.

0 [19] headx.dat^tim.byte[0:18] PIC 9(19).

The date and time the record was logged.

19 [2] headx.rec^typ.byte[0:1] PIC X(2).

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
01 = Customer transaction
04 = Administrative transaction record
20 = Exception caused by invalid data in the STM,
but the transaction was posted.
21 = Exception caused by invalid data in the STM
and the transaction was not posted.
22 = Exception (for future use)

21 [4] headx.auth^ppd.byte[0:3] PIC X(4).

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

25 [24] headx.term

The values in the following fields identify the terminal where the transaction originated.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

25	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	---------------------------------	-----------

The logical network associated with the terminal.

29	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------------	-----------

The FIID of the financial institution owning the terminal.

33	[16]	headx.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	---	------------

The terminal ID of the terminal originating the transaction.

49	[30]	headx.crd	
----	------	-----------	--

The values in the following fields identify the card issuer and cardholder associated with the transaction.

49	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the card issuer.

53	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the card issuer.

57	[19]	headx.crd.pan.byte[0:18]	PIC X(19).
----	------	--------------------------	------------

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

76	[3]	headx.crd.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
----	-----	--	-----------

The member number associated with the cardholder's account number.

79	[4]	headx.brch^id.byte[0:3] [BRCH]	PIC X(4).
----	-----	-----------------------------------	-----------

The branch ID associated with the terminal originating the transaction.

83	[4]	headx.regn^id.byte[0:3] [REGN]	PIC X(4).
----	-----	-----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

87	[2]	headx.user^fldlx.byte[0:1]	PIC X(2).
----	-----	----------------------------	-----------

This field is not used.

89	[767]	term^setl	
----	-------	-----------	--

The following fields are included in terminal balancing records logged to the TLF in ASCII-only format. Terminal balancing records are identified by a value of 04 in the REC-TYP field in the TLF header. These records are further identified by values of 05, 06, or 09 in the TERM-SETL.ADMIN-CDE field.

89	[6]	term^setl.admin^dat [DAT]	
----	-----	------------------------------	--

The date (YYMMDD) the administrative transaction occurred.

89	[2]	term^setl.admin^dat.yy.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

91	[2]	term^setl.admin^dat.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

93	[2]	term^setl.admin^dat.dd.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

95	[8]	term^setl.admin^tim [TIM]	
----	-----	------------------------------	--

The time (HHMMSSTT) the administrative transaction occurred.

95	[2]	term^setl.admin^tim.hh.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

97	[2]	term^setl.admin^tim.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

99	[2]	term^setl.admin^tim.ss.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

101	[2]	term^setl.admin^tim.tt.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

103	[2]	term^setl.admin^cde.byte[0:1]	PIC 9(2).
-----	-----	-------------------------------	-----------

An indicator used to determine how the terminal was cut over. Values are:

05 = Terminal cutover via the Device Handler.
06 = Terminal cutover via CRT.
09 = Forced cutover via Settlement Initiator.

105	[606]	term^setl.hopr[0:5]	
-----	-------	---------------------	--

The following fields contain the hopper values from the TDF just prior to the terminal being balanced.

105	[2]	term^setl.hopr[0:5].contents.byte[0:1]	PIC X(2).
-----	-----	--	-----------

A code used to identify the contents of the hopper. Valid values are:

00 = Cash
01 = Coin

107	[19]	term^setl.hopr[0:5].beg^cash.byte[0:18]	PIC 9(19).
-----	------	---	------------

The amount of currency in the hopper at the start of the current balancing period.

126	[19]	term^setl.hopr[0:5].cash^incr.byte[0:18]	PIC 9(19).
-----	------	--	------------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The amount of currency added to the hopper during the current balancing period.

145	[19]	term^setl.hopr[0:5].cash^decr.byte[0:18]	PIC 9(19).
-----	------	--	------------

The amount of currency removed from the hopper during the current balancing period.

164	[19]	term^setl.hopr[0:5].cash^out.byte[0:18]	PIC 9(19).
-----	------	---	------------

The amount of currency dispensed from the hopper through customer withdrawals between terminal balancing periods.

183	[19]	term^setl.hopr[0:5].end^cash.byte[0:18]	PIC 9(19).
-----	------	---	------------

The amount of currency remaining in the hopper at the end of the balancing period.

202	[3]	term^setl.hopr[0:5].crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code identifying the currency in the hopper. Valid values are listed in the booklet "Codes for the Representation of Currencies and Funds", ISO 4217:1990.

205	[1]	term^setl.hopr[0:5].user^fld5	PIC X(1).
-----	-----	-------------------------------	-----------

This field is not used.

711	[5]	term^setl.num^dep.byte[0:4]	PIC 9(5).
-----	-----	-----------------------------	-----------

The number of envelope deposits accepted at the terminal since the last terminal balancing transaction.

716	[19]	term^setl.amt^dep.byte[0:18]	PIC 9(19).
-----	------	------------------------------	------------

The unverified amount of the deposits accepted at the terminal since the last terminal balancing transaction.

Offset[Len] Field Name and Description Data Type

735 [5] term^setl.num^cmrcl^dep.byte[0:4] PIC 9(5).

The number of envelope deposits accepted in the commercial (e.g., Securomatic) depository since the last terminal balancing transaction.

740 [19] term^setl.amt^cmrcl^dep.byte[0:18] PIC 9(19).

The unverified amount of the deposits accepted in the commercial (e.g., Securomatic) depository since the last terminal balancing transaction.

759 [5] term^setl.num^pay.byte[0:4] PIC 9(5).

The number of envelope payments accepted at the terminal since the last terminal balancing transaction.

764 [19] term^setl.amt^pay.byte[0:18] PIC 9(19).

The unverified amount of payments accepted at the terminal since the last terminal balancing transaction.

783 [5] term^setl.num^msg.byte[0:4] PIC 9(5).

The number of messages-to-institution transaction envelopes accepted since the last terminal balancing transaction.

788 [5] term^setl.num^chk.byte[0:4] PIC 9(5).

The total number of checks received (i.e. cashed or deposited) since the terminal was last balanced.

793 [19] term^setl.amt^chk.byte[0:18] PIC 9(19).

The unverified total amount of checks received (i.e. cashed or deposited) since the terminal was last balanced. terminal balancing transaction.

MM/DD/YY HH:MM \$VOLUME AT60DDL TLFY-TERM-SETL PAGE: 27

Offset[Len] Field Name and Description Data Type

END [size 856]

Offset[Len] Field Name and Description Data Type

DEF TLFY-TERM-CASH

0 [150]

0 [89] headx [HEADX]

The following pages describe the fields included in the TLF extract record format.

The following fields contain header information for all TLF extract records.

0 [19] headx.dat^tim.byte[0:18] PIC 9(19).

The date and time the record was logged.

19 [2] headx.rec^typ.byte[0:1] PIC X(2).

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM,
 but the transaction was posted.
 21 = Exception caused by invalid data in the STM
 and the transaction was not posted.
 22 = Exception (for future use)

21 [4] headx.auth^ppd.byte[0:3] PIC X(4).

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

25 [24] headx.term

The values in the following fields identify the terminal where the transaction originated.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

25	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	---------------------------------	-----------

The logical network associated with the terminal.

29	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------------	-----------

The FIID of the financial institution owning the terminal.

33	[16]	headx.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	---	------------

The terminal ID of the terminal originating the transaction.

49	[30]	headx.crd	
----	------	-----------	--

The values in the following fields identify the card issuer and cardholder associated with the transaction.

49	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the card issuer.

53	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the card issuer.

57	[19]	headx.crd.pan.byte[0:18]	PIC X(19).
----	------	--------------------------	------------

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

76	[3]	headx.crd.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
----	-----	--	-----------

The member number associated with the cardholder's account number.

79	[4]	headx.brch^id.byte[0:3] [BRCH]	PIC X(4).
----	-----	-----------------------------------	-----------

The branch ID associated with the terminal originating the transaction.

83	[4]	headx.regn^id.byte[0:3] [REGN]	PIC X(4).
----	-----	-----------------------------------	-----------

The region ID associated with the terminal originating the transaction.

87	[2]	headx.user^fldlx.byte[0:1]	PIC X(2).
----	-----	----------------------------	-----------

This field is not used.

89	[61]	term^cash	
----	------	-----------	--

The following fields are included in Terminal Cash Adjustment records logged to the TLF in ASCII-only format. Terminal Cash Adjustment records are identified by a value of 04 in the REC-TYP field in the TLF header. These records are further identified by values of 01, 02, 03, 04, 07, or 08 in the TERM-CASH.ADMIN-CDE field.

89	[6]	term^cash.admin^dat [DAT]	
----	-----	------------------------------	--

The date (YYMMDD) the administrative transaction occurred.

89	[2]	term^cash.admin^dat.yy.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

91	[2]	term^cash.admin^dat.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

93	[2]	term^cash.admin^dat.dd.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

95	[8]	term^cash.admin^tim [TIM]	
----	-----	------------------------------	--

The time (HHMMSSTT) the administrative transaction occurred.

95	[2]	term^cash.admin^tim.hh.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

97	[2]	term^cash.admin^tim.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

99	[2]	term^cash.admin^tim.ss.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

101	[2]	term^cash.admin^tim.tt.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

103	[2]	term^cash.admin^cde.byte[0:1]	PIC 9(2).
-----	-----	-------------------------------	-----------

A code indicating a transaction type that involves increases and decreases of currency. This code also identifies whether the transaction was performed by a Device Handler or at a CRT. Valid values are:

01 = Initialize cash, hopper #n (Device Handler).
 02 = Initialize cash, hopper #n (CRT).
 03 = Increase cash, hopper #n (Device Handler).
 04 = Increase cash, hopper #n (CRT).
 07 = Decrease cash, hopper #n (Device Handler).
 08 = Decrease cash, hopper #n (CRT).

105	[1]	term^cash.hopr^num	PIC X(1).
-----	-----	--------------------	-----------

The number of the hopper being affected by the administrative transaction.

106	[2]	term^cash.hopr^contents.byte[0:1]	PIC X(2).
-----	-----	-----------------------------------	-----------

The contents contained in the hopper. Valid values are:

00 = Cash
 01 = Coin

108	[12]	term^cash.amt.byte[0:11]	PIC 9(12).
-----	------	--------------------------	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The amount of increase or decrease to the hopper
because of the administrative transaction.

120	[3]	term^cash.crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code identifying the type of currency used for the
administrative transaction. Valid
values are listed in the "ISO Codes for the
Representation of Currencies and Funds", 4217-1990.

123	[1]	term^cash.user^fld8	PIC X(1).
-----	-----	---------------------	-----------

This field is not used.

124	[5]	term^cash.tim^ofst.byte[0:4]	PIC 9(5).
-----	-----	------------------------------	-----------

The time difference (plus or minus in minutes) between
the terminal location and the Tandem processor location.
This field is filled with the TIM-OFST from the TDF.

129	[21]	term^cash.cash^area.byte[0:20]	PIC X(21).
-----	------	--------------------------------	------------

This field is not used.

END [size 150]

Offset[Len] Field Name and Description Data Type

DEF TLFX-SETL-TTL

0 [182]

0 [89] headx [HEADX]

The following pages describe the fields included in the TLF extract record format.

The following fields contain header information for all TLF extract records.

0 [19] headx.dat^tim.byte[0:18] PIC 9(19).

The date and time the record was logged.

19 [2] headx.rec^typ.byte[0:1] PIC X(2).

The type of TLF record logged. The value in this field is set by the process that creates the TLF record (i.e. Authorization, Device Handler or Settlement).

00 = Extract position record
 01 = Customer transaction
 04 = Administrative transaction record
 20 = Exception caused by invalid data in the STM,
 but the transaction was posted.
 21 = Exception caused by invalid data in the STM
 and the transaction was not posted.
 22 = Exception (for future use)

21 [4] headx.auth^ppd.byte[0:3] PIC X(4).

The PPD name (without the initial "\$") of the Authorization process that logged the record to the TLF.

25 [24] headx.term

The values in the following fields identify the terminal where the transaction originated.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

25	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
----	-----	---------------------------------	-----------

The logical network associated with the terminal.

29	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------------	-----------

The FIID of the financial institution owning the terminal.

33	[16]	headx.term.term^id.byte[0:15] [SYM-NAME]	PIC X(16).
----	------	---	------------

The terminal ID of the terminal originating the transaction.

49	[30]	headx.crd	
----	------	-----------	--

The values in the following fields identify the card issuer and cardholder associated with the transaction.

49	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network associated with the card issuer.

53	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the card issuer.

57	[19]	headx.crd.pan.byte[0:18]	PIC X(19).
----	------	--------------------------	------------

The cardholder's Primary Account Number (PAN) for card initiated transactions. This field will contain an AFT group number and user number for DCT initiated transactions.

Offset[Len] Field Name and Description Data Type

95 [8] setl^ttl.admin^tim
[TIM]

The time (HHMMSSTT) the administrative transaction occurred.

95 [2] setl^ttl.admin^tim.hh.byte[0:1] PIC X(2).

97 [2] setl^ttl.admin^tim.mm.byte[0:1] PIC X(2).

99 [2] setl^ttl.admin^tim.ss.byte[0:1] PIC X(2).

101 [2] setl^ttl.admin^tim.tt.byte[0:1] PIC X(2).

103 [2] setl^ttl.admin^cde.byte[0:1] PIC 9(2).

An indicator used to determine the type of settlement transaction and originator of the transaction. Valid values are:

20 = Terminal totals sent by the CRT
21 = Terminal totals sent by the Device Handler
22 = Terminal totals sent by the Settlement Initiator

105 [12] setl^ttl.term^db.byte[0:11] PIC 9(12).

The unverified amount of terminal debits since the terminal was last balanced. The amount in this field consists of debits from the institution's point of view. Transaction amounts are added to the balance in this field for:

- o On-us and not-on-us deposits. This includes all types of deposit transactions (i.e. deposit transactions, split deposit transactions and deposit with cash back transactions). Note that these transactions are supported for envelop, commercial and check deposit types.
- o On-us and not-on-us payment-enclosed transactions
- o On-us and not-on-us transfers
- o On-us and not-on-us payments between accounts

117 [12] setl^ttl.term^cr.byte[0:11] PIC 9(12).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The total amount of terminal credits since the terminal was last balanced. The amount in this field consists of credits from the institution's point of view. Transaction amounts are added to the balance in this field for:

- o On-us and not-on-us withdrawals
- o On-us and not-on-us cash checks
- o On-us and not-on-us deposits with cash back. Note that only the cash back amount is included in the TERM-CR amount.
- o On-us and not-on-us transfers
- o On-us and not-on-us payments between accounts

129	[12]	setl^ttl.on^us^db.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The total amount of on-us debits since the terminal was last balanced. The amount in this field consists of debits from the customer's point of view. Transaction amounts are added to the balance in this field for:

- o On-us withdrawals
- o On-us cash checks
- o On-us and not-on-us deposits with cash back. Note that only the cash back amount is included in the ON-US-DB amount.
- o On-us transfers
- o On-us payments between accounts

141	[12]	setl^ttl.on^us^cr.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The total amount of on-us credits since the terminal was last balanced. The amount in this field consists of credits from the customer's point of view. Transaction amounts are added to the balance in this field for:

- o On-us deposits. This includes all types of deposit transactions (i.e. deposit transactions, split deposit transactions and deposit with cash back transactions). Note that these transactions are supported for envelop, commercial

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

and check deposit types.

- o On-us payment enclosed transactions
- o On-us transfers
- o On-us payments between accounts

153	[3]	setl^ttl.crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used during settlement.

Valid values are listed in the "ISO Codes for the Representation of Currencies and Funds", 4217-1990.

156	[1]	setl^ttl.user^fld9	PIC X(1).
-----	-----	--------------------	-----------

This field is not used.

157	[5]	setl^ttl.tim^ofst.byte[0:4]	PIC 9(5).
-----	-----	-----------------------------	-----------

The time difference (plus or minus in minutes) between the terminal location and the Tandem processor location. This field is filled with the TIM-OFST from the TDF.

162	[20]	setl^ttl.ttl^area.byte[0:19]	PIC X(20).
-----	------	------------------------------	------------

This field is not used.

END [size 182]