

Offset[Len] Field Name and Description Data Type

DEF CSFX

0 [88]

```
*****
                                History Section
*****
                                RELEASE 5.0
*****
92/04/01      Release 5.0 Design Team
-----
SYMPTOM:      Self Service Banking CHECK Enhancement
PROBLEM:      (E) None.
FIX:          None.
DEPENDENCIES: DDL. All modules that source in the CSF
              be recompiled. Refer to the Release 5.0
              Documentation for further details.
REFERENCE:    BASE24 Release 5.0 External Specificatio
              - Self Service Banking CHECK Application

#####
#              CHECK STATUS FILE REFRESH FORMAT
#####
1  5.0.1      Check Status File Refresh Format
1  5.0.1.1    Identification
1
1      The Check Status File Refresh Format (CSFX) conta
1      record for every pre-approved/declined or registe
1      that may be acquired at a BASE24 terminal support
1      Service Banking. The CSFX definition will be use
1      the CSF file. The CSF file contains status infor
1      specific checking account which will be used in r
1      check related transaction authorization. The rec
1      by institution identification number and checking
1      number.
1
1
1  5.0.1.2    Security
1
1      Not Applicable.
1
1
1  5.0.1.3    Usage
1
1      Not Applicable.
1
*****
```

The following fields make up the CSF Refres
format.

Offset	Len	Field Name and Description	Data Type
0	[9]	cnt.byte[0:8]	PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that for the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual CSF records.

9	[60]	prikey	
---	------	--------	--

The values in the following fields make up the primary key of the CSF.

9	[11]	prikey.inst^id^num.byte[0:10]	PIC X(11).
---	------	-------------------------------	------------

The transit/routing number of the check issuing institution or the check-issuer identification number. The number is derived from the check MICR ABA number.

20	[19]	prikey.acct^num.byte[0:18]	PIC X(19).
----	------	----------------------------	------------

The checking account number derived from the check MICR data.

39	[8]	prikey.user^fld1.byte[0:7]	PIC X(8).
----	-----	----------------------------	-----------

This field is not used.

47	[19]	prikey.rgstr^pan.byte[0:18]	PIC X(19).
----	------	-----------------------------	------------

The cardholder Primay Account Number (PAN) derived from the Track2 data in the BASE24-atm Standard Internal Message (STM). This number corresponds to the PAN in the Cardholder Authorization File (CAF), Negative Card File (NEG), or Usage Accumulation File (UAF).

Note that this field will only be used for registered institution/account combinations. If this particular institution identification number/account number is either a pre-approved or pre-declined

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

combination, this field should contain the default value which is a string of 19 "9"'s. Note that the value of "9"'s is displayed on the CSF CRT access screen as all asterisks.

66	[3]	prikey.rgstr^mbr^num.byte[0:2]	PIC X(3).
----	-----	--------------------------------	-----------

The cardholder member number derived from the Track2 data in the BASE24-atm Standard Internal Message (STM) or from the Card Prefix File (CPF) as configured in the MBR-NUM field.

Note that this field will only be used for registered institution/account combinations. If this particular institution identification number/account number is either a pre-approved or pre-declined combination, this field should contain the default value which is a string of 3 "9"'s. Note that the value of "9"'s is displayed on the CSF CRT access screen as all asterisks.

69	[1]	rec^typ	PIC X(1).
----	-----	---------	-----------

A code indicating the operation to be performed on the CSF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

70	[1]	chk^stat	PIC X(1).
----	-----	----------	-----------

A code specifying the disposition of a check with this ABA/account number. Valid values are:

0 = Accept all checks
1 = Accept for deposit only
2 = Do not accept any checks

71	[1]	ret^chk^flg	PIC X(1).
----	-----	-------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The retention status for denied transactions from
this particular institution/account. Valid values are:

0 = return all checks
1 = retain all checks

72	[15]	chk^lmt.byte[0:14]	PIC X(15).
----	------	--------------------	------------

The maximum acceptable check amount for this particular
institution/account. Checks above the specified limit
are not authorized. This field is not required if the
CHK-STAT field indicates that the check should be
denied.

87	[1]	user^fld2	PIC X(1).
----	-----	-----------	-----------

This field is not used.

END [size 88]

Offset[Len] Field Name and Description Data Type

DEF CCFX

0 [768]

 History Section

 RELEASE 5.0

92/04/01 Release 5.0 Design Team

 SYMPTOM: Self Service Banking CHECK Enhancement

PROBLEM: (E) None.

FIX: None.

DEPENDENCIES: DDL. All modules that source in the CCF
 be recompiled. Refer to the Release 5.0
 Documentation for further details.

REFERENCE: BASE24 Release 5.0 External Specificatio
 - Self Service Banking CHECK Application

 # CORPORATE CHECK FILE REFRESH FORMAT

 1 5.0.1 Corporate Check File Refresh Format

1 5.0.1.1 Identification

1

1 The Corporate Check File (CCFX) Refresh Format wi
 1 information regarding institutions with which the
 1 owner has previously derived a check processing a
 1 The CCFX will be the record format used to Refres
 1 Note the CCF will only be accessed given a check
 1 transaction was inititated with a Check Cashing c
 1 type = "SP".

1

1 5.0.1.2 Security

1

1 Not applicable.

1

1 5.0.1.3 Usage

1

3 Only Refresh will read the CCFX records from tap

1

The following fields make up the CCF Refres
 format.

0 [9] cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

on the refresh tape. The value in this field should always be one greater than that of the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual CCF records.

9	[10]	prikey
---	------	--------

The values in the following field makes up the primary key of the CCF.

9	[10]	prikey.corp^num.byte[0:9]	PIC X(10).
---	------	---------------------------	------------

The corporation identification number as specified in the Cardholder Authorization File (CAF) or Negative Card File (NEG). This field allows a link between the cardholder and the check-issuing institution. This field is left-justified, right blank filled. The default value for this field is all "9"'s. Note that the default value will be displayed on the CCF CRT access screen as asterisks.

19	[1]	rec^typ	PIC X(1).
----	-----	---------	-----------

A code indicating the operation to be performed on the CCF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

20	[25]	corp^descr.byte[0:24]	PIC X(25).
----	------	-----------------------	------------

This field is used for informational purposes only. It is used to provide a description for each corporation.

45	[1]	user^fld1	PIC X(1).
----	-----	-----------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

This field is not used.

46	[2]	corp^cnt.byte[0:1]	PIC X(2).
----	-----	--------------------	-----------

The number of institutions/accounts associated with the corpotation.

48	[720]	corp^acct[0:14]	
----	-------	-----------------	--

The following fields contain information about each institution/account associated with the corporation.

48	[11]	corp^acct[0:14].inst^id^num.byte[0:10]	PIC X(11).
----	------	--	------------

Valid check ABA numbers for this corporation.
This field may contain the routing and transit number. This field should be right-justified and zero-filled to the left.

59	[19]	corp^acct[0:14].acct^num.byte[0:18]	PIC X(19).
----	------	-------------------------------------	------------

Valid check account numbers for this corporation.
This field is left-justified, right blank filled.

78	[1]	corp^acct[0:14].acct^stat	PIC X(1).
----	-----	---------------------------	-----------

The status for this institution/account number.
Valid values are:

0 = Accept all checks for this institution/
account number
1 = Deny all checks for this institution/
account number

79	[1]	corp^acct[0:14].user^fld2	PIC X(1).
----	-----	---------------------------	-----------

This field is not used.

80	[15]	corp^acct[0:14].chk^lmt.byte[0:14]	PIC X(15).
----	------	------------------------------------	------------

MM/DD/YY HH:MM

\$VOLUME AT60CDDL

CCFX

PAGE: 8

Offset[Len]

Field Name and Description

Data Type

The maximum check transaction amount that can be approved for this particular institution/account number. Checks above this specified limit are not authorized. This field is not required if the ACCT-STAT field indicates that the check should not be accepted.

95

[1]

corp^acct[0:14].user^fld3

PIC X(1).

This field is not used.

END [size 768]