

MM/DD/YY HH:MM

\$VOLUME FH60DDL

ULF

PAGE: 1

Offset[Len] Field Name and Description

Data Type

RECORD ULF

```
*SEQ0.04 11/01/00 DDLFULF 6003 DDL FH60DDL FH04000
*FIX2.09 11/19/99 DDLFULF 5303 DDL FH53DDL FH04006
*SYNC.04 12/08/98 DDLFULF 5302 DDL FH53DDL FH04000
*SYNC.03 08/28/98 DDLFULF 5302 DDL FH53DDL FH03000
*SYNC.03 08/22/97 DDLFULF 5102 DDL FH51DDL FH03000
*SYNC.02 06/25/96 DDLFULF 5102 DDL FH51DDL FH02000
*FIX2.00 12/21/95 DDLFULF 5102 DDL FH51DDL FH51050
*FIX2.00 06/19/95 DDLFULF 5101 DDL FH51DDL FH51002
```

History Section

RELEASE 5.0

93/03/19 Release 5.0 Design Team

SYMPTOM: BASE24 BASE Enhancements

PROBLEM: (E) None

FIX: 1. Added CAF-EXPONENT.
Decreased USER-FLD1 to PIC X(14).
2. Expanded the REC-IMAGE area from 1
3. A new file type "WH" was added for
4. A new file type "CO" was added for
5. A new file type "CS" was added for

DEPENDENCIES: All modules that source in the ULF must be recompiled.

REFERENCE: BASE24 BASE Release 5.0 External Specifications
- Amount Field Sizes
- Pre-Authorization Enhancement
BASE24-teller Release 5.0 External Specifications
- SPF/WHFF Processing
BASE24-atm SSB Release 5.0 External Specifications
- Self-Service Banking CHECK Application

RELEASE 5.1

94/07/05 JAS - JMS/583

SYMPTOM: None.

PROBLEM: (E) None.

FIX: BASE24 Release 5.0 Telebanking Support
Added file types for CARF (CR) and CUST (C)

DEPENDENCIES: None. Only comments were added to support

REFERENCE: WO TB930301-01

95/11/07 DPS/1064 - JJM

SYMPTOM: None.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

PROBLEM: (E) None.

FIX: BASE24 Release 1.0 Customer Service/Fraud
Added two new values to FILE-TYP: CI for
CM for CCMF. The change is only to a com
documentation purposes.

DEPENDENCIES: None.

REFERENCE: Work order #950212-3.

16NOV1999 KEW/728 RMM/379

Symptom: None.

Problem: Need to update the comments for FILE-TYP wi
valid values for the remote banking CSTT, C
and PIT SQL tables.

Fix: Added file types CT, AC, CP, and PT to the
Modified: Only the comments for FILE-TYP.

Dependency: Apply fix to DDLFULF and remake.

Reference: None (retro of FH5B035 from Case #319821)

#####

ULF - UPDATE LOG FILE

#####

1 3.1.2.12 Update Log File

1 3.1.2.12.1 Identification

1

1 The Update Log File (ULF) is used by the From Host
1 process to log successful update transactions init
1 the host.

1

1 3.1.2.12.2 Security

1

1 The ULF is secured under Tandem's group level sec
1 only the authorized personnel can access the file

1

1 User Identification - <BASE24 node name>.*

1 File Code - 0

1 Access Security - GGGG

1

1 3.1.2.12.3 Usage

1

1 The ULF is used by the "From Host Maintenance" p
1 update transactions initiated from the host. Th
1 contain all attempts to update the Tandem applic
1 The "From Host Maintenance" Reporting and the Su
1 processes will have access to the file. The rep
1 process will report all records on the file to p
1 audit trail of all update activity. The Extract
1 read the ULF and put all records on a tape for a
1 backup or processing on the host.

1

1

From Host	Create	
From Host	Output	Sequential

Reporting	Input	Sequential	(
-----------	-------	------------	---

Extract	Input	Sequential
---------	-------	------------

1

1 - Organization

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

1		
1		
1		
1		
1		
1		

The ULF is an entry sequenced file with variable records. One alternate key has been defined to reporting process.

The Update Log File (ULF) is used by BASE2 maintenance to log update transactions in the host. This file contains all attempts the Tandem application files.

The From Host Maintenance report program and Extract process have access to this file. The program lists all records on the file to provide an audit trail of all update activity. Super extracts ULF records for additional backup processing on the host.

The following pages describe the fields in ULF record. The information below summarizes other information specific to the ULF.

LCONF ASSIGN:

ULF

0 [4072]

0 [98] hdr

0 [52] hdr.altkey

The following fields make up the alternate key to the ULF that is used by the report program.

0	[4]	hdr.altkey.ln.byte[0:3] [LN]	PIC X(4).
---	-----	---------------------------------	-----------

The logical network associated with the updated record.

4	[4]	hdr.altkey.fiid.byte[0:3] [FIID]	PIC X(4).
---	-----	-------------------------------------	-----------

The FIID of the financial institution that owns the updated record.

8	[2]	hdr.altkey.file^typ.byte[0:1]	PIC X(2).
---	-----	-------------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code identifying the file being updated. Valid values are:

CA = CAF Account information
 CC = Credit card Positive Balance File (PBF)
 CF = Cardholder Authorization File (CAF)
 CI = Customer/Cardholder Information File (CCIF)
 CM = Customer/Cardholder Memo File (CCMF)
 CO = Corporate Check File (CCF)
 CS = Check Status File (CSF)
 CU = Customer File (CUST)
 CR = Customer/Account Relation File (CARF)
 DA = DDA or NOW Positive Balance File (PBF)
 NB = Passbook No Book File (NBF)
 NF = Negative Card File (NEG)
 SP = Stop Payment File (SPF)
 SV = Savings Positive Balance File (PBF)
 WH = Warning/Hold/Float File (WHFF)
 CT = Customer Table (CSTT)
 AC = Customer/Account Relation Table (CACT)
 CP = Customer/Personal ID Relation Table (CPIT)
 PT = Personal Information Table (PIT)

10	[28]	hdr.altkey.acct^num.byte[0:27]	PIC X(28).
----	------	--------------------------------	------------

The account number of the record being added, deleted, or updated. For a CAF update, this field contains the card number. For a PBF update, this field contains the application account number.

38	[6]	hdr.altkey.updt^dat [DAT]	
----	-----	------------------------------	--

The date (YYMMDD) from the Tandem clock.

38	[2]	hdr.altkey.updt^dat.yy.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

40	[2]	hdr.altkey.updt^dat.mm.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

42	[2]	hdr.altkey.updt^dat.dd.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

44	[8]	hdr.altkey.updt^tim [TIM]	
----	-----	------------------------------	--

The time (HHMMSSSTT) from the Tandem clock.

Offset[Len]	Field Name and Description	Data Type
44 [2]	hdr.altkey.updt^tim.hh.byte[0:1]	PIC X(2).
46 [2]	hdr.altkey.updt^tim.mm.byte[0:1]	PIC X(2).
48 [2]	hdr.altkey.updt^tim.ss.byte[0:1]	PIC X(2).
50 [2]	hdr.altkey.updt^tim.tt.byte[0:1]	PIC X(2).
52 [1]	hdr.rec^typ	PIC X(1).

The type of ULF record. Valid values are:

E = Added record
 F = Updated Before image
 G = Updated After image
 H = Deleted record
 R = Rejected message in record format

53 [4]	hdr.dpc^num.byte[0:3]	PIC 9(4).
-------------	-----------------------	-----------

The DPC location number used for routing messages to a specific host.

57 [6]	hdr.trace^num.byte[0:5]	PIC 9(6).
-------------	-------------------------	-----------

The network trace number of the message.

63 [16]	hdr.fm	
--------------	--------	--

The values in the following fields identify certain characteristics of the last file maintenance performed on this record. This includes the user, his or her password, and the location from which the update originated.

63 [4]	hdr.fm.user^grp.byte[0:3]	PIC 9(4).
-------------	---------------------------	-----------

The group number of the user who performed the file maintenance.

67 [8]	hdr.fm.user^num.byte[0:7]	PIC 9(8).
-------------	---------------------------	-----------

The user number of the user who performed the file

Offset[Len]	Field Name and Description	Data Type
	maintenance.	

75	[4]	hdr.fm.sta^no.byte[0:3]	PIC X(4).
----	-----	-------------------------	-----------

The station number of the terminal from which the update originated. On an inquiry, this is the station where the last update on the file was performed (FHM or AFT) and not the station from where the inquiry originated.

79	[1]	hdr.file^cde	PIC X(1).
----	-----	--------------	-----------

The type of action taken with the update message.
Valid values are:

1 = Record add
2 = Record update
3 = Record delete
9 = Record increment

80	[3]	hdr.resp^code.byte[0:2]	PIC X(3).
----	-----	-------------------------	-----------

The response code that was sent to the host, reflecting the final completion of the entered file update.

83	[1]	hdr.caf^exponent	PIC X(1).
----	-----	------------------	-----------

The exponent value used to determine the multiplication factor for CAF limits.

84	[14]	hdr.user^fld1.byte[0:13]	PIC X(14).
----	------	--------------------------	------------

This field is not used.

98	[2]	rec^image^lgth	TYPE BINARY 16 UNSIGNED.
----	-----	----------------	--------------------------

The number of bytes of record image data. Values for this field are 0 through 3972. Audit header records contain no record image data. The records are variable-length depending on what product segments are present.

100	[3972]	rec^image	
-----	--------	-----------	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The following field contains the record to be audited.

100	[3972]	rec^image.rec^image^var[0:3971]	PIC X(1).
			[OCCURS DEPENDING ON REC^IMAGE^LGTH]
	END	[size 4072]	