

Offset[Len] Field Name and Description Data Type

DEF CHX

0 [490]

```
#####
#          CARD HISTORY FILE TAPE FORMAT
#####
```

The following is the tape record format us
the CHF.

0 [9] cx^cnt.byte[0:8] PIC 9(9).

The following field contains a number which indicates !
which record this is on the refresh file. Every !
record's number is one greater than the previous !
record. File and card issuer header records are !
counted as well as individual records. !

9 [37] cx^pri^key

9 [4] cx^pri^key.fiid.byte[0:3] PIC X(4).
[FIID]

This field contains the FIID for this cardholder. !

13 [28] cx^pri^key.crd^num.byte[0:27] PIC X(28).

This field contains the cardnumber. !

41 [3] cx^pri^key.mbr^num.byte[0:2] PIC 9(3).
[MBR-NUM]

This field contains the member number. !

44 [2] cx^pri^key.typ.byte[0:1] PIC 9(2).

This field contains the type of account described by !
this CHF record. !

"31" = Credit Card

46 [1] rec^typ PIC X(1).

This field indicates the operation which will be !
performed on the Cardholder record. An add, change !
balances, delete or change are legitimate for a !
partial file refresh. A full file refresh (indicated !
on file header record) will only accept full file !
changes. Legitimate values and their meanings are: !
"A" = ADD !
"D" = DELETE !

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

	"C" = CHANGE	!
	"F" = FULL FILE CHANGE	!

47	[2]	cx^crd^typ.byte[0:1]	PIC X(2).
----	-----	----------------------	-----------

	This field describes the cardtype. It contains	!
	the following known values. The customer may define	!
	new cardtypes as is needed.	!

"***" = All
 "AX" = American Express
 "C " = Private Label Credit
 "CB" = Carte Blanche
 "DC" = Diners Club
 "M " = MasterCard Credit
 "MD" = MasterCard Debit
 "MM" = MasterCard Dual
 "V " = VISA Credit
 "VD" = VISA Debit
 "VV" = VISA Dual

NOTE: Proprietary Debit cards must be defined with the first character as "P". Due to routing requirements, POS needs to know the difference between credit cards and proprietary debits cards. "PA" thru "PZ", "P0" thru "P9" and "P " are allowable proprietary debit cardtypes.

POS is assuming that any cardtypes not defined above will be considered Proprietary Credit Cards.

49	[139]	cx^pri^cardholder	
		This section contains info on the primary cardholder.	!

49	[30]	cx^pri^cardholder.name.byte[0:29]	PIC X(30).
----	------	-----------------------------------	------------

79	[25]	cx^pri^cardholder.addr.byte[0:24]	PIC X(25).
----	------	-----------------------------------	------------

104	[11]	cx^pri^cardholder.ssn^num.byte[0:10]	PIC X(11).
		Social Security number XXX-XX-XXXX	!

115	[13]	cx^pri^cardholder.city.byte[0:12]	PIC X(13).
-----	------	-----------------------------------	------------

128	[15]	cx^pri^cardholder.cnty.byte[0:14]	PIC X(15).
-----	------	-----------------------------------	------------

143	[3]	cx^pri^cardholder.state.byte[0:2]	PIC X(3).
-----	-----	-----------------------------------	-----------

146	[2]	cx^pri^cardholder.cntry.byte[0:1]	PIC X(2).
-----	-----	-----------------------------------	-----------

148	[20]	cx^pri^cardholder.home^phone.byte[0:19]	
		[PHONE-NUM]	PIC X(20).

Offset	Len	Field Name and Description	Data Type
168	[20]	cx^pri^cardholder.wrk^phone.byte[0:19] [PHONE-NUM]	PIC X(20).
188	[139]	cx^sec^cardholder This section contains info on the secondary cardholder.!	
188	[30]	cx^sec^cardholder.name.byte[0:29]	PIC X(30).
218	[25]	cx^sec^cardholder.addr.byte[0:24]	PIC X(25).
243	[11]	cx^sec^cardholder.ssn^num.byte[0:10] Social Security number XXX-XX-XXXX !	PIC X(11).
254	[13]	cx^sec^cardholder.city.byte[0:12]	PIC X(13).
267	[15]	cx^sec^cardholder.cnty.byte[0:14]	PIC X(15).
282	[3]	cx^sec^cardholder.state.byte[0:2]	PIC X(3).
285	[2]	cx^sec^cardholder.cntry.byte[0:1]	PIC X(2).
287	[20]	cx^sec^cardholder.home^phone.byte[0:19] [PHONE-NUM]	PIC X(20).
307	[20]	cx^sec^cardholder.wrk^phone.byte[0:19] [PHONE-NUM]	PIC X(20).
327	[10]	cx^token^id.byte[0:9] This field contains a personal identifier used in special authorization circumstances. !	PIC X(10).
337	[2]	cx^num^crds^issued.byte[0:1] This field contains the number of cards issued. 2 digit field with default of "01". !	PIC 9(2).
339	[6]	cx^cr^line^chg^dat.byte[0:5] This field contains the date of when the credit line or overdraft limit was last changed. YYMMDD.	PIC 9(6).
339	[6]	cx^overdrft^lim^chg^dat.byte[0:5] [REDEFINES CX^CR^LINE^CHG^DAT]	PIC 9(6).
345	[144]	cx^stat^hist This section contains account information for all twelve months in the year. !	

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

MNTH[0] = Jan.	MNTH[6] = Jul.
MNTH[1] = Feb.	MNTH[7] = Aug.
MNTH[2] = Mar.	MNTH[8] = Sep.
MNTH[3] = Apr.	MNTH[9] = Oct.
MNTH[4] = May.	MNTH[10] = Nov.
MNTH[5] = Jun.	MNTH[11] = Dec.

ACCT-STAT contains the account status for the particular month.

ACCT-BAL contains the account balance for the particular month.

345 [144] cx^stat^hist.mm[0:11]

345 [2] cx^stat^hist.mm[0:11].acct^stat.byte[0:1] PIC 9(2).

347 [10] cx^stat^hist.mm[0:11].acct^bal.byte[0:9] PIC 9(10).

345 [144] cx^credit^stat^hist
[REDEFINES CX^STAT^HIST]

This redefine contains account information for all twelve months in the year for credit accounts.

MM[0] = Jan.

.

.

.

MM[11] = Dec.

ACCT-STAT contains the account status for the particular month.

ACCT-BAL contains the account balance for the particular month.

345 [144] cx^credit^stat^hist.mm[0:11]

345 [2] cx^credit^stat^hist.mm[0:11].acct^stat.byte[0:1] PIC 9(2).

347 [10] cx^credit^stat^hist.mm[0:11].acct^bal.byte[0:9] PIC 9(10).

345 [144] cx^debit^stat^hist
[REDEFINES CX^STAT^HIST]

This redefine contains account information for the last six months for debit accounts.

ACCT-STAT contains the account status for the particular month.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

ACCT-BAL contains the account balance for the particular month.

NFS-PER-MONTH contains the number of times for the particular month the account did not have sufficient funds.

OD-PER-MONTH contains the number of times for the particular month that the account was overdrawn.

345	[72]	cx^debit^stat^hist.mm^d[0:5]	
345	[2]	cx^debit^stat^hist.mm^d[0:5].acct^stat.byte[0:1]	PIC 9(2).
347	[10]	cx^debit^stat^hist.mm^d[0:5].acct^bal.byte[0:9]	PIC 9(10).
417	[18]	cx^debit^stat^hist.nsf[0:5]	
417	[3]	cx^debit^stat^hist.nsf[0:5].nsf^per^month.byte[0:2]	PIC 9(3).
435	[18]	cx^debit^stat^hist.od[0:5]	
435	[3]	cx^debit^stat^hist.od[0:5].od^per^month.byte[0:2]	PIC 9(3).
453	[36]	cx^debit^stat^hist.user^fld^debit.byte[0:35]	PIC X(36).
489	[1]	user^fld1	PIC X(1).
		END [size 490]	