

Offset[Len] Field Name and Description Data Type

DEF PTLFX

0 [1070]

0 [183] headx [HEADX]

The POS Transaction Log File (PTLF) contains a record of each financial transaction (approved or denied) processed by BASE24-pos for a single processing day. Transactions declined by a Device Handler (for example, bad format), are typically not posted to the PTLF. It also contains settlement records for each POS terminal in the system. This file is an audit record at the transaction level of the system's processing and is extracted daily to provide detailed transaction data for processing by a host.

Records are written to the PTLF sequentially, and two PTLFs are always accessible to the system for logging: the current day's PTLF and the next day's PTLF. Which PTLF a transaction posts to is based on the transaction's PTDF posting date. This is derived from the current business date of the terminal at which the transaction originated. Use of two PTLFs allows BASE24-pos terminals to be cut over at different times. As terminals are cut over, transactions from those terminals begin posting to the next day's PTLF; transactions from terminals that have not been cut over for the day continue to post to the current day's PTLF.

When network settlement occurs, a new PTLF is created and the current day's PTLF is closed to the online system. At that time, the current day's PTLF is available for reporting and extract processing.

LCONF ASSIGN: POS-PTLF

PTLF RECORD STRUCTURE

There are five formats used in writing PTLF records in the ASCII-only format.

- o Financial Transaction (PTLFX)
- o Settlement Totals (PTLFX-SET-REC)
- o Clerk Totals (PTLFX-CLERK-TOT)
- o First Services (PTLFX-SRVCS-1)
- o Second Services (PTLFX-SRVCS-2)

The values contained in the HEADX.REC-TYP and HEADX.TKEY.RKEY.REC-FRMT fields identify the type of information contained in the PTLFX record. The various value combinations and the resulting record format and contents include:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

REC-TYP	REC-FRMT	RECORD FORMAT AND CONTENTS
00	-	Initial
01	5	Financial Transaction--Customer
04	0	Settlement Totals--Batch
04	1	Settlement Totals--Shift
04	2	Settlement Totals--Daily
04	3	Settlement Totals--Network
04	4	Clerk Totals
04	8	Second Services
04	9	First Services
20	5	Financial Transaction--Exception (posted)
21	5	Financial Transaction--Exception (not posted)
22	5	Financial Transaction--Exception (partially posted)
23	5	Financial Transaction--Exception (invalid data)

0	[19]	headx.dat^tim.byte[0:18]	PIC X(19).
---	------	--------------------------	------------

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility.

19	[2]	headx.rec^typ.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

A code indicating the type of record. Authorization sets the value in this field when the record is logged. Valid values are:

00 = Initial record
 01 = Customer transaction
 04 = Administrative transaction
 20 = Exception--posted
 21 = Exception--not posted
 22 = Exception--partially posted
 23 = Exception--invalid data encountered in the
 POS Standard Internal Message (PSTM)

In situations where a transaction cannot be completely processed because of a processing error (e.g., invalid data, unable to locate an authorization record, etc), the Authorization process logs the transaction to the PTLF as an exception. Exception transactions are included as detail items in the BASE24-pos reports but are not included in the BASE24-pos settlement totals.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

```
21      [30]      headx.crd
```

The values in the following fields describe the cardholder and card issuer for the transaction. This is an alternate key used for reporting and perusal purposes.

```

21      [4]      headx.crd.ln.byte[0:3]
                                [LN]                                PIC X(4) .

```

The logical network with which the institution that issued the card is associated.

```

25      [4]      headx.crd.fiid.byte[0:3]
                                [FIID]                                PIC X(4).

```

The FIID of the institution that issued the card.

```
29      [22]      headx.crd.card
```

The values in the following fields identify the card used in the transaction.

```
29      [19]      headx.crd.card.crd^num.byte[0:18]      PIC X(19).
```

The card number identifying the card used in the transaction.

```

48      [3]      headx.crd.card.mbr^num.byte[0:2]
                                [MBR-NUM]                                PIC 9(3).

```

The member number associated with the card used in the transaction.

```
51      [57]      headx.ret1
```

The values in the following fields describe the retailer involved in the transaction. The values in these fields are used for reporting purposes.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

51	[35]	headx.ret1.ky	
----	------	---------------	--

51	[4]	headx.ret1.ky.ln.byte[0:3] [LN]	PIC X(4).
----	-----	------------------------------------	-----------

The logical network with which the retailer is associated.

55	[31]	headx.ret1.ky.rdfkey	
----	------	----------------------	--

The values in the following fields compose the key to the retailer's POS Retailer Definition File (PRDF) record.

55	[4]	headx.ret1.ky.rdfkey.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	---	-----------

The FIID of the institution with which the retailer is associated.

59	[4]	headx.ret1.ky.rdfkey.grp.byte[0:3]	PIC X(4).
----	-----	------------------------------------	-----------

The group to which the retailer belongs.

63	[4]	headx.ret1.ky.rdfkey.regn.byte[0:3] [REGN]	PIC X(4).
----	-----	---	-----------

The retailer region group to which the retailer belongs.

67	[19]	headx.ret1.ky.rdfkey.id.byte[0:18]	PIC X(19).
----	------	------------------------------------	------------

The retailer ID identifying the retailer.

86	[16]	headx.ret1.term^id.byte[0:15]	PIC X(16).
----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

102	[3]	headx.ret1.shift^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The shift number with which the transaction is associated.

105	[3]	headx.ret1.batch^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

The batch number with which the transaction is associated.

108	[32]	headx.term	
-----	------	------------	--

The following fields define the terminal and time at which the transaction occurred. These fields are used as an alternate key to peruse transactions by terminal and time.

108	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
-----	-----	---------------------------------	-----------

The logical network with which the terminal is associated.

112	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
-----	-----	-------------------------------------	-----------

The FIID of the institution with which the terminal is associated.

116	[16]	headx.term.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

132	[8]	headx.term.tim [TIM]	
-----	-----	----------------------	--

The time the transaction occurred.

132	[2]	headx.term.tim.hh.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

134	[2]	headx.term.tim.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

136	[2]	headx.term.tim.ss.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

138	[2]	headx.term.tim.tt.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

140	[42]	headx.tkey	
-----	------	------------	--

The following fields identify the terminal, retailer, and clerk associated with the transaction. These fields are used as an alternate key to peruse transactions by terminal, retailer, and clerk.

140	[16]	headx.tkey.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

156	[26]	headx.tkey.rkey	
-----	------	-----------------	--

156	[1]	headx.tkey.rkey.rec^frmt	PIC X(1).
-----	-----	--------------------------	-----------

A code indicating the type of information in this record. Valid values are:

- 0 = Batch Totals
- 1 = Shift Totals
- 2 = Day Totals
- 3 = Network Totals
- 4 = Clerk Totals
- 5 = Data Record
- 8 = Services Totals
- 9 = Services Totals

157	[19]	headx.tkey.rkey.retailer^id.byte[0:18]	PIC X(19).
-----	------	--	------------

The retailer ID identifying the retailer.

176	[6]	headx.tkey.rkey.clerk^id.byte[0:5]	PIC X(6).
-----	-----	------------------------------------	-----------

The clerk identification number.

182	[1]	headx.data^flag	PIC X(1).
-----	-----	-----------------	-----------

Indicates whether the user-data field is appended to the PTLF record. Valid values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

0 = No user-data appended
1 = User-data appended

183	[683]	authx [AUTHX]
-----	-------	---------------

183	[4]	authx.typ.byte[0:3] PIC 9(4).
-----	-----	-------------------------------

A code identifying the specific message type of this record. Valid values are:

0210 = Authorization response
0220 = Authorization advice
0412 = Chargeback response
0420 = Reversal
0500 = Reconciliation request

187	[2]	authx.rte^stat.byte[0:1] PIC 9(2).
-----	-----	------------------------------------

A code indicating the status of a message at the system level. Valid values are:

00 = No error
11 = Destination not available
12 = Line down
20 = Originator not available
21 = Unknown message type
22 = Unknown card number

189	[1]	authx.originator PIC X(1).
-----	-----	----------------------------

Indicates where the transaction originated.

Valid values are:

1 = Device controlled by BASE24
2 = Device handler
3 = Authorization process
4 = Host Interface process
5 = Host
6 = Interchange Interface process
7 = Interchange

190	[1]	authx.responder PIC X(1).
-----	-----	---------------------------

Indicates where the response message to this transaction originated. Valid values are:

1 = Device controlled by BASE24
2 = Device handler

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

3 = Authorization process
 4 = Host Interface process
 5 = Host
 6 = Interchange Interface process
 7 = Interchange

191	[2]	authx.iss^cde.byte[0:1]	PIC X(2).
-----	-----	-------------------------	-----------

An indicator used to determine the issuer of the transaction. Valid values are:

00-29 = On-us
 30-99 = Not-on-us
 *_ = All

193	[19]	authx.entry^tim.byte[0:18]	PIC X(19).
-----	------	----------------------------	------------

The time at which the transaction entered into the BASE24 system.

212	[19]	authx.exit^tim.byte[0:18]	PIC X(19).
-----	------	---------------------------	------------

The time at which the Host Interface or Interchange Interface transmitted the authorization request to the authorizing entity.

231	[19]	authx.re^entry^tim.byte[0:18]	PIC X(19).
-----	------	-------------------------------	------------

The time at which the Host Interface or Interchange Interface received a response to its original request from the authorizing entity.

250	[6]	authx.tran^dat [DAT]	
-----	-----	----------------------	--

The date (YYMMDD) the transaction began.

250	[2]	authx.tran^dat.yy.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

252	[2]	authx.tran^dat.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

254	[2]	authx.tran^dat.dd.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

256	[8]	authx.tran^tim [TIM]	
-----	-----	----------------------	--

Offset[Len] Field Name and Description Data Type

The time (HHMMSSTT) the transaction began.

256	[2]	authx.tran^tim.hh.byte[0:1]	PIC X(2).
258	[2]	authx.tran^tim.mm.byte[0:1]	PIC X(2).
260	[2]	authx.tran^tim.ss.byte[0:1]	PIC X(2).
262	[2]	authx.tran^tim.tt.byte[0:1]	PIC X(2).
264	[6]	authx.post^dat [DAT]	

The date (YYMMDD) the transaction is to be posted by
BASE24.

264	[2]	authx.post^dat.yy.byte[0:1]	PIC X(2).
266	[2]	authx.post^dat.mm.byte[0:1]	PIC X(2).
268	[2]	authx.post^dat.dd.byte[0:1]	PIC X(2).
270	[6]	authx.acq^ichg^setl^dat [DAT]	

The date (YYMMDD) the transaction is to be settled by
the acquirer interchange, if an interchange is
involved in processing this transaction. Otherwise,
this field is zero-filled.

270	[2]	authx.acq^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
272	[2]	authx.acq^ichg^setl^dat.mm.byte[0:1]	PIC X(2).
274	[2]	authx.acq^ichg^setl^dat.dd.byte[0:1]	PIC X(2).
276	[6]	authx.iss^ichg^setl^dat [DAT]	

The date (YYMMDD) the transaction is to be settled by
the issuer interchange, if an interchange is
involved in processing this transaction. Otherwise,
this field is zero-filled.

276	[2]	authx.iss^ichg^setl^dat.yy.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

278	[2]	authx.iss^ichg^set1^dat.mm.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

280	[2]	authx.iss^ichg^set1^dat.dd.byte[0:1]	PIC X(2).
-----	-----	--------------------------------------	-----------

282	[12]	authx.seq^num.byte[0:11]	PIC X(12).
-----	------	--------------------------	------------

The transaction sequence number generated by the terminal or the Device Handler.

294	[25]	authx.term^name^loc.byte[0:24]	PIC X(25).
-----	------	--------------------------------	------------

The terminal name and location as defined in the PTDF.

319	[22]	authx.term^owner^name.byte[0:21]	PIC X(22).
-----	------	----------------------------------	------------

The name of the financial institution that owns the terminal, as defined in the PTDF.

341	[13]	authx.term^city.byte[0:12]	PIC X(13).
-----	------	----------------------------	------------

The city in which the terminal is located.

354	[3]	authx.term^st.byte[0:2]	PIC X(3).
-----	-----	-------------------------	-----------

The state in which the terminal is located.

357	[2]	authx.term^cntry^cde.byte[0:1]	PIC X(2).
-----	-----	--------------------------------	-----------

A code indicating the country in which the terminal is located.

359	[4]	authx.brch^id.byte[0:3]	PIC X(4).
-----	-----	-------------------------	-----------

This field is not currently used.

363	[3]	authx.user^fld2.byte[0:2]	PIC X(3).
-----	-----	---------------------------	-----------

Reserved for future use.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

366	[5]	authx.term^tim^ofst.byte[0:4]	PIC X(5).
-----	-----	-------------------------------	-----------

The time difference between the terminal and the Tandem processor location. This is the signed (+ or -) number of minutes to be added to the BASE24 Tandem system time in order to obtain the terminal local time.

371	[11]	authx.acq^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

The route/transit number of the terminal owner as defined in the PTDF.

382	[11]	authx.rcv^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

The route/transit number of the card issuer as defined in the Institution Definition File (IDF).

393	[2]	authx.term^typ.byte[0:1]	PIC X(2).
-----	-----	--------------------------	-----------

The terminal type as defined in the PTDF.

395	[6]	authx.clerk^id.byte[0:5]	PIC X(6).
-----	-----	--------------------------	-----------

The clerk ID, as defined in the PTDF, of the POS device operator who performed the transaction.

401	[12]	authx.crt^auth	
-----	------	----------------	--

The following fields contain the PATHWAY operator group and user identifications used for CRT Authorization.

401	[4]	authx.crt^auth.grp.byte[0:3]	PIC X(4).
-----	-----	------------------------------	-----------

The PATHWAY operator group identification used for CRT Authorization.

405	[8]	authx.crt^auth.user^id.byte[0:7]	PIC X(8).
-----	-----	----------------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The PATHWAY operator user identification used for CRT Authorization.

413	[4]	authx.ret1^sic^cde.byte[0:3]	PIC X(4).
-----	-----	------------------------------	-----------

The Standard Industrial Classification (SIC) code identifying the retailer's line of business.

417	[4]	authx.orig.byte[0:3]	PIC X(4).
-----	-----	----------------------	-----------

The originator of this transaction.

421	[4]	authx.dest.byte[0:3]	PIC X(4).
-----	-----	----------------------	-----------

The destination of this transaction.

425	[6]	authx.tran^cde	
-----	-----	----------------	--

The values in the following fields identify the type of transaction in TCTAAC format.

425	[2]	authx.tran^cde.tc.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

A code identifying the type of transaction. Valid values are:

- 10 = Normal purchase
- 11 = Preauthorization purchase
- 12 = Preauthorization purchase completion
- 13 = Mail/phone order
- 14 = Merchandise return
- 15 = Cash advance
- 16 = Card verification
- 17 = Balance inquiry
- 18 = Purchase with cash back
- 19 = Check verification
- 20 = Check guarantee
- 21 = Purchase adjustment
- 22 = Adjustment--merchandise return
- 23 = Adjustment--cash advance
- 24 = Adjustment--purchase with cash back

Offset[Len] Field Name and Description Data Type

427 [1] authx.tran^cde.t PIC X(1).

A code identifying the card type associated with the transaction. Valid values are:

0 = None
1 = Credit card
2 = Debit card

428 [2] authx.tran^cde.aa.byte[0:1] PIC X(2).

A code identifying the type of account associated with the transaction. Valid values are:

00 = None
01 = DDA
11 = Savings
31 = Credit

430 [1] authx.tran^cde.c PIC X(1).

A code identifying the transaction category associated with the transaction. Valid values are:

0 = Normal
1 = Sales draft
2 = Representation
3 = Chargeback
4 = Personal check/cash
5 = Personal check/amount of purchase
6 = Personal check/amount of purchase with cash back
7 = Government check
8 = Payroll check
9 = Electronic check
A-Z = Reserved for future use

431 [2] authx.crd^typ.byte[0:1] PIC X(2).

A code identifying the type of card used to initiate the transaction.

433 [19] authx.acct.byte[0:18] PIC X(19).

The account number of the affected account.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

452 [3]	authx.resp^cde.byte[0:2]	PIC 9(3).
---------	--------------------------	-----------

The response code for the transaction. For a listing of the valid codes, refer to the "BASE24-pos Transaction Processing Manual".

455 [19]	authx.amt^1.byte[0:18]	PIC X(19).
----------	------------------------	------------

The transaction amount requested. For adjustment transactions, this field contains the original amount. For purchase with cash back transactions, this field contains the total amount (purchase plus cash back). The cash back amount is contained in the AUTH.AMT-2 field. For preauthorization completions, this field contains the completed amount.

474 [19]	authx.amt^2.byte[0:18]	PIC X(19).
----------	------------------------	------------

For adjustment transactions, this field contains the new amount. For purchase with cash back transactions, this field contains the cash back amount (the AUTH.AMT-1 field contains the total amount). For chargebacks, this field contains the replacement amount.

493 [4]	authx.exp^dat.byte[0:3]	PIC X(4).
---------	-------------------------	-----------

The expiration date (YYMM) of the card.

497 [40]	authx.track2.byte[0:39]	PIC X(40).
----------	-------------------------	------------

The Track 2 information taken from the magnetic strip on the card or entered manually.

537 [16]	authx.pin^ofst.byte[0:15]	PIC X(16).
----------	---------------------------	------------

This field is currently not used.

553 [12]	authx.pre^auth^seq^num.byte[0:11]	PIC X(12).
----------	-----------------------------------	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The sequence number assigned to the preauthorization transaction.

565	[10]	authx.invoice^num.byte[0:9]	PIC X(10).
-----	------	-----------------------------	------------

The transaction invoice number sent from the terminal, if used.

575	[10]	authx.orig^invoice^num.byte[0:9]	PIC X(10).
-----	------	----------------------------------	------------

The invoice number of the original transaction sent from the terminal, if used.

585	[16]	authx.authorizer.byte[0:15]	PIC X(16).
-----	------	-----------------------------	------------

The symbolic name of the authorizer of the transaction.

601	[1]	authx.auth^ind	PIC X(1).
-----	-----	----------------	-----------

A code indicating if the authorizer in the previous field (if Router 1) was the primary, alternate 1, alternate 2, or if a default action was taken. Valid values are:

0 = None
1 = Alternate 1
2 = Alternate 2
4 = DFLT authorization
9 = Default action
F = SPROUTE primary
f = SPROUTE alternate
P = Primary

602	[3]	authx.shift^num.byte[0:2]	PIC X(3).
-----	-----	---------------------------	-----------

The number of the shift to which the transaction belongs.

605	[3]	authx.batch^seq^num.byte[0:2]	PIC X(3).
-----	-----	-------------------------------	-----------

The batch sequence number for the transaction.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

608	[8]	authx.apprv^cde.byte[0:7]	PIC X(8).
-----	-----	---------------------------	-----------

The approval code generated by the transaction authorizer. This code can be generated by an interchange or host, as well as by BASE24-pos Authorization. If BASE24 generates the code, a _B (B preceded by a space) is inserted into the last byte of this field.

616	[1]	authx.apprv^cde^lgth	PIC 9(1).
-----	-----	----------------------	-----------

The length of the approval code that the device can handle. The value in this field is used only if an approval code is generated by Authorization. Valid values are 2 through 6.

617	[8]	authx.ichg^resp.byte[0:7]	PIC X(8).
-----	-----	---------------------------	-----------

The interchange response, if there was an interchange involved in processing this transaction. Otherwise, this field is left blank. The value in this field is set by the Interchange Interface.

625	[4]	authx.pseudo^term^id.byte[0:3]	PIC X(4).
-----	-----	--------------------------------	-----------

The pseudo identification associated with the terminal.

629	[20]	authx.rfrl^phone.byte[0:19] [PHONE-NUM]	PIC X(20).
-----	------	--	------------

The telephone number used for referral transactions.

649	[1]	authx.dft^capture^flg	PIC 9(1).
-----	-----	-----------------------	-----------

A code indicating the action taken regarding the authorization and draft capture of this transaction. Valid codes are:

- 0 = Authorize only
- 1 = Authorize and capture
- 2 = Authorize only and expect electronic follow-up
- 3 = Electronic follow-up of previously authorized

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

transaction. This option does not update settlement balances.

9 = Value not found (Router was unable to match the card type to a value in the PTDF or the PRDF.)

650	[1]	authx.set1^flag	PIC 9(1).
-----	-----	-----------------	-----------

Indicates how the terminal is cut over if the terminal is directly-connected to BASE24.

651	[2]	authx.rvrl^cde.byte[0:1]	PIC 9(2).
-----	-----	--------------------------	-----------

A code specifying the reason for reversal or adjustment transactions. Valid values are:

- 01 = Time-out
- 02 = Command reject
- 03 = Destination not available
- 08 = Customer canceled
- 10 = Hardware error
- 12 = Original amount incorrect
- 14 = Suspicious reversal override
- 15 = Misdispense reversal override
- 16 = Duplicate transaction
- 17 = Reconciliation error
- 18 = Reserved
- 19 = System error
- 20 = Suspect reversal
- 21 = MAC failure
- 22 = KMAC sync error
- 23 = Message replay error
- 24 = Invalid MAC

653	[2]	authx.rea^for^chrgbck.byte[0:1]	PIC X(2).
-----	-----	---------------------------------	-----------

A code identifying the reason for the chargeback. Valid values are:

- 03 = Invalid merchant
- 12 = Invalid transaction
- 18 = Customer dispute
- 59 = Suspected fraud
- 63 = Security violation
- 64 = Original transaction amount incorrect
- 68 = Supporting documentation received too late
- 93 = Transaction in violation of the law
- 94 = Duplicate transaction
- 96 = System malfunction

Offset[Len] Field Name and Description Data Type

655 [1] authx.num^of^chrgbck PIC 9(1).

The occurrence of the chargeback. Valid values are 1 through 9.

656 [2] authx.pt^srv^cond^cde.byte[0:1] PIC 9(2).

A code identifying the transaction origin. The code indicates a special condition that exists at the time the transaction is initiated. Valid values are:

00 = Normal presentment
 01 = Customer not present
 02 = Unattended terminal, able to retain card
 03 = Merchant suspicious
 04 = Electronic cash register interface
 05 = Customer present, but card not present
 06 = Preauthorization request
 07 = Telephone device request
 08 = Mail order/telephone order
 09 = Security alert
 10 = Customer identity verified
 11 = Suspected fraud
 12 = Security reasons
 13 = Representment of an item
 14 = Public utility terminal
 15 = Customer terminal (home terminal)
 16 = Administration terminal
 17 = Returned item (chargeback)
 18 = No check in envelope/all returned
 19 = Deposit out-of-balance/all returned
 20 = Payment out-of-balance/all returned
 21 = Manual reversal
 22 = Terminal error/counted
 23 = Terminal error/not counted
 24 = Deposit out-of-balance/applied contents
 25 = Payment out-of-balance/applied contents
 26 = Withdrawal had error/reversed
 27 = Unattended terminal, unable to retain card
 28-40 = Reserved for ISO use
 41-50 = Reserved for national use
 51-99 = Reserved for private use

658 [3] authx.pt^srv^entry^mde.byte[0:2] PIC 9(3).

A code indicating how the Primary Account Number (PAN) is entered into the system and the PIN entry

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

capabilities when performing POS transactions. The valid values for PAN entry (positions 1 and 2) are:

00 = Unspecified
 01 = Manual
 02 = Magnetic stripe
 03 = Bar code
 04 = OCR
 05 = Integrated circuit card
 06-60 = Reserved for ISO use
 61-80 = Reserved for national use
 81-99 = Reserved for private use

The valid values for PIN entry capabilities (position 3) are:

0 = Unspecified
 1 = PIN entry capability
 2 = No PIN entry capability
 3-5 = Reserved for ISO use
 6-7 = Reserved for national use
 8-9 = Reserved for private use

661	[1]	authx.auth^ind2	PIC X(1).
-----	-----	-----------------	-----------

A code indicating if the authorizer in the AUTHORIZER field (if Router 2) was the primary, alternate 1, alternate 2, or if a default action was taken. Valid values are:

0 = None
 1 = Alternate 1
 2 = Alternate 2
 4 = DFLT authorization
 9 = Default action
 F = SPROUTE primary
 f = SPROUTE alternate
 P = Primary

662	[3]	authx.orig^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the currency of the transaction.

665	[41]	authx.user^fld4.byte[0:40]	PIC X(41).
-----	------	----------------------------	------------

665	[41]	authx.mult^crncy [REDEFINES USER^FLD4]	
-----	------	---	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The following five fields apply only in multiple-currency systems; they are redefined as a user field in single-currency systems. Multiple-currency systems are not currently supported by BASE24.

665	[3]	authx.mult^crncy.auth^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code indicating the type of currency used in the response from the authorizing entity.

668	[8]	authx.mult^crncy.auth^conv^rate.byte[0:7]	PIC 9(8).
-----	-----	---	-----------

The exchange rate of the authorizing entity. Used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

676	[3]	authx.mult^crncy.setl^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	--	-----------

A code indicating the type of currency used in the settlement of the transaction.

679	[8]	authx.mult^crncy.setl^conv^rate.byte[0:7]	PIC 9(8).
-----	-----	---	-----------

The exchange rate of the settlement entity. Used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are used, the default value is 61000000.

687	[19]	authx.mult^crncy.conv^dat^tim.byte[0:18]	PIC X(19).
-----	------	--	------------

The time and day when the exchange rate was applied between the transaction amount and the currency of the database. The value in this field indicates when the actual conversion between the currency of the transaction and the currency of the database occurred. The value in this field is displayed in Greenwich Mean Time (GMT).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

706	[6]	authx.refr
-----	-----	------------

The values in the following nine fields indicate to the Refresh process when to impact the Positive Balance File (PBF) and how to impact the various amount fields in the PBF, when impacting is required.

A reversal transaction does not affect the codes in the following nine fields. When the value in the AUTH.TYP field identifies the transaction as a reversal, the Refresh process multiplies the values in the AUTH.AMT-1 and AUTH.AMT-2 fields by negative 1 to determine how to impact the various PBF amount fields. Adding an amount that has been multiplied by negative 1 has the same effect as subtracting the amount.

706	[1]	authx.refr.imp^ind	PIC X(1).
-----	-----	--------------------	-----------

A code indicating whether this record should be considered when impacting a set of account records that has been refreshed. Valid values are:

0 = Do not use the record for impacting.
1 = Use the record for impacting.

707	[1]	authx.refr.avail^bal	PIC X(1).
-----	-----	----------------------	-----------

A code indicating the manner in which this record impacts the amount in the AVAIL-BAL field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

707	[1]	authx.refr.avail^cr [REDEFINES AVAIL^BAL]	PIC X(1).
-----	-----	--	-----------

A code indicating the manner in which this record impacts the amount in the AVAIL-CR field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

Offset[Len] Field Name and Description Data Type

708 [1] authx.refr.ledg^bal PIC X(1).

A code indicating the manner in which this record impacts the amount in the LEDG-BAL field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

708 [1] authx.refr.cr^lmt PIC X(1).
[REDEFINES LEDG^BAL]

A code indicating the manner in which this record impacts the amount in the CR-LMT field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

709 [1] authx.refr.amt^on^hold PIC X(1).

A code indicating the manner in which this record impacts the amount in the AMT-ON-HOLD field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

709 [1] authx.refr.cr^bal PIC X(1).
[REDEFINES AMT^ON^HOLD]

A code indicating the manner in which this record impacts the amount in the CR-BAL field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

710 [1] authx.refr.ttl^float PIC X(1).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

A code indicating the manner in which this record impacts the amount in the TOTAL FLOAT field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

711	[1]	authx.refr.cur^float	PIC X(1).
-----	-----	----------------------	-----------

A code indicating the manner in which this record impacts the amount in the CURRENT FLOAT field in the PBF account records. Valid values are:

0 = No effect on balance
1 = Add to balance
2 = Subtract from balance

712	[1]	authx.adj^setl^impact^flg	PIC X(1).
-----	-----	---------------------------	-----------

A code indicating whether adjustments impact settlement. Valid values are:

0 = Adjustments do not impact settlement.
1 = Adjustments do have impact settlement.

713	[4]	authx.refr^ind	
-----	-----	----------------	--

An alphabetic indicator set by Authorization from the value a corresponding field in the IDF. It is used by Refresh to determine when transaction impacting can be terminated.

Four different settings exist. However, three settings are used because an institution can have three separate PBFs used for BASE24-pos and, therefore, three refresh schedules: one for checking accounts (PBF1), one for savings accounts (PBF2) and one for credit accounts (PBF3).

713	[1]	authx.refr^ind.pbf1	PIC X(1).
-----	-----	---------------------	-----------

714	[1]	authx.refr^ind.pbf2	PIC X(1).
-----	-----	---------------------	-----------

715	[1]	authx.refr^ind.pbf3	PIC X(1).
-----	-----	---------------------	-----------

716	[1]	authx.refr^ind.pbf4	PIC X(1).
-----	-----	---------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

717	[11]	authx.frwd^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

The identification of the forwarding institution for full fee accounting.

728	[11]	authx.crd^acct^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	--	------------

A code identifying the card acceptor on a 0200 transaction originating from an acquirer host. The value in this field is only used in cases where the acquirer is not the actual card acceptor. Otherwise, this field is left blank.

739	[11]	authx.crd^iss^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

A code identifying the actual card issuer on a 0210 response from an authorizing host, if desired. The value in this field is only used in cases where the receiving institution is not the actual card acceptor. Otherwise, this field is left blank.

750	[4]	authx.orig^msg^typ.byte[0:3]	PIC X(4).
-----	-----	------------------------------	-----------

The original message type associated with the transaction. The value in this field is used for adjustments, representments or reversal transactions.

754	[8]	authx.orig^tran^tim [TIM]	
-----	-----	------------------------------	--

The original time (HHMMSSTT) at which the transaction occurred. The value in this field is used for adjustments, representments or reversal transactions.

754	[2]	authx.orig^tran^tim.hh.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

756	[2]	authx.orig^tran^tim.mm.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

758	[2]	authx.orig^tran^tim.ss.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

760	[2]	authx.orig^tran^tim.tt.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

762	[4]	authx.orig^tran^dat.byte[0:3]	PIC X(4).
-----	-----	-------------------------------	-----------

The original date (MMDD) on which the transaction occurred. The value in this field is used for adjustments, representments or reversal transactions.

766	[12]	authx.orig^seq^num.byte[0:11]	PIC X(12).
-----	------	-------------------------------	------------

The original sequence number assigned to the transaction. The value in this field is used for adjustments, representments or reversal transactions.

778	[4]	authx.orig^b24^post^dat.byte[0:3]	PIC X(4).
-----	-----	-----------------------------------	-----------

The original date (MMDD) on which the transaction posted to BASE24. The value in this field is used for adjustments, representments or reversal transactions.

782	[3]	authx.excp^rsn^cde.byte[0:2]	PIC X(3).
-----	-----	------------------------------	-----------

A reason code indicating why the exception flag is set. The value in this field is used only for exception records. For any other records, this field is set to blanks.

785	[1]	authx.ovrrde^flg	PIC X(1).
-----	-----	------------------	-----------

A code distinguishing between normal transactions and transactions handled through CRT Authorization. Valid values are:

- 0 = Normal transaction--Transaction received from POS device without CRT Authorization involvement.
- 1 = Referral override with response sent to the CRT Device Handler--Transaction was not authorized due to insufficient information and has been referred for manual authorization.
- 2 = Referral override with transaction sent out of CRT Device Handler/Router/Authorization--Force-post transaction indicating whether a transaction that was previously referred for manual authorization has been approved or declined.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

3 = Normal CRT Authorization transaction--Transaction received from CRT Authorization terminal instead of POS device, but no referrals were necessary.

786	[20]	authx.addr.byte[0:19]	PIC X(20).
-----	------	-----------------------	------------

The cardholder billing address received with the transaction when performing address verification. This field contains zeros when the transaction contains a status code without an address or ZIP code.

806	[9]	authx.zip^cde.byte[0:8]	PIC X(9).
-----	-----	-------------------------	-----------

The cardholder billing ZIP code received with the transaction when performing address verification. This field contains zeros when the transaction contains a status code without an address or ZIP code.

815	[1]	authx.addr^vrfy^stat	PIC X(1).
-----	-----	----------------------	-----------

A code identifying the result of comparing address verification information received in the transaction and address verification information contained in the processor's database. Valid values are:

A = ADDRESS--Addresses matched, but ZIP codes did not match.
 E * = ERROR--The transaction was not eligible for address verification or an editing error occurred while attempting to process the message.
 N = NO--Addresses did not match and ZIP codes did not match.
 R * = RETRY--Primary and secondary authorizers were unavailable or declined the transaction and address verification was not performed on BASE24-pos.
 S * = SERVICE NOT SUPPORTED--BASE24-pos authorized the transaction, but did not have the add-on Address Verification module.
 U * = UNAVAILABLE--Address information was not available to the processor performing address verification.
 W = WHOLE ZIP--Nine-digit ZIP codes matched, but addresses did not match.
 X = EXACT--Addresses and nine-digit ZIP codes matched.
 Y = YES--Addresses and five-digit ZIP codes matched.
 Z = ZIP--Five-digit ZIP codes matched, but addresses

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

did not match.

_ * = Address verification information was not included in this transaction (_ denotes a blank character).

0 * = Address verification information was included in this transaction, but was not verified. A transaction to be verified by a host or interchange carries this code. A transaction to be verified on BASE24-pos, but declined before address verification could be performed also carries this code.

* This value identifies a reason that a comparison was not made. Each interchange specifies the value it uses to identify this reason. Interchange interfaces substitute the interchange-specific value before sending the message from BASE24-pos to the interchange. Refer to section 1 of the "BASE24-pos Address Verification Manual" for a listing of interchange-specific values.

Interchange response messages received by BASE24-pos may contain interchange-specific values.

BASE24 Interchange Interfaces do not change a value received from the interchange.

Refer to the individual interchange documentation for details of interchange-specific values.

816	[1]	authx.pin^ind	PIC 9(1).
-----	-----	---------------	-----------

An indicator as to whether the PIN was present in the transaction. Valid values are:

0 = PIN not present

1 = PIN present

817	[1]	authx.pin^tries	PIC X(1).
-----	-----	-----------------	-----------

The number of PIN tries.

818	[14]	authx.pre^auth^ts	
-----	------	-------------------	--

The expiration date and time assigned to a pre-auth hold entry when it is added to the CAF, UAF or PBF.

818	[6]	authx.pre^auth^ts.dat [DAT]	
-----	-----	--------------------------------	--

818	[2]	authx.pre^auth^ts.dat.yy.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

820	[2]	authx.pre^auth^ts.dat.mm.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

822	[2]	authx.pre^auth^ts.dat.dd.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

824	[8]	authx.pre^auth^ts.tim [TIM]	
-----	-----	--------------------------------	--

824	[2]	authx.pre^auth^ts.tim.hh.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

826	[2]	authx.pre^auth^ts.tim.mm.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

828	[2]	authx.pre^auth^ts.tim.ss.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

830	[2]	authx.pre^auth^ts.tim.tt.byte[0:1]	PIC X(2).
-----	-----	------------------------------------	-----------

832	[1]	authx.pre^auth^hlds^lvl	PIC X(1).
-----	-----	-------------------------	-----------

A code identifying the file or files in which a pre-auth hold entry is stored. Valid values are:

0 = No holds level, or not applicable
 1 = Holds stored at CAF level
 2 = Holds stored at PBF level
 3 = Holds stored at CAF and PBF levels
 4 = Holds stored at UAF level

833	[33]	authx.user^fld5.byte[0:32]	PIC X(33).
-----	------	----------------------------	------------

Reserved for future use.

866	[204]	user^data^d [USER-DATA-D]	
-----	-------	---------------------------	--

866	[4]	user^data^d.len.byte[0:3]	PIC X(4).
-----	-----	---------------------------	-----------

User data information loaded from the PSTM for the transaction. The user data area is used by the originator of the PSTM.

870	[200]	user^data^d.info.byte[0:199]	PIC X(200).
-----	-------	------------------------------	-------------

END [size 1070]

Offset[Len] Field Name and Description Data Type

DEF PTLFX-SET-REC

0 [846]

0 [183] headx [HEADX]

The POS Transaction Log File (PTLF) contains a record of each financial transaction (approved or denied) processed by BASE24-pos for a single processing day. Transactions declined by a Device Handler (for example, bad format), are typically not posted to the PTLF. It also contains settlement records for each POS terminal in the system. This file is an audit record at the transaction level of the system's processing and is extracted daily to provide detailed transaction data for processing by a host.

Records are written to the PTLF sequentially, and two PTLFs are always accessible to the system for logging: the current day's PTLF and the next day's PTLF. Which PTLF a transaction posts to is based on the transaction's PTDF posting date. This is derived from the current business date of the terminal at which the transaction originated. Use of two PTLFs allows BASE24-pos terminals to be cut over at different times. As terminals are cut over, transactions from those terminals begin posting to the next day's PTLF; transactions from terminals that have not been cut over for the day continue to post to the current day's PTLF.

When network settlement occurs, a new PTLF is created and the current day's PTLF is closed to the online system. At that time, the current day's PTLF is available for reporting and extract processing.

LCONF ASSIGN: POS-PTLF

PTLF RECORD STRUCTURE

There are five formats used in writing PTLF records in the ASCII-only format.

- o Financial Transaction (PTLFX)
- o Settlement Totals (PTLFX-SET-REC)
- o Clerk Totals (PTLFX-CLERK-TOT)
- o First Services (PTLFX-SRVCS-1)
- o Second Services (PTLFX-SRVCS-2)

The values contained in the HEADX.REC-TYP and HEADX.TKEY.RKEY.REC-FRMT fields identify the type of information contained in the PTLFX record. The various value combinations and the resulting record format and contents include:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

REC-TYP	REC-FRMT	RECORD FORMAT AND CONTENTS
00	-	Initial
01	5	Financial Transaction--Customer
04	0	Settlement Totals--Batch
04	1	Settlement Totals--Shift
04	2	Settlement Totals--Daily
04	3	Settlement Totals--Network
04	4	Clerk Totals
04	8	Second Services
04	9	First Services
20	5	Financial Transaction--Exception (posted)
21	5	Financial Transaction--Exception (not posted)
22	5	Financial Transaction--Exception (partially posted)
23	5	Financial Transaction--Exception (invalid data)

0	[19]	headx.dat^tim.byte[0:18]	PIC X(19).
---	------	--------------------------	------------

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility.

19	[2]	headx.rec^typ.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

A code indicating the type of record. Authorization sets the value in this field when the record is logged. Valid values are:

00 = Initial record
 01 = Customer transaction
 04 = Administrative transaction
 20 = Exception--posted
 21 = Exception--not posted
 22 = Exception--partially posted
 23 = Exception--invalid data encountered in the
 POS Standard Internal Message (PSTM)

In situations where a transaction cannot be completely processed because of a processing error (e.g., invalid data, unable to locate an authorization record, etc), the Authorization process logs the transaction to the PTLF as an exception. Exception transactions are included as detail items in the BASE24-pos reports but are not included in the BASE24-pos settlement totals.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

21	[30]	headx.crd	
----	------	-----------	--

The values in the following fields describe the cardholder and card issuer for the transaction. This is an alternate key used for reporting and perusal purposes.

21	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network with which the institution that issued the card is associated.

25	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the institution that issued the card.

29	[22]	headx.crd.card	
----	------	----------------	--

The values in the following fields identify the card used in the transaction.

29	[19]	headx.crd.card.crd^num.byte[0:18]	PIC X(19).
----	------	-----------------------------------	------------

The card number identifying the card used in the transaction.

48	[3]	headx.crd.card.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
----	-----	---	-----------

The member number associated with the card used in the transaction.

51	[57]	headx.ret1	
----	------	------------	--

The values in the following fields describe the retailer involved in the transaction. The values in these fields are used for reporting purposes.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

51	[35]	headx.ret1.ky	
----	------	---------------	--

51	[4]	headx.ret1.ky.ln.byte[0:3] [LN]	PIC X(4).
----	-----	------------------------------------	-----------

The logical network with which the retailer is associated.

55	[31]	headx.ret1.ky.rdfkey	
----	------	----------------------	--

The values in the following fields compose the key to the retailer's POS Retailer Definition File (PRDF) record.

55	[4]	headx.ret1.ky.rdfkey.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	---	-----------

The FIID of the institution with which the retailer is associated.

59	[4]	headx.ret1.ky.rdfkey.grp.byte[0:3]	PIC X(4).
----	-----	------------------------------------	-----------

The group to which the retailer belongs.

63	[4]	headx.ret1.ky.rdfkey.regn.byte[0:3] [REGN]	PIC X(4).
----	-----	---	-----------

The retailer region group to which the retailer belongs.

67	[19]	headx.ret1.ky.rdfkey.id.byte[0:18]	PIC X(19).
----	------	------------------------------------	------------

The retailer ID identifying the retailer.

86	[16]	headx.ret1.term^id.byte[0:15]	PIC X(16).
----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

102	[3]	headx.ret1.shift^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

136	[2]	headx.term.tim.ss.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

138	[2]	headx.term.tim.tt.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

140	[42]	headx.tkey	
-----	------	------------	--

The following fields identify the terminal, retailer, and clerk associated with the transaction. These fields are used as an alternate key to peruse transactions by terminal, retailer, and clerk.

140	[16]	headx.tkey.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

156	[26]	headx.tkey.rkey	
-----	------	-----------------	--

156	[1]	headx.tkey.rkey.rec^frmt	PIC X(1).
-----	-----	--------------------------	-----------

A code indicating the type of information in this record. Valid values are:

- 0 = Batch Totals
- 1 = Shift Totals
- 2 = Day Totals
- 3 = Network Totals
- 4 = Clerk Totals
- 5 = Data Record
- 8 = Services Totals
- 9 = Services Totals

157	[19]	headx.tkey.rkey.retailer^id.byte[0:18]	PIC X(19).
-----	------	--	------------

The retailer ID identifying the retailer.

176	[6]	headx.tkey.rkey.clerk^id.byte[0:5]	PIC X(6).
-----	-----	------------------------------------	-----------

The clerk identification number.

182	[1]	headx.data^flag	PIC X(1).
-----	-----	-----------------	-----------

Indicates whether the user-data field is appended to the PTLF record. Valid values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

0 = No user-data appended
1 = User-data appended

183	[459]	set^rec	
183	[168]	set^rec.set^rec1d [SET-REC1D]	
183	[4]	set^rec.set^rec1d.typ.byte[0:3]	PIC 9(4).

A code indicating the type of PTLF record. The valid code is 0500, reconciliation record.

187	[6]	set^rec.set^rec1d.post^dat [DAT]	
The posting date (YYMMDD) for the settlement record.			
187	[2]	set^rec.set^rec1d.post^dat.yy.byte[0:1]	PIC X(2).
189	[2]	set^rec.set^rec1d.post^dat.mm.byte[0:1]	PIC X(2).
191	[2]	set^rec.set^rec1d.post^dat.dd.byte[0:1]	PIC X(2).
193	[2]	set^rec.set^rec1d.prod^id.byte[0:1]	PIC 9(2).

A code identifying the BASE24 product. The valid code is 02, BASE24-pos.

195	[2]	set^rec.set^rec1d.rel^num.byte[0:1]	PIC 9(2).
-----	-----	-------------------------------------	-----------

A code identifying the current version of the product.

197	[4]	set^rec.set^rec1d.dpc^num.byte[0:3]	PIC 9(4).
-----	-----	-------------------------------------	-----------

The number of the institution's Data Processing Center (DPC). This is the host computer that processes messages received from BASE24.

201	[5]	set^rec.set^rec1d.term^tim^ofst.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The time difference between the terminal and the

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

Tandem processor location. It is the signed (+ or -) number of minutes to be added to the BASE24 Tandem system time in order to obtain the terminal local time.

206	[16]	set^rec.set^recld.term^id.byte[0:15]	PIC X(16).
-----	------	--------------------------------------	------------

The terminal ID of the terminal on which the settlement occurred.

222	[71]	set^rec.set^recld.ret1	
-----	------	------------------------	--

The values in the following fields describe the retailer portion of the settlement record.

222	[11]	set^rec.set^recld.ret1.rtn.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

The institution's route and transit number, transit/routing number, or issuer identification number of the terminal owner. The identification data is right-justified with high-order zero fill.

233	[19]	set^rec.set^recld.ret1.acct.byte[0:18]	PIC X(19).
-----	------	--	------------

The account number at the retailer's financial institution for the retailer associated with the settlement record.

252	[40]	set^rec.set^recld.ret1.nam.byte[0:39]	PIC X(40).
-----	------	---------------------------------------	------------

The name of the retailer associated with the settlement record.

292	[1]	set^rec.set^recld.ret1.user^fld1	PIC X(1).
-----	-----	----------------------------------	-----------

Reserved for future use.

293	[1]	set^rec.set^recld.set1^typ	PIC 9(1).
-----	-----	----------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code identifying the type of settlement record being displayed. Valid values are:

- 0 = Batch
- 1 = Shift
- 2 = Daily
- 3 = Network
- 4 = Clerk
- 8 = Services 2 (last 13 services)
- 9 = Services 1 (first 17 services)

294	[1]	set^rec.set^recld.bal^flg	PIC 9(1).
-----	-----	---------------------------	-----------

A code identifying the method used to perform the most recent balancing of this terminal. Valid options are:

- 5 = Balanced--Terminal balanced by a close transaction from terminal. Totals sent by terminal agreed with BASE24 totals or terminal did not send any totals. Totals were written to the PTLF and cleared.
- 6 = Balanced (with problems)--Terminal balanced by a close transaction from terminal. Totals sent by terminal did not agree with BASE24 totals and require verification. Totals were written to the PTLF and cleared.
- 8 = Force-balanced (incomplete batch)--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. The terminal was cut over to a new reporting day, and its totals were written to the PTLF, but only current network totals were reset to zero. This method is used when the value in the TERM-CUTOVER-TC field in the PTDF is 0, 1, or 2, and the close transaction has not been received from the terminal within the time window defined by the values in the RETAILER-BAL-AND-CUTVR-START and RETAILER-BAL-AND-CUTVR-END fields in the PRDF.
- 9 = Force-balanced--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 3.
Also set to 9 when the terminal was cut over by the device handler on the first financial transaction after the retailer cutover balance start time as specified in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 4.
In both cases, the terminal was cut over to a new reporting day, its totals were written to the PTLF and all BASE24 totals for the terminal were cleared.

Offset[Len] Field Name and Description Data Type

295 [1] set^rec.set^recld.user^fld2 PIC X(1).

Reserved for future use.

296 [6] set^rec.set^recld.tran^dat
[DAT]

The date (YYMMDD) of the transaction. The value in this field is set by the Device Handler or Settlement.

296 [2] set^rec.set^recld.tran^dat.yy.byte[0:1] PIC X(2).

298 [2] set^rec.set^recld.tran^dat.mm.byte[0:1] PIC X(2).

300 [2] set^rec.set^recld.tran^dat.dd.byte[0:1] PIC X(2).

302 [6] set^rec.set^recld.tran^tim.byte[0:5] PIC X(6).

The time (HHMMSS) of the transaction. The value in this field is set by the Device Handler or Settlement.

308 [1] set^rec.set^recld.ob^flg PIC X(1).

A flag indicating whether this balancing record has an associated balancing record if a terminal is out-of-balance with BASE24-pos. This flag is used if the value in the BAL-FLG field of this record is 5 or 6. Valid codes are:

0 = No associated record exists
1 = Associated record exists

309 [10] set^rec.set^recld.ach^comp^id.byte[0:9] PIC X(10).

This field is reserved for Automated Clearinghouse (ACH) information that may be required for processing transactions from this retailer. Information in this field has no impact on BASE24-pos processing.

319 [10] set^rec.set^recld.billing^info.byte[0:9] PIC X(10).

Offset[Len] Field Name and Description Data Type

A free-form informational field used at the discretion of the institution. Typically, this field contains ACH information that BASE24-pos passes on to the host for use by the ACH system. Information in this field has no impact on BASE24-pos processing.

329 [3] set^rec.set^recld.auth^crncy^cde.byte[0:2]
[CRNCY-CDE] PIC 9(3).

A code indicating the type of currency used for the transactions pertaining to this terminal.

332 [8] set^rec.set^recld.auth^conv^rate.byte[0:7] PIC X(8).

The exchange rate of the authorizing entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

340 [3] set^rec.set^recld.setl^crncy^cde.byte[0:2]
[CRNCY-CDE] PIC 9(3).

A code indicating the type of currency used in the settlement of the transaction.

343 [8] set^rec.set^recld.setl^conv^rate.byte[0:7] PIC X(8).

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are used, the default value is 61000000.

351 [1] set^rec.user^fld7 PIC X(1).

352 [288] set^rec.set^rec2d
[SET-REC2D]

352 [288] set^rec.set^rec2d.stl

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The following fields contain the total counts and amounts of debits, credits, and adjustments for draft capture and non-draft capture transactions.

352	[72]	set^rec.set^rec2d.stl.dc^tot
-----	------	------------------------------

The following fields contain the total counts and amounts of debits, credits, and adjustments for draft capture transactions.

352	[5]	set^rec.set^rec2d.stl.dc^tot.db^cnt.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The number of draft capture debit transactions.

357	[19]	set^rec.set^rec2d.stl.dc^tot.db.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture debit transactions.

376	[5]	set^rec.set^rec2d.stl.dc^tot.cr^cnt.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The number of draft capture credit transactions.

381	[19]	set^rec.set^rec2d.stl.dc^tot.cr.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture credit transactions.

400	[5]	set^rec.set^rec2d.stl.dc^tot.adj^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The number of draft capture adjustment transactions.

405	[19]	set^rec.set^rec2d.stl.dc^tot.adj.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture

Offset[Len] Field Name and Description Data Type

adjustment transactions.

424 [72] set^rec.set^rec2d.stl.tot

424 [5] set^rec.set^rec2d.stl.tot.db^cnt.byte[0:4] PIC X(5).

The number of draft capture and non-draft capture debit transactions.

429 [19] set^rec.set^rec2d.stl.tot.db.byte[0:18] PIC X(19).

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture and non-draft capture debit transactions.

448 [5] set^rec.set^rec2d.stl.tot.cr^cnt.byte[0:4] PIC X(5).

The number of draft capture and non-draft capture credit transactions.

453 [19] set^rec.set^rec2d.stl.tot.cr.byte[0:18] PIC X(19).

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture and non-draft capture credit transactions.

472 [5] set^rec.set^rec2d.stl.tot.adj^cnt.byte[0:4] PIC X(5).

The number of draft capture and non-draft capture adjustment transactions.

477 [19] set^rec.set^rec2d.stl.tot.adj.byte[0:18] PIC X(19).

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all draft capture and non-draft capture adjustment transactions.

496 [72] set^rec.set^rec2d.stl.cn^dc^tot

496 [5] set^rec.set^rec2d.stl.cn^dc^tot.db^cnt.byte[0:4] PIC X(5).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The number of debit draft capture transactions that have occurred since terminal cutover.

501	[19]	set^rec.set^rec2d.stl.cn^dc^tot.db.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all debit draft capture transactions that have occurred at the terminal since terminal cutover.

520	[5]	set^rec.set^rec2d.stl.cn^dc^tot.cr^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The number of credit draft capture transactions that have occurred since terminal cutover.

525	[19]	set^rec.set^rec2d.stl.cn^dc^tot.cr.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all credit draft capture transactions that have occurred at the terminal since terminal cutover.

544	[5]	set^rec.set^rec2d.stl.cn^dc^tot.adj^cnt.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The number of adjustment draft capture transactions that have occurred since terminal cutover.

549	[19]	set^rec.set^rec2d.stl.cn^dc^tot.adj.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all adjustment draft capture transactions that have occurred at the terminal since terminal cutover.

568	[72]	set^rec.set^rec2d.stl.cn^tot	
-----	------	------------------------------	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

568 [5]	set^rec.set^rec2d.stl.cn^tot.db^cnt.byte[0:4]	PIC X(5).
---------	---	-----------

The number of debit draft capture and non-draft capture transactions that have occurred since terminal cutover.

573 [19]	set^rec.set^rec2d.stl.cn^tot.db.byte[0:18]	PIC X(19).
----------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all debit draft capture and non-draft capture transactions that have occurred at the terminal since terminal cutover.

592 [5]	set^rec.set^rec2d.stl.cn^tot.cr^cnt.byte[0:4]	PIC X(5).
---------	---	-----------

The number of credit draft capture and non-draft capture transactions that have occurred since terminal cutover.

597 [19]	set^rec.set^rec2d.stl.cn^tot.cr.byte[0:18]	PIC X(19).
----------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all credit draft capture and non-draft capture transactions that have occurred at the terminal since terminal cutover.

616 [5]	set^rec.set^rec2d.stl.cn^tot.adj^cnt.byte[0:4]	PIC X(5).
---------	--	-----------

The number of adjustment draft capture and non-draft capture transactions that have occurred since terminal cutover.

621 [19]	set^rec.set^rec2d.stl.cn^tot.adj.byte[0:18]	PIC X(19).
----------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), of all adjustment draft capture and non-draft capture transactions that have occurred at the terminal since terminal cutover.

640 [2]	set^rec.user^fld8.byte[0:1]	PIC X(2).
---------	-----------------------------	-----------

642 [204]	user^data^d [USER-DATA-D]	
-----------	---------------------------	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

642 [4]	user^data^d.len.byte[0:3]	PIC X(4).
---------	---------------------------	-----------

User data information loaded from the PSTM for the transaction. The user data area is used by the originator of the PSTM.

646 [200]	user^data^d.info.byte[0:199]	PIC X(200).
-----------	------------------------------	-------------

END [size 846]

Offset[Len] Field Name and Description Data Type

DEF PTLFX-SRVCS-1

0 [1820]

0 [183] headx [HEADX]

The POS Transaction Log File (PTLF) contains a record of each financial transaction (approved or denied) processed by BASE24-pos for a single processing day. Transactions declined by a Device Handler (for example, bad format), are typically not posted to the PTLF. It also contains settlement records for each POS terminal in the system. This file is an audit record at the transaction level of the system's processing and is extracted daily to provide detailed transaction data for processing by a host.

Records are written to the PTLF sequentially, and two PTLFs are always accessible to the system for logging: the current day's PTLF and the next day's PTLF. Which PTLF a transaction posts to is based on the transaction's PTLF posting date. This is derived from the current business date of the terminal at which the transaction originated. Use of two PTLFs allows BASE24-pos terminals to be cut over at different times. As terminals are cut over, transactions from those terminals begin posting to the next day's PTLF; transactions from terminals that have not been cut over for the day continue to post to the current day's PTLF.

When network settlement occurs, a new PTLF is created and the current day's PTLF is closed to the online system. At that time, the current day's PTLF is available for reporting and extract processing.

LCONF ASSIGN: POS-PTLF

PTLF RECORD STRUCTURE

There are five formats used in writing PTLF records in the ASCII-only format.

- o Financial Transaction (PTLFX)
- o Settlement Totals (PTLFX-SET-REC)
- o Clerk Totals (PTLFX-CLERK-TOT)
- o First Services (PTLFX-SRVCS-1)
- o Second Services (PTLFX-SRVCS-2)

The values contained in the HEADX.REC-TYP and HEADX.TKEY.RKEY.REC-FRMT fields identify the type of information contained in the PTLFX record. The various value combinations and the resulting record format and contents include:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

REC-TYP	REC-FRMT	RECORD FORMAT AND CONTENTS
00	-	Initial
01	5	Financial Transaction--Customer
04	0	Settlement Totals--Batch
04	1	Settlement Totals--Shift
04	2	Settlement Totals--Daily
04	3	Settlement Totals--Network
04	4	Clerk Totals
04	8	Second Services
04	9	First Services
20	5	Financial Transaction--Exception (posted)
21	5	Financial Transaction--Exception (not posted)
22	5	Financial Transaction--Exception (partially posted)
23	5	Financial Transaction--Exception (invalid data)

0	[19]	headx.dat^tim.byte[0:18]	PIC X(19).
---	------	--------------------------	------------

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility.

19	[2]	headx.rec^typ.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

A code indicating the type of record. Authorization sets the value in this field when the record is logged. Valid values are:

00 = Initial record
 01 = Customer transaction
 04 = Administrative transaction
 20 = Exception--posted
 21 = Exception--not posted
 22 = Exception--partially posted
 23 = Exception--invalid data encountered in the
 POS Standard Internal Message (PSTM)

In situations where a transaction cannot be completely processed because of a processing error (e.g., invalid data, unable to locate an authorization record, etc), the Authorization process logs the transaction to the PTLF as an exception. Exception transactions are included as detail items in the BASE24-pos reports but are not included in the BASE24-pos settlement totals.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

21	[30]	headx.crd	
----	------	-----------	--

The values in the following fields describe the cardholder and card issuer for the transaction. This is an alternate key used for reporting and perusal purposes.

21	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network with which the institution that issued the card is associated.

25	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the institution that issued the card.

29	[22]	headx.crd.card	
----	------	----------------	--

The values in the following fields identify the card used in the transaction.

29	[19]	headx.crd.card.crd^num.byte[0:18]	PIC X(19).
----	------	-----------------------------------	------------

The card number identifying the card used in the transaction.

48	[3]	headx.crd.card.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
----	-----	---	-----------

The member number associated with the card used in the transaction.

51	[57]	headx.ret1	
----	------	------------	--

The values in the following fields describe the retailer involved in the transaction. The values in these fields are used for reporting purposes.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

51	[35]	headx.ret1.ky	
----	------	---------------	--

51	[4]	headx.ret1.ky.ln.byte[0:3] [LN]	PIC X(4).
----	-----	------------------------------------	-----------

The logical network with which the retailer is associated.

55	[31]	headx.ret1.ky.rdfkey	
----	------	----------------------	--

The values in the following fields compose the key to the retailer's POS Retailer Definition File (PRDF) record.

55	[4]	headx.ret1.ky.rdfkey.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	---	-----------

The FIID of the institution with which the retailer is associated.

59	[4]	headx.ret1.ky.rdfkey.grp.byte[0:3]	PIC X(4).
----	-----	------------------------------------	-----------

The group to which the retailer belongs.

63	[4]	headx.ret1.ky.rdfkey.regn.byte[0:3] [REGN]	PIC X(4).
----	-----	---	-----------

The retailer region group to which the retailer belongs.

67	[19]	headx.ret1.ky.rdfkey.id.byte[0:18]	PIC X(19).
----	------	------------------------------------	------------

The retailer ID identifying the retailer.

86	[16]	headx.ret1.term^id.byte[0:15]	PIC X(16).
----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

102	[3]	headx.ret1.shift^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The shift number with which the transaction is associated.

105	[3]	headx.ret1.batch^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

The batch number with which the transaction is associated.

108	[32]	headx.term	
-----	------	------------	--

The following fields define the terminal and time at which the transaction occurred. These fields are used as an alternate key to peruse transactions by terminal and time.

108	[4]	headx.term.ln.byte[0:3] [LN]	PIC X(4).
-----	-----	---------------------------------	-----------

The logical network with which the terminal is associated.

112	[4]	headx.term.fiid.byte[0:3] [FIID]	PIC X(4).
-----	-----	-------------------------------------	-----------

The FIID of the institution with which the terminal is associated.

116	[16]	headx.term.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

132	[8]	headx.term.tim [TIM]	
-----	-----	----------------------	--

The time the transaction occurred.

132	[2]	headx.term.tim.hh.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

134	[2]	headx.term.tim.mm.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

136	[2]	headx.term.tim.ss.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

138	[2]	headx.term.tim.tt.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

140	[42]	headx.tkey	
-----	------	------------	--

The following fields identify the terminal, retailer, and clerk associated with the transaction. These fields are used as an alternate key to peruse transactions by terminal, retailer, and clerk.

140	[16]	headx.tkey.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

156	[26]	headx.tkey.rkey	
-----	------	-----------------	--

156	[1]	headx.tkey.rkey.rec^frmt	PIC X(1).
-----	-----	--------------------------	-----------

A code indicating the type of information in this record. Valid values are:

- 0 = Batch Totals
- 1 = Shift Totals
- 2 = Day Totals
- 3 = Network Totals
- 4 = Clerk Totals
- 5 = Data Record
- 8 = Services Totals
- 9 = Services Totals

157	[19]	headx.tkey.rkey.retailer^id.byte[0:18]	PIC X(19).
-----	------	--	------------

The retailer ID identifying the retailer.

176	[6]	headx.tkey.rkey.clerk^id.byte[0:5]	PIC X(6).
-----	-----	------------------------------------	-----------

The clerk identification number.

182	[1]	headx.data^flag	PIC X(1).
-----	-----	-----------------	-----------

Indicates whether the user-data field is appended to the PTLF record. Valid values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

0 = No user-data appended
1 = User-data appended

183	[1433]	srvcs^1	
183	[168]	srvcs^1.set^rec1d [SET-REC1D]	
183	[4]	srvcs^1.set^rec1d.typ.byte[0:3]	PIC 9(4).

A code indicating the type of PTLF record. The valid code is 0500, reconciliation record.

187	[6]	srvcs^1.set^rec1d.post^dat [DAT]	
The posting date (YYMMDD) for the settlement record.			
187	[2]	srvcs^1.set^rec1d.post^dat.yy.byte[0:1]	PIC X(2).
189	[2]	srvcs^1.set^rec1d.post^dat.mm.byte[0:1]	PIC X(2).
191	[2]	srvcs^1.set^rec1d.post^dat.dd.byte[0:1]	PIC X(2).
193	[2]	srvcs^1.set^rec1d.prod^id.byte[0:1]	PIC 9(2).

A code identifying the BASE24 product. The valid code is 02, BASE24-pos.

195	[2]	srvcs^1.set^rec1d.rel^num.byte[0:1]	PIC 9(2).
-----	-----	-------------------------------------	-----------

A code identifying the current version of the product.

197	[4]	srvcs^1.set^rec1d.dpc^num.byte[0:3]	PIC 9(4).
-----	-----	-------------------------------------	-----------

The number of the institution's Data Processing Center (DPC). This is the host computer that processes messages received from BASE24.

201	[5]	srvcs^1.set^rec1d.term^tim^ofst.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The time difference between the terminal and the

Offset[Len]	Field Name and Description	Data Type
	Tandem processor location. It is the signed (+ or -) number of minutes to be added to the BASE24 Tandem system time in order to obtain the terminal local time.	
206 [16]	srvcs^1.set^recld.term^id.byte[0:15]	PIC X(16).
	The terminal ID of the terminal on which the settlement occurred.	
222 [71]	srvcs^1.set^recld.ret1	
	The values in the following fields describe the retailer portion of the settlement record.	
222 [11]	srvcs^1.set^recld.ret1.rtn.byte[0:10] [ID-NUM]	PIC 9(11).
	The institution's route and transit number, transit/routing number, or issuer identification number of the terminal owner. The identification data is right-justified with high-order zero fill.	
233 [19]	srvcs^1.set^recld.ret1.acct.byte[0:18]	PIC X(19).
	The account number at the retailer's financial institution for the retailer associated with the settlement record.	
252 [40]	srvcs^1.set^recld.ret1.nam.byte[0:39]	PIC X(40).
	The name of the retailer associated with the settlement record.	
292 [1]	srvcs^1.set^recld.ret1.user^fld1	PIC X(1).
	Reserved for future use.	
293 [1]	srvcs^1.set^recld.set1^typ	PIC 9(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code identifying the type of settlement record being displayed. Valid values are:

- 0 = Batch
- 1 = Shift
- 2 = Daily
- 3 = Network
- 4 = Clerk
- 8 = Services 2 (last 13 services)
- 9 = Services 1 (first 17 services)

294	[1]	srvcs^1.set^recld.bal^flg	PIC 9(1).
-----	-----	---------------------------	-----------

A code identifying the method used to perform the most recent balancing of this terminal. Valid options are:

- 5 = Balanced--Terminal balanced by a close transaction from terminal. Totals sent by terminal agreed with BASE24 totals or terminal did not send any totals. Totals were written to the PTLF and cleared.
- 6 = Balanced (with problems)--Terminal balanced by a close transaction from terminal. Totals sent by terminal did not agree with BASE24 totals and require verification. Totals were written to the PTLF and cleared.
- 8 = Force-balanced (incomplete batch)--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. The terminal was cut over to a new reporting day, and its totals were written to the PTLF, but only current network totals were reset to zero. This method is used when the value in the TERM-CUTOVER-TC field in the PTDF is 0, 1, or 2, and the close transaction has not been received from the terminal within the time window defined by the values in the RETAILER-BAL-AND-CUTVR-START and RETAILER-BAL-AND-CUTVR-END fields in the PRDF.
- 9 = Force-balanced--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 3.
Also set to 9 when the terminal was cut over by the device handler on the first financial transaction after the retailer cutover balance start time as specified in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 4.
In both cases, the terminal was cut over to a new reporting day, its totals were written to the PTLF and all BASE24 totals for the terminal were cleared.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

295	[1]	srvcs^1.set^rec1d.user^fld2	PIC X(1).
-----	-----	-----------------------------	-----------

Reserved for future use.

296	[6]	srvcs^1.set^rec1d.tran^dat [DAT]	
-----	-----	-------------------------------------	--

The date (YYMMDD) of the transaction. The value in this field is set by the Device Handler or Settlement.

296	[2]	srvcs^1.set^rec1d.tran^dat.yy.byte[0:1]	PIC X(2).
-----	-----	---	-----------

298	[2]	srvcs^1.set^rec1d.tran^dat.mm.byte[0:1]	PIC X(2).
-----	-----	---	-----------

300	[2]	srvcs^1.set^rec1d.tran^dat.dd.byte[0:1]	PIC X(2).
-----	-----	---	-----------

302	[6]	srvcs^1.set^rec1d.tran^tim.byte[0:5]	PIC X(6).
-----	-----	--------------------------------------	-----------

The time (HHMMSS) of the transaction. The value in this field is set by the Device Handler or Settlement.

308	[1]	srvcs^1.set^rec1d.ob^flg	PIC X(1).
-----	-----	--------------------------	-----------

A flag indicating whether this balancing record has an associated balancing record if a terminal is out-of-balance with BASE24-pos. This flag is used if the value in the BAL-FLG field of this record is 5 or 6. Valid codes are:

0 = No associated record exists
1 = Associated record exists

309	[10]	srvcs^1.set^rec1d.ach^comp^id.byte[0:9]	PIC X(10).
-----	------	---	------------

This field is reserved for Automated Clearinghouse (ACH) information that may be required for processing transactions from this retailer. Information in this field has no impact on BASE24-pos processing.

319	[10]	srvcs^1.set^rec1d.billing^info.byte[0:9]	PIC X(10).
-----	------	--	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A free-form informational field used at the discretion of the institution. Typically, this field contains ACH information that BASE24-pos passes on to the host for use by the ACH system. Information in this field has no impact on BASE24-pos processing.

329	[3]	srvcs^1.set^recld.auth^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used for the transactions pertaining to this terminal.

332	[8]	srvcs^1.set^recld.auth^conv^rate.byte[0:7]	PIC X(8).
-----	-----	--	-----------

The exchange rate of the authorizing entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

340	[3]	srvcs^1.set^recld.setl^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used in the settlement of the transaction.

343	[8]	srvcs^1.set^recld.setl^conv^rate.byte[0:7]	PIC X(8).
-----	-----	--	-----------

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are used, the default value is 61000000.

351	[1]	srvcs^1.user^fld9	PIC X(1).
-----	-----	-------------------	-----------

352	[1263]	srvcs^1.set^rec3d [SET-REC3D]	
-----	--------	----------------------------------	--

352	[5]	srvcs^1.set^rec3d.num^srv.byte[0:4]	PIC X(5).
-----	-----	-------------------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The total number of services supported by this terminal, as defined in the NUM-SRV field of the PTDF. If more than 17 services are being used, the First Services record contains only the first 17 services. All subsequent services (the last 13) are contained in the Second Services record. For example, if 27 services are being used, the value in this field is 27. The first 17 services are contained in the SET-REC3D field of the First Services record and the last 10 services are contained in the SET-REC4D field of the Second Services record.

357	[1258]	srvcs^1.set^rec3d.srv[0:16]
-----	--------	-----------------------------

The following fields identify the first 17 services being used.

357	[2]	srvcs^1.set^rec3d.srv[0:16].typ.byte[0:1]	PIC X(2).
-----	-----	---	-----------

A code identifying each of the service types associated with the First Services record.

One- or two-character codes are used to identify card types in files throughout BASE24. The same codes must be used for a particular card type in all of the files. These codes are also used to identify service types in BASE24-pos. Codes used in this field are either reserved by BASE24 or user-defined. Reserved codes are to be used only as defined, and include:

AD = Administrative (BASE24-atm only)
 AX = American Express credit
 BD = Business deposit (BASE24-atm and BASE24-teller only)
 C* = Private label credit (includes C, C0-C9, CA, and CC-CZ)
 CB = Carte Blanche credit
 D = Demonstration (BASE24-atm only)
 DC = Diners Club credit
 DS = Discover (Sears) credit
 M = MasterCard credit
 MD = MasterCard debit (See BASE24-pos note below)
 MM = MasterCard dual (See BASE24-pos note below)
 P* = Proprietary debit (includes P, P0-P9, and PA-PZ)
 SC = Special, Check (BASE24-pos only)
 SP = Special purpose (BASE24-atm Self-Service Banking Check Application only)
 ST = Super teller (BASE24-atm Self-Service Banking Base Application only)

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

V = VISA credit

VD = VISA debit (See BASE24-pos note below)

VV = VISA dual (See BASE24-pos note below)

Codes with a first character of C, except code CB, are recommended to identify private label credit cards.

Codes with a first character of P are required to identify proprietary debit cards. BASE24 treats cards with proprietary debit codes and codes MD and VD as debit cards and treats cards with all other codes as credit cards.

Administrative (AD), Business deposit (BD), Demonstration (D), Special purpose (SP), and Super teller (ST) are special-use card types used by BASE24-atm.

Business deposit (BD) is also a special-use card type used by BASE24-teller to identify cards that can only be used to initiate deposit transactions.

BASE24-teller does not perform any other processing based on card type; however, BASE24 guidelines should still be used when establishing card types for BASE24-teller.

MasterCard dual (MM) and VISA dual (VV) can be processed as debit or credit card types, based on the default combo card type specified in the CPF.

Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only.

BASE24-pos NOTE: BASE24-pos does not allow MasterCard debit (MD), MasterCard dual (MM), VISA debit (VD), or VISA dual (VV) card types in the PRDF and PTDF.

BASE24-pos automatically includes the MD and MM card types with the MasterCard credit (M) card type, and automatically includes the VD and VV card types with the VISA credit (V) card type.

User-defined Codes: The user can add any one- or two-character code not included in the reserved code list above, according to the following guidelines:

- o The first character must be alphabetic (A, B, D-O, and Q-Z).
- o The second character can be A-Z, 0-9, or a blank.
- o A valid COBNAMES table entry is recommended for each user-defined code.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

359	[5]	srvcs^1.set^rec3d.srv[0:16].db^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The total number of debit transactions for the service during the current batch.

364	[19]	srvcs^1.set^rec3d.srv[0:16].db.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for debit transactions for the service during the current batch.

383	[5]	srvcs^1.set^rec3d.srv[0:16].cr^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The total number of credit transactions for the service during the current batch.

388	[19]	srvcs^1.set^rec3d.srv[0:16].cr.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for credit transactions for the service during the current batch.

407	[5]	srvcs^1.set^rec3d.srv[0:16].adj^cnt.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The total number of adjustment transactions for the service during the current batch.

412	[19]	srvcs^1.set^rec3d.srv[0:16].adj.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for adjustment transactions for the service during the current batch.

1615	[1]	srvcs^1.user^fld8	PIC X(1).
------	-----	-------------------	-----------

1616	[204]	user^data^d [USER-DATA-D]	
------	-------	---------------------------	--

1616	[4]	user^data^d.len.byte[0:3]	PIC X(4).
------	-----	---------------------------	-----------

User data information loaded from the PSTM for the

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

transaction. The user data area is used by the
originator of the PSTM.

1620 [200]	user^data^d.info.byte[0:199]	PIC X(200).
------------	------------------------------	-------------

END [size 1820]

Offset[Len] Field Name and Description Data Type

DEF PTLFX-SRVCS-2

0 [1520]

0 [183] headx [HEADX]

The POS Transaction Log File (PTLF) contains a record of each financial transaction (approved or denied) processed by BASE24-pos for a single processing day. Transactions declined by a Device Handler (for example, bad format), are typically not posted to the PTLF. It also contains settlement records for each POS terminal in the system. This file is an audit record at the transaction level of the system's processing and is extracted daily to provide detailed transaction data for processing by a host.

Records are written to the PTLF sequentially, and two PTLFs are always accessible to the system for logging: the current day's PTLF and the next day's PTLF. Which PTLF a transaction posts to is based on the transaction's PTLF posting date. This is derived from the current business date of the terminal at which the transaction originated. Use of two PTLFs allows BASE24-pos terminals to be cut over at different times. As terminals are cut over, transactions from those terminals begin posting to the next day's PTLF; transactions from terminals that have not been cut over for the day continue to post to the current day's PTLF.

When network settlement occurs, a new PTLF is created and the current day's PTLF is closed to the online system. At that time, the current day's PTLF is available for reporting and extract processing.

LCONF ASSIGN: POS-PTLF

PTLF RECORD STRUCTURE

There are five formats used in writing PTLF records in the ASCII-only format.

- o Financial Transaction (PTLFX)
- o Settlement Totals (PTLFX-SET-REC)
- o Clerk Totals (PTLFX-CLERK-TOT)
- o First Services (PTLFX-SRVCS-1)
- o Second Services (PTLFX-SRVCS-2)

The values contained in the HEADX.REC-TYP and HEADX.TKEY.RKEY.REC-FRMT fields identify the type of information contained in the PTLFX record. The various value combinations and the resulting record format and contents include:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

REC-TYP	REC-FRMT	RECORD FORMAT AND CONTENTS
00	-	Initial
01	5	Financial Transaction--Customer
04	0	Settlement Totals--Batch
04	1	Settlement Totals--Shift
04	2	Settlement Totals--Daily
04	3	Settlement Totals--Network
04	4	Clerk Totals
04	8	Second Services
04	9	First Services
20	5	Financial Transaction--Exception (posted)
21	5	Financial Transaction--Exception (not posted)
22	5	Financial Transaction--Exception (partially posted)
23	5	Financial Transaction--Exception (invalid data)

0	[19]	headx.dat^tim.byte[0:18]	PIC X(19).
---	------	--------------------------	------------

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility.

19	[2]	headx.rec^typ.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

A code indicating the type of record. Authorization sets the value in this field when the record is logged. Valid values are:

00 = Initial record
 01 = Customer transaction
 04 = Administrative transaction
 20 = Exception--posted
 21 = Exception--not posted
 22 = Exception--partially posted
 23 = Exception--invalid data encountered in the
 POS Standard Internal Message (PSTM)

In situations where a transaction cannot be completely processed because of a processing error (e.g., invalid data, unable to locate an authorization record, etc), the Authorization process logs the transaction to the PTLF as an exception. Exception transactions are included as detail items in the BASE24-pos reports but are not included in the BASE24-pos settlement totals.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

21	[30]	headx.crd	
----	------	-----------	--

The values in the following fields describe the cardholder and card issuer for the transaction. This is an alternate key used for reporting and perusal purposes.

21	[4]	headx.crd.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network with which the institution that issued the card is associated.

25	[4]	headx.crd.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the institution that issued the card.

29	[22]	headx.crd.card	
----	------	----------------	--

The values in the following fields identify the card used in the transaction.

29	[19]	headx.crd.card.crd^num.byte[0:18]	PIC X(19).
----	------	-----------------------------------	------------

The card number identifying the card used in the transaction.

48	[3]	headx.crd.card.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
----	-----	---	-----------

The member number associated with the card used in the transaction.

51	[57]	headx.ret1	
----	------	------------	--

The values in the following fields describe the retailer involved in the transaction. The values in these fields are used for reporting purposes.

Offset[Len] Field Name and Description Data Type

51 [35] headx.ret1.ky

51 [4] headx.ret1.ky.ln.byte[0:3]
[LN] PIC X(4).

The logical network with which the retailer is associated.

55 [31] headx.ret1.ky.rdfkey

The values in the following fields compose the key to the retailer's POS Retailer Definition File (PRDF) record.

55 [4] headx.ret1.ky.rdfkey.fiid.byte[0:3]
[FIID] PIC X(4).

The FIID of the institution with which the retailer is associated.

59 [4] headx.ret1.ky.rdfkey.grp.byte[0:3] PIC X(4).

The group to which the retailer belongs.

63 [4] headx.ret1.ky.rdfkey.regn.byte[0:3]
[REGN] PIC X(4).

The retailer region group to which the retailer belongs.

67 [19] headx.ret1.ky.rdfkey.id.byte[0:18] PIC X(19).

The retailer ID identifying the retailer.

86 [16] headx.ret1.term^id.byte[0:15] PIC X(16).

The terminal ID of the terminal at which the transaction occurred.

102 [3] headx.ret1.shift^num.byte[0:2] PIC X(3).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

136	[2]	headx.term.tim.ss.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

138	[2]	headx.term.tim.tt.byte[0:1]	PIC X(2).
-----	-----	-----------------------------	-----------

140	[42]	headx.tkey	
-----	------	------------	--

The following fields identify the terminal, retailer, and clerk associated with the transaction. These fields are used as an alternate key to peruse transactions by terminal, retailer, and clerk.

140	[16]	headx.tkey.term^id.byte[0:15]	PIC X(16).
-----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

156	[26]	headx.tkey.rkey	
-----	------	-----------------	--

156	[1]	headx.tkey.rkey.rec^frmt	PIC X(1).
-----	-----	--------------------------	-----------

A code indicating the type of information in this record. Valid values are:

- 0 = Batch Totals
- 1 = Shift Totals
- 2 = Day Totals
- 3 = Network Totals
- 4 = Clerk Totals
- 5 = Data Record
- 8 = Services Totals
- 9 = Services Totals

157	[19]	headx.tkey.rkey.retailer^id.byte[0:18]	PIC X(19).
-----	------	--	------------

The retailer ID identifying the retailer.

176	[6]	headx.tkey.rkey.clerk^id.byte[0:5]	PIC X(6).
-----	-----	------------------------------------	-----------

The clerk identification number.

182	[1]	headx.data^flag	PIC X(1).
-----	-----	-----------------	-----------

Indicates whether the user-data field is appended to the PTLF record. Valid values are:

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

0 = No user-data appended
1 = User-data appended

183	[1133]	srvcs^2	
183	[168]	srvcs^2.set^rec1d [SET-REC1D]	
183	[4]	srvcs^2.set^rec1d.typ.byte[0:3]	PIC 9(4).
A code indicating the type of PTLF record. The valid code is 0500, reconciliation record.			
187	[6]	srvcs^2.set^rec1d.post^dat [DAT]	
The posting date (YYMMDD) for the settlement record.			
187	[2]	srvcs^2.set^rec1d.post^dat.yy.byte[0:1]	PIC X(2).
189	[2]	srvcs^2.set^rec1d.post^dat.mm.byte[0:1]	PIC X(2).
191	[2]	srvcs^2.set^rec1d.post^dat.dd.byte[0:1]	PIC X(2).
193	[2]	srvcs^2.set^rec1d.prod^id.byte[0:1]	PIC 9(2).
A code identifying the BASE24 product. The valid code is 02, BASE24-pos.			
195	[2]	srvcs^2.set^rec1d.rel^num.byte[0:1]	PIC 9(2).
A code identifying the current version of the product.			
197	[4]	srvcs^2.set^rec1d.dpc^num.byte[0:3]	PIC 9(4).
The number of the institution's Data Processing Center (DPC). This is the host computer that processes messages received from BASE24.			
201	[5]	srvcs^2.set^rec1d.term^tim^ofst.byte[0:4]	PIC X(5).
The time difference between the terminal and the			

Offset[Len]	Field Name and Description	Data Type
	Tandem processor location. It is the signed (+ or -) number of minutes to be added to the BASE24 Tandem system time in order to obtain the terminal local time.	
206 [16]	srvcs^2.set^recld.term^id.byte[0:15]	PIC X(16).
	The terminal ID of the terminal on which the settlement occurred.	
222 [71]	srvcs^2.set^recld.ret1	
	The values in the following fields describe the retailer portion of the settlement record.	
222 [11]	srvcs^2.set^recld.ret1.rtn.byte[0:10] [ID-NUM]	PIC 9(11).
	The institution's route and transit number, transit/routing number, or issuer identification number of the terminal owner. The identification data is right-justified with high-order zero fill.	
233 [19]	srvcs^2.set^recld.ret1.acct.byte[0:18]	PIC X(19).
	The account number at the retailer's financial institution for the retailer associated with the settlement record.	
252 [40]	srvcs^2.set^recld.ret1.nam.byte[0:39]	PIC X(40).
	The name of the retailer associated with the settlement record.	
292 [1]	srvcs^2.set^recld.ret1.user^fld1	PIC X(1).
	Reserved for future use.	
293 [1]	srvcs^2.set^recld.set1^typ	PIC 9(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code identifying the type of settlement record being displayed. Valid values are:

- 0 = Batch
- 1 = Shift
- 2 = Daily
- 3 = Network
- 4 = Clerk
- 8 = Services 2 (last 13 services)
- 9 = Services 1 (first 17 services)

294	[1]	srvcs^2.set^recld.bal^flg	PIC 9(1).
-----	-----	---------------------------	-----------

A code identifying the method used to perform the most recent balancing of this terminal. Valid options are:

- 5 = Balanced--Terminal balanced by a close transaction from terminal. Totals sent by terminal agreed with BASE24 totals or terminal did not send any totals. Totals were written to the PTLF and cleared.
- 6 = Balanced (with problems)--Terminal balanced by a close transaction from terminal. Totals sent by terminal did not agree with BASE24 totals and require verification. Totals were written to the PTLF and cleared.
- 8 = Force-balanced (incomplete batch)--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. The terminal was cut over to a new reporting day, and its totals were written to the PTLF, but only current network totals were reset to zero. This method is used when the value in the TERM-CUTOVER-TC field in the PTDF is 0, 1, or 2, and the close transaction has not been received from the terminal within the time window defined by the values in the RETAILER-BAL-AND-CUTVR-START and RETAILER-BAL-AND-CUTVR-END fields in the PRDF.
- 9 = Force-balanced--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 3.
Also set to 9 when the terminal was cut over by the device handler on the first financial transaction after the retailer cutover balance start time as specified in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 4.
In both cases, the terminal was cut over to a new reporting day, its totals were written to the PTLF and all BASE24 totals for the terminal were cleared.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

295	[1]	srvcs^2.set^recld.user^fld2	PIC X(1).
-----	-----	-----------------------------	-----------

Reserved for future use.

296	[6]	srvcs^2.set^recld.tran^dat [DAT]	
-----	-----	-------------------------------------	--

The date (YYMMDD) of the transaction. The value in this field is set by the Device Handler or Settlement.

296	[2]	srvcs^2.set^recld.tran^dat.yy.byte[0:1]	PIC X(2).
-----	-----	---	-----------

298	[2]	srvcs^2.set^recld.tran^dat.mm.byte[0:1]	PIC X(2).
-----	-----	---	-----------

300	[2]	srvcs^2.set^recld.tran^dat.dd.byte[0:1]	PIC X(2).
-----	-----	---	-----------

302	[6]	srvcs^2.set^recld.tran^tim.byte[0:5]	PIC X(6).
-----	-----	--------------------------------------	-----------

The time (HHMMSS) of the transaction. The value in this field is set by the Device Handler or Settlement.

308	[1]	srvcs^2.set^recld.ob^flg	PIC X(1).
-----	-----	--------------------------	-----------

A flag indicating whether this balancing record has an associated balancing record if a terminal is out-of-balance with BASE24-pos. This flag is used if the value in the BAL-FLG field of this record is 5 or 6. Valid codes are:

0 = No associated record exists
1 = Associated record exists

309	[10]	srvcs^2.set^recld.ach^comp^id.byte[0:9]	PIC X(10).
-----	------	---	------------

This field is reserved for Automated Clearinghouse (ACH) information that may be required for processing transactions from this retailer. Information in this field has no impact on BASE24-pos processing.

319	[10]	srvcs^2.set^recld.billing^info.byte[0:9]	PIC X(10).
-----	------	--	------------

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

A free-form informational field used at the discretion of the institution. Typically, this field contains ACH information that BASE24-pos passes on to the host for use by the ACH system. Information in this field has no impact on BASE24-pos processing.

329	[3]	srvcs^2.set^recld.auth^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used for the transactions pertaining to this terminal.

332	[8]	srvcs^2.set^recld.auth^conv^rate.byte[0:7]	PIC X(8).
-----	-----	--	-----------

The exchange rate of the authorizing entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

340	[3]	srvcs^2.set^recld.setl^crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
-----	-----	---	-----------

A code indicating the type of currency used in the settlement of the transaction.

343	[8]	srvcs^2.set^recld.setl^conv^rate.byte[0:7]	PIC X(8).
-----	-----	--	-----------

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are used, the default value is 61000000.

351	[1]	srvcs^2.user^fld11	PIC X(1).
-----	-----	--------------------	-----------

352	[962]	srvcs^2.set^rec4d [SET-REC4D]	
-----	-------	----------------------------------	--

352	[962]	srvcs^2.set^rec4d.srv[0:12]	
-----	-------	-----------------------------	--

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The following fields identify the last 13 services being used.

352	[2]	srvcs^2.set^rec4d.srv[0:12].typ.byte[0:1]	PIC X(2).
-----	-----	---	-----------

A code identifying each of the service types associated with the Second Services record.

One- or two-character codes are used to identify card types in files throughout BASE24. The same codes must be used for a particular card type in all of the files. These codes are also used to identify service types in BASE24-pos. Codes used in this field are either reserved by BASE24 or user-defined. Reserved codes are to be used only as defined, and include:

AD = Administrative (BASE24-atm only)
 AX = American Express credit
 BD = Business deposit (BASE24-atm and BASE24-teller only)
 C* = Private label credit (includes C, C0-C9, CA, and CC-CZ)
 CB = Carte Blanche credit
 D = Demonstration (BASE24-atm only)
 DC = Diners Club credit
 DS = Discover (Sears) credit
 M = MasterCard credit
 MD = MasterCard debit (See BASE24-pos note below)
 MM = MasterCard dual (See BASE24-pos note below)
 P* = Proprietary debit (includes P, P0-P9, and PA-PZ)
 SC = Special, Check (BASE24-pos only)
 SP = Special purpose (BASE24-atm Self-Service Banking Check Application only)
 ST = Super teller (BASE24-atm Self-Service Banking Base Application only)
 V = VISA credit
 VD = VISA debit (See BASE24-pos note below)
 VV = VISA dual (See BASE24-pos note below)

Codes with a first character of C, except code CB, are recommended to identify private label credit cards.

Codes with a first character of P are required to identify proprietary debit cards. BASE24 treats cards with proprietary debit codes and codes MD and VD as debit cards and treats cards with all other codes as credit cards.

Administrative (AD), Business deposit (BD), Demonstration (D), Special purpose (SP), and Super teller (ST) are special-use card types used by

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

BASE24-atm.

Business deposit (BD) is also a special-use card type used by BASE24-teller to identify cards that can only be used to initiate deposit transactions.

BASE24-teller does not perform any other processing based on card type; however, BASE24 guidelines should still be used when establishing card types for BASE24-teller.

MasterCard dual (MM) and VISA dual (VV) can be processed as debit or credit card types, based on the default combo card type specified in the CPF.

Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only.

BASE24-pos NOTE: BASE24-pos does not allow MasterCard debit (MD), MasterCard dual (MM), VISA debit (VD), or VISA dual (VV) card types in the PRDF and PTDF.

BASE24-pos automatically includes the MD and MM card types with the MasterCard credit (M) card type, and automatically includes the VD and VV card types with the VISA credit (V) card type.

User-defined Codes: The user can add any one- or two-character code not included in the reserved code list above, according to the following guidelines:

- o The first character must be alphabetic (A, B, D-O, and Q-Z).
- o The second character can be A-Z, 0-9, or a blank.
- o A valid COBNAMES table entry is recommended for each user-defined code.

354	[5]	srvcs^2.set^rec4d.srv[0:12].db^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The total number of debit transactions for the service during the current batch.

359	[19]	srvcs^2.set^rec4d.srv[0:12].db.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for debit transactions for the service during the current batch.

Offset	[Len]	Field Name and Description	Data Type
--------	-------	----------------------------	-----------

378	[5]	srvcs^2.set^rec4d.srv[0:12].cr^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The total number of credit transactions for the service during the current batch.

383	[19]	srvcs^2.set^rec4d.srv[0:12].cr.byte[0:18]	PIC X(19).
-----	------	---	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for credit transactions for the service during the current batch.

402	[5]	srvcs^2.set^rec4d.srv[0:12].adj^cnt.byte[0:4]	PIC X(5).
-----	-----	---	-----------

The total number of adjustment transactions for the service during the current batch.

407	[19]	srvcs^2.set^rec4d.srv[0:12].adj.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for adjustment transactions for the service during the current batch.

1314	[2]	srvcs^2.user^fld12.byte[0:1]	PIC X(2).
------	-----	------------------------------	-----------

1316	[204]	user^data^d [USER-DATA-D]	
------	-------	--------------------------------	--

1316	[4]	user^data^d.len.byte[0:3]	PIC X(4).
------	-----	---------------------------	-----------

User data information loaded from the PSTM for the transaction. The user data area is used by the originator of the PSTM.

1320	[200]	user^data^d.info.byte[0:199]	PIC X(200).
------	-------	------------------------------	-------------

END [size 1520]

Offset[Len] Field Name and Description Data Type

DEF PTLFX-CLERK-TOT

0 [678]

0 [183] headx [HEADX]

The POS Transaction Log File (PTLF) contains a record of each financial transaction (approved or denied) processed by BASE24-pos for a single processing day. Transactions declined by a Device Handler (for example, bad format), are typically not posted to the PTLF. It also contains settlement records for each POS terminal in the system. This file is an audit record at the transaction level of the system's processing and is extracted daily to provide detailed transaction data for processing by a host.

Records are written to the PTLF sequentially, and two PTLFs are always accessible to the system for logging: the current day's PTLF and the next day's PTLF. Which PTLF a transaction posts to is based on the transaction's PTLF posting date. This is derived from the current business date of the terminal at which the transaction originated. Use of two PTLFs allows BASE24-pos terminals to be cut over at different times. As terminals are cut over, transactions from those terminals begin posting to the next day's PTLF; transactions from terminals that have not been cut over for the day continue to post to the current day's PTLF.

When network settlement occurs, a new PTLF is created and the current day's PTLF is closed to the online system. At that time, the current day's PTLF is available for reporting and extract processing.

LCONF ASSIGN: POS-PTLF

PTLF RECORD STRUCTURE

There are five formats used in writing PTLF records in the ASCII-only format.

- o Financial Transaction (PTLFX)
- o Settlement Totals (PTLFX-SET-REC)
- o Clerk Totals (PTLFX-CLERK-TOT)
- o First Services (PTLFX-SRVCS-1)
- o Second Services (PTLFX-SRVCS-2)

The values contained in the HEADX.REC-TYP and HEADX.TKEY.RKEY.REC-FRMT fields identify the type of information contained in the PTLFX record. The various value combinations and the resulting record format and contents include:

Offset[Len] Field Name and Description Data Type

REC-TYP	REC-FRMT	RECORD FORMAT AND CONTENTS
00	-	Initial
01	5	Financial Transaction--Customer
04	0	Settlement Totals--Batch
04	1	Settlement Totals--Shift
04	2	Settlement Totals--Daily
04	3	Settlement Totals--Network
04	4	Clerk Totals
04	8	Second Services
04	9	First Services
20	5	Financial Transaction--Exception (posted)
21	5	Financial Transaction--Exception (not posted)
22	5	Financial Transaction--Exception (partially posted)
23	5	Financial Transaction--Exception (invalid data)

0 [19] headx.dat^tim.byte[0:18] PIC X(19).

The date and time the record was logged. The value in this field is generated via a call to Tandem's JULIANTIMESTAMP utility.

19 [2] headx.rec^typ.byte[0:1] PIC X(2).

A code indicating the type of record. Authorization sets the value in this field when the record is logged. Valid values are:

00 = Initial record
 01 = Customer transaction
 04 = Administrative transaction
 20 = Exception--posted
 21 = Exception--not posted
 22 = Exception--partially posted
 23 = Exception--invalid data encountered in the
 POS Standard Internal Message (PSTM)

In situations where a transaction cannot be completely processed because of a processing error (e.g., invalid data, unable to locate an authorization record, etc), the Authorization process logs the transaction to the PTLF as an exception. Exception transactions are included as detail items in the BASE24-pos reports but are not included in the BASE24-pos settlement totals.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

```
21      [30]      headx.crd
```

The values in the following fields describe the cardholder and card issuer for the transaction. This is an alternate key used for reporting and perusal purposes.

```

21      [4]      headx.crd.ln.byte[0:3]
                                [LN]                                PIC X(4) .

```

The logical network with which the institution that issued the card is associated.

```

25      [4]      headx.crd.fiid.byte[0:3]
                                [FIID]                                PIC X(4).

```

The FIID of the institution that issued the card.

```
29      [22]      headx.crd.card
```

The values in the following fields identify the card used in the transaction.

```
29      [19]      headx.crd.card.crd^num.byte[0:18]      PIC X(19).
```

The card number identifying the card used in the transaction.

```

48      [3]      headx.crd.card.mbr^num.byte[0:2]
                                [MBR-NUM]                                PIC 9(3).

```

The member number associated with the card used in the transaction.

```
51      [57]      headx.ret1
```

The values in the following fields describe the retailer involved in the transaction. The values in these fields are used for reporting purposes.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

51	[35]	headx.ret1.ky	
----	------	---------------	--

51	[4]	headx.ret1.ky.ln.byte[0:3] [LN]	PIC X(4).
----	-----	------------------------------------	-----------

The logical network with which the retailer is associated.

55	[31]	headx.ret1.ky.rdfkey	
----	------	----------------------	--

The values in the following fields compose the key to the retailer's POS Retailer Definition File (PRDF) record.

55	[4]	headx.ret1.ky.rdfkey.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	---	-----------

The FIID of the institution with which the retailer is associated.

59	[4]	headx.ret1.ky.rdfkey.grp.byte[0:3]	PIC X(4).
----	-----	------------------------------------	-----------

The group to which the retailer belongs.

63	[4]	headx.ret1.ky.rdfkey.regn.byte[0:3] [REGN]	PIC X(4).
----	-----	---	-----------

The retailer region group to which the retailer belongs.

67	[19]	headx.ret1.ky.rdfkey.id.byte[0:18]	PIC X(19).
----	------	------------------------------------	------------

The retailer ID identifying the retailer.

86	[16]	headx.ret1.term^id.byte[0:15]	PIC X(16).
----	------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

102	[3]	headx.ret1.shift^num.byte[0:2]	PIC X(3).
-----	-----	--------------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

136 [2]	headx.term.tim.ss.byte[0:1]	PIC X(2).
------------	-----------------------------	-----------

138 [2]	headx.term.tim.tt.byte[0:1]	PIC X(2).
------------	-----------------------------	-----------

140 [42]	headx.tkey	
-------------	------------	--

The following fields identify the terminal, retailer, and clerk associated with the transaction. These fields are used as an alternate key to peruse transactions by terminal, retailer, and clerk.

140 [16]	headx.tkey.term^id.byte[0:15]	PIC X(16).
-------------	-------------------------------	------------

The terminal ID of the terminal at which the transaction occurred.

156 [26]	headx.tkey.rkey	
-------------	-----------------	--

156 [1]	headx.tkey.rkey.rec^frmt	PIC X(1).
------------	--------------------------	-----------

A code indicating the type of information in this record. Valid values are:

0 = Batch Totals
1 = Shift Totals
2 = Day Totals
3 = Network Totals
4 = Clerk Totals
5 = Data Record
8 = Services Totals
9 = Services Totals

157 [19]	headx.tkey.rkey.retailer^id.byte[0:18]	PIC X(19).
-------------	--	------------

The retailer ID identifying the retailer.

176 [6]	headx.tkey.rkey.clerk^id.byte[0:5]	PIC X(6).
------------	------------------------------------	-----------

The clerk identification number.

182 [1]	headx.data^flag	PIC X(1).
------------	-----------------	-----------

Indicates whether the user-data field is appended to the PTLF record. Valid values are:

Offset[Len] Field Name and Description Data Type

0 = No user-data appended
 1 = User-data appended

183 [291] clerk^tot

183 [168] clerk^tot.set^rec1d
[SET-REC1D]

183 [4] clerk^tot.set^rec1d.typ.byte[0:3] PIC 9(4).

A code indicating the type of PTLF record. The valid code is 0500, reconciliation record.

187 [6] clerk^tot.set^rec1d.post^dat
[DAT]

The posting date (YYMMDD) for the settlement record.

187 [2] clerk^tot.set^rec1d.post^dat.yy.byte[0:1] PIC X(2).

189 [2] clerk^tot.set^rec1d.post^dat.mm.byte[0:1] PIC X(2).

191 [2] clerk^tot.set^rec1d.post^dat.dd.byte[0:1] PIC X(2).

193 [2] clerk^tot.set^rec1d.prod^id.byte[0:1] PIC 9(2).

A code identifying the BASE24 product. The valid code is 02, BASE24-pos.

195 [2] clerk^tot.set^rec1d.rel^num.byte[0:1] PIC 9(2).

A code identifying the current version of the product.

197 [4] clerk^tot.set^rec1d.dpc^num.byte[0:3] PIC 9(4).

The number of the institution's Data Processing Center (DPC). This is the host computer that processes messages received from BASE24.

201 [5] clerk^tot.set^rec1d.term^tim^ofst.byte[0:4] PIC X(5).

The time difference between the terminal and the

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

Tandem processor location. It is the signed (+ or -) number of minutes to be added to the BASE24 Tandem system time in order to obtain the terminal local time.

206	[16]	clerk^tot.set^recld.term^id.byte[0:15]	PIC X(16).
-----	------	--	------------

The terminal ID of the terminal on which the settlement occurred.

222	[71]	clerk^tot.set^recld.ret1	
-----	------	--------------------------	--

The values in the following fields describe the retailer portion of the settlement record.

222	[11]	clerk^tot.set^recld.ret1.rtn.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

The institution's route and transit number, transit/routing number, or issuer identification number of the terminal owner. The identification data is right-justified with high-order zero fill.

233	[19]	clerk^tot.set^recld.ret1.acct.byte[0:18]	PIC X(19).
-----	------	--	------------

The account number at the retailer's financial institution for the retailer associated with the settlement record.

252	[40]	clerk^tot.set^recld.ret1.nam.byte[0:39]	PIC X(40).
-----	------	---	------------

The name of the retailer associated with the settlement record.

292	[1]	clerk^tot.set^recld.ret1.user^fld1	PIC X(1).
-----	-----	------------------------------------	-----------

Reserved for future use.

293	[1]	clerk^tot.set^recld.set1^typ	PIC 9(1).
-----	-----	------------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code identifying the type of settlement record being displayed. Valid values are:

- 0 = Batch
- 1 = Shift
- 2 = Daily
- 3 = Network
- 4 = Clerk
- 8 = Services 2 (last 13 services)
- 9 = Services 1 (first 17 services)

294	[1]	clerk^tot.set^recld.bal^flg	PIC 9(1).
-----	-----	-----------------------------	-----------

A code identifying the method used to perform the most recent balancing of this terminal. Valid options are:

- 5 = Balanced--Terminal balanced by a close transaction from terminal. Totals sent by terminal agreed with BASE24 totals or terminal did not send any totals. Totals were written to the PTLF and cleared.
- 6 = Balanced (with problems)--Terminal balanced by a close transaction from terminal. Totals sent by terminal did not agree with BASE24 totals and require verification. Totals were written to the PTLF and cleared.
- 8 = Force-balanced (incomplete batch)--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. The terminal was cut over to a new reporting day, and its totals were written to the PTLF, but only current network totals were reset to zero. This method is used when the value in the TERM-CUTOVER-TC field in the PTDF is 0, 1, or 2, and the close transaction has not been received from the terminal within the time window defined by the values in the RETAILER-BAL-AND-CUTVR-START and RETAILER-BAL-AND-CUTVR-END fields in the PRDF.
- 9 = Force-balanced--Terminal was cut over by Settlement Initiator at the time specified in the RETAILER-BAL-AND-CUTVR-END field in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 3.
Also set to 9 when the terminal was cut over by the device handler on the first financial transaction after the retailer cutover balance start time as specified in the PRDF. This method is used when the value of the TERM-CUTOVER-TC field in the PTDF equals 4.
In both cases, the terminal was cut over to a new reporting day, its totals were written to the PTLF and all BASE24 totals for the terminal were cleared.

Offset[Len] Field Name and Description Data Type

295 [1] clerk^tot.set^recld.user^fld2 PIC X(1).

Reserved for future use.

296 [6] clerk^tot.set^recld.tran^dat
[DAT]

The date (YYMMDD) of the transaction. The value in this field is set by the Device Handler or Settlement.

296 [2] clerk^tot.set^recld.tran^dat.yy.byte[0:1] PIC X(2).

298 [2] clerk^tot.set^recld.tran^dat.mm.byte[0:1] PIC X(2).

300 [2] clerk^tot.set^recld.tran^dat.dd.byte[0:1] PIC X(2).

302 [6] clerk^tot.set^recld.tran^tim.byte[0:5] PIC X(6).

The time (HHMMSS) of the transaction. The value in this field is set by the Device Handler or Settlement.

308 [1] clerk^tot.set^recld.ob^flg PIC X(1).

A flag indicating whether this balancing record has an associated balancing record if a terminal is out-of-balance with BASE24-pos. This flag is used if the value in the BAL-FLG field of this record is 5 or 6. Valid codes are:

0 = No associated record exists
1 = Associated record exists

309 [10] clerk^tot.set^recld.ach^comp^id.byte[0:9] PIC X(10).

This field is reserved for Automated Clearinghouse (ACH) information that may be required for processing transactions from this retailer. Information in this field has no impact on BASE24-pos processing.

319 [10] clerk^tot.set^recld.billing^info.byte[0:9] PIC X(10).

Offset[Len] Field Name and Description Data Type

A free-form informational field used at the discretion of the institution. Typically, this field contains ACH information that BASE24-pos passes on to the host for use by the ACH system. Information in this field has no impact on BASE24-pos processing.

329 [3] clerk^tot.set^recld.auth^crncy^cde.byte[0:2]
[CRNCY-CDE] PIC 9(3).

A code indicating the type of currency used for the transactions pertaining to this terminal.

332 [8] clerk^tot.set^recld.auth^conv^rate.byte[0:7] PIC X(8).

The exchange rate of the authorizing entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are involved, the default value is 61000000.

340 [3] clerk^tot.set^recld.set1^crncy^cde.byte[0:2]
[CRNCY-CDE] PIC 9(3).

A code indicating the type of currency used in the settlement of the transaction.

343 [8] clerk^tot.set^recld.set1^conv^rate.byte[0:7] PIC X(8).

The exchange rate of the settlement entity. The value in this field is used to compute the final settlement amount. The first digit contains the offset of the decimal point from the right-hand side. Unless multiple currencies are used, the default value is 61000000.

351 [1] clerk^tot.user^fld13 PIC X(1).

352 [120] clerk^tot.set^rec5d
[SET-REC5D]

352 [5] clerk^tot.set^rec5d.db^cnt.byte[0:4] PIC X(5).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The total number of debit transactions occurring under the operator's logon since the last batch close transaction.

357	[19]	clerk^tot.set^rec5d.db^amt.byte[0:18]	PIC X(19).
-----	------	---------------------------------------	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for debit transactions occurring under the operator's logon since the last batch close transaction.

376	[5]	clerk^tot.set^rec5d.cr^cnt.byte[0:4]	PIC X(5).
-----	-----	--------------------------------------	-----------

The total number of credit transactions occurring under the operator's logon since the last batch close transaction.

381	[19]	clerk^tot.set^rec5d.cr^amt.byte[0:18]	PIC X(19).
-----	------	---------------------------------------	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for credit transactions occurring under the operator's logon since the last batch close transaction.

400	[5]	clerk^tot.set^rec5d.adj^cnt.byte[0:4]	PIC X(5).
-----	-----	---------------------------------------	-----------

The total number of adjustment transactions occurring under the operator's logon since the last batch close transaction.

405	[19]	clerk^tot.set^rec5d.adj^amt.byte[0:18]	PIC X(19).
-----	------	--	------------

The total amount, in whole and fractional currency units (e.g., dollars and cents), for adjustment transactions occurring under the operator's logon since the last batch close transaction.

424	[5]	clerk^tot.set^rec5d.cash^cnt.byte[0:4]	PIC X(5).
-----	-----	--	-----------

The total number of cash back transactions occurring under the operator's logon since the last

Offset[Len] Field Name and Description Data Type

batch close transaction.

429 [19] clerk^tot.set^rec5d.cash^amt.byte[0:18] PIC X(19).

The total amount, in whole and fractional currency units (e.g., dollars and cents), for cash back transactions occurring under the operator's logon since the last batch close transaction.

448 [5] clerk^tot.set^rec5d.chk^cnt.byte[0:4] PIC X(5).

The total number of check transactions occurring under the operator's logon since the last batch close transaction.

453 [19] clerk^tot.set^rec5d.chk^amt.byte[0:18] PIC X(19).

The total amount, in whole and fractional currency units (e.g., dollars and cents), for check transactions occurring under the operator's logon since the last batch close transaction.

472 [2] clerk^tot.user^fld14.byte[0:1] PIC X(2).

474 [204] user^data^d [USER-DATA-D]

474 [4] user^data^d.len.byte[0:3] PIC X(4).

User data information loaded from the PSTM for the transaction. The user data area is used by the originator of the PSTM.

478 [200] user^data^d.info.byte[0:199] PIC X(200).

END [size 678]