

Offset[Len] Field Name and Description Data Type

DEF TTLFX

0 [652]

0 [120] head

0 [19] head.dat^tim.byte[0:18] PIC X(19).

The JULIANTIMESTAMP of when the record was written to the TTLF.

19 [2] head.rec^typ.byte[0:1] PIC X(2).

A code indicating the general type of the record.
Valid values are:

01 = Financial Transaction
02 = File Inquiry/Update Transaction
03 = Reserved for Future Use
04 = Administrative Transaction
Reflects the information from the logon/logoff and sign on/sign off transactions.

21 [4] head.auth^ppd.byte[0:3] PIC X(4).

The Authorization or Device Handler process that added the record to the TTLF by its PPD name. The \$ sign is not included. It is anticipated that this field will be used by various Performance Tools to be developed for BASE24-teller.

25 [30] head.tlr

The following fields contain the header data of each transaction written to the TTLF using keytag TR.

25 [4] head.tlr.ln.byte[0:3]
[LN] PIC X(4).

The logical network of the financial institution whose terminal initiated the transaction.

29 [4] head.tlr.fiid.byte[0:3]
[FIID] PIC X(4).

The FIID of the financial institution whose terminal initiated the transaction.

33 [8] head.tlr.tlr^id.byte[0:7] PIC X(8).

The teller identification information used to determine which teller unit initiated the transaction.

Offset[Len]	Field Name and Description	Data Type
41 [6]	head.tlr.tran^dat [DAT] The date (YYMMDD) the transaction occurred.	
41 [2]	head.tlr.tran^dat.yy.byte[0:1]	PIC X(2).
43 [2]	head.tlr.tran^dat.mm.byte[0:1]	PIC X(2).
45 [2]	head.tlr.tran^dat.dd.byte[0:1]	PIC X(2).
47 [8]	head.tlr.tran^tim [TIM] The time (HHMMSSTT) the transaction occurred.	
47 [2]	head.tlr.tran^tim.hh.byte[0:1]	PIC X(2).
49 [2]	head.tlr.tran^tim.mm.byte[0:1]	PIC X(2).
51 [2]	head.tlr.tran^tim.ss.byte[0:1]	PIC X(2).
53 [2]	head.tlr.tran^tim.tt.byte[0:1]	PIC X(2).
25 [30]	head.tlr^r [REDEFINES TLR]	
25 [16]	head.tlr^r.fi^tlr	
25 [4]	head.tlr^r.fi^tlr.ln.byte[0:3] [LN]	PIC X(4).
29 [4]	head.tlr^r.fi^tlr.fiid.byte[0:3] [FIID]	PIC X(4).
33 [8]	head.tlr^r.fi^tlr.tlr^id.byte[0:7]	PIC X(8).
41 [6]	head.tlr^r.tran^dat [DAT]	
41 [2]	head.tlr^r.tran^dat.yy.byte[0:1]	PIC X(2).
43 [2]	head.tlr^r.tran^dat.mm.byte[0:1]	PIC X(2).
45 [2]	head.tlr^r.tran^dat.dd.byte[0:1]	PIC X(2).
47 [8]	head.tlr^r.tran^tim [TIM]	
47 [2]	head.tlr^r.tran^tim.hh.byte[0:1]	PIC X(2).
49 [2]	head.tlr^r.tran^tim.mm.byte[0:1]	PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

51	[2]	head.tlr^r.tran^tim.ss.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

53	[2]	head.tlr^r.tran^tim.tt.byte[0:1]	PIC X(2).
----	-----	----------------------------------	-----------

55	[33]	head.acct	
----	------	-----------	--

The following fields contain the header data of each transaction written to the TTLF using keytag AC.

55	[4]	head.acct.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--------------------------------	-----------

The logical network of the account owner.

59	[4]	head.acct.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	------------------------------------	-----------

The FIID of the account owner.

63	[19]	head.acct.acct^num.byte[0:18]	PIC X(19).
----	------	-------------------------------	------------

The application account number involved in the transaction.

82	[6]	head.acct.tran^typ^cde.byte[0:5]	PIC X(6).
----	-----	----------------------------------	-----------

The transaction code of the transaction. This field contains the original transaction code. This code is not modified as a result of account type ranges.

55	[33]	head.acct^r [REDEFINES ACCT]	
----	------	---------------------------------	--

55	[27]	head.acct^r.fi^acct	
----	------	---------------------	--

55	[4]	head.acct^r.fi^acct.ln.byte[0:3] [LN]	PIC X(4).
----	-----	--	-----------

59	[4]	head.acct^r.fi^acct.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	--	-----------

63	[19]	head.acct^r.fi^acct.acct^num.byte[0:18]	PIC X(19).
----	------	---	------------

82	[6]	head.acct^r.tran^typ^cde.byte[0:5]	PIC X(6).
----	-----	------------------------------------	-----------

88	[30]	head.crd	
----	------	----------	--

The following fields contain the header data of each transaction written to the TTLF using the keytag CR.

Offset[Len]	Field Name and Description	Data Type
88 [4]	head.crd.ln.byte[0:3] [LN] The logical network of the card owner.	PIC X(4).
92 [4]	head.crd.fiid.byte[0:3] [FIID] The FIID of the card owner.	PIC X(4).
96 [19]	head.crd.pan.byte[0:18] The card number (PAN) involved in the transaction.	PIC X(19).
115 [3]	head.crd.mbr^num.byte[0:2] [MBR-NUM] The member number. Right-justified and zero-filled on the left.	PIC 9(3).
88 [30]	head.crd^r [REDEFINES CRD]	
88 [30]	head.crd^r.fi^crd	
88 [4]	head.crd^r.fi^crd.ln.byte[0:3] [LN]	PIC X(4).
92 [4]	head.crd^r.fi^crd.fiid.byte[0:3] [FIID]	PIC X(4).
96 [19]	head.crd^r.fi^crd.crd^num.byte[0:18]	PIC X(19).
115 [3]	head.crd^r.fi^crd.mbr^num.byte[0:2] [MBR-NUM]	PIC 9(3).
118 [2]	head.user^fld1.byte[0:1] Reserved for future use.	PIC X(2).
120 [157]	refr^hdr	
120 [1]	refr^hdr.impact^ind A code indicating whether the record should be considered when impacting a new refreshed set of account records. Valid values are: 0 = No, do not use the record for impacting. 1 = Yes, use the record for impacting.	PIC X(1).
121 [1]	refr^hdr.user^fld3 Reserved for future use.	PIC X(1).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

122	[2]	refr^hdr.amt^on^hld^ind[0:1]	PIC X(1).
-----	-----	------------------------------	-----------

These fields indicate how the AMT-ON-HLD field in the Base segment of the PBF should be impacted. The amount on hold is impacted by the amount specified in REFR-HDR.AMT-ON-HLD. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction. Valid values are:

I = Increment
 D = Decrement
 _ = Not Impacted (_ denotes a blank)

124	[38]	refr^hdr.amt^on^hld[0:1]	PIC X(19).
-----	------	--------------------------	------------

These fields contain the amount to be added to or subtracted from the AMT-ON-HLD field in the Base segment of the PBF. These fields are initialized for all types of transactions. The amount on hold is the total amount of account funds being held and not available to the customer. An example of held funds would be a deposit at the teller line consisting of checks. Although the funds might be credited to the current account balance, the customer could not make use of them until they were verified or cleared. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction.

162	[2]	refr^hdr.avail^bal^ind[0:1]	PIC X(1).
-----	-----	-----------------------------	-----------

These fields indicate how the AVAIL-BAL field in the Base segment of the PBF should be impacted. These fields are initialized for all types of transactions. The available balance is impacted by the amount specified in REFR-HDR.AVAIL-BAL-AMT. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction. Valid values are:

I = Increment
 D = Decrement
 _ = Not Impacted (_ denotes a blank)

164	[38]	refr^hdr.avail^bal^amt[0:1]	PIC X(19).
-----	------	-----------------------------	------------

These fields contain the amount to be added to or subtracted from the AVAIL-BAL field in the Base

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

segment of the PBF. These fields are initialized for all types of transactions. On approved "debit" type transactions, this amount is subtracted from the available balance. On approved "credit" type transactions, this amount is added to the available balance. On approved "debit" reversal transactions, this amount is added to the available balance. On approved "credit" reversal transactions, this amount is subtracted from the available balance. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction.

202	[2]	refr^hdr.amt^dep^cr^ind[0:1]	PIC X(1).
-----	-----	------------------------------	-----------

These fields indicate how the AMT-DEP-CR field in the Teller segment of the PBF should be impacted. These fields are initialized for all types of transactions. The amount of deposit credit is impacted by the amount specified in REFR-HDR.AMT-DEP-CR. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction. Valid values are:

I = Increment
 D = Decrement
 _ = Not Impacted (_ denotes a blank)

204	[38]	refr^hdr.amt^dep^cr[0:1]	PIC X(19).
-----	------	--------------------------	------------

These fields contain the amount to be added to or subtracted from the AMT-DEP-CR in the Teller segment of the PBF. These fields are initialized for all transactions. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction.

242	[2]	refr^hdr.ledg^cr^bal^ind[0:1]	PIC X(1).
-----	-----	-------------------------------	-----------

These fields indicate how the LEDGER-BAL and CR-BAL fields in the Base segment of the PBF should be impacted. The balances are impacted by the transaction amount(s) specified in the Financial Token. The amount fields actually used will depend on the type of transaction. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

involved in the transaction. Valid values are:

I = Increment

D = Decrement

_ = Not Impacted (_ denotes a blank)

244	[2]	refr^hdr.cash^out^ind[0:1]	PIC X(1).
-----	-----	----------------------------	-----------

These fields indicate how the CASH-OUT-TODAY fields in the Base segment of the PBF should be impacted. Cash out today is impacted by the cash out amount specified in the Financial Token. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction. Valid values are:

I = Increment

D = Decrement

_ = Not Impacted (_ denotes a blank)

246	[2]	refr^hdr.cash^in^ind[0:1]	PIC X(1).
-----	-----	---------------------------	-----------

These fields indicate how the CASH-IN-TODAY fields in the Base segment of the PBF should be impacted. Cash in today is impacted by the cash in amount specified in the Financial Token. The first occurrence of this field applies to the "from" or first account involved in the transaction. The second occurrence of this field applies to the "to" or second account involved in the transaction. Valid values are:

I = Increment

D = Decrement

_ = Not Impacted (_ denotes a blank)

248	[19]	refr^hdr.tran^amt.byte[0:18]	PIC X(19).
-----	------	------------------------------	------------

The amount of the transaction. This field has been defined in the refresh header so it would not be necessary to parse for the Financial Token in order to display the transaction amount on the TTLF Perusal Summary Screen. This field is also used by BASE24-teller Report Programs.

267	[1]	refr^hdr.spf^refr^ind	PIC X(1).
-----	-----	-----------------------	-----------

A code indicating that the SPF has been impacted for Refresh.

268	[1]	refr^hdr.nbf^refr^ind	PIC X(1).
-----	-----	-----------------------	-----------

A code indicating that the NBF has been impacted for Refresh.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

269 [1]	refr^hdr.whff^refr^ind	PIC X(1).
---------	------------------------	-----------

A code indicating that the WHFF has been impacted for Refresh.

270 [1]	refr^hdr.dda^refr^ind	PIC X(1).
---------	-----------------------	-----------

A code indicating that the PBF for the DDA account has been impacted for Refresh.

271 [1]	refr^hdr.sav^refr^ind	PIC X(1).
---------	-----------------------	-----------

A code indicating that the PBF for the savings account has been impacted for Refresh.

272 [1]	refr^hdr.ccd^refr^ind	PIC X(1).
---------	-----------------------	-----------

A code indicating that the PBF for the credit card account has been impacted for Refresh.

273 [2]	refr^hdr.from^acct^passbook^ind[0:1]	PIC X(1).
---------	--------------------------------------	-----------

A flag indicating whether a record was added to, or deleted from the NBF. This field is only used if the from/first account is a passbook account. The first occurrence of this field is associated with the Financial Transaction being performed (e.g., Withdrawal from Savings, Deposit to Savings, etc.). The second occurrence is used if the from account is a passbook account and a credit line/backup account was accessed to authorize the transaction. For example, if a credit line/backup account is accessed to authorize a Withdrawal from Savings Transaction, the second occurrence of this field indicates whether a record was added to the NBF to reflect the transfer of funds from the credit line/backup account to the from account. Valid values are:

I = The from account was a passbook account, and the NBF record count was Incremented
 D = The from account was a passbook account, and the NBF record count was Decrementated
 _ = The from account was not a passbook account, and the NBF record count was not changed
 (_ denotes a blank)

275 [1]	refr^hdr.to^acct^passbook^ind	PIC X(1).
---------	-------------------------------	-----------

A flag indicating whether a record was added to, or deleted from the NBF. This field is only used if the to/second account is a passbook account. Valid values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

I	= The to account was a passbook account, and the NBF record count was Incremented	
D	= The to account was a passbook account, and the NBF record count was Decrementated	
_	= The to account was not a passbook account, and the NBF record count was not changed (_ denotes a blank)	

276	[1]	refr^hdr.cr^line^acct^passbook^ind	PIC X(1).
-----	-----	------------------------------------	-----------

A flag indicating whether a record was added to, or deleted from the NBF. This field is only used if the credit line/backup account is a passbook account. Valid values are:

I	= The credit line/backup account was a passbook account, and the NBF record count was Incremented
D	= The credit line/backup account was a passbook account, and the NBF record count was Decrementated
_	= The credit line/backup account was not a passbook account, and the NBF record count was not changed (_ denotes a blank)

277	[375]	tstmh^data
-----	-------	------------

The TSTMH portion of the TTLF record. This portion of the record contains transaction message data.

277	[42]	tstmh^data.sys
-----	------	----------------

277	[4]	tstmh^data.sys.msg^typ.byte[0:3]	PIC 9(4).
-----	-----	----------------------------------	-----------

The type of message. The following message types are supported:

0210	= Financial Transaction Response
0220	= Financial Transaction Advice
0230	= Financial Transaction Advice Response
0420	= Financial Transaction Reversal Advice
0430	= Financial Transaction Reversal Response
0310	= File Update Response
0320	= File Update Advice
0330	= File Update Advice Response
0610	= Administrative Response
0620	= Administrative Advice
0630	= Administrative Advice Response

281	[1]	tstmh^data.sys.originator	PIC X(1).
-----	-----	---------------------------	-----------

A code indicating where the transaction request, reversal or advice originated. Applicable to 0200, 0300, 0600, 0220, 0320, 0420 and 0620 messages. Valid values are:

Offset[Len]	Field Name and Description	Data Type
	1 = Device controlled by BASE24 2 = Device Handler 3 = Authorization Process 4 = Host Interface Process 5 = Host	
282 [1]	tstmh^data.sys.responder	PIC X(1).
	A code indicating where the transaction response was generated. Applicable to 0210, 0310, 0610, 0230, 0330, 0430 and 0630 messages. Valid values are: 1 = Device controlled by BASE24 2 = Device Handler 3 = Authorization Process 4 = Host Interface Process 5 = Host	
283 [18]	tstmh^data.sys.orig	
	The following fields contain the transaction origination data.	
283 [16]	tstmh^data.sys.orig.sta^name.byte[0:15] [SYM-NAME]	PIC X(16).
	The name of the station originating the message. This field represents the terminal id.	
299 [2]	tstmh^data.sys.orig.rte^stat.byte[0:1]	PIC 9(2).
	The status of a message at the system level. If the value is "00", the response code field indicates the disposition of the message. This field is set by the Host Interface and used by the Authorization process. This field is reserved for the future development of online/offline processing.	
301 [6]	tstmh^data.sys.tran^seq^num.byte[0:5]	PIC X(6).
	The sequence number of the transaction, typically generated by the BASE24-teller Device Handler.	
307 [6]	tstmh^data.sys.dev^seq^num.byte[0:5]	PIC 9(6).
	The sequence number supplied by the device and printed on the receipt.	
313 [6]	tstmh^data.sys.trace^num.byte[0:5]	PIC 9(6).
	The network trace number of the transaction.	
319 [94]	tstmh^data.bnk	

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The following fields contain the institution and teller terminal identification data.

319	[4]	tstmh^data.bnk.regn^id.byte[0:3] [REGN]	PIC X(4).
-----	-----	--	-----------

The region ID associated with the terminal.

323	[4]	tstmh^data.bnk.brch^id.byte[0:3] [BRCH]	PIC X(4).
-----	-----	--	-----------

The branch ID associated with the terminal.

327	[25]	tstmh^data.bnk.term^loc.byte[0:24]	PIC X(25).
-----	------	------------------------------------	------------

The address or location description of the terminal where the transation was initiated.

352	[13]	tstmh^data.bnk.term^city.byte[0:12]	PIC X(13).
-----	------	-------------------------------------	------------

The city of the terminal where the transaction was initiated.

365	[3]	tstmh^data.bnk.term^st.byte[0:2]	PIC X(3).
-----	-----	----------------------------------	-----------

The state, province, or political division of the terminal where the transaction was initiated. In the United States, only the first two characters are used to identify the state where the terminal is located. Codes for other countries must be agreed upon by all sharing institutions.

368	[2]	tstmh^data.bnk.term^cntry.byte[0:1]	PIC X(2).
-----	-----	-------------------------------------	-----------

The country of the terminal where the transaction was initiated. Valid values are listed in the Codes for the Representation of Names of Countries, ISO 3166-1988.

370	[11]	tstmh^data.bnk.acq^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

The institution id number of the terminal owner if the terminal is directly connected to BASE24-teller. Otherwise, the id number of the acquiring entity introducing the transaction into BASE24. Data is right-justified and zero-filled on the left.

381	[11]	tstmh^data.bnk.rcv^inst^id^num.byte[0:10] [ID-NUM]	PIC 9(11).
-----	------	---	------------

The institution id number of the account owner or card issuer. Data is right-justified and zero-filled

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

on the left.

392	[1]	tstmh^data.bnk.dda^cur^flg	PIC X(1).
-----	-----	----------------------------	-----------

A code specifying if the PBF for DDA accounts is current
Valid values are:

Y = Yes, the file is current.
N = No, the file is not current.

393	[1]	tstmh^data.bnk.sav^cur^flg	PIC X(1).
-----	-----	----------------------------	-----------

A code specifying if the PBF for savings accounts is current. Valid values are:

Y = Yes, the file is current.
N = No, the file is not current.

394	[1]	tstmh^data.bnk.ccd^cur^flg	PIC X(1).
-----	-----	----------------------------	-----------

A code specifying if the PBF for credit accounts is current. Valid values are:

Y = Yes, the file is current.
N = No, the file is not current.

395	[1]	tstmh^data.bnk.spf^cur^flg	PIC X(1).
-----	-----	----------------------------	-----------

A code specifying if the SPF and PBF are current. Valid values are:

Y = Yes, the files are current.
N = No, the files are not current.

396	[1]	tstmh^data.bnk.nbf^cur^flg	PIC X(1).
-----	-----	----------------------------	-----------

A code specifying if the NBF and PBF are current.
Valid values are:

Y = Yes, the files are current.
N = No, the files are not current.

397	[1]	tstmh^data.bnk.whff^cur^flg	PIC X(1).
-----	-----	-----------------------------	-----------

A code specifying if the WHFF and PBF are current.
Valid values are:

Y = Yes, the files are current.
N = No, the files are not current.

398	[11]	tstmh^data.bnk.bnk^rtg^cde.byte[0:10]	PIC X(11).
-----	------	---------------------------------------	------------

The bank routing code that may be entered by the teller order to identify the institution that owns the account.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

If entered, this routing code is used to locate the appropriate information from the Account Routing File (ARF). The bank routing code is right-justified and zero-filled.

409	[1]	tstmh^data.bnk.bnk^relnshp	PIC X(1).
-----	-----	----------------------------	-----------

The banking relationship defined for the terminal owner and account owner.

410	[3]	tstmh^data.bnk.crncy^cde.byte[0:2]	PIC 9(3).
-----	-----	------------------------------------	-----------

The type of currency used for the transaction.

413	[131]	tstmh^data.rqst	
-----	-------	-----------------	--

The following fields contain the transaction-specific processing data.

413	[6]	tstmh^data.rqst.dev^tran^cde.byte[0:5]	PIC X(6).
-----	-----	--	-----------

The device transaction code from the device native message. The contents of this field varies for each device type and transaction code.

419	[19]	tstmh^data.rqst.cust^passbook^bal.byte[0:18]	PIC X(19).
-----	------	--	------------

The customer's passbook balance entered by the teller and used for passbook printing.

438	[1]	tstmh^data.rqst.auth^lvl	PIC X(1).
-----	-----	--------------------------	-----------

A code indicating the authorizer of the transaction from the perspective of the account owner. Valid values are:

- 0 = Transaction Not Supported
- 1 = Online Authorization, Host Authorizes
- 2 = Offline Authorization, BASE24 Authorizes
- 3 = Reserved for future use
- 4 = Log Only, BASE24-teller Authorization Process logs transaction to the TTLF

The Positive Balance File (PBF) on BASE24 is only updated for transactions with an AUTH-LVL value of 2 (Offline Authorization).

439	[40]	tstmh^data.rqst.track2.byte[0:39]	PIC X(40).
-----	------	-----------------------------------	------------

The Track 2 Data as received from the teller device. The data may be read electronically or entered manually. The data is in the following general format:

1) start sentinel (;)

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

- 2) PAN, left justified
- 3) a field separator (=)
- 4) expiration date (MMYY or YYMM)
- 5) discretionary data
- 6) end sentinel (?)

If the data is manually entered, the device handler replaces the start sentinel with a value of M.

479	[19]	tstmh^data.rqst.from^acct [ACCT]	
		The from account number or the account number associated with the first account type. If the from account number is not applicable or not available, this field is initialized to blanks.	
479	[19]	tstmh^data.rqst.from^acct.acct^num.byte[0:18]	PIC X(19).
498	[19]	tstmh^data.rqst.to^acct [ACCT]	
		The to account number or the account number associated with the second account type. If the to account number not applicable or not available, this field is initialized to blanks.	
498	[19]	tstmh^data.rqst.to^acct.acct^num.byte[0:18]	PIC X(19).
517	[6]	tstmh^data.rqst.tran	
		The values in the following fields identify the type of transaction and from and to account types. Refer to the DDL source file for the BASE24-teller Standard Internal Message Header (TSTMH) or the Teller Transaction File (TTF) for a complete list of the transaction codes and account types supported by BASE24-teller.	
517	[2]	tstmh^data.rqst.tran.cde.byte[0:1]	PIC X(2).
519	[2]	tstmh^data.rqst.tran.from^acct^typ.byte[0:1] [ACCT-TYP]	PIC X(2).
		The from account type of the transaction.	
521	[2]	tstmh^data.rqst.tran.to^acct^typ.byte[0:1] [ACCT-TYP]	PIC X(2).
		The to account type of the transaction.	
523	[1]	tstmh^data.rqst.intl^ovrrd^lvl	PIC X(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code indicating the initial override level used to process the transaction. Valid values are:

- 0 = No override level--The transaction was processed without a particular override level.
- 1 = Teller override level--The transaction was processed with an override level of a teller.
- 2 = Supervisor override level--The transaction was processed with an override level of a supervisor.
- 3 = Manager override level--The transaction was processed with an override level of a manager.

524	[1]	tstmh^data.rqst.max^term^ovrrd^lvl	PIC X(1).
-----	-----	------------------------------------	-----------

A code indicating the maximum override level that a particular terminal can handle. For example, if the terminal has the capability of processing teller overrides (level "1") and supervisor overrides (level "2"), then this field should be set to a "2". Valid values are:

- 1 = Teller level. The terminal has the capability of processing teller overrides.
- 2 = Supervisor level. This terminal has the capability of processing teller and supervisor overrides.
- 3 = Manager level. This terminal has the capability of processing teller, supervisor, and manager overrides.

525	[1]	tstmh^data.rqst.paperless^tran	PIC X(1).
-----	-----	--------------------------------	-----------

A code indicating whether the transaction is paperless or should be processed using a paper source document. The value in this field is not used by BASE24-teller, but is provided to assist the host software. Valid values are:

- Y = Yes, the transaction is paperless and should be posted to host files from the TTLFX.
- N = No, the transaction is not paperless. It should be posted to host files from a paper source document instead of the TTLFX.

526	[1]	tstmh^data.rqst.compl^req	PIC X(1).
-----	-----	---------------------------	-----------

A code specifying whether BASE24 should send completion messages to the host for transactions. Valid values are:

- N = No, do not send completion messages to the host.
- A = Yes, send completion messages to the host for approved transactions only.
- D = Yes, send completion messages to the host for

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

denied transactions only.

B = Yes, send completion messages to the host for approved and denied transactions.

527	[1]	tstmh^data.rqst.advc^resp^req	PIC X(1).
-----	-----	-------------------------------	-----------

A code specifying whether a response is required for a teller initiated advice or reversal advice message. Valid values are:

0 = No response is required.

1 = Yes, a response is required.

528	[1]	tstmh^data.rqst.crd^present	PIC X(1).
-----	-----	-----------------------------	-----------

A code indicating whether the transaction was initiated by a card at the teller terminal. Valid values are:

Y = Yes, the transaction was initiated by a card.

N = No, the transaction was not initiated by a card.

529	[3]	tstmh^data.rqst.entry^mde.byte[0:2]	PIC X(3).
-----	-----	-------------------------------------	-----------

A code indicating the entry mode of the teller transaction. It contains both how the card information was entered (positions 1 and 2) and the device PIN entry capability (position 3). Valid values are:

Position 1-2

00 - Unspecified

01 - Manual

02 - Magnetic Stripe

03 - Bar Code

04 - OCR

05 - Integrated Circuit Card

06-60 - Reserved for ISO use

61-80 - Reserved for National use

81-99 - Reserved for Private use

Position 3

0 - No PIN entry capability

1 - PIN entry capability

2-5 - Reserved for ISO use

6-7 - Reserved for National use

8-9 - Reserved for Private use

532	[2]	tstmh^data.rqst.rsn^cde.byte[0:1]	PIC X(2).
-----	-----	-----------------------------------	-----------

An informational field which can be used to distinguish between different types of the same transaction. This field is frequently used for Miscellaneous Debit/Credit Transactions and Debit/Credit Memo Post Transactions to indicate the specific reason for the transaction. The

Offset[Len]	Field Name and Description	Data Type
	values associated with this field are user-defined and may vary for each BASE24-teller customer.	
534 [1]	tstmh^data.rqst.mult^acct	PIC 9(1).
	A code indicating whether the terminal supports multiple account selection. Valid values are: 0 = Terminal does not support; default to primary account 1 = Terminal supports; return account selection information	
535 [8]	tstmh^data.rqst.ovrrd^tlr^id.byte[0:7]	PIC X(8).
	The identification of the teller, supervisor or manager that overrode the transaction.	
543 [1]	tstmh^data.rqst.user^fld2	PIC X(1).
	Reserved for future use.	
544 [5]	tstmh^data.tim^ofst.byte[0:4]	PIC X(5).
	The time difference between the transaction-initiating terminal and the Tandem processor location. It is the signed number of minutes to be added to the Tandem system time in order to obtain the terminal time.	
549 [46]	tstmh^data.resp^hdr	
	The following fields contain the transaction response data.	
549 [1]	tstmh^data.resp^hdr.crd^action	PIC X(1).
	A code representing the return/retain card action that was set on the original response prior to the override. This field is only used for card-initiated transactions. Valid values are: 0 = Return Card 1 = Retain Card	
550 [3]	tstmh^data.resp^hdr.resp^cde.byte[0:2]	PIC X(3).
	The response code associated with the transaction. Refer to the DDL source file for the BASE24-teller Standard Internal Message Header (TSTMH) or the Override Response File (ORF) for a complete list of the response codes supported by BASE24-teller.	
553 [6]	tstmh^data.resp^hdr.post^dat [DAT]	

Offset[Len]	Field Name and Description	Data Type
	The date (YYMMDD) the transaction is posted by the financial institution.	
553 [2]	tstmh^data.resp^hdr.post^dat.yy.byte[0:1]	PIC X(2).
555 [2]	tstmh^data.resp^hdr.post^dat.mm.byte[0:1]	PIC X(2).
557 [2]	tstmh^data.resp^hdr.post^dat.dd.byte[0:1]	PIC X(2).
559 [6]	tstmh^data.resp^hdr.auth^id^resp.byte[0:5]	PIC X(6).
	The authorization id response. The value is not generated by BASE24-teller but may optionally be generated by the authorizing host.	
565 [1]	tstmh^data.resp^hdr.err^flg	PIC X(1).
	A code used to provide additional information regarding the disposition of the transaction. Valid values are:	
	C = Card Verification Failed	
	K = KMAC Synchronization Error (future)	
	M = MAC Failure (future)	
	S = Sanity Check	
	T = Token Error	
566 [1]	tstmh^data.resp^hdr.min^ovrrd^lvl	PIC X(1).
	A code indicating the minimum level of override necessary to authorize the transaction in situations when the transaction is normally declined. This level is defined in the Override Response File (ORF). Valid values are:	
	0 = No override required--The transaction is approved and does not require an authorization override.	
	1 = Teller authorizes override--The transaction can be approved if entered by a teller.	
	2 = Supervisor authorizes override--The transaction can be approved if entered by a supervisor.	
	3 = Manager authorizes override--The transaction can be approved if entered by a manager.	
	4 = Override restricted--The transaction is denied and cannot be approved with an authorization override.	
567 [1]	tstmh^data.resp^hdr.acct^ind	PIC X(1).
	A code used when a fatal response code is associated with a specific account (i.e. From, To or Credit Line). This indicator is set by the Authorization process on selected card related response codes (i.e. F32, F33, F34, F3C), account related response codes (i.e. F4x where x indicates a value from 0 to 9)	

Offset[Len]	Field Name and Description	Data Type
	stop payment related response codes (i.e. F5x), warning/hold/float related response codes (i.e. F6x) and passbook related response codes (i.e. F7x). The account indicator may also be set in conjunction with response codes F08, F0B, F0C, 04x, 05x, 06x, and 07x. The account indicator will only be set in conjunction with an overridable response code when the response code can not be overridden. Valid values are: F = From Account T = To Account C = Credit/Backup Line Account	
568 [1]	tstmh^data.resp^hdr.crd^vrfy^flg A code indicating the card verification action performed by the Authorization process. Valid values are: C = Card verification performed, CVD invalid, condition noted, transaction authorization continued. D = Card verification performed, CVD invalid, transaction denied. ERR-FLG contains a value of "C". N or 0 = Card verification not attempted or security device error. Y = Card verification performed, CVD valid.	PIC X(1).
569 [16]	tstmh^data.resp^hdr.user^fld4.byte[0:15] Reserved for future use.	PIC X(16).
585 [10]	tstmh^data.resp^hdr.user^fld5.byte[0:9] Reserved for future use.	PIC X(10).
595 [19]	tstmh^data.entry^tim.byte[0:18] The time, expressed in Greenwich Mean Time, the transaction entered the BASE24 system for the first time. A Device Handler loads this field when the TSTMH is initialized.	PIC X(19).
614 [19]	tstmh^data.exit^tim.byte[0:18] The time, expressed in Greenwich Mean Time, the transaction left the BASE24 system for authorization through the Host Interface process.	PIC X(19).
633 [19]	tstmh^data.re^entry^tim.byte[0:18]	PIC X(19).

Offset[Len] Field Name and Description

Data Type

The time, expressed in Greenwich Mean Time, when
the response to an original transaction re-enters
the BASE24 system.

END [size 652]