

Offset[Len] Field Name and Description Data Type

DEF NBX-DISPLAY

0 [136]

0 [9] nx^cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual NBF records.

9 [1] nx^rec^typ PIC X(1).

A code indicating the operation to be performed on the NBF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

10 [4] nx^fiid.byte[0:3] [FIID] PIC X(4).

The FIID of the financial institution that owns the account.

14 [19] nx^acct^num.byte[0:18] PIC X(19).

The account number of the passbook account. The entry in this field must be left-justified with trailing spaces.

33 [2] nx^acct^typ.byte[0:1] PIC 9(2).

A code indicating the type of account. Savings (11) or NOW accounts (21) are normally associated with passbook accounts. Valid values are:

11, 14 - 19 = Savings
12 = IRA
13 = Certificate of Deposit
21 = NOW
41 = Installment Loan
42 = Mortgage Loan

Offset[Len] Field Name and Description Data Type

43 = Commercial Loan

35	[6]	nx^tran^dat [DAT]	
		The date (YYMMDD) the record was added to the NBF.	
35	[2]	nx^tran^dat.yy.byte[0:1]	PIC X(2).
37	[2]	nx^tran^dat.mm.byte[0:1]	PIC X(2).
39	[2]	nx^tran^dat.dd.byte[0:1]	PIC X(2).
41	[8]	nx^tran^tim [TIM]	
		The time (HHMMSSTT) the record was added to the NBF.	
41	[2]	nx^tran^tim.hh.byte[0:1]	PIC X(2).
43	[2]	nx^tran^tim.mm.byte[0:1]	PIC X(2).
45	[2]	nx^tran^tim.ss.byte[0:1]	PIC X(2).
47	[2]	nx^tran^tim.tt.byte[0:1]	PIC X(2).
49	[6]	nx^post^dat [DAT]	
		The date (YYMMDD) the record was logged to the Teller Transaction Log File (TTLF).	
49	[2]	nx^post^dat.yy.byte[0:1]	PIC X(2).
51	[2]	nx^post^dat.mm.byte[0:1]	PIC X(2).
53	[2]	nx^post^dat.dd.byte[0:1]	PIC X(2).
55	[1]	nx^prnt^stat	PIC X(1).
		A code indicating whether the record has been printed in the customer's passbook. Valid values are:	
		Y = Yes, the record has been printed.	
		N = No, the record has not been printed.	
56	[1]	nx^posting^sys	PIC X(1).
		A code indicating where the record originated. Valid values are:	
		A = BASE24 file maintenance	
		H = Host	
		R = Refresh	
		T = Teller Authorization process	

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

57 [2]	nx^tran^typ.byte[0:1]	PIC X(2).
-------------	-----------------------	-----------

A code indicating whether the transaction was a debit, a credit, a debit reversal, or a credit reversal. Valid values are:

C_ = Credit (_ denotes a blank)
D_ = Debit (_ denotes a blank)
DR = Debit Reversal
CR = Credit Reversal

59 [6]	nx^tran^cde.byte[0:5]	PIC X(6).
-------------	-----------------------	-----------

The transaction code that identifies the type of transaction that created this record. Positions 1 and 2 identify the transaction type, positions 3 and 4 identify the from account type, and positions 5 and 6 identify the to account type. Valid transaction type values are:

10	= Withdrawal
11	= Cash Transit Check
12	= Cash Official Check
16	= Miscellaneous Debit
17	= Affiliate/Correspondant Check Cash
18	= Debit Memo Post
20	= Deposit
21	= Split Deposit
22	= Miscellaneous Credit
23	= Credit Memo Post
40	= Transfer
50	= Payment From/To
60	= Purchase Money Order
61	= Purchase Cashier's Check
62	= Purchase Traveler's Checks
63	= Purchase Bank Draft
64	= Purchase Certified Check
65	= Purchase Bond
66	= Purchase Miscellaneous

Valid account type values are:

11	= Savings
12	= IRA
13	= Certificate of Deposit
21	= NOW
41	= Installment Loan
42	= Mortgage Loan
43	= Commercial Loan

65 [15]	nx^tran^amt.byte[0:14]	PIC 9(15).
--------------	------------------------	------------

Offset	Len	Field Name and Description	Data Type
		The amount of the transaction in whole and fractional currency units.	
80	[18]	nx^prnt^bal.byte[0:17]	PIC 9(18).
		The passbook balance amount in whole and fractional currency units as it would appear when printed in the passbook.	
98	[6]	nx^dev^tran^cde.byte[0:5]	PIC X(6).
		The device transaction code that defines the type of transaction performed.	
104	[8]	nx^tlr^id.byte[0:7]	PIC X(8).
		The identification number of the teller terminal operator who performed the transaction.	
112	[4]	nx^regn^id.byte[0:3] [REGN]	PIC X(4).
		The region of the terminal where the transaction was initiated.	
116	[4]	nx^brch^id.byte[0:3] [BRCH]	PIC X(4).
		The regional branch of the terminal where the transaction was initiated.	
120	[13]	nx^city.byte[0:12]	PIC X(13).
		The city of the terminal where the transaction was initiated.	
133	[3]	user^fld1.byte[0:2]	PIC X(3).
		Reserved for future use.	
		END [size 136]	

Offset[Len] Field Name and Description Data Type

DEF WHFX-DISPLAY

0 [112]

0 [9] wx^cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual WHFF records.

9 [1] wx^rec^typ PIC X(1).

A code indicating the operation to be performed on the WHFF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

10 [4] wx^fiid.byte[0:3] [FIID] PIC X(4).

The FIID of the financial institution owning the account.

14 [19] wx^acct^num.byte[0:18] PIC X(19).

The account number of the customer's account at the institution that is associated with this WHFF record. The account number must match a Positive Balance File (PBF) account number. The entry in this field must be left-justified with trailing spaces.

33 [2] wx^acct^typ.byte[0:1] PIC X(2).

The type of customer account specified in the WX-ACCT-NUM field having the WHFF record. Valid values are:

01 = DDA (Checking Account)
02 - 09 = Checking Accounts
11 = Savings
12 = IRA
13 = CD

Offset[Len]	Field Name and Description	Data Type
	14 - 19 = Savings Accounts	
	21 = NOW	
	31 = Credit Card	
	32 = Credit Line	
	33 - 39 = Credit Card	
	41 = Installment Loan	
	42 = Mortgage	
	43 = Commercial Loan	
35 [2]	wx^whff^rec^typ.byte[0:1]	PIC X(2).
	The type of WHFF record. Valid values are:	
	01 = Warning	
	02 = Hold	
	03 = Deposit Float	
37 [15]	wx^amt.byte[0:14]	PIC 9(15).
	The amount in whole and fractional currency units for which the record has been issued.	
52 [6]	wx^dat [DAT]	
	The date (YYMMDD) the record was added to the WHFF.	
52 [2]	wx^dat.yy.byte[0:1]	PIC X(2).
54 [2]	wx^dat.mm.byte[0:1]	PIC X(2).
56 [2]	wx^dat.dd.byte[0:1]	PIC X(2).
58 [8]	wx^tim [TIM]	
	The time (HHMMSSHH) the record was added to the WHFF.	
58 [2]	wx^tim.hh.byte[0:1]	PIC X(2).
60 [2]	wx^tim.mm.byte[0:1]	PIC X(2).
62 [2]	wx^tim.ss.byte[0:1]	PIC X(2).
64 [2]	wx^tim.tt.byte[0:1]	PIC X(2).
66 [6]	wx^exp^dat [DAT]	
	The expiration date (YYMMDD) for this WHFF record.	
66 [2]	wx^exp^dat.yy.byte[0:1]	PIC X(2).
68 [2]	wx^exp^dat.mm.byte[0:1]	PIC X(2).
70 [2]	wx^exp^dat.dd.byte[0:1]	PIC X(2).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

72 [35]	wx^descr.byte[0:34]	PIC X(35).
---------	---------------------	------------

A message regarding this WHFF record. It documents and displays any data about the WHFF record that the institution placed on the file.

107 [5]	user^fld1.byte[0:4]	PIC X(5).
---------	---------------------	-----------

Reserved for future use.

END [size 112]