

Offset[Len] Field Name and Description Data Type

RECORD RFH

The file header identifies the file to be refreshed and whether a full-file or partial-file refresh is to be run. It also contains various processing parameters required by Refresh.

At least one file header is required per refresh tape.

0 [150]

0 [9] rec^cnt.byte[0:8] PIC 9(9).

9 [2] rec^typ.byte[0:1] PIC X(2).

The record type. This field must contain the value FH (File Header).

11 [1] ref^typ PIC X(1).

The type of refresh for which the records on the tape are to be used. Valid values are:

0 = Full-file Refresh--Refresh creates an entirely new file and adds to that file every record on the tape.

1 = Partial-file Refresh--Refresh updates the existing file using records on the tape.

12 [2] appl.byte[0:1] PIC X(2).

Indicates the BASE24 file or table being refreshed. Valid values are:

AC = Customer Account Relation Table (CACT)

CC = Positive Balance File (PBF) for credit accounts only

CF = Cardholder Authorization File (CAF)

CH = Card History File (CHF)

CI = Customer/Card Information File (CCIF)

CM = Customer/Card Memo File (CCMF)

CO = Corporate Check File (CCF)

CP = Customer/Personal Id Relation Table (CPIT)

CS = Check Status File (CSF)

CT = Customer Table (CSTT)

DA = PBF for checking or NOW accounts only

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

MB = Mail Box File (MBF)
 NB = No Book File (NBF)
 NF = Negative Card File (NEG)
 PF = PBF for all account types
 PT = Personal Information Table (PIT)
 SD = Switch Dispute File (SDF)
 SP = Stop Payment File (SPF)
 SV = PBF for savings accounts only
 TH = Transaction History File (THF)
 WH = Warning/Hold/Float File (WHFF)

A single PBF can contain multiple account types, or a PBF can contain a single account type.

14	[4]	grp.byte[0:3]	PIC X(4).
----	-----	---------------	-----------

The refresh group to be refreshed. Refresh groups identify groupings of institutions that share the same physical files. Institutions are assigned to refresh groups via the value in the REFR-GRP field in the Base segment of the Institution Definition File (IDF).

18	[8]	tape^dat.byte[0:7]	PIC X(8).
----	-----	--------------------	-----------

The date (YYYYMMDD) that this tape was created.

26	[4]	tape^tim.byte[0:3]	PIC 9(4).
----	-----	--------------------	-----------

The time (HHMM) that this tape was created.

30	[4]	ln.byte[0:3]	PIC X(4).
----	-----	--------------	-----------

The identifier assigned to the logical network in which the records being refreshed reside.

34	[2]	rel^num.byte[0:1]	PIC 9(2).
----	-----	-------------------	-----------

The ACI-assigned release number identifying the BASE24 software release with which the BASE24 file being refreshed is compatible. Valid values are:
 60, 50 and 11.
 Note: The value "11" pertains only to BASE24-telebanking.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

36 [2]	part^num.byte[0:1]	PIC X(2).
--------	--------------------	-----------

Indicates the file partition to be refreshed, if the file is partitioned. The value in this field is only used for full-file refreshes; it should be set to blanks for partial-file refreshes. Valid values are:

blanks = The tape records represent the entire file.
 00 = The tape records represent those records to be placed in the primary file partition.
 01-15 = The tape records represent those records to be placed in the file partition indicated.

38 [26]	atm	
---------	-----	--

The following fields contain information about the last extract of the BASE24-atm Transaction Log File (TLF). These fields are used for CAF and PBF refreshes with impacting when the BASE24-atm product is part of the BASE24 system.

38 [6]	atm.lst^extr^dat.byte[0:5]	PIC X(6).
--------	----------------------------	-----------

The date (YYMMDD) of the last TLF that was fully extracted. A value is required in this field when performing a CAF or PBF refresh with impacting and BASE24-atm is installed. The value in this field cannot be overridden.

44 [8]	atm.imp^strt^dat.byte[0:7]	PIC X(8).
--------	----------------------------	-----------

The date (YYYYMMDD) of the last TLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial TLF.

A value is required in this field when performing a CAF or PBF refresh with impacting and BASE24-atm is installed. The value in this field can be overridden when Refresh is started by the specifying a date in ATM IMPACT START DATE field on REFR screen 1, or by specifying a <atm impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the TLF.

52	[12]	atm.imp^strt^tim.byte[0:11]	PIC X(12).
----	------	-----------------------------	------------

The time (HHMMSSMMMMMM) of the last TLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial TLF.

A value is required in this field when performing a CAF or PBF refresh with impacting and BASE24-atm is installed. The value in this field can be overridden when Refresh is started by the specifying a date in ATM IMPACT START TIME field on REFR screen 1, or by specifying a <atm impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the TLF.

64	[26]	pos	
----	------	-----	--

The following fields contain information about the last extract of the POS Transaction Log File (PTLF). These fields are used for PBF refreshes with impacting when the BASE24-pos product is part of the BASE24 system.

Offset[Len]	Field Name and Description	Data Type
64 [6]	pos.lst^extr^dat.byte[0:5]	PIC X(6).

The date (YYMMDD) of the last PTLF that was fully extracted. A value is required in this field when performing a PBF refresh with impacting and BASE24-pos is installed. The value in this field cannot be overridden.

70 [8]	pos.imp^strt^dat.byte[0:7]	PIC X(8).
--------	----------------------------	-----------

The date (YYYYMMDD) of the last PTLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial PTLF.

A value required in this field when performing a PBF refresh with impacting and BASE24-pos is installed. The value in this field can be overridden when Refresh is started by the specifying a date in POS IMPACT START DATE field on REFR screen 1, or by specifying a <pos impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the PTLF.

78 [12]	pos.imp^strt^tim.byte[0:11]	PIC X(12).
---------	-----------------------------	------------

The time (HHMMSSMMMMMM) of the last PTLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial PTLF.

A value is required in this field when performing a PBF refresh with impacting and BASE24-pos is installed. The value in this field can be overridden when Refresh

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

is started by the specifying a date in POS IMPACT START TIME field on REFR screen 1, or by specifying a <pos impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the PTLF.

90	[26]	tlr	
----	------	-----	--

The following fields contain information about the last extract of the Teller Transaction Log File (TTLF). These fields are used for NBF, PBF, SPF, or WHFF refreshes with impacting when the BASE24-teller product is part of the BASE24 system.

90	[6]	tlr.lst^extr^dat.byte[0:5]	PIC X(6).
----	-----	----------------------------	-----------

The date (YYMMDD) of the last TTLF that was fully extracted. A value is required in this field when performing an NBF, PBF, SPF, or WHFF refresh with impacting and BASE24-teller is installed. The value in this field cannot be overridden.

96	[8]	tlr.imp^strt^dat.byte[0:7]	PIC X(8).
----	-----	----------------------------	-----------

The date (YYYYMMDD) of the last TTLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial TTLF.

A value required in this field when performing an NBF, PBF, SPF, or WHFF refresh with impacting and BASE24-teller is installed. The value in this field can be overridden when Refresh is started by the specifying a date in TLR IMPACT START DATE field on REFR screen 1, or by specifying a <teller impact start date/time>

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the TTLF.

104	[12]	tlr.imp^strt^tim.byte[0:11]	PIC X(12).
-----	------	-----------------------------	------------

The time (HHMMSSMMMMMM) of the last TTLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial TTLF.

A value is required in this field when performing an NBF, PBF, SPF, or WHFF refresh with impacting and BASE24-teller is installed. The value in this field can be overridden when Refresh is started by the specifying a date in TLR IMPACT START TIME field on REFR screen 1, or by specifying a <teller impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the TTLF.

116	[1]	imp^typ	PIC X(1).
-----	-----	---------	-----------

Indicates whether CAF, NBF, PBF, SPF, or WHFF records are to be impacted. Valid values are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

0 = Do not impact refreshed records.
 1 = Impact refreshed records.

Impacting refers to the process by which transactions occurring since the last transaction log file extract are applied to the new records created or updated by Refresh.

The value in this field is only used for CAF, NBF, PBF, SPF, or WHFF refreshes. Otherwise, it should be set to a blank or zero.

117	[1]	caf^expnt	PIC X(1).
-----	-----	-----------	-----------

The power of 10 to be used when evaluating the following CAF amount fields:

- o GRP-LMT.TTL-WDL-LMT, GRP-LMT.OFFL-WDL-LMT, GRP-LMT.TTL-CCA-LMT, GRP-LMT.OFFL-CCA-LMT, GRP-LMT.AGGR-LMT, and GRP-LMT.OFFL-AGGR-LMT in the Base segment
- o GRP-LMT.TTL-WDL-LMT, GRP-LMT.OFFL-WDL-LMT, GRP-LMT.TTL-CCA-LMT, and GRP-LMT.OFFL-CCA-LMT in the BASE24-atm segment
- o GRP-LMT.TTL-PUR-LMT, GRP-LMT.OFFL-PUR-LMT, GRP-LMT.TTL-CCA-LMT, GRP-LMT.OFFL-CCA-LMT, GRP-LMT.TTL-WDL-LMT, GRP-LMT.OFFL-WDL-LMT, GRP-LMT.TTL-RFND-CR-LMT, and GRP-LMT.OFFL-RFND-CR-LMT in the BASE24-pos segment
- o GRP-LMT.TTL-CHK-LMT, GRP-LMT.OFFL-CHK-LMT, GRP-LMT.TTL-CSF-CHK-LMT, and GRP-LMT.OFFL-CSF-CHK-LMT in the BASE24-atm SSB Check (SSBC) segment

Refresh multiplies the CAF amount fields on the refresh tape or disk by the appropriate power of 10 before applying them to the CAF. Valid values are:

- _ = Not applicable. This is not a CAF refresh. (_ indicates a space).
- 0 = Use the CAF amount field as it appears in the message.
- 1 = Multiply the refresh amount fields by 10.
- 2 = Multiply the refresh amount fields by 100.
- 3 = Multiply the refresh amount fields by 1000.

118	[1]	pre^auth^support	PIC X(1).
-----	-----	------------------	-----------

Indicates whether the host provides preauthorization information. This field is used for partial refreshes of the CAF and PBF. It specifies whether Refresh

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

retains the current preauthorization holds in the CAF or PBF, or replaces them with the information from the tape. Valid values are:

0 = Host does not provide preauthorization holds
1 = Host provides preauthorization holds.

119	[5]	user^fld2.byte[0:4]	PIC X(5).
-----	-----	---------------------	-----------

This field is not used.

124	[26]	tb	
-----	------	----	--

The following fields contain information about the last extract of the BASE24 Telebanking Transaction Log File (ITLF). The following TB structure is used when performing a full or partial PBF refresh with impacting.

124	[6]	tb.lst^extr^dat.byte[0:5]	PIC X(6).
-----	-----	---------------------------	-----------

The date (YYMMDD) of the last ITLF that was fully extracted. A value is required in this field when performing a PBF refresh with impacting and BASE24-telebanking is installed. The value in this field cannot be overridden.

130	[8]	tb.imp^strt^dat.byte[0:7]	PIC X(8).
-----	-----	---------------------------	-----------

The date (YYYYMMDD) of the last ITLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial ITLF.

A value required in this field when performing a PBF refresh with impacting and BASE24-telebanking is installed. The value in this field can be overridden when Refresh is started by the specifying a date in TB IMPACT START DATE field on REFR screen 1, or by specifying a <telebanking impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the ITLF.

138	[12]	tb.imp^strt^tim.byte[0:11]	PIC X(12).
-----	------	----------------------------	------------

The time (HHMMSSMMMMMM) of the last ITLF record extracted. The IMP-STRT-DAT and IMP-STRT-TIM fields can be used to specify a timestamp value. If specified, Refresh will use this timestamp value as an indication of where impacting will start in the initial ITLF.

A value is required in this field when performing a PBF refresh with impacting and BASE24-telebanking is installed. The value in this field can be overridden when Refresh is started by the specifying a date in TB IMPACT START TIME field on REFR screen 1, or by specifying a <telebanking impact start date/time> value from the Network Control Supervisor (NCS) screen.

When performing multiple partial extracts of the log file, extract places the timestamp value of the last log file record extracted in the first 20 bytes of USER-FLD2 of the file trailer record. The value in the USER-FLD2 field of the last partial extract used to update the host files can be echoed back to Refresh in the IMP-STRT-DAT and IMP-STRT-TIM fields.

All blanks or all nines ("9"s) for the IMP-STRT-DAT and IMP-STRT-TIM fields indicates to start impacting at the beginning of the ITLF.

END [size 150]

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

RECORD RBH

The organization header identifies, by FIID, the institution whose files are to be refreshed.

One organization header is required for each set of institution records on the refresh tape. If records are not grouped by institution, only one organization header is required on the tape.

0 [44]

0	[9]	rec^cnt.byte[0:8]	PIC 9(9).
---	-----	-------------------	-----------

The record number. The value in this field should be one greater than that in the previous record, which must be a file header or an organization trailer.

9	[2]	rec^typ.byte[0:1]	PIC X(2).
---	-----	-------------------	-----------

The record type. This field must contain the value BH (organization header record).

11	[4]	crd^iss.byte[0:3]	PIC X(4).
----	-----	-------------------	-----------

The FIID of the institution whose refresh records follow. The entry in this field is left-justified and blank-filled on the right. It is only used with PBF refreshes and THF refreshes.

For THF refreshes, this field combined with RFH.GRP and RBH.END-RANGE allow a file to be optionally defined at a lower level than Refresh Group.

15	[28]	end^range.byte[0:27]	PIC X(28).
----	------	----------------------	------------

The account number end range that is associated with the refresh records for this institution. This field combined with RFH.GRP and RBH.CRD-ISS allow a file to be optionally defined at a lower level than Refresh Group. This field is only used for THF refreshes.

43	[1]	user^fld	PIC X(1).
----	-----	----------	-----------

MM/DD/YY HH:MM \$VOLUME BA60DDL RBH PAGE: 12

Offset[Len] Field Name and Description Data Type

 This field is not used. It should be left blank.

END [size 44]

Offset[Len]	Field Name and Description	Data Type
RECORD RBT		

The organization trailer signals the end of an institution's refresh records. It contains a verification count and amount for the institution's records, which Refresh uses to check its processing.

One organization trailer is required for each set of institution records on the refresh tape. If records are not grouped by institution, only one organization trailer is required on the tape.

0 [38]

0 [9] rec^cnt.byte[0:8] PIC 9(9).

The record number. The value in this field should be one greater than that in the previous record.

9 [2] rec^typ.byte[0:1] PIC X(2).

The record type. This field must contain the value BT (organization trailer record).

11 [18] amt.byte[0:17] PIC 9(18).

A verification amount used with NBF, PBF, SPF, and WHFF refreshes. This amount must contain the sum of all NBF transaction amounts, PBF ledger balances, SPF amounts, or WHFF amounts (respectively) included for the organization.

To derive this sum, a host must add together the NBF.TRAN-AMT, PBF.BASE.LEDG-BAL, SPF.AMT, or WHFF.PRIKEY.AMT field values for all NBF, PBF, SPF, and WHFF records.

29 [9] num^recs.byte[0:8] PIC 9(9).

The number of application records for the organization, not including the organization header or trailer records.

MM/DD/YY HH:MM \$VOLUME BA60DDL RBT

PAGE: 14

Offset[Len] Field Name and Description

Data Type

END [size 38]

Offset[Len] Field Name and Description Data Type

RECORD RFT

The file trailer signals the end of the refresh records. It contains a verification count, which is used by Refresh to check its processing.

One file trailer is required for each refresh tape.

0 [24]

0 [9] rec^cnt.byte[0:8] PIC 9(9).

The record number for this record. The value in this field should be one greater than that in the previous record, which must be an organization trailer record.

9 [2] rec^typ.byte[0:1] PIC X(2).

The record type. This field must contain the value FT (file trailer record).

11 [9] num^recs.byte[0:8] PIC 9(9).

The total number of refresh records on the tape, excluding file headers and trailers and organization headers and trailers.

20 [1] nxt^file^ind PIC X(1).

Indicates whether another input file follows. Valid values are:

0 = This is the last file in the input file.
1 = A subsequent file is present in the input file.

21 [3] user^fld1.byte[0:2] PIC X(3).

This field is not used. It should be left blank.

END [size 24]

MM/DD/YY HH:MM \$VOLUME BA60DDL RFT

PAGE: 16

Offset[Len] Field Name and Description

Data Type

Offset[Len] Field Name and Description Data Type

DEF CAFXD

0 [2644]

0 [346] seg0 [CAFXBASE-DISPLAY]

The following fields make up the Base segment of the Cardholder Authorization File (CAF) Refresh Format.

0 [4] seg0.lgth.byte[0:3] PIC 9(4).

The length of the Base segment. The value in this field must be set to 0346.

4 [9] seg0.cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that for the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual CAF records.

13 [22] seg0.prikey

The primary key of the file record.

13 [19] seg0.prikey.pan.byte[0:18] PIC X(19).

The Primary Account Number (PAN), as it appears in Track 2 of the card. The entry in this field is left-justified and blank-filled to the right.

32 [3] seg0.prikey.mbr^num.byte[0:2]
[MBR-NUM] PIC 9(3).

The member number for the card. If member numbers are not used, the value in this field must be set to 000.

35 [1] seg0.rec^typ PIC X(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code indicating the operation to be performed on the CAF record. Valid values are:

A = Add
 C = Change
 D = Delete
 F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

36	[2]	seg0.crd^typ.byte[0:1]	PIC X(2).
----	-----	------------------------	-----------

One- or two-character codes are used to identify card types in files throughout BASE24. The same codes must be used for a particular card type in all of the files. These codes are also used to identify service types in BASE24-pos. Codes used in this field are either reserved by BASE24 or user-defined. Reserved codes are to be used only as defined, and include:

AD = Administrative (BASE24-atm only)
 AX = American Express credit
 BD = Business deposit (BASE24-atm and BASE24-teller only)
 C* = Private label credit (includes C, C0-C9, CA, and CC-CZ)
 CB = Carte Blanche credit
 D = Demonstration (BASE24-atm only)
 DC = Diners Club credit
 DS = Discover (Sears) credit
 M = MasterCard credit
 MD = MasterCard debit (See BASE24-pos note below)
 MM = MasterCard dual (See BASE24-pos note below)
 P* = Proprietary debit (includes P, P0-P9, and PA-PZ)
 SC = Special, Check (BASE24-pos only)
 SP = Special purpose (BASE24-atm Self-Service Banking Check Application only)
 ST = Super teller (BASE24-atm Self-Service Banking Base Application only)
 V = VISA credit
 VD = VISA debit (See BASE24-pos note below)
 VV = VISA dual (See BASE24-pos note below)

Codes with a first character of C, except code CB, are recommended to identify private label credit cards.

Codes with a first character of P are required to identify proprietary debit cards. BASE24 treats cards with proprietary debit codes and codes MD and VD as

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

debit cards and treats cards with all other codes as credit cards.

Administrative (AD), Business deposit (BD), Demonstration (D), Special purpose (SP), and Super teller (ST) are special-use card types used by BASE24-atm.

Business deposit (BD) is also a special-use card type used by BASE24-teller to identify cards that can only be used to initiate deposit transactions.

BASE24-teller does not perform any other processing based on card type; however, BASE24 guidelines should still be used when establishing card types for BASE24-teller.

MasterCard dual (MM) and VISA dual (VV) can be processed as debit or credit card types, based on the default combo card type specified in the CPF.

Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only.

BASE24-pos NOTE: BASE24-pos does not allow MasterCard debit (MD), MasterCard dual (MM), VISA debit (VD), or VISA dual (VV) card types in the PRDF and PTDF. BASE24-pos automatically includes the MD and MM card types with the MasterCard credit (M) card type, and automatically includes the VD and VV card types with the VISA credit (V) card type.

User-defined Codes: The user can add any one- or two-character code not included in the reserved code list above, according to the following guidelines:

- o The first character must be alphabetic (A, B, D-O, and Q-Z).
- o The second character can be A-Z, 0-9, or a blank.
- o A valid COBNAMES table entry is recommended for each user-defined code.

38	[4]	seg0.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------	-----------

The FIID of the institution that issued the card associated with the CAF record.

42	[1]	seg0.crd^stat	PIC X(1).
----	-----	---------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code indicating the status of the card. Values are:

0 = Issued but not active--no transactions allowed
 1 = Open--transactions allowed
 2 = Lost--no transactions allowed
 3 = Stolen--no transaction allowed
 4 = Restricted--no withdrawals allowed
 5 = VIP--transaction allowed
 6 = Check reason code--see note below
 9 = Closed--no transactions allowed
 A = Referral--see note below
 B = Maybe--see note below
 C = Denial--see note below
 D = Signature restricted--see note below
 E = Country club--see note below
 F = Expired--see note below
 G = Commercial--see note below

Status code 6 is a status code used exclusively by BASE24-pos, whereby the value in the RSN-CDE field in the BASE24-pos segment must be checked to determine the status of the card. Outside of BASE24-pos, no transactions are allowed on cards with this status, and the card is returned.

Status codes "A" - "G" are used primarily by BASE24-teller and BASE24-pos where these status codes may be used to inform the teller or operator to perform some additional action in order to authorize the transaction (e.g. obtain signature, call for authorization, etc.). BASE24-atm transactions are not allowed on cards with these status codes and the card is returned.

43	[16]	seg0.pin^ofst.byte[0:15]	PIC X(16).
----	------	--------------------------	------------

The cardholder's PIN offset, PIN verification key indicator, PIN verification value, or PIN verification number, depending on the type of PIN verification performed.

59	[12]	seg0.ttl^wdl^lmt.byte[0:11]	PIC 9(12).
----	------	-----------------------------	------------

The maximum amount of purchases and cash withdrawals allowed against non-credit accounts during a single usage accumulation period. This amount must be in whole currency units.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

71 [12]	seg0.offl^wdl^lmt.byte[0:11]	PIC 9(12).
---------	------------------------------	------------

The maximum amount of purchases and cash withdrawals allowed offline against non-credit accounts during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

83 [12]	seg0.ttl^cca^lmt.byte[0:11]	PIC 9(12).
---------	-----------------------------	------------

The maximum amount of cash advances allowed against credit accounts during a single usage accumulation period. This amount must be in whole currency units.

95 [12]	seg0.offl^cca^lmt.byte[0:11]	PIC 9(12).
---------	------------------------------	------------

The maximum amount of cash advances allowed offline against credit accounts during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

107 [12]	seg0.aggr^lmt.byte[0:11]	PIC 9(12).
----------	--------------------------	------------

The maximum aggregate amount of cash disbursements allowed against credit and non-credit accounts during a single usage accumulation period, plus purchases allowed against non-credit accounts during a single usage accumulation period. This amount must be in whole currency units.

119 [12]	seg0.offl^aggr^lmt.byte[0:11]	PIC 9(12).
----------	-------------------------------	------------

The maximum aggregate amount of cash disbursements allowed offline against credit and non-credit accounts during a single usage accumulation period, plus purchases allowed offline against non-credit accounts during a single usage accumulation period. This amount must be in whole currency units.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

131	[6]	seg0.first^used^dat.byte[0:5]	PIC X(6).
-----	-----	-------------------------------	-----------

The date (YYMMDD) the card was first used in the system.

137	[6]	seg0.last^reset^dat.byte[0:5]	PIC X(6).
-----	-----	-------------------------------	-----------

The date (YYMMDD) the usage accumulation totals in the Base segment of the CAF record were last cleared.

143	[4]	seg0.exp^dat.byte[0:3]	PIC 9(4).
-----	-----	------------------------	-----------

The expiration date (YYMM) of the card. If the card has expired, the account is considered closed.

147	[4]	seg0.effective^dat.byte[0:3]	PIC X(4).
-----	-----	------------------------------	-----------

The date the card becomes effective. Format (YYMM).

151	[1]	seg0.user^fld1	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be blank filled.

152	[9]	seg0.scnd^crd^data	
-----	-----	--------------------	--

These fields are related to a re-issued card where the same logical card is used but a different physical card.

152	[4]	seg0.scnd^crd^data.exp^dat^2.byte[0:3]	PIC 9(4).
-----	-----	--	-----------

The expiration date (YYMM) of the second card.

156	[4]	seg0.scnd^crd^data.effective^dat^2.byte[0:3]	PIC X(4).
-----	-----	--	-----------

The date the second card becomes effective. Format (YYMM).

160	[1]	seg0.scnd^crd^data.crd^stat^2	PIC X(1).
-----	-----	-------------------------------	-----------

The card status of the second card.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

161	[35]	seg0.user^fld2.byte[0:34]	PIC X(35).
-----	------	---------------------------	------------

This field is not used and should be blank filled.

196	[50]	seg0.user^fld^aci.byte[0:49]	PIC X(50).
-----	------	------------------------------	------------

USER-FLD-ACI is reserved for future BASE24 product use only. The designation of "product use only" provides ACI with the ability to deplete the number of bytes available within USER-FLD-ACI as product enhancements are introduced. When product enhancements require the addition of new fields within this file, the procedure to be followed is to deplete bytes from USER-FLD-ACI and use that number of bytes to define new fields. The new field definition(s) should precede the USER-FLD-ACI field.

The length of this field may not match the length of the corresponding field in DDLFCAF. This field cannot be decreased for fields defined in DDLFCAF that are not part of the CAF Refresh format. Decreasing this field in that case will shorten the overall record length.

246	[50]	seg0.user^fld^regn.byte[0:49]	PIC X(50).
-----	------	-------------------------------	------------

USER-FLD-REGN is reserved for ACI regional use only. Only ACI regions are allowed to use USER-FLD-REGN space.

296	[50]	seg0.user^fld^cust.byte[0:49]	PIC X(50).
-----	------	-------------------------------	------------

USER-FLD-CUST is reserved for BASE24 customer use only. Only customers are allowed to use USER-FLD-CUST space.

346	[88]	seg1 [ATMCAFX-DISPLAY]	
-----	------	------------------------	--

The following fields make up the ATM segment of the Cardholder Authorization File (CAF) Refresh Format.

346	[4]	seg1.lgth.byte[0:3]	PIC 9(4).
-----	-----	---------------------	-----------

The length of the BASE24-atm segment. The value in this field must be set to 0088. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

350	[4]	seg1.use^lmt.byte[0:3]	PIC 9(4).
-----	-----	------------------------	-----------

The maximum number of times the card may be used to withdraw cash via BASE24-atm during a single usage accumulation period.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

354	[12]	seg1.ttl^wdl^lmt.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The maximum amount of cash withdrawals allowed against non-credit accounts via BASE24-atm during a single usage accumulation period. This amount must be in whole currency units.

366	[12]	seg1.offl^wdl^lmt.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The maximum amount of cash withdrawals allowed offline against non-credit accounts via BASE24-atm during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

378	[12]	seg1.ttl^cca^lmt.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The maximum amount of cash advances allowed against credit accounts via BASE24-atm during a single usage accumulation period. This amount must be in whole currency units.

390	[12]	seg1.offl^cca^lmt.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The maximum amount of cash advances allowed offline against credit accounts via BASE24-atm during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

402	[10]	seg1.dep^cr^lmt.byte[0:9]	PIC 9(10).
-----	------	---------------------------	------------

The maximum amount of deposit credit the cardholder is allowed during a single usage accumulation period. This amount must be in whole currency units.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

412	[6]	seg1.last^used.byte[0:5]	PIC 9(6).
-----	-----	--------------------------	-----------

The date (YYMMDD) the card was last used via BASE24-atm. The date in this field should be less than the beginning date of the current withdrawal period. (Refresh does not verify this, however.)

418	[16]	seg1.iss^txn^prfl.byte[0:15] [PRFL]	PIC X(16).
-----	------	--	------------

This defines a general profile. A profile is an identifier used to define a specific configuration (e.g., transaction profile, retailer profile). Left justified, blank filled, no embedded spaces.

434	[140]	seg2 [POSCAFX-DISPLAY]	
-----	-------	------------------------	--

The following fields make up the POS segment of the Cardholder Authorization File (CAF) Refresh Format.

434	[16]	seg2.segx^lgth [SEGX-LGTH]	
-----	------	----------------------------	--

The length of the BASE24-pos segment. The value in this field must be 0140. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

434	[4]	seg2.segx^lgth.lgth.byte[0:3]	PIC 9(4).
-----	-----	-------------------------------	-----------

438	[12]	seg2.segx^lgth.seg^data	
-----	------	-------------------------	--

438	[4]	seg2.segx^lgth.seg^data.id.byte[0:3]	PIC 9(4).
-----	-----	--------------------------------------	-----------

442	[8]	seg2.segx^lgth.seg^data.b24^rsrvd.byte[0:7]	PIC X(8).
-----	-----	---	-----------

450	[12]	seg2.ttl^pur^lmt.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The maximum amount of purchases allowed against credit accounts via BASE24-pos during a single usage accumulation period. This amount must be in whole currency units.

462	[12]	seg2.offl^pur^lmt.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The maximum amount of purchases allowed offline against credit accounts via BASE24-pos during a single usage

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

474	[12]	seg2.ttl^cca^lmt.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The maximum amount of cash advances allowed against credit accounts via BASE24-pos during a single usage accumulation period. This amount must be in whole currency units.

486	[12]	seg2.offl^cca^lmt.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The maximum amount of cash advances allowed offline against credit accounts via BASE24-pos during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

498	[12]	seg2.ttl^wdl^lmt.byte[0:11]	PIC 9(12).
-----	------	-----------------------------	------------

The maximum amount of purchases and cash withdrawals allowed against non-credit accounts via BASE24-pos during a single usage accumulation period. This amount must be in whole currency units.

510	[12]	seg2.offl^wdl^lmt.byte[0:11]	PIC 9(12).
-----	------	------------------------------	------------

The maximum amount of purchases and cash withdrawals allowed offline against non-credit accounts via BASE24-pos during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

522	[4]	seg2.use^lmt.byte[0:3]	PIC 9(4).
-----	-----	------------------------	-----------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The maximum number of times the card may be used via BASE24-pos during a single usage accumulation period.

526	[12]	seg2.ttl^rfnd^cr^lmt.byte[0:11]	PIC 9(12).
-----	------	---------------------------------	------------

The maximum amount of refunds/replenishment credit that can be received during a single usage accumulation period. This amount must be in whole currency units.

538	[12]	seg2.offl^rfnd^cr^lmt.byte[0:11]	PIC 9(12).
-----	------	----------------------------------	------------

The maximum amount of refunds/replenishment credits that can be received offline during a single usage accumulation period. This amount must be in whole currency units.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

550	[1]	seg2.rsn^cde	PIC X(1).
-----	-----	--------------	-----------

A code indicating the reason the card is restricted.
Valid values are:

A = Referral
B = Maybe
C = Denial
D = Signature restricted
E = Country club
F = Expired
G = Commercial

551	[6]	seg2.last^used.byte[0:5]	PIC 9(6).
-----	-----	--------------------------	-----------

The date (YYMMDD) the card was last used via BASE24-pos. The date in this field should be less than the beginning date of the current withdrawal period. (Refresh does not verify this, however.)

557	[1]	seg2.user^fld2	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be blank filled.

Offset[Len]	Field Name and Description	Data Type
558 [16]	seg2.iss^txn^prfl.byte[0:15] [PRFL]	PIC X(16).
	This defines a general profile. A profile is an identifier used to define a specific configuration (e.g., transaction profile, retailer profile). Left justified, blank filled, no embedded spaces.	
574 [36]	seg9 [EMVCAFX-DISPLAY]	
	The following fields make up the Europay, MasterCard and Visa (EMV) segment of the Cardholder Authorization File (CAF) Refresh Format.	
574 [4]	seg9.segx^lgth.byte[0:3]	PIC 9(4).
	This field contains the segment length.	
578 [4]	seg9.atc^lmt.byte[0:3]	PIC 9(4).
	This field contains the Application Transaction Sequence Number Limit.	
582 [1]	seg9.send^crd^blk	PIC X(1).
	This field determines whether a Card Block script should be sent to the device. Valid values are:	
	N = Do not send CARD BLOCK script command Y = Send CARD BLOCK script command.	
583 [1]	seg9.send^put^data	PIC X(1).
	This field determines whether a PUT script command should be sent to the device. Valid values are:	
	N = Do not send PUT DATA script command Y = Send PUT DATA script command.	
584 [8]	seg9.vlcty^lmts	
	Velocity Limits for the card.	
584 [4]	seg9.vlcty^lmts.lwr^consec^lmt.byte[0:3]	PIC 9(4).
	This field is the lower consecutive off-line limit and is used in the PUT DATA script command.	
588 [4]	seg9.vlcty^lmts.user^fld2.byte[0:3]	PIC X(4).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

This field is not used.

588	[4]	seg9.vlcty^lmts.data^tag.byte[0:3] [REDEFINES USER^FLD2]	PIC X(4).
-----	-----	---	-----------

The EMV Tag of the data element included in the PUT DATA script command, contains hexadecimal value.

592	[1]	seg9.send^pin^unblk	PIC X(1).
-----	-----	---------------------	-----------

This field indicates the circumstances under which a "PIN Unblock" script command will be generated and returned by BASE24-atm. Valid values are:

- 0 - No action required (this is the current processing)
- 1 - Implicit (an EMV transaction indicates that the offline bad PIN try limit has been exceeded)
- 2 - Explicit (an EMV PIN Unblock transaction is received)
- 3 - Implicit and Explicit (an EMV transaction indicates that the offline bad PIN try limit has been exceeded or an EMV PIN Unblock transaction is received).

593	[1]	seg9.send^pin^chng	PIC X(1).
-----	-----	--------------------	-----------

This field indicates the circumstances under which a "PIN Change" script command will be generated and returned by BASE24-atm. Valid values are:

- 0 - Do not send script (current processing)
- 1 - An EMV PIN Unblock transaction is received
- 2 - An EMV PIN Change transaction is received
- 3 - An EMV PIN Unblock transaction or an EMV PIN Change transaction is received.

594	[1]	seg9.pin^sync^act	PIC X(1).
-----	-----	-------------------	-----------

This field indicates whether synchronisation of the online and offline PIN is required for the card. Valid values are:

- 0 = PIN synchronisation not required (current processing)
- 1 = PIN synchronisation required.

595	[1]	seg9.access^script^mgmt^sub^sys	PIC X(1).
-----	-----	---------------------------------	-----------

This field indicates when to access the Script Management Sub-System. Valid values are:

- 0 - Do not send script Management Sub-System
- 1 - Access Script Management Sub-System.

Offset[Len]	Field Name and Description	Data Type
596 [1]	seg9.iss^appl^data^frmt	PIC X(1).
	The Issuer Application Data Format type specifies the format of the EMV Issuer Application Data that will be used for this card prefix. A number of predefined formats for Issuer Application Data exist, as specified by the Payment Associations (VISA and Mastercard/Europay), but Issuer specific layouts may also be defined. Issuer Application Data typically contains information which is used in the derivation of the Application Cryptogram. Valid values are: 0 Use the current value defined in CAF Issuer Application Data Format field 3 Issuer Application Data format as recommended for Mastercard/Europay (M/Chip 4 format) cards.	
597 [1]	seg9.action^table^index	PIC X(1).
	This field is used to identify which of the preset rules for status field processing are to be used for this Card scheme. The decision array which defines the action to be taken based on the CVR (Card Verification Results) is pre-configured in an EDIT file (CVRTBLS), sourced in to the EMV authorization modules at compile time. Four different arrays are supported to cater for the processing requirements of different card schemes. This field is used to select the appropriate array for the card scheme. Valid values are 1 to 4.	
598 [2]	seg9.cap^apsn^1.byte[0:1]	PIC X(2).
	This field contains the CAP Application PAN Sequence Number (APSN) of the primary card.	
600 [2]	seg9.cap^dki^1.byte[0:1]	PIC X(2).
	This field contains the CAP Derivation Key Index (DKI) of the primary card.	
602 [2]	seg9.cap^apsn^2.byte[0:1]	PIC X(2).
	This field contains the CAP Application PAN Sequence Number (APSN) of the secondary card.	
604 [2]	seg9.cap^dki^2.byte[0:1]	PIC X(2).
	This field contains the CAP Derivation Key Index (DKI) of the secondary card.	
606 [1]	seg9.bad^cap^tkn^ovrrd^flg	PIC X(1).

Offset[Len]	Field Name and Description	Data Type
	This field contains the Bad CAP Token Override Flag for the card. This field will allow the CAP Token validation to be performed, if the Bad CAP Token Validation Limit (on the CPF) has been reached. If the validation is successful, then the Bad CAP Token Validation Accumulator will be reset to zero. This mechanism is the only way that the Bad CAP Token Validation Accumulator can be reset once the limit has been reached, without deleting/re-adding or replacing the CAF record.	
607 [1]	seg9.script^tplt^tag	PIC X(1).
	This field specifies the template tag to be used when an issuer script is sent to the card. Valid values are:	
	0 - Use CPF value	
	1 - 71	
	2 - 72	
608 [1]	seg9.script^mac^lgth	PIC X(1).
	This field specifies the MAC length to be used when an issuer script is sent to the card. Valid values are:	
	0 - Use CPF value	
	4 - 4 bytes	
	6 - 6 bytes	
	8 - 8 bytes	
609 [1]	seg9.user^fld	PIC X(1).
	This field is not used and should be blank filled.	
610 [256]	seg12 [CRDCAFX-DISPLAY]	
610 [4]	seg12.seg^lgth.byte[0:3]	PIC 9(4).
	This field contains the card segment length. Always set to 248 when BASE24-card present.	
614 [4]	seg12.branch^num.byte[0:3]	PIC X(4).
	Branch identifier for this cardholder. (For identification only - not a key field).	
618 [2]	seg12.dept^num.byte[0:1]	PIC X(2).
	Department identifier for this cardholder. (For identification only - not a key field).	
620 [1]	seg12.pin^mailer	PIC X(1).
	This field singles out records which would reflect a cardholder pin and whether or not a pin mailer is	

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

required with this card. Valid values are:

0 = No

1 = Yes

621	[1]	seg12.card^carrier	PIC X(1).
-----	-----	--------------------	-----------

This field singles out records which would reflect a cardholder card and whether or not a cardholder is required with this card. Valid values are:

0 = No

1 = Yes

622	[1]	seg12.crdhldr^title	PIC X(1).
-----	-----	---------------------	-----------

This field reflects the sex of the cardholder and is intended for statistical and marketing use. Valid values are:

0 = N/A

1 = Mr.

2 = Mrs.

3 = Miss

4 = Ms.

5 = Dr.

623	[40]	seg12.open^text1.byte[0:39]	PIC X(40).
-----	------	-----------------------------	------------

This field is an alternate key and is used to locate records using a soundex algorithm.

663	[30]	seg12.name^line^1.byte[0:29]	PIC X(30).
-----	------	------------------------------	------------

This field contains the data in the format it is to be embossed on card line 1 and optionally placed on Track 1. Cardholder name. Used in embossing, addresses.

693	[30]	seg12.name^line^2.byte[0:29]	PIC X(30).
-----	------	------------------------------	------------

Optional second name line. May be used in embossing.

723	[34]	seg12.addr^line^1.byte[0:33]	PIC X(34).
-----	------	------------------------------	------------

Mandatory first address line.

757	[34]	seg12.addr^line^2.byte[0:33]	PIC X(34).
-----	------	------------------------------	------------

Optional second address line.

791	[22]	seg12.city.byte[0:21]	PIC X(22).
-----	------	-----------------------	------------

Mandatory city name.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

813	[3]	seg12.state.byte[0:2]	PIC X(3).
-----	-----	-----------------------	-----------

State code (US states or Canadian provinces).

816	[9]	seg12.postal^code.byte[0:8]	PIC X(9).
-----	-----	-----------------------------	-----------

ZIP+4 (USA) or optional alphanumeric (foreign).

825	[3]	seg12.country^code.byte[0:2]	PIC X(3).
-----	-----	------------------------------	-----------

Country code

828	[2]	seg12.issue^stat.byte[0:1]	PIC X(2).
-----	-----	----------------------------	-----------

Lifetime count of plastics issued for this record.

This table contains the card account status for this cardholder. If an institution does not use member numbers, this field reflects the status for all cards issued for this account. Valid values are:

00 = Normal (no issue status)
 01 = New issue
 02 = Force issue
 03 = Mass issue
 04 = Expired
 05 = Due to purge
 07 = Due for reissue
 09 = Suspend further issue
 11 = New issue - In manufacture
 12 = Force issue - In manufacture
 13 = Mass issue - In manufacture
 17 = Reissue - In manufacture

830	[4]	seg12.issue^num.byte[0:3]	PIC 9(4).
-----	-----	---------------------------	-----------

This field records how many issues an individual card has been through. If an institution does not use member numbers, this field records how many issues all cards of from this account have been through.

834	[4]	seg12.cards^to^issue.byte[0:3]	PIC 9(4).
-----	-----	--------------------------------	-----------

This field contains the number of cards to be embossed from this entry.

838	[4]	seg12.cards^issued.byte[0:3]	PIC 9(4).
-----	-----	------------------------------	-----------

Lifetime count of plastics issued for this record.

842	[4]	seg12.cards^ret.byte[0:3]	PIC 9(4).
-----	-----	---------------------------	-----------

Lifetime count of plastics returned for this record.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

846	[1]	seg12.sec^char	PIC X(1).
-----	-----	----------------	-----------

This field contains a one byte security character that can be embossed on the card.

847	[6]	seg12.issue^dat [DAT]	
-----	-----	-----------------------	--

This field contains the date of the last issue. If an institution does not use member numbers, this field reflects the date of the last card issued for this account.

847	[2]	seg12.issue^dat.yy.byte[0:1]	PIC X(2).
-----	-----	------------------------------	-----------

849	[2]	seg12.issue^dat.mm.byte[0:1]	PIC X(2).
-----	-----	------------------------------	-----------

851	[2]	seg12.issue^dat.dd.byte[0:1]	PIC X(2).
-----	-----	------------------------------	-----------

853	[6]	seg12.effective^dat [DAT]	
-----	-----	------------------------------	--

This field contains the date that the card becomes effective. This field is for informational purposes only and may be embossed on the card.

853	[2]	seg12.effective^dat.yy.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

855	[2]	seg12.effective^dat.mm.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

857	[2]	seg12.effective^dat.dd.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

859	[3]	seg12.cvv^value.byte[0:2]	PIC X(3).
-----	-----	---------------------------	-----------

This field contains the VISA card verification value.

862	[3]	seg12.srv^cde.byte[0:2]	PIC 9(3).
-----	-----	-------------------------	-----------

This field contains the card's 3-digit Service Code.

865	[1]	seg12.user^fld1	PIC X(1).
-----	-----	-----------------	-----------

866	[184]	seg17 [SSBBCAFX-DISPLAY]	
-----	-------	--------------------------	--

The following fields make up the BASE24-atm Self-Service Banking Base segment of the Cardholder Authorization File (CAF) Refresh Format.

866	[4]	seg17.lgth.byte[0:3]	PIC 9(4).
-----	-----	----------------------	-----------

The length of the BASE24-atm Self-Service Banking Base segment. The value in this field must be set to

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

0184 or 0004 dependent upon whether the SSBB segment data is present or not. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

870 [160]	seg17.super^tlr^term^id[0:9]	PIC X(16).
-----------	------------------------------	------------

Identifies terminals at which Super Teller transactions can be performed. Up to ten terminals can be specified. Super Teller transactions are initiated via Super Teller Cards. A Super Teller card is indicated by a card type of ST.

1030 [20]	seg17.user^fld.byte[0:19]	PIC X(20).
-----------	---------------------------	------------

This field is not used and should be blank filled.

1050 [68]	seg18 [SSBCCAFX-DISPLAY]	
-----------	--------------------------	--

The following fields make up the BASE24-atm Self-Service Banking Check segment of the Cardholder Authorization File (CAF) Refresh Format.

1050 [4]	seg18.lgth.byte[0:3]	PIC 9(4).
----------	----------------------	-----------

The length of the BASE24-atm Self-Service Banking Check segment. The value in this field must be set to 0068. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

1054 [10]	seg18.corp^num.byte[0:9]	PIC X(10).
-----------	--------------------------	------------

The Corporation that is responsible for the issuing of this check cashing card. Note this field is only applicable when the card type indicates SP (Special Purpose (Check Cashing)).

1064 [1]	seg18.chk^base^flg	PIC X(1).
----------	--------------------	-----------

A flag used to indicate whether check transactions involving checks not defined in the Check Status File should be included in the BASE aggregate usage fields and checked against the BASE aggregate limit fields. Valid values are:
Y = Yes, include in BASE processing
N = No, do not include in BASE processing

Offset[Len] Field Name and Description Data Type

1065 [1] seg18.csf^chk^base^flg PIC X(1).

A flag used to indicate whether check transactions involving checks defined in the Check Status File should be included in the BASE aggregate usage fields and checked against the BASE aggregate limit fields. Valid values are:
 Y = Yes, include in BASE processing
 N = No, do not include in BASE processing

1066 [4] seg18.csf^chk^use^lmt.byte[0:3] PIC 9(4).

The maximum number of times the card can be used to perform check transactions involving checks defined in the Check Status File during the current usage accumulation period. Valid values are 0 to 9999.

1070 [48] seg18.grp^lmt

The values in the following fields can be used to limit the amount of cash disbursements relative to check initiated transactions allowed via BASE24-atm during a single usage accumulation period.

1070 [12] seg18.grp^lmt.ttl^chk^lmt.byte[0:11] PIC 9(12).

The maximum amount of cash disbursements allowed for cash check or deposit with cash back transactions involving checks not defined in the Check Status File.

1082 [12] seg18.grp^lmt.offl^chk^lmt.byte[0:11] PIC 9(12).

The maximum accumulation of cash disbursement allowed as a result of a cash check or deposit with cash back transaction in an offline mode involving checks not defined in the Check Status File.

The amount in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

This amount cannot exceed the following amount:
 o GRP-LMT.TTL-CHK-LMT in this (SSBC) segment.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

If the CHK-BASE-FLG field is set to a value of "Y",
this amount cannot exceed the following amounts:

- o GRP-LMT.AGGR-LMT in the Base segment.
- o GRP-LMT.OFFL-AGGR-LMT in the Base segment.

1094 [12]	seg18.grp^lmt.ttl^csf^chk^lmt.byte[0:11]	PIC 9(12).
-----------	--	------------

The maximum amount of cash disbursements allowed for
cash check or deposit with cash back transactions
involving checks defined in the Check Status File.

1106 [12]	seg18.grp^lmt.offl^csf^chk^lmt.byte[0:11]	PIC 9(12).
-----------	---	------------

The maximum accumulation of cash disbursement allowed
as a result of a cash check or deposit with cash back
transaction in an offline mode involving checks
defined in the Check Status File.

The amount in this field is only used with
Authorization level 3 (online/offline), where the
authorizing host is unavailable and BASE24 performs
stand-in authorization.

This amount cannot exceed the following amount:
o GRP-LMT.CSF-TTL-CHK-LMT in this (SSBC) segment.

If the CSF-CHK-BASE-FLG field is set to a value of "Y",
this amount cannot exceed the following amounts:

- o GRP-LMT.AGGR-LMT in the Base segment.
- o GRP-LMT.OFFL-AGGR-LMT in the Base segment.

1070 [48]	seg18.chk^lmt[0:3] [REDEFINES GRP^LMT]	PIC 9(12).
-----------	---	------------

This REDEFINE allows the previous fields to be accessed
by index.

1118 [68]	seg19 [AVCAFX-DISPLAY]	
-----------	------------------------	--

The following fields make up the Address Verification
segment of the Cardholder Authorization File (CAF)
Refresh Format.

1118 [16]	seg19.segx^lgth [SEGX-LGTH]	
-----------	-----------------------------	--

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The length of the BASE24-pos Address Verification segment. The value in this field must be set to 0068. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

1118	[4]	seg19.segx^lgth.lgth.byte[0:3]	PIC 9(4).
------	-----	--------------------------------	-----------

1122	[12]	seg19.segx^lgth.seg^data	
------	------	--------------------------	--

1122	[4]	seg19.segx^lgth.seg^data.id.byte[0:3]	PIC 9(4).
------	-----	---------------------------------------	-----------

1126	[8]	seg19.segx^lgth.seg^data.b24^rsrvd.byte[0:7]	PIC X(8).
------	-----	--	-----------

1134	[20]	seg19.addr.byte[0:19]	PIC X(20).
------	------	-----------------------	------------

The cardholder billing address used when performing address verification. All information that is numeric in nature must be entered as numeric data.

1154	[9]	seg19.zip^cde.byte[0:8]	PIC X(9).
------	-----	-------------------------	-----------

The cardholder billing ZIP code used when performing address verification. Five-digit ZIP codes must be left-justified. Remaining positions must be blank.

1163	[6]	seg19.last^used.byte[0:5]	PIC 9(6).
------	-----	---------------------------	-----------

The date (YYMMDD) this segment was last refreshed.

1169	[17]	seg19.user^fld.byte[0:16]	PIC X(17).
------	------	---------------------------	------------

This field is not used and should be blank filled.

1186	[666]	seg22 [PREAUTHCAFX-DISPLAY]	
------	-------	-----------------------------	--

The following fields make up the Preauthorization holds segment of the Cardholder Authorization File (CAF) Refresh Format.

1186	[4]	seg22.lgth.byte[0:3]	PIC 9(4).
------	-----	----------------------	-----------

The length of the Preauthorization segment. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP. If configured to be supported, each

Offset[Len]	Field Name and Description	Data Type
	CAF input record must contain this segment. The segment length will vary depending on the number of preauthorization holds in this CAF record. Possible lengths are:	
	00 pre-auths = 0006 bytes	
	01 pre-auth = 0072 bytes	
	02 pre-auths = 0138 bytes	
	03 pre-auths = 0204 bytes	
	04 pre-auths = 0270 bytes	
	05 pre-auths = 0336 bytes	
	06 pre-auths = 0402 bytes	
	07 pre-auths = 0468 bytes	
	08 pre-auths = 0534 bytes	
	09 pre-auths = 0600 bytes	
	10 pre-auths = 0666 bytes	
1190 [2]	seg22.pre^auth^cnt.byte[0:1]	PIC X(2).
	The number of Preauthorization holds contained in this segment. The valid values are from "00" to "10".	
1192 [660]	seg22.pre^auth[0:9]	
	This Preauthorization structure has all of the information needed for the Preauthorization hold. There will be from zero to ten of these Preauthorization entries.	
1192 [12]	seg22.pre^auth[0:9].seq^num.byte[0:11]	PIC X(12).
	The Preauthorization sequence number for this hold entry. This field contains alpha-numeric values.	
1204 [18]	seg22.pre^auth[0:9].hold^amt.byte[0:17]	PIC 9(18).
	The hold amount for the Preauthorization hold. The field is numeric values, right-justified and zero filled.	
1222 [14]	seg22.pre^auth[0:9].pr^ts	
	The Preauthorization expiration timestamp for this hold entry.	
1222 [6]	seg22.pre^auth[0:9].pr^ts.dat [DAT]	
	The expiration timestamp date. The format for this field is YYMMDD.	
1222 [2]	seg22.pre^auth[0:9].pr^ts.dat.yy.byte[0:1]	PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

1224	[2]	seg22.pre^auth[0:9].pr^ts.dat.mm.byte[0:1]	PIC X(2).
------	-----	--	-----------

1226	[2]	seg22.pre^auth[0:9].pr^ts.dat.dd.byte[0:1]	PIC X(2).
------	-----	--	-----------

1228	[8]	seg22.pre^auth[0:9].pr^ts.tim [TIM]	
------	-----	--	--

The expiration timestamp time. The format for this field is HHMMSSSTT.

1228	[2]	seg22.pre^auth[0:9].pr^ts.tim.hh.byte[0:1]	PIC X(2).
------	-----	--	-----------

1230	[2]	seg22.pre^auth[0:9].pr^ts.tim.mm.byte[0:1]	PIC X(2).
------	-----	--	-----------

1232	[2]	seg22.pre^auth[0:9].pr^ts.tim.ss.byte[0:1]	PIC X(2).
------	-----	--	-----------

1234	[2]	seg22.pre^auth[0:9].pr^ts.tim.tt.byte[0:1]	PIC X(2).
------	-----	--	-----------

1236	[2]	seg22.pre^auth[0:9].acct^typ.byte[0:1]	PIC X(2).
------	-----	--	-----------

The account type for the account associated with this Preauthorization hold entry. Valid values are

01-09 = Checking
11-19 = Savings
31-39 = Credit

Specific values reserved by one or more BASE24 products are listed below. All of these account types are not supported by all BASE24 products.

01 = Checking
11 = Savings
12 = Individual retirement
13 = Certified deposit
21 = NOW
31 = Credit
32 = Credit line
41 = Installment
42 = Mortgage
43 = Commercial
50 = Utility
51-55 = Utility (1 to 5)
90 = General ledger

1238	[19]	seg22.pre^auth[0:9].acct.byte[0:18]	PIC X(19).
------	------	-------------------------------------	------------

The account number for the Preauthorization hold entry. This field is left-justified and blank filled.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

1257	[1]	seg22.pre^auth[0:9].user^fld	PIC X(1).
------	-----	------------------------------	-----------

This field is not used

1852	[162]	seg23 [NCDCAFX-DISPLAY]	
------	-------	-------------------------	--

The following fields make up the Non-Currency Dispense (NCD) segment of the Cardholder Authorization File (CAF) Refresh Format.

1852	[4]	seg23.lgth.byte[0:3]	PIC 9(4).
------	-----	----------------------	-----------

The length of the BASE24-atm Non-Currency Dispense segment. The value in this field must be set to 0162. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

1856	[4]	seg23.use^lmt.byte[0:3]	PIC 9(4).
------	-----	-------------------------	-----------

The maximum number of times the card may be used to perform a non-currency dispense transaction during a single usage accumulation period.

1860	[12]	seg23.cash^val^ttl^wdl^lmt.byte[0:11]	PIC 9(12).
------	------	---------------------------------------	------------

The maximum amount of cash value transactions allowed against non-credit accounts during a single usage accumulation period.

1872	[12]	seg23.cash^val^offl^wdl^lmt.byte[0:11]	PIC 9(12).
------	------	--	------------

The maximum amount of cash value transactions allowed offline against non-credit accounts during a single usage accumulation period.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

1884	[12]	seg23.cash^val^ttl^cca^lmt.byte[0:11]	PIC 9(12).
------	------	---------------------------------------	------------

The maximum amount of cash value transactions allowed

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

against credit accounts during a single usage accumulation period.

1896 [12]	seg23.cash^val^offl^cca^lmt.byte[0:11]	PIC 9(12).
-----------	--	------------

The maximum amount of cash value transactions allowed offline against credit accounts during a single usage accumulation period.

The value in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

1908 [2]	seg23.ncd1^cde.byte[0:1]	PIC X(2).
----------	--------------------------	-----------

The code of the hopper contents for which the NCD1 fields pertain.

1910 [12]	seg23.ncd1^ttl^wdl^lmt.byte[0:11]	PIC 9(12).
-----------	-----------------------------------	------------

The maximum amount of transactions made against non-credit accounts for the item type identified by the content code (NCD1-CDE).

1922 [12]	seg23.ncd1^offl^wdl^lmt.byte[0:11]	PIC 9(12).
-----------	------------------------------------	------------

The maximum amount of transactions made offline against non-credit accounts for the item type identified by the content code (NCD1-CDE).

The amount in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

1934 [12]	seg23.ncd1^ttl^cca^lmt.byte[0:11]	PIC 9(12).
-----------	-----------------------------------	------------

The maximum amount of transactions made against credit accounts for the item type identified by the content code (NCD1-CDE).

1946 [12]	seg23.ncd1^offl^cca^lmt.byte[0:11]	PIC 9(12).
-----------	------------------------------------	------------

The maximum amount of transactions made offline

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

against credit accounts for the item type identified by the content code (NCD1-CDE).

The amount in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

1958	[2]	seg23.ncd2^cde.byte[0:1]	PIC X(2).
------	-----	--------------------------	-----------

The code of the hopper contents for which the NCD2 limit fields pertain.

1960	[12]	seg23.ncd2^ttl^wdl^lmt.byte[0:11]	PIC 9(12).
------	------	-----------------------------------	------------

The maximum amount of transactions made against non-credit accounts for the item type identified by the content code (NCD2-CDE).

1972	[12]	seg23.ncd2^offl^wdl^lmt.byte[0:11]	PIC 9(12).
------	------	------------------------------------	------------

The maximum amount of transactions made offline against non-credit accounts for the item type identified by the content code (NCD2-CDE).

The amount in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

1984	[12]	seg23.ncd2^ttl^cca^lmt.byte[0:11]	PIC 9(12).
------	------	-----------------------------------	------------

The maximum amount of transactions made against credit accounts for the item type identified by the content code (NCD2-CDE).

1996	[12]	seg23.ncd2^offl^cca^lmt.byte[0:11]	PIC 9(12).
------	------	------------------------------------	------------

The maximum amount of transactions made offline against credit accounts for the item type identified by the content code (NCD2-CDE).

The amount in this field is only used with Authorization level 3 (online/offline), where the authorizing host is unavailable and BASE24 performs stand-in authorization.

Offset[Len] Field Name and Description Data Type

2008 [6] seg23.last^used.byte[0:5] PIC 9(6).

The date (YYMMDD) the card was last used for non-currency dispense transactions. The date in this field should be less than the beginning date of the current withdrawal period. (Refresh does not verify this, however.)

2014 [80] seg27 [PFRD-TXN-CAFX-DISPLAY]

The following fields make up the preferred transaction segment of the Cardholder Authorization File (CAF). This segment contains the information associated with the cardholder's preferred transaction.

2014 [16] seg27.segx^lgth [SEGX-LGTH]

2014 [4] seg27.segx^lgth.lgth.byte[0:3] PIC 9(4).

2018 [12] seg27.segx^lgth.seg^data

2018 [4] seg27.segx^lgth.seg^data.id.byte[0:3] PIC 9(4).

2022 [8] seg27.segx^lgth.seg^data.b24^rsrvd.byte[0:7] PIC X(8).

2030 [19] seg27.acct [ACCT]

The account number of the cardholder's preferred transaction.

2030 [19] seg27.acct.acct^num.byte[0:18] PIC X(19).

2049 [2] seg27.tran^cde.byte[0:1] PIC X(2).

The transaction code for the cardholder's preferred transaction.

2051 [2] seg27.from^acct^typ.byte[0:1]
[ACCT-TYP] PIC X(2).

The "from" account type for the cardholder's preferred transaction.

Offset[Len] Field Name and Description Data Type

2079 [15] seg27.user^fld^aci.byte[0:14] PIC X(15).

USER-FLD-ACI is reserved for future BASE24 product use only.

2094 [550] seg31 [ACCTCAFX-DISPLAY]

The following fields make up the Account Information segment of the Cardholder Authorization File (CAF) Refresh Format.

2094 [4] seg31.lgth.byte[0:3] PIC 9(4).

The length of the Accounts segment. This varies depending on the number of accounts associated with the CAF record. Possible lengths are:

00 accounts = 0006 bytes
 01 account = 0040 bytes
 02 accounts = 0074 bytes
 03 accounts = 0108 bytes
 04 accounts = 0142 bytes
 05 accounts = 0176 bytes
 06 accounts = 0210 bytes
 07 accounts = 0244 bytes
 08 accounts = 0278 bytes
 09 accounts = 0312 bytes
 10 accounts = 0346 bytes
 11 accounts = 0380 bytes
 12 accounts = 0414 bytes
 13 accounts = 0448 bytes
 14 accounts = 0482 bytes
 15 accounts = 0516 bytes
 16 accounts = 0550 bytes

2098 [2] seg31.acct^cnt.byte[0:1] PIC X(2).

The actual number of application accounts associated with this CAF record. Valid values are from "00" to "16".

2100 [544] seg31.acct[0:15]

The following fields make up a table containing application account information for multiple account support. (For example, with BASE24, institutions can

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

accommodate cardholders who want to access more than one checking, savings, and/or credit account with a single card.)

2100 [2]	seg31.acct[0:15].typ.byte[0:1]	PIC X(2).
----------	--------------------------------	-----------

A code indicating the type of account. The general ranges of values supported by all BASE24 products are:

01-09 = Checking
11-19 = Savings
31-39 = Credit

Specific values reserved by one or more BASE24 products are listed below. All of these account types are not supported by all BASE24 products.

01 = Checking
11 = Savings
12 = Individual retirement
13 = Certified deposit
21 = NOW
31 = Credit
32 = Credit line
41 = Installment
42 = Mortgage
43 = Commercial
50 = Utility
51-55 = Utility (1 to 5)
90 = General ledger

2102 [19]	seg31.acct[0:15].num.byte[0:18]	PIC X(19).
-----------	---------------------------------	------------

The application account number. The value in this field is left-justified and blank-filled to the right.

2121 [1]	seg31.acct[0:15].stat	PIC X(1).
----------	-----------------------	-----------

A code indicating the status of the account. Values are:

0, A, B, C = No relationship (inactive account)
1, D, E, F, G, H, I = Open
2, J, K, L = Restricted to deposits
3, M, N, O, P, Q, R = Open primary account
4, S, T, U = Restricted primary account
9, V, W, Y, Z = Closed

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

NOTE: BASE24 does not distinguish between the alphabetic and numeric values grouped together above. The alphabetic values are intended to give institutions a wider range of values for assigning account statuses.

2122 [10]	seg31.acct[0:15].descr.byte[0:9]	PIC X(10).
-----------	----------------------------------	------------

A text description of the account or the account issuer's Routing Transit Number (RTTN).

2122 [10]	seg31.acct[0:15].ach^rttn.byte[0:9] [REDEFINES DESCR]	PIC X(10).
-----------	--	------------

The following REDEFINE of the DESCR field will contain the account issuer's Routing Transit Number (RTTN) if the specified account is an ACH debit account. Please refer to the ACCT.ACH-IND field for further details.

2132 [1]	seg31.acct[0:15].corp	PIC X(1).
----------	-----------------------	-----------

NOTE: This flag was used only in conjunction with BASE24-cash manager, but has been expanded to enable ACH debit support. See ACH-IND redefinition below.

2132 [1]	seg31.acct[0:15].ach^ind [REDEFINES CORP]	PIC X(1).
----------	--	-----------

A flag indicating whether the specified account is an ACH debit account. Valid value are:
A = ACH, this is an ACH debit account
_ = This account is not an ACH debit account (_ denotes blank)

Please note that an ACH debit account is only allowed if the specified account is a checking (ACCT.TYP = 01 through 09) or savings (ACCT.TYP = 11 through 19) account type.

2133 [1]	seg31.acct[0:15].qual	PIC X(1).
----------	-----------------------	-----------

A value used to differentiate between various customer accounts which have the same account type. Valid values are "0", "1", "2", and "3".

MM/DD/YY HH:MM \$VOLUME BA60DDL CAFXD

PAGE: 49

Offset[Len] Field Name and Description

Data Type

END [size 2644]

Offset[Len] Field Name and Description Data Type

DEF NEGXD

0 [254]

0 [56] seg0 [NEGXBASE-DISPLAY]

The following fields make up the Base segment of the Negative Card File (NEG) Refresh Format.

0 [4] seg0.lgth.byte[0:3] PIC 9(4).

The length of the Base segment. The value in this field must be set to 0056.

4 [9] seg0.cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual NEG records.

13 [22] seg0.prikey

The primary key of the file record.

13 [19] seg0.prikey.pan.byte[0:18] PIC X(19).

The Primary Account Number (PAN) as it appears on Track 2 of the card (which includes the card issuer identifier and the cardholder's individual account number).

32 [3] seg0.prikey.mbr^num.byte[0:2]
[MBR-NUM] PIC 9(3).

The member number for the card. If member numbers are not used, the value in this field must be set to 000.

35 [1] seg0.rec^typ PIC X(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

A code indicating the operation to be performed on the NEG record. Valid values are:

A = Add
 C = Change
 D = Delete
 F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value of F is required for full-file refreshes.

36	[2]	seg0.crd^typ.byte[0:1]	PIC X(2).
----	-----	------------------------	-----------

One- or two-character codes are used to identify card types in files throughout BASE24. The same codes must be used for a particular card type in all of the files. These codes are also used to identify service types in BASE24-pos. Codes used in this field are either reserved by BASE24 or user-defined. Reserved codes are to be used only as defined, and include:

AD = Administrative (BASE24-atm only)
 AX = American Express credit
 BD = Business deposit (BASE24-atm and BASE24-teller only)
 C* = Private label credit (includes C, C0-C9, CA, and CC-CZ)
 CB = Carte Blanche credit
 D = Demonstration (BASE24-atm only)
 DC = Diners Club credit
 DS = Discover (Sears) credit
 M = MasterCard credit
 MD = MasterCard debit (See BASE24-pos note below)
 MM = MasterCard dual (See BASE24-pos note below)
 P* = Proprietary debit (includes P, P0-P9, and PA-PZ)
 SC = Special, Check (BASE24-pos only)
 SP = Special purpose (BASE24-atm Self-Service Banking Check Application only)
 ST = Super teller (BASE24-atm Self-Service Banking Base Application only)
 V = VISA credit
 VD = VISA debit (See BASE24-pos note below)
 VV = VISA dual (See BASE24-pos note below)

Codes with a first character of C, except code CB, are recommended to identify private label credit cards.

Codes with a first character of P are required to identify proprietary debit cards. BASE24 treats cards

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

with proprietary debit codes and codes MD and VD as debit cards and treats cards with all other codes as credit cards.

Administrative (AD), Business deposit (BD), Demonstration (D), Special purpose (SP), and Super teller (ST) are special-use card types used by BASE24-atm.

Business deposit (BD) is also a special-use card type used by BASE24-teller to identify cards that can only be used to initiate deposit transactions. BASE24-teller does not perform any other processing based on card type; however, BASE24 guidelines should still be used when establishing card types for BASE24-teller.

MasterCard dual (MM) and VISA dual (VV) can be processed as debit or credit card types, based on the default combo card type specified in the CPF.

Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only.

BASE24-pos NOTE: BASE24-pos does not allow MasterCard debit (MD), MasterCard dual (MM), VISA debit (VD), or VISA dual (VV) card types in the PRDF and PTDF. BASE24-pos automatically includes the MD and MM card types with the MasterCard credit (M) card type, and automatically includes the VD and VV card types with the VISA credit (V) card type.

User-defined Codes: The user can add any one- or two-character code not included in the reserved code list above, according to the following guidelines:

- o The first character must be alphabetic (A, B, D-O, and Q-Z).
- o The second character can be A-Z, 0-9, or a blank.
- o A valid COBNAMES table entry is recommended for each user-defined code.

38	[4]	seg0.fiid.byte[0:3] [FIID]	PIC X(4).
----	-----	-------------------------------	-----------

The FIID of the financial institution that issued the card associated with this NEG record.

Offset	Len	Field Name and Description	Data Type
42	[2]	seg0.rsn^cde.byte[0:1]	PIC 9(2).

A code indicating the reason this card number is contained in the NEG. Valid values are:

```

00    = Account open
01    = Lost card
02    = Stolen card
03    = Referral
04    = Maybe
05    = Denial
06    = Signature restricted
07    = Country club
08    = Account expired
09    = Commercial
10    = VIP
11    = Account closed
Other = Contact bank

```

44	[1]	seg0.capture^cde	PIC X(1).
----	-----	------------------	-----------

A code indicating whether the card should be captured when a transaction is attempted. Valid values are:

```

0      = Return card
Other = Retain card

```

45	[6]	seg0.add^dat [DAT]	
----	-----	--------------------	--

The date (YYMMDD) this record was added to the NEG.

45	[2]	seg0.add^dat.yy.byte[0:1]	PIC X(2).
----	-----	---------------------------	-----------

47	[2]	seg0.add^dat.mm.byte[0:1]	PIC X(2).
----	-----	---------------------------	-----------

49	[2]	seg0.add^dat.dd.byte[0:1]	PIC X(2).
----	-----	---------------------------	-----------

51	[4]	seg0.exp^dat.byte[0:3]	PIC X(4).
----	-----	------------------------	-----------

The expiration date (YYMM) of this NEG record. After this date, the NEG record no longer affects processing.

55	[1]	seg0.user^fld1	PIC X(1).
----	-----	----------------	-----------

Not used. This field should be left blank.

Offset[Len] Field Name and Description Data Type

56 [184] seg17 [SSBBNEGX-DISPLAY]

The following fields make up the BASE24-atm Self-Service Banking Base segment of the Negative Card File (NEG) Refresh Format.

56 [4] seg17.lgth.byte[0:3] PIC 9(4).

The length of the BASE24-atm Self-Service Banking Base segment. The value in this field must be set to 0184 or 0004 dependent upon whether the SSBB segment data is present or not. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

60 [160] seg17.super^tlr^term^id[0:9] PIC X(16).

Identifies terminals at which Super Teller transactions can be performed. Up to ten terminals can be specified. Super Teller transactions are initiated via Super Teller Cards. A Super Teller card is indicated by a card type of ST.

220 [20] seg17.user^fld.byte[0:19] PIC X(20).

240 [14] seg18 [SSBCNEGX-DISPLAY]

The following fields make up the BASE24-atm Self-Service Banking Check segment of the Negative Card File (NEG) Refresh Format.

240 [4] seg18.lgth.byte[0:3] PIC 9(4).

The length of the BASE24-atm Self-Service Banking Check segment. The value in this field must be set to 0014 or 0004 dependent upon whether the SSBC segment data is present or not. This is an optional segment controlled at the FIID level via the IDF FIID-SEG-MAP.

244 [10] seg18.corp^num.byte[0:9] PIC X(10).

The Corporation that is responsible for the issuing of this check cashing card. Note this field is only applicable when the card type indicates SP (Special Purpose (Check Cashing)).

MM/DD/YY HH:MM \$VOLUME BA60DDL NEGXD

PAGE: 55

Offset[Len] Field Name and Description

Data Type

END [size 254]

Offset[Len] Field Name and Description Data Type

DEF PBFXD

0 [1456]

0 [300] seg0 [PFBXBASE-DISPLAY]

The following fields make up the Base segment of the Positive Balance File (PBF) Refresh Format.

0 [4] seg0.lgth.byte[0:3] PIC 9(4).

The length of the Base segment. The value in this field must be set to 0300.

4 [9] seg0.cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual PBF records.

13 [25] seg0.prikey

The primary key of the file record.

13 [4] seg0.prikey.fiid.byte[0:3] [FIID] PIC X(4).

The FIID of the institution that maintains the PBF account.

17 [19] seg0.prikey.num.byte[0:18] PIC X(19).

The account number of this account. The entry in this field is left-justified and blank-filled on the right.

36 [2] seg0.prikey.typ.byte[0:1] PIC X(2).

A code indicating the type of account. The general ranges of values supported by all BASE24 products are:

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

01 - 09 = Checking (non-credit accounts).
 11 - 19 = Savings (non-credit accounts).
 31 - 39 = Credit (credit accounts).

Specific values reserved by one or more BASE24 products are listed below. (Note that not all of these account types are supported by all BASE24 products.)

01 = Checking
 11 = Savings
 12 = Individual retirement (IRA)
 13 = Certified deposit
 21 = NOW
 31 = Credit
 32 = Credit line
 41 = Installment
 42 = Mortgage
 43 = Commercial
 50 = Utility
 51 - 55 = Utility (1 to 5)
 90 = General ledger

38	[1]	seg0.acct^stat	PIC X(1).
----	-----	----------------	-----------

A code indicating the status of the account. Values are:

0, A, B, C = No relationship (inactive account)
 1, D, E, F, G, H, I = Open
 2, J, K, L = Restricted to deposits
 3, M, N, O, P, Q, R = Open primary account
 4, S, T, U = Restricted primary account
 9, V, X, W, Y, Z = Closed

NOTE: BASE24 does not distinguish between the alphabetic and numeric values grouped together above. The alphabetic values are intended to give institutions a wider range of values for assigning account statuses.

39	[1]	seg0.rec^typ	PIC X(1).
----	-----	--------------	-----------

A code indicating the operation to be performed on the PBF record. Valid values are:

A = Add
 C = Change
 D = Delete
 F = Full-file change

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

Values of A, C, and D are intended for use with partial-file refreshes. The value of F is required for full-file refreshes.

40	[18]	seg0.avail^bal.byte[0:17]	PIC 9(18).
----	------	---------------------------	------------

For non-credit accounts, this field contains the available balance.

For credit accounts, this field contains the available credit.

For negative amounts, Refresh expects the sign bit to be embedded in the low-order byte of the field. (In other words, use of the zoned-data format is required.)

58	[18]	seg0.ledg^bal.byte[0:17]	PIC 9(18).
----	------	--------------------------	------------

For non-credit accounts, this field contains the ledger balance.

For credit accounts, this field contains the credit limit.

For negative amounts, Refresh expects the sign bit to be embedded in the low-order byte of the field. (In other words, use of the zoned-data format is required.)

76	[18]	seg0.amt^on^hld.byte[0:17]	PIC 9(18).
----	------	----------------------------	------------

For non-credit accounts, this field contains the total amount of funds being held and not available to the cardholder.

For credit accounts, this field contains the credit balance.

94	[10]	seg0.ovrdrft^lmt.byte[0:9]	PIC 9(10).
----	------	----------------------------	------------

For non-credit accounts, this field contains the amount of overdraft protection available.

The value in this field is not used for credit accounts.

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

For negative amounts, Refresh expects the sign bit to be embedded in the low-order byte of the field. (In other words, use of the zoned-data format is required.)

104 [6]	seg0.last^dep^dat.byte[0:5]	PIC 9(6).
---------	-----------------------------	-----------

For non-credit accounts, this field contains the date (YYMMDD) of the last deposit or transfer to the account.

For credit accounts, this field contains the date (YYMMDD) of the last payment to the account.

110 [15]	seg0.last^dep^amt.byte[0:14]	PIC 9(15).
----------	------------------------------	------------

For non-credit accounts, this field contains the amount of the last deposit or transfer to the account.

For credit accounts, this field contains the amount of the last payment to the account.

125 [6]	seg0.last^wdl^dat.byte[0:5]	PIC 9(6).
---------	-----------------------------	-----------

For non-credit accounts, this field contains the date (YYMMDD) of the last withdrawal, transfer, or payment from the account.

For credit accounts, this field contains the date (YYMMDD) of the last charge to the account.

131 [15]	seg0.last^wdl^amt.byte[0:14]	PIC 9(15).
----------	------------------------------	------------

For non-credit accounts, this field contains the amount of the last withdrawal, transfer, or payment from the account.

For credit accounts, this field contains the amount of the last charge to the account.

146 [3]	seg0.crncy^cde.byte[0:2] [CRNCY-CDE]	PIC 9(3).
---------	---	-----------

This is the currency of the account.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

149	[1]	seg0.user^fld1	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be space filled.

150	[50]	seg0.user^fld^aci.byte[0:49]	PIC X(50).
-----	------	------------------------------	------------

USER-FLD-ACI is reserved for future BASE24 product use only. The designation of "product use only" provides ACI with the ability to deplete the number of bytes available within USER-FLD-ACI as product enhancements are introduced. When product enhancements require the addition of new fields within this file, the procedure to be followed is to deplete bytes from USER-FLD-ACI and use that number of bytes to define new fields. The new field definition(s) should precede the USER-FLD-ACI field.

200	[50]	seg0.user^fld^regn.byte[0:49]	PIC X(50).
-----	------	-------------------------------	------------

USER-FLD-REGN is reserved for ACI regional use only. Only ACI regions are allowed to use USER-FLD-REGN space.

250	[50]	seg0.user^fld^cust.byte[0:49]	PIC X(50).
-----	------	-------------------------------	------------

USER-FLD-CUST is reserved for BASE24 customer use only. Only customers are allowed to use USER-FLD-CUST space.

300	[42]	seg2 [POSPBFX-DISPLAY]	
-----	------	------------------------	--

The following fields make up the POS segment of the Positive Balance File (PBF) Refresh Format.

300	[16]	seg2.segx^lgth [SEGX-LGTH]	
-----	------	----------------------------	--

The length of the BASE24-pos segment. The value in this field must be set to 0042. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field.

300	[4]	seg2.segx^lgth.lgth.byte[0:3]	PIC 9(4).
-----	-----	-------------------------------	-----------

304	[12]	seg2.segx^lgth.seg^data	
-----	------	-------------------------	--

304	[4]	seg2.segx^lgth.seg^data.id.byte[0:3]	PIC 9(4).
-----	-----	--------------------------------------	-----------

308	[8]	seg2.segx^lgth.seg^data.b24^rsrvd.byte[0:7]	PIC X(8).
-----	-----	---	-----------

316	[15]	seg2.ttl^float.byte[0:14]	PIC 9(15).
-----	------	---------------------------	------------

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The total amount of transactions on the account for which the paperwork has not been received.

331	[2]	seg2.days^delinq.byte[0:1]	PIC 9(2).
-----	-----	----------------------------	-----------

The number of days the account has been delinquent.

333	[2]	seg2.months^active.byte[0:1]	PIC 9(2).
-----	-----	------------------------------	-----------

The number of months the account has been active. Months active is defined by the institution.

335	[2]	seg2.cycle^1.byte[0:1]	PIC 9(2).
-----	-----	------------------------	-----------

The number of times the account has been one cycle delinquent. One-cycle delinquencies are defined by the institution.

337	[2]	seg2.cycle^2.byte[0:1]	PIC 9(2).
-----	-----	------------------------	-----------

The number of times the account has been two cycles delinquent. Two-cycle delinquencies are defined by the institution.

339	[2]	seg2.cycle^3.byte[0:1]	PIC 9(2).
-----	-----	------------------------	-----------

The number of times the account has been three cycles delinquent. Three-cycle delinquencies are defined by the institution.

341	[1]	seg2.user^fld2	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be space filled.

342	[84]	seg3	[TLRPBFX-DISPLAY]
-----	------	------	-------------------

The following fields make up the Teller segment of the Positive Balance File (PBF) Refresh Format.

Offset[Len] Field Name and Description Data Type

342 [4] seg3.lgth.byte[0:3] PIC 9(4).

The length of the BASE24-teller segment. The value in this field must be set to 0084. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field.

346 [1] seg3.confidential^flg PIC X(1).

Currently not used by BASE24-teller.

347 [1] seg3.sp^stat PIC X(1).

A flag indicating if stop payments or warnings have been placed on this account. Valid values are:

0 = No stops or warnings
1 = Stops
2 = Warnings
3 = Stops and Warnings

348 [18] seg3.accrued^interest^ytd.byte[0:17] PIC 9(18).

The year-to-date accrued interest on this account.

366 [18] seg3.strt^bal.byte[0:17] PIC 9(18).

The ledger balance of the account as of the last refresh.

384 [18] seg3.passbook^bal.byte[0:17] PIC 9(18).

The customer's passbook balance as of the last passbook update.

402 [4] seg3.nbf^rec^cnt.byte[0:3] PIC 9(4).

The number of entries for the account in the No Book File (NBF).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

406	[9]	seg3.sig^crd^loc.byte[0:8]	PIC X(9).
-----	-----	----------------------------	-----------

The location of the signature card for the account.

415	[1]	seg3.passbook^ind	PIC X(1).
-----	-----	-------------------	-----------

A flag indicating whether the account is a passbook account. Valid values are:

Y = Yes, this is a passbook account.

N = No, this is not a passbook account.

416	[1]	seg3.cust^class	PIC X(1).
-----	-----	-----------------	-----------

A flag that specifies how much cash is available to the customer after a check deposit. There are ten possible options that are defined by each institution and maintained on the Institution Definition File (IDF). Valid values are 0 through 9.

417	[4]	seg3.cashout^lmt.byte[0:3]	PIC 9(4).
-----	-----	----------------------------	-----------

The maximum amount (in thousands) that may be disbursed on the account via BASE24-teller during a processing day. If this field contains zeros, this means that the account involved is exempt from limit checking.

421	[4]	seg3.cashin^lmt.byte[0:3]	PIC 9(4).
-----	-----	---------------------------	-----------

The maximum amount (in thousands) that may be deposited to the account via BASE24-teller during a processing day. If this field contains zeros, this means that the account involved is exempt from limit checking.

425	[1]	seg3.user^fld1	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be space filled.

426	[84]	seg14	[TBPBFX-DISPLAY]
-----	------	-------	------------------

The following fields make up the Telebanking segment

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

of the Positive Balance File (PBF) Refresh Format.

426	[4]	seg14.lgth.byte[0:3]	PIC 9(4).
-----	-----	----------------------	-----------

The length of the Telebanking segment. The value in this field must be set to 0004 or 0084 dependent on whether a Telebanking segment is present or not. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field. If configured to be supported, each PBF input record must contain this segment. The segment length will vary depending on whether the PBF record contains Telebanking data.

430	[15]	seg14.cash^adv^min.byte[0:14]	PIC 9(15).
-----	------	-------------------------------	------------

The minimum cash advance amount, in whole currency units (e.g., dollars), allowed by BASE24-telebanking. A value of zero indicates no minimum is required. This field applies to transactions which debit the account.
Note: This field is relevant only for credit-type accounts.

This amount cannot exceed the amounts specified in the amount limit fields in this segment of the PBF, if those limit amounts are non-zero.

445	[15]	seg14.cash^adv^incr.byte[0:14]	PIC 9(15).
-----	------	--------------------------------	------------

The standard increment, in whole currency units (e.g., dollars), over the minimum cash advance amount required by BASE24-telebanking. A value of zero indicates no increment is required. This field applies to transactions which debit the account. Note: This field is relevant only for credit-type accounts.

For example, if the value in the CASH-ADV-MIN field is set to \$100 and the value in the CASH-ADV-INCR field is set to \$50, then allowable cash advance amounts include \$100, \$150, \$200, etc.

460	[19]	seg14.prd^lmt	
-----	------	---------------	--

The following sets of limits define limits for transfers (intrabank) and payments during the usage period specified in the Telebanking segment of the IDF.

460	[19]	seg14.prd^lmt.xfer	
-----	------	--------------------	--

460	[15]	seg14.prd^lmt.xfer.amt.byte[0:14]	PIC 9(15).
-----	------	-----------------------------------	------------

The maximum amount of money which may be debited from

Offset[Len]	Field Name and Description	Data Type
	the account during the specified usage period for transfer and payment transactions involving this account as the FROM account. This is expressed in whole units of the account-issuing FI's currency.	
475 [4]	seg14.prd^lmt.xfer.cnt.byte[0:3]	PIC 9(4).
	The maximum number of times money may be debited from the account during the specified usage period for transfer and payment transactions involving this account as the FROM account.	
479 [19]	seg14.cyc^lmt	
	The following sets of limits define limits for transfers (intrabank) and payments during the usage cycle specified in the Telebanking segment of the IDF.	
479 [19]	seg14.cyc^lmt.xfer	
479 [15]	seg14.cyc^lmt.xfer.amt.byte[0:14]	PIC 9(15).
	The maximum amount of money which may be debited from the account during the specified usage period for transfer and payment transactions involving this account as the FROM account. This is expressed in whole units of the account-issuing FI's currency.	
494 [4]	seg14.cyc^lmt.xfer.cnt.byte[0:3]	PIC 9(4).
	The maximum number of times money may be debited from the account during the specified usage period for transfer and payment transactions involving this account as the FROM account.	
498 [6]	seg14.last^prd^reset^dat [DAT]	
	This field contains the date that the period usage accumulators were last reset to zero.	
498 [2]	seg14.last^prd^reset^dat.yy.byte[0:1]	PIC X(2).
500 [2]	seg14.last^prd^reset^dat.mm.byte[0:1]	PIC X(2).
502 [2]	seg14.last^prd^reset^dat.dd.byte[0:1]	PIC X(2).
504 [6]	seg14.last^cyc^reset^dat [DAT]	
	This field contains the date that the cycle usage accumulators were last reset to zero.	
504 [2]	seg14.last^cyc^reset^dat.yy.byte[0:1]	PIC X(2).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

506	[2]	seg14.last^cyc^reset^dat.mm.byte[0:1]	PIC X(2).
-----	-----	---------------------------------------	-----------

508	[2]	seg14.last^cyc^reset^dat.dd.byte[0:1]	PIC X(2).
-----	-----	---------------------------------------	-----------

510	[26]	seg15 [CRLINEPBFX-DISPLAY]	
-----	------	----------------------------	--

The following fields make up the Credit Line segment of the Positive Balance File (PBF) Refresh Format.

510	[4]	seg15.lgth.byte[0:3]	PIC 9(4).
-----	-----	----------------------	-----------

The length of the credit line segment. The value in this field must be set to 0004 or 0026 dependent on whether a credit line segment is present or not. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field.

514	[2]	seg15.cr^line^acct^typ.byte[0:1]	PIC X(2).
-----	-----	----------------------------------	-----------

The account type associated with the backup account. The account type will represent the actual PBF account type and will be used as part of the key to read the PBF record for the backup account.

516	[19]	seg15.cr^line^acct.byte[0:18]	PIC X(19).
-----	------	-------------------------------	------------

The account number associated with the backup account. This account number will represent the actual PBF account number and will be used as part of the key to read the PBF record for the backup account. The account number will be left-justified and blank-filled.

535	[1]	seg15.user^fld	PIC X(1).
-----	-----	----------------	-----------

This field is not used and should be space filled.

536	[44]	seg16 [NAMPBFX-DISPLAY]	
-----	------	-------------------------	--

The following fields make up the Customer Short Name segment of the Positive Balance File (PBF) Refresh Format.

536	[4]	seg16.lgth.byte[0:3]	PIC 9(4).
-----	-----	----------------------	-----------

The length of the customer short name segment. The value in this field must be set to 0044. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field.

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

540	[40]	seg16.cust^short^nam.byte[0:39]	PIC X(40).
-----	------	---------------------------------	------------

The customer short name, left-justified and blank-filled.

580	[430]	seg21 [CSFCPBFX-DISPLAY]	
-----	-------	--------------------------	--

The following fields make up the Customer Service/Fraud Control segment of the PBF. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field. This segment is not required. If this segment is not present, the LGTH must be set to 0004.

580	[4]	seg21.lgth.byte[0:3]	PIC 9(4).
-----	-----	----------------------	-----------

The length of the Customer Service/Fraud Control segment. The segment length will vary depending on the number of cycles present in the record. Possible lengths are:

00 cycles = 0070 bytes
 01 cycles = 0100 bytes
 02 cycles = 0130 bytes
 03 cycles = 0160 bytes
 04 cycles = 0190 bytes
 05 cycles = 0220 bytes
 06 cycles = 0250 bytes
 07 cycles = 0280 bytes
 08 cycles = 0310 bytes
 09 cycles = 0340 bytes
 10 cycles = 0370 bytes
 11 cycles = 0400 bytes
 12 cycles = 0430 bytes

584	[18]	seg21.prior^ytd^intrst.byte[0:17]	PIC X(18).
-----	------	-----------------------------------	------------

Prior year-to-date interest. For credit accounts, this represents the amount of interest charged. For debit accounts, this represents the amount of interest earned. This field is optional; the default is zero.

602	[8]	seg21.cur^intrst^rate.byte[0:7]	PIC 9(8).
-----	-----	---------------------------------	-----------

Current interest rate. For credit accounts, this will be the rate of interest charged. For debit accounts, this will be the rate of interest earned. This field is optional; the default is zeroes. If data is entered,

Offset[Len]	Field Name and Description	Data Type
	the first byte will indicate the scale (number of digits to the right of the decimal point).	
610 [8]	seg21.cash^adv^intrst^rate.byte[0:7]	PIC 9(8).
	Cash advance interest rate for a credit account. This field is optional; the default is zeroes. If data is entered, the first byte will indicate the scale (number of digits to the right of the decimal point).	
618 [18]	seg21.min^amt^due.byte[0:17]	PIC X(18).
	Minimum amount due for a credit account. This field is optional; the default is zero.	
636 [6]	seg21.next^pmnt^due^dat [DAT]	
	Next payment due date (YYMMDD) for a credit account. This field is optional; the default is spaces.	
636 [2]	seg21.next^pmnt^due^dat.yy.byte[0:1]	PIC X(2).
638 [2]	seg21.next^pmnt^due^dat.mm.byte[0:1]	PIC X(2).
640 [2]	seg21.next^pmnt^due^dat.dd.byte[0:1]	PIC X(2).
642 [6]	seg21.cr^ovrdft^lmt^chng^dat [DAT]	
	Date the Credit Limit/Overdraft Limit was last changed in the format YYMMDD. This field is optional; the default is spaces.	
642 [2]	seg21.cr^ovrdft^lmt^chng^dat.yy.byte[0:1]	PIC X(2).
644 [2]	seg21.cr^ovrdft^lmt^chng^dat.mm.byte[0:1]	PIC X(2).
646 [2]	seg21.cr^ovrdft^lmt^chng^dat.dd.byte[0:1]	PIC X(2).
648 [2]	seg21.cyc^cnt.byte[0:1]	PIC X(2).
	Number of cycles present in this record. A record may contain up to 12 cycles.	
650 [360]	seg21.cyc^data[0:11]	
650 [10]	seg21.cyc^data[0:11].db^cr^hist.byte[0:9]	PIC 9(10).

Offset[Len]	Field Name and Description	Data Type
650 [10]	seg21.cyc^data[0:11].db^hist [REDEFINES DB^CR^HIST] Debit account history.	
650 [5]	seg21.cyc^data[0:11].db^hist.nsf.byte[0:4] Number of times the account did not have sufficient funds for the particular cycle. This field is optional; the default is zero.	PIC 9(5).
655 [5]	seg21.cyc^data[0:11].db^hist.ovrdft.byte[0:4] Number of times account was overdrawn for the particular cycle. This field is optional; the default is zero.	PIC 9(5).
650 [10]	seg21.cyc^data[0:11].cr^hist [REDEFINES DB^CR^HIST] Credit account history.	
650 [5]	seg21.cyc^data[0:11].cr^hist.num^delinq.byte[0:4] Number of delinquent payments for the particular cycle. This field is optional; the default is zero.	PIC 9(5).
655 [5]	seg21.cyc^data[0:11].cr^hist.num^cr^lmt^exceed.byte[0:4] Number of times the credit limit was exceeded during the particular cycle. This field is optional; the default is zero.	PIC 9(5).
660 [18]	seg21.cyc^data[0:11].acct^bal.byte[0:17] Account balance for the particular cycle. This field is optional; the default is zero.	PIC X(18).
678 [1]	seg21.cyc^data[0:11].acct^stat Account status for the particular cycle. This field is optional; the default is a space.	PIC X(1).
679 [1]	seg21.cyc^data[0:11].user^fld1 Reserved for future use.	PIC X(1).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

1010	[446]	seg22	[PREAUTHPBFX-DISPLAY]
------	-------	-------	-----------------------

The following fields make up the Preauthorization holds segment of the Positive Balance File (PBF) Refresh Format.

1010	[4]	seg22.lgth.byte[0:3]	PIC 9(4).
------	-----	----------------------	-----------

The length of the Preauthorization segment. The presence of this segment is controlled at the FIID level via the IDF FIID-SEG-MAP indicator field. If configured to be supported, each PBF input record must contain this segment. The segment length will vary depending on the number of preauthorization holds in this PBF record. Possible lengths are:

```
00 pre-auths = 0006 bytes
01 pre-auth  = 0050 bytes
02 pre-auths = 0094 bytes
03 pre-auths = 0138 bytes
04 pre-auths = 0182 bytes
05 pre-auths = 0226 bytes
06 pre-auths = 0270 bytes
07 pre-auths = 0314 bytes
08 pre-auths = 0358 bytes
09 pre-auths = 0402 bytes
10 pre-auths = 0446 bytes
```

1014	[2]	seg22.pre^auth^cnt.byte[0:1]	PIC X(2).
------	-----	------------------------------	-----------

The number of Preauthorization holds contained in this segment. The valid values are from "00" to "10".

1016	[440]	seg22.pre^auth[0:9]	
------	-------	---------------------	--

This Preauthorization structure has all of the information needed for the Preauthorization hold. There will be from zero to ten of these Preauthorization entries.

1016	[12]	seg22.pre^auth[0:9].seq^num.byte[0:11]	PIC X(12).
------	------	--	------------

The Preauthorization sequence number for this hold entry. This field contains numeric values.

1028	[18]	seg22.pre^auth[0:9].hold^amt.byte[0:17]	PIC 9(18).
------	------	---	------------

The hold amount for the Preauthorization hold. The field is numeric values, right-justified and zero-filled.

Offset[Len]	Field Name and Description	Data Type
1046 [14]	seg22.pre^auth[0:9].pr^ts The Preauthorization expiration timestamp for this hold entry.	
1046 [6]	seg22.pre^auth[0:9].pr^ts.dat [DAT] The expiration timestamp date. The format for this field is YYMMDD.	
1046 [2]	seg22.pre^auth[0:9].pr^ts.dat.yy.byte[0:1]	PIC X(2).
1048 [2]	seg22.pre^auth[0:9].pr^ts.dat.mm.byte[0:1]	PIC X(2).
1050 [2]	seg22.pre^auth[0:9].pr^ts.dat.dd.byte[0:1]	PIC X(2).
1052 [8]	seg22.pre^auth[0:9].pr^ts.tim [TIM] The expiration timestamp time. The format for this field is HHMMSSSTT.	
1052 [2]	seg22.pre^auth[0:9].pr^ts.tim.hh.byte[0:1]	PIC X(2).
1054 [2]	seg22.pre^auth[0:9].pr^ts.tim.mm.byte[0:1]	PIC X(2).
1056 [2]	seg22.pre^auth[0:9].pr^ts.tim.ss.byte[0:1]	PIC X(2).
1058 [2]	seg22.pre^auth[0:9].pr^ts.tim.tt.byte[0:1]	PIC X(2).
END [size 1456]		

Offset[Len] Field Name and Description Data Type

DEF SPX-DISPLAY

0 [132]

0 [9] sx^cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape.

Header and trailer records must be reflected in this count as well as individual SPF records.

9 [1] sx^rec^typ PIC X(1).

A code indicating the operation to be performed on the SPF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value F is required for full-file refreshes.

10 [4] sx^fiid.byte[0:3] [FIID] PIC X(4).

The FIID of the financial institution owning the account.

14 [19] sx^acct^num.byte[0:18] PIC X(19).

The account number of the customer's account at the institution that has a stop payment on the check. In a BASE24-teller system, the account number must match a Positive Balance File (PBF) account number. The entry in this field must be left-justified with trailing spaces.

33 [2] sx^acct^typ.byte[0:1] PIC X(2).

The type of customer account specified in the SX-ACCT-NUM field having the stop payment record. Valid values are:

01, 02 - 09 = DDA (Checking Account)
21 = NOW

35 [11] sx^hi^chk^num.byte[0:10] PIC X(11).

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

The check number of the stop payment. For a range of check numbers, this field contains the highest check number in the range. Check numbers are right-justified and zero filled.

46	[11]	sx^lo^chk^num.byte[0:10]	PIC X(11).
----	------	--------------------------	------------

For a range of check numbers, this field will contain the lowest check number in the range. Check numbers are right-justified and zero filled. For a single check, this field will contain blanks.

57	[15]	sx^amt.byte[0:14]	PIC 9(15).
----	------	-------------------	------------

The amount of the check in whole and fractional currency units for the stop payment issued.

72	[6]	sx^dat [DAT]	
----	-----	--------------	--

The date (YYMMDD) of the stop payment.

72	[2]	sx^dat.yy.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

74	[2]	sx^dat.mm.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

76	[2]	sx^dat.dd.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

78	[8]	sx^tim [TIM]	
----	-----	--------------	--

The time (HHMMSSHH) of the stop payment.

78	[2]	sx^tim.hh.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

80	[2]	sx^tim.mm.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

82	[2]	sx^tim.ss.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

84	[2]	sx^tim.tt.byte[0:1]	PIC X(2).
----	-----	---------------------	-----------

86	[6]	sx^exp^dat [DAT]	
----	-----	------------------	--

The expiration date (YYMMDD) for the stop payment.

86	[2]	sx^exp^dat.yy.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

88	[2]	sx^exp^dat.mm.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

90	[2]	sx^exp^dat.dd.byte[0:1]	PIC X(2).
----	-----	-------------------------	-----------

92	[35]	sx^descr.byte[0:34]	PIC X(35).
----	------	---------------------	------------

A message regarding the stop payment order. It documents and displays any data about the stop payment

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

order that the institution placed on the file.

127 [5]	user^fld1.byte[0:4]	PIC X(5).
------------	---------------------	-----------

Reserved for future use.

END [size 132]