

Offset[Len] Field Name and Description Data Type

RECORD ITS-TLF

The Transaction Log File contains one record for each transaction processed by BASE24 ITS.

Each record contains data specific to the given transaction.

LCONF ASSIGN: TLF-<lcf.tlf\_asgn>

0 [4070]

0 [8] tlf^hdr [TLF-HDR]

HDR - the TLF header

0 [2] tlf^hdr.ver [VER] TYPE BINARY 16 SIGNED.

Version of the Transaction Log record.

2 [2] tlf^hdr.ctx^cde TYPE BINARY 16 SIGNED.

The type of TLF record. Valid values are:

0 = Business transaction record

4 [2] tlf^hdr.ctx^st TYPE BINARY 16 SIGNED.

The state of the context. Valid values are:

0 = not in use  
1 = compressed  
2 = journalled  
3 = live  
4 = suspended

6 [2] tlf^hdr.olf^byte^cnt TYPE BINARY 16 SIGNED.

The number of bytes logged in the Optionally Logged Fields.

8 [50] intf^key [INTF-KEY]

Interface Alternate Key definition.

8 [28] intf^key.pan [PAN]

Primary Account Number - Binary coded decimal.

8 [28] intf^key.pan.num.byte[0:27] PIC X(28).

| Offset[Len]  | Field Name and Description                                                                | Data Type              |
|--------------|-------------------------------------------------------------------------------------------|------------------------|
| 36      [8]  | intf^key.amt      [AMT]                                                                   | TYPE BINARY 64 SIGNED. |
|              | Amount of the transaction.                                                                |                        |
| 44      [12] | intf^key.seq^num.byte[0:11]<br>[ITD-SEQ-NUM]                                              | PIC X(12).             |
|              | Transaction sequence number.                                                              |                        |
| 56      [2]  | intf^key.discrim      [ITD-DISCRIM]                                                       | TYPE BINARY 16 SIGNED. |
|              | Discriminant. This value is used by interface objects for duplicate transaction checking. |                        |
| 58      [36] | pan^key      [PAN-KEY]                                                                    |                        |
|              | Primary Account Number alternate key definition.                                          |                        |
| 58      [8]  | pan^key.iss                                                                               |                        |
|              | The following two fields contain the isssuer logical network and issuer fiid.             |                        |
| 58      [4]  | pan^key.iss.lgnt.byte[0:3]<br>[LGNT-DEF]                                                  | PIC X(4).              |
|              | Issuer Logical Network.                                                                   |                        |
| 62      [4]  | pan^key.iss.fiid.byte[0:3]<br>[FIID-DEF]                                                  | PIC X(4).              |
|              | Issuer FIID.                                                                              |                        |
| 66      [28] | pan^key.pan      [PAN]                                                                    |                        |
|              | Primary Account Number - ASCII                                                            |                        |
| 66      [28] | pan^key.pan.num.byte[0:27]                                                                | PIC X(28).             |
| 94      [24] | acct^key      [ACCT-KEY]                                                                  |                        |
|              | Account number alternate key definition.                                                  |                        |
| 94      [8]  | acct^key.iss                                                                              |                        |
|              | The following two fields contain the isssuer logical network and issuer fiid.             |                        |
| 94      [4]  | acct^key.iss.lgnt.byte[0:3]<br>[LGNT-DEF]                                                 | PIC X(4).              |

| Offset | [Len] | Field Name and Description | Data Type |
|--------|-------|----------------------------|-----------|
|--------|-------|----------------------------|-----------|

Issuer Logical Network.

|    |     |                                           |           |
|----|-----|-------------------------------------------|-----------|
| 98 | [4] | acct^key.iss.fiid.byte[0:3]<br>[FIID-DEF] | PIC X(4). |
|----|-----|-------------------------------------------|-----------|

Issuer FIID.

|                                        |      |                          |  |
|----------------------------------------|------|--------------------------|--|
| 102                                    | [16] | acct^key.acct [ACCT-BCD] |  |
| Account Number - Binary coded decimal. |      |                          |  |

|     |      |                              |            |
|-----|------|------------------------------|------------|
| 102 | [14] | acct^key.acct.num.byte[0:13] | PIC X(14). |
|-----|------|------------------------------|------------|

|     |     |                    |                        |
|-----|-----|--------------------|------------------------|
| 116 | [2] | acct^key.acct.lgth | TYPE BINARY 16 SIGNED. |
|-----|-----|--------------------|------------------------|

|     |        |                       |              |
|-----|--------|-----------------------|--------------|
| 118 | [3952] | tlf^body.byte[0:3951] | PIC X(3952). |
|-----|--------|-----------------------|--------------|

The following fields contain the remainder of  
the transaction data.

END [size 4070]

Offset[Len]      Field Name and Description      Data Type

DEF TLF-EXTR

0      [920]

0      [8]      tlf^hdr      [TLF-HDR]

HDR - the TLF header

0      [2]      tlf^hdr.ver      [VER]      TYPE BINARY 16 SIGNED.

Version of the Transaction Log record.

2      [2]      tlf^hdr.ctx^cde      TYPE BINARY 16 SIGNED.

The type of TLF record. Valid values are:

0 = Business transaction record

4      [2]      tlf^hdr.ctx^st      TYPE BINARY 16 SIGNED.

The state of the context. Valid values are:

0 = not in use

1 = compressed

2 = journalled

3 = live

4 = suspended

6      [2]      tlf^hdr.olf^byte^cnt      TYPE BINARY 16 SIGNED.

The number of bytes logged in the Optionally  
Logged Fields.

8      [50]      intf^key      [INTF-KEY]

Interface Alternate Key definition.

8      [28]      intf^key.pan      [PAN]

Primary Account Number - Binary coded decimal.

8      [28]      intf^key.pan.num.byte[0:27]      PIC X(28).

36      [8]      intf^key.amt      [AMT]      TYPE BINARY 64 SIGNED.

Amount of the transaction.

44      [12]      intf^key.seq^num.byte[0:11]      PIC X(12).  
[ITD-SEQ-NUM]

Transaction sequence number.

| Offset | Len  | Field Name and Description                                                                                                                                | Data Type  |
|--------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| 56     | [2]  | intf^key.discrim<br>[ITD-DISCRIM] TYPE BINARY 16 SIGNED.<br><br>Discriminant. This value is used by interface objects for duplicate transaction checking. |            |
| 58     | [36] | pan^key [PAN-KEY]<br><br>Primary Account Number alternate key definition.                                                                                 |            |
| 58     | [8]  | pan^key.iss<br><br>The following two fields contain the isssuer logical network and issuer fiid.                                                          |            |
| 58     | [4]  | pan^key.iss.lgnt.byte[0:3]<br>[LGNT-DEF]                                                                                                                  | PIC X(4).  |
|        |      | Issuer Logical Network.                                                                                                                                   |            |
| 62     | [4]  | pan^key.iss.fiid.byte[0:3]<br>[FIID-DEF]                                                                                                                  | PIC X(4).  |
|        |      | Issuer FIID.                                                                                                                                              |            |
| 66     | [28] | pan^key.pan [PAN]<br><br>Primary Account Number - ASCII                                                                                                   |            |
| 66     | [28] | pan^key.pan.num.byte[0:27]                                                                                                                                | PIC X(28). |
| 94     | [24] | acct^key [ACCT-KEY]<br><br>Account number alternate key definition.                                                                                       |            |
| 94     | [8]  | acct^key.iss<br><br>The following two fields contain the isssuer logical network and issuer fiid.                                                         |            |
| 94     | [4]  | acct^key.iss.lgnt.byte[0:3]<br>[LGNT-DEF]                                                                                                                 | PIC X(4).  |
|        |      | Issuer Logical Network.                                                                                                                                   |            |
| 98     | [4]  | acct^key.iss.fiid.byte[0:3]<br>[FIID-DEF]                                                                                                                 | PIC X(4).  |
|        |      | Issuer FIID.                                                                                                                                              |            |
| 102    | [16] | acct^key.acct [ACCT-BCD]                                                                                                                                  |            |

Offset[Len] Field Name and Description Data Type

Account Number - Binary coded decimal.

102 [14] acct^key.acct.num.byte[0:13] PIC X(14).

116 [2] acct^key.acct.lgth TYPE BINARY 16 SIGNED.

118 [2] partial^cnt TYPE BINARY 16 SIGNED.

A value one less than the number of partial extracts that have been performed on the TLF file. This value will be used to access the last entry in the EXTR-POSITIONS array of extract position markers that has been filled.

120 [800] extr^positions[0:99]

The values in the following fields are used to hold the location of the last record extracted in the corresponding partial extract. Up to 100 partial extracts can be tracked in a given TLF file.

120 [4] extr^positions[0:99].rba TYPE BINARY 32 SIGNED.

The relative byte address of the beginning of the TLF data block that contained the last TLF record extracted in the corresponding partial extract.

124 [2] extr^positions[0:99].blk^rec^cnt TYPE BINARY 16 SIGNED.

The number of the record in the block of the last TLF record extracted in the corresponding partial extract.

126 [2] extr^positions[0:99].part^num TYPE BINARY 16 SIGNED.

For a partitioned TLF log file, this field contains the number of the partition within the TLF file that contained the last TLF record extracted in the in the corresponding partial extract.

END [size 920]

Offset[Len]      Field Name and Description      Data Type

DEF ITS-TLFXB

|    |        |                                                                         |                        |
|----|--------|-------------------------------------------------------------------------|------------------------|
| 0  | [3990] |                                                                         |                        |
| 0  | [8]    | tlf^hdr      [TLF-HDR]                                                  |                        |
|    |        | HDR - the TLF header                                                    |                        |
| 0  | [2]    | tlf^hdr.ver      [VER]                                                  | TYPE BINARY 16 SIGNED. |
|    |        | Version of the Transaction Log record.                                  |                        |
| 2  | [2]    | tlf^hdr.ctx^cde                                                         | TYPE BINARY 16 SIGNED. |
|    |        | The type of TLF record. Valid values are:                               |                        |
|    |        | 0 = Business transaction record                                         |                        |
| 4  | [2]    | tlf^hdr.ctx^st                                                          | TYPE BINARY 16 SIGNED. |
|    |        | The state of the context. Valid values are:                             |                        |
|    |        | 0 = not in use                                                          |                        |
|    |        | 1 = compressed                                                          |                        |
|    |        | 2 = journalled                                                          |                        |
|    |        | 3 = live                                                                |                        |
|    |        | 4 = suspended                                                           |                        |
| 6  | [2]    | tlf^hdr.olf^byte^cnt                                                    | TYPE BINARY 16 SIGNED. |
|    |        | The number of bytes logged in the Optionally<br>Logged Fields.          |                        |
| 8  | [336]  | bus^mlf      [BUS-MLF]                                                  |                        |
|    |        | Mandatory log fields for Business messages.                             |                        |
| 8  | [50]   | bus^mlf.alt^key1                                                        |                        |
|    |        | Alternate key 1. Only used as an alternate key by<br>interface objects. |                        |
| 8  | [28]   | bus^mlf.alt^key1.pan<br>[PAN]                                           |                        |
| 8  | [28]   | bus^mlf.alt^key1.pan.num.byte[0:27]                                     | PIC X(28).             |
| 36 | [8]    | bus^mlf.alt^key1.amt<br>[AMT]                                           | TYPE BINARY 64 SIGNED. |
| 44 | [12]   | bus^mlf.alt^key1.seq^num.byte[0:11]                                     |                        |

| Offset[Len] | Field Name and Description                                      | Data Type              |
|-------------|-----------------------------------------------------------------|------------------------|
|             | [ITD-SEQ-NUM]                                                   | PIC X(12).             |
| 56 [2]      | bus^mlf.alt^key1.discrim<br>[ITD-DISCRIM]                       | TYPE BINARY 16 SIGNED. |
| 58 [36]     | bus^mlf.alt^key2<br>Alternate key 2. Used for log file perusal. |                        |
| 58 [8]      | bus^mlf.alt^key2.iss                                            |                        |
| 58 [4]      | bus^mlf.alt^key2.iss.lgnt.byte[0:3]<br>[LGNT-DEF]               | PIC X(4).              |
| 62 [4]      | bus^mlf.alt^key2.iss.fiid.byte[0:3]<br>[FIID-DEF]               | PIC X(4).              |
| 66 [28]     | bus^mlf.alt^key2.pan<br>[PAN]                                   |                        |
| 66 [28]     | bus^mlf.alt^key2.pan.num.byte[0:27]                             | PIC X(28).             |
| 94 [24]     | bus^mlf.alt^key3<br>Alternate key 3. Used for log file perusal. |                        |
| 94 [8]      | bus^mlf.alt^key3.iss                                            |                        |
| 94 [4]      | bus^mlf.alt^key3.iss.lgnt.byte[0:3]<br>[LGNT-DEF]               | PIC X(4).              |
| 98 [4]      | bus^mlf.alt^key3.iss.fiid.byte[0:3]<br>[FIID-DEF]               | PIC X(4).              |
| 102 [16]    | bus^mlf.alt^key3.acct<br>[ACCT-BCD]                             |                        |
| 102 [14]    | bus^mlf.alt^key3.acct.num.byte[0:13]                            | PIC X(14).             |
| 116 [2]     | bus^mlf.alt^key3.acct.lgth                                      | TYPE BINARY 16 SIGNED. |
| 118 [82]    | bus^mlf.bcd<br>Mandatory logged fields - Binary                 |                        |
| 118 [18]    | bus^mlf.bcd.acct1<br>[ITD-ACCT1]                                |                        |
| 118 [16]    | bus^mlf.bcd.acct1.num^bcd<br>[ACCT-BCD]                         |                        |
| 118 [14]    | bus^mlf.bcd.acct1.num^bcd.num.byte[0:13]                        | PIC X(14).             |
| 132 [2]     | bus^mlf.bcd.acct1.num^bcd.lgth                                  | TYPE BINARY 16 SIGNED. |



| Offset | Len   | Field Name and Description                           | Data Type              |
|--------|-------|------------------------------------------------------|------------------------|
| 134    | [2]   | bus^mlf.bcd.acct1.typ.byte[0:1]<br>[ACCT-TYP-DEF]    | PIC X(2).              |
| 136    | [18]  | bus^mlf.bcd.acct2<br>[ITD-ACCT2]                     |                        |
| 136    | [16]  | bus^mlf.bcd.acct2.num^bcd<br>[ACCT-BCD]              |                        |
| 136    | [14]  | bus^mlf.bcd.acct2.num^bcd.num.byte[0:13]             | PIC X(14).             |
| 150    | [2]   | bus^mlf.bcd.acct2.num^bcd.lgth                       | TYPE BINARY 16 SIGNED. |
| 152    | [2]   | bus^mlf.bcd.acct2.typ.byte[0:1]<br>[ACCT-TYP-DEF]    | PIC X(2).              |
| 154    | [2]   | bus^mlf.bcd.acq^obj^id<br>[ITD-ACQ-OBJ-ID]           | TYPE BINARY 16 SIGNED. |
| 156    | [2]   | bus^mlf.bcd.auth^obj^id<br>[ITD-AUTH-OBJ-ID]         | TYPE BINARY 16 SIGNED. |
| 158    | [2]   | bus^mlf.bcd.msg^substate<br>[ITD-MSG-SUBSTATE]       | TYPE BINARY 16 SIGNED. |
| 160    | [2]   | bus^mlf.bcd.prod^id<br>[ITD-PROD-ID]                 | TYPE BINARY 16 SIGNED. |
| 162    | [22]  | bus^mlf.bcd.refr<br>[ITD-REFR]                       |                        |
| 162    | [2]   | bus^mlf.bcd.refr.cnt                                 | TYPE BINARY 16 SIGNED. |
| 164    | [20]  | bus^mlf.bcd.refr.file[0:9]                           |                        |
| 164    | [1]   | bus^mlf.bcd.refr.file[0:9].typ                       | PIC X(1).              |
| 165    | [1]   | bus^mlf.bcd.refr.file[0:9].ind                       | PIC X(1).              |
| 184    | [8]   | bus^mlf.bcd.tim^entry^ts<br>[ITD-TIM-ENTRY-TS]       | TYPE BINARY 64 SIGNED. |
| 192    | [8]   | bus^mlf.bcd.tim^log^ts<br>[ITD-TIM-LOG-TS]           | TYPE BINARY 64 SIGNED. |
| 200    | [144] | bus^mlf.ascii<br><br>Mandatory logged fields - ascii |                        |

| Offset | Len  | Field Name and Description                          | Data Type  |
|--------|------|-----------------------------------------------------|------------|
| 200    | [22] | bus^mlf.ascii.acq<br>[ITD-ACQ]                      |            |
| 200    | [4]  | bus^mlf.ascii.acq.fiid.byte[0:3]<br>[FIID-DEF]      | PIC X(4).  |
| 204    | [3]  | bus^mlf.ascii.acq.inst^cntry^cde.byte[0:2]          | PIC X(3).  |
| 207    | [11] | bus^mlf.ascii.acq.id^cde.byte[0:10]<br>[ID-CDE-DEF] | PIC X(11). |
| 218    | [4]  | bus^mlf.ascii.acq.lgnt.byte[0:3]<br>[LGNT-DEF]      | PIC X(4).  |
| 222    | [4]  | bus^mlf.ascii.act<br>[ITD-ACT]                      |            |
| 222    | [3]  | bus^mlf.ascii.act.cde.byte[0:2]<br>[ACT-CDE-DEF]    | PIC X(3).  |
| 225    | [1]  | bus^mlf.ascii.act.ind                               | PIC X(1).  |
| 226    | [22] | bus^mlf.ascii.auth<br>[ITD-AUTH]                    |            |
| 226    | [16] | bus^mlf.ascii.auth.nam.byte[0:15]<br>[SYM-NAM-DEF]  | PIC X(16). |
| 242    | [6]  | bus^mlf.ascii.auth.stan.byte[0:5]                   | PIC 9(6).  |
| 248    | [2]  | bus^mlf.ascii.auth^ind<br>[ITD-AUTH-IND]            |            |
| 248    | [1]  | bus^mlf.ascii.auth^ind.flg                          | PIC X(1).  |
| 249    | [1]  | bus^mlf.ascii.auth^ind.xfill                        | PIC X(1).  |
| 250    | [6]  | bus^mlf.ascii.captr^dat<br>[ITD-CAPTR-DAT]          |            |
| 250    | [2]  | bus^mlf.ascii.captr^dat.yy.byte[0:1]                | PIC X(2).  |
| 252    | [2]  | bus^mlf.ascii.captr^dat.mm.byte[0:1]                | PIC X(2).  |
| 254    | [2]  | bus^mlf.ascii.captr^dat.dd.byte[0:1]                | PIC X(2).  |
| 256    | [20] | bus^mlf.ascii.iss<br>[ITD-ISS]                      |            |
| 256    | [4]  | bus^mlf.ascii.iss.fiid.byte[0:3]<br>[FIID-DEF]      | PIC X(4).  |
| 260    | [11] | bus^mlf.ascii.iss.id^cde.byte[0:10]                 |            |

| Offset[Len] | Field Name and Description                                   | Data Type   |
|-------------|--------------------------------------------------------------|-------------|
|             | [ID-CDE-DEF]                                                 | PIC X(11) . |
| 271 [4]     | bus^mlf.ascii.iss.lgnt.byte[0:3]<br>[LGNT-DEF]               | PIC X(4) .  |
| 275 [1]     | bus^mlf.ascii.iss.discrd^non^fncl^rvsl                       | PIC X(1) .  |
| 276 [12]    | bus^mlf.ascii.local^txn<br>[ITD-LOCAL-TXN]                   |             |
| 276 [6]     | bus^mlf.ascii.local^txn.dat<br>[DAT]                         |             |
| 276 [2]     | bus^mlf.ascii.local^txn.dat.yy.byte[0:1]                     | PIC X(2) .  |
| 278 [2]     | bus^mlf.ascii.local^txn.dat.mm.byte[0:1]                     | PIC X(2) .  |
| 280 [2]     | bus^mlf.ascii.local^txn.dat.dd.byte[0:1]                     | PIC X(2) .  |
| 282 [6]     | bus^mlf.ascii.local^txn.tim.byte[0:5]                        | PIC X(6) .  |
| 288 [4]     | bus^mlf.ascii.mti.byte[0:3]<br>[ITD-MTI]                     | PIC X(4) .  |
| 292 [4]     | bus^mlf.ascii.mti^orig.byte[0:3]<br>[ITD-MTI-ORIG]           | PIC X(4) .  |
| 296 [6]     | bus^mlf.ascii.proc^cde<br>[ITD-PROC-CDE]                     |             |
| 296 [2]     | bus^mlf.ascii.proc^cde.txn^cde.byte[0:1]<br>[TXN-CDE-DEF]    | PIC X(2) .  |
| 298 [2]     | bus^mlf.ascii.proc^cde.acct1^typ.byte[0:1]<br>[ACCT-TYP-DEF] | PIC X(2) .  |
| 300 [2]     | bus^mlf.ascii.proc^cde.acct2^typ.byte[0:1]<br>[ACCT-TYP-DEF] | PIC X(2) .  |
| 302 [14]    | bus^mlf.ascii.pt^svc<br>[ITD-PT-SVC]                         |             |
| 302 [1]     | bus^mlf.ascii.pt^svc.crd^data^input^cap                      | PIC X(1) .  |
| 303 [1]     | bus^mlf.ascii.pt^svc.crdhldr^auth^cap                        | PIC X(1) .  |
| 304 [1]     | bus^mlf.ascii.pt^svc.crd^captr^cap                           | PIC X(1) .  |
| 305 [1]     | bus^mlf.ascii.pt^svc.oper^environ                            | PIC X(1) .  |
| 306 [1]     | bus^mlf.ascii.pt^svc.crdhldr^prsn                            | PIC X(1) .  |
| 307 [1]     | bus^mlf.ascii.pt^svc.crd^prsn                                | PIC X(1) .  |

| Offset[Len] | Field Name and Description                           | Data Type  |
|-------------|------------------------------------------------------|------------|
| 308 [1]     | bus^mlf.ascii.pt^svc.crd^data^input^mde              | PIC X(1).  |
| 309 [1]     | bus^mlf.ascii.pt^svc.crdhldr^auth^method             | PIC X(1).  |
| 310 [1]     | bus^mlf.ascii.pt^svc.crdhldr^auth^entity             | PIC X(1).  |
| 311 [1]     | bus^mlf.ascii.pt^svc.crd^data^output^cap             | PIC X(1).  |
| 312 [1]     | bus^mlf.ascii.pt^svc.term^output^cap                 | PIC X(1).  |
| 313 [1]     | bus^mlf.ascii.pt^svc.pin^captr^cap                   | PIC X(1).  |
| 314 [1]     | bus^mlf.ascii.pt^svc.pin^prsn^flg                    | PIC X(1).  |
| 315 [1]     | bus^mlf.ascii.pt^svc.xfill                           | PIC X(1).  |
| 316 [4]     | bus^mlf.ascii.rte^cde.byte[0:3]<br>[ITD-RTE-CDE]     | PIC X(4).  |
| 320 [2]     | bus^mlf.ascii.rte^flr<br>[ITD-RTE-FLR]               |            |
| 320 [1]     | bus^mlf.ascii.rte^flr.flg                            | PIC X(1).  |
| 321 [1]     | bus^mlf.ascii.rte^flr.xfill                          | PIC X(1).  |
| 322 [2]     | bus^mlf.ascii.rte^typ<br>[ITD-RTE-TYP]               |            |
| 322 [1]     | bus^mlf.ascii.rte^typ.flg                            | PIC X(1).  |
| 323 [1]     | bus^mlf.ascii.rte^typ.xfill                          | PIC X(1).  |
| 324 [16]    | bus^mlf.ascii.term^id.byte[0:15]<br>[ITD-TERM-ID]    | PIC X(16). |
| 340 [2]     | bus^mlf.ascii.txn^originator<br>[ITD-TXN-ORIGINATOR] |            |
| 340 [1]     | bus^mlf.ascii.txn^originator.flg                     | PIC X(1).  |
| 341 [1]     | bus^mlf.ascii.txn^originator.xfill                   | PIC X(1).  |
| 342 [2]     | bus^mlf.ascii.txn^responder<br>[ITD-TXN-RESPONDER]   |            |
| 342 [1]     | bus^mlf.ascii.txn^responder.flg                      | PIC X(1).  |
| 343 [1]     | bus^mlf.ascii.txn^responder.xfill                    | PIC X(1).  |
| 344 [3646]  | bus^olf[0:3645]                                      | PIC X(1).  |
|             | END [size 3990]                                      |            |

MM/DD/YY HH:MM      \$VOLUME OC60DICT      ITS-TLFXB

PAGE:    13

Offset[Len]    Field Name and Description

Data Type