

Offset[Len] Field Name and Description Data Type

DEF CCIFX

0 [788]

0 [4] lgth.byte[0:3] PIC X(4).

4 [9] cnt.byte[0:8] PIC 9(9).

13 [1] user^flda PIC X(1).

14 [22] prikey

14 [19] prikey.pan.byte[0:18] PIC X(19).

33 [3] prikey.mbr^num.byte[0:2]
[CRD-SEQ-NUM-DEF] PIC 9(3).

36 [1] rec^typ PIC X(1).

37 [1] user^fldb PIC X(1).

38 [246] ccifx000 [CCIFX000]

The Customer/Card Information File (CCIF) contains information about the primary and secondary cardholders which can be used to perform or assist with Customer Service and/or Fraud Control functions. The primary key to the record is card number (PAN), and member number. There are no alternate keys. The Customer/Card Information File may contain one record for every CAF record on BASE24, although CCIF records are not required.

Primary cardholder information. This segment is required.

38 [12] ccifx000.segx^info
[SEGX-INFO]

Identifies the segment ID, length, and version.

38 [4] ccifx000.segx^info.id.byte[0:3] PIC 9(4).

42 [4] ccifx000.segx^info.lgth.byte[0:3] PIC 9(4).

46 [4] ccifx000.segx^info.ver.byte[0:3] PIC 9(4).

50 [30] ccifx000.nam.byte[0:29] PIC X(30).

Offset[Len]	Field Name and Description	Data Type
	The name of the primary cardholder. This field is required.	
80 [15]	ccifx000.govt^id.byte[0:14]	PIC X(15).
	Government ID or taxpayer ID. In the United States, this is the Social Security Number. This field is optional; the default is spaces.	
95 [1]	ccifx000.user^fld0	PIC X(1).
	Reserved for future use. Default is spaces.	
96 [20]	ccifx000.mthr^mdn^nam.byte[0:19]	PIC X(20).
	Mother's maiden name. This field is optional; the default is spaces.	
116 [6]	ccifx000.dob.byte[0:5]	PIC X(6).
	Date of birth in the format YYMMDD. This field is optional; the default is spaces.	
122 [30]	ccifx000.str^addr1.byte[0:29]	PIC X(30).
	The first line of the primary cardholder's street address. This field is optional; the default is spaces.	
152 [30]	ccifx000.str^addr2.byte[0:29]	PIC X(30).
	The second line of the primary cardholder's street address. This field is optional; the default is spaces.	
182 [18]	ccifx000.city.byte[0:17]	PIC X(18).
	The primary cardholder's city of residence. This field is optional; the default is spaces.	
200 [3]	ccifx000.st.byte[0:2]	PIC X(3).
	The alpha representation of the primary cardholder's state of residence. Refer to the FIPS Processing Standards Publication 6-3 for valid values. This field is optional; the default is spaces.	
203 [3]	ccifx000.cntry.byte[0:2]	PIC X(3).

Offset[Len]	Field Name and Description	Data Type
	The alpha representation of the primary cardholder's country of residence. Refer to ISO 3166 (1988) manual for valid values. This field is optional, the default is spaces.	
206 [10]	ccifx000.postal^cde.byte[0:9] [POSTAL-CDE-DEF]	PIC X(10).
	The postal code/zip code for the primary cardholder's residence. This field is optional; the default is spaces.	
216 [20]	ccifx000.phn^home.byte[0:19] [PHONE-NUM-DEF]	PIC X(20).
	The primary cardholder's home telephone number. This field is optional. The data in this field will be left-justified; the default is spaces.	
236 [20]	ccifx000.phn^wrk.byte[0:19] [PHONE-NUM-DEF]	PIC X(20).
	The primary cardholder's work telephone number. This field is optional. The data in this field will be left-justified; the default is spaces.	
256 [20]	ccifx000.phn^othr1.byte[0:19]	PIC X(20).
	A third telephone number for the primary cardholder. This field is optional. The data in this field will be left-justified; the default is spaces.	
276 [8]	ccifx000.phn^othr1^descr.byte[0:7]	PIC X(8).
	Description of OTHR1 telephone number. This may be used to indicate Fax, Cellular, Neighbor, Second Business, etc. This field is optional. The data in this field will be left-justified; the default is spaces.	
284 [70]	ccifx001 [CCIFX001] Additional primary cardholder information.	
284 [12]	ccifx001.segx^info [SEGX-INFO] Identifies the segment ID, length, and	

Offset[Len]	Field Name and Description	Data Type
	version.	
284 [4]	ccifx001.segx^info.id.byte[0:3]	PIC 9(4).
288 [4]	ccifx001.segx^info.lgth.byte[0:3]	PIC 9(4).
292 [4]	ccifx001.segx^info.ver.byte[0:3]	PIC 9(4).
296 [30]	ccifx001.str^addr3.byte[0:29]	PIC X(30).
	The third line of the primary cardholder's street address. This field is optional; the default is spaces.	
326 [20]	ccifx001.phn^othr2.byte[0:19]	PIC X(20).
	A fourth telephone number for the primary cardholder. This field is optional. The data in this field will be left-justified; the default is spaces.	
346 [8]	ccifx001.phn^othr2^descr.byte[0:7]	PIC X(8).
	Description of OTHR2 telephone number. This may be used to indicate Fax, Cellular, Neighbor, Second Business, etc. This field is optional. The data in this field will be left-justified; the default is spaces.	
354 [84]	ccifx002 [CCIFX002]	
	Secondary cardholder name information.	
354 [12]	ccifx002.segx^info [SEGX-INFO]	
	Identifies the segment ID, length, and version.	
354 [4]	ccifx002.segx^info.id.byte[0:3]	PIC 9(4).
358 [4]	ccifx002.segx^info.lgth.byte[0:3]	PIC 9(4).
362 [4]	ccifx002.segx^info.ver.byte[0:3]	PIC 9(4).
366 [30]	ccifx002.nam.byte[0:29]	PIC X(30).
	The name of the secondary cardholder. This field is optional; the default is spaces.	
396 [15]	ccifx002.govt^id.byte[0:14]	PIC X(15).

Offset[Len]	Field Name and Description	Data Type
	The secondary cardholder's government ID or taxpayer ID. In the United States, this is the Social Security Number. This field is optional; the default is spaces.	
411 [1]	ccifx002.user^fld2	PIC X(1).
	Reserved for future use. Default is spaces.	
412 [20]	ccifx002.mthr^mdn^nam.byte[0:19]	PIC X(20).
	The secondary cardholder's mother's maiden name. This field is optional; the default is spaces.	
432 [6]	ccifx002.dob.byte[0:5]	PIC X(6).
	The secondary cardholder's date of birth in the format YYMMDD. This field is optional; the default is spaces.	
438 [136]	ccifx003 [CCIFX003]	
	Secondary cardholder address information. This data should only be present if the secondary cardholder's address is different from that of the primary cardholder.	
438 [12]	ccifx003.segx^info [SEGX-INFO]	
	Identifies the segment ID, length, and version.	
438 [4]	ccifx003.segx^info.id.byte[0:3]	PIC 9(4).
442 [4]	ccifx003.segx^info.lgth.byte[0:3]	PIC 9(4).
446 [4]	ccifx003.segx^info.ver.byte[0:3]	PIC 9(4).
450 [30]	ccifx003.str^addr1.byte[0:29]	PIC X(30).
	The first line of the secondary cardholder's street address. This field is optional; the default is spaces.	
480 [30]	ccifx003.str^addr2.byte[0:29]	PIC X(30).
	The second line of the secondary cardholder's street address. This field is optional; the default is spaces.	

Offset[Len]	Field Name and Description	Data Type
510 [30]	ccifx003.str^addr3.byte[0:29] The third line of the secondary cardholder's street address. This field is optional; the default is spaces.	PIC X(30).
540 [18]	ccifx003.city.byte[0:17] The secondary cardholder's city of residence. This field is optional; the default is spaces.	PIC X(18).
558 [3]	ccifx003.st.byte[0:2] The alpha representation of the secondary cardholder's state of residence. Refer to the FIPS Processing Standards Publication 6-3 for valid values. This field is optional; the default is spaces.	PIC X(3).
561 [3]	ccifx003.cntry.byte[0:2] The alpha representation of the secondary cardholder's country of residence. Refer to ISO 3166 (1988) manual for valid values. This field is optional, the default is spaces.	PIC X(3).
564 [10]	ccifx003.postal^cde.byte[0:9] [POSTAL-CDE-DEF]	PIC X(10).
	The postal code/zip code for the secondary cardholder's residence. This field is optional; the default is spaces.	
574 [108]	ccifx004 [CCIFX004] Secondary cardholder telephone information. This data should only be present if the secondary cardholder's telephone information is different from that of the primary cardholder.	
574 [12]	ccifx004.segx^info [SEGX-INFO] Identifies the segment ID, length, and version.	
574 [4]	ccifx004.segx^info.id.byte[0:3]	PIC 9(4).
578 [4]	ccifx004.segx^info.lgth.byte[0:3]	PIC 9(4).
582 [4]	ccifx004.segx^info.ver.byte[0:3]	PIC 9(4).

Offset[Len] Field Name and Description Data Type

586 [20] ccifx004.phn^home.byte[0:19]
[PHONE-NUM-DEF] PIC X(20).

The secondary cardholder's home telephone number. This field is optional. The data in this field will be left-justified; the default is spaces.

606 [20] ccifx004.phn^wrk.byte[0:19]
[PHONE-NUM-DEF] PIC X(20).

The secondary cardholder's work telephone number. This field is optional. The data in this field will be left-justified; the default is spaces.

626 [20] ccifx004.phn^othr1.byte[0:19]
[PHONE-NUM-DEF] PIC X(20).

Another telephone number for the secondary cardholder. This field is optional. The data in this field will be left-justified; the default is spaces.

646 [8] ccifx004.phn^othr1^descr.byte[0:7] PIC X(8).

Description of OTHR1 telephone number. This may be used to indicate Fax, Cellular, Neighbor, Second Business, etc. This field is optional. The data in this field will be left-justified; the default is spaces.

654 [20] ccifx004.phn^othr2.byte[0:19]
[PHONE-NUM-DEF] PIC X(20).

Another telephone number for the secondary cardholder. This field is optional. The data in this field will be left-justified; the default is spaces.

674 [8] ccifx004.phn^othr2^descr.byte[0:7] PIC X(8).

Description of OTHR2 telephone number. This may be used to indicate Fax, Cellular, Neighbor, Second Business, etc. This field is optional. The data in this field will be left-justified; the default is spaces.

682 [22] ccifx005 [CCIFX005]

Other cardholder information.

Offset[Len]	Field Name and Description	Data Type
682 [12]	ccifx005.segx^info [SEGX-INFO] Identifies the segment ID, length, and version.	
682 [4]	ccifx005.segx^info.id.byte[0:3]	PIC 9(4).
686 [4]	ccifx005.segx^info.lgth.byte[0:3]	PIC 9(4).
690 [4]	ccifx005.segx^info.ver.byte[0:3]	PIC 9(4).
694 [3]	ccifx005.bhvr^score.byte[0:2] Behavioral score.	PIC X(3).
697 [1]	ccifx005.recent^reiss^ind Recently reissued indicator. Valid values are "Y" and "N".	PIC X(1).
698 [3]	ccifx005.cvv^val.byte[0:2] Card verification value.	PIC X(3).
701 [2]	ccifx005.num^iss.byte[0:1] Number of cards issued.	PIC X(2).
703 [1]	ccifx005.user^fld5 Reserved for future use. Default is spaces.	PIC X(1).
704 [84]	ccifx006 [CCIFX006] Discretionary data segment.	
704 [12]	ccifx006.segx^info [SEGX-INFO] Identifies the segment ID, length, and version.	
704 [4]	ccifx006.segx^info.id.byte[0:3]	PIC 9(4).
708 [4]	ccifx006.segx^info.lgth.byte[0:3]	PIC 9(4).
712 [4]	ccifx006.segx^info.ver.byte[0:3]	PIC 9(4).
716 [72]	ccifx006.discr^data.byte[0:71]	PIC X(72).

MM/DD/YY HH:MM \$VOLUME OC60DICT CCIFX

PAGE: 9

Offset[Len] Field Name and Description

Data Type

Discretionary data.

END [size 788]

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

DEF CCMFX

0 [632]

!

The Customer/Card Memo File (CCMF) allows Customer Service personnel to enter information about a lost or stolen card, and/or other general memo information about the customer, cardholder, or card. The primary key to the record is card number (PAN), and member number. There are no alternate keys. The Customer/Card Memo File (CCMF) may contain one record for every cardholder on BASE24, although a CCMF record is not required for every cardholder.

0	[9]	cnt.byte[0:8]	PIC 9(9).
---	-----	---------------	-----------

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape. Header and trailer records must be reflected in this count as well as individual CCMF records.

9	[1]	user^fld0	PIC X(1).
---	-----	-----------	-----------

Reserved for future use.

10	[22]	prikey	
----	------	--------	--

The primary key to the CCMF.

10	[19]	prikey.pan.byte[0:18]	PIC X(19).
----	------	-----------------------	------------

The card number. This field is left-justified and blank-filled to the right.

29	[3]	prikey.mbr^num.byte[0:2] [CRD-SEQ-NUM-DEF]	PIC 9(3).
----	-----	---	-----------

The member number of the card. The default is 000.

32	[1]	rec^typ	PIC X(1).
----	-----	---------	-----------

A code indicating the operation to be performed on the CCMF record. Valid values are:

Offset[Len]	Field Name and Description	Data Type
	A = Add C = Change D = Delete F = Full-file change Values of A, C, and D are intended for use with partial-file refreshes. The value of F is required for full-file refreshes.	
33 [1]	user^fld1 Reserved for future use.	PIC X(1).
34 [4]	ver.byte[0:3] Version number of the CCMF record.	PIC X(4).
38 [6]	dat^lost [DAT] The date the card was actually lost or stolen in the format YYMMDD. This field is optional; the default is spaces.	
38 [2]	dat^lost.yy.byte[0:1]	PIC X(2).
40 [2]	dat^lost.mm.byte[0:1]	PIC X(2).
42 [2]	dat^lost.dd.byte[0:1]	PIC X(2).
44 [6]	dat^rptd [DAT] The date the card was reported lost or stolen in the format YYMMDD. This field is optional; the default is spaces.	
44 [2]	dat^rptd.yy.byte[0:1]	PIC X(2).
46 [2]	dat^rptd.mm.byte[0:1]	PIC X(2).
48 [2]	dat^rptd.dd.byte[0:1]	PIC X(2).
50 [3]	rpt^taken^by.byte[0:2] Initials of the operator who originally took the lost/stolen report. This field is optional; the default is spaces.	PIC X(3).
53 [1]	lost^stln^ind A user-defined indicator that identifies the circumstances under which the card was lost or stolen. This field is optional. Valid values are 0-9, A-Z.	PIC X(1).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

54	[2] line^cnt.byte[0:1]	PIC 9(2).
----	-----------------------------	-----------

Counter for the number of memo lines
that contain data.

56	[576] memo^data[0:7]	PIC X(72).
	[OCCURS DEPENDING ON LINE^CNT]	

Free-format memo area.

END [size 632]

Offset[Len] Field Name and Description Data Type

DEF THFX

0 [144]

0 [9] cnt.byte[0:8] PIC 9(9).

A record number indicating the position of this record on the refresh tape. The value in this field should always be one greater than that in the previous record on the tape. Header and trailer records must be reflected in this count as well as individual THFX records.

9 [1] user^fld1 PIC X(1).

Reserved for future use.

10 [60]

prikey

The following fields form the primary key to records in the THF. It forms the key to the file that allows the retrieval of debit and credit information or account information by date.

10 [4] prikey.fiid.byte[0:3] [FIID-DEF] PIC X(4).

The financial institution associated with the customer who initiated the transaction. This field is left-justified, blank-filled.

14 [28] prikey.acct^num.byte[0:27] [ACCT-NUM-DEF] PIC X(28).

The account number. This field is left-justified, blank-filled.

42 [2] prikey.acct^typ.byte[0:1] [ACCT-TYP-DEF] PIC X(2).

The account type.

44 [14] prikey.dat^tim.byte[0:13] PIC 9(14).

The date/time the transaction was performed or posted. Format is YYYYMMDDHHMMSS.

58 [12] prikey.ref^num.byte[0:11] PIC X(12).

The reference number. This number is a unique identifier for each transaction in the file. The key letters "B24" in the first three

Offset	Len	Field Name and Description	Data Type
--------	-----	----------------------------	-----------

positions are reserved for BASE24 use.
When transactions are written to the THF by BASE24 they will be identified with a reference number beginning with "B24", followed by a two-byte product identifier. This field is left-justified, blank-filled.

70	[1]	rec^typ	PIC X(1).
----	-----	---------	-----------

A code indicating the operation to be performed on the THF record. Valid values are:

A = Add
C = Change
D = Delete
F = Full-file change

Values of A, C, and D are intended for use with partial-file refreshes. The value of F is required for full-file refreshes.

71	[1]	user^fld2	PIC X(1).
----	-----	-----------	-----------

Reserved for future use.

72	[12]	alt^key1	
----	------	----------	--

The value in the following field combined with values from primary key fields form the alternate key to the file that allows the retrieval of information pertaining to a specific cheque clearance inquiry.

72	[12]	alt^key1.chq^num.byte[0:11]	PIC X(12).
----	------	-----------------------------	------------

The number of the cheque. The cheque number must be right-justified and zero-filled. If the record is not for a cheque, this field must be space filled.

84	[2]	alt^key2	
----	-----	----------	--

The value in the following field combined with values from primary key fields form the alternate key to the file that allows the retrieval of history information that originated at various sources (eg. ATMs).

84	[1]	alt^key2.src	PIC X(1).
----	-----	--------------	-----------

A code indicating the source of origination for a transaction, eg. an ATM or POS device.

BASE24 defined valid values are:

Offset[Len]	Field Name and Description	Data Type
	A = ATM Device B = Telebanking Device (eg. PC, VRU, CSI) P = POS Device T = Teller	
85 [1]	alt^key2.user^fld3 Reserved for future use.	PIC X(1).
86 [2]	alt^key3 The value in the following field combined with values from primary key fields form the alternate key to the file that allows the retrieval of history information based upon the transaction code.	
86 [2]	alt^key3.txn^cde.byte[0:1] [TXN-CDE-DEF] The transaction code.	PIC X(2).
88 [2]	alt^key4 The value in the following field combined with values from primary key fields form the alternate key to the file that allows the retrieval of debit or credit information or last set of cheque transactions.	
88 [1]	alt^key4.db^cr^ind A flag indicating whether the transaction is a debit or credit transaction. Valid values are: C = Credit D = Debit	PIC X(1).
89 [1]	alt^key4.user^fld4 Reserved for future use.	PIC X(1).
90 [4]	ver.byte[0:3] Version number of the THFX record.	PIC 9(4).
94 [50]	det1 The following fields make up the detail information that is returned for an inquiry request.	
94 [18]	det1.amt.byte[0:17]	PIC 9(18).

Offset[Len]	Field Name and Description	Data Type
-------------	----------------------------	-----------

The amount of the transaction.
This field is right-justified, zero-filled.

112	[16]	detl.txn^flg.byte[0:15]	PIC X(16).
-----	------	-------------------------	------------

Flags. Each byte specifies an attribute of the transaction.

Byte 0:
Indicates whether the customer had sufficient funds to perform the transaction.
Valid values are:
1 = Not Sufficient Funds
0 = Sufficient Funds

Byte 1:
Indicates whether the transaction is a reversal.
Valid values are:
1 = Reversed
0 = Not Reversed

Bytes 2-15: Reserved

128	[8]	detl.host^txn^cde.byte[0:7]	PIC X(8).
-----	-----	-----------------------------	-----------

Host defined transaction code.
This field is left-justified, blank-filled.

136	[8]	detl.purge^dat.byte[0:7]	PIC X(8).
-----	-----	--------------------------	-----------

Logical purge date (YYYYMMDD).

END [size 144]