

Files Maintenance Manual

BASE24-pos[®]



© 2012 by ACI Worldwide, Inc. All rights reserved.

All information contained in this documentation, as well as the software described in it, is confidential and proprietary to ACI Worldwide, Inc., or one of its subsidiaries, is subject to a license agreement, and may be used or copied only in accordance with the terms of such license. Except as permitted by such license, no part of this documentation may be reproduced, stored in a retrieval system, or transmitted in any form or by electronic, mechanical, recording, or any other means, without the prior written permission of ACI Worldwide, Inc., or one of its subsidiaries.

ACI, ACI Worldwide, and the ACI product names used in this documentation are trademarks or registered trademarks of ACI Worldwide, Inc., or one of its subsidiaries.

Other companies' trademarks, service marks, or registered trademarks and service marks are trademarks, service marks, or registered trademarks and service marks of their respective companies.

Contents

What's New	vii
Preface	ix
Conventions Used in This Manual	xiii
1: Introduction	1-1
BASE24-pos Files and Functions	1-2
File Access	1-3
POS Product Menu	1-4
Function Keys	1-7
BASE24 Authorization Terminology	1-8
2: Administrative Card File (ADMN)	2-1
Screen 1	2-2
3: Authorization Selection Table (AST)	3-1
Function Keys	3-2
Screens 1, 3, 5, and 7	3-5
Screens 2, 4, 6, and 8	3-11
Screen 9	3-16
4: Card Authorization Parameters File (CAPF)	4-1
Screen 1	4-2
5: Check Authorization Routing Table File (CART)	5-1
Screen 1	5-3
6: National Negative Card File (NNF)	6-1
Screen 1	6-2

7: POS Retailer Definition File (PRDF).....	7-1
Screen 1.....	7-2
Screens 2 and 3.....	7-12
Screen 4.....	7-16
8: POS Terminal Data Files (PTD).....	8-1
Grouping Terminals at a Site	8-2
Function Keys.....	8-3
Screen 1.....	8-4
Screen 2.....	8-16
Screen 3.....	8-22
Screen 4.....	8-30
Screen 5.....	8-43
Screen 6.....	8-47
Format 1	8-48
Format 2	8-53
Screen 7.....	8-55
Screens 8, 9, and 10	8-61
Screens 11, 12, 13, 14, 15, and 16	8-65
Screen 17.....	8-69
Screen 18.....	8-70
Screen 19.....	8-76
9: POS Transaction Log File (PTLF).....	9-1
PTLF Key Screens (Screens 1 and 2).....	9-2
Key Screen Function Keys	9-3
PTLF Key Screen 1.....	9-4
PTLF Key Screen 2.....	9-11
PTLF Summary Screen Formats (Screen 3).....	9-15
Summary Screen Function Keys.....	9-15
Paging Forward or Backward	9-16
Screen 3-Format 1.....	9-18
Screen 3-Format 2.....	9-22

PTLF Summary Screen Formats (Screen 3) <i>continued</i>	
Screen 3-Format 3.	9-25
Screen 3-Format 4.	9-29
PTLF Detail Screen Formats (Screen 4).	9-34
Screen 4-Format 1.	9-35
Screen 4-Format 2.	9-54
Screen 4-Format 3.	9-61
10: Response Code Description File (RCDF)	10-1
Screen 1 Function Keys	10-2
Screen 1.	10-3
Screen 2.	10-6
11: Routing Table File (RTBL).	11-1
Screen 1.	11-2
Index	Index-1
Index by Field Name.	Index-5
Index by Data Name	Index-11

ACI Worldwide, Inc.

What's New

This section highlights the major changes that have been made in updates to the *BASE24-pos Files Maintenance Manual*. The first column of the tables list the sections and appendixes in which major changes have been made. The second column of the tables describe the major changes for each section or appendix.

September 2012

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|---|
| 2 | Clarifies the descriptions of the PIN MASTER KEY and MAC MASTER KEY fields on POS Terminal Data file screen 7 for Transaction Security Services support to indicate that by default, a logical network indicator (if configured) followed by the terminal ID, is used as the key locator value. |
|---|---|

June 2012

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|---|
| 2 | Updates the description of the MASTER KEY field on POS Terminal Data file screen 7 for Transaction Security Services support. |
|---|---|

June 2011

Section/ Appendix	Major Changes
----------------------	---------------

- | | |
|---|--|
| 3 | Clarifies supported card type values and descriptions. |
|---|--|

ACI Worldwide, Inc.

Preface

Using the BASE24 CRT access system, BASE24-pos users can access the BASE24-pos files and functions. BASE24-pos files are accessed from the POS entry on the Virtual Menu. The BASE24-pos product can use other files not included in this manual. The additional files that are shared between several BASE24 products are included in the ***BASE24 Base Files Maintenance Manual***. Files specific to particular Device Handler modules are included in the device-specific device support manuals.

This manual provides descriptions of the BASE24 CRT screens that access BASE24-pos files and functions. The information in this manual allows users to enter and update records in BASE24-pos files as well as perform individual functions correctly.

The screen descriptions included in this manual contain information about the purpose of the fields on the screen, the codes that can be placed in these fields, and the default values and field lengths.

To enhance clarity, throughout this manual the Authorization, Device Handler, and Router modules are referred to as if they were separate processes. However, in the BASE24-pos product, these modules are bound together in a single process called the Device Handler/Router/Authorization process. Therefore, all occurrences in this manual of the individual module names (i.e., Authorization module, Device Handler module, or Router module) for the BASE24-pos product are actually referring to a portion of the bound process of Device Handler/Router/Authorization.

Audience

ACI prepared this publication for distribution to institution personnel responsible for updating and maintaining the BASE24-pos database.

Prerequisites

It is recommended that readers be familiar with the ***BASE24 CRT Access Manual*** before reading this manual. Some knowledge of BASE24-pos processing is also suggested.

Additional Documentation

The BASE24 documentation set is arranged so that each BASE24 manual presents a topic or group of related topics in detail. When one BASE24 manual presents a topic that has already been covered in detail in another BASE24 manual, the topic is summarized and the reader is directed to the other manual for additional information. Information has been arranged in this manner to be more efficient for readers that do not need the additional detail and at the same time provide the source for readers that require the additional information. This manual contains references to the following BASE24 publications.

- The ***BASE24 CRT Access Manual*** describes how to access files and functions using the CRT access system. It also describes the standard BASE24 function keys.
- The ***BASE24-pos CRT Authorization and CRT Administration Manual*** describes the files specific to the CRT Authorization and CRT Administration products.
- The ***BASE24-pos Standard POS Device Configuration Manual*** describes the files specific to the Standard POS Device Handler module (SPDH).
- The ***BASE24-pos EMV Support Manual*** describes POS Terminal Data Files (PTD) screen 17, which is specific to the BASE24-pos EMV add-on product.
- The ***BASE24-pos Hypercom Device Support Manual*** describes the files specific to the Hypercom Device Handler process.
- The ***BASE24-pos Merchant Host Interface Manual*** describes the files specific to the Merchant Host Interface process (MHI).
- The ***BASE24 Base Files Maintenance Manual*** describes files that are shared among BASE24 products. It also describes standard function keys and reserved card types.
- The ***BASE24-pos Settlement and Reporting Manual*** describes the POS Report Generator (PRG), a function specific to POS reporting.

In addition to these publications this manual contains a reference to the ISO 4217 standard, ***Codes for the Representation of Currencies and Funds***.

Software

This manual documents standard processing as of its publication date. Software that is not current and custom software modifications (CSMs) may result in processing that differs from the material presented in this manual. The customer is responsible for identifying and noting these changes.

Manual Summary

The following is a summary of the contents of this manual:

“Conventions Used in this Manual” follows this preface and describes notation and documentation conventions necessary to understand the information in the manual.

Section 1, “Introduction,” introduces the reader to the files and functions specific to the BASE24-pos product and the file maintenance screens and function keys used to access them.

Section 2, “Administrative Card File (ADMN),” describes the screen used to access the Administrative Card File (ADMN), which contains one record for every valid administrative card number.

Section 3, “Authorization Selection Table (AST),” describes the screens used to access the Authorization Selection Table (AST), which defines authorization routing for BASE24-pos transactions.

Section 4, “Card Authorization Parameters File (CAPF),” describes the screen used to access the Card Authorization Parameters File (CAPF), which contains one record for each credit card type supported by each card-issuing institution that uses the Parametric Authorization method.

Section 5, “Check Authorization Routing Table File (CART),” describes the screen used to access the Check Authorization Routing Table File (CART), which contains information that defines how check guarantee and check verification transactions are routed.

Section 6, “National Negative Card File (NNF),” describes the screen used to access the National Negative Card Files (NNFs), which contain one record for every restricted national credit, debit, and dual card.

Section 7, “POS Retailer Definition File (PRDF),” describes the screens used to access the POS Retailer Definition File (PRDF), which contains one record for each retailer in the logical network. These records are used in validating POS transactions and defining authorization and routing parameters.

Section 8, “POS Terminal Data Files (PTD),” describes the screens used to access the POS Terminal Data files, which describe the characteristics for every point-of-sale (POS) terminal in the logical network.

Section 9, “POS Transaction Log File (PTLF),” describes the screens used to access the POS Transaction Log File (PTLF), which provides an audit trail for activity occurring at POS terminals. All financial transactions occurring for each BASE24 processing day at POS terminals throughout the logical network are logged to the PTLF. The PTLF has key screens, summary screens, and detail screens that provide the user with transaction information.

Section 10, “Response Code Description File (RCDF),” describes the screens used to access the Response Code Description File (RCDF), which is used by the BASE24-pos product to identify BASE24 and ISO response codes.

Section 11, “Routing Table File (RTBL),” describes the screen used to access the Routing Table File (RTBL), which is used by the BASE24-pos product to identify allowable authorization destination processes and their associated codes for the routing of transactions.

Readers can use the index by field name to locate information about a particular screen field and the index by data name to locate information about a particular field from a file or record structure.

Publication Identification

Three entries appearing at the bottom of each page uniquely identify this BASE24 publication. The publication number (for example, PS-AE000-02 for the ***BASE24-pos Files Maintenance Manual***) appears on every page to assist readers in identifying the manual from which a page of information was printed. The publication date (for example, Sep-2012 for September, 2012) indicates the issue of the manual. The software release information (for example, R6.0v10 for release 6.0, version 10) specifies the software that the manual describes. This information matches the document information on the copyright page of the manual.

Conventions Used in This Manual

This section explains how field descriptions and required blank spaces in field values are documented in this manual.

Field Descriptions

Each field appearing on a file maintenance screen is listed by name and then described. Field descriptions briefly summarize the contents, purpose, and permissible values, as shown in the following example taken from the BASE24-pos Terminal Data files (PTD).

Example

RETAILER GROUP — An identifier indicating the retailer group with which this BASE24-pos terminal is associated for reporting purposes. The group entered in this field must match the group in the POS Retailer Definition File (PRDF).

Field Length:	1–4 alphanumeric characters
Required Field:	Yes
Default Value:	No default value
Data Name:	PTDD1.TERM-OWNER.RETAILER-GRP PTDF.REC.TERM-OWNER.RETAILER-GRP

Explanation

Each field description is completed by one or more of the following items of information:

Item	Description
Example	Illustrates a possible entry for the field to further clarify the value or values that can be entered.

Item	Description
Field Length	Specifies the size of the field and the type of characters that can be entered. This length refers to the field and valid values for the file maintenance screen, not the field in the DDLs. Possible values are alphabetic, alphanumeric, hexadecimal, and numeric. The term <i>alphanumeric</i> includes all alphabetic, numeric, and special characters that can be entered from a keyboard without using a control sequence. The term <i>hexadecimal</i> includes all numbers and the letters A through F. When a field value cannot be modified by the operator, the field length is System protected.
Occurs	Indicates the number of times the field can be displayed on the screen. This information is provided only when the field can be displayed multiple times.
Required Field	Specifies whether a value has to be entered in the field. Possible values are Yes and No. Some fields are required only under certain conditions. In this case, the entry is Yes, followed by the conditions that determine when the field is required.
Default Value	Specifies the value that is automatically placed in the field when the screen is first displayed or when the F8 key is pressed to clear the screen.
Data Name	Provides the DDL name associated with the field appearing on the screen. Data names are included in the documentation to assist in communicating screen and field issues to your technical staff. Note that screen data is not always stored in the BASE24 database as it appears on the screen or as it is described in the field description. If you need information on how screen data is actually stored, consult the DDLs.

Required Blank Spaces

Throughout this manual when discussing the impact of required blanks or spaces in entered field data, the symbol *b* is used to denote a required blank character or space.

1: Introduction

This section provides an introduction to the files and functions specific to the BASE24-pos product and the file maintenance screens and function keys used to access them.

BASE24-pos Files and Functions

The following BASE24-pos files and functions can be accessed using file maintenance screens. Each is described in this manual.

- Administrative Card File (ADMN)
- Authorization Selection Table (AST)
- Card Authorization Parameters File (CAPF)
- Check Authorization Routing Table File (CART)
- National Negative Card Files (NNFs)
- POS Retailer Definition File (PRDF)
- POS Terminal Data Files (PTD)
- POS Transaction Log File (PTLF)
- Response Code Description File (RCDF)
- Routing Table File (RTBL)

File Access

All BASE24-pos files and functions that the user can access are listed on the POS Product Menu. The POS Product Menu is accessed from the Virtual Menu by placing the cursor in front of POS on the menu and pressing the **F1** key. Each operator will see only the files and screen groupings available to him or her. Below is an example of a Virtual Menu:

```
BASE24-ADMN  VIRTUAL MENU                LLLL      YY/MM/DD  HH:MM  01 OF 01
                V I R T U A L  M E N U

      BASE                      ATM
      POS                      TELLER
      CORE                     BILLPAY
      KERNEL/IEP               MAIL
      CARD MANAGEMENT          CUSTOMER SERVICE
      OPERATOR FUNCTIONS       FREQUENT SHOPPER
      CHKA                     RFND
```

```
***** BASE24 *****
                        FILE DESTINATION:
F1-ENTER DATA  F9-NEXT PAGE  F11-PREVIOUS PAGE      F10-PRINT  F16-EXIT
```

POS Product Menu

The files and functions that can be accessed using the POS Product Menu are listed below. The POS Product Menu is shown on the following page.

ACNF	=	ACI Standard Device Handler Configuration File
ADMN	=	Administrative Card File
ARSP	=	ACI Standard Device Response File
AST	=	Authorization Selection Table
CAPF	=	Card Authorization Parameters File
CART	=	Check Authorization Routing Table File
CHF	=	Card History File
CRED	=	Credibility History
CRUF	=	CRT Authorization Retailer Usage File
CRTA	=	CRT Administration
CSEC	=	CRT Authorization Security File
HPCF	=	Hypercom Configuration File
HPTC	=	Hypercom T7 Configuration File
MCNF	=	Merchant Host Interface Configuration File
MHCF	=	Merchant Host Configuration File
MRF	=	Multiple Referrals File
MRSP	=	Merchant Host Response File
MTCF	=	Merchant Totals Configuration File
NNF	=	National Negative Card File
OLT	=	Online Transaction
PAF	=	Parameter Authentication File
PRDF	=	POS Retailer Definition File
PRF	=	POS Referral File
PRG	=	Periodic Report Generator
PTD	=	BASE24-pos Terminal Data files
PTLF	=	POS Transaction Log File
RCDF	=	Response Code Description File
RTBL	=	Routing Table File
SVDF	=	Stored Value Dormancy File
SVHF	=	Stored Value History File
VVT	=	Visa II Terminal and Configuration Maintenance File

Users can access a file or function listed on the menu by placing the cursor beside an individual item and pressing the **F1** key. The order in which the files and functions are displayed for individual users is dependent on the order in which the user received access to them. A more detailed explanation for accessing files and functions is provided in the ***BASE24 CRT Access Manual***.

```

BASE24-ADMN  MENU                LLLL      YY/MM/DD  HH:MM  01 OF 01
                P O S      P R O D U C T  M E N U

      ACNF          ADMN          ARSP          AST
      CAPF          CART          CHF           CRED
      CRTA          CRUF          CSEC          HPCF
      HPTC          MCNF          MHCF          MREG
      MRF           MRSP          MTCF          NNF
      OLT           PAF           PRDF          PRF
      PRG           PTD           PTLF          RCDF
      RTBL          SVHF          VVT

***** BASE24 *****
                FILE DESTINATION:
F1-ENTER DATA  F9-NEXT PAGE    F11-PREVIOUS PAGE    F10-PRINT    F12-HELP

```

Documentation for the following files is included in this manual.

- Administrative Card File (ADMN)
- Authorization Selection Table (AST)
- Card Authorization Parameters File (CAPF)
- Check Authorization Routing Table File (CART)
- National Negative Card File (NNF)
- POS Retailer Definition File (PRDF)
- POS Terminal Data files (PTD)
- POS Transaction Log File (PTLF)
- Response Code Description File (RCDF)
- Routing Table File (RTBL)

The Card History File (CHF), Credibility History (CRED), CRT Administration (CRTA), CRT Authorization Retailer Usage File (CRUF), CRT Authorization Security File (CSEC), Multiple Referrals File (MRF), Online Transaction (OLT), and POS Referral File (PRF) are operator and file maintenance screens used with the BASE24-pos CRT Authorization and CRT Administration add-on products. These screens are documented in the ***BASE24-pos CRT Authorization and CRT Administration Manual***.

The ACI Standard Device Handler Configuration File (ACNF) and ACI Standard Device Response File (ARSP) are files used specifically by the BASE24 Standard POS Device Handler. Documentation for these files is contained in the ***BASE24-pos Standard POS Device Configuration Manual***.

The Hypercom Configuration File (HPCF) and Hypercom T7 Configuration File (HPTC) are used specifically by the Hypercom Device Handler. Documentation for these files is contained in the ***BASE24-pos Hypercom Device Support Manual***. The Merchant Host Interface Configuration File (MCNF), Merchant Host Configuration File (MHCF), Merchant Host Interface Regulation-E File (MREG), Merchant Host Response File (MRSP), and Merchant Totals Configuration File (MTCF) are files used specifically by the Merchant Host Interface process. Documentation for these files is contained in the ***BASE24-pos Merchant Host Interface Manual***. The Visa II Terminal and Configuration Maintenance File (VVT) is used specifically by the Visa II Device Handler.

The Parameter Authentication File (PAF) is used specifically by the 4B Device Handler. Documentation concerning the 4B Device Handler is not available at this time.

The POS Report Generator (PRG) screen is used to generate periodic reports for the BASE24-pos product. Documentation for this screen is contained in the ***BASE24-pos Settlement and Reporting Manual***.

The SVHF and SVDF screens are documented in the ***BASE24-pos Stored Value Support Manual***.

Function Keys

The standard BASE24 function keys are used on BASE24-pos screens. These function keys are described in the ***BASE24 Base Files Maintenance Manual*** and in the ***BASE24 CRT Access Manual***. When the use of these function keys varies with BASE24-pos files and functions, the differences are noted with the screen descriptions for the file.

BASE24 products also supply an online Help screen which lists the function keys that apply to each screen. Operators can display the Help screen by pressing the **F12** key.

BASE24 Authorization Terminology

A number of terms are used throughout documentation to describe the various fields and how they function. It is important to understand the meaning of each of these terms as they are used in the BASE24 environment.

These terms are described in the ***BASE24 Base Files Maintenance Manual***.

2: Administrative Card File (ADMN)

The Administrative Card File (ADMN) contains one record for every valid administrative card number.

The ADMN defines administrative card numbers, retailer identifications, and the administrative transaction set that can be performed with particular administrative cards.

The CARD NUMBER and RETAILER ID fields combine to form the primary key to this file.

This section describes the file maintenance screen used to access records in the ADMN.

Screen 1

ADMN screen 1 is shown below, followed by descriptions of its fields.

```
BASE24-POS   ADMN FILE           LLLL       YY/MM/DD  HH:MM  01 OF 01
              ADMINISTRATIVE CARD FILE
CARD NUMBER:                                RETAILER ID:

              FIID:                        CLERK NAME:

              LAST RESET DATE:              PIN OFFSET:
              LAST USED DATE:              BAD PIN TRIES:      0
              ADMIN TXN PROFILE:          MAXIMUM PIN TRIES:    0

***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
              F12-HELP
```

ADMINISTRATIVE CARD FILE

The following fields define administrative card numbers, retailer IDs, and other parameters that can be set for specific administrative cards.

CARD NUMBER — The card number or primary account number (PAN) identifying the administrative card being defined. Currently BASE24 products support up to a 19-digit PAN.

Field Length:	1–28 numeric characters (currently 1–19 numeric characters are supported)
Required Field:	Yes
Default Value:	No default value
Data Name:	ADMN.PRIKEY.CARD-NUM

RETAILER ID — A unique identifier (retailer ID) for the retailer associated with this ADMN record.

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: ADMN.PRIKEY.RETAILER-ID

FIID — The FIID of the financial institution that issued the card. The FIID is an identifier which must be unique within the logical network.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: The FIID previously entered
Data Name: ADMN.FIID

CLERK NAME — The name of the operator who uses this card to perform BASE24-pos administrative transactions.

Field Length: 1–25 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: ADMN.CLERK-NAME

LAST RESET DATE — The date, in YYMMDD format, that the number of bad PIN tries for this record was last cleared. The Authorization process updates this field.

Field Length: System protected
Data Name: ADMN.LAST-RESET-DATE

PIN OFFSET — The PIN offset value for the card. The PIN offset is used in a PIN verification algorithm.

Field Length: 1–16 numeric characters
Required Field: No
Default Value: No default value
Data Name: ADMN.PIN-OFST

LAST USED DATE — The date, in YYMMDD format, that the administrative card was last used by the BASE24-pos product.

Field Length: System protected
Data Name: ADMN.LAST-USED-DATE

BAD PIN TRIES — The number of times the administrative cardholder has entered an incorrect PIN during the current usage accumulation period. Each institution defines the maximum number of incorrect PIN tries allowed by the cardholder in the MAXIMUM PIN TRIES field on this screen. When the number of incorrect PIN tries exceeds the value in the MAXIMUM PIN TRIES field, all transactions for the cardholder are denied subject to the settings in the PIN TRIES RESET OPTION field on screen 2 of the Institution Definition File (IDF) or on screen 2 of the Card Prefix File (CPF), depending on whether PIN verification parameters are defined at the institution level or the card prefix level.

This field is cleared when the Authorization process clears the usage accumulation totals in the CAF, or when the cardholder enters a correct PIN, subject to the settings in the PIN TRIES RESET OPTION field on screen 2 of the IDF or screen 2 of the CPF.

Field Length: System protected
Data Name: ADMN.BAD-PIN-TRY

ADMN TXN PROFILE — A code identifying a group of BASE24-pos transaction processing codes allowed for this administrative card. The value of this field is part of the key used to read the Acquirer Processing Code File (APCF) extended memory table. The value in this field overrides the default administrative card transaction profile defined at the institution level in the Institution Definition File (IDF).

Field Length: 16 alphanumeric characters
Required: No
Data Name: ADMN.ADMIN-TXN-PRFL

MAXIMUM PIN TRIES — The maximum number of times the institution allows an administrative cardholder to enter an incorrect PIN for a particular administrative card during a single usage accumulation period. Once a PIN has been entered incorrectly the maximum number of times, all further requests are denied and the BASE24 system takes the action designated in the BAD PIN ACTION field on screen 2 of the IDF or screen 2 of the CPF.

How the BASE24 system uses this field depends on the setting in the PIN TRIES RESET OPTION field on screen 2 of the IDF or screen 2 of the CPF. The value in this field can be overridden if the PIN TRIES RESET OPTION field contains a value of 2.

Field Length:	1–4 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	ADMN.MAX-PIN-TRY

ACI Worldwide, Inc.

3: Authorization Selection Table (AST)

The Authorization Selection Table (AST) defines authorization routing for BASE24-pos transactions. For a given transaction, each record defines by card type and issuer code, the primary authorizer, up to two secondary (alternate) authorizers, and a default action in the event that all authorizers specified are unavailable.

Records must be added to the Routing Table File (RTBL) before the AST data can be entered.

The FIID field and the RETAILER ID field combine to form the primary key to this file.

This section describes the file maintenance screens used to access records in the AST. Screens 1, 3, 5, and 7 are identical, and screens 2, 4, 6, and 8 are identical. Therefore, only screen 1, screen 2, and screen 9 are shown on the following pages.

Function Keys

The use of several function keys on the AST screens varies from the standard function keys explained in the ***BASE24 Base Files Maintenance Manual*** and the ***BASE24 CRT Access Manual***. The use of these function keys is explained in the table below.

The first column shows the BASE24 function key. The second column describes the functions that can be accomplished with these keys on the AST screens.

Key	Description
F3	Add Record — Adds a record to the file. The record must be unique within the file. The F3 key also automatically sorts reserved service codes according to the service code hierarchy listed in the F7 key description.
F5	Update Record — Changes a record already in the file. The record changed depends upon the data entered on the screen. The F5 key also automatically sorts reserved service codes according to the service code hierarchy listed in the F7 key description.

Key	Description
F7	Insert — Inserts data in the AST SERVICE fields by moving the last item in the list to the line above that in which the cursor is located. Only user-defined private label codes can be reordered using this function key. These codes always appear after the following reserved codes, which always appear in the order listed. —Visa debit (VD) (See BASE24-pos product note below) —Visa dual (VV) (See BASE24-pos product note below) —Visa credit (<i>Vb</i>) —MasterCard debit (MD) (See BASE24-pos product note below) —MasterCard dual (MM) (See BASE24-pos product note below) —MasterCard credit (<i>Mb</i>) —American Express credit (AX) —Discover (Sears) credit (DS) —User-defined private label credit (includes C, C0–C9, CA, and CC–CZ) —Carte Blanche credit (CB) —Diners Club credit (DC) —Japan Credit Bureau (JCB) credit (JB) —Special Check (SC) (BASE24-pos product only) —User-defined proprietary debit (includes P, P0–P9, and PA–PZ) —China UnionPay (CUP) credit (UP) —Demonstration (<i>Db</i>) —All services (**) —User-defined private label codes Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only. BASE24-pos Note: The BASE24-pos product does not allow MasterCard debit (MD), MasterCard dual (MM), Visa debit (VD), or Visa dual (VV) card types in the PRDF and POS Terminal Data files (PTD). The BASE24-pos product automatically includes the MD and MM card types with the MasterCard credit (<i>Mb</i>) card type, and automatically includes the VD and VV card types with the Visa credit (<i>Vb</i>) card type.

Key	Description
F7 <i>continued</i>	The F3 and F5 keys automatically reorder reserved service codes according to this hierarchy.
F8	RTBL — Displays data in the Routing Table File (RTBL) without exiting the AST or going back to the menu.

Screens 1, 3, 5, and 7

AST screens 1, 3, 5, and 7 contain the online and offline floor limits for single purchase, cash advance, and mail order transactions. The fields in the table occur up to 12 times per screen (or a total of 48 times for all four screens). One line of the table must be completed to add an AST record. AST screens 1, 3, 5, and 7 are identical; therefore, only screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS  AUTH SELECTION TABLE  LLLL  FIID  YY/MM/DD  HH:MM  01 OF 09
          FIID:          RETAILER ID:
          COMMENTS:

SERVICE          ISSUER          PUR          ADV          MO          LIM
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0
          0          0          0          0

***** BASE24 *****
          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
          F7-INSERT          F8-RTBL/RETURN          F12-HELP

```

FIID — The FIID of the financial institution or interchange to which the information contained in this AST record applies. The network participant (i.e., card issuer, interchange, terminal owner, or retailer sponsor) specifies the FIID that controls its transactions. The FIID must be unique within the logical network. Financial institution FIIDs are defined in the Institution Definition File (IDF), and interchange FIIDs are defined in the Interchange Configuration File (ICF) or Enhanced Interchange Configuration File (ICFE).

The BASE24-pos Router module uses one of three possible FIID values to locate an AST record containing an authorization table entry that matches the service and issuer codes received with the transaction.

If no CPF record exists and the TERM-FIID field in the BASE24-pos Standard Internal Message (PSTM) contains an entry other than zeros or blanks, the Router module attempts to locate a valid AST record using the FIID in the TERM-FIID field in the PSTM.

If no CPF record exists, the TERM-FIID field in the PSTM contains zeros or blanks, and the transaction did not originate at an interchange, the Router module reads the POS Retailer Definition File (PRDF) and attempts to locate a valid AST record using the FIID contained in the FIID field on screen 1 of the retailer sponsor's PRDF record.

If a CPF record exists, the Router module reads the CPF and attempts to locate a valid AST record using the FIID contained in the FIID field on screen 1 of the CPF record. When a CPF record exists and a valid AST record cannot be located using this FIID, the Router module can make a second attempt to locate a valid AST record, depending on the source of the transaction and the value of the POS-RTAU-AST-ROUTE param in the Logical Network Configuration File (LCONF). The POS-RTAU-AST-ROUTE param specifies whether the Router module makes the second attempt to locate a valid AST record when the transaction originated at a POS device or a host.

- If the transaction originated at a POS device or a host and the POS-RTAU-AST-ROUTE param is set to a value of 0 (normal routing), the Router module does not make a second attempt to locate a valid AST record.
- If the transaction originated at a POS device or a host and the POS-RTAU-AST-ROUTE param is set to a value of 1 (enhanced routing), the Router module searches for a valid AST record using the FIID in the TERM-FIID field in the PSTM, if available, or the FIID field on screen 1 of the retailer sponsor's PRDF record.
- If the transaction originated at an interchange, the Router module searches for a valid AST record using the FIID in the TERM-FIID field in the PSTM regardless of the POS-RTAU-AST-ROUTE param value. The Interchange Interface process obtains the value in the TERM-FIID field in the PSTM from the INTERCHANGE FIID field on screen 1 of an interchange's ICF or ICFE record. The Device Handler module obtains the value in the TERM-FIID field in the PSTM from the FIID field on BASE24-pos Terminal Data files (PTD) screen 1 for the terminal's record.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: The FIID previously entered
 Data Name: AST.PRI-KEY.FIID

RETAILER ID — A code uniquely identifying the retailer associated with this AST record or, for check guarantee and check verification transactions, a check routing group.

If the transaction is not a check guarantee or check verification transaction, this field can contain a retailer ID, a retailer program, or an asterisk. A retailer ID indicates that this record applies to that retailer only. A retailer program indicates that this record applies to all retailers with the specified program that do not have their own record. An asterisk indicates that this record applies to all retailers that do not have an AST record and do not participate in a retailer program that has its own AST record.

If the transaction is not a check guarantee or check verification transaction, the Router module searches for the specific retailer in this field. If it cannot find a match on a specific retailer ID, it checks for a match on the retailer program (set on screen 1 of the PRDF). If a retailer program is not found and a record containing an asterisk exists in the AST, the Router module uses the routing parameters in that record.

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: AST.PRI-KEY.RETAILER-ID

COMMENTS — User-defined comments about this AST record.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: AST.COMMENTS

SERVICE — A code identifying the type of card to which these routing parameters apply. A maximum of 48 entries can be placed in this field. This field can also be used to delete a card entry from the table by spacing over the SERVICE field of the card to be deleted and pressing the **F5** key.

Refer to the ***BASE24 Base Files Maintenance Manual*** for definitions and qualifications of the allowed service types.

Field Length: 1–2 alphanumeric characters
 Occurs: Up to 12 times per screen
 Required Field: Yes, at least one entry is required in order to add an AST record.
 Default Value: No default value
 Data Name: AST.AUTH-TBL.SRV

ISSUER — The issuer code to which these routing parameters apply.

The issuer codes to be entered in this field are defined in the ISSUER field on CPF screen 7. They range from 00 through 99. If routing parameters do not need to be set up for a specific issuer code, this field can be set to **b* (asterisk space). If the card type is SC (special check), this field must be set to **b* (asterisk space). If the card type is to be determined by SPROUTE routing or algorithm checking, this field must be set to 99. Special, Check (SC) is a special-use card type used to initiate BASE24-pos check guarantee and check verification transactions only.

A description of up to 10 characters must be entered following the code. These 10 characters are user-defined and can be used to describe some identifying characteristic for the entry, such as whether the issuer code represents an on-us (00 through 29) or not-on-us (30 through 99) card.

Field Length: 1–2 alphanumeric characters followed by a 1–10 character description
 Occurs: Up to 12 times per screen
 Required Field: Yes
 Default Value: No default value
 Data Name: AST.AUTH-TBL.ISS
 Data Name: AST.AUTH-TBL.ISS-DESC

----- ONLINE -----

The following three fields define the floor limits, by transaction type, for the service (card type) and issuer code defined on the same line of the table. Whether these floor limits are used depends upon parameters set in the BASE24-pos Terminal Data files.

A floor limit is used to determine the authorization entity for transactions based on the currency amount. If the transaction amount is greater than the floor limit, the transaction is sent to the OVER authorizer destination. If the transaction amount is less than or equal to the floor limit, the transaction is sent to the UNDER authorizer destination.

If both the ONLINE field in the AST and the CARD FLOOR LIMITS field in the PTD contain values greater than zero, the lesser floor limit for the transaction type is used. If the CARD FLOOR LIMITS field in the PTD is zero for the transaction type, the ONLINE field entry for the transaction type is used. If the ONLINE field in the AST is zero for the transaction type, any amount is considered to be over the floor limit.

ONLINE PUR — The floor limit, in whole currency units, allowed for all transactions except cash advances and mail or telephone orders. Valid entries are 0 through 999999999.

Field Length: 1–9 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: 0
Data Name: AST.AUTH-TBL.PR-FLR-LMT

ONLINE ADV — The floor limit, in whole currency units, allowed for cash advance transactions. Valid entries are 0 through 999999999.

Field Length: 1–9 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: 0
Data Name: AST.AUTH-TBL.CA-FLR-LMT

ONLINE MO — The floor limit, in whole currency units, allowed for mail or telephone order transactions. Valid entries are 0 through 999999999.

Field Length: 1–9 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: 0
Data Name: AST.AUTH-TBL.MO-FLR-LMT

OFFLINE LIM — The maximum amount, in whole currency units, allowed for the card type and issuer code combination defined on the same line of the table for all transactions when the primary and alternate authorizers designated on screen 2 of the AST are unavailable or when the authorizer is NEGF (National Negative Card File).

Field Length: 1–9 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: 0
Data Name: AST.AUTH-TBL.OFF-LMT

Screens 2, 4, 6, and 8

AST screens 2, 4, 6, and 8 contain the over and under routing destinations used to authorize transactions when the amount is either over or under the floor limit allowed for the designated card type and issuer code combination. Screens 2, 4, 6, and 8 also contain the default routing destination used when all authorizers identified on this screen are unavailable. AST screens 2, 4, 6, and 8 are identical; therefore, only screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-POS  AUTH SELECTION TABLE      LLLL  FIID  YY/MM/DD  HH:MM  02 OF 09
              FIID:                    RETAILER ID:
              COMMENTS:
SERVICE          ISSUER      P  A1  A2  DA  P  A1  A2  DA
----- OVER -----
----- UNDER -----

***** BASE24 *****
              FILE DESTINATION:          NEW LOGICAL NETWORK ID:
              F7-INSERT      F8-RTBL/RETURN      F12-HELP

```

SERVICE — The card type entered on the previous screen.

Field Length: System protected
Occurs: Up to 12 times per screen
Data Name: AST.AUTH-TBL.SRV

ISSUER — The issuer code entered on the previous screen.

Field Length: System protected
Occurs: Up to 12 times per screen
Data Name: AST.AUTH-TBL.ISS

----- OVER -----**----- UNDER -----**

The following fields contain codes defining authorization destinations for particular card type and issuer code combinations. Either the OVER or the UNDER authorizer destinations are used depending on whether the transaction is over or under the floor limit set by the card issuer or retail sponsor for this card type. The exception to this is MasterCard or Visa cards defined in the SERVICE field when the retailer designated in the RETAILER ID field for this AST record has a code T, A, or B in the RETAILER PROGRAM field on screen 1 of the POS Retailer Definition File (PRDF). In this case, the only authorization destinations used are those designated in the OVER fields (P, A1, A2).

OVER P — A code identifying the primary authorization destination that is checked for availability first when a transaction over the floor limit occurs for the indicated card type and issuer code. If this field is used, entries must match one of the identification values in the Routing Table File (RTBL).

Retailers can override the authorizer specified in this field by specifying a destination process name for card types in the OVERRIDE DEST PROCESS fields on screens 2 and 3 of the PRDF.

Valid values for this field are 01, 02, and 14. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL.

Field Length:	2 numeric characters
Occurs:	Up to 12 times per screen
Required Field:	Yes
Default Value:	No default value
Data Name:	AST.AUTH-TBL.OVER-LMT.PRI

OVER A1 — A code identifying the alternate authorization destination that is checked for availability when the primary authorization destination specified in the OVER P field is unavailable. If this field is used, the entry must match one of the identification values in the Routing Table File (RTBL).

Valid values are 00 and 01. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL. If the value in the OVER P field is 14, this field must be blank.

Field Length: 2 numeric characters or blank if the value in the OVER P field is 14
 Occurs: Up to 12 times per screen
 Required Field: No
 Default Value: No default value
 Data Name: AST.AUTH-TBL.OVER-LMT.ALT1

OVER A2 — A code identifying the alternate authorization destination that is checked for availability when the alternate authorization destination specified in the OVER A1 field is unavailable. If this field is used, the entry must match one of the identification values in the Routing Table File (RTBL).

Valid values are 00 and 01. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL. If the value in the OVER P field is 14, this field must be blank.

Field Length: 2 numeric characters or blank if the value in the OVER P field is 14
 Occurs: Up to 12 times per screen
 Required Field: No
 Default Value: No default value
 Data Name: AST.AUTH-TBL.OVER-LMT.ALT2

OVER DA — A code indicating the default action (DA) to take if all specified authorizers in the OVER fields in the AST are unavailable or if the OVER P field contains a value of 14. In order to take the action specified by the code in this field, the transaction amount must be less than or equal to the value in the OFFLINE LIM field for this card type and issuer code indicated on screens 1, 3, and 5. Valid values are as follows:

A = Authorize blind
 C = Issue a call
 D = Decline

Field Length: 1 alphabetic character
 Occurs: Up to 12 times per screen

Required Field: Yes
 Default Value: No default value
 Data Name: AST.AUTH-TBL.OVER-LMT.DFLT-ACTION

UNDER P — A code identifying the primary authorization destination that is checked for availability first when a transaction under the floor limit occurs for the indicated card type and issuer code. If this field is used, the entry must match one of the identification values in the Routing Table File (RTBL).

Retailers can override the authorizer specified in this field by specifying a destination process name for card types in the OVERRIDE DEST PROCESS fields on screens 2 and 3 of the PRDF.

Valid values are 00, 01, 02, and 14. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL.

Field Length: 2 numeric characters
 Occurs: Up to 12 times per screen
 Required Field: Yes
 Default Value: No default value
 Data Name: AST.AUTH-TBL.UNDER-LMT.PRI

UNDER A1 — A code identifying the alternate authorization destination that is checked for availability when the primary authorization destination specified in the UNDER P field is unavailable. If this field is used, the entry must match one of the identification values in the Routing Table File (RTBL).

Valid values are 00 and 01. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL. If the value in the UNDER P field is 14, this field must be blank.

Field Length: 2 numeric characters or blank if UNDER P is 14
 Occurs: Up to 12 times per screen
 Required Field: No
 Default Value: No default value
 Data Name: AST.AUTH-TBL.UNDER-LMT.ALT1

UNDER A2 — A code identifying the alternate authorization destination that is checked for availability when the alternate authorization destination specified in the UNDER A1 field is unavailable. If this field is used, the entry must match one of the identification values in the Routing Table File (RTBL).

Valid values are 00 and 01. Values between 04 and 13 and between 15 and 99 are valid if they are set in the RTBL. If the value in the UNDER P field is 14, this field must be blank.

Field Length: 2 numeric characters or blank if UNDER P is 14
Occurs: Up to 12 times per screen
Required Field: No
Default Value: No default value
Data Name: AST.AUTH-TBL.UNDER-LMT.ALT2

UNDER DA — A code indicating the default action (DA) to take if all specified authorizers in the UNDER fields in the AST are unavailable or if the UNDER P field contains a value of 14. In order to take the action specified by the code in this field, the transaction amount must be less than or equal to the value in the OFFLINE LIM field for this card type and issuer code on screens 1, 3, and 5.

Valid values are as follows:

A = Authorize blind
C = Issue a call
D = Decline

Field Length: 1 alphabetic character
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: No default value
Data Name: AST.AUTH-TBL.UNDER-LMT.DFLT-ACTION

Screen 9

AST screen 9 contains allowable authorization processes and their associated codes used for routing transactions. The information on this screen is taken from the Routing Table File (RTBL) and is for perusal only.

```
BASE24-POS    ROUTE-TABLE FILE          LLLL          YY/MM/DD  HH:MM  09 OF 09

DESTINATION PROC ID      DESTINATION PROC ID      DESTINATION PROC ID
AUTHF          00        AUTHH          01
NEGN           02        NEGF           03
DFLT           14        P1A^VISA      04
P1A^LINK       05        P1A^NET       06
```

```
***** BASE24 *****
FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                        F12-HELP
```

ID — The codes associated with the symbolic names in the DESTINATION PROCESS fields in the RTBL. Codes 00 through 03 and 14 are predefined and always remain the same. The remaining 37 codes are user-defined. These are the codes that are allowed in the Authorization Selection Table (AST).

Note: Codes 04, 05, and 06 are shown as examples only.

Field Length:	System protected
Occurs:	Up to 42 times
Data Name:	RTBL.AUTH.ID

DESTINATION PROC — The symbolic name of the allowable authorizers.

Five authorizers are predefined and always remain the same. The remaining 37 are user-defined but must match symbolic process names configured in the XPNET system.

Field Length:	System protected
Occurs:	Up to 42 times
Data Name:	RTBL.AUTH.NAM

ACI Worldwide, Inc.

4: Card Authorization Parameters File (CAPF)

The Card Authorization Parameters File (CAPF) contains one record for each credit card type supported by each card-issuing institution that uses the Parametric Authorization method. Each record contains criteria that expand on those defined in the Positive Balance File (PBF) and the Cardholder Authorization File (CAF) for use when considering transactions for authorization. The criteria contained in this file include an account delinquency check, a credit overlimit check, a single purchase check, and a single cash advance check.

When specified in the routing table in the BASE24-pos segment of the Institution Definition File (IDF), the Parametric Authorization method is used for the following transactions involving credit accounts: normal and preauthorization purchase, cash advance, mail or telephone order, purchase adjustment, and cash advance adjustment. Other transaction types involving credit accounts, as well as any transactions involving noncredit accounts, are processed using the Positive Balance Authorization method.

With the Parametric Authorization method, the BASE24-pos Authorization module checks the CAF for card status and account activity (e.g., times used, aggregate, cash withdrawals, and purchases) during the current usage accumulation period before it checks the PBF and CAPF. If the Authorization module determines that a transaction should be denied due to the information in the CAF, the transaction is denied regardless of the authorization parameters in the PBF and CAPF. If CAF checks are successful, the Authorization module then compares the PBF delinquency history to the CAPF delinquency table. Next, the Authorization module computes the amount of available credit, and uses the CAPF overlimit table in an attempt to authorize the transaction if sufficient credit is not available. Finally, the Authorization module checks the single transaction limits in the CAPF before approving the transaction.

This section describes the file maintenance screen used to access records in the CAPF.

Screen 1

CAPF screen 1 contains delinquency, overlimit, and single transaction values used by institutions supporting the Parametric Authorization method. CAPF screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS    CAPF FILE                LLLL  FIID  YY/MM/DD  HH:MM  01 OF 01
FIID:          CARD TYPE:  (******)    ISSUER: 00
                # OF USES EXCEEDED RESPONSE:  (******)

                LIMIT          PERCENT          RESPONSE
SINGLE PURCHASE:          0          0          D (DECLINE)
SINGLE ADVANCE:           0          0          D (DECLINE)

                DELINQUENT TABLE
TABLE    DAYS    ACTIVE    CYCLE 1    CYCLE 2    CYCLE 3    RESPONSE
A        30      36        0          0          0        D (DECLINE)
B        20      24        0          0          0        D (DECLINE)
C        10      12        0          0          0        D (DECLINE)

                OVERLIMIT TABLE
TABLE    PERCENT  ACTIVE    CYCLE 1    CYCLE 2    CYCLE 3    RESPONSE
A        30      36        0          0          0        D (DECLINE)
B        20      24        0          0          0        D (DECLINE)
C        10      12        0          0          0        D (DECLINE)

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP

```

FIID — The FIID of the card-issuing institution whose parameters are being defined. The FIID must be unique within the logical network.

Field Length: 1–4 alphanumeric characters

Required Field: Yes

Default Value: The FIID previously entered

Data Name: CAPF.PRI-KEY.FIID

CARD TYPE — A code identifying the type of card whose parameters are being defined. Debit cards are not processed using CAPF parameters. Codes used in this field are either reserved for BASE24 products or are user defined. Refer to the

BASE24 Base Files Maintenance Manual for a list of reserved codes and the qualifications that apply to user-defined codes. A text description is automatically displayed following the code.

Field Length: 1–2 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: CAPF.PRI-KEY.CRD-TYP

ISSUER — The issuer code to which the CAPF parameters are to be applied.

The issuer codes to be entered in this field are defined in the ISSUER field on screen 7 of the CPF. Valid values are 00 through 99.

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 00
Data Name: CAPF.PRI-KEY.ISS

OF USES EXCEEDED RESPONSE — A code indicating the action taken if the transaction cannot be authorized because the number of card uses exceeds the maximum number of uses allowed for the cardholder by the financial institution. A text description is automatically displayed following the code.

Authorization compares the value in the TIMES USED PER PERIOD LIMIT field on CPF screen 6 or the TIMES USED PER PERIOD LIMIT field on CAF screen 10 to the value in the TIMES USED THIS PERIOD field on CAF screen 10 to determine cardholder usage.

If the card has been used the number of times specified in the applicable TIMES USED PER PERIOD LIMIT field, the action specified by the code in this field is taken. Valid values are as follows:

D = Decline
C = Referral or issue a call me message
P = Pick up card

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: CAPF.NUM-USES-RESP

SINGLE PURCHASE LIMIT — The maximum amount, in whole currency units (e.g., 00250 for \$250.00 in U.S. currency), the card-issuing institution allows for a single credit account purchase. The final check made before approving a normal or preauthorization purchase or a mail or telephone order transaction uses this value or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by the SINGLE PURCHASE PERCENT field value in the CAPF, whichever is greater.

Field Length: 1–9 numeric characters
Required Field: Yes
Default Value: 0
Data Name: CAPF.SGL-PUR.LMT

SINGLE PURCHASE PERCENT — The maximum amount, expressed as a percentage of the value in the CREDIT LIMIT field on PBF screen 1, the card-issuing institution allows for a single credit account purchase. The final check made before approving a normal or preauthorization purchase or a mail or telephone order transaction uses the SINGLE PURCHASE LIMIT field value in the CAPF or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by this value, whichever is greater. Valid values are 0 through 100.

Field Length: 1–3 numeric characters
Required Field: Yes
Default Value: 0
Data Name: CAPF.SGL-PUR.PERCENT

SINGLE PURCHASE RESPONSE — A code indicating the action taken if the transaction cannot be authorized because the transaction amount is greater than the maximum amount allowed for a single purchase. A text description is automatically displayed following the code. The maximum amount allowed for a single purchase is the SINGLE PURCHASE LIMIT field value from the CAPF or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by the SINGLE PURCHASE PERCENT field value in the CAPF, whichever is greater. Valid values are as follows:

D = Decline
C = Referral or issue a call me message
P = Pick up card

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: CAPF.SGL-PUR.PUR-RESP

SINGLE ADVANCE LIMIT — The maximum amount, in whole currency units, the card-issuing institution allows for a single cash advance. The final check made before approving a cash advance transaction uses this value or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by the SINGLE ADVANCE PERCENT field value in the CAPF, whichever is greater.

Field Length: 1–9 numeric characters
Required Field: Yes
Default Value: 0
Data Name: CAPF.SGL-ADV.LMT

SINGLE ADVANCE PERCENT — The maximum amount, expressed as a percentage of the value in the CREDIT LIMIT field on PBF screen 1, allowed by the card-issuing institution for a single cash advance. The final check made before approving a cash advance transaction uses the value in the SINGLE ADVANCE LIMIT field in the CAPF or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by this value, whichever is greater. Valid values are 0 through 100.

Field Length: 1–3 numeric characters
Required Field: Yes
Default Value: 0
Data Name: CAPF.SGL-ADV.PERCENT

SINGLE ADVANCE RESPONSE — A code indicating the action taken if the transaction cannot be authorized because the advance amount requested is greater than the maximum amount allowed for a single advance. A text description is automatically displayed following the code. The maximum amount allowed for a single cash advance is the value in the SINGLE ADVANCE LIMIT field of the CAPF or the value in the CREDIT LIMIT field on PBF screen 1 multiplied by the SINGLE ADVANCE PERCENT field value in the CAPF, whichever is greater. Valid values are as follows:

D = Decline
P = Pick up card
C = Referral/call me

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: CAPF.SGL-ADV.ADV-RESP

DELINQUENT TABLE

Institutions employing the Parametric Authorization method use the DELINQUENT TABLE to establish the number of days and billing cycles an account can be delinquent and still have transactions authorized.

Fields from the PBF are compared to fields established in the DELINQUENT TABLE for the transaction's card type and issuer code combination. If the DAYS DELINQUENT field on screen 8 of the PBF record for the cardholder's account contains a zero, the account is not delinquent and, therefore, the transaction passes the DELINQUENT TABLE check and authorization continues with a check of available credit. If the DAYS DELINQUENT field on PBF screen 8 contains a value greater than zero, the data in the PARAMETRIC AUTH fields on PBF screen 8 is compared to the criteria established in the DELINQUENT TABLE.

One, two, or three levels of delinquency checks can be performed, based on the values contained in the DELINQUENT TABLE. Line A must be used alone when one level of checks is performed; lines A and B must be used together when two levels of checks are performed; and lines A, B, and C are used when three levels of checks are performed. Unused lines must contain zeros in the DAYS and ACTIVE fields. When used, values in the DAYS and ACTIVE fields on line B must be less than the corresponding values on line A and values in the DAYS and ACTIVE fields on line C must be less than the corresponding values on line B.

The BASE24-pos Authorization module uses the DELINQUENT TABLE as follows:

1. If the PBF data meets all the requirements on at least one line of the table, the Authorization module continues with a check of available credit.
2. If the DAYS DELINQUENT field value on PBF screen 8 is greater than the DAYS field value on line A, the Authorization module takes the action specified in the RESPONSE field on line A. If the DAYS check is successful but any of the other checks on line A are unsuccessful, the Authorization module continues checking delinquency using the values on line B.
3. If the DAYS DELINQUENT field value on PBF screen 8 is greater than the DAYS field value on line B, the Authorization module takes the action specified in the RESPONSE field on line B. If the DAYS check is successful but any of the other checks on line B are unsuccessful, the Authorization module continues checking delinquency using the values on line C.
4. If any of the checks on line C are unsuccessful, the Authorization module takes the action indicated in the RESPONSE field on line C.

TABLE — A system-generated field indicating the line of the table. Lines of the table are A, B, and C.

Field Length: System protected
Data Name: Not applicable

DAYS — The maximum number of days an account can be delinquent and still meet authorization requirements.

When all three DAYS fields are used, the entry in the DAYS field on line A of the table must be greater than the entry in the DAYS field on line B of the table, which must be greater than the entry in the DAYS field on line C of the table.

If the DAYS DELINQUENT field value on PBF screen 8 is greater than the value specified in the DAYS field on one of the lines, the Authorization module takes the action designated in the RESPONSE field on the same line. If the DAYS DELINQUENT field value on PBF screen 8 is less than or equal to the DAYS field value, other PBF data is checked against the remaining parameters on that line of the table.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes, a nonzero entry is required on line A.
Default Value: 0
Data Names: CAPF.DELINQ-TBL.A.DAYS-DELINQ (for line A)
CAPF.DELINQ-TBL.B.DAYS-DELINQ (for line B)
CAPF.DELINQ-TBL.C.DAYS-DELINQ (for line C)

ACTIVE — The minimum number of months this account can be active and still meet authorization requirements.

When all three ACTIVE fields are used, the entry in the ACTIVE field on line A of the table must be greater than the entry in the ACTIVE field on line B of the table, which must be greater than the entry in the ACTIVE field on line C of the table.

The MONTHS ACTIVE field on PBF screen 8 must be greater than or equal to the data contained in at least one of the ACTIVE fields in order for authorization to continue.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes, a nonzero entry is required on line A.

Default Value: 0
Data Names: CAPF.DELINQ-TBL.A.MONTHS-ACTIVE (for line A)
CAPF.DELINQ-TBL.B.MONTHS-ACTIVE (for line B)
CAPF.DELINQ-TBL.C.MONTHS-ACTIVE (for line C)

CYCLE 1 — The maximum number of times an account can be one cycle delinquent and still meet authorization requirements.

At refresh, the host specifies the number of times an account has been delinquent for one cycle. Cycles are user-defined and can represent days, weeks, months, statements, etc. Valid entries in this field are 0 through 36. Typically, the entry in the CYCLE 1 field on line A of the table is less than the CYCLE 1 entry on line B of the table, and the CYCLE 1 entry on line B of the table is less than the CYCLE 1 entry on line C of the table.

The data obtained from the number of 1, 2, and 3 cycles delinquent fields on PBF screen 8 cannot exceed the corresponding data on at least one line of the DELINQUENT TABLE in order for authorization to continue.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes
Default Value: 0
Data Names: CAPF.DELINQ-TBL.A.CYCLE-1 (for line A)
CAPF.DELINQ-TBL.B.CYCLE-1 (for line B)
CAPF.DELINQ-TBL.C.CYCLE-1 (for line C)

CYCLE 2 — The maximum number of times an account can be two cycles delinquent and still meet authorization requirements. Valid entries in this field are 0 through 24. Typically, the entry in the CYCLE 2 field on line A of the table is less than the CYCLE 2 entry on line B of the table, and the CYCLE 2 entry on line B of the table is less than the CYCLE 2 entry on line C of the table.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes
Default Value: 0
Data Names: CAPF.DELINQ-TBL.A.CYCLE-2 (for line A)
CAPF.DELINQ-TBL.B.CYCLE-2 (for line B)
CAPF.DELINQ-TBL.C.CYCLE-2 (for line C)

CYCLE 3 — The maximum number of times an account can be three cycles delinquent and still meet authorization requirements. Valid entries in this field are 0 through 12. Typically, the entry in the CYCLE 3 field on line A of the table is less than the CYCLE 3 entry on line B of the table, and the CYCLE 3 entry on line B of the table is less than the CYCLE 3 entry on line C of the table.

Field Length: 1–2 numeric characters
 Occurs: 3 times
 Required Field: Yes
 Default Value: 0
 Data Names: CAPF.DELINQ-TBL.A.CYCLE-3 (for line A)
 CAPF.DELINQ-TBL.B.CYCLE-3 (for line B)
 CAPF.DELINQ-TBL.C.CYCLE-3 (for line C)

RESPONSE — A code indicating the action taken if the transaction cannot be authorized because of the parameters set in fields on lines A, B, or C of the DELINQUENT TABLE. A text description is automatically displayed following the code.

The response on line A is used when the DAYS check on line A is unsuccessful. The response on line A is also used when any other check on line A is unsuccessful and the DAYS and ACTIVE fields on line B contain zeros. The response on line B is used when the DAYS check on line B is unsuccessful. The response on line B is also used when any other check on line B is unsuccessful and the DAYS and ACTIVE fields on line C contain zeros. The response on line C is used when any of the checks on line C are unsuccessful. Valid values are as follows:

D = Decline
 P = Pick up card
 C = Referral/call me

Field Length: 1 alphabetic character
 Occurs: 3 times
 Required Field: Yes
 Default Value: D
 Data Names: CAPF.DELINQ-TBL.A.RESP (for line A)
 CAPF.DELINQ-TBL.B.RESP (for line B)
 CAPF.DELINQ-TBL.C.RESP (for line C)

OVERLIMIT TABLE

Institutions employing the Parametric Authorization method use the OVERLIMIT TABLE to establish the percentage an account can be overlimit and the number of cycles it can be delinquent and still have transactions authorized.

Fields from the CAF and PBF are used to determine if a transaction will create an overlimit situation when it is approved. If an overlimit situation will not occur, the transaction passes the OVERLIMIT TABLE check and authorization continues with a check of the single transaction limits. An overlimit situation exists if the sum of the following values is greater than the amount in the CREDIT LIMIT field on PBF screen 1.

- Amount in the CREDIT BALANCE field on PBF screen 1.
- Amount in the TOTAL FLOAT field on PBF screen 8.
- Amounts in the PRE-AUTH HOLDS AMOUNT fields on CAF screen 5 or the PRE-AUTH HOLDS fields on PBF screen 3, depending on where preauthorized holds are being maintained.
- Amount of the transaction being authorized.

If an overlimit situation would be created for the account, the Authorization module calculates an overlimit percentage for comparison to the PERCENT field values in the OVERLIMIT TABLE for the transaction's card type and issuer code combination. The overlimit percentage is determined by the formula shown below.

Overlimit percentage equals:

$$\frac{100 \times (\text{PBF CREDIT BALANCE} + \text{PBF TOTAL FLOAT} + \text{CAF PRE-AUTH HOLDS or PBF PRE-AUTH HOLDS} + \text{TRANSACTION AMOUNT} - \text{PBF CREDIT LIMIT})}{\text{PBF CREDIT LIMIT}}$$

PBF CREDIT LIMIT

The calculated overlimit percentage and data in the PARAMETRIC AUTH fields on PBF screen 8 are compared to the criteria established in the OVERLIMIT TABLE. One, two, or three levels of overlimit checks can be performed, based on the values contained in the OVERLIMIT TABLE. Line A must be used alone when one level of checks is performed; lines A and B must be used together when two levels of checks are performed; and lines A, B, and C are used when three levels of checks are performed. Unused lines must contain zeros in the PERCENT and ACTIVE fields. When used, values in the PERCENT and ACTIVE fields on

line B must be less than the corresponding values on line A and values in the PERCENT and ACTIVE fields on line C must be less than the corresponding values on line B.

The BASE24-pos Authorization module uses the OVERLIMIT TABLE as follows:

1. If the calculated overlimit percentage and PBF data meet the criteria on at least one line of the table, the Authorization module continues with a check of the single transaction limits.
2. If the calculated overlimit percentage is greater than the PERCENT field value on line A, the Authorization module takes the action indicated in the RESPONSE field on line A. If the PERCENT check is successful but any of the other checks on line A are unsuccessful, the Authorization module continues checking overlimits using the values on line B.
3. If the calculated overlimit percentage is greater than the PERCENT field value on line B, the action indicated in the RESPONSE field on line B is taken. If the PERCENT check is successful but any of the other checks on line B are unsuccessful, the Authorization module continues checking overlimits using the values on line C.
4. If any of the checks on line C are unsuccessful, the Authorization module takes the action indicated in the RESPONSE field on line C.

TABLE — A system-generated field indicating the line of the table. Lines of the table are A, B, and C.

Field Length: System protected
Data Name: Not applicable

PERCENT — The maximum percentage an account can be over the credit limit allowed by the institution and still meet authorization requirements.

All PERCENT fields must contain entries between 0 and 100. When all three PERCENT fields are used, the entry in the PERCENT field on line A of the table must be greater than the entry in the PERCENT field on line B of the table, which must be greater than the entry in the PERCENT field on line C of the table.

If the overlimit percentage calculated by the Authorization module is greater than the value set in the PERCENT field on one of the lines, the Authorization module takes the action designated in the RESPONSE field on the same line. If the percentage calculated passes the PERCENT field criteria, other PBF data is checked against the remaining parameters on that line of the table.

Field Length: 1–3 numeric characters
Occurs: 3 times
Required Field: Yes, a nonzero entry is required on line A.
Default Value: 0
Data Names: CAPF.OVRLIM-TBL.A.PERCENT-OVR (for line A)
CAPF.OVRLIM-TBL.B.PERCENT-OVR (for line B)
CAPF.OVRLIM-TBL.C.PERCENT-OVR (for line C)

ACTIVE — The minimum number of months this account can be active and still meet authorization requirements.

When all three ACTIVE fields are used, the entry in the ACTIVE field on line A must be greater than the entry in the ACTIVE field on line B of the table, which must be greater than the entry in the ACTIVE field on line C of the table.

The MONTHS ACTIVE field on PBF screen 8 must be greater than or equal to the data contained in at least one of the ACTIVE fields in order for authorization to continue.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes, a nonzero entry is required on line A.
Default Value: 0
Data Names: CAPF.OVRLIM-TBL.A.MONTHS-ACTIVE (for line A)
CAPF.OVRLIM-TBL.B.MONTHS-ACTIVE (for line B)
CAPF.OVRLIM-TBL.C.MONTHS-ACTIVE (for line C)

CYCLE 1 — The maximum number of times an account can be one cycle delinquent and still meet authorization requirements.

At refresh, the host specifies the number of times an account has been delinquent for one cycle. Cycles are user-defined and can represent days, weeks, months, statements, etc. Valid entries in this field are 0 through 36. Typically, the entry in

the CYCLE 1 field on line A of the table is less than the CYCLE 1 entry on line B of the table, and the CYCLE 1 entry on line B of the table is less than the CYCLE 1 entry on line C of the table.

The data obtained from the number of 1, 2, and 3 cycles delinquent fields on PBF screen 8 cannot exceed the corresponding data on at least one line of the OVERLIMIT TABLE in order for authorization to continue.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes
Default Value: 0
Data Names: CAPF.OVRLIM-TBL.A.CYCLE-1 (for line A)
CAPF.OVRLIM-TBL.B.CYCLE-1 (for line B)
CAPF.OVRLIM-TBL.C.CYCLE-1 (for line C)

CYCLE 2 — The maximum number of times an account can be two cycles delinquent and still meet authorization requirements. Valid entries in this field are 0 through 24. Typically, the entry in the CYCLE 2 field on line A of the table is less than the CYCLE 2 entry on line B of the table, and the CYCLE 2 entry on line B of the table is less than the CYCLE 2 entry on line C of the table.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes
Default Value: 0
Data Names: CAPF.OVRLIM-TBL.A.CYCLE-2 (for line A)
CAPF.OVRLIM-TBL.B.CYCLE-2 (for line B)
CAPF.OVRLIM-TBL.C.CYCLE-2 (for line C)

CYCLE 3 — The maximum number of times an account can be three cycles delinquent and still meet authorization requirements. Valid entries in this field are 0 through 12. Typically, the entry in the CYCLE 3 field on line A of the table is less than the CYCLE 3 entry on line B of the table, and the CYCLE 3 entry on line B of the table is less than the CYCLE 3 entry on line C of the table.

Field Length: 1–2 numeric characters
Occurs: 3 times
Required Field: Yes
Default Value: 0

Data Names: CAPF.OVRLIM-TBL.A.CYCLE-3 (for line A)
 CAPF.OVRLIM-TBL.B.CYCLE-3 (for line B)
 CAPF.OVRLIM-TBL.C.CYCLE-3 (for line C)

RESPONSE — A code indicating the action taken if the transaction cannot be authorized because of the parameters set in fields on lines A, B, or C of the OVERLIMIT TABLE. A text description is automatically displayed following the code.

The response on line A is used when the PERCENT check on line A is unsuccessful. The response on line A is also used when any other check on line A is unsuccessful and the PERCENT and ACTIVE fields on line B contain zeros. The response on line B is used when the PERCENT check on line B is unsuccessful. The response on line B is also used when any other check on line B is unsuccessful and the PERCENT and ACTIVE fields on line C contain zeros. The response on line C is used when any of the checks on line C are unsuccessful. Valid values are as follows:

D = Decline
P = Pick up card
C = Referral/call me

Field Length: 1 alphabetic character
Occurs: 3 times
Required Field: Yes
Default Value: D
Data Names: CAPF.OVRLIM-TBL.A.RESP (for line A)
 CAPF.OVRLIM-TBL.B.RESP (for line C)
 CAPF.OVRLIM-TBL.C.RESP (for line D)

5: Check Authorization Routing Table File (CART)

The Check Authorization Routing Table File (CART) contains information that defines how check guarantee and check verification transactions are routed. If check guarantee and check verification transactions are not supported, the CART does not exist.

The BASE24-pos standard product provides check authorization processing as a *pass-through* function. The BASE24-pos product can receive check authorization transactions from a device, an ISO host, or an interchange. The BASE24-pos product then uses the CART to route the transactions to another destination where check authorization transactions are authorized. The authorizing entity then sends the transaction response back to the BASE24-pos product, which returns the transaction response to the entity that originated the transaction request. The BASE24-pos product does not authorize check authorization transactions.

When the BASE24-pos eCheck add-on product is installed, check guarantee and check verification transactions also can be authorized using the Positive Balance Authorization method with any authorization level. The BASE24-pos eCheck add-on product enables the authorizer to impact Positive Balance File (PBF) account balances upon authorization of check guarantee transactions. When check guarantee transactions are authorized offline by the BASE24-pos product, PBF balances on the BASE24 system are impacted immediately upon authorization. When check guarantee transactions are authorized online by the host or interchange, PBF balances on the BASE24 system can be impacted when the response is returned from the host or interchange, or the authorizer can choose not to impact the PBF.

The CART contains one record for each routing group and acquiring financial institution that processes check authorization transactions. These CART records define the entities to which check authorization transactions are routed for authorization. Each record can contain up to 36 entries. Check authorization transactions are routed according to transaction code, check guarantee and check verification service provider codes, and check ID type, all of which are included in

the CART record. The CART record also includes the FIID, the symbolic name, and the DPC number of the host as well as the authorization method and authorization level.

The primary key to the CART is a combination of the ROUTING GROUP and FIID fields. POS check routing groups are established in the CHECK RTG GROUP field in the POS Retailer Definition File (PRDF) record for each retailer. The FIID for the terminal owner is established in the BASE24-pos Terminal Data files. The FIID for an interchange is established in the Interchange Configuration File (ICF) or Enhanced Interchange Configuration File (ICFE). The alternate key to the CART is the INSTITUTION ID NUM field.

The CART consists of three identical screens. Therefore, only screen 1 of the CART is shown and described in this section.

```

BASE24-POS    CHECK AUTH RTG TBL          LLLL          YY/MM/DD  HH:MM  01 OF 03

ROUTING GROUP:          FIID:          INSTITUTION ID NUM:

TRAN          PROVIDER
CODE  CHECK ID TYPE      CODE  FIID    SYMBOLIC NAME      DPC  TYPE  LEVEL  SPF

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP

```

Field Length:	1–19 alphanumeric characters
Required Field:	Yes
Default Value:	No default value
Data Name:	CART.PRIKEY.RTG-GRP

5-3

the transaction includes the cardholder's primary account number (i.e., the FIID for the card prefix in the Card Prefix File). For interchange acquired transactions, the value in this field must match the FIID for the interchange from which the transaction was acquired (i.e., the FIID for the interchange in the Interchange Configuration File or Enhanced Interchange Configuration File) or the FIID for the card prefix as described above.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: CART.PRIKEY.FIID

INSTITUTION ID NUM — The institution routing number from the magnetic ink character recognition (MICR) data included in the check authorization transaction. If this field is used, the value must match the corresponding value for the acquiring institution in the Institution Definition File (IDF). If this field is not used, it can default to blanks or all zeros.

In the United States, this field can contain the routing and transit number of nine characters that should be right-justified and zero filled to the left.

Field Length: 11 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: CART.INST-ID-NUM

TRAN CODE — The transaction code for which these routing parameters apply. Valid values are as follows:

19 = Check verification
20 = Check guarantee
** = All

Field Length: 2 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes, at least one transaction code must be entered.
Default Value: No default value
Data Name: CART.RTE-TBL.TRAN-CDE

CHECK ID TYPE — A code indicating the type of identification used for the check guarantee or check verification transaction. This code is followed by a text description. Valid values are as follows:

01 = Credit card
02 = Drivers license
03 = Account number
04 = Debit card
05 = Cash card
06 = State identification
07 = Social security number
08 = Student identification
09 = Employee identification
10 = Passport number
11 = MICR data
** = All

Field Length: 2 alphanumeric characters
Occurs: Up to 12 times per screen
Required Field: Yes, at least one entry is required.
Default Value: No default value
Data Name: CART.RTE-TBL.CHK-ID-TYP

PROVIDER CODE — A value identifying the entity (e.g., 861400, 894400, etc.) that authorizes the funds for check guarantee and check verification transactions and to which these routing parameters apply. The value in this field must match the value in the CHECK SRV PROVIDER CODE field on screen 1 of the PRDF. Valid values are as follows:

1 = 861400
2 = 813500
3 = 894400
4 = 810000
5 = 763060
6 = 763057
7 = 762135
* = All

Note: Refer to the appropriate interchange-specific documentation for the names of companies associated with each check service provider code value. Although the provider code values listed above do not change, the companies associated with them may change from time to time.

Field Length: 1 alphanumeric character
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: No default value
Data Name: CART.RTE-TBL.CHK-PROVIDER

FIID — The FIID of the authorizer to which these transactions are to be routed. This field is for informational purposes only.

Field Length: 1–4 alphanumeric characters
Occurs: Up to 12 times per screen
Required Field: No
Default Value: No default value
Data Name: CART.RTE-TBL.FIID

SYMBOLIC NAME — The symbolic name of the Host Interface or Interchange Interface process used by the data processing center (DPC) identified in the DPC field. This symbolic name can identify either a host or an interchange.

Field Length: 1–16 alphanumeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: No default value
Data Name: CART.RTE-TBL.SYM-NAME

DPC — A value identifying the data processing center (DPC) to which check guarantee and check verification transactions are routed when the authorizer is the host.

Field Length: 1–4 numeric characters
Occurs: Up to 12 times per screen
Required Field: Yes
Default Value: 0
Data Name: CART.RTE-TBL.DPC

AUTH TYPE — A code indicating the type of authorization method used to process check authorization transactions. This field is used only when the BASE24-pos eCheck add-on product is installed. Valid value are as follows:

- 0 = Host authorization
- 3 = Positive balance authorization

A value of 3 in this field is valid only if the BASE24-pos eCheck add-on product is installed.

Field Length:	1 numeric character
Occurs:	Up to 12 times per screen
Required Field:	No
Default Value:	0
Data Name:	CART.RTE-TBL.AUTH-TYP

AUTH LEVEL — A code indicating the authorization level used to process check authorization transactions. The authorization level specifies the amount of participation a host has in the processing of a transaction. This field is used only when the BASE24-pos eCheck add-on product is installed. Valid values are as follows:

- 0 = Online, authorize transactions on the host only and do not update the PBF on the BASE24 system for host approvals (check guarantee transactions only). If the host is offline, deny the transaction. This code is used when the AUTH TYPE field contains a value of 0.
- 1 = Online, authorize transactions on the host only and update the PBF on the BASE24 system for host approvals (check guarantee transactions only). If the host is offline, deny the transaction. This code is used when the AUTH TYPE field contains a value of 0.
- 2 = Offline, authorize transactions on the BASE24 system only (includes updates to the PBF for approved check guarantee transactions).
- 3 = Online/offline, authorize transactions on the host if the host is online; if the host is offline, authorize transactions on the BASE24 system (includes updates to the PBF for approved check guarantee transactions) and forward completions to the host when the host is online.

Field Length: 1 numeric character
Occurs: Up to 12 times per screen
Required Field: No
Default Value: 0
Data Name: CART.RTE-TBL.AUTH-LVL

CHECK SPF — These fields are reserved for future use.

Field Length: 1 numeric character
Occurs: Up to 12 times per screen
Required Field: No
Default Value: 0
Data Name: CART.RTE-TBL.CHK-SPF

6: National Negative Card File (NNF)

The NNF screen allows operators with appropriate access to manually add card numbers to or delete card numbers from certain National Negative Card Files (NNFs). The card number entered on the NNF screen is checked against the INAS Negative File (INEG) for MasterCard, the BASE Negative File (BNEG) for Visa, or the American Express Negative File (ANEG) for American Express. The card number is entered on the screen by an operator and the system automatically adds or deletes the card number to or from the appropriate file, based on the card prefix and PAN length.

For example, if a card number is entered on the screen using the **F3** key (used to add card numbers to the appropriate national negative file), the system checks for a valid card prefix, based on an algorithm using the account number. If the card prefix is valid, the system checks the INEG, BNEG, and ANEG files for the card number and adds the card number to the appropriate national negative file. If the prefix is invalid or if the card is already on one of the national negative files, a message is displayed at the bottom of the screen to indicate the problem.

Note: When a card number is added to the INEG, BNEG, or ANEG from the NNF screen, the card status is left blank.

The NNFs contain one record for every restricted national credit, debit, and dual card. The NNFs are used to flag national cards that are restricted in some way (e.g., stolen, lost, overdrawn, etc.). The Authorization module checks these files to determine if a transaction request should be approved or denied. NNFs are normally maintained by refreshing the files from an update tape supplied by MasterCard, Visa, or American Express.

This section describes the file maintenance screen used to access the NNFs.

Note: The Authorization module can also check MasterCard national credit cards against the INAS National Range File (INR) and Visa national credit cards against the BASE1 National Range File (BNR). These NNFs are used to restrict blocks of national account numbers and cannot be accessed using the BASE24 CRT access system. Any changes to the INR and BNR must be made by performing a refresh on the files.

```
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:    NEW LOGICAL NETWORK ID:
                F12-HELP
```

Data Name: ANEG.CRD-NUM
 BNEG.CRD-NUM
 INEG.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

ACI Worldwide, Inc.

7: POS Retailer Definition File (PRDF)

The POS Retailer Definition File (PRDF) contains one record for each retailer in the logical network. These records are used in validating POS transactions and defining authorization and routing parameters.

The retailer ID is the primary key to this file. The FIID, retailer group, retailer region, and retailer ID form the alternate key to this file.

This section describes the file maintenance screens used to access the PRDF.

Screen 1

PRDF screen 1 contains retailer description information such as name, address, and telephone number. The lower portion of screen 1 contains retailer cutover times and posting dates. These fields are used to set terminal and retailer cutover parameters. PRDF screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS   RETAILER DEFINITION   LLLL           YY/MM/DD  HH:MM  01 OF 04
RETAILER ID:                FIID:           GROUP:           REGION:

RETAILER NAME:
ADDRESS:
  CITY:                STATE:                COUNTY:
POSTAL CODE:          COUNTRY:                RTTN: 000000000000
ACCT #:
PHONE:                AFTER HOURS PHONE:
  SIC CODE:           0
MAIL/PHONE SIC CODE:  0          SERVICE ESTABLISHMENT #:          0
ACH COMP ID:                REFERRAL PHONE:
RETAILER PROG: R  (REGULAR)    SETTLEMENT METHOD: D (DRAFT CAPTURE)

CHECK MERCH ID:                CHECK SRV PROVIDER CODE: 0 (NONE)
CHECK RTG GROUP:

RETAILER CUTOVER/BALANCE START: 00:00          END: 00:00
POSTING DATES          PREVIOUS: 000000    CURRENT: 000000    NEXT: 000000

***** BASE24 *****
NEW PAGE:                FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                        F12-HELP

```

RETAILER ID — A code used to uniquely identify this retailer.

Field Length: 1–19 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: PRDF.RKEY.RETAILER-ID

FIID — The FIID of the financial institution with which this retailer is associated. The FIID is an identifier which must be unique within the logical network.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: The FIID previously entered
 Data Name: PRDF.RKEY.FIID

GROUP — An identifier indicating the retailer group with which this retailer is associated for reporting purposes.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RKEY.GRP

REGION — A code identifying the retailer region to which this retailer belongs. The field is used for reporting purposes.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RKEY.REGN

RETAILER NAME — The name of the retailer.

Field Length: 1–40 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RETAILER.NAME

ADDRESS — The address where the retailer is located.

Field Length: 1–25 alphanumeric characters
Occurs: 2 times, with the fields separated by a space.
Required Field: Yes, the first field is required; the second field is an address extension and is not required.
Default Value: No default value
Data Name: PRDF.RETAILER.ADDR
Data Name: PRDF.RETAILER.ADDR-EXT

CITY — The city in which the retailer is located.

Field Length: 1–18 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RETAILER.CITY

STATE — A code indicating the state in which the retailer is located.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.ST

COUNTY — A code indicating the county in which the institution is located.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.CNTY

POSTAL CODE — The postal code corresponding to the location of the BASE24-pos terminal performing the transaction. In the United States, postal code is synonymous with ZIP code.

Example: 681540000
Field Length: 1–10 alphanumeric characters
Required Field: No, unless required by authorizing entities.
Default Value: No default value
Data Name: PRDF.RETAILER.POSTAL-CDE

COUNTRY — The country code associated with the country in which the retailer is located.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.CNTRY

RTTN — The Route Transit Number (RTTN), transit/routing number, or issuer identification number for this retailer. This field is not currently used, although the BASE24 system requires a value to be entered.

The data is right-justified and zero-filled to the left. This field will default to zeros, but cannot be left as zeros.

Field Length: 11 numeric characters
Required Field: Yes
Default Value: 00000000000
Data Name: PRDF.RETAILER.RTTN

ACCT # — The account number associated with the retailer at its associated financial institution. Currently BASE24 products support up to a 19-digit account number.

Field Length: 1–28 numeric characters (currently 1–19 numeric characters are used)
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RETAILER.ACCT

PHONE — The telephone number of the retailer.

Example: (402)390-7600
Field Length: 1–20 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PRDF.RETAILER.PHONE

AFTER HOURS PHONE — The telephone number to use in the event that a terminal needs repair after business hours.

Example: (402)390-7600
Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.AFT-HRS-PHONE

SIC CODE — The Standard Industrial Classification (SIC) code or Category code identifying the retailer's line of business. This field does not pertain to mail or telephone order transaction retailers.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: 0
Data Name: PRDF.RETAILER.SIC-CDE

MAIL/PHONE SIC CODE — The Standard Industrial Classification (SIC) code or Category code identifying the mail or telephone order retailer's line of business.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: 0
Data Name: PRDF.MAIL-PO-SIC-CDE

SERVICE ESTABLISHMENT # — The service establishment number assigned by American Express used to identify this retailer.

Field Length: 1–10 numeric characters
Required Field: No
Default Value: 0
Data Name: PRDF.RETAILER.SRV-EST-NUM

ACH COMP ID — The Automated Clearing House (ACH) company identification code. This code identifies the ACH associated with the retailer. It can also be used by the ACH to identify the retailer.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.ACH-COMPANY-ID

REFERRAL PHONE — The telephone number the retailer uses when referring a transaction authorization because the BASE24 system or another authorizing entity is unable to authorize the transaction.

Example: 4023907600
Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RETAILER.RFRL-PHONE

RETAILER PROG — A code identifying the program under which this retailer operates. A text description is automatically displayed following the code.

All alphabetic characters are valid for this field. However, certain characters are predefined codes. Values 1 through 9 and alphabetic characters not listed below are user-defined. Predefined valid values are as follows:

A = MasterCard retailer program
B = MasterCard and Visa retailer programs
N = Non-dial
R = Regular program or standard Interlink merchant
T = Visa retailer program
W = Pre-existing qualified Interlink supermarket
X = Pre-existing Interlink merchant
Y = Qualified Interlink supermarket
Z = All programs
0 = No program

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: R
Data Name: PRDF.RETAILER-PROG

SETTLEMENT METHOD — A code indicating the settlement method used by the retailer. A text description is automatically displayed following the code. Valid values are as follows:

P = Paper
D = Draft capture by card type

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: PRDF.SETL

CHECK MERCH ID — The merchant ID by which the check acceptance vendor refers to the merchant.

Field Length: 1–15 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.CHK-MRCHNT-ID

CHECK SRV PROVIDER CODE — A code that identifies the entity (e.g., 861400, 894400, etc.) that authorizes the funds. The check service provider value is automatically displayed following the code. Valid values are as follows:

0 = None
1 = 861400
2 = 813500
3 = 894400
4 = 810000
5 = 763060
6 = 763057
7 = 762135

Note: Refer to the appropriate interchange-specific documentation for the names of companies associated with each check service provider code value. Although the provider code values listed above do not change, the companies associated with them may change from time to time.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: PRDF.CHK-PROVIDER

CHECK RTG GROUP — The routing group by which the check acceptance transaction will be routed. This field is used for CART-based routing of check guarantee and check verification transactions.

Field Length: 1–11 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.CHK-RTG-GRP

RETAILER CUTOVER/BALANCE START — The first of two hour and minute fields (hh:mm) based on 24-hour time that establish the retailer's cutover time window. This field identifies the beginning time.

For retailers that are cut over using a close transaction (the **TERMINAL CUTOVER** field on PTD screen 3 is set to a value of 0, 1, or 2), the time in this field designates the beginning of the time period during which POS terminals are normally cut over. For retailers that are cut over using a financial transaction (the **TERMINAL CUTOVER** field on PTD screen 3 is set to value of 4), this field designates the time period during which these POS terminals can cut over.

The time entered in this field must be less than the time entered in the **BALANCE END** field. The time defaults to zeros but cannot be left as zeros.

When entering a time, a colon can be blanked out or entered. Either way, the colon is displayed. The system edits the four numbers entered into hh:mm format.

Example:	14:00
Field Length:	4 numeric characters
Required Field:	Yes
Default Value:	00:00 (midnight)
Data Name:	PRDF.RETAILER-BAL-AND-CUTVR-STRT

RETAILER CUTOVER/BALANCE END — The second of two hour and minute fields (hh:mm) based on 24-hour time that establish the retailer's cutover time window. This field identifies the ending time.

Terminals not cut over by the time specified in this field are cut over automatically to a new posting date by either the Settlement Initiator process or the Device Handler module.

For retailers using forced cutover (i.e., the **TERMINAL CUTOVER** field on PTD screen 3 is set to a value of 3), the time in this field is the time the Settlement Initiator process cuts over the retailer's terminals to a new posting date.

The time entered in this field must be greater than the time entered in the **BALANCE START** field. The time defaults to zeros but cannot be left as zeros.

When entering a time, a colon can be blanked out or entered. Either way, the colon is displayed. The system edits the four numbers entered into hh:mm format.

Example: 14:00
Field Length: 4 numeric characters
Required Field: Yes
Default Value: 00:00 (midnight)
Data Name: PRDF.RETAILER-BAL-AND-CUTVR-END

POSTING DATES PREVIOUS — The BASE24-pos product automatically displays the posting date (YYMMDD) used by the retailer prior to the last cutover. The previous posting date must be one day less than the current posting date.

At retailer cutover (the end time indicated in the RETAILER CUTOVER/BALANCE END field on this screen) the date is increased by one to the next calendar day. The value in this field always follows a seven-day-per-week schedule.

The date in this field can be changed for record maintenance purposes (i.e., in the event that the Settlement Initiator process fails).

Field Length: 6 numeric characters
Required Field: Yes
Default Value: 000000
Data Name: PRDF.PRE-POST-DAT

POSTING DATES CURRENT — The BASE24-pos product automatically displays the posting date (YYMMDD) currently used by the retailer.

At retailer cutover (the end time indicated in the RETAILER CUTOVER/BALANCE END field on this screen) the date is increased by one to the next calendar day. The value in this field always follows a seven-day-per-week schedule.

The date in this field can be changed for record maintenance purposes (i.e., in the event that the Settlement Initiator process fails).

Field Length: 6 numeric characters
Required Field: Yes
Default Value: 000000
Data Name: PRDF.CUR-POST-DAT

POSTING DATES NEXT — The BASE24-pos product automatically displays the posting date (YYMMDD) used by the retailer following the next cutover. The next posting date must be one day greater than the current posting date.

At retailer cutover (the end time indicated in the RETAILER CUTOVER/BALANCE END field on this screen) the date is increased by one to the next calendar day. The value in this field always follows a seven-day-per-week schedule.

The date in this field can be changed for record maintenance purposes (i.e., in the event that the Settlement Initiator process fails).

Field Length:	6 numeric characters
Required Field:	Yes
Default Value:	000000
Data Name:	PRDF.NXT-POST-DAT

Screens 2 and 3

PRDF screens 2 and 3 contain authorization parameters, by card type, for transactions processed for the retailer. Screens 2 and 3 also determine if the National Negative Files (NNFs) should be checked for transactions attempted with a particular card type. Up to 15 entries are allowed on each PRDF screen. PRDF screens 2 and 3 are identical; therefore, only PRDF screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-POS  RETAILER DEFINITION  LLLL  YY/MM/DD  HH:MM  02 OF 04
RETAILER ID:  FIID:  GROUP:  REGION:
          DRAFT  OVERRIDE  DEST  NNEG  CEILING  ALTERNATE
          CARD TYPE  CAPTURE  PROCESS  FIRST  LIMIT  MERCHANT ID

```

```

***** BASE24 *****
NEW PAGE:  FILE DESTINATION:  NEW LOGICAL NETWORK ID:
          F12-HELP

```

CARD TYPE — A code identifying the types of cards to which the authorization parameters apply. A maximum of 30 entries can be placed in this field. No edit checks are performed on this field, with the exception of the M**b** and V**b** values, where **b** denotes a blank space.

Codes used in this field are either reserved for BASE24 products or are user-defined. Refer to the ***BASE24 Base Files Maintenance Manual*** for a list of reserved codes and the qualifications of user-defined codes.

Field Length: 1–2 alphanumeric characters
Occurs: Up to 15 times per screen
Required Field: Yes
Default Value: No default value
Data Name: PRDF.SRV-INFO.SRV-INFO-DATA

DRAFT CAPTURE — The default draft capture value used for transactions performed through the BASE24-pos CRT Authorization add-on product. If a CRT authorization operator does not enter a draft capture value with a transaction, the value in this field is used to determine whether draft capture is used with the transaction for this retailer. This field is used exclusively for transactions performed through the BASE24-pos CRT Authorization add-on product. Valid values are as follows:

0 = Authorize only
1 = Authorize and capture

Field Length: 1 numeric character
Occurs: Up to 15 times per screen
Required Field: Yes
Default Value: 0
Data Name: PRDF.SRV-INFO.SRV-INFO-DATA

OVERRIDE DEST PROCESS — A field that allows retailers to override authorization destinations that are displayed in the AST record for this retailer and service type. Valid entries for this field are the symbolic names of the destination processes. This field overrides the OVER and UNDER authorizer P fields in the AST for the card type or service.

Field Length: 1–16 alphanumeric characters
Occurs: Up to 15 times per screen
Required Field: No
Default Value: No default value
Data Name: PRDF.SRV-INFO.SRV-INFO-DATA

NNEG FIRST — A code identifying whether the National Negative Card Files (NNFs) should be accessed for the card type specified on the same line of the table.

If the code in this field is Y and the card number is contained in the appropriate NNF, the transaction can be approved VIP, denied, or referred based on the card status value in the NNF record. If the code in this field is Y and the card number is

not contained in the appropriate NNF, the transaction is sent to the primary destination in the Authorization Selection Table (AST) for further authorization. Valid values are as follows:

Y = Yes, access the NNFs first for this card type.

N = No, do not access the NNFs first for this card type.

Field Length: 1 alphabetic character

Required Field: Yes

Default Value: N

Data Name: PRDF.SRV-INFO.SRV-INFO-DATA

CEILING LIMIT — The maximum amount, in whole currency units, this retailer allows for a single transaction associated with the card type on the same line of the table. Entries in this field are overridden by accounts with VIP statuses.

If both the CEILING LIMIT field in the PRDF and the TRAN LIMIT field in the PTD contain values greater than zero, the lesser amount limit for the card type is used.

If the CEILING LIMIT field entry for the card type in the PRDF contains a value greater than zero and the TRAN LIMIT field in the PTD is zero for the card type, the CEILING LIMIT field entry for the card type in the PRDF is used.

If the CEILING LIMIT field in the PRDF is zero and the TRAN LIMIT field in the PTD contains a value greater than zero for the card type, the TRAN LIMIT field entry for the card type in the PTD is used.

If the CEILING LIMIT field the PRDF is zero and the TRAN LIMIT field in the PTD is zero for the card type, a limit check on the transaction amount is not performed.

Field Length: 1–9 numeric characters

Occurs: Up to 15 times per screen

Required Field: Yes

Default Value: 0

Data Name: PRDF.SRV-INFO.SRV-INFO-DATA

ALTERNATE MERCHANT ID — The retailer's alternate merchant ID for the card type. The alternate merchant ID can be assigned by interchanges to merchants that accept their cards.

Field Length:	1–15 alphanumeric characters
Occurs:	Up to 15 times per screen
Required Field:	No
Default Value:	No default value
Data Name:	PRDF.SRV-INFO.SRV-INFO-DATA

Screen 4

PRDF screen 4 contains settlement reporting controls, a flag indicating whether debit cards can be used with the BASE24-pos CRT Authorization add-on product, and transaction profiles. PRDF screen 4 is shown below, followed by descriptions of its fields.

```
BASE24-POS   RETAILER DEFINITION   LLLL   YY/MM/DD   HH:MM   04 OF 04
RETAILER ID:   FIID:   GROUP:   REGION:

      SETTLEMENT REPORTING INFORMATION

      PRINT LOCATION: $S.#RETL
        REPORT SET: 0   (ALL REPORTS)
      RETAIN REPORTS: 7   (DAYS)

      CRT AUTHORIZATION DEBIT CARD SUPPORT: N

ACQUIRER TXN PROFILE:
RETAILER TXN PROFILE:

      EMV DELAYED AUTH SUPPORT:
        AMEX SE NUMBER CHECK:
        AUTH PARTIAL AMOUNT:

***** BASE24 *****
NEW PAGE:   FILE DESTINATION:   NEW LOGICAL NETWORK ID:
              F12-HELP
```

SETTLEMENT REPORTING INFORMATION

The following three fields control settlement reporting for this retailer.

PRINT LOCATION — The spooler location where this retailer's daily activity reports are printed.

This field must contain the characters \$S.# followed by an alphabetic character. This field can also contain a HP NonStop system name, a spooler location group, and a spooler location destination.

Example: \PRO1.\$S.#PRNTR1
Field Length: 5–16 alphanumeric characters
Required Field: Yes
Default Value: \$S.#RETL
Data Name: PRDF.MERCH-ACTIVITY-RPT.PRNT-LOC

REPORT SET — A value indicating the types of reports being created. Valid values are as follows:

- 0 = All reports
- 1 = All reports (print separate totals pages)
- 2 = Totals pages only
- 3 = No reports

Field Length: 1 numeric character
Required Field: No
Default Value: 0
Data Name: PRDF.MERCH-ACTIVITY-RPT.RPT-CREATION-FLG

RETAIN REPORTS — The number of days periodic data is retained in the Periodic Retailer Report File (PRRF) for this retailer. The Report programs automatically purge data that is dated outside the report retention period specified by the entry in this field. Valid values are 0 through 999.

Field Length: 1–3 numeric characters
Required Field: Yes
Default Value: 7
Data Name: PRDF.MERCH-ACTIVITY-RPT.PERIODIC-FILE-RET

CRT AUTHORIZATION DEBIT CARD SUPPORT — A code used to determine whether transactions can be performed through the BASE24-pos CRT Authorization add-on product using debit cards. This field is used exclusively with the BASE24-pos CRT Authorization add-on product. Valid values are as follows:

- Y = Yes, support transactions performed with debit cards through CRT Authorization.
- N = No, do not support transactions performed with debit cards through CRT Authorization.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PRDF.DEBIT-SUPPORT-FLG

ACQUIRER TXN PROFILE — A code identifying a group of BASE24-pos cardholder transaction processing codes allowed at POS terminals for this retailer. The value of this field is part of the key used to read the Acquirer Processing Code File (APCF) extended memory table. The value in this field overrides the default acquirer transaction profile at the institution level in the Institution Definition File (IDF). The acquirer transaction profile must be defined in the APCF before it can be used here.

Field Length: 16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.ACQ-TXN-PRFL

RETAILER TXN PROFILE — A code identifying a group of BASE24-pos administrative transaction processing codes allowed for this retailer that require employees to use an administrative card. The value of this field is part of the key used to read the Acquirer Processing Code File (APCF) extended memory table. The value in this field overrides the default retailer transaction profile defined at the institution level in the Institution Definition File (IDF). The retailer transaction profile must be defined in the APCF before it can be used here.

Field Length: 16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PRDF.RTLR-TXN-PRFL

EMV DELAYED AUTH SUPPORT — A code indicating whether the retailer supports EMV delayed authorizations. Valid values are as follows:

Y = Yes, the retailer supports delayed authorizations.
N = No, the retailer does not support delayed authorizations.

Field Length: 1 alphanumeric character
Required Field: N
Default Value: No default value
Data Name: PRDF.EMV-DELAYED-AUTH-SPPT

AMEX SE NUMBER CHECK — A code identifying whether additional validation of the American Express SE number can be performed for this retailer. Valid values are as follows:

b = Not used (where *b* denotes a blank space)
Y = Yes, perform additional validation.
N = No, do not perform additional validation.

Field Length: 1 alphanumeric character
Required Field: N
Default Value: No default value
Data Name: PRDF.SRV-EST-NUM-CHK

AUTH PARTIAL AMOUNT — A code indicating whether a retailer allows partial authorization for all transaction types, only for transactions not involving cash or not for any transactions. Valid values are as follows:

0 = Not allowed.
1 = Lesser allowed.
2 = Non-cash only.

Field Length: 1 numeric character
Required Field: No
Default Value: 0
Data Name: AUTH-PARTIAL-AMT

ACI Worldwide, Inc.

8: POS Terminal Data Files (PTD)

The POS Terminal Data files contain one record for every point-of-sale (POS) terminal in the logical network.

The POS Terminal Data files define the characteristics of the POS terminal, including the transaction security methods, terminal owner, logging and transaction data, floor limits, card type, and the POS retail transaction set. POS Terminal Data files are also used to accumulate transaction and settlement counts and amounts and preserve transaction context. POS Terminal Data files are read and updated every time a transaction is processed for a POS terminal.

This section describes the file maintenance screens used to access the POS Terminal Data files.

Data entered on POS Terminal Data files (PTD) screens is actually stored in different files, depending on the type of terminal being defined. For Hypercom and Standard POS Device Handler terminals, dynamic data is stored in the POS Terminal Data Dynamic File—general data (PTDD1) and static data is stored in the POS Terminal Data Static File—general data (PTDS1). For all other types of POS terminals, all data from the PTD screens is stored in the POS Terminal Data File (PTDF). If changes are made to the Terminal Data Static File—general data (PTDS1) and the LCONF param POS-DH-PTD-STATIC-REPL is set to “Y”, the Standard POS Device Handler (SPDH) will load these changes without rebooting.

Note: When adding a record for a new terminal that uses hardware-encrypted keys, and the Transaction Security Services process is implemented, you also must add a corresponding record to the Channel Security Configuration File (CSECD). For more information on the Transaction Security Services process and the CSECD, refer to the *BASE24 Transaction Security Services Processing Guide*.

Grouping Terminals at a Site

BASE24 users must add a PTD record for each terminal in the system. In the case of some retailers, for example a pay-at-the-pump service station or a grocery store, multiple terminals exist at a single site. To aid with shared files maintenance and accumulation of aggregate transaction totals, the Standard POS Device Handler process (SPDH) supports grouping terminals by site.

A site configuration uses one PTD record for each terminal at the site plus one PTD record for the site itself. The value in the SITE ID field on PTD screen 1 identifies a site. The site-level PTD records are called primary records, and the terminal-level PTD records are called secondary records. Each site can have only one primary PTD record. For example, assume that a retailer has three merchant sites and a primary record is entered in the PTD for each site. The SITE IDs for these records are East, West, and North. The East site has 18 terminals, the West site has 24 terminals, and the North site has 13 terminals. In this example, the PTD holds one primary and 18 secondary records for the East site, one primary and 24 secondary records for the West site, and one primary and 13 secondary records for the North site.

Once the primary and all secondary PTD records have been created for a site, modifications made to the primary record can be applied to all secondary records sharing the same SITE ID value. By using the **Shift-F5** function key, the contents of the user-modifiable PTDS1 fields (other than TERMINAL ID and TERMINAL TYPE fields) are copied from the primary record to every secondary record.

The primary record also is used to accumulate the site's aggregate transaction totals. Refer to the *Standard POS Device Configuration Manual* for additional information on transaction totals.

Function Keys

The use of three function keys on the PTD screens varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained in the table below.

The first column shows the BASE24 function key. The second column describes the functions that can be accomplished with these keys on the PTD screens.

Key	Description
Shift-F2	Read Site Primary Record — Reads the primary record for the value entered in the SITE ID field.
Shift-F5	Update Site Secondary Records — Changes all of the selected site's secondary records with inheritable data from the site's primary record. The site's primary record must first be read using the Shift-F2 key, and updated using the F5 key, before using the Shift-F5 key to update the secondary records. When the Shift-F5 is pressed, every secondary record with the same value in the SITE ID field is updated with inheritable data from the primary record. Note: User-modifiable PTDS1 fields of all secondary PTD records associated with a primary PTD record are overwritten by this function. Any changes made to user-modifiable PTDS1 fields of individual secondary PTD records will have to be reapplied.
Shift-F6	Read Next Record by Site ID — Reads the next record sequentially by Site ID.

Screen 1

PTD screen 1 defines characteristics of the POS device such as terminal identification, location, type, and owner. PTD screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS   TERMINAL DATA           LLLL      YY/MM/DD  HH:MM  01 OF 19

  TERMINAL ID:                               FIID:
  RETAILER GROUP:                           LOGICAL NET:
    SITE ID:                               REGION:
    LOCATION:                             RECORD TYPE:
    STATE:                                CITY:
    COUNTRY:                             POSTAL CODE:
  TERMINAL TYPE:      (******)          PROTOCOL:      (N/A)
  TERMINAL PHONE:      BAUD RATE: 99      (N/A)
  TERMINAL OWNER:      TERM GROUP:
    TIME OFFSET:      0                  RELEASE #: 00
    TERM SIC CODE:    0                  MAIL/PHONE SIC CODE: 0
    RETAILER ID:      RTN: 000000000000
    TERM STATUS:  D (DEACTIVATED )      BILLING INFO:
    CLERK ID:      LANGUAGE ID: 0

  DH PROCESS NAME:                        DFLT CHECK ID:  (******)
  ROUTING GROUP:                        DUAL SITE INDICATOR:

***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                F12-HELP

```

TERMINAL ID — An identifier (terminal ID) for the BASE24-pos terminal associated with this record. Each entry in the TERMINAL ID field must be unique within the logical network. An attempt to add a duplicate TERMINAL ID will be rejected. This field is an alternate key to the POS Terminal Data files.

Field Length: 1–16 alphanumeric characters
 Required Field: Yes
 Default: No default value
 Data Name: PTDD1.TERM-ID
 PTDS1.TERM-ID
 PTDF.REC.TERM-ID

FIID — The FIID of the financial institution associated with this terminal. The REGION, GROUP, RETAILER ID, and LOGICAL NET fields combine with this field to form an alternate key to the indicated POS Terminal Data files.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: The FIID previously entered
Data Name: PTDD1.TERM-OWNER.FIID
PTDF.REC.TERM-OWNER.FIID

LOGICAL NET — The name of the logical network to which the BASE24-pos terminal owner belongs.

Field Length: System protected
Data Name: PTDD1.TERM-OWNER.LN
PTDF.REC.TERM-OWNER.LN

RETAILER GROUP — An identifier indicating the retailer group with which this BASE24-pos terminal is associated for reporting purposes. The group entered in this field must match the group in the POS Retailer Definition File (PRDF).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDD1.TERM-OWNER.RETAILER-GRP
PTDF.REC.TERM-OWNER.RETAILER-GRP

REGION — A code identifying the retailer region with which this BASE24-pos terminal is associated. This field is used for reporting purposes. The region entered in this field must match the region in the POS Retailer Definition File (PRDF).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDD1.TERM-OWNER.RETAILER-REGN
PTDF.REC.TERM-OWNER.RETAILER-REGN

SITE ID — A value used to group terminals at a specific site. The SITE ID identifies the site. The SITE ID and RECORD TYPE fields form an alternate key to the PTD. This field cannot be blank if the RECORD TYPE field contains a non-blank value. This field is used only by the BASE24-pos Standard POS Device Handler module.

This field is used only with the SPDH Enhanced Multithreading optional functionality. If the SPDH Enhanced Multi-threading functionality is not used, this field should remain blank.

Field Length: 16 alphanumeric characters
Required Field: Yes, if the RECORD TYPE field contains a non-blank value
Default Value: Blanks
Data Name: PTDD1.MULT-THREAD-SPDH.SITE-ID

RECORD TYPE — A value used to identify the PTD record type. The SITE ID and RECORD TYPE fields form an alternate key to the PTD. This field cannot be blank if the SITE ID field contains a non-blank value. This field is used only by the BASE24-pos Standard POS Device Handler module.

A primary record defines a site. A secondary record defines a terminal at the site. Only one primary PTD record can exist for a site. It does not define an actual terminal. The primary PTD record is used for the following purposes:

- To update inheritable fields in all of the site's secondary PTD records. Inheritable fields are the fields the user can modify that are stored in the PTD static (PTDS1) file, with the exception of the TERMINAL ID and TERMINAL TYPE fields. By using the **SF5** function key, the contents of the inheritable fields are copied from the primary record to every secondary record with the same value in the SITE ID field.
- To accumulate the site's aggregate transaction totals.

The secondary PTD record defines a physical terminal at a site. A site may have multiple secondary records.

This field is used only with the SPDH Enhanced Multi-threading optional functionality. If the SPDH Enhanced Multithreading functionality is not used, this field should remain blank.

P = Primary record
S = Secondary record

Field Length: 1 alphanumeric character
Required Field: Yes, if the SITE ID field contains a non-blank value
Default Value: *b*, where *b* denotes a blank space
Data Name: PTDD1.MULT-THREAD-SPDH.REC-TYP

LOCATION — The address or location of the BASE24-pos terminal. This information is printed on the customer receipt in accordance with Regulation E, which requires that this data be included with each transaction in the United States.

Field Length: 1–25 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.TERM-NAM-LOC
PTDF.REC.TERM-NAM-LOC

CITY — The name of the city in which the BASE24-pos terminal is located.

Regulation E requires that this data be included with each transaction in the United States.

Field Length: 1–18 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Names: PTDS1.PTDS1-CORE.TERM-CITY-ST.CITY
PTDS1.PTDS1-CORE.CITY-EXT
PTDF.REC.TERM-CITY-ST.CITY
PTDF.REC.CITY-EXT

STATE — The state, province, region, or political subdivision in which the BASE24-pos terminal is located.

In the United States, this field must contain a two-character state code. Regulation E requires that this data be included with each transaction. In other countries, an understandable code can be used for informational purposes only.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.TERM-CITY-ST.ST
PTDF.REC.TERM-CITY-ST.ST

COUNTRY — The country code associated with the country in which the BASE24-pos terminal is located. This field will not accept blank spaces.

Field Length: 1–2 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.CNTRY-CDE
PTDF.REC.CNTRY-CDE

POSTAL CODE — The postal code corresponding to the location of the BASE24-pos terminal specified in the LOCATION field. In the United States, postal code is synonymous with ZIP code.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.POSTAL-CDE
PTDF.REC.POSTAL-CDE

TERMINAL TYPE — A code identifying the type of BASE24-pos terminal. When a code is entered in the TERMINAL TYPE field, the terminal type description is automatically displayed following the code. Standard BASE24-pos codes are as follows:

41 = ACI Standard POS Device Handler
43 = NCR 2123 and NCR 2126
44 = NCR 2127
45 = NCR 7000
70 = Visa I, APACS 70 (Auth Only)
71 = Visa II Dialup, APACS 70
78 = Merchant Host Interface
D0 = Hypercom TDS
D1 = Custom POS device 1
D2 = Custom POS device 2
D3 = Custom POS device 3
D4 = Custom POS device 4
D5 = Custom POS device 5
D6 = BASE24 SPDH (fuel)
D7 = BASE24 SPDH (electronic cash register)
D8 = BASE24 SPDH (script dispenser)

Field Length: 2 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.TERM-TYP
PTDS1.PTDS1-CORE.TERM-TYP
PTDF.REC.TERM-TYP

PROTOCOL — A code identifying the line protocol used for communications with this terminal. A text description is automatically displayed following the code. Valid values are as follows:

A = Asynchronous
B = Bisynchronous (EBCDIC)
D = Dialup
P = TCP/IP
S = SDLC (SNA) (Synchronous Data Link Control)
T = Bisynchronous (Transparent EBCDIC)
X = X.25
Y = X.21

Field Length: 1 alphabetic character
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.TERM-PROTO
PTDF.REC.TERM-PROTO

TERMINAL PHONE — The terminal phone number.

Field Length: 1–20 alphanumeric characters
Required Field: Yes, if using the X.21 protocol.
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.TERM-PHONE.NUM
PTDF.REC.TERM-PHONE.NUM

BAUD RATE — The terminal baud rate. This value must match the baud rate configured for the line used by the terminal in the XPNET system. A text description is automatically displayed following the code. Valid values and their corresponding baud rates are as follows:

00 = 50
01 = 75
02 = 110
03 = 134.5
04 = 150
05 = 300
06 = 600
07 = 1200
08 = 1800
09 = 2000
10 = 2400
11 = 3600
12 = 4800
13 = 7200
14 = 9600
15 = 19200
16 = 200
17 = Autobaud
99 = Baud rate not used

Note: If the X.21 protocol is not being used, this field must contain a value of 99.

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 99
Data Name: PTDS1.PTDS1-CORE.TERM-PHONE.BAUD-RATE
PTDF.REC.TERM-PHONE.BAUD-RATE

TERMINAL OWNER — The name of the retailer that owns the POS terminal. This name is printed on customer receipts and is included as the card acceptor name in transactions sent to an interchange.

Field Length: 1–22 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.TERM-OWNER-NAM
PTDF.REC.TERM-OWNER-NAM

TERM GROUP — Identifies the terminal group to which this terminal belongs for downloads.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.TERM-GRP
PTDF.REC.TERM-GRP

TIME OFFSET — The time difference, in minutes, between this terminal and the HP NonStop processor location. The value entered is added or subtracted from the HP NonStop time in order to obtain the terminal local time used when logging transactions and when creating settlement records. This offset is also used to determine if a balancing transaction occurs within the balancing window. For example, if the HP NonStop processor is located in Denver, Colo., and the terminal is located in Los Angeles, Calif., the value entered in this field is -060.

A sign (- or +) indicates whether the value is added or subtracted. The + sign is the default and is not displayed on the screen. Valid values range from -1400 through 1400.

Field Length: 1–4 numeric characters plus the sign
Required Field: Yes
Default Value: 0
Data Name: PTDD1.PTDD1-CORE.TIM-OFST
PTDF.REC.TIM-OFST

RELEASE # — The release number of the BASE24-pos message format used by the terminal. Valid values are 30, 34, 50, and 60.

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 00
Data Name: PTDS1.PTDS1-CORE.REL-NUM
PTDF.REC.REL-NUM

TERM SIC CODE — The Standard Industrial Classification (SIC) code for transactions other than mail or telephone order transactions.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.TERM-SIC-CDE
PTDF.REC.TERM-SIC-CDE

MAIL/PHONE SIC CODE — The Standard Industrial Classification (SIC) code for transactions originating by mail or telephone order.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.MAIL-PO-SIC-CDE
PTDF.REC.MAIL-PO-SIC-CDE

RETAILER ID — The retailer ID of the retailer associated with this POS terminal. The value in this field must match the value in a RETAILER ID field in the POS Retailer Definition File (PRDF).

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDD1.TERM-OWNER.RETAILER-ID
PTDF.REC.TERM-OWNER.RETAILER-ID

RTTN — The Route Transit Number (RTTN), transit/routing number, or issuer identification number for the institution that owns the terminal.

The data is right-justified and zero filled to the left. This field defaults to zeros, but it must be changed.

Field Length: 11 numeric characters
Required Field: Yes
Default Value: 00000000000
Data Name: PTDD1.PTDD1-CORE.RTTN
PTDF.REC.RTTN

TERM STATUS — A code indicating the current status of the terminal. Network control operators can deactivate or activate this terminal from a network control facility. A text description is automatically displayed following the code. Valid codes are as follows:

A = Activated
D = Deactivated
P = Pending Deactivate

Field Length: 1 alphabetic character
Default Value: D
Data Name: PTDD1.PTDD1-CORE.DEACTIVATE-FLG
PTDF.REC.DEACTIVATE-FLG

BILLING INFO — A user-defined field containing billing information added to each balancing and cutover transaction. Typically, this field contains automated clearing house (ACH) information that the BASE24-pos product passes on to the host for use by the ACH system. Information in this field does not impact BASE24-pos processing.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.BILLING-INFO
PTDF.REC.BILLING-INFO

CLERK ID — The identification number of the operator who is logged on to this terminal.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.CLERK-ID
PTDF.REC.CLERK-ID

LANGUAGE ID — A code identifying to the Device Handler module the language in which text is to be displayed at this BASE24-pos terminal.

The predefined codes are 0, 1, and 2. The language associated with each code is user-defined.

Field Length: 1 numeric character
Required Field: No
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.LANGUAGE-IND
PTDF.REC.LANGUAGE-IND

DH PROCESS NAME — The symbolic name of the Device Handler/Router/Authorization process for this terminal. This field must be identical to the symbolic name configured for the Device Handler/Router/Authorization process associated with this terminal in the XPNET system.

Example: P1A^SPDH1
Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDD1.DH-PRO-NAM
PTDF.REC.DH-PRO-NAM

DFLT CHECK ID — The default check identification type. The value in this field is used when a check guarantee or check verification request does not contain a check identification type. A text description is automatically displayed following the code. Valid values are as follows:

01 = Credit card
02 = Drivers license
03 = Account number
04 = Debit card
05 = Cash card
06 = State identification
07 = Social security number
08 = Student identification
09 = Employee identification
10 = Passport number
11 = MICR data

Field Length: 2 numeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.DFLT-CHK-ID
PTDF.REC.DFLT-CHK-ID

ROUTING GROUP — The terminal routing group. This field is used for SPROUTE routing of transactions initiated by cardholders that are outside the logical network.

Field Length: 11 alphanumeric characters
Required Field: No
Default: No default value
Data Name: PTDS1.PTDS1-CORE.RTE-GRP
PTDF.REC.RTE-GRP

DUAL SITE INDICATOR — Indicates whether the terminal is operating as a local or remote terminal when part of a dual site support system. Valid values are as follows:

␣ = Blank. In dual site mode this value is interpreted as Local.
L = Local.
R = Remote.

Field Length: 2 alpha characters
Required Field: No
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.DUAL-SITE-IND

Screen 2

PTD screen 2 contains the terminal load file name, service representative information, currency information, and parameters used during transaction processing and logging. PTD screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-POS    POS TERMINAL DATA    LLLL    YY/MM/DD HH:MM    02 OF 19

TERMINAL ID:                                     FIID:

        LOAD FILE NAME:

                SERVICE REPRESENTATIVE
                NAME:
                ADDRESS:
                CITY/STATE:                CNTRY:        PHONE:

                LOGGING AND TRANSACTION INFORMATION
                LOG ROUTE CODE:        2
CUSTOMER BALANCE DISPLAY: 0 (DO NOT PRINT)
                BALANCE RETURNED:    N
                CURRENCY CODE:    840        MC TALLING TYPE: 0
                RECONCILE MODE:    (***** )
                APPROVAL CODE LENGTH: 6        COMPLETE TRACK DATA: Y
                SOFTWARE RELEASE:

***** BASE24 *****
NEW PAGE:        FILE DESTINATION:        NEW LOGICAL NETWORK ID:
                F12-HELP

```

LOAD FILE NAME — The fully qualified name of the load image file for this terminal. This field has been reserved for future use.

Field Length: 1–35 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Data Name: PTDS1.PTDS1-CORE.LOAD-FIL-NAM
 PTDF.REC.LOAD-FIL-NAM

SERVICE REPRESENTATIVE

The following fields contain information required for contacting the service representative responsible for servicing this POS terminal.

NAME — The name of the service representative or company to contact when problems occur with this terminal. This contact is responsible for servicing the terminal.

Field Length: 1–25 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SRV-REP.NAM
PTDF.REC.SRV-REP.NAM

ADDRESS — The address of the service representative or company responsible for servicing the terminal.

Field Length: 1–25 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SRV-REP.ADDR
PTDF.REC.SRV-REP.ADDR

CITY/STATE — The city and state in which the service representative or company responsible for servicing the terminal is located.

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SRV-REP.CITY-ST
PTDF.REC.SRV-REP.CITY-ST

CNTRY — A code identifying the country in which the service representative or company responsible for servicing the terminal is located.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SRV-REP.CNTRY
PTDF.REC.SRV-REP.CNTRY

PHONE — The telephone number of the service representative or company responsible for servicing the terminal.

Example: 4023907600
Field Length: 1–20 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SRV-REP.PHONE
PTDF.REC.SRV-REP.PHONE

LOGGING AND TRANSACTION INFORMATION

The following fields allow parameters to be set for logging transactions and transaction processing.

LOG ROUTE CODE — A routing code used by the Device Handler module for all network messages logged for this terminal.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: 2
Data Name: PTDS1.PTDS1-CORE.LOG-RT-CDE
PTDF.REC.LOG-RT-CDE

CUSTOMER BALANCE DISPLAY — A code indicating how customer balance information is to be displayed at this terminal for balance inquiry transactions. A text description is automatically displayed following the code. Valid codes are as follows:

- 0 = Do not print or display
- 1 = Display on screen only
- 2 = Print on receipt only
- 3 = Print on receipt and display on screen

Currently, this field is not used.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 3
Data Name: PTDF.REC.CUST-BAL-DSPY

BALANCE RETURNED — A flag indicating whether the available balance is returned to the terminal for all transactions. This field is currently used only by the BASE24-pos Standard POS Device Handler module. Valid values are as follows:

- Y = Yes, return the balance.
- N = No, do not return the balance.

Note: If this flag is set to the value N, balances are returned to the terminal when the RETURN BALANCE field in the CPF is set to the value 1.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: N
Data Name: PTDS1-CORE.BAL-RTRN-FLG

CURRENCY CODE — A numeric ISO code identifying the currency dispensed from this terminal. A text description is automatically displayed following the code. Possible values are listed in the ISO 4217 standard, *Codes for the Representation of Currencies and Funds*. If no value is entered in this field, it defaults to the value of the first entry in the CURRENCY-CODE-TABLE in the COBNAMES file.

Field Length: 3 numeric characters
Required Field: Yes
Default Value: Value of the first entry in the CURRENCY-CODE-TABLE in the COBNAMES file.
Data Name: PTDD1.PTD1-CORE.CRNCY-CDE
PTDF.REC.CRNCY-CDE

MC TALLING TYPE — A code indicating whether terminal totals in a multi-currency environment are stored in the PTDD1 or PTDF as hash totals or in the primary terminal currency. If this field is set to a value of 1, amounts in the POS Standard Internal Message (PSTM) are converted into the primary terminal currency before they are stored in the PTDD1 or PTDF. If this field is set to a value of 0, amounts in the PSTM are not converted before they are stored in the PTDD1 or PTDF. Valid values are as follows:

- 0 = Terminal totals are stored in the PTDD1 or PTDF as hash totals.
- 1 = Terminal totals are stored in the PTDD1 or PTDF in the primary terminal currency.

Field Length: 1 numeric character
Required Field: No
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.MULT-CRNCY-TTL
PTDF.REC.MULT-CRNCY-TTL

RECONCILE MODE — A code indicating how the institution reconciles transactions performed at this terminal. This code describes the transaction profile. This field is informational only and is not used in actual processing. A text description is automatically displayed following the code. Valid values are as follows:

- 0 = Paper reconciliation
- 1 = Electronic reconciliation without adjustments
- 2 = Electronic reconciliation with adjustments

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: PTDF.REC.RECONCILE-MODE

APPROVAL CODE LENGTH — The length of the approval code that this terminal can handle. This value is placed in the POS Standard Internal Message (PSTM) for messages coming into the BASE24-pos system if the approval code length is not contained in the message from the terminal. The Authorization module generates the length of the approval code based on this parameter. Valid values are 2 through 6.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 6
Data Name: PTDS1.PTDS1-CORE.APPRV-CDE-LGTH
PTDF.REC.APPRV-CDE-LGTH

COMPLETE TRACK DATA — A code indicating whether the terminal is capable of capturing and transmitting complete track data on transactions initiated by swiping the card through the reader on the POS terminal. Valid values are as follows:

Y = Yes, the terminal is capable of capturing and transmitting complete track data.
N = No, the terminal is not capable of capturing and transmitting complete track data.

Field Length: 1 alphabetic character
Required Field: No
Default Value: Y
Data Name: PTDS1.PTDS1-CORE.COMPLETE-TRACK2-DATA
PTDF.REC.COMPLETE-TRACK2-DATA

SOFTWARE RELEASE — A free-format text description of the terminal software.

Field Length: 8 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.SFTWR-REL
PTDF.REC.SFTWR-REL

Screen 3

PTD screen 3 defines terminal limits for preauthorizations, adjustments, and returns. Screen 3 also contains terminal totals such as the terminal and batch cutover number and amounts, the shift number, and terminal balance support. PTD screen 3 is shown below, followed by descriptions of its fields.

```

BASE24-POS    TERMINAL DATA          LLLL      YY/MM/DD  HH:MM  03 OF 19

TERMINAL ID:                                     FIID:

                                TERMINAL LIMITS
DEFAULT PRE-AUTH AMOUNT:                0
PRE-AUTH HOLD INCREMENT:                0  PRE-AUTH HOLD TIME:    0
TERM. ADJUSTMENT LIMIT:                 .00  ADJUSTMENT COUNT:    0
RETURN LIMIT:                          .00  RETURN COUNT:      0

                                TERMINAL TOTALS
BATCH NUMBER:                          0  SEQUENCE NUMBER:    0
BATCH CUTOVER COUNT:                  0  NUMBER OF BATCHES:  0
SHIFT NUMBER:                        0  NUMBER OF SHIFTS:   0
TERMINAL CUTOVER: 3 (NETWORK FORCED CUTOVER)
BALANCE SUPPORT: 5 (END OF DAY)

                                LOG TOTALS
BATCH:  N    SHIFT:  N    DAY:  N    NETWORK:  N    SERVICE:  N

***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                F12-HELP

```

TERMINAL LIMITS

The following fields contain the maximum values allowed by the institution for particular functions carried out at the terminal.

DEFAULT PRE-AUTH AMOUNT — The amount to be used for a preauthorization request if the terminal does not supply an amount.

Field Length:	1–9 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	PTDS1.PTDS1-CORE.PRE-AUTH-DFT-AMT PTDF.REC.PRE-AUTH-DFT-AMT

PRE-AUTH HOLD INCREMENT — A value indicating the time increment (minutes, hours, days) associated with the number in the PRE-AUTH HOLD TIME field. Valid values are as follows:

0 = Minutes
1 = Hours
2 = Days

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.PRE-AUTH-HLD
PTDF.REC.PRE-AUTH-HLD

PRE-AUTH HOLD TIME — The default time limit to hold a preauthorization transaction. It is used as a preauthorization hold time if a time limit is not set at the BASE24-pos terminal. Valid values are 0 through 99. The number in this field corresponds to the units of time specified in the PRE-AUTH HOLD INCREMENT field.

Field Length: 1–2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.PRE-AUTH-HLD
PTDF.REC.PRE-AUTH-HLD

TERM. ADJUSTMENT LIMIT — The maximum monetary value of adjustment transactions, in whole and fractional currency units, that can be performed at this terminal within a single batch. When this limit is reached, the Device Handler module generates an event message. The transaction, however, is still processed. The last three positions in this field must contain a decimal point and a cent amount when using U.S. currency.

Field Length: 1–15 numeric characters plus a decimal point
Required Field: No
Default Value: .00 (for a currency with two decimals such as U.S. currency)
Data Name: PTDS1.PTDS1-CORE.ADJ-LMT-AMT
PTDF.REC.ADJ-LMT-AMT

ADJUSTMENT COUNT — The number of adjustments that can be performed at this terminal within a single batch. When the adjustment limit is reached, the Device Handler module generates an event message. The transaction, however, is still processed.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.ADJ-LMT-CNT
PTDF.REC.ADJ-LMT-CNT

RETURN LIMIT — The maximum monetary value of merchandise return transactions, in whole and fractional currency units, that can be performed at this terminal within a single batch. When this limit is reached, the Device Handler module generates an event message. The transaction, however, is still processed. The last three positions of this field must contain a decimal point and a cent amount when using U.S. currency.

Field Length: 1–15 numeric characters plus a decimal point
Required Field: No
Default Value: .00 (for a currency with two decimals such as U.S. currency)
Data Name: PTDS1.PTDS1-CORE.RETURN-LMT-AMT
PTDF.REC.RETURN-LMT-AMT

RETURN COUNT — The number of merchandise return transactions that can be performed at this terminal within a single batch. When this limit is reached, the Device Handler module generates an event message. The transaction, however, is still processed.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.RETURN-LMT-CNT
PTDF.REC.RETURN-LMT-CNT

TERMINAL TOTALS

The following fields contain the activity totals for the terminal.

BATCH NUMBER — The number of the batch represented by the data currently displayed on this screen. This number increases by one each time a batch transaction is performed. When the number in this field is 999, the field is reset to one and begins increasing again. This field is reset to one each time a close shift transaction is performed.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.BATCH-NUM
PTDF.REC.BATCH-NUM

SEQUENCE NUMBER — The sequence number identifying the last transaction performed in the current batch. The number in this field increases by one for each occurrence of a transaction within the current batch. This field is reset to zero when a batch close transaction is performed and begins accumulating within the new batch when the first transaction occurs.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.SEQ-NUM
PTDF.REC.SEQ-NUM

BATCH CUTOVER COUNT — The maximum number of transactions allowed within a batch prior to a batch transaction being performed. Currently, this field is not used.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: 0
Data Name: PTDF.REC.BATCH-CUTOVER-CNT

NUMBER OF BATCHES — The number of batch transactions performed since the last terminal cutover. The value in this field increases by one each time a batch transaction is performed. The batch transaction can be performed either manually by an operator or automatically by the Device Handler module.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.NUM-BATCHES
PTDF.REC.NUM-BATCHES

SHIFT NUMBER — The number of the shift represented by the data currently displayed on the screen. The value in this field increases by one for each shift transaction performed. When an end-of-day transaction occurs, the count in this field is logged to the POS Transaction Log File (PTLF) and then reset to one.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.SHIFT-NUM
 PTDF.REC.SHIFT-NUM

NUMBER OF SHIFTS — The number of shift transactions performed since the last terminal cutover. The value in this field increases by one each time a shift transaction is performed. The shift transaction can be performed either manually by an operator or automatically by the Device Handler module.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.NUM-SHIFTS
 PTDF.REC.NUM-SHIFTS

TERMINAL CUTOVER — A code indicating the type of transaction used to cut over this terminal. If the cutover transaction is performed during the balancing window set in the POS Retailer Definition File (PRDF), on the first occurrence, the Device Handler module cuts the terminal over to a new processing day. If a second cutover transaction is performed on the same day during the balancing window, the terminal is not cut over again. Refer to the ***BASE24-pos Settlement and Reporting Manual*** for more information on the terminal cutover options. A text description is automatically displayed following the code. Valid values are as follows:

- 0 = End-of-day request
- 1 = End-of-shift request
- 2 = End-of-batch request
- 3 = Network forced-cutover by the Settlement Initiator process
- 4 = Network forced-cutover by the Device Handler module

Note: If the SPDH Enhanced Multithreading optional functionality is used, this value should be set to a value of 3 for all primary and secondary PTD records.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 3
Data Name: PTDD1.PTDD1-CORE.TERM-CUTOVER-TC
 PTDF.REC.TERM-CUTOVER-TC

BALANCE SUPPORT — A value indicating the type of totals the terminal supports. The BASE24-pos product clears terminal totals at cutover based on the value entered in this field. This field allows the appropriate retailer's totals to continue accumulating through terminal cutover. A text description is automatically displayed following the code.

When the Device Handler module receives a close transaction within the retailer's cutover window, it checks this field. Totals in the PTDD1 or PTDF are cleared based on the values entered in this field (network totals are always cleared at network cutover). Valid values are as follows:

- 0 = The terminal supports terminal batch totals. If a close-batch transaction is received within the retailer's cutover window, batch, shift, and day totals in the PTDD1 or PTDF are cleared.
- 1 = The terminal supports terminal batch and shift totals. If a close-batch transaction is received within the retailer's cutover window, batch and day totals in the PTDD1 or PTDF are cleared. If a close-shift transaction is received within the retailer's cutover window, shift and day totals in the PTDD1 or PTDF are cleared.
- 2 = The terminal supports terminal batch and day totals. If a close-batch transaction is received within the retailer's cutover window, batch and shift totals in the PTDD1 or PTDF are cleared. If a close-day transaction is received within the retailer's cutover window, shift and day totals in the PTDD1 or PTDF are cleared.
- 3 = The terminal supports terminal batch, shift, and day totals. If a close-batch transaction is received within the retailer's cutover window, batch totals in the PTDD1 or PTDF are cleared. If a close-shift transaction is received within the retailer's cutover window, shift totals in the PTDD1 or PTDF are cleared. Finally, if a close-day transaction is received within the retailer's cutover window, day totals in the PTDD1 or PTDF are cleared.
- 4 = The terminal supports terminal shift and day totals. If a close-shift transaction is received within the retailer's cutover window, shift and batch totals in the PTDD1 or PTDF are cleared. If a close-day transaction is received within the retailer's cutover window, batch and day totals in the PTDD1 or PTDF are cleared.
- 5 = The terminal supports terminal day totals. If a close-day transaction is received within the retailer's cutover window, day totals in the PTDD1 or PTDF are cleared.
- 9 = The terminal does not support any terminal totals. All totals in the PTDD1 or PTDF are cleared when the terminal is forced to cut over.

For more information about clearing PTD totals at cutover, refer to the ***BASE24-pos Settlement and Reporting Manual***.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 5
Data Name: PTDS1.PTDS1-CORE.BAL-SUPPORT
PTDF.REC.BAL-SUPPORT

LOG TOTALS

The following fields indicate which settlement records are logged to the PTLF during a cutover.

BATCH — Indicates whether batch totals are logged to the PTLF during a cutover. Valid values are as follows:

Y = Yes, log batch totals to the PTLF.
N = No, do not log batch totals to the PTLF.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.LOG-TOTALS
PTDF.REC.LOG-TOTALS

SHIFT — Indicates whether shift totals are logged to the PTLF during a cutover. Valid values are as follows:

Y = Yes, log shift totals to the PTLF.
N = No, do not log shift totals to the PTLF.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.LOG-TOTALS
PTDF.REC.LOG-TOTALS

DAY — Indicates whether day totals are logged to the PTLF during a cutover.
Valid values are as follows:

Y = Yes, log day totals to the PTLF.
N = No, do not log day totals to the PTLF.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.LOG-TOTALS
PTDF.REC.LOG-TOTALS

NETWORK — Indicates whether network totals are logged to the PTLF during a cutover. Valid values are as follows:

Y = Yes, log network totals to the PTLF.
N = No, do not log network totals to the PTLF.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.LOG-TOTALS
PTDF.REC.LOG-TOTALS

SERVICE — Indicates whether service totals are logged to the PTLF during a cutover. Valid values are as follows:

Y = Yes, log service totals to the PTLF during a cutover.
N = No, do not log service totals to the PTLF during a cutover.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.LOG-TOTALS
PTDF.REC.LOG-TOTALS

Screen 4

PTD screen 4 contains draft capture and non-draft capture settlement totals for the terminal. Totals are displayed for debits, credits, and adjustments, by batch, shift, current network, and previous network. Other fields contain additional balancing information such as the last settled date, posting date, and the number of cards retained. PTD screen 4 is shown below, followed by descriptions of its fields.

BASE24-POS		TERMINAL DATA		LLLL	YY/MM/DD	HH:MM	04 OF 19	
TERMINAL ID:				FIID:				
TERM SETTLEMENT	DEBIT	CREDIT		ADJUST				
	COUNT	AMOUNT	COUNT	AMOUNT	COUNT	AMOUNT		
BATCH:	0		0	0	0	0	0	0
BATCH-DC:	0		0	0	0	0	0	0
SHIFT:	0		0	0	0	0	0	0
SHIFT-DC:	0		0	0	0	0	0	0
DAILY:	0		0	0	0	0	0	0
DAILY-DC:	0		0	0	0	0	0	0
CUR NT:	0		0	0	0	0	0	0
CUR NT-DC:	0		0	0	0	0	0	0
PRV NT:	0		0	0	0	0	0	0
PRV NT-DC:	0		0	0	0	0	0	0
BALANCE FLAG: (*****)				POST DATE: 000000				
LAST SETTLED DATE: 0		TIME: 0000		CARDS RETAINED: 0				
TRANSACTION CONTROL NUMBERS - BEGINNING: 0				ENDING: 0				
***** BASE24 *****								
NEW PAGE:		FILE DESTINATION:		NEW LOGICAL NETWORK ID:				
F12-HELP								

TERMINAL SETTLEMENT

The following fields contain the number and amounts for debits, credits, and adjustments performed at the terminal during a single usage accumulation period. This information is used for terminal settlement.

BATCH — The total number and amount for all debit, credit, and adjustment transactions performed at the terminal during the current batch.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal.

The first financial transaction within the retailer's cutover window clears batch totals if the TERMINAL CUTOVER field in this record contains a value of 4 (network forced-cutover by the Device Handler module). The Settlement Initiator process clears batch totals at the end of the retailer's balancing window if the value set in the TERMINAL CUTOVER field in this record is 3 (network forced-cutover by the Settlement Initiator process) or if the value set in the TERMINAL CUTOVER field in this record is 4 and no financial transaction occurred within the retailer's cutover window.

A batch close transaction from the terminal is needed to clear batch totals if the value set in the TERMINAL CUTOVER field is 0, 1, or 2 (operator request). If the terminal does not support a batch close transaction, the close transaction specified by the value set in the TERMINAL CUTOVER field will clear batch totals during terminal cutover.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.BATCH.DB-CNT (debit transaction count)
	PTDD1.PTDD1-CORE.BATCH.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.BATCH.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.BATCH.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.BATCH.CR (credit transaction amount)
	PTDD1.PTDD1-CORE.BATCH.ADJ (adjustment transaction amount)
	PTDF.REC.BATCH.DB-CNT (debit transaction count)
	PTDF.REC.BATCH.CR-CNT (credit transaction count)
	PTDF.REC.BATCH.ADJ-CNT (adjustment transaction count)
	PTDF.REC.BATCH.DB (debit transaction amount)
	PTDF.REC.BATCH.CR (credit transaction amount)
	PTDF.REC.BATCH.ADJ (adjustment transaction amount)

BATCH-DC — The total number and amount for draft capture debit, credit, and adjustment transactions performed at the terminal during the current batch.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal and are cleared in the same manner as the BATCH totals above.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.BATCH-DC.DB-CNT (debit transaction count)
	PTDD1.PTDD1-CORE.BATCH-DC.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.BATCH-DC.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.BATCH-DC.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.BATCH-DC.CR (credit transaction amount)
	PTDD1.PTDD1-CORE.BATCH-DC.ADJ (adjustment transaction amount)
	PTDF.REC.BATCH-DC.DB-CNT (debit transaction count)
	PTDF.REC.BATCH-DC.CR-CNT (credit transaction count)
	PTDF.REC.BATCH-DC.ADJ-CNT (adjustment transaction count)
	PTDF.REC.BATCH-DC.DB (debit transaction amount)
	PTDF.REC.BATCH-DC.CR (credit transaction amount)
	PTDF.REC.BATCH-DC.ADJ (adjustment transaction amount)

SHIFT — The total number and amount for all debit, credit, and adjustment transactions performed at the terminal during the current shift.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal.

The first financial transaction within the retailer's cutover window clears shift totals if the TERMINAL CUTOVER field in this record contains a value of 4 (network forced-cutover by the Device Handler module). The Settlement Initiator process clears shift totals at the end of the retailer's balancing window if the value set in the TERMINAL CUTOVER field in this record is 3 (network forced-cutover

by the Settlement Initiator process) or if the value set in the **TERMINAL CUTOVER** field in this record is 4 and no financial transaction occurred within the retailer's cutover window.

A shift close transaction from the terminal is needed to clear shift totals if the value set in the **TERMINAL CUTOVER** field is 0, 1, or 2 (operator request). If the terminal does not support a shift close transaction, the close transaction specified by the value set in the **TERMINAL CUTOVER** field clears shift totals during terminal cutover.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.SHIFT.DB-CNT (debit transaction count)
	PTDD1.PTDD1-CORE.SHIFT.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.SHIFT.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.SHIFT.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.SHIFT.CR credit transaction amount)
	PTDD1.PTDD1-CORE.SHIFT.ADJ (adjustment transaction amount)
	 PTDF.REC.SHIFT.DB-CNT (debit transaction count)
	PTDF.REC.SHIFT.CR-CNT (credit transaction count)
	PTDF.REC.SHIFT.ADJ-CNT (adjustment transaction count)
	 PTDF.REC.SHIFT.DB (debit transaction amount)
	PTDF.REC.SHIFT.CR credit transaction amount)
	PTDF.REC.SHIFT.ADJ (adjustment transaction amount)

SHIFT-DC — The total number and amount for draft capture debit, credit, and adjustment transactions performed at the terminal during the current shift.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal and are cleared in the same manner as the SHIFT totals.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.SHIFT-DC.DB-CNT (debit transaction count) PTDD1.PTDD1-CORE.SHIFT-DC.CR-CNT (credit transaction count) PTDD1.PTDD1-CORE.SHIFT-DC.ADJ-CNT (adjustment transaction count) PTDD1.PTDD1-CORE.SHIFT-DC.DB (debit transaction amount) PTDD1.PTDD1-CORE.SHIFT-DC.CR (credit transaction amount) PTDD1.PTDD1-CORE.SHIFT-DC.ADJ (adjustment transaction amount) PTDF.REC.SHIFT-DC.DB-CNT (debit transaction count) PTDF.REC.SHIFT-DC.CR-CNT (credit transaction count) PTDF.REC.SHIFT-DC.ADJ-CNT (adjustment transaction count) PTDF.REC.SHIFT-DC.DB (debit transaction amount) PTDF.REC.SHIFT-DC.CR (credit transaction amount) PTDF.REC.SHIFT-DC.ADJ (adjustment transaction amount)

DAILY — The total number and amount for all debit, credit, and adjustment transactions performed during the current day.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal.

The first financial transaction within the retailer's cutover window clears daily totals if the **TERMINAL CUTOVER** field in this record contains a value of 4 (network forced-cutover by the Device Handler module). The Settlement Initiator process clears daily totals at the end of the retailer's balancing window if the value set in the **TERMINAL CUTOVER** field in this record is 3 (network forced-cutover by the Settlement Initiator process) or if the value set in the **TERMINAL CUTOVER** field in this record is 4 and no financial transaction occurred within the retailer's cutover window.

A day close transaction from the terminal is needed to clear daily totals if the value set in the TERMINAL CUTOVER field is 0, 1, or 2 (operator request). If the terminal does not support a day close transaction, the close transaction specified by the value set in the TERMINAL CUTOVER field clears day totals during terminal cutover.

Field Length: System protected

Data Names: PTDD1.PTDD1-CORE.DAILY.DB-CNT (debit transaction count)

PTDD1.PTDD1-CORE.DAILY.CR-CNT (credit transaction count)

PTDD1.PTDD1-CORE.DAILY.ADJ-CNT (adjustment transaction count)

PTDD1.PTDD1-CORE.DAILY.DB (debit transaction amount)

PTDD1.PTDD1-CORE.DAILY.CR (credit transaction amount)

PTDD1.PTDD1-CORE.DAILY.ADJ (adjustment transaction amount)

PTDF.REC.DAILY.DB-CNT (debit transaction count)

PTDF.REC.DAILY.CR-CNT (credit transaction count)

PTDF.REC.DAILY.ADJ-CNT (adjustment transaction count)

PTDF.REC.DAILY.DB (debit transaction amount)

PTDF.REC.DAILY.CR (credit transaction amount)

PTDF.REC.DAILY.ADJ (adjustment transaction amount)

DAILY-DC — The total number and amount for draft capture debit, credit, and adjustment transactions performed at the terminal during the current day.

The DEBIT, CREDIT, and ADJUST fields are updated appropriately for each transaction performed at the terminal and are cleared in the same manner as the DAILY totals.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.DAILY-DC.DB-CNT (debit transaction count)
	PTDD1.PTDD1-CORE.DAILY-DC.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.DAILY-DC.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.DAILY-DC.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.DAILY-DC.CR (credit transaction amount)
	PTDD1.PTDD1-CORE.DAILY-DC.ADJ (adjustment transaction amount)
	PTDF.REC.DAILY-DC.DB-CNT (debit transaction count)
	PTDF.REC.DAILY-DC.CR-CNT (credit transaction count)
	PTDF.REC.DAILY-DC.ADJ-CNT (adjustment transaction count)
	PTDF.REC.DAILY-DC.DB (debit transaction amount)
	PTDF.REC.DAILY-DC.CR (credit transaction amount)
	PTDF.REC.DAILY-DC.ADJ (adjustment transaction amount)

CUR NT — The total of all transactions performed at this terminal for all card types since the last terminal cutover.

The values in the COUNT and AMOUNT fields associated with the CUR NT field are moved into the COUNT and AMOUNT fields associated with the PRV NT field when the terminal is cut over. At this point, the CUR NT fields are reset to zero.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.CUR-NET.DB-CNT debit transaction count)
	PTDD1.PTDD1-CORE.CUR-NET.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.CUR-NET.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.CUR-NET.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.CUR-NET.CR (credit transaction amount)
	PTDD1.PTDD1-CORE.CUR-NET.ADJ (adjustment transaction count)
	PTDF.REC.CUR-NET.DB-CNT debit transaction count)
	PTDF.REC.CUR-NET.CR-CNT (credit transaction count)
	PTDF.REC.CUR-NET.ADJ-CNT (adjustment transaction count)
	PTDF.REC.CUR-NET.DB (debit transaction amount)
	PTDF.REC.CUR-NET.CR (credit transaction amount)
	PTDF.REC.CUR-NET.ADJ (adjustment transaction count)

CUR NT-DC — The total of all draft capture transactions performed at this terminal for all card types since the last terminal cutover.

The values in the COUNT and AMOUNT fields associated with the CUR NT-DC field roll into the COUNT and AMOUNT fields associated with the PRV NT-DC field when the terminal is cut over. At this point, the CUR NT-DC fields are reset to zero.

Field Length:	System protected
Data Names:	PTDD1.PTDD1-CORE.CUR-NET-DC.DB-CNT (debit transaction count)
	PTDD1.PTDD1-CORE.CUR-NET-DC.CR-CNT (credit transaction count)
	PTDD1.PTDD1-CORE.CUR-NET-DC.ADJ-CNT (adjustment transaction count)
	PTDD1.PTDD1-CORE.CUR-NET-DC.DB (debit transaction amount)
	PTDD1.PTDD1-CORE.CUR-NET-DC.CR (credit transaction amount)
	PTDD1.PTDD1-CORE.CUR-NET-DC.ADJ (adjustment transaction amount)
	PTDF.REC.CUR-NET-DC.DB-CNT (debit transaction count)
	PTDF.REC.CUR-NET-DC.CR-CNT (credit transaction count)
	PTDF.REC.CUR-NET-DC.ADJ-CNT (adjustment transaction count)
	PTDF.REC.CUR-NET-DC.DB (debit transaction amount)
	PTDF.REC.CUR-NET-DC.CR (credit transaction amount)
	PTDF.REC.CUR-NET-DC.ADJ (adjustment transaction amount)

PRV NT — The total of all transactions performed in the last cutover period.

Field Length: System protected

Data Names: PTDF.REC.PRE-NET.DB-CNT (debit transaction count)
PTDF.REC.PRE-NET.CR-CNT (credit transaction count)
PTDF.REC.PRE-NET.ADJ-CNT (adjustment transaction count)

PTDF.REC.PRE-NET.DB (debit transaction amount)
PTDF.REC.PRE-NET.CR (credit transaction amount)
PTDF.REC.PRE-NET.ADJ (adjustment transaction amount)

PTDF.REC.PRE-NET.DB-CNT (debit transaction count)
PTDF.REC.PRE-NET.CR-CNT (credit transaction count)
PTDF.REC.PRE-NET.ADJ-CNT (adjustment transaction count)

PTDF.REC.PRE-NET.DB (debit transaction amount)
PTDF.REC.PRE-NET.CR (credit transaction amount)
PTDF.REC.PRE-NET.ADJ (adjustment transaction amount)

PRV NT-DC — The total counts and amounts of the draft capture transactions performed in the last cutover period.

Field Length: System protected

Data Names: PTDD1.PTDD1-CORE.PRE-NET-DC.DB-CNT (debit transaction count)
PTDD1.PTDD1-CORE.PRE-NET-DC.CR-CNT (credit transaction count)
PTDD1.PTDD1-CORE.PRE-NET-DC.ADJ-CNT (adjustment transaction count)

PTDD1.PTDD1-CORE.PRE-NET-DC.DB (debit transaction amount)
PTDD1.PTDD1-CORE.PRE-NET-DC.CR (credit transaction amount)
PTDD1.PTDD1-CORE.PRE-NET-DC.ADJ (adjustment transaction amount)

PTDF.REC.PRE-NET-DC.DB-CNT (debit transaction count)
PTDF.REC.PRE-NET-DC.CR-CNT (credit transaction count)
PTDF.REC.PRE-NET-DC.ADJ-CNT (adjustment transaction count)

PTDF.REC.PRE-NET-DC.DB (debit transaction amount)
PTDF.REC.PRE-NET-DC.CR (credit transaction amount)
PTDF.REC.PRE-NET-DC.ADJ (adjustment transaction amount)

BALANCE FLAG — A code indicating whether the Settlement Initiator process forced this terminal to cut over or the terminal was cut over by a POS balancing transaction. A text description is automatically displayed following the code. Valid values are as follows:

- 5 = Balanced. The terminal was balanced by a close transaction from the terminal. The totals sent by the terminal balanced with BASE24 totals or the terminal did not send any totals. Totals were written to the PTLF and cleared.
- 6 = Balanced (with problems). The terminal was balanced by a close transaction from the terminal. The totals sent by the terminal did not balance with BASE24 totals and require verification. Totals were written to the PTLF and cleared.

- 8 = Force balanced (incomplete batch). The terminal was cut over by the Settlement Initiator process at the time specified in the RETAILER CUTOVER/BALANCE END field in the PRDF. The terminal was cut over to a new reporting day, and its totals were written to the PTLF, but only current network totals were reset to zero. This method is used when the TERMINAL CUTOVER field in the PTD contains a value of 0, 1, or 2, and the close transaction has not been received from the terminal within the time window defined in the RETAILER CUTOVER/BALANCE START and RETAILER CUTOVER/BALANCE END fields in the PRDF.
- 9 = Force balanced. The terminal was cut over by either the Settlement Initiator process or the Device Handler module. If the Settlement Initiator process cut over the terminal, the terminal was cut over at the time specified in the RETAILER CUTOVER/BALANCE END fields in the PRDF. This method is used when the value of the TERMINAL CUTOVER field in the PTD is 3. This method is also used when the value in the TERMINAL CUTOVER field in the PTD is 4 and no financial transaction occurs within the retailer's cutover window.

If the Device Handler module cut over the terminal, the terminal was cut over when the Device Handler module received the first financial transaction initiated during the retailer's cutover window. This method is used when the value of the TERMINAL CUTOVER field in the PTD is 4.

With either of these methods, when the terminal was cut over to a new reporting day, its totals were written to the PTLF and all BASE24 totals for the terminal were cleared.

Field Length: System protected
 Data Name: PTDD1.PTDD1-CORE.BAL-FLG
 PTDF.REC.BAL-FLG

POST DATE — The current settlement date (YYMMDD) for this terminal. All transactions originating at this terminal are posted on this date, regardless of the card issuer's current business date.

Upon terminal cutover, or when the time specified in the RETAILER CUTOVER/
BALANCE END field in the PRDF is reached, the date in this field is changed to
the date reflected in the POSTING DATE - NEXT field in the PRDF.

Field Length: 6 numeric characters
Default Value: 000000
Data Name: PTDD1.PTDD1-CORE.POST-DAT
PTDF.REC.POST-DAT

LAST SETTLED DATE — The date (YYMMDD) this terminal was last
balanced.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.LAST-SETL-DAT
PTDF.REC.LAST-SETL-DAT

TIME — The 24-hour time (hhmm) this terminal was last balanced.

Field Length: System protected
Data Name: PTDD1.PTDD1-CORE.LAST-SETL-TIM
PTDF.REC.LAST-SETL-TIM

CARDS RETAINED — The total number of cards that should have been retained
since the last network cutover. Currently, this field is not used.

Field Length: System protected
Data Name: PTDF.REC.CRDS-RET

TRANSACTION CONTROL NUMBERS-BEGINNING/ENDING — These
fields have been reserved for future use.

Field Length: 9 numeric characters
Required Field: No
Default Value: 0
Data Names: PTDF.REC.BEG-TRAN-CNTL-NUM
PTDF.REC.END-TRAN-CNTL-NUM

Screen 5

PTD screen 5 contains totals for the number and amount of debit, credit, adjustment, cash out, and check transactions performed by the operator currently logged on to the terminal indicated in the CLERK ID field on PTD screen 1. PTD screen 5 is shown below, followed by descriptions of its fields.

```

BASE24-POS   TERMINAL DATA           LLLL       YY/MM/DD  HH:MM  05 OF 19

TERMINAL ID:                               FIID:

                                CLERK TOTALS

CLERK TOTALS FLAG:  0  (NO TOTALS)

                                COUNT          AMOUNT
DEBIT:              0                      0
CREDIT:             0                      0
ADJUSTMENT:        0                      0
CASH:               0                      0
CHECK:             0                      0

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                   F12-HELP

```

CLERK TOTALS

The following fields contain the total number and amount of debit, credit, adjustment, cash out, and check transactions the operator logged on to this terminal has processed. These totals are cleared by a batch close transaction or a new operator logon.

CLERK TOTALS FLAG — A value indicating whether operator totals are accumulated for this terminal. A text description is automatically displayed following the code.

If the value in this field is set to 1, 2, or 3, clerk totals are written to the PTLF each time a new operator logs on to the terminal. These totals can then be perused from the PTLF. If the value in this field is 0, no clerk totals are written to the PTLF.

Valid values are as follows:

- 0 = No totals accumulated.
- 1 = Net totals accumulated (debits, credits, and adjustments). Currently, this value is not used.
- 2 = Cash out totals accumulated. Currently, this value is not used.
- 3 = All totals accumulated (debits, credits, adjustments, and cash out).

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.CLERK-FLAG
PTDF.REC.CLERK-FLAG

DEBIT — The total number and amount of all debit transactions occurring under the current operator's logon since the last batch close transaction. DEBIT field totals include the following transactions:

- Normal purchase
- Preauthorization purchase
- Preauthorization completion
- Mail or telephone order
- Cash advance
- Purchase with cash back (allowed only with debit cards)

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.CLERK-TOTS.DB-CNT
PTDD1.PTDD1-CORE.CLERK-TOTS.DB-AMT

PTDF.REC.CLERK-TOTS.DB-CNT
PTDF.REC.CLERK-TOTS.DB-AMT

CREDIT — The total number and amount of all credit transactions occurring under the current operator's logon since the last batch close transaction. CREDIT field totals include merchandise return transactions.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.CLERK-TOTS.CR-CNT
PTDD1.PTDD1-CORE.CLERK-TOTS.CR-AMT

PTDF.REC.CLERK-TOTS.CR-CNT
PTDF.REC.CLERK-TOTS.CR-AMT

ADJUSTMENT — The total number and amount of all adjustment transactions occurring under the current operator's logon since the last batch close transaction. ADJUSTMENT field totals include the following transactions:

- Adjustment to a purchase (with or without cash back)
- Adjustment to a merchandise return
- Adjustment to a cash advance

Each adjustment transaction has two amounts. The first amount (amount-1) is the original transaction amount. The second amount (amount-2) is the new transaction amount. The value in the ADJUSTMENT field is calculated by subtracting amount-1 from the current value in the ADJUSTMENT field and then adding amount-2. For example, if the ADJUSTMENT field contains a value of 0.00, the original transaction amount (amount-1) is \$200.00, and the new transaction amount (amount-2) is \$100.00, the new value in the ADJUSTMENT field will be (-)100.00 (i.e., $0.00 - 200.00 + 100.00$).

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.CLERK-TOTS.ADJ-CNT
PTDD1.PTDD1-CORE.CLERK-TOTS.ADJ-AMT

PTDF.REC.CLERK-TOTS.ADJ-CNT
PTDF.REC.CLERK-TOTS.ADJ-AMT

CASH — The total number and amount of all cash transactions occurring under the current operator's logon since the last batch close transaction. CASH field totals include the following transactions:

- Cash advance
- Purchase with cash back
- Adjustment to a purchase with cash back

Field Length: System protected
 Data Names: PTDD1.PTDD1-CORE.CLERK-TOTS.CASH-CNT
 PTDD1.PTDD1-CORE.CLERK-TOTS.CASH-AMT

 PTDF.REC.CLERK-TOTS.CASH-CNT
 PTDF.REC.CLERK-TOTS.CASH-AMT

CHECK — The total number and amount of all check guarantee and check verification transactions occurring under the current operator's logon since the last batch close transaction.

Field Length: System protected
 Data Names: PTDD1.PTDD1-CORE.CLERK-TOTS.CHK-CNT
 PTDD1.PTDD1-CORE.CLERK-TOTS.CHK-AMT

 PTDF.REC.CLERK-TOTS.CHK-CNT
 PTDF.REC.CLERK-TOTS.CHK-AMT

Screen 6

PTD screen 6 defines the retailer transactions the terminal owner allows at the POS terminal. Screen 6 also contains the default transaction code used by the Device Handler module if the terminal is unable to send a transaction code to the BASE24 system.

The format of this screen varies according to the value displayed in the **TERMINAL TYPE** field on PTD screen 1. For Hypercom and POS Standard Device Handlers, PTD screen 6 displays an acquirer transaction profile that defines the transactions allowed at the terminal. This profile is used as a key to reading the Acquirer Processing Code File (APCF), which defines all of the transactions allowed for the profile. For discussion purposes, this format of the screen is referred to as format 1. For all other BASE24-pos Device Handlers, PTD screen 6 displays a field for each transaction in the BASE24-pos retail set. Each of these fields indicates whether the transaction is allowed at the terminal if it is capable of performing the transaction. For discussion purposes, this format of the screen is referred to as format 2.

Both screen 6 formats and their field descriptions are described on the following pages.

Format 1

The format of PTD screen 6 when the TERMINAL TYPE field on PTD screen 1 is blank or set to a value of 41, 78, D0, or D6–D8 is shown below, followed by descriptions of its fields.

```

BASE24-POS    POS TERMINAL DATA          LLLL          YY/MM/DD  HH:MM  06 OF 19

TERMINAL ID:                                     FIID:

          DEFAULT TRAN CODE: 10  (NORMAL PURCHASE)

          ADJUST AMT2 > AMT1: Y
            SALES DRAFTS: Y
            CLERK TOTALS: Y
            AUTH PARTIAL AMT: Y
            ENHANCED PREAUTH: 0
            PREAUTH CHARGEBACKS: N

          ACQUIRER TXN PROFILE:

          TOKEN RETRIEVAL OPTION: 9

          PASS-THROUGH PARAMETERS
DESTINATION DPC: 0000  RECONCILIATION ENTITY: 0

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP

```

DEFAULT TRAN CODE — The transaction code the Device Handler module attempts to use as a default if the terminal is unable to send a transaction code to the BASE24 system. A text description is automatically displayed following the code. Valid values are as follows:

10 = Normal purchase
 13 = Mail or telephone order
 15 = Cash advance
 16 = Card verification
 17 = Balance inquiry

Field Length: 2 numeric characters
 Required Field: Yes
 Default Value: 10
 Data Name: PTDS1.PTDS1-CORE.DFLT-TC

ADJUST AMT2 > AMT1 — A flag indicating whether this terminal allows an adjustment transaction when the new transaction amount (amount 2) is greater than the original transaction amount (amount 1).

For transactions originating from this terminal, the Device Handler module sets the ADJ-FLG field in the POS Standard Internal Message (PSTM) based on the value in this field. The BASE24-pos Router module checks the value in the ADJ-FLG field to determine whether processing of an adjustment transaction can continue when the new transaction amount (amount 2) is greater than the original transaction amount (amount 1). After this check, the BASE24-pos Authorization module checks the value in the ADJUST AMT2 > AMT1 field on Institution Definition File (IDF) screen 19 to determine whether the institution allows the adjustment transaction. Valid values are as follows:

Y = Yes, allow adjustment.
N = No, do not allow adjustment.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: PTDS1.PTDS1-CORE.ADJ-FLG

SALES DRAFTS — A flag indicating whether sales draft transactions are allowed from this POS terminal. Valid values are as follows:

Y = Yes, sales draft transactions are allowed from this terminal if it is capable of performing the transaction.
N = No, sales draft transactions are not allowed from this terminal or the terminal is incapable of performing the transaction.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: PTDS1.PTDS1-CORE.SALES-DFT-FLG

CLERK TOTALS — A flag indicating whether clerk totals transactions are allowed from this POS terminal. Valid values are as follows:

Y = Yes, clerk totals transactions are allowed from this terminal if it is capable of performing the transaction.
N = No, clerk totals transactions are not allowed from this terminal or the terminal is incapable of performing the transaction.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: PTDS1.PTDS1-CORE.CLERK-TTL-FLG

AUTH PARTIAL AMT — A flag indicating whether this terminal allows partial authorizations for all transaction types, only for transactions not involving cash, or not for any transactions. Valid values are as follows:

0 = Not allowed.
1 = Lesser allowed.
2 = Non-cash only.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: PTDS1.PTDS1-CORE.PRE-AUTH-LESS-AMT-FLG

ENHANCED PREAUTH — A flag indicating whether enhanced preauthorization processing is supported for this terminal. This field is currently used only by the BASE24-pos Standard POS Device Handler module. Valid values are as follows:

0 = Enhanced preauthorization not supported.
1 = Enhanced preauthorization, debit only.
2 = Enhanced preauthorization, credit only.
3 = Enhanced preauthorization, both debit and credit.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: N
Data Name: PTDS1.PTDS1-CORE.ENHNC-PRE-AUTH-FLG

PREAUTH CHARGEBACKS — A flag indicating whether chargeback transactions can be generated for preauthorization completion transactions initiated from this terminal where the hold cannot be found, the hold has expired,

or the completion amount is greater than the hold amount. This field is currently used only by the BASE24-pos Standard POS Device Handler module. Valid values are as follows:

Y = Yes, chargebacks will be generated.

N = No, chargebacks will not be generated.

Field Length: 1 alphanumeric character

Required Field: No

Default Value: N

Data Name: PTDS1.PTDS1-CORE.PRE-AUTH-CHRGBCK-FLG

ACQUIRER TXN PROFILE — A code identifying a group of BASE24-pos cardholder transaction processing codes allowed at this POS terminal. The value of this field is part of the key used to read the Acquirer Processing Code File (APCF) extended memory table. The value in this field overrides the value at the retailer level in the POS Retailer Definition File (PRDF) and the value at the institution level in the Institution Definition File (IDF). The acquirer transaction profile must be defined in the APCF before it can be used here.

Field Length: 16 alphanumeric characters

Required: No

Default Value: *****

Data Name: PTDS1.PTDS1-CORE.ACQ-TXN-PRFL

TOKEN RETRIEVAL OPTION — A code indicating whether BASE24-pos Device Handler modules include tokens in reversal messages, and if so, from where the token data is retrieved. The last message token data is only retrieved from the POS Terminal Data Dynamic File—scratch pad (PTDD2) or the POS Transaction Log File (PTLF) if it is no longer in extended memory or the PSTM is no longer available. If token data is to be retrieved from the PTLF, only tokens configured to be logged to the PTLF using the Token File (TKN) are available for the reversal message. The Device Handler process drops a reversal transaction if the TLF is unavailable for any reason, such as the primary TLF being unavailable during backup processing. The reversal transaction is logged as an exception item and must be reconciled manually. Valid values are as follows:

0 = No tokens are included in reversal messages.

- 1 = Token data is retrieved from the PTDD2 and appended to reversal messages.
- 2 = Token data is retrieved from the PTLF and appended to reversal messages.
- 9 = Use the token retrieval option specified for the terminal owner in the Institution Definition File (IDF).

Field Length: 1 numeric character
 Required Field: No
 Default Value: 2
 Data Name: PTDS1.PTDS1-CORE.TKN-RETRV-OPT

PASS-THROUGH PARAMETERS

The following fields are used for pass-through processing.

DESTINATION DPC — The DPC number of the accepting entity to route transactions to for POS pass-through processing. This field is currently used only by the BASE24-pos Standard POS Device Handler module. Valid values are 0000 through 9999.:

Field Length: 4 alphanumeric characters
 Required Field: No
 Default Value: 0000
 Data Name: PTDS1.PTDS1-CORE.DPC-NUM

RECONCILIATION ENTITY — The type of entity that will be used to reconcile for POS pass-through processing. This field is currently used only by the BASE24-pos Standard POS Device Handler module. Valid values are as follows:

- 0 = No totals
- 1 = Totals by DPC
- 2 = Totals by Retailer ID
- 3 = Totals by Retailer Group
- 4 = Totals by Terminal ID
- 5 = Totals by Clerk ID

Field Length: 1 alphanumeric character

Required Field: No
 Default Value: 0
 Data Name: PTDS1.PTDS1-CORE.RCNCL-ENT

Format 2

The format of PTD screen 6 when the TERMINAL TYPE field on PTD screen 1 is set to a value of 43–45, 70–71, or D1–D5 is shown below, followed by descriptions of its fields.

```

BASE24-POS    POS TERMINAL DATA      LLLL      YY/MM/DD  HH:MM  06 OF 19

TERMINAL ID:                                     FIID:

      DEFAULT TRAN CODE: 10  (NORMAL PURCHASE)

                POS  RETAIL TRANSACTION SET

      NORMAL PURCHASE      Y    PRE-AUTH PURCHASE      Y    PRE-AUTH PUR COMPL      Y
      MAIL/PHONE ORDER      Y    MERCHANDISE RETURN      Y    CASH ADVANCE              Y
      CARD VERIFICATION      Y    BALANCE INQUIRY        Y    PURCHASE CASH BACK      Y
      CHECK VERIFICATION      Y    CHECK GUARANTEE        Y    ADJUST PURCHASE          Y
      ADJUST MERCH RTN      Y    ADJUST CASH ADV          Y    TERM BATCH TOTALS      Y
      TERM SHIFT TOTALS      Y    TERM DAILY TOTALS      Y    RESERVED                  N
      REQ RETAILER MAIL      Y    SEND MAIL PASSTHRU      Y    SEND MAIL STORED        Y
      SALES DRAFTS          Y    CLERK TOTALS          Y    ADJUST CASH BACK        Y
      ADJUST AMT2 > AMT1      Y    AUTH LESSER AMT        Y    RESERVED                  N
      ENTER 'Y' FOR EACH TRANSACTION WHICH IS ALLOWED AT THIS TERMINAL.

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP
  
```

DEFAULT TRAN CODE — The transaction code the Device Handler module attempts to use as a default if the terminal is unable to send a transaction code to the BASE24 system. A text description is automatically displayed following the code. Valid values are as follows:

- 10 = Normal purchase
- 13 = Mail or telephone order
- 15 = Cash advance
- 16 = Card verification
- 17 = Balance inquiry

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 10
Data Name: PTDF.REC.DFLT-TC

POS RETAILER TRANSACTION SET — Codes indicating the retailer transactions allowed or not allowed by the terminal owner at this POS terminal. The transactions specified with a value of Y can be performed only if the POS terminal is capable of performing them. Valid values are as follows:

Y = Yes, this transaction is allowed if the terminal is capable of performing the transaction.
N = No, this transaction is not allowed or the terminal is incapable of performing the transaction.

Field Length: 1 alphabetic character
Occurs: 27 times
Required Field: Yes
Default Value: Y
Data Name: PTDF.REC.ALLOWED-TRANS

Screen 7

PTD screen 7 contains encryption and decryption data for transactions sent to and from the terminal. It also contains transaction security data for this terminal. PTD screen 7 is shown below, followed by descriptions of its fields.

```

BASE24-POS    POS TERMINAL DATA    LLLL    YY/MM/DD  HH:MM  07 OF 19

TERMINAL ID:                                     FIID:

                                ENCRYPTION KEYS

    PIN PAD CHARACTER:

    PIN ENCRYPTION TYPE:  00  (NO ENCRYPTION)
    PIN MASTER KEY:      0000000000000000    CHECK DIGITS:  0000
    VALIDATE PIN:        N
    DERIVATION KEY GROUP:

                                MAC TYPE:  00  (NO MAC'ING)
                                MAC MASTER KEY:  0000000000000000    CHECK DIGITS:  0000

    DATA ENCRYPTION TYPE:  00  (NO ENCRYPTION)

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                   F12-HELP

```

ENCRYPTION KEYS

The following fields relate to the encryption and decryption of transaction data sent to and from this terminal, to the verification of PIN data presented by this terminal, and to the authentication of messages exchanged with this terminal. Several of these fields are used in support of a security module.

PIN PAD CHARACTER — Specifies the pad character used in the formation of the external message PIN block if the PIN/PAD PIN block format is used in PIN encryption. Valid values are A through F and 0 through 9.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: No default value
Data Name: PTDD1.PTDD1-CORE.PIN-PAD-CHAR
PTDF.REC.PIN-PAD-CHAR

PIN ENCRYPTION TYPE — A value indicating the type of PIN encryption used. A text description is automatically displayed following the code. Valid values are as follows:

00 = No encryption
01 = DES algorithm (no security device, PIN/PAD PIN block)
02 = DES algorithm (no security device, ANSI standard PIN/PAN PIN block, 12 right-most digits of PAN excluding the check digit)
03 = DES algorithm (security device, PIN/PAD PIN block)
04 = DES algorithm (security device, ANSI standard PIN/PAN PIN block, 12 rightmost digits of PAN excluding the check digit)
06 = Reversible PIN encryption (used only with the 4B Device Handler module)
07 = Derived unique key per transaction (DUKPT) (used with the SPDH and HPDH modules)

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 00
Data Name: PTDD1.PTDD1-CORE.ENCR-PIN.PIN-ENCRYPT-TYP
PTDF.REC.ENCR-PIN.PIN-ENCRYPT-TYP

PIN MASTER KEY — The master key or Transaction Security Services key locator used for PIN encryption at this terminal.

If PINs are encrypted in software, the PIN master key must be a clear key.

If PINs are encrypted under keys known only to a security module, the content of this field depends on whether the Transaction Security Services process is implemented.

- With the Transaction Security Services process, this field must contain a non-encrypted value known as a key locator. For more information on the Transaction Security Services process and the key locator, refer to the ***BASE24 Transaction Security Services Processing Guide***. By default, a logical network indicator (if configured) followed by the terminal ID, is used as the key locator value.

- Without the Transaction Security Services process, this field must contain the master key of the terminal encrypted by or for the specific security module being used in the system.

For SPDH and HPDH-compliant terminals using the derived unique key per transaction (DUKPT) method, this field must contain an intermediate PIN block encryption key. If the PIN block in an incoming transaction is in DUKPT format, the SPDH and HPDH modules translate the block to be encrypted under the intermediate PIN block encryption key.

Field Length: 1–16 alphanumeric characters for a key locator or 16 hexadecimal characters for a master key
 Required Field: Yes, if the PIN ENCRYPTION TYPE is not 00.
 Default Value: 0000000000000000 or default key locator value
 Data Name: PTDD1.PTDD1-CORE.ENCR-PIN.ENCR-KEYS.M-KEY
 PTDF.REC.ENCR-PIN.ENCR-KEYS.M-KEY

CHECK DIGITS — The check digits used in validating the PIN master key. The value in this field should match the value returned by the security module when encrypting the key.

Field Length: 4 hexadecimal characters
 Required Field: No
 Default Value: 0000
 Data Name: PTDD1.PTDD1-CORE.M-KEY-CHK-VALUE
 PTDF.REC.M-KEY-CHK-VALUE

VALIDATE PIN — A code indicating whether this terminal is capable of receiving PIN data. Valid codes are as follows:

Y = Yes, this terminal has PIN entry capability.
 N = No, this terminal does not have PIN entry capability.

Field Length: 1 alphabetic character
 Required Field: Yes
 Default Value: N
 Data Name: PTDD1.PTDD1-CORE.ENCR-PIN.PIN-VAL-TERM
 PTDF.REC.ENCR-PIN.PIN-VAL-TERM

DERIVATION KEY GROUP — An identifier indicating the Derivation Key File (KEYD) group with which this terminal is associated for retrieval of the derivation key. This is an optional field that allows multiple terminal records to be associated with the same KEYD record. This field is used only for ACI Standard POS Device Handler-compliant terminals and Hypercom using the derived unique key per transaction (DUKPT) method of PIN encryption.

Field Length: 4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTDS1.PTDS1-CORE.KEYD-GRP

MAC TYPE — A value indicating the message authentication code (MAC) generation method used between the terminal and the BASE24 system. A text description is automatically displayed following the code. Valid values are as follows:

00 = No message authentication
01 = Software message authentication
02 = Proprietary software message authentication
03 = Security module message authentication
07 = DUKPT message authentication—PIN translation (SPDH module only)
08 = DUKPT message authentication—no PIN translation (SPDH module only)

Note: Only values 00 and 01 are valid for the Hypercom Device Handler module.

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 00
Data Name: PTDD1.PTDD1-CORE.MAC-DATA.MAC-ENCRYPT-TYP
PTDF.REC.MAC-DATA.MAC-ENCRYPT-TYP

MAC MASTER KEY — The message authentication code (MAC) master key or Transaction Security Services key locator for this terminal.

If messages between the Device Handler process and the terminal are to be authenticated under keys known only to a security module, the content of this field depends on whether the Transaction Security Services process is implemented.

- With the Transaction Security Services process, this field must contain a non-encrypted value known as a key locator. For more information on the Transaction Security Services process and the key locator, refer to the

BASE24 Transaction Security Services Processing Guide. By default, a logical network indicator (if configured) followed by the terminal ID, is used as the key locator value.

- Without the Transaction Security Services process, this field must contain the message authentication code (MAC) master key encrypted by or for the specific security module being used in the system.

Field Length: 1–16 alphanumeric characters for a key locator or 16 hexadecimal characters for a master key
 Required Field: No
 Default Value: 0000000000000000 or default key locator value
 Data Name: PTDD1.PTDD1-CORE.MAC-DATA.ENCR-KEYS.MAS-KEY
 PTDF.REC.MAC-DATA.ENCR-KEYS.MAS-KEY

CHECK DIGITS — The check digits used in validating the MAC master key. The value in this field should match the value returned by the security module when encrypting the key.

Field Length: 4 hexadecimal characters
 Required Field: No
 Default Value: 0000
 Data Name: PTDD1.PTDD1-CORE.MAS-KEY-CHK-VALUE
 PTDF.REC.MAS-KEY-CHK-VALUE

DATA ENCRYPTION TYPE — A code indicating whether data encryption is used for the terminal. Data encryption is only supported with Transaction Security Services (TSS). The TSS Channel Security File (CSECD) contains the actual encryption method used. Valid values are as follows:

00 = No encryption
 01 = Available balance encryption - ASCII
 02 = Available balance encryption - binary
 03 = Full message encryption
 04 = Configurable message encryption
 05 = Full message encryption - DUKPT
 06 = Configurable message encryption - DUKPT

Field Length: 2 alphanumeric characters

Required Field: No
Default Value: 00
Data Name: PTDD1.PTDD1-CORE.DATA-ENCRYPT-TYP

Screens 8, 9, and 10

PTD screens 8, 9, and 10 contain, by card type, the card floor limits for purchases, cash advances, and mail or telephone orders at this terminal. The card floor limits contained on screens 8, 9, and 10 are identical; therefore, only screen 8 is shown below, followed by descriptions of its fields.

```

BASE24-POS    TERMINAL DATA          LLLL      YY/MM/DD  HH:MM  08 OF 19

TERMINAL ID:                                     FIID:

CARD TYPE          EF  TP  CARD FLOOR LIMITS
PURCHASE          CASH ADV  MAIL ORDER  TRAN LIMIT
UK  (UNKNOWN)      0   0           0           0           0           0

```

```

***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                   F12-HELP

```

CARD FLOOR LIMITS

The following fields contain the floor limit amount allowed for each purchase, cash advance, and mail or telephone order transaction for this card type at this terminal.

Use of the following transaction floor limit fields depends upon entries in the ONLINE fields on screen 1 of the Authorization Selection Table File (AST) as described below.

If both the CARD FLOOR LIMIT field on PTD screen 8 and the ONLINE field on AST screen 1 contain values greater than zero, the lesser floor limit for the transaction type is used.

If the CARD FLOOR LIMITS field on PTD screen 8 is zero for the transaction type, the ONLINE field entry for the transaction type on AST screen 1 is used.

If the ONLINE field on AST screen 1 is zero for the transaction type, any amount is considered to be over the floor limit.

CARD TYPE — A code identifying the type of card for which floor limits are established. A text description is automatically displayed following the code. A maximum of 30 entries can be placed in this field.

Codes used in this field are either reserved for BASE24 products or are user-defined. Refer to the ***BASE24 Base Files Maintenance Manual*** for definitions of reserved card types and the qualifications of user-defined card types.

Field Length: 1–2 alphanumeric characters
Occurs: Up to 10 times per screen
Required Field: Yes
Default Value: UK (Unknown)
Data Name: PTDD1.PTDD1-CORE.SRV.TYP
PTDF.REC.SRV.TYP

EF — A value indicating how the BASE24 system should handle electronic follow-up transactions. Valid values are as follows:

- 0 = Post the transaction.
- 1 = The terminal sends an electronic follow-up transaction to the BASE24 system, and the electronic follow-up transaction **is not** posted for this card type.
- 2–9 = Reserved for future use.

Field Length: 1 numeric character
Occurs: Up to 10 times per screen
Required Field: Yes
Default Value: 0
Data Name: PTDD1.PTDD1-CORE.SRV.ELEC-FOLLOWUP
PTDF.REC.SRV.ELEC-FOLLOWUP

TP — A value indicating the transaction profile. Valid values are as follows:

- 0 = Authorize only
- 1 = Authorize and capture
- 2 = Authorize and expect electronic follow-up
- 3 = Terminal determines data capture mode for each transaction

Field Length: 1 numeric character
 Occurs: Up to 10 times per screen
 Required Field: Yes
 Default Value: 0
 Data Name: PTDD1.PTDD1-CORE.SRV.TRAN-PROFILE
 PTDF.REC.SRV.TRAN-PROFILE

PURCHASE — The transaction floor limit, in whole currency units, for a single transaction performed at this terminal by the card type specified on the same line of the table. This limit does not apply to cash advance and mail or telephone order transactions.

Field Length: 1–9 numeric characters
 Occurs: Up to 10 times per screen
 Required Field: Yes
 Default Value: 0
 Data Name: PTDD1.PTDD1-CORE.SRV.NP-FLR-LMT
 PTDF.REC.SRV.NP-FLR-LMT

CASH ADV — The transaction floor limit, in whole currency units, for a single cash advance transaction performed at this terminal by the card type specified on the same line of the table.

Field Length: 1–9 numeric characters
 Occurs: Up to 10 times per screen
 Required Field: Yes
 Default Value: 0
 Data Name: PTDD1.PTDD1-CORE.SRV.CA-FLR-LMT
 PTDF.REC.SRV.CA-FLR-LMT

MAIL ORDER — The transaction floor limit, in whole currency units, for a single mail or telephone order transaction performed at this terminal by the card type specified on the same line of the table.

Field Length: 1–9 numeric characters
Occurs: Up to 10 times per screen
Required Field: Yes
Default Value: 0
Data Name: PTDD1.PTDD1-CORE.SRV.MO-FLR-LMT
PTDF.REC.SRV.MO-FLR-LMT

TRAN LIMIT — The maximum amount, in whole currency units, allowed for a single transaction performed at this terminal. The limit in this field can be overridden by accounts with a VIP status.

Entries in this field depend upon data entered in the CEILING LIMIT field on POS Retailer Definition File (PRDF) screen 2 or 3. If both the TRAN LIMIT field on this screen and the CEILING LIMIT field on PRDF screen 2 or 3 contain values greater than zero, the lesser amount limit for the card type is used.

If the TRAN LIMIT field on this screen contains a value greater than zero and the value in the CEILING LIMIT field on PRDF screen 2 or 3 equals zero for the card type, the TRAN LIMIT field entry for the card type is used.

If the value in the TRAN LIMIT field on this screen is zero for the card type, the value in the CEILING LIMIT field on PRDF screen 2 or 3 is used.

If the value in the TRAN LIMIT field on this screen is zero for the card type and the value in the CEILING LIMIT field on PRDF screen 2 or 3 is zero for the card type, a limit check on the transaction amount is not performed.

Field Length: 1–9 numeric characters
Occurs: Up to 10 times per screen
Required Field: Yes
Default Value: 0
Data Name: PTDD1.PTDD1-CORE.SRV.TRAN-LMT
PTDF.REC.SRV.TRAN-LMT

CARD TYPE — A code identifying the type of card for which the card totals fields are displayed. A text description is automatically displayed following the code. The card types displayed in this field are taken from the CARD TYPE field on screens 8, 9, and 10 of the PTD.

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.TYP
 PTDF.REC.SRV.TYP

DEBITS NUM — The number of times the card type on the same line has been used at this terminal for debit transactions. DEBITS field totals include the following transactions:

- Normal purchase
- Preauthorization purchase
- Preauthorization completion
- Mail or telephone order
- Cash advance
- Purchase cash advance
- Purchase with cash back

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.DB-CNT
 PTDF.REC.SRV.DB-CNT

DEBITS AMOUNT — The total amount of debit transactions involving the card type on the same line that have occurred at the terminal during the current batch.

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.DB
 PTDF.REC.SRV.DB

CREDITS NUM — The number of times the card type on the same line has been used at this terminal for credit transactions. CREDITS field totals include merchandise return transactions.

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.CR-CNT
PTDF.REC.SRV.CR-CNT

CREDITS AMOUNT — The amount of credit transactions involving the card type on the same line that occurred at this terminal during the current batch.

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.CR
PTDF.REC.SRV.CR

ADJUST. NUM — The number of times the card type on the same line has been used at this terminal for adjustment transactions. ADJUST field totals include the following transactions:

- Adjustment to a purchase (with or without cash back)
- Adjustment to a merchandise return
- Adjustment to a cash advance

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.ADJ-CNT
PTDF.REC.SRV.ADJ-CNT

ADJUST. AMOUNT — The amount for adjustment transactions involving the card type on the same line that occurred at this terminal during the current batch.

Each adjustment transaction has two amounts. The first amount is the original amount. The second amount is the new amount. The original amount is added to the adjustment total if the transaction performed is a purchase adjustment or a cash advance adjustment. The original amount is subtracted from the adjustment total if

the transaction performed is a merchandise return adjustment. The new amount is added to the debit total or credit total depending on whether the transaction performed is a purchase adjustment, cash advance, or merchandise return.

Field Length: System protected
Occurs: Up to 5 times per screen
Data Name: PTDD1.PTDD1-CORE.SRV.ADJ
 PTDF.REC.SRV.ADJ

Screen 17

Screen 17 of the POS Terminal Data files (PTD) is specific to the BASE24-pos EMV add-on product and is documented in the ***BASE24-pos EMV Support Manual***.

Screen 18

PTD screen 18 contains information required to broadcast messages or memos to all of the terminals on the system, to specific groups of terminals, or to individual terminals when BASE24-mail is installed. PTD screen 18 is shown below, followed by descriptions of its fields.

```

BASE24-POS    TERMINAL DATA          LLLL          YY/MM/DD  HH:MM  18 OF 19

TERMINAL ID:                                     FIID:

          MAIL PRO NAME:
          SCROLL THRU: 1 (SCROLL THRU CATEGORIES)
TIMEOUT RESPONSE TO TERM: Y (Y/N)
          POS/NEG CONFIRMATION: Y (Y/N)
          UNSOLICITED MESSAGES: N (Y/N)
COMPLETION UNSOLICITED MESSAGES: N (Y/N)
          COMPLETION STORED MESSAGES: N (Y/N)
          RESET MAIL OFFSET FLAG: Y (Y/N)

          TERMINAL IN                      TERMINAL OUT

COMPLETION CODE:
DELIVERY MODE:  (*****)(*****)
CATEGORY NAME:
MESSAGE ID:
MESSAGE DATE:
STATUS FLAG:

***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                  F12-HELP

```

MAIL PRO NAME — The name of the Mail process that sends electronic mail messages to the terminal and receives electronic mail messages from the terminal.

Example: P1A^MAILBOX
 Field Length: 1–16 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-PRO-NAM
 PTDF.REC.MAIL-DATA.MAIL-PRO-NAM

SCROLL THRU — A value indicating whether a category can be scrolled through. A text description is automatically displayed following the code. Valid values are as follows:

- 0 = Scroll within a specified category
- 1 = Scroll through categories, starting at a specified category

Field Length: 1 numeric character
Required Field: Yes
Default Value: 1
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
SCROLL-THRU
PTDF.REC.MAIL-DATA.OPTION-FLAGS.SCROLL-
THRU

TIMEOUT RESPONSE TO TERM — Reserved for future use.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: Y
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
TIMOUT-RESP-TO-TERM
PTDF.REC.MAIL-DATA.OPTION-FLAGS.TIMOUT-
RESP-TO-TERM

POS/NEG CONFIRMATION — Reserved for future use.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: Y
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
POS-NEG-CONFIRMATIONS
PTDF.REC.MAIL-DATA.OPTION-FLAGS.POS-NEG-
CONFIRMATIONS

UNSOLICITED MESSAGES — A value indicating whether the terminal supports unsolicited mail. Valid values are as follows:

- Y = Yes, the terminal can receive unsolicited mail.
- N = No, the terminal cannot receive unsolicited mail.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
UNSOLICITED-MSG
PTDF.REC.MAIL-DATA.OPTION-FLAGS.
UNSOLICITED-MSG

COMPLETION UNSOLICITED MESSAGES — Reserved for future use.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: N
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
TERM-COMPL-UNSOLICITED-MSG
PTDF.REC.MAIL-DATA.OPTION-FLAGS.TERM-
COMPL-UNSOLICITED-MSG

COMPLETION STORED MESSAGES — Reserved for future use.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: N
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
TERM-COMPL-STORED-MSG
PTDF.REC.MAIL-DATA.OPTION-FLAGS.TERM-
COMPL-STORED-MSG

RESET MAIL OFFSET FLAG — A value indicating whether the device is to set the mail-offset flag to zero when the device receives a nonmail transaction. If the flag is reset to zero, subsequent read mail request messages retrieve mail text beginning at the start of the mail packet. If the mail offset flag is not reset, subsequent read mail request messages retrieve mail text from the mail packet at the point indicated by the mail-offset flag. Valid values are as follows:

Y = Yes, reset mail offset to zero.
N = No, do not reset mail offset to zero.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: PTDD1.PTDD1-CORE.MAIL-DATA.OPTION-FLAGS.
OFST-RESET
PTDF.REC.MAIL-DATA.OPTION-FLAGS.OFST-RESET

COMPLETION CODE — Reserved for future use.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
INBOUND.COMPL-CDE
PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
OUTBOUND.COMPL-CDE

PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.COMPL-
CDE
PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.
COMPL-CDE

DELIVERY MODE — Reserved for future use.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
INBOUND.DELIVERY-MDE
PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
OUTBOUND.DELIVERY-MDE

PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.
DELIVERY-MDE
PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.
DELIVERY-MDE

CATEGORY NAME — Reserved for future use.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
INBOUND.CATEGORY-NAM
PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
OUTBOUND.CATEGORY-NAM

PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.
CATEGORY-NAM
PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.
CATEGORY-NAM

MESSAGE ID — Reserved for future use.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
INBOUND.TXT-ID.MSG-ID
PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
OUTBOUND.TXT-ID.MSG-ID

PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.TXT-ID.
MSG-ID
PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.TXT-
ID.MSG-ID

MESSAGE DATE — Reserved for future use.

Field Length: System protected
Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
INBOUND.TXT-ID.MSG-DAT
PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
OUTBOUND.TXT-ID.MSG-DAT

PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.TXT-ID.
MSG-DAT
PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.TXT-
ID.MSG-DAT

STATUS FLAG — Reserved for future use.

Field Length: System protected

Data Names: PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
 INBOUND.STATUS-FLG

 PTDD1.PTDD1-CORE.MAIL-DATA.MAIL-MSG.
 OUTBOUND.STATUS-FLG

 PTDF.REC.MAIL-DATA.MAIL-MSG.INBOUND.
 STATUS-FLG

 PTDF.REC.MAIL-DATA.MAIL-MSG.OUTBOUND.
 STATUS-FLG

Screen 19

PTD screen 19 provides floor limit information and information about point of service indicators. PTD screen 19 is shown below, followed by descriptions of its fields.

```
BASE24-POS   TERMINAL DATA           LLLL      YY/MM/DD  HH:MM  19 OF 19

TERMINAL ID:                                     FIID:

                                FLOOR LIMIT INFORMATION
      PRE-COMM FLOOR LIMIT:
      POST-COMM FLOOR LIMIT:
      PRE-COMM LIMIT FLAG:
      POST-COMM LIMIT FLAG:

                                POINT OF SERVICE INDICATORS
      TERMINAL ATTENDANCE:
      TERMINAL LOCATION:
      CARD CAPTURE:
      CARDHOLDER ACTIVATED TERMINAL:
      CONTACT INPUT CAPABILITIES:
      CONTACTLESS INPUT CAPABILITIES:
      TERMINAL OUTPUT CAPABILITIES:
      CARDHOLDER AUTHENTICATION:

***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                F12-HELP
```

FLOOR LIMIT INFORMATION

The following fields contains floor limit information used only by the APACS 70 POS Device Handler module.

PRE-COMM FLOOR LIMIT — The maximum value of a transaction that can be authorized by the terminal without attempting to communicate with the host. You must specify the limit in whole currency units using the primary terminal currency (i.e., the currency specified in the CURRENCY CODE field on PTD screen 2). The range of valid values is 000–999.

Field Length: 3 numeric characters

Required Field: No
Default Value: 000
Data Name: PTDS1.PTDS1-CORE.PRE-COMM-FLR-LMT
PTDF.PRE-COMM-FLR-LMT

POST-COMM FLOOR LIMIT — The maximum value of a transaction that can be authorized by the terminal when communications attempts with the host have failed. You must specify the limit in whole currency units using the primary Terminal currency (i.e., the currency specified in the CURRENCY CODE field on PTD screen 2). The range of valid values is 000–999.

Field Length: 3 numeric characters
Required Field: No
Default Value: 000
Data Name: PTDS1-CORE.POST-COMM-FLR-LMT
PTDF.POST-COMM-FLR-LMT

PRE-COMM LIMIT FLAG — Indicates whether the PRE-COMM FLOOR LIMIT value should be sent to the terminal by the Device Handler module. This field is followed by a text description of the value entered. Valid values are as follows:

- 0 = Do not use the PRE-COMM FLOOR LIMIT value for this device type. Use the value of the corresponding flag in the Logical Network Configuration File (LCONF).
- 1 = Send the PRE-COMM FLOOR LIMIT value to the device.
- 2 = Do not send the PRE-COMM FLOOR LIMIT value to the device.

Field Length: 1 numeric character, followed by 15 alphabetic characters
Required Field: No
Default Value: 0
Data Name: PTDS1-CORE.PRE-COMM-LMT-FLG
PTDF.PRE-COMM-LMT-FLG

POST-COMM LIMIT FLAG — Indicates whether the POST-COMM FLOOR LIMIT value should be sent to the terminal by the Device Handler module. This field is followed by a text description of the value entered. Valid values are as follows:

- 0 = Do not use the POST-COMM FLOOR LIMIT value for this device type. Use the value of the corresponding flag in the LCONF.
- 1 = Send the POST-COMM FLOOR LIMIT value to the device.
- 2 = Do not send the POST-COMM FLOOR LIMIT value to the device.

Field Length: 1 numeric character, followed by 15 alphabetic characters
Required Field: No
Default Value: 0
Data Name: PTDS1-CORE.POST-COMM-LMT-FLG
PTDF.POS-COMM-LMT-FLG

POINT OF SERVICE INDICATORS

The following fields contain additional information regarding the originating point of service terminal.

TERMINAL ATTENDANCE — A code indicating whether the terminal is attended by the card acceptor. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = Attended terminal
- 1 = Unattended terminal (cardholder-activated terminal, home PC)
- 2 = No terminal used (voice or ARU authorization).

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDS1.TERM-ATTEND-IND

TERMINAL LOCATION — A code indicating the location of the terminal. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = On premises of card acceptor facility
- 1 = Off premises of card acceptor facility (merchant terminal—remote location)
- 2 = On premises of cardholder (home PC)
- 3 = No terminal used (voice or ARU authorization)

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDS1.TERM-LOC-IND

CARD CAPTURE — A code indicating whether the terminal has the ability to capture cards. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = The terminal does not have the ability to capture cards.
- 1 = The terminal has the ability to capture cards.

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDS1.CRD-CAPTR-IND

CARDHOLDER ACTIVATED TERMINAL — A code indicating whether the cardholder activated the terminal with the use of a card, as well as the security level for the cardholder activated terminal. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = Not a cardholder activated terminal transaction
- 1 = Automated dispensing machine with PIN—level 1 security
- 2 = Self-service terminal—level 2 security
- 3 = Limited amount terminal—level 3 security
- 4 = In-flight commerce—level 4 security
- 5 = Script device
- 6 = Electronic commerce
- 7 = Radio frequency device

Note: Contactless/proximity terminals should be set to “2”.

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDS1.CRDHLDR-ACTVT-TERM-IND

CONTACT INPUT CAPABILITIES — A code indicating the contact capabilities for transferring the data on the card into the terminal. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = Unknown or unspecified
- 1 = None (contactless-only or no terminal used, e.g. voice or ARU authorization)
- 2 = Magnetic stripe reader
- 3 = Reserved for future use
- 4 = Reserved for future use
- 5 = Magnetic stripe reader and EMV compatible ICC reader
- 6 = Key entry only
- 7 = Magnetic stripe reader and key entry
- 8 = Magnetic stripe reader, key entry, and EMV compatible ICC reader
- 9 = EMV compatible ICC reader

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDS1.TERM-INPUT-CAP-IND

CONTACTLESS INPUT CAPABILITIES — A code indicating the contactless capabilities for transferring the data on the card into the terminal. This field is followed by a text description of the value entered. If this field is not used, it can be left blank. If this field is used, it must contain one of the following valid values:

- 0 = Unknown or unspecified
- 1 = None (contact-only or no terminal used, e.g. voice or ARU authorization)
- 2 = Contactless magnetic stripe reader
- 3 = Contactless EMV
- 4 = Contactless magnetic stripe and contactless EMV

Field Length: 1 numeric character
Required Field: No
Default Value: No default value
Data Name: PTDD1.CTLS-INPUT-CAP-IND

TERMINAL OUTPUT CAPABILITIES — A code indicating whether the terminal can display messages, print messages, or both. Valid values are as follows:

b = Not used (where *b* denotes a blank space)

0 = Unknown

1 = None

2 = Printing

3 = Display

4 = Printing and display

Field Length: 1 numeric character

Required Field: No

Default Value: No default value

Data Name: PTDS1.TERM-OUTPUT-CAP-IND

CARDHOLDER AUTHENTICATION — A code indicating the methods supported by the terminal for verifying the identity of the cardholder. Valid values are as follows:

ACI Worldwide, Inc.

b = Not used (where *b* denotes a blank space)

0 = No electronic authentication

1 = PIN

2 = Electronic signature analysis

3 = Biometrics

4 = Biographics

5 = Electronic authentication inoperative

6 = Other

7 = Reserved for future use

8 = Reserved for future use

9 = Authentication value

Field Length: 1 numeric character

Required Field: No

Default Value: No default value

Data Name: PTDS1.CRDHLDR-AUTHN-CAP-IND

9: POS Transaction Log File (PTLF)

The PTLF provides an audit trail for activity occurring at POS terminals. All financial transactions occurring for each BASE24 processing day at POS terminals throughout the logical network are logged to the PTLF. Services totals and settlement totals for POS terminals are also logged to the PTLF. This audit trail enables financial institutions to track cardholder, retailer, and terminal activity. It also helps to reconcile the merchant when an out-of-balance situation occurs. Institutions can peruse the file online for transactions initiated by a specific retailer, terminal, or operator.

The BASE24 system maintains PTLF records for the number of days specified by the POS-SETL-PTLF-FILE-RETENTION param in the Logical Network Configuration File (LCONF). The param default is seven. When the param is set to seven, PTLFs from the previous seven days are maintained for perusal and reporting only, as well as two PTLFs for logging transactions. The BASE24 system automatically purges the oldest PTLF once a new PTLF has been created.

The PTLF is written sequentially. Operators can peruse records in the PTLF online by terminal ID only, card number only, retailer ID and clerk ID, and terminal ID and transaction time. Records in the PTLF can be perused by reading the file both forward and backward.

The PTLF perusal function uses three types of screen formats that appear on four screens. The key screen formats (screens 1 and 2) are screens on which key information is entered to access specific records. Summary screen formats (screen 3) display summary information for twelve PTLF records at one time. Detail screen formats (screen 4) display one record at a time with information specific to that record.

This section describes how these screens are accessed. It also shows an example of each screen format and describes the information each screen format provides.

PTLF Key Screens (Screens 1 and 2)

The PTLF key screens are used to display records in the PTLF. There are two key screen formats - PTLF key screen 1 and PTLF key screen 2. PTLF key screen 1 enables an operator to access records using the following keys:

- Card Key - Includes the cardholder number, logical network ID, FIID, and, if available, the member number.
- Terminal ID/Time Key - Includes the terminal ID, logical network ID, FIID, and transaction time.
- Terminal/Retailer Key - Includes the terminal ID, record format, and, if desired, the retailer ID and clerk ID.
- Retailer/Clerk Key - Includes the record format, retailer ID, and, if desired, the clerk ID.

PTLF key screen 2 enables an operator to access records using the following keys:

- Terminal/Retailer Key - Includes the terminal ID, record format, and, if desired, the retailer ID and clerk ID.
- Retailer /Clerk Key - Includes the record format, retailer ID, and, if desired, the clerk ID.

Note: The POS Transaction Log File (PTLF) can also have a Retailer Key; however, this key is not used to peruse the records in this file.

The PTLF key screens are displayed when an operator selects the PTLF item from the POS Product Menu.

The security record of each user can be configured to allow the user access to PTLF screen 1. Once the user has access to PTLF screen 1, the user is able to access the PTLF using any of the perusal types described above.

Key Screen Function Keys

Some function keys for these screens differ from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained in the table below.

The first column shows the BASE24 function keys. The second column provides descriptions of how the function keys work on the PTLF key screens.

Key	Description
F1	Card - Accesses the summary screen for card number perusal. The summary screen is displayed but only the key fields contain data. Before using this function key, you must first complete the fields in the CARD NUMBER PERUSAL portion of the PTLF key screen. This function key is valid only when used from PTLF key screen 1.
F2	Terminal ID/Time - Accesses the summary screen for terminal ID/time perusal. The summary screen is displayed but only the key fields contain data. Before using this function key, you must first complete the fields in the TERMINAL ID/TIME PERUSAL portion of the PTLF key screen. This function key is valid only when used from PTLF key screen 1.
F3	Terminal ID - Accesses the summary screen for terminal ID perusal. The summary screen is displayed but only the key fields contain data. Before using this function key, you must first complete the fields in the TERMINAL ID PERUSAL portion of the PTLF key screen. This function key is valid on both PTLF key screens 1 and 2.
F4	Retailer/Clerk - Accesses the summary screen for retailer/clerk perusal. The summary screen is displayed but only the key fields contain data. Before using this function key, you must first complete the fields in the RETAILER/CLERK PERUSAL portion of the PTLF key screen. This function key is valid on both PTLF key screens 1 and 2.

PTLF Key Screen 1

PTLF key screen 1 can be displayed if the system is configured for PTLF perusal and the operator has access to PTLF key screen 1 in the Security File (SEC). The type of perusal performed (card number, terminal ID/time, terminal ID, or retailer/clerk) depends on the fields the operator enters on the key screen.

To access PTLF key screen 1, place the cursor before PTLF on the POS Product Menu and press the **F1** key. PTLF key screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS      PTLF KEY      LLLL  FIID      YY/MM/DD  HH:MM      01 OF 04
*****
CARD NUMBER      PERUSAL TYPE:  D      DATE (YYMMDD):  999999
PERUSAL          FIID:          LNET:  LLLL
                  CARD:          MEMBER NUM:
*****
TERMINAL ID/TIME PERUSAL TYPE:  D      DATE (YYMMDD):  999999
PERUSAL          FIID:          LNET:  LLLL
                  TERMINAL:      TIME (HHMMSSTT):  00000000
*****
TERMINAL ID      RECORD FORMAT:  5      DATE (YYMMDD):  999999
PERUSAL          TERMINAL:
                  RETAILER:      CLERK:
*****
RETAILER/CLERK   RECORD FORMAT:  5      DATE (YYMMDD):  999999
PERUSAL          RETAILER:      CLERK:
*****
***** BASE24 *****
FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F1-CARD  F2-TERMINAL ID/TIME  F3-TERMINAL ID  F4-RETAILER/CLERK  F12-HELP

```

CARD NUMBER PERUSAL

The following fields are used to select specific transactions for card number perusal. Records are displayed based on the logical network accessed, the FIID of the card-issuing institution, the date of the transactions, and the cardholder number.

PERUSAL TYPE — A code indicating the type of transactions being perused. Valid values are as follows:

D = Detail record perusal (PTLF.REC-TYP = 01, 20, 21, or 22)
T = Totals perusal (PTLF.REC-TYP = 04)

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: Not applicable

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: Not applicable

FIID — The financial institution identifier of the card-issuing institution. The value in this field is used to select the correct PTLF records.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: The last FIID accessed
Data Name: PTLF.HEAD.CRD.FIID

LNET — The logical network. The value in this field is used to select the correct PTLF records.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: Current logical network ID
Data Name: PTLF.HEAD.CRD.LN

CARD — The card number of the card that initiated the transactions selected for perusal. This field can also contain the terminal ID if perusing terminal totals records.

Field Length: 1–19 numeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

MEMBER NUM — The member number associated with the card number entered in the CARD field. If this field is asterisk- or blank-filled, the records displayed are for all transactions for the card number entered in the CARD field, regardless of member number.

Field Length: 1–3 numeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.CRD.CARD.MBR-NUM

TERMINAL ID/TIME PERUSAL

The following fields are used to select specific transactions for terminal ID and time perusal. Records are displayed based on the logical network accessed, the FIID of the terminal-owning institution, the terminal ID, and the time of each transaction.

PERUSAL TYPE — A code indicating the type of transactions being perused. Valid values are as follows:

D = Detail record perusal (PTLF.REC-TYP = 01, 20, 21, or 22)
T = Totals perusal (PTLF.REC-TYP = 04)

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: Not applicable

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: Not applicable

FIID — The financial institution identifier of the terminal-owning institution. The value in this field is used to select the correct PTLF records.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: The last FIID accessed
Data Name: PTLF.HEAD.TERM.FIID

LNET — The logical network to which the terminal belongs. The value in this field is used to select the correct PTLF records.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: Current logical network
Data Name: PTLF.HEAD.TERM.LN

TERMINAL — The terminal ID of the terminal for which PTLF records are being perused.

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.TERM.TERM-ID

TIME — The time (hhmmssstt) at which the first transaction to be perused was initiated. If this field is zero filled, all records for the logical network, FIID, and terminal, for the date in the DATE field, are displayed.

Field Length: 8 numeric characters
Required Field: No
Default Value: 00000000
Data Name: PTLF.HEAD.TERM.TIM

TERMINAL ID PERUSAL

The following fields are used to select specific transactions for terminal ID perusal. Records are displayed based on the type of totals records being perused, the retailer and clerk that issued the transaction requests, the terminal ID, and the date of the transactions.

RECORD FORMAT — A code indicating the format of the totals records being perused. Valid values are as follows:

- 0 = Batch totals records.
- 1 = Shift totals records.
- 2 = Day totals records.
- 3 = Network totals records.
- 4 = Clerk totals records.
- 5 = Detail financial records.
- 8 = Services totals records containing services 18 through 30.
- 9 = Services totals records containing services 1 through 17.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 5
Data Name: PTLF.HEAD.TKEY.REC-FRMT

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: Not applicable

TERMINAL — The terminal ID of the terminal for which PTLF records are being perused.

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.TERM-ID

RETAILER — The retailer ID of the retailer for which PTLF records are being perused.

Field Length: 1–19 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk for which PTLF records are being perused.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

RETAILER/CLERK PERUSAL

The following fields are used to select specific transactions for retailer ID and clerk ID perusal. Records are displayed based on the type of totals being perused, the retailer and clerk that issued the transaction requests, and the date of the transactions.

RECORD FORMAT — A code indicating the format of the totals records being perused. Valid values are as follows:

- 0 = Batch totals records
- 1 = Shift totals records
- 2 = Day totals records
- 3 = Network totals records
- 4 = Clerk totals records

- 5 = Detail financial records
- 8 = Services totals records containing services 18 through 30
- 9 = Services totals records containing services 1 through 17

Field Length: 1 numeric character
Required Field: Yes
Default Value: 5
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: N/A

RETAILER — The retailer ID of the retailer for which PTLF records are being perused.

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk for which PTLF records are being perused.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

PTLF Key Screen 2

PTLF key screen 2 can be displayed if the operator has security access to PTLF screen 2. PTLF key screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-POS      PTLF KEY      LLLL  FIID      YY/MM/DD  HH:MM      02 OF 04
*****
                                TERMINAL ID PERUSAL

RECORD FORMAT:                                DATE (YYMMDD) :
  TERMINAL:
  RETAILER:                                CLERK:

*****

                                RETAILER ID/CLERK ID PERUSAL

RECORD FORMAT:                                DATE (YYMMDD) :
  RETAILER:                                CLERK:

*****
***** BASE24 *****
                                FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F3-TERMINAL ID      F4-RETAILER/CLERK      F12-HELP

```

TERMINAL ID PERUSAL

The following fields are used to select specific transactions for terminal ID perusal. Records are displayed based on the type of totals records being perused, the retailer and clerk that issued the transaction requests, the terminal ID, and the date of the transactions.

RECORD FORMAT — A code indicating the format of the totals records being perused. Valid values are as follows:

- 0 = Batch totals records
- 1 = Shift totals records
- 2 = Day totals records
- 3 = Network totals records
- 4 = Clerk totals records

- 5 = Detail financial records
- 8 = Services totals records containing services 18 through 30
- 9 = Services totals records containing services 1 through 17

Field Length: 1 numeric character
Required Field: Yes
Default Value: 5
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: Not applicable

TERMINAL — The terminal ID of the terminal for which PTLF records are being perused.

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.TERM-ID

RETAILER — The retailer ID of the retailer for which PTLF records are being perused.

Field Length: 1–19 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk for which PTLF records are being perused.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

RETAILER ID/CLERK ID PERUSAL

The following fields are used to select specific transactions for retailer ID and clerk ID perusal. Records are displayed based on the type of totals being perused, the retailer and clerk that issued the transaction requests, and the date of the transactions.

RECORD FORMAT — A code indicating the format of the totals records being perused. Valid values are as follows:

- 0 = Batch totals records
- 1 = Shift totals records
- 2 = Day totals records
- 3 = Network totals records
- 4 = Clerk totals records
- 5 = Detail financial records
- 8 = Services totals records containing services 18 through 30
- 9 = Services totals records containing services 1 through 17

Field Length: 1 numeric character
Required Field: Yes
Default Value: 5
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date (YYMMDD) of the PTLF used in selecting records to be displayed.

Field Length: 6 numeric characters
Required Field: Yes
Default Value: Current date
Data Name: Not applicable

RETAILER — The retailer ID of the retailer for which PTLF records are being perused.

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk for which PTLF records are being perused.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

PTLF Summary Screen Formats (Screen 3)

The PTLF perusal summary screen formats (screen 3) display summary information about the records specified by the key screen formats (screens 1 and 2). When a summary screen format is first displayed, only the key fields contain information. This information is carried over from the PTLF key screen used to access the summary screen.

Twelve summary records are displayed on the summary screen at one time. The summary screen format displayed depends on the key screen format, perusal key, and perusal type or record format requested. There are four summary screen formats. Each summary screen format is described on the following pages along with an explanation of when the format is displayed.

Summary Screen Function Keys

Using function keys, operators can perform the following tasks:

- Display either the first or last twelve records in the PTLF.
- Page forward or backward through the PTLF.
- Display the details of a particular record on the summary screen.

The function keys explained in the table below enable operators to perform these tasks. The first column shows the BASE24 function keys. The second column provides descriptions of how the function keys work on the summary screens.

Key	Description
F1	First Page - Displays the first twelve records in the PTLF.
F2	Last Page - Displays the last twelve records in the PTLF.
F4	Detail - Displays the detail record for the selected record on the summary screen. This function key can be used only after records have been displayed on the screen by pressing either the F1 or F2 key.
F8	Go to Key Screen - Displays the key screen with the information that was previously entered.

Key	Description
F9	Next Page - Reads the <i>next</i> twelve records in the PTLF and displays them on the summary screen. The direction in which the file is being read determines the records read when this key is pressed. Refer to “Paging Forward or Backward” for further explanation.
F11	Previous Page - Reads the <i>previous</i> twelve records in the PTLF and displays them on the summary screen. The direction in which the file is being read determines the records read when this key is pressed. Refer to “Paging Forward or Backward” for further explanation.

Paging Forward or Backward

Four function keys - **F1**, **F2**, **F9**, and **F11** - work together to control which records are read and displayed on the PTLF Summary screens. The **F1** and **F2** keys determine the direction in which the PTLF will be read, which in turn affects which records are read when the **F9** and **F11** keys are pressed.

Using a PTLF containing 60 records as an example, the following table illustrates how these function keys operate.

Paging Forward		Paging Backward	
Function Key Pressed	PTLF Records Displayed	Function Key Pressed	PTLF Records Displayed
F1	1–12	F2	49–60
F9	13–24	F9	37–48
F9	25–36	F9	25–36
F11	13–24	F11	37–48
F9	25–36	F9	25–36

Once a PTLF Summary screen is displayed and the operator has chosen a specific PTLF record to display on one of the PTLF detail screen formats, the operator can read other detail records within the PTLF by perusing forward and backward

through the file. However, the only detail records that can be accessed by perusing forward or backward in the file are those records that were displayed on the PTLF Summary screen.

For example, when records 13 through 24 are displayed on the PTLF Summary screen, an operator can choose to display detail record number 15. When detail record number 15 is displayed, the operator can peruse back to detail record number 13 or forward to detail record number 24. The operator cannot access detail records out of that range. To do so, the operator must return to the PTLF Summary screen and request a new range of records.

Note: Using the summary screens, an operator can page completely through the PTLF from either front to back or back to front. However, if the operator changes direction while paging through the summary records, the operator can access only 50 summary pages in that changed direction. For example, an operator beginning perusal at the front of the file can page through to the end of the file. If the operator, however, uses the **F11** (PREV PAGE) key at summary page 100, the operator can continue to page backward using the **F11** key until reaching summary page 50. The operator cannot access summary pages before page 50.

Screen 3-Format 1

Screen 3-format 1 is displayed from the PTLF key screen format (screen 1) when the perusal key is CARD NUMBER and the perusal type is D (detail records). Screen 3-format 1 is shown below, followed by descriptions of its fields.

```
BASE24-POS    PTLF SUMMARY LIST          LLLL  FIID  YY/MM/DD  HH:MM  03 OF 04

PERUSAL TYPE:      DATE (YYMMDD) :      FIID:      LNET:
CARD:              MEMBER NUM:

      TRAN      CURR  RESP  APPRV  TRAN  TRAN
      CODE      CODE  CODE  CODE   DATE  TIME

      TERMINAL      AMOUNT

***** BASE24 *****
      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP
```

PERUSAL TYPE — A code indicating the type of transactions being perused. Valid value is D (detail record perusal).

Field Length: System protected
Data Name: Not applicable

DATE — The date of the PTLF to which the records belong.

Field Length: System protected
Data Name: Not applicable

FIID — The financial institution identifier associated with the records.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.FIID

LNET — The logical network associated with the records.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.LN

CARD — The card number of the card that initiated the transactions.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

MEMBER NUM — The member number of the card associated with the transactions. If this field contains blanks or asterisks, the records listed are for the card number in the CARD field without regard to a specific member number.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.CARD.MBR-NUM

TERMINAL — The terminal ID of the terminal at which the transaction originated.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.HEAD.RETL.TERM-ID

TRAN CODE — The transaction code associated with this record.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-CDE

AMOUNT — The original amount of the transaction. When the transaction amount is too large to be displayed, this field contains asterisks. A code following the amount indicates certain types of transactions. Some transactions, such as requests, do not have a corresponding code. Valid codes are as follows:

A = Adjustment
C = Chargeback
F = Force post
O = Offline/SAF
R = Reversal
S = Suspect reversal
U = File update/transfer advice
X = Exception

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.AMT-1

CURR CODE — An alphabetic ISO code indicating the currency in which this transaction was logged. Valid values are listed in the ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.CRNCY-CDE

RESP CODE — The response code assigned to the transaction by the transaction authorizer. The first digit in this field is the responder; the last three digits in this field are the actual response code.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.AUTH.RESPONDER
 PTLF.AUTH.RESP-CDE

APPRV CODE — The approval code assigned to the transaction by the transaction authorizer.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.APPRV-CDE

TRAN DATE — The date the transaction was initiated. The date format is either DD/MM or MM/DD as indicated in the DATE-DISPLAY-TYPE param in the LCONF.

Note: The TRAN DATE is not checked by the interface. As a result, an incorrect date in this field will not generate an error.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-DAT

TRAN TIME — The 24-hour time in hh:mm format that the transaction was initiated. The time displayed includes the time offset.

Note: The TRAN TIME is not checked by the interface. As a result, an incorrect date in this field will not generate an error.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-TIM

Screen 3-Format 2

Screen 3-format 2 is displayed when an operator requests summary records by:

- Using the PTLF key screen 1 format, a perusal key of terminal ID and time, and a perusal type of D (detail records).
- Using the PTLF key screen 1 format, a perusal key of terminal ID, and a record format of 5 (detail records).
- Using the PTLF key screen 2 format, a perusal key of terminal ID, and a record format of 5 (detail records).

Screen 3-format 2 is shown below, followed by descriptions of its fields.

```

BASE24-POS      PTLF SUMMARY LIST          LLLL  FIID  YY/MM/DD  HH:MM  03 OF 04

PERUSAL TYPE/REC FRMT:    DATE(YMMDD) :          FIID:          LNET:
      TERMINAL:

      PAN                TRAN          CURR  RESP  APPRV  TRAN  TRAN
                        CODE          CODE  CODE  CODE  DATE  TIME

***** BASE24 *****
                FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

PERUSAL TYPE/REC FRMT — A code indicating the type of transactions being perused. Valid values are as follows:

- D = Detail record (PTLF.REC-TYP = 01, 20, 21, or 22). This code is valid when perusing by terminal ID and time.
- 5 = Detail record. This code is valid when perusing by terminal ID only.

Field Length: System protected

Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date of the PTLF to which the records were logged.

Field Length: System protected

Data Name: Not applicable

FIID — The financial institution identifier associated with these records. When perusing by terminal ID only, this field is blank.

Field Length: System protected

Data Name: PTLF.HEAD.TERM.FIID

LN — The logical network associated with these records. When perusing by terminal ID only, this field is blank.

Field Length: System protected

Data Name: PTLF.HEAD.TERM.LN

TERMINAL — The terminal ID of the terminal for which PTLF records are being displayed.

Field Length: System protected

Data Name: PTLF.HEAD.TERM.TERM-ID
(when perusing by terminal ID and time)
PTLF.HEAD.TKEY.TERM-ID
(when perusing by terminal ID only)

PAN — The cardholder's primary account number (PAN).

Field Length: System protected

Occurs: Up to 12 times

Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

TRAN CODE — The transaction code associated with this record.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-CDE

AMOUNT — The original amount of the transaction. When the transaction amount is too large to be displayed, this field contains asterisks. A code following the amount indicates certain types of transactions. Some transactions, such as requests, do not have a corresponding code. Valid codes are as follows:

A = Adjustment
C = Chargeback
F = Force post
O = Offline/Store-and-forward
R = Reversal
S = Suspect reversal
U = File update/transfer advice
X = Exception

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.AMT-1

CURR CODE — An alphabetic ISO code indicating the currency in which this transaction was logged. Valid values are listed in the ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.CRNCY-CDE

RESP CODE — The response code assigned to the transaction by the transaction authorizer. The first digit in this field is the responder; the last three digits in this field are the actual response code.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.AUTH.RESPONDER
 PTLF.AUTH.RESP-CDE

APPRV CODE — The approval code assigned to the transaction by the transaction authorizer.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.APPRV-CDE

TRAN DATE — The date the transaction entered the BASE24-pos system. Date format is either DD/MM or MM/DD as indicated in the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-DAT

TRAN TIME — The 24-hour time, in hh:mm format, that the transaction entered the BASE24-pos system. The time displayed includes the time offset.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-TIM

Screen 3-Format 3

Screen 3-format 3 is displayed when an operator requests summary records by:

- Using the PTLF key screen 1 format, a perusal key of RETAILER ID/CLERK ID, and a record format of 5 (detail records).
- Using the PTLF key screen 2 format, a perusal key of RETAILER ID/CLERK ID, and a record format of 5 (detail records).

Screen 3-format 3 is shown below, followed by descriptions of its fields.

```
BASE24-POS    PTLF SUMMARY LIST          LLLL  FIID  YY/MM/DD  HH:MM  03 OF 04

RECORD FORMAT:                                DATE (YYMMDD) :
RETAILER:                                       CLERK ID:

          PAN          TRAN          CURR    RESP    APPRV    TRAN    TRAN
          CODE         AMOUNT    CODE    CODE    CODE    DATE    TIME

***** BASE24 *****
          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP
```

RECORD FORMAT — A code indicating the type of transactions being perused. The valid value is 5 (detail record).

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date, in YYMMDD format, of the PTLF to which the records were logged.

Field Length: System protected
Data Name: Not applicable

RETAILER — The retailer ID of the retailer for which PTLF records are being displayed.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK ID — The clerk ID of the clerk for which PTLF records are being displayed.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

PAN — The cardholder's primary account number (PAN).

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

TRAN CODE — The transaction code associated with this record.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-CDE

AMOUNT — The original amount of the transaction. When the transaction amount is too large to be displayed, this field contains asterisks. A code following the amount indicates certain types of transactions. Some transactions, such as requests, do not have a corresponding code. Valid codes are as follows:

A = Adjustment
C = Chargeback
F = Force post
O = Offline/Store-and-forward
R = Reversal
S = Suspect reversal
U = File update or transfer advice
X = Exception

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.AMT-1

CURR CODE — An alphabetic ISO code indicating the currency of the transaction. Valid values are listed in the ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.AUTH.ORIG-CRNCY-CDE

RESP CODE — The response code assigned to the transaction by the transaction authorizer. The first digit in this field is the responder; the last three digits in this field are the actual response code.

Field Length: System protected
Occurs: Up to 12 times
Data Names: PTLF.AUTH.RESPONDER
PTLF.AUTH.RESP-CDE

APPRV CODE — The approval code assigned to the transaction by the transaction authorizer.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.APPRV-CDE

TRAN DATE — The date the transaction entered the BASE24-pos system. The date format is either DD/MM or MM/DD as indicated in the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-DAT

TRAN TIME — The 24-hour time, in hh:mm format, that the transaction entered the BASE24-pos system. The time displayed includes the time offset.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.AUTH.TRAN-TIM

Screen 3-Format 4

Screen 3-format 4 is displayed when an operator requests summary records by:

- Using the PTLF key screen 1 format, a perusal key of CARD NUMBER, and a perusal type of T (totals records).
- Using the PTLF key screen 1 format, a perusal key of TERMINAL ID/TIME, and a perusal type of T (totals records).
- Using the PTLF key screen 1 format, a perusal key of TERMINAL ID, and a record format of 0 (batch totals), 1 (shift totals), 2 (day totals), 3 (network totals), 4 (clerk totals), or 8 or 9 (services totals).
- Using the PTLF key screen 1 format, a perusal key of RETAILER ID/CLERK ID, and a record format of 0 (batch totals), 1 (shift totals), 2 (day totals), 3 (network totals), 4 (clerk totals), or 8 or 9 (services totals).
- Using the PTLF key screen 2 format, a perusal key of TERMINAL ID, and a record format of 0 (batch totals), 1 (shift totals), 2 (day totals), 3 (network totals), 4 (clerk totals), or 8 or 9 (services totals).
- Using the PTLF key screen 2 format, a perusal key of RETAILER ID/CLERK ID, and a record format of 0 (batch totals), 1 (shift totals), 2 (day totals), 3 (network totals), 4 (clerk totals), or 8 or 9 (services totals).

Note: Summary records appear on screen in chronological order only when requested using the first two methods described above. When using the other methods, summary records may or may not appear in chronological order, depending on whether the record was originally logged with the clerk ID. In order for transactions to appear in chronological order, the transactions must be logged with both the retailer and clerk ID.

Screen 3-format 4 is shown below, followed by descriptions of its fields.

```

BASE24-POS    PTLF SUMMARY LIST          LLLL  FIID  YY/MM/DD  HH:MM  03 OF 04

PERUSAL TYPE/REC FRMT:    DATE(YMMDD) :    FIID:    LNET:
TERMINAL:                RETAILER:          CLERK:

                BATCH    SHIFT    SETTLE    TRAN    TRAN
                NUM      NUM      TYPE      DATE    TIME

***** BASE24 *****
                FILE DESTINATION:    NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

PERUSAL TYPE/REC FRMT — A code indicating the type of transactions being perused. When perusing by card number or terminal ID and time, T is the only valid value. When perusing by terminal ID or retailer ID and clerk ID, valid values are as follows:

- 0 = Batch totals
- 1 = Shift totals
- 2 = Day totals
- 3 = Network totals
- 4 = Clerk totals
- 8 = Services totals records containing services 18 through 30
- 9 = Services totals records containing services 1 through 17

Field Length: System protected
 Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date of the PTLF to which the records were logged.

Field Length: System protected
 Data Name: Not applicable

FIID — The financial institution identifier associated with the records. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected
Data Name: Dependent on the key used for perusing the PTLF.

LNET — The logical network associated with the records. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected
Data Name: Dependent on the key used for perusing the PTLF.

TERMINAL — The terminal ID of the terminal for which PTLF records are being perused. When perusing the PTLF by retailer ID and clerk ID, this field is blank.

Field Length: System protected
Data Name: Dependent on the key used for perusing the PTLF.

RETAILER — The retailer ID of the retailer for which PTLF records are being perused. When perusing the PTLF by card number of terminal ID and time, this field is blank.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk for which PTLF records are being perused. When perusing the PTLF by card number or terminal ID and time, this field is blank.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

BATCH NUM — The batch number associated with the terminal ID in the TERMINAL field.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.HEAD.RETL.BATCH-NUM

SHIFT NUM — The shift number associated with the terminal ID in the TERMINAL field.

Field Length: System protected
 Occurs: Up to 12 times
 Data Name: PTLF.HEAD.RETL.SHIFT-NUM

SETTLE TYPE — The type of settlement record. Valid values are as follows:

- 0 = Batch
- 1 = Shift
- 2 = Daily
- 3 = Network
- 4 = Clerk
- 8 = Services totals records containing services 18 through 30
- 9 = Services totals records containing services 1 through 17

Field Length: System protected
 Occurs: Up to 12 times
 Data Name: PTLF.SRVCS-1.SET-REC1.SETL-TYP
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC1.SETL-TYP
 (when SETTLE TYPE is 8)
 PTLF.SET-REC.SET-REC1.SETL-TYP
 (when SETTLE TYPE is 0, 1, 2, 3, or 4)

TRAN DATE — The date the transaction entered the BASE24-pos system. The date will be in either DD/MM or MM/DD format as indicated by the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
 Occurs: Up to 12 times
 Data Name: PTLF.SRVCS-1.SET-REC1.TRAN-DAT
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC1.TRAN-DAT
 (when SETTLE TYPE is 8)
 PTLF.SET-REC.SET-REC1.TRAN-DAT
 (when SETTLE TYPE is 0, 1, 2, 3, or 4)

TRAN TIME — The 24-hour time, in hh:mm format, that the transaction entered the BASE24-pos system.

Field Length: System protected
Occurs: Up to 12 times
Data Name: PTLF.SRVCS-1.SET-REC1.TRAN-TIM
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC1.TRAN-TIM
 (when SETTLE TYPE is 8)
 PTLF.SET-REC.SET-REC1.TRAN-TIM
 (when SETTLE TYPE is 0, 1, 2, 3, or 4)

PTLF Detail Screen Formats (Screen 4)

The PTLF detail screen formats (screen 4) display information for a specific record chosen from one of the PTLF summary screen formats (screen 3). Operators can read other detail records within the PTLF by perusing forward and backward through the file. However, the only detail records that can be accessed by perusing forward or backward in the file are those records that were displayed on the summary screen.

For example, when records 13 through 24 are displayed on the summary screen, an operator can choose to display detail record number 15. When detail record number 15 is displayed, the operator can peruse back through the records as far as detail record number 13 or forward through the records as far as detail record number 24. The operator cannot access detail records out of that range. To do so, the operator must return to the summary screen and request a new range of records.

Five detail screen formats can be displayed, depending on the perusal type and record format entered on the original key screen format. Each detail screen format is shown and explained on the following pages.

Screen 4-Format 1

Screen 4-format 1 displays detailed information for cardholder transaction records or retailer and terminal transaction records, depending on which perusal method is being used. Possible perusal methods include the following: card number; terminal ID and time; terminal ID only; and retailer ID and clerk ID. The table below illustrates which transaction records are displayed according to perusal method and key screen format.

Perusal Method	Perusal Type	Record Format	Record Displayed
Card number	D (detail)	N/A	Cardholder Transaction
Terminal ID and time			
Terminal ID	N/A	5 (detail)	Retailer and Terminal Transaction
Retailer ID and clerk ID			

Screen 4-format 1 contains up to two pages, depending on the type of transaction selected from the summary screen. The first page contains information for each transaction detail record. The screen has a second page only when the PTLF contains check token information or address verification data for the requested detail record. If the PTLF contains check token information or address verification data for the requested detail record, the message, “MORE DETAIL INFORMATION AVAILABLE,” is displayed on page 1. If the PTLF does not contain check token information or address verification data for the requested detail record, page 2 is not displayed and the message, “NO MORE DETAIL INFORMATION AVAILABLE,” is displayed on page 1.

Screen 4-format 1 contains multiple screen overlays for perusing transactions. The fields displayed on the screen will be different depending on the type of transaction selected from the summary screen. The overlays are all considered part of page 4 and are described below and on the following pages.

Transaction Detail Records - Standard Overlay

The standard overlay contains information that is always displayed for each detail record. Information presented on this display screen is present for each transaction type.

Page 1. Page 1 of screen 4-format 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS      PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:      DATE(YMMDD):          FIID:          LNET:
CARD:                      MEMBER NUM:
TERMINAL:                  RETAILER:                CLERK:

      PAN:                      MEMBER NUM:          EXP DATE:
CARD TYPE:                  ISS CODE:                BATCH NUM:
TERM:                      SIC CODE:                SHIFT NUM:
TRAN DATE:                  TIME OFST:              TRAN TIME:
TRAN:                      ERR FLAG:                PIN PRESENT:
DRAFT CAP:                  APPRV CODE:              INVOICE:
ACCT:                      OVERRIDE FLAG:            ORIG INVOICE:
AUTHORIZER:                AUTH IND:                SEQ NUM:
RESP CODE:                  AUTH SEQ NUM:
AMT 1:                      INDUSTRY FRMT:
AMT 2:                      CONV FLAG:              ICHG PROC CDE:
ALT MRCHNT:                TXN SUBTYPE:

<dual site txn>

***** BASE24 *****
FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY  F6-NEXT REC  F7-PREV REC  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

PERUSAL TYPE/REC FRMT — A code indicating the type of transaction being perused. When perusing by card number or terminal ID and time, T is the only valid value. When perusing by terminal ID or by retailer ID and clerk ID, valid values are as follows:

- 0 = Batch totals
- 1 = Shift totals
- 2 = Day totals
- 3 = Network totals
- 4 = Clerk totals
- 8 = Services totals
- 9 = Services totals

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE(YYMMDD) — The date of the PTLF to which this record was logged.

Field Length: System protected

Data Name: Not applicable

FIID — The financial institution identifier associated with this record. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected

Data Name: PTLF.HEAD.TERM.FIID

LN — The logical network associated with this record. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected

Data Name: PTLF.HEAD.TERM.LN

CARD — The card number used to select the PTLF transaction record for perusal.

Field Length: System protected

Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

MEMBER NUM — The member number associated with the card number in the CARD field. Asterisks or blanks in this field indicate that the record accessed is associated with the card number regardless of the member number.

Field Length: System protected

Data Name: PTLF.HEAD.CRD.CARD.MBR-NUM

TERMINAL — The terminal ID of the terminal where this transaction was initiated.

Field Length: System protected

Data Name: PTLF.HEAD.RETL.TERM-ID

RETAILER — The retailer ID of the retailer who initiated this transaction.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

CLERK — The clerk ID of the clerk who processed this transaction.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

PAN — The cardholder's primary account number.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.CARD.CRD-NUM

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

MEMBER NUM — The member number associated with the card number of this record.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.CARD.MBR-NUM

EXP DATE — The expiration date, in YYMM format, of the card used in this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.EXP-DAT

Note: This field will be completely masked if the PAN is configured for masking.

CARD TYPE — The type of card used in this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.CRD-TYP

ISS CODE — The issuer code indicating whether the card was an on-us card or a not-on-us card. Valid values are as follows:

00–29 = On-us
30–99 = Not-on-us

Field Length: System protected
Data Name: PTLF.AUTH.ISS-CDE

BATCH NUM — The number of the batch to which this transaction belongs.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.BATCH-NUM

TERM — The terminal ID of the terminal at which this transaction originated.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.TERM-ID

SIC CODE — The Standard Industrial Classification (SIC) code of this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.RETL-SIC-CDE

SHIFT NUM — The number of the shift during which this transaction occurred.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.SHIFT-NUM

TRAN DATE — The date this transaction entered the BASE24-pos system. The date format is determined by the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
Data Name: PTLF.AUTH.TRAN-DAT

TIME OFST — The time difference, in minutes, between the location of terminal where this transaction originated and the location of the HP NonStop processor. This time must be added to the BASE24-pos system time to obtain the terminal's local time.

Field Length: System protected
Data Name: PTLF.AUTH.TERM-TIM-OFST

TRAN TIME — The 24-hour time, in hh:mm:ss format, that this transaction entered the BASE24-pos system. The time displayed in this field includes the time offset displayed in the TIME OFST field.

Field Length: System protected
Data Name: PTLF.AUTH.TRAN-TIM

TRAN — The transaction code associated with this record.

Field Length: System protected
Data Name: PTLF.AUTH.TRAN-CDE

ERR FLAG — A value indicating whether this transaction was declined. If the transaction was not declined, this field will be blank. The value in this field is used with the response code to further define the reason the transaction was declined.

Field Length: System protected
Data Name: PTLF.PS50-TKN.ERR-FLG

PIN PRESENT — A value indicating if a PIN was used for this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.PIN-IND

DRAFT CAP — A value indicating whether this transaction was a draft capture item. Valid values are as follows:

- 0 = Authorize only
- 1 = Authorize and capture
- 2 = Authorize only and expect an electronic follow-up
- 3 = Electronic follow-up for a previously authorized transaction

Field Length: System protected
Data Name: PTLF.AUTH.DFT-CAPTURE-FLG

APPRV CODE — The approval code assigned to this transaction by the transaction authorizer.

Field Length: System protected
Data Name: PTLF.AUTH.APPRV-CDE

INVOICE — The transaction invoice number if the invoice number was sent up from the terminal.

Field Length: System protected
Data Name: PTLF.AUTH.INVOICE-NUM

ACCT — The account number of the account from which funds were removed for this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.ACCT

OVERRIDE FLAG — A value that indicates whether this transaction was a normal transaction or a referral override from CRT Authorization. Valid values are as follows:

- 0 = Normal transaction
- 1 = Referral override; response sent to the CRT Device Handler module
- 2 = Referral override; transaction sent from the Router/Authorization module
- 3 = Normal transaction from the CRT Authorization terminal

Field Length: System protected
Data Name: PTLF.AUTH.OVRRDE-FLG

ORIG INVOICE — The original transaction invoice number if the transaction invoice number was sent to the BASE24-pos system by the terminal.

Field Length: System protected
Data Name: PTLF.AUTH.ORIG-INVOICE-NUM

AUTHORIZER — The symbolic process name of the process that authorized the transaction.

Field Length: System protected
Data Name: PTLF.AUTH.AUTHORIZER

AUTH IND — A value indicating whether the authorizer was the primary, first alternate, second alternate, or default authorizer. Valid values are as follows:

P = Primary authorizer
1 = First alternate authorizer
2 = Second alternate authorizer
F = Primary authorizer determined by SPROUTE routing procedures
f = First alternate authorizer determined by SPROUTE routing procedures
4 = Default authorizer; blind authorization
9 = Default authorizer
0 = No authorizer

Field Length: System protected
Data Name: PTLF.AUTH.AUTH-IND

SEQ NUM — The sequence number the BASE24-pos system assigned to this transaction.

Field Length: System protected
Data Name: PTLF.AUTH.SEQ-NUM

RESP CODE — The response code assigned to this transaction by the transaction authorizer. The first digit in this field is the responder; the last three digits in this field are the actual response code. The response code is followed by a text description of the response code.

Field Length: System protected
Data Names: PTLF.AUTH.RESPONDER
 PTLF.AUTH.RESP-CDE

AUTH SEQ NUM — The transaction sequence number of the preauthorization transaction. If this transaction was not a preauthorization transaction, this field is zero-filled.

Field Length: System protected
Data Name: PTLF.AUTH.PRE-AUTH-SEQ-NUM

AMT 1 — The amount of this transaction. When the transaction amount is too large to be displayed, this field contains asterisks. A code indicating the type of transaction follows this amount. Valid codes are as follows:

A = Adjustment
C = Chargeback
F = Force post
O = Offline/Store-and-forward
R = Reversal
S = Suspect reversal
U = File update or file transfer advice
X = Exception

In the case of exception transactions, two of the codes listed above could follow the transaction amount. For example, if a \$20.00 transaction is an exception reversal, this field would contain the value “20.00 R X”. When two codes are listed following the transaction amount, one of the codes must be X (exception).

If the transaction was a balance inquiry, the balance is not displayed in this field.

Field Length: System protected
Data Name: PTLF.AUTH.AMT-1

INDUSTRY FRMT — The American Express industry format. This field is used only if the American Express token was present in the internal message. If the American Express token was not present, this field is blank-filled. Valid values are as follows:

AUTO = Auto rental
LODG = Lodging
OIL = Oil
REST = Restaurant
RETL = General retail

Field Length: System protected
Data Name: PTLF.AMEX-TKN.FRMT-CDE

AMT 2 — The adjustment amount or the cash back amount of this transaction. If this transaction was not an adjustment or did not require cash back, this field is blank-filled. An identifier following the amount indicates the country from which the currency originated.

Field Length: System protected
Data Name: PTLF.AUTH.AMT-2

ALT MRCHNT — The alternate merchant number. This field contains a value only if the Alternate Merchant ID token was present in the internal message. If the Alternate Merchant ID token was not present in the internal message, this field is blank-filled

Field Length: System protected
Data Name: PTLF.ALT-MERCH-ID-TKN.ALT-MERCH-ID

CONV FLAG — The conversion flag identifies if the transaction is converted to an electronic transaction from a paper check transaction at the point of sale. This flag can be updated by Device Handler modules and Interchange Interface processes. This field contains a value only if the Check Guarantee/Verification 2 Token was present in the internal message. If the Check Guarantee/Verification 2 Token was not present in the internal message, this field is blank-filled. Valid codes are as follows:

- 0 = No conversion
- 1 = Conversion with Check Verification or Check Guarantee
- 2 = Conversion only

Field Length: System protected
Data Name: PTLF.CHK-AUTH2-TKN.CONV-FLG

ICHG PROC CDE — This field contains the acquiring interchange interface's external message processing code. If the acquiring interchange interface's external message processing code is equal to zeros or blanks, the issuer processing code is

used. This field contains a value only if the Transaction Subtype Token was present in the internal message. If the Transaction Subtype Token was not present in the internal message, this field is blank-filled.

Field Length: System protected
Data Name: PTLF.TXN-SUBTYP-TKN.ISS-PROC-CDE
PTLF.TXN-SUBTYP-TKN.ACQ-PROC-CDE

TXN SUBTYPE — A subtype identifier to further describe this transaction. All alphanumeric characters are valid in this field.

Field Length: System protected
Data Name: PTLF.TXN-SUBTYP-TKN.TXN-SUBTYP

<dual site txn> — Indicates whether the transaction originated on or was authorized by a different logical network. This value is taken from the MULT-LN-TKN and is present only in a system that has dual site support. The presence of the token and the value p in this field indicates a remote transaction.

Field Length: System protected
Data Name: MULT-LN-TKN.SITE-IND

Page 2. Page 2 of screen 4-format 1 contains check token information, address verification data, electronic benefit transfer data, and mobile-top-up information that is displayed only if the information is present in the PTLF for that detail record. The message, “MORE DETAIL INFORMATION AVAILABLE”, is displayed on the bottom of page 1 when page 2 contains information. If page 2

does not contain any information, the message, “NO MORE DETAIL INFORMATION AVAILABLE”, is displayed. Page 2 of screen 4-format 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS    PTLF DETAIL                LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:    DATE(YMMDD) :          FIID:          LNET:
CARD:                     MEMBER NUM:
TERMINAL:                 RETAILER:                CLERK:

    ADDR:                 ZIP:                 ADDR STAT:
    CHK ID:
    CHK TYP:              STATE:              BIRTH/ID DATE:
    VOUCHER:
    TRAN SURCHARGE:
    ORIG SURCHARGE:

MOBILE PHONE NUM:         TAX AMOUNT:
TOP-UP REF NUM:           RESP CODE:
MNO CODE:

***** BASE24 *****
FILE DESTINATION:        NEW LOGICAL NETWORK ID:

```

ADDR — The cardholder billing address received with the transaction if address verification was performed. When the transaction contains an address verification status code without an address or a postal code, this field contains zeros. If address verification was not performed, this field contains blanks.

Field Length: System protected
Data Name: PTLF.AUTH.ADDR

ZIP — The cardholder billing postal code received with the transaction if address verification was performed. When the transaction contains an address verification status code without an address or a postal code, this field contains zeros. If address verification was not performed, this field contains blanks. In the United States, postal code is synonymous with ZIP code.

Field Length: System protected
Data Name: PTLF.AUTH.ZIP-CDE

ADDR STAT — A code identifying the result of comparing address verification information received in the transaction and address verification information contained in the processor's database.

The following values can be set by BASE24-pos through its address verification processing. If a transaction is sent to an interchange for processing, the response message may contain other interchange-specific values (BASE24 does not change values received from the interchanges).

- A = ADDRESS - Addresses matched, but postal codes did not match.
- E = ERROR - The transaction was not eligible for address verification or an editing error occurred while attempting to process the message.
- N = NO - Addresses did not match and postal codes did not match.
- R = RETRY - Primary and secondary authorizers were unavailable or declined the transaction and address verification was not performed on the BASE24-pos system.
- S = SERVICE NOT SUPPORTED - The BASE24-pos system authorized the transaction, but did not have the add-on Address Verification module.
- U = UNAVAILABLE - Address information was not available to the processor performing address verification.
- W = WHOLE ZIP - Nine-digit postal codes matched, but addresses did not match.
- X = EXACT - Addresses and nine-digit postal codes matched.
- Y = YES - Addresses and five-digit postal codes matched.
- Z = ZIP - Five-digit postal codes matched, but addresses did not match.
- b* = Address verification information was not included in this transaction (*b* denotes a blank character).
- 0 = Address verification information was included in this transaction, but was not verified. A transaction to be verified by a host or interchange carries this code. A transaction to be verified on the BASE24-pos system, but declined before address verification could be performed also carries this code.

Field Length: System protected
Data Name: PTLF.AUTH.ADDR-VRFY-STAT

CHK ID — The number from the customer's identification when the transaction is a check guarantee or check verification. The ID number is followed by a text description of the type of identification used in this transaction. If this transaction was not a check guarantee or check verification or if the Check Guarantee/Verification token was not present in the internal message, this field is blank.

Field Length: System protected
Data Name: PTLF.CHK-AUTH-TKN.CHK-ID-NUM

CHK TYP — A description of the type of check involved in this check guarantee or check verification transaction. If this transaction was not a check guarantee or check verification or if the Check Guarantee/Verification token was not present in the internal message, this field is blank.

Field Length: System protected
Data Name: PTLF.AUTH-TRAN-CDE.C

STATE — The state in which the drivers license was issued. This field is used if the transaction was a check guarantee or check verification, if the Check Guarantee/Verification token was present in the internal message, and if the customer identification used was a drivers license.

Field Length: System protected
Data Name: PTLF.CHK-AUTH-TKN.STATE-CDE

BIRTH/ID DATE — The date of birth on the drivers license or the expiration date of the card used in this transaction. This field is used if the transaction was a check guarantee or check verification and the Check Guarantee/Verification token was present in the internal message.

Field Length: System protected
Data Name: PTLF.CHK-AUTH-TKN.BIRTH-ID-DAT

VOUCHER — The voucher number for manually entered electronic benefit transfer (EBT) transactions that were voice authorized. This field is used if the transaction was an electronic benefit transfer transaction and the Voucher Number token was present in the internal message.

Field Length: System protected
Data Name: PTLF.EBT-VOUCHER-NUM-TKN.VOUCHER-NUM

TRAN SURCHARGE — The transaction surcharge amount assessed. This field will be displayed if the surcharge data token (token 25) is present in the internal message and contains a non-zero amount. If the amount in this field is a negative amount, it must be preceded by a minus sign (–). This field is filled in by the Authorization module (acquirer traffic) or Interchange Interface process (issuer traffic). This field is updated on reversals by the Device Handler process (acquirer traffic) or the Interchange Interface process (issuer traffic).

Field Length: System protected
Data Name: SURCHARGE-DATA-TKN.TRAN-FEE

ORIG SURCHARGE — The original transaction surcharge assessed. This field will be displayed if the surcharge data token (token 25) is present in the internal message and contains a non-zero amount. If the amount in this field is a negative amount, it must be preceded by a minus sign (–). This field is filled in by the Authorization module (acquirer traffic) or the Interchange Interface process (issuer traffic).

Field Length: System protected
Data Name: SURCHARGE-DATA-TKN.ORIG-FEE

MOBILE PHONE NUM — The mobile phone number to receive the top-up. This number is provided by the cardholder at the acquiring device. This value is taken from the PRE-PAY TOP-UP TOKEN.

Field Length: System protected
Data Name: PTLF.PRE-PAY-TOP-UP-TKN.PHN-NUM

MNO CODE — The approval code if supplied by the mobile carrier in the response message. For declined transactions, this field may contain the response code returned from the operator. This value is taken from the PRE-PAY TOP-UP TOKEN.

Field Length: System protected
Data Name: PTLF.PRE-PAY-TOP-UP-TKN.APPRV-CDE

TOP-UP REF NUM — The reference number taken from the PRE-PAY TOP-UP TOKEN. This number is unique for each transaction.

Field Length: System protected
Data Name: PTLF.PRE-PAY-TOP-UP-TKN.REF

RESP CODE — The mobile carrier's response code or the BASE24-pos transaction context manager's response code. Alternatively, this field may contain a generic response code agreed upon between the mobile carrier and the service provider. This code is converted by the BASE24 mobile interface process into an internal BASE24 response code that is carried in the STM/PSTM response code field.

This value is mandated by the LINK Interchange Interface process.

Field Length: System protected
Data Name: PTLF.PRE-PAY-TOP-UP-TKN.RESP-CDE

TAX AMOUNT — The tax amount to be applied to the top-up transaction. This value is taken from the PRE-PAY RESPONSE TOKEN.

Field Length: System protected
Data Name: PTLF.PRE-PAY-RESP-TKN.TAX-AMT

Transaction Detail Records - Stored Value Overlay

Page 1 of screen 4-format 1 for the Stored Value overlay contains information that is always displayed for each detail record. The last two lines of the screen will display additional information specific to a stored value transaction. Page 1 of screen 4-format 1 for a stored value transaction is shown below, followed by descriptions of the fields used only with the BASE24-pos Stored Value product.

```

BASE24-POS      PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:      DATE (YYMMDD) :      FIID:      LNET:
CARD:                        MEMBER NUM:
TERMINAL:                    RETAILER:              CLERK:

      PAN:                        MEMBER NUM:      EXP DATE:
CARD TYPE:                    ISS CODE:      BATCH NUM:
TERM:                          SIC CODE:      SHIFT NUM:
TRAN DATE:                    TIME OFST:      TRAN TIME:
TRAN:                          ERR FLAG:      PIN PRESENT:
DRAFT CAP:                    APPRV CODE:      INVOICE:
ACCT:                          OVERRIDE FLAG:  ORIG INVOICE:
AUTHORIZER:                    AUTH IND:      SEQ NUM:
RESP CODE:                    AUTH SEQ NUM:
AMT 1:                          INDUSTRY FRMT:
AMT 2:                          CONV FLAG:      ICHG PROC CDE:
ALT MRCHNT:                    TXN SUBTYPE:
ADDITIONAL CARD NUMBER:

***** BASE24 *****
FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY  F6-NEXT REC  F7-PREV REC  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

ADDITIONAL CARD NUMBER — The card number of a stored value card on which an additional card activation transaction was performed. This field is displayed only when the BASE24-pos Stored Value product is used and an additional card activation transaction is performed.

Field Length: System protected
Data Name: Not applicable

Note: This field can be masked based on a setting in the Security File (SEC). The degree of masking is based on the setting of the AFT-PAN-DIGITS parameter in the Logical Network Configuration File.

Transaction Detail Records - Secure Internet Validation Overlay

Page 1 of screen 4-format 1 of the Secure Internet Validation overlay contains information that is always displayed for each detail record. The last two lines of the screen will display additional information specific to a secure internet validation transaction. Page 1 of screen 4-format 1 for a secure internet validation transaction is shown below, followed by descriptions of the fields used that are present only with a card verification or an online purchase.

```

BASE24-POS      PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:      DATE (YYMMDD):      FIID:      LNET:
CARD:                      MEMBER NUM:
TERMINAL:                  RETAILER:              CLERK:

      PAN:                      MEMBER NUM:      EXP DATE:
CARD TYPE:                  ISS CODE:      BATCH NUM:
TERM:                      SIC CODE:      SHIFT NUM:
TRAN DATE:                  TIME OFST:      TRAN TIME:
TRAN:                      ERR FLAG:      PIN PRESENT:
DRAFT CAP:                  APPRV CODE:      INVOICE:
ACCT:                      OVERRIDE FLAG:      ORIG INVOICE:
AUTHORIZER:                  AUTH IND:      SEQ NUM:
RESP CODE:                  AUTH SEQ NUM:
AMT 1:                      INDUSTRY FRMT:
AMT 2:                      CONV FLAG:      ICHG PROC CDE:
ALT MRCHNT:                  TXN SUBTYPE:

      VIRTUAL PAN:                  EXP DATE:

***** BASE24 *****
      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY  F6-NEXT REC  F7-PREV REC  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

VIRTUAL PAN — The virtual primary account number used for the transaction. This value, along with the expiration date, is carried in the Virtual Primary Account Number token. This field is displayed only when the transaction contains the Virtual Primary Account Number token.

Field Length: System protected
Data Name: PSEUDO-CRD-NUM-TKN.PSEUDO-CRD-NUM

EXP DATE — The expiration date of the authentication transaction associated with the virtual primary account number. This value, along with the virtual primary account number, is carried in the Virtual Primary Account Number token. This field is displayed only when the transaction contains the Virtual Primary Account Number token.

Field Length: System protected

Data Name: PSEUDO-CRD-NUM-TKN.EXP-DAT

Note: This field will be completely masked if the PAN is configured for masking.

Screen 4-Format 2

Screen 4-format 2 displays service totals records. Service totals are displayed using format 2 only when the SETTLE TYPE field is set to the value 8 or 9 (service totals). Perusal methods include card number; terminal ID and time; terminal ID only; and retailer ID and clerk ID. The table below illustrates which transaction records are displayed according to perusal method, key screen format, and perusal type.

Perusal Method	Perusal Type	Record Format	Record Displayed
CARD NUMBER	T (totals) and SETL-TYP is 8 or 9	N/A	Service Totals
TERMINAL ID/ TIME			
TERMINAL ID	N/A	8 or 9 (service totals)	
RETAILER ID/ CLERK ID			

Pages 1 and 2 of screen 4-format 2 are shown below, followed by descriptions of their fields. When the settle type is 8 or 9, a third page can also be displayed. This third page is identical to page 2.

```

BASE24-POS    PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:    DATE(YMMDD) :        FIID:        LNET:
RETAILER:                TERM:                CLERK:

      DESC:                CRNCY:                DATE:                TIME:
BATCH NUM:                SHIFT NUM:                TIME OFST:
RETL ACCT:                BAL FLAG:
TYPE                      DEBIT                CREDIT                ADJUSTMENT
UK (UNKNOWN)
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00

***** BASE24 *****
FILE DESTINATION:        NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY  F6-NEXT REC  F7-PREV REC  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

```

BASE24-POS    PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

PERUSAL TYPE/REC FRMT:    DATE(YMMDD) :        FIID:        LNET:
RETAILER:                TERM:                CLERK:

TYPE                      DEBIT                CREDIT                ADJUSTMENT
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00
(                )                0.00                0.00                0.00

***** BASE24 *****
FILE DESTINATION:        NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY  F6-NEXT REC  F7-PREV REC  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

PERUSAL TYPE/REC FRMT — A code indicating the type of transaction being perused. When perusing by card number or terminal ID and time, T is the only valid value. When perusing by terminal ID or by retailer ID and clerk ID, valid values are as follows:

0 = Batch totals
1 = Shift totals
2 = Day totals
3 = Network totals
4 = Clerk totals
8 = Services totals
9 = Services totals

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE(YYMMDD) — The date of the PTLF to which this record was logged.

Field Length: System protected
Data Name: Not applicable

FIID — The financial institution identifier associated with this record. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected
Data Name: PTLF.HEAD.TERM.FIID

LNET — The logical network associated with this record. When perusing the PTLF by terminal ID only or by retailer ID and clerk ID, this field is blank.

Field Length: System protected
Data Name: PTLF.HEAD.TERM.LN

RETAILER — The retailer ID of the retailer associated with the terminal that generated this transaction.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.RETAILER-ID

TERM — The terminal ID of the terminal for which this PTLF record is displayed.

Field Length: System protected
Data Names: PTLF.HEAD.TERM.TERM-ID
(when perusing by terminal ID and time)
PTLF.HEAD.TKEY.TERM-ID
(when perusing by terminal ID only)

CLERK — The clerk ID of the clerk for which this PTLF record is displayed.

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.CLERK-ID

DESC — The description of this record (SERVICES SETTLE).

Field Length: System protected
Data Name: Not applicable

CRNCY — An alphabetic ISO code indicating the currency in which the amount totals are displayed. Valid values are listed in the ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.AUTH-CRNCY-CDE
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC1.AUTH-CRNCY-CDE
(when SETTLE TYPE is 8)

DATE — The date this record was logged to the PTLF. The date format is determined by the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.TRAN-DAT
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC1.TRAN-DAT
(when SETTLE TYPE is 8)

TIME — The 24-hour time, in hh:mm:ss format, this transaction was logged to the PTLF. The time displayed in this field includes the time offset displayed in the TIME OFST field.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.TRAN-TIM
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC1.TRAN-TIM
(when SETTLE TYPE is 8)

BATCH NUM — The batch number associated with the terminal ID in the TERMINAL field and to which this transaction belongs.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.BATCH-NUM

SHIFT NUM — The shift number associated with the terminal ID in the TERMINAL field and to which this transaction belongs.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.SHIFT-NUM

TIME OFST — The time difference, in minutes, between the location of the terminal that generated this transaction and the location of the HP NonStop processor. The value in this field is added to the BASE24-pos system time to obtain the local terminal time.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.TERM-TIM-OFST
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC1.TERM-TIM-OFST
(when SETTLE TYPE is 8)

RETL ACCT — The retailer's account number.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.RETL.ACCT
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC1.RETL.ACCT
(when SETTLE TYPE is 8)

BAL FLAG — A value indicating the type of totals that this record represents.
Valid values are as follows:

- 5 = PTDF TTLS (PTDD1 or PTDF totals)
- 6 = TERM TTLS (Terminal totals)
- 8 = FRCD INCMP (Forced; incomplete batch)
- 9 = FRCD CMPLT (Forced; complete batch)

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC1.BAL-FLG
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC1.BAL-FLG
 (when SETTLE TYPE is 8)

TYPE — The description of the card type associated with the totals.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC3.SRV.TYP
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.TYP
 (when SETTLE TYPE is 8)

DEBIT — The total count and total amount of debit transactions included in this batch for the specified card type.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC3.SRV.DB-CNT
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.DB-CNT
 (when SETTLE TYPE is 8)

PTLF.SRVCS-1.SET-REC3.SRV.DB
(when SETTLE TYPE is 9)
PTLF.SRVCS-2.SET-REC4.SRV.DB
(when SETTLE TYPE is 8)

CREDIT — The total count and total amount of credit transactions included in this batch for the specified card type.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC3.SRV.CR-CNT
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.CR-CNT
 (when SETTLE TYPE is 8)

 PTLF.SRVCS-1.SET-REC3.SRV.CR
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.CR
 (when SETTLE TYPE is 8)

ADJUSTMENT — The total count and total amount of adjustment transactions included in this batch for the specified card type.

Field Length: System protected
Data Names: PTLF.SRVCS-1.SET-REC3.SRV.ADJ-CNT
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.ADJ-CNT
 (when SETTLE TYPE is 8)

 PTLF.SRVCS-1.SET-REC3.SRV.ADJ
 (when SETTLE TYPE is 9)
 PTLF.SRVCS-2.SET-REC4.SRV.ADJ
 (when SETTLE TYPE is 8)

Screen 4-Format 3

Screen 4-format 3 displays batch, shift, day, or network totals records. These totals are displayed using format 3 only when the SETL-TYP field is set to the value 0 (batch totals), 1 (shift totals), 2 (day totals), or 3 (network totals). Perusal methods include card number and terminal ID and time. The table below illustrates which transaction records are displayed according to perusal method.

Perusal Method	Perusal Type	Record Format	Record Displayed
Card number	T (totals) and SETL-TYP is not 4, 8, or 9	N/A	Batch, Shift, Day, or Network Totals
Terminal ID and time			

Screen 4-format 3 is shown below, followed by descriptions of its fields.

```

BASE24-POS      PTLF DETAIL                      LLLL  FIID  YY/MM/DD  HH:MM  04 OF 04

  PERUSAL TYPE:      DATE (YYMMDD) :      FIID:      LNET:
  CARD/TERMINAL:      TIME:

  RETAILER:          BATCH NUM:      DATE:
  DESC:              SHIFT NUM:      TIME:
  BAL FLAG:          TIME OFST:

  DB AMT:            DB CNT:      CRNCY:
  CR AMT:            CR CNT:
  ADJ AMT:           ADJ CNT:

                        DRAFT CAPTURE
  DB AMT:            DB CNT:
  CR AMT:            CR CNT:
  ADJ AMT:           ADJ CNT:

***** BASE24 *****
                        FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F5-GOTO SUMMARY      F6-NXT REC      F7-PRV REC      F9-NXT PAGE      F11-PRV PAGE      F12-HELP

```

PERUSAL TYPE — A code indicating the type of transaction being perused.
Valid values are as follows:

D = Detail record perusal (PTLF.REC-TYP = 01, 20, 21, or 22)
T = Totals perusal (PTLF.REC-TYP = 04)

Field Length: System protected
Data Name: PTLF.HEAD.TKEY.RKEY.REC-FRMT

DATE — The date, in YYMMDD format, of the PTLF used in selecting this record to be displayed.

Field Length: System protected
Data Name: Not applicable

FIID — The financial institution identifier of the card-issuing institution associated with this transaction.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.FIID

LNET — The logical network associated with this transaction.

Field Length: System protected
Data Name: PTLF.HEAD.CRD.LN

CARD/TERMINAL — The card number used to select the PTLF transaction records for perusal or the terminal ID of the terminal for which PTLF records are displayed.

Field Length: System protected
Data Names: PTLF.HEAD.CRD.CARD.CRD-NUM
PTLF.HEAD.RETL.TERM-ID
(when perusing by terminal ID and time)
PTLF.HEAD.TKEY.TERM-ID
(when perusing by terminal ID only)

TIME — The 24-hour time, in hh:mm:ss format, this transaction was logged to the PTLF.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC1.TRAN-TIM

RETAILER — The retailer ID of the retailer associated with the terminal.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.KY.RDFKEY.ID

BATCH NUM — The batch number associated with the terminal ID in the TERMINAL field.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.BATCH-NUM

DATE — The date this record was logged to the PTLF. The date format is either DD/MM or MM/DD, depending on the value of the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC1.TRAN-DAT

DESC — A description of the record being displayed (i.e., batch, shift, daily, or network totals) and a notation indicating the nature of the totals. Valid values for the notation are as follows:

BASE24	= Totals are from the PTD.
BASE24 OB	= Totals are from the PTD and are out of balance with the totals from the terminal.
TERM OB	= Totals are from the terminal and are out of balance with the totals from the PTD.
FORCED	= Totals are from the PTD and were generated at cutover. The terminals were configured to be forced cut over by the Settlement Initiator process.
FORCED INCL	= Totals are from the PTD and were generated at cutover. The terminals were forced to cut over because the balancing transaction that was to initiate cutover never occurred within the balancing window.

Field Length: System protected
Data Name: Not applicable

SHIFT NUM — The shift number associated with the terminal ID in the TERMINAL field.

Field Length: System protected
Data Name: PTLF.HEAD.RETL.SHIFT-NUM

TIME — The 24-hour time, in hh:mm:ss format, this record was logged to the PTLF. The time in this field includes the time indicated in the TIME OFST field.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC1.TRAN-TIM

BAL FLAG — A value indicating the type of totals this record represents. Valid values are as follows:

- 5 = PTDF TTLS (PTD totals)
- 6 = TERM TTLS (Terminal totals)
- 8 = FRCD INCMP (Forced; incomplete batch)
- 9 = FRCD CMPLT (Forced; complete batch)

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC1.BAL-FLG

TIME OFST — The time difference, in minutes, between the location of the terminal that initiated this transaction and the location of the HP NonStop processor. The value in this field is added to the BASE24-pos system time to obtain the terminal's local time.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC1.TERM-TIM-OFST

DB AMT — The total amount of all draft capture and non-draft capture debit transactions occurring since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.DB

DB CNT — The number of all draft capture and non-draft capture debit transactions that have occurred since the totals were last cleared.

Field Length: System protected

Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.DB-CNT

CRNCY — A code indicating the country of the currency used in this transaction.

Field Length: System protected

Data Name: Not applicable

CR AMT — The total amount of all draft capture and non-draft capture credit transactions that have occurred since the totals were last cleared.

Field Length: System protected

Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.CR

CR CNT — The number of all draft capture and non-draft capture credit transactions that have occurred since the totals were last cleared.

Field Length: System protected

Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.CR-CNT

ADJ AMT — The total amount of all draft capture and non-draft capture adjustment transactions that have occurred since the totals were last cleared.

Field Length: System protected

Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.ADJ

ADJ CNT — The number of all draft capture and non-draft capture adjustment transactions that have occurred since the totals were last cleared.

Field Length: System protected

Data Name: PTLF.SET-REC.SET-REC2.STL.TOT.ADJ-CNT

DRAFT CAPTURE

The following fields are the counts and amounts of draft capture transactions. Nondraft capture items are not included in these fields.

DB AMT — The total amount of draft capture debit transactions that have occurred since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.DC-TOT.DB

DB CNT — The number of draft capture debit transactions that have occurred since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.DC-TOT.DB-CNT

CR AMT — The total amount of draft capture credit transactions that have occurred since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.DC-TOT.CR

CR CNT — The number of draft capture credit transactions that have occurred since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.DC-TOT.CR-CNT

ADJ AMT — The total amount of draft capture adjustment transactions that have occurred since the totals were last cleared.

Field Length: System protected
Data Name: PTLF.SET-REC.SET-REC2.STL.DC-TOT.ADJ

10: Response Code Description File (RCDF)

The Response Code Description File (RCDF) contains one record for every ISO response code and BASE24 response code supported in the BASE24 system that have been defined to be returned to the terminal. The RCDF records contain ISO response codes and descriptions as well as BASE24 response codes and descriptions that are sent to the terminal during transaction processing.

Values in the RCDF can be used to override the BASE24 response code description listed in the ACI Standard Response file (ARSP). During transaction processing, the RCDF is accessed to determine the response code description to be sent to the terminal. If no record exists in the RCDF, the response code description in the ARSP is used.

This file is currently used by the Standard POS Device Handler (SPDH).

The TERMINAL GROUP, RECORD TYPE, FIID, LANGUAGE INDICATOR, ACCOUNT TYPE, and RESPONSE CODE fields combine to form the primary key to this file.

Information from the RCDF is used by BASE24 processes in the Response Code Description File extended memory table (RCDFEMT). Any time a change is made to the RCDF, the RCDFEMT should be rebuilt using the Extended Memory Table Build utility and reallocated to processes that access the table using the EMT Control Commands screen. The Extended Memory Table Build utility is described in detail in the *BASE24-pos Transaction Processing Manual*. The EMT Control Commands screen is accessed from the Device Control Terminal (DCT) Product Menu and is described in the *BASE24 Device Control Manual*.

This section describes the file maintenance screen used to access records in the RCDF.

Screen 1 Function Keys

The use of four function keys on RCDF screen 1 varies from the standard function keys. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on RCDF screen 1.

Key	Description
F1	Select The Detail Record - Switches to RCDF screen 2 and displays the details for the selected record. A transaction record is selected by positioning the cursor on the same line as the summarized record when the F1 key is pressed.
F2	Read Summary Records — Displays a summary of the first 12 RCDF records for the terminal group, FIID, language indicator, and record type entered.
Shift-F2	Scroll Down — Displays a summary of the next 12 RCDF records for the terminal group, FIID, language indicator, and record type entered.
Shift-F3	Scroll Up — Displays a summary of the previous 12 RCDF records for the terminal group, FIID, language indicator, and record type entered.

```
***** BASE24 *****
FILE DESTINATION: NEW LOGICAL NETWORK ID:
F1-SELECT SF2-SCROLL-DOWN SF3-SCROLL-UP F12-HELP
```

Data Name: RCDF.PRIKEY.TERM-GRP

FIID — Indicates the FIID of the financial institution associated with this terminal. This value is defined in the POS Terminal Data File (PTD).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: *****
Data Name: RCDF.PRIKEY.FIID

LANGUAGE INDICATOR — A code identifying the language in which the record is stored. This value corresponds to the language indicator in the SPDH native message. Valid values are an asterisk 0, 1, or 2.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: *
Data Name: RCDF.PRIKEY.LANG-IND

RECORD TYPE — Indicates the record type for the RCDF record. Valid values are as follows:

01 = ISO
02 = BASE24

Field Length: 2 alphanumeric characters
Required Field: Yes
Default Value: 01
Data Name: RCDF.PRIKEY.REC-TYP

SELECT — Selects an RCDF record to be displayed. When you place the cursor in this field and press the **F1** key, the selected record is displayed on RCDF screen 2.

Field Length: Cursor placement only
Occurs: Up to 12 times
Data Name: Not applicable

ACCOUNT TYPE — Indicates which account type is valid for this RCDF record.

Field Length: System protected
Occurs: Up to 12 times
Data Name: RCDF.PRIKEY.ACCT-TYP

RESPONSE CODE — Indicates the response code associated with the response code description.

Field Length: System protected
Occurs: Up to 12 times
Data Name: RCDF.PRIKEY.RESP-CODE

DESCRIPTION — A text description for this response code.

Field Length: System protected
Occurs: Up to 12 times
Data Name: RCDF.DESCR

Screen 2

RCDF screen 2 displays individual response code records. From this screen, you can read, add, update, and delete individual RCDF records. RCDF screen 2 is shown below, followed by descriptions of its fields.

```
BASE24-POS  RESPONSE CODE DESCRIPTION LLLL          YY/MM/DD  HH:MM  02 OF 02

  TERMINAL GROUP:          FIID:          LANGUAGE INDICATOR:
    RECORD TYPE:

ACCOUNT TYPE:          RESPONSE CODE:
  DESCRIPTION:

***** BASE24 *****
          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                F12-HELP
```

TERMINAL GROUP — Identifies the terminal group to which the originating terminal belongs. This value is defined in the POS Terminal Data File (PTD).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: ****
Data Name: RCDF.PRIKEY.TERM-GRP

FIID — Indicates the FIID of the financial institution associated with this terminal. This value is defined in the POS Terminal Data File (PTD).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: ****
Data Name: RCDF.PRIKEY.FIID

LANGUAGE INDICATOR — A code identifying the language in which the record is stored. This value corresponds to the language indicator in the SPDH native message. Valid values are an asterisk 0, 1, or 2.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: *
Data Name: RCDF.PRIKEY.LANG-IND

RECORD TYPE — A code identifying the record type for the RCDF record. Valid values are as follows:

01 = ISO. The value in the RESPONSE CODE field is an ISO response code
02 = BASE24. The value in the RESPONSE CODE field is a BASE24 response code.

Field Length: 1–2 alphanumeric characters
Required Field: Yes
Default Value: 01
Data Name: RCDF.PRIKEY.REC-TYP

ACCOUNT TYPE — A code identifying which account type is valid for this RCDF record.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: RCDF.PRIKEY.ACCT-TYP

RESPONSE CODE — Indicates the response code associated with the response code description.

Field Length: 1–3 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: RCDF.PRIKEY.RESP-CDE

DESCRIPTION — A text description for this response code.

Field Length: 1–48 alphanumeric characters
Required Field: Yes
Default Value: Spaces
Data Name: RCDF.DESCR

11: Routing Table File (RTBL)

The Routing Table File (RTBL) is used by the BASE24-pos product to identify allowable authorization destination processes and their associated codes for the routing of transactions. Any authorization destination code entered in the Authorization Selection Table (AST) must be defined in the RTBL, and the RTBL record must be set up prior to the AST record.

This section describes the file maintenance screen used to access the RTBL.

Screen 1

RTBL screen 1 contains allowable authorization processes and their associated codes used for routing transactions. Screen 1 is divided into three columns containing identical fields. Up to 42 entries, 14 in each column, can be entered on this screen. RTBL screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-POS   ROUTE-TABLE FILE           LLLL           YY/MM/DD  HH:MM  01 OF 01

DESTINATION  PROC ID      DESTINATION  PROC ID      DESTINATION  PROC ID
AUTHF        00          AUTHH          01
NEGN         02          NEGF           03
DFLT         14          P1A^VISA    04
P1A^LINK     05          P1A^NET     06

```

```

***** BASE24 *****
FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                        F12-HELP

```

DESTINATION PROC — The symbolic names of the processes that communicate with allowable authorizers.

Five entries are predefined and always remain the same. These are not process names, but rather methods of authorization to be employed by the BASE24-pos product. The remaining 37 entries are user-defined and must be symbolic process names. They are the processes to which transactions bound for an authorizer must be sent, and they must match symbolic process names configured to the XPNET system. The only appropriate process names to be included are those of Interchange Interface processes.

The predefined entries are as follows:

- AUTHF** = Authorize transactions using the authorization methods and levels specified in the IDF routing table, except when the authorization level specifies that the transaction should be handled online/offline. AUTHF overrides the online/offline setting and forces the transaction to be processed by the BASE24-pos product without being sent to the host, even if the host is online and available. (The authorization method used is the authorization method specified in the IDF routing table for the transaction.) This option is designed to offload processing from the host. It can be used as an alternate authorizer in the AST for both over and under the floor destinations and as a primary authorizer for under the floor destinations. However, it cannot be used as an alternate authorizer in the AST if AUTHH is configured as the primary authorizer.
- AUTHH** = Authorize transactions using the authorization methods and levels specified in the IDF routing table. Under this option, transactions can be authorized by the BASE24-pos product or sent to a host. This option can be used as a primary or alternate authorizer in the AST. It can be used for both over and under the floor destinations. If more than one HISO process is configured as an authorizer in the AST, then the first of these entries must be specified as "AUTHH" (i.e., where the actual destination is configured in the IDF Routing Table).
- NEGN** = Authorize transactions using the National Negative Card Files (NNFs). Under this option, if the card number is found in the appropriate NNF, the transaction can be approved VIP, denied, or referred based on the card status value in the NNF record. If the card number is not found in the NNF record, the transaction is approved. This option can be used only as a primary authorizer in the AST. It can be used for both over or under the floor destinations.

- NEGF = Authorize transactions using the National Negative Card Files (NNFs). Under this option, if the card number is found in the appropriate NNF, the transaction can be approved VIP, denied, or referred based on the card status value in the NNF record. If the card number is not found in the NNF, the transaction amount is compared to the offline limit amount in the AST. If the transaction amount is less than or equal to the offline limit amount, the default action in the AST is taken. If the transaction amount is greater than the offline limit amount, the transaction is denied. This option can be used only as an alternate authorizer in the AST. It can be used for both over and under the floor destinations.
- DFLT = Authorize transactions using the default action (authorize blind, issue a call, or decline) specified in the Authorization Selection Table (AST). Under this option, transactions are not routed to an authorizer. This option can be used as a primary authorizer and can be used for either under or over the floor limit. If DFLT is used as a primary authorizer in the AST, values are not allowed in the alternate authorizer fields.

When multiple XPNET nodes or logical networks share a single AST, you can define RTBL symbolic process names that use asterisks (*) as wildcard characters in the second or third character positions or both. During initialization, the Router module substitutes values representing the XPNET node or logical network in which it resides. This RTBL character substitution also is called star routing. For example, if the AST is accessed by XPNET nodes A and B in logical networks 1 and 2, you can enter the symbolic name P**^BNET to indicate the Banknet Interchange Interface process in logical network 1 or 2 and XPNET node A or B. At initialization, the Router module in logical network 1, XPNET node A converts the symbolic name to P1A^BNET, and the Router module in logical network 1, XPNET node B converts it to P1B^BNET. For more information about star routing, refer to the *BASE24-pos Transaction Processing Manual*.

Field Length: 1-16 alphanumeric characters
 Occurs: Up to 42 times
 Required Field: Yes
 Default Value: No default value
 Data Name: RTBL.AUTH.NAM

ID — The codes associated with the symbolic names in the DESTINATION PROCESS fields in the table. Five codes, 00 through 03 and 14, are predefined and always remain the same. The remaining 37 codes, 04 through 13 and 15 through 41, are user-defined. These codes are placed in the appropriate fields in the Authorization Selection Table (AST).

The predefined codes are as follows:

00 = AUTHF
01 = AUTHH
02 = NEGN
03 = NEGF
14 = DFLT

Field Length:	2 numeric characters
Occurs:	Up to 42 times
Required Field:	Yes
Default Value:	No default value
Data Name:	RTBL.AUTH.ID

ACI Worldwide, Inc.

Index

A

- Account delinquency, number of cycles, [4-8](#)
- Adjustment transactions, terminal limits, [8-22](#)
- Administrative Card File (ADMN)
 - accessing from POS Product Menu, [1-5](#)
 - description, [2-1](#)
 - screen 1 illustration, [2-2](#)
- ADMN
 - see* Administrative Card File (ADMN)
- Alternate authorization destination, [3-12](#)
- AST
 - see* Authorization Selection Table (AST)
- Authorization parameters
 - card type, [4-3](#)
 - delinquent table, [4-6](#)
 - overlimit table, [4-10](#)
 - single advance limits, [4-5](#)
 - single purchase limit, [4-4](#)
 - single purchase percent, [4-4](#)
- Authorization routing, description, [3-1](#)
- Authorization Selection Table (AST)
 - accessing from POS Product Menu, [1-5](#)
 - deleting card entries, [3-7](#)
 - description, [3-1](#)
 - function keys, [3-2](#)
 - relationship to RTBL, [3-1](#)
 - screen 9 illustration, [3-16](#)
 - screens 1, 3, 5, and 7 illustration, [3-5](#)
 - screens 2, 4, 6, and 8 illustration, [3-11](#)
 - using FIID to locate, [3-5](#)

C

- CAPF
 - see* Card Authorization Parameters File (CAPF)
- Card Authorization Parameters File (CAPF)
 - accessing from POS Product Menu, [1-5](#)
 - description, [4-1](#)
 - screen 1 illustration, [4-2](#)
- Card floor limits, [8-61](#)
- Card key, PTLF, [9-2](#)
- Card number perusal
 - see* POS Transaction Log File (PTLF) perusal
- Card totals, [8-65](#)
- CART
 - see* Check Authorization Routing Table File (CART)

- Cash advance transaction
 - card floor limits, [8-61](#)
 - floor limits, [3-9](#)
- Check Authorization Routing Table File (CART)
 - accessing from POS Product Menu, [1-5](#)
 - description, [5-1](#)
 - screen illustration, [5-3](#)
- Check guarantee transactions, routing, [5-1](#)
- Check verification transactions, routing, [5-1](#)

D

- Decryption data, [8-55](#)
- Delinquency checks, [4-6](#)
- Delinquent table
 - description, [4-6](#)
 - response, [4-9](#)
- Dual site transaction field
 - PTLF Detail Screen Formats (Screen 4), [9-45](#)

E

- EMT Control Commands screen, RCDF extended memory table, [10-1](#)
- Encryption data, [8-55](#)
- Extended Memory Table Build utility, RCDF extended memory table, [10-1](#)

F

- Field descriptions, format explanation, [1-8](#)
- Files
 - accessing with files maintenance screens, [1-3](#)
 - using product menus to locate, [1-3](#)
- Floor limit, description, [3-9](#)
- Function keys
 - AST screens, [3-2](#)
 - PTLF key screens, [9-3](#)
 - PTLF summary screens, [9-15](#)
 - RCDF screen 1, [10-2](#)
 - standard, [1-7](#)
- Functions
 - accessing with files maintenance screens, [1-3](#)
 - using product menus to locate, [1-3](#)

G

Grouping terminals at a site, [8-2](#)

K

Key locator, [8-56](#), [8-58](#)

L

Logical Network Configuration File (LCONF) params

DATE-DISPLAY-TYPE, [9-21](#), [9-63](#)

POS-RTAU-AST-ROUTE, [3-6](#)

POS-SETL-PTLF-FILE-RETENTION, [9-1](#)

M

Mail or telephone order transaction

card floor limits, [8-61](#)

floor limits, [3-9](#)

Menus

POS Product Menu, [1-4](#)

Virtual Menu, [1-3](#)

Messages to terminal, [8-70](#)

N

National Negative Card File (NNF)

accessing from POS Product Menu, [1-5](#)

description, [6-1](#)

screen illustration, [6-2](#)

NNF

see National Negative Card File (NNF)

O

Offline floor limits, defining, [3-10](#)

Online floor limits, defining, [3-8](#)

Operator totals, [8-43](#)

Overlimit table, [4-10](#)

P

Parametric Authorization method, authorization criteria
in CAPF, [4-1](#)

POS devices

characteristics, [8-4](#)

service representative information, [8-16](#)

POS Product Menu

accessing from Virtual Menu, [1-3](#)

files and functions, [1-4](#)

illustration, [1-5](#)

POS Retailer Definition File (PRDF)

accessing from POS Product Menu, [1-5](#)

description, [7-1](#)

screen 1 illustration, [7-2](#)

screen 4 illustration, [7-16](#)

screens 2 and 3 illustration, [7-12](#)

POS Terminal Data Dynamic—general data
(PTDD1), [8-1](#)

POS Terminal Data File (PTD)

function keys, [8-3](#)

POS Terminal Data File (PTDF), [8-1](#)

POS Terminal Data files (PTD)

accessing from POS Product Menu, [1-5](#)

description, [8-1](#)

screen 1 illustration, [8-4](#)

screen 2 illustration, [8-16](#)

screen 3 illustration, [8-22](#)

screen 4 illustration, [8-30](#)

screen 5 illustration, [8-43](#)

screen 6 illustration, format 1, [8-48](#)

screen 6 illustration, format 2, [8-53](#)

screen 7 illustration, [8-55](#)

screen 18 illustration, [8-70](#)

screen 19 illustration, [8-76](#)

screens 8, 9, and 10 illustration, [8-61](#)

screens 11, 12, 13, 14, 15, and 16 illustration, [8-65](#)

terminology, [8-1](#)

POS Terminal Data Static File—general data
(PTDS1), [8-1](#)

POS Transaction Log File (PTLF)

accessing from POS Product Menu, [1-5](#)

description, [9-1](#)

detail screen formats, [9-34](#)

function keys, key screens, [9-3](#)

function keys, summary screen, [9-15](#)

key screen 1, [9-4](#)

key screen 2, [9-11](#)

key screen, description, [9-2](#)

perusal summary screen formats, [9-15](#)

screen 3—format 1, [9-18](#)

screen 3—format 2, [9-22](#)

screen 3—format 3, [9-25](#)

screen 3—format 4, [9-29](#)

screen 4—format 1, [9-35](#)

screen 4—format 1, page 1, [9-36](#)

screen 4—format 1, page 2, [9-45](#)

screen 4—format 2, [9-54](#), [9-55](#)

screen 4—format 3, [9-61](#)

specifying terminal totals to be logged, [8-28](#), [8-29](#)

POS Transaction Log File (PTLF) perusal

card number perusal, [9-5](#), [9-35](#)

retailer ID and clerk ID perusal, [9-9](#), [9-13](#), [9-35](#)

terminal ID and time perusal, [9-6](#)

terminal ID perusal, [9-8](#), [9-11](#), [9-35](#)

PRDF

see POS Retailer Definition File (PRDF)

Preauthorization transactions, terminal limits, [8-22](#)

Primary authorization destination, overriding, [3-12](#),
[3-14](#)

PTD

see POS Retailer Definition File (PRDF)

see POS Terminal Data files (PTD)

PTDD1

see POS Terminal Data Dynamic File—general data
(PTDD1), [8-1](#)

PTDF
 see POS Terminal Data File (PTDF)
PTDS1
 see POS Terminal Data Static File—general data (PTDS1), 8-1
PTLF
 see POS Transaction Log File (PTLF)
Purchase transactions, card floor limits, 8-61

R

RCDF
 see Response Code Description File (RCDF)
RCDF extended memory table, 10-1
Response Code Description File (RCDF)
 description, 10-1
 screen 1 function keys, 10-2
 screen 1 illustration, 10-3
 screen 2 illustration, 10-6
Retailer ID, AST record, 3-7
Retailer ID/clerk ID perusal
 see POS Transaction Log File (PTLF) perusal
Retailer/clerk key, PTLF, 9-2
Return transactions, terminal limits, 8-22
Routing Table File (RTBL)
 accessing from POS Product Menu, 1-5
 alternate authorization destination, 3-12, 3-14
 character substitution, 11-4
 description, 11-1
 displaying from AST, 3-4
 relationship to AST, 3-1
 screen 1, 11-2
Routing transactions, authorization processes, 3-16
RTBL
 see Routing Table File (RTBL)
RTBL character substitution, 11-4

S

Service code, AST, 3-7
Settlement totals, terminal, 8-30
Star routing
 see RTBL character substitution
Stored Value History File (SVHF)
 accessing from POS Product Menu, 1-5

T

Terminal ID perusal
 see POS Transaction Log File (PTLF) perusal
Terminal ID/time key, PTLF, 9-2
Terminal ID/time perusal
 see POS Transaction Log File (PTLF) perusal
Terminal limits, 8-22

Terminal totals
 logging to PTLF, 8-28, 8-29
 PTD fields, 8-25
Terminal/retailer key, PTLF, 9-2
Transaction processing parameters, 8-16
Transaction routing, Authorization processes, 3-16
Transaction Security Services key locator, 8-56, 8-58
Transaction set, administrative, 2-1
Transaction set, retailer, 8-47

V

Virtual Menu
 accessing POS or BASE PS product menus, 1-3
 illustration, 1-3

ACI Worldwide, Inc.

Index by Field Name

Special Characters

OF USES EXCEEDED RESPONSE, [4-3](#)

A

ACCOUNT TYPE

RCDF screen 1, [10-5](#)

RCDF screen 2, [10-7](#)

ACCT, [9-41](#)

ACCT #, [7-5](#)

ACH COMP ID, [7-6](#)

ACQUIRER TXN PROFILE

PRDF, [7-18](#)

PTD, [8-51](#)

ACTIVE

CAPF screen 1, delinquent table, [4-7](#)

CAPF screen 1, overlimit table, [4-12](#)

ADDITIONAL CARD NUMBER, [9-51](#)

ADDR, [9-46](#)

ADDR STAT, [9-47](#)

ADDRESS

PRDF, [7-3](#)

PTD, [8-17](#)

ADJ AMT

PTLF detail screen 4—format 3, [9-65](#)

PTLF detail screen 4—format 3, draft capture, [9-66](#)

ADJ CNT

PTLF detail screen 4—format 3, [9-65](#)

ADJUST AMT2 > AMT1, [8-49](#)

ADJUST. AMOUNT, [8-67](#)

ADJUST. NUM, [8-67](#)

ADJUSTMENT

PTD, [8-45](#)

PTLF, [9-60](#)

ADJUSTMENT COUNT, [8-24](#)

ADMINISTRATIVE CARD FILE, [2-2](#)

ADMN TXN PROFILE, [2-4](#)

AFTER HOURS PHONE, [7-5](#)

ALT MRCHNT, [9-44](#)

ALTERNATE MERCHANT ID, [7-15](#)

AMEX SE NUMBER CHECK, [7-19](#)

AMOUNT

PTLF summary screen 3—format 1, [9-20](#)

PTLF summary screen 3—format 2, [9-24](#)

PTLF summary screen 3—format 3, [9-27](#)

AMT 1, [9-43](#)

AMT 2, [9-44](#)

APPROVAL CODE LENGTH, [8-21](#)

APPRV CODE

PTLF detail screen formats, [9-41](#)

PTLF summary screen 3—format 1, [9-20](#)

PTLF summary screen 3—format 2, [9-25](#)

PTLF summary screen 3—format 3, [9-28](#)

AUTH IND, [9-42](#)

AUTH LEVEL

CART, [5-7](#)

AUTH PARTIAL AMOUNT, [7-19](#)

AUTH PARTIAL AMT, [8-50](#)

AUTH SEQ NUM, [9-43](#)

AUTH TYPE, [5-7](#)

AUTHORIZER, [9-42](#)

B

BAD PIN TRIES, [2-4](#)

BAL FLAG

PTLF detail screen 4—format 2, [9-59](#)

PTLF detail screen 4—format 3, [9-64](#)

BALANCE FLAG, [8-40](#)

BALANCE RETURNED, [8-19](#)

BALANCE SUPPORT, [8-27](#)

BATCH

PTD screen 3, [8-28](#)

PTD screen 4, [8-30](#)

BATCH CUTOVER COUNT, [8-25](#)

BATCH NUM

PTLF detail screen 4—format 1, [9-39](#)

PTLF detail screen 4—format 2, [9-58](#)

PTLF detail screen 4—format 3, [9-63](#)

PTLF summary screen formats, [9-31](#)

BATCH NUMBER, [8-25](#)

BATCH-DC, [8-32](#)

BAUD RATE, [8-10](#)

BILLING INFO, [8-13](#)

BIRTH/ID DATE, [9-48](#)

- C**
- CARD
 - PTLF detail screen formats, [9-37](#)
 - PTLF key screens, [9-6](#)
 - PTLF summary screen formats, [9-19](#)
 - CARD CAPTURE, [8-80](#)
 - CARD FLOOR LIMITS, [8-61](#)
 - CARD NUMBER
 - ADMN, [2-2](#)
 - NNF, [6-2](#)
 - CARD NUMBER PERUSAL, [9-5](#)
 - CARD TOTALS, [8-65](#)
 - CARD TYPE
 - CAPF, [4-2](#)
 - PRDF, [7-12](#)
 - PTD screens 11-16, [8-66](#)
 - PTD screens 8, 9, and 10, [8-62](#)
 - PTLF, [9-38](#)
 - CARDHOLDER ACTIVATED TERMINAL, [8-80](#)
 - CARDHOLDER AUTHENTICATION, [8-82](#)
 - CARDS RETAINED, [8-42](#)
 - CARD/TERMINAL, [9-62](#)
 - CASH, [8-46](#)
 - CASH ADV, [8-63](#)
 - CATEGORY NAME, [8-74](#)
 - CEILING LIMIT, [7-14](#)
 - CHECK, [8-46](#)
 - CHECK DIGITS
 - PTD screen 7, MAC key, [8-59](#)
 - PTD screen 7, PIN key, [8-57](#)
 - CHECK ID TYPE, [5-5](#)
 - CHECK MERCH ID, [7-8](#)
 - CHECK RTG GROUP, [7-8](#)
 - CHECK SPF, [5-8](#)
 - CHECK SRV PROVIDER CODE, [7-8](#)
 - CHK ID, [9-48](#)
 - CHK TYP, [9-48](#)
 - CITY
 - PRDF, [7-3](#)
 - PTD, [8-7](#)
 - CITY/STATE, [8-17](#)
 - CLERK
 - PTLF detail screen 4—format 1, [9-38](#)
 - PTLF detail screen 4—format 2, [9-57](#)
 - PTLF key screen 1 retailer/clerk perusal, [9-10](#)
 - PTLF key screen 1 terminal ID perusal, [9-9](#)
 - PTLF key screen 2 retailer ID/clerk ID perusal, [9-14](#)
 - PTLF key screen 2 terminal ID perusal, [9-12](#)
 - PTLF summary screen formats, [9-31](#)
 - CLERK ID
 - PTD, [8-13](#)
 - PTLF, [9-27](#)
 - CLERK NAME, [2-3](#)
 - CLERK TOTALS
 - PTD screen 5, [8-43](#)
 - PTD screen 6, format 1, [8-49](#)
 - CLERK TOTALS FLAG, [8-43](#)
 - CNTRY, [8-18](#)
 - COMMENTS, [3-7](#)
 - COMPLETE TRACK2 DATA, [8-21](#)
 - COMPLETION CODE, [8-73](#)
 - COMPLETION STORED MESSAGES, [8-72](#)
 - COMPLETION UNSOLICITED MESSAGES, [8-72](#)
 - CONTACT INPUT CAPABILITIES, [8-81](#)
 - CONTACTLESS INPUT CAPABILITIES, [8-81](#)
 - CONV FLAG, [9-44](#)
 - COUNTRY
 - PRDF, [7-4](#)
 - PTD, [8-8](#)
 - COUNTY, [7-4](#)
 - CR AMT
 - PTLF detail screen 4—format 3, [9-65](#)
 - PTLF detail screen 4—format 3, draft capture, [9-66](#)
 - CR CNT
 - PTLF detail screen 4—format 3, [9-65](#)
 - PTLF detail screen 4—format 3, draft capture, [9-66](#)
 - CREDIT
 - PTD, [8-45](#)
 - PTLF, [9-60](#)
 - CREDITS AMOUNT, [8-67](#)
 - CREDITS NUM, [8-67](#)
 - CRNCY
 - PTLF detail screen 4—format 2, [9-57](#)
 - PTLF detail screen 4—format 3, [9-65](#)
 - CRT AUTHORIZATION DEBIT CARD SUPPORT, [7-17](#)
 - CUR NT, [8-37](#)
 - CUR NT-DC, [8-38](#)
 - CURR CODE
 - PTLF summary screen 3—format 1, [9-20](#)
 - PTLF summary screen 3—format 2, [9-24](#)
 - PTLF summary screen 3—format 3, [9-28](#)
 - CURRENCY CODE, [8-19](#)
 - CUSTOMER BALANCE DISPLAY, [8-19](#)
 - CYCLE 1
 - CAPF screen 1, delinquent table, [4-8](#)
 - CAPF screen 1, overlimit table, [4-12](#)
 - CYCLE 2
 - CAPF screen 1, delinquent table, [4-8](#)
 - CAPF screen 1, overlimit table, [4-13](#)
 - CYCLE 3
 - CAPF screen 1, delinquent table, [4-9](#)
 - CAPF screen 1, overlimit table, [4-13](#)
- D**
- DAILY, [8-34](#)

DAILY-DC, [8-36](#)

DATA ENCRYPTION TYPE

PTD screen 7, [8-59](#)

DATE

PTLF detail screen 4—format 1, [9-37](#)

PTLF detail screen 4—format 2, [9-56](#), [9-57](#)

PTLF detail screen 4—format 3, [9-62](#), [9-63](#)

PTLF key screen 1 card number perusal, [9-5](#)

PTLF key screen 1 retailer/clerk perusal, [9-10](#)

PTLF key screen 1 terminal ID perusal, [9-8](#)

PTLF key screen 1 terminal ID/time perusal, [9-7](#)

PTLF key screen 2 retailer ID/clerk ID perusal, [9-13](#)

PTLF key screen 2 terminal ID perusal, [9-12](#)

PTLF summary screen 3—format 1, [9-18](#)

PTLF summary screen 3—format 2, [9-23](#)

PTLF summary screen 3—format 3, [9-26](#)

PTLF summary screen 3—format 4, [9-30](#)

DAY, [8-29](#)

DAYS, [4-7](#)

DB AMT

PTLF detail screen 4—format 3, [9-64](#)

PTLF detail screen 4—format 3, draft capture, [9-66](#)

DB CNT

PTLF detail screen 4—format 3, [9-65](#)

PTLF detail screen 4—format 3, draft capture, [9-66](#)

DEBIT

PTD, [8-44](#)

PTLF, [9-59](#)

DEBITS AMOUNT, [8-66](#)

DEBITS NUM, [8-66](#)

DEFAULT PRE-AUTH AMOUNT, [8-22](#)

DEFAULT TRAN CODE

PTD screen 6—format 1, [8-48](#)

PTD screen 6—format 2, [8-53](#)

DELINQUENT TABLE, [4-6](#)

DELIVERY MODE, [8-73](#)

DESC

PTLF detail screen 4—format 2, [9-57](#)

PTLF detail screen 4—format 3, [9-63](#)

DESCR, [10-5](#)

DESCRIPTION

RCDF screen 1, [10-5](#)

RCDF screen 2, [10-8](#)

DESTINATION DPC, [8-52](#)

DESTINATION PROC

AST, [3-17](#)

RTBL, [11-2](#)

DFLT CHECK ID, [8-14](#)

DH PROCESS NAME, [8-14](#)

DPC, [5-6](#)

DRAFT CAP, [9-40](#)

DRAFT CAPTURE

PRDF, [7-13](#)

PTLF, [9-66](#)

DUAL SITE INDICATOR, [8-15](#)

E

EF, [8-62](#)

EMV DELATED AUTH SUPPORT, [7-18](#)

ENCRYPTION KEYS, [8-55](#)

ENHANCED PREAUTH, [8-50](#)

ERR FLAG, [9-40](#)

EXP DATE, [9-38](#), [9-53](#)

F

FIID

ADMN, [2-3](#)

AST, [3-5](#)

CAPF, [4-2](#)

CART, [5-3](#), [5-6](#)

PRDF, [7-2](#)

PTD, [8-5](#)

PTLF detail screen 4—format 1, [9-37](#)

PTLF detail screen 4—format 2, [9-56](#)

PTLF detail screen 4—format 3, [9-62](#)

PTLF key screens, [9-5](#), [9-7](#)

PTLF summary screen 3—format 1, [9-19](#)

PTLF summary screen 3—format 2, [9-23](#)

PTLF summary screen 3—format 4, [9-31](#)

RCDF screen 1, [10-4](#)

RCDF screen 2, [10-6](#)

G

GROUP, [7-3](#)

I

ICHG PROC CDE, [9-44](#)

ID

AST, [3-16](#)

RTBL, [11-5](#)

INDUSTRY FRMT, [9-43](#)

INSTITUTION ID NUM, [5-4](#)

INVOICE, [9-41](#)

ISS CODE, [9-39](#)

ISSUER

AST, [3-8](#), [3-11](#)

CAPF, [4-3](#)

K

KEYD-GRP, [8-58](#)

L

LANGUAGE ID, [8-14](#)

LANGUAGE INDICATOR

RCDF screen 1, [10-4](#)

RCDF screen 2, [10-7](#)

LAST RESET DATE, [2-3](#)

LAST SETTLED DATE, [8-42](#)

LAST USED DATE, [2-4](#)

LIS5 CODE, [9-50](#)

LNET

PTLF detail screen 4—format 1, [9-37](#)

PTLF detail screen 4—format 2, [9-56](#)

PTLF detail screen 4—format 3, [9-62](#)

PTLF key screens, [9-6](#), [9-7](#)

PTLF summary screen 3—format 1, [9-19](#)

PTLF summary screen 3—format 2, [9-23](#)

PTLF summary screen 3—format 4, [9-31](#)

LOCATION, [8-7](#)

LOG ROUTE CODE, [8-18](#)

LOG TOTALS, [8-28](#)

LOGGING AND TRANSACTION
INFORMATION, [8-18](#)

LOGICAL NET, [8-5](#)

M

MAC MASTER KEY, [8-58](#)

MAC TYPE, [8-58](#)

MAIL ORDER, [8-64](#)

MAIL PRO NAME, [8-70](#)

MAIL/PHONE SIC CODE

PRDF, [7-6](#)

PTD, [8-12](#)

MAXIMUM PIN TRIES, [2-4](#)

MC TALLING TYPE, [8-20](#)

MEMBER NUM

PTLF detail screen formats, [9-37](#), [9-38](#)

PTLF key screens, [9-6](#)

PTLF summary screen formats, [9-19](#)

MESSAGE DATE, [8-74](#)

MESSAGE ID, [8-74](#)

MNO CODE, [9-49](#)

MOBILE PHONE NUM, [9-49](#)

N

NAME, [8-17](#)

NETWORK, [8-29](#)

NNEG FIRST, [7-13](#)

NUMBER OF BATCHES, [8-25](#)

NUMBER OF SHIFTS, [8-26](#)

O

OFFLINE LIM, [3-10](#)

ONLINE, [3-8](#)

ONLINE ADV, [3-9](#)

ONLINE MO, [3-9](#)

ONLINE PUR, [3-9](#)

ORIG INVOICE, [9-41](#)

OVER, [3-12](#)

OVER A1, [3-12](#)

OVER A2, [3-13](#)

OVER DA, [3-13](#)

OVER P, [3-12](#)

OVERLIMIT TABLE, [4-10](#)

OVERRIDE DEST PROCESS, [7-13](#)

OVERRIDE FLAG, [9-41](#)

P

PAN

PTLF detail screen formats, [9-38](#)

PTLF summary screen formats, [9-23](#), [9-27](#)

PASS-THROUGH PARAMETERS

PTD screen 6, [8-52](#)

PERCENT, [4-11](#)

PERUSAL TYPE

PTLF detail screen formats, [9-62](#)

PTLF key screens, [9-5](#), [9-6](#)

PTLF summary screen formats, [9-18](#)

PERUSAL TYPE/REC FRMT

PTLF detail screen formats, [9-36](#), [9-56](#)

PTLF summary screen formats, [9-22](#), [9-30](#)

PHONE

PRDF, [7-5](#)

PTD, [8-18](#)

PIN ENCRYPTION TYPE, [8-56](#)

PIN MASTER KEY, [8-56](#)

PIN OFFSET, [2-3](#)

PIN PAD CHARACTER, [8-55](#)

PIN PRESENT, [9-40](#)

POS RETAILER TRANSACTION SET, [8-54](#)

POS Transaction Log File (PTLF) perusal

card number perusal, [9-54](#), [9-61](#)

retailer ID/clerk ID perusal, [9-54](#)

terminal ID perusal, [9-54](#)

terminal ID/time perusal, [9-54](#), [9-61](#)

POS/NEG CONFIRMATION, [8-71](#)

POST DATE, [8-41](#)

POSTAL CODE

PRDF, [7-4](#)

PTD, [8-8](#)

POST-COMM FLOOR LIMIT, [8-77](#)

POST-COMM LIMIT FLAG, [8-78](#)

POSTING DATES CURRENT, [7-10](#)

POSTING DATES NEXT, [7-11](#)

POSTING DATES PREVIOUS, [7-10](#)

PREAUTH CHARGEBACKS, [8-50](#)

PRE-AUTH HOLD INCREMENT, [8-23](#)

PRE-AUTH HOLD TIME, [8-23](#)

PRE-COMM FLOOR LIMIT, 8-76
 PRE-COMM LIMIT FLAG, 8-77
 PRIKEY.ACCT-TYP, 10-5
 PRIKEY.RESP-CODE, 10-5
 PRINT LOCATION, 7-16
 PROTOCOL, 8-9
 PROVIDER CODE, 5-5
 PRV NT, 8-39
 PRV NT-DC, 8-40
 PTLF.TXN-SUBTYP-TKN.TXN-SUBTYP, 9-45
 PURCHASE, 8-63

R

RECONCILE MODE, 8-20
 RECONCILIATION ENTITY, 8-52
 RECORD FORMAT
 PTLF key screen 1 retailer/clerk perusal, 9-9
 PTLF key screen 1 terminal ID perusal, 9-8
 PTLF key screen 2 retailer ID/clerk ID perusal, 9-13
 PTLF key screen 2 terminal ID perusal, 9-11
 PTLF summary screen formats, 9-26
 RECORD TYPE
 PTD, 8-6
 RCDF screen 1, 10-4
 RCDF screen 2, 10-7
 REFERRAL PHONE, 7-6
 REGION
 PRDF, 7-3
 PTD, 8-5
 RELEASE #, 8-11
 REPORT SET, 7-17
 RESET MAIL OFFSET FLAG, 8-72
 RESP CODE
 PTLF detail screen formats, 9-42
 PTLF summary screen formats, 9-20, 9-24, 9-28
 RESPONSE
 CAPF screen 1, delinquent table, 4-9
 CAPF screen 1, overlimit table, 4-14
 RESPONSE CODE
 RCDF screen 1, 10-5
 RCDF screen 2, 10-7
 RETAILER
 PTLF detail screen 4—format 1, 9-38
 PTLF detail screen 4—format 2, 9-56
 PTLF detail screen 4—format 3, 9-63
 PTLF key screen 1 retailer/clerk perusal, 9-10
 PTLF key screen 1 terminal ID perusal, 9-9
 PTLF key screen 2 retailer ID/clerk ID perusal, 9-13
 PTLF key screen 2 terminal ID perusal, 9-12
 PTLF summary screen formats, 9-26, 9-31
 RETAILER CUTOVER/BALANCE END, 7-9
 RETAILER CUTOVER/BALANCE START, 7-9
 RETAILER GROUP, 8-5

RETAILER ID
 ADMN, 2-3
 AST, 3-7
 PRDF, 7-2
 PTD, 8-12
 RETAILER ID/CLERK ID PERUSAL, 9-13
 RETAILER NAME, 7-3
 RETAILER PROG, 7-7
 RETAILER TXN PROFILE, 7-18
 RETAILER/CLERK PERUSAL, 9-9
 RETAIN REPORTS, 7-17
 RETL ACCT, 9-58
 RETURN COUNT, 8-24
 RETURN LIMIT, 8-24
 ROUTING GROUP
 CART, 5-3
 PTD, 8-15
 RTTN
 PRDF, 7-4
 PTD, 8-12

S

SALES DRAFTS, 8-49
 SCROLL THRU, 8-71
 SELECT
 RCDF screen 1, 10-4
 SEQ NUM, 9-42
 SEQUENCE NUMBER, 8-25
 SERVICE
 AST, 3-7, 3-11
 PTD, 8-29
 SERVICE ESTABLISHMENT #, 7-6
 SERVICE REPRESENTATIVE, 8-17
 SETTLE TYPE, 9-32
 SETTLEMENT METHOD, 7-7
 SETTLEMENT REPORTING INFORMATION, 7-16
 SHIFT
 PTD screen 3, 8-28
 PTD screen 4, 8-32
 SHIFT NUM
 PTLF detail screen 4—format 1, 9-39
 PTLF detail screen 4—format 2, 9-58
 PTLF detail screen 4—format 3, 9-64
 PTLF summary screen formats, 9-32
 SHIFT NUMBER, 8-26
 SHIFT-DC, 8-33
 SIC CODE
 PRDF, 7-6
 PTLF, 9-39
 SINGLE ADVANCE LIMIT, 4-5
 SINGLE ADVANCE PERCENT, 4-5
 SINGLE ADVANCE RESPONSE, 4-5

SINGLE PURCHASE LIMIT, [4-4](#)
SINGLE PURCHASE PERCENT, [4-4](#)
SINGLE PURCHASE RESPONSE, [4-4](#)
SITE ID
 PTD, [8-6](#)
SOFTWARE RELEASE, [8-21](#)
STATE
 PRDF, [7-4](#)
 PTD, [8-7](#)
 PTLF, [9-48](#)
STATUS FLAG, [8-75](#)
SYMBOLIC NAME, [5-6](#)

T

TABLE
 CAPF screen 1, delinquent table, [4-7](#)
 CAPF screen 1, overlimit table, [4-11](#)
TAX AMOUNT, [9-50](#)
TERM
 PTLF detail screen 4—format 1, [9-39](#)
 PTLF detail screen 4—format 2, [9-57](#)
TERM GROUP, [8-11](#)
TERM SIC CODE, [8-12](#)
TERM STATUS, [8-13](#)
TERM. ADJUSTMENT LIMIT, [8-23](#)
TERMINAL
 PTLF detail screen formats, [9-37](#)
 PTLF key screens, [9-7](#), [9-9](#), [9-12](#)
 PTLF summary screen formats, [9-19](#), [9-23](#), [9-31](#)
TERMINAL ATTENDANCE, [8-79](#)
TERMINAL CUTOVER, [8-26](#)
TERMINAL GROUP
 RCDF screen 1, [10-3](#)
 RCDF screen 2, [10-6](#)
TERMINAL ID, [8-4](#)
TERMINAL ID PERUSAL
 PTLF key screen 1, [9-8](#)
 PTLF key screen 2, [9-11](#)
TERMINAL ID/TIME PERUSAL, [9-6](#)
TERMINAL LIMITS, [8-22](#)
TERMINAL LOCATION, [8-79](#)
TERMINAL OUTPUT CAPABILITIES, [8-82](#)
TERMINAL OWNER, [8-10](#)
TERMINAL PHONE, [8-9](#)
TERMINAL SETTLEMENT, [8-30](#)
TERMINAL TOTALS, [8-25](#)
TERMINAL TYPE, [8-8](#)
TIME
 PTD, [8-42](#)
 PTLF detail screen 4—format 2, [9-58](#)
 PTLF detail screen 4—format 3, [9-63](#), [9-64](#)
 PTLF key screens, [9-8](#)

TIME OFFSET, [8-11](#)
TIME OFST
 PTLF detail screen 4—format 1, [9-40](#)
 PTLF detail screen 4—format 2, [9-58](#)
 PTLF detail screen 4—format 3, [9-64](#)
TIMEOUT RESPONSE TO TERM, [8-71](#)
TOKEN RETRIEVAL OPTION, [8-51](#)
TOP-UP REF NUM, [9-49](#)
TP, [8-63](#)
TRAN, [9-40](#)
TRAN CODE
 CART, [5-4](#)
 PTLF, [9-19](#), [9-24](#), [9-27](#)
TRAN DATE
 PTLF detail screen formats, [9-39](#)
 PTLF summary screen formats, [9-21](#), [9-25](#), [9-28](#),
 [9-32](#)
TRAN LIMIT, [8-64](#)
TRAN TIME
 PTLF detail screen formats, [9-40](#)
 PTLF summary screen formats, [9-21](#), [9-25](#), [9-28](#),
 [9-33](#)
TRANSACTION CONTROL NUMBERS-
 BEGINNING/ENDING, [8-42](#)
TXN SUBTYPE, [9-45](#)
TYPE, [9-59](#)

U

UNDER, [3-12](#)
UNDER A1, [3-14](#)
UNDER A2, [3-14](#)
UNDER DA, [3-15](#)
UNDER P, [3-14](#)
UNSOLICITED MESSAGES, [8-71](#)

V

VALIDATE PIN, [8-57](#)
VIRTUAL PAN, [9-52](#)
VOUCHER, [9-48](#)

Z

ZIP, [9-46](#)

Index by Data Name

A

ACQ-TXN-PRFL
 PRDF, [7-18](#)
 PTDS1-CORE, [8-51](#)
ADJ-FLG, [8-49](#)
ADJ-LMT-AMT
 PTDF, [8-23](#)
 PTDS1-CORE, [8-23](#)
ADJ-LMT-CNT
 PTDF, [8-24](#)
 PTDS1-CORE, [8-24](#)
ADMIN-TXN-PRFL, [2-4](#)
ALLOWED-TRANS, [8-54](#)
ALT-MERCH-ID-TKN.ALT-MERCH-ID, [9-44](#)
AMEX-TKN.FRMT-CDE, [9-44](#)
APPRV-CDE-LGTH
 PTDF, [8-21](#)
 PTDS1-CORE, [8-21](#)
AUTH.ACCT, [9-41](#)
AUTH.ADDR, [9-46](#)
AUTH.ADDR-VRFY-STAT, [9-47](#)
AUTH.AMT-1, [9-20](#), [9-24](#), [9-27](#), [9-43](#)
AUTH.AMT-2, [9-44](#)
AUTH.APPRV-CDE, [9-20](#), [9-25](#), [9-28](#), [9-41](#)
AUTH.AUTH-IND, [9-42](#)
AUTH.AUTHORIZER, [9-42](#)
AUTH.CRD-TYP, [9-38](#)
AUTH.DFT-CAPTURE-FLG, [9-41](#)
AUTH.EXP-DAT, [9-38](#)
AUTH.ID, [3-16](#), [11-5](#)
AUTH.INVOICE-NUM, [9-41](#)
AUTH.ISS-CDE, [9-39](#)
AUTH.NAM, [3-17](#), [11-4](#)
AUTH.ORIG-CRNCY-CDE, [9-28](#)
AUTH.ORIG-INVOICE-NUM, [9-41](#)
AUTH.OVRRDE-FLG, [9-41](#)
AUTH.PIN-IND, [9-40](#)
AUTH.PRE-AUTH-SEQ-NUM, [9-43](#)
AUTH.RESP-CDE, [9-20](#), [9-24](#), [9-28](#), [9-42](#)
AUTH.RESPONDER, [9-20](#), [9-24](#), [9-28](#), [9-42](#)
AUTH.RETL-SIC-CDE, [9-39](#)

AUTH.SEQ-NUM, [9-42](#)
AUTH.TERM-TIM-OFST, [9-40](#)
AUTH.TRAN-CDE, [9-19](#), [9-24](#), [9-27](#), [9-40](#)
AUTH.TRAN-CDE.C, [9-48](#)
AUTH.TRAN-DAT, [9-21](#), [9-25](#), [9-28](#), [9-39](#)
AUTH.TRAN-TIM, [9-21](#), [9-25](#), [9-28](#), [9-40](#)
AUTH.ZIP-CDE, [9-46](#)
AUTH-PARTIAL-AMT, [7-19](#)
AUTH-TBL.CA-FLR-LMT, [3-9](#)
AUTH-TBL.ISS, [3-8](#), [3-11](#)
AUTH-TBL.ISS-DESC, [3-8](#)
AUTH-TBL.MO-FLR-LMT, [3-9](#)
AUTH-TBL.OFF-LMT, [3-10](#)
AUTH-TBL.OVER-LMT.ALT1, [3-13](#)
AUTH-TBL.OVER-LMT.ALT2, [3-13](#)
AUTH-TBL.OVER-LMT.DFLT-ACTION, [3-14](#)
AUTH-TBL.OVER-LMT.PRI, [3-12](#)
AUTH-TBL.PR-FLR-LMT, [3-9](#)
AUTH-TBL.SRV, [3-8](#), [3-11](#)
AUTH-TBL.UNDER-LMT.ALT1, [3-14](#)
AUTH-TBL.UNDER-LMT.ALT2, [3-15](#)
AUTH-TBL.UNDER-LMT.DFLT-ACTION, [3-15](#)
AUTH-TBL.UNDER-LMT.PRI, [3-14](#)

B

BAD-PIN-TRY, [2-4](#)
BAL-FLG
 PTDD1-CORE, [8-41](#)
 PTDF, [8-41](#)
BAL-RTRN-FLG
 PTDS1-CORE, [8-19](#)
BAL-SUPPORT
 PTDF, [8-28](#)
 PTDS1-CORE, [8-28](#)
BATCH.ADJ
 PTDD1-CORE, [8-31](#)
 PTDF, [8-31](#)
BATCH.ADJ-CNT
 PTDD1-CORE, [8-31](#)
 PTDF, [8-31](#)

BATCH.CR
PTDD1-CORE, 8-31
PTDF, 8-31

BATCH.CR-CNT
PTDD1-CORE, 8-31
PTDF, 8-31

BATCH.DB
PTDD1-CORE, 8-31
PTDF, 8-31

BATCH.DB-CNT
PTDD1-CORE, 8-31
PTDF, 8-31

BATCH-CUTOVER-CNT, 8-25

BATCH-DC.ADJ
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-DC.ADJ-CNT
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-DC.CR
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-DC.CR-CNT
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-DC.DB
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-DC.DB-CNT
PTDD1-CORE, 8-32
PTDF, 8-32

BATCH-NUM
PTDD1-CORE, 8-25
PTDF, 8-25

BEG-TRAN-CNTL-NUM, 8-42

BILLING-INFO
PTDD1-CORE, 8-13
PTDF, 8-13

C

CHK-AUTH2-TKN.CONV-FLG, 9-44

CHK-AUTH-TKN.BIRTH-ID-DAT, 9-48

CHK-AUTH-TKN.CHK-ID-NUM, 9-48

CHK-AUTH-TKN.STATE-CDE, 9-48

CHK-MRCHNT-ID, 7-8

CHK-PROVIDER, 7-8

CHK-RTG-GRP, 7-8

CITY-EXT
PTDF, 8-7
PTDS1-CORE, 8-7

CLERK-FLAG
PTDF, 8-44
PTDS1-CORE, 8-44

CLERK-ID
PTDD1-CORE, 8-13
PTDF, 8-13

CLERK-NAME, 2-3

CLERK-TOTS.ADJ-AMT
PTDD1-CORE, 8-45
PTDF, 8-45

CLERK-TOTS.ADJ-CNT
PTDD1-CORE, 8-45
PTDF, 8-45

CLERK-TOTS.CASH-AMT
PTDD1-CORE, 8-46
PTDF, 8-46

CLERK-TOTS.CASH-CNT
PTDD1-CORE, 8-46
PTDF, 8-46

CLERK-TOTS.CHK-AMT
PTDD1-CORE, 8-46
PTDF, 8-46

CLERK-TOTS.CHK-CNT
PTDD1-CORE, 8-46
PTDF, 8-46

CLERK-TOTS.CR-AMT
PTDD1-CORE, 8-45
PTDF, 8-45

CLERK-TOTS.CR-CNT
PTDD1-CORE, 8-45
PTDF, 8-45

CLERK-TOTS.DB-AMT
PTDD1-CORE, 8-44
PTDF, 8-44

CLERK-TOTS.DB-CNT
PTDD1-CORE, 8-44
PTDF, 8-44

CLERK-TTL-FLG, 8-50

CNTRY-CDE
PTDF, 8-8
PTDS1-CORE, 8-8

COMMENTS, 3-7

COMPLETE-TRACK2-DATA
PTDF, 8-21
PTDS1-CORE, 8-21

CR-BAL, 9-20, 9-24, 9-28

CRD-CAPTR-IND, 8-80

CRDHLDR-ACTVT-TERM-IND, 8-80

CRDHLDR-AUTHN-CAP-IND, 8-82

CRD-NUM
ANEG, 6-3
BNEG, 6-3
INEG, 6-3

CRDS-RET, 8-42

CRNCY-CDE
PTDD1-CORE, 8-20
PTDF, 8-20
PTLF, 9-20, 9-24

CTLS-INPUT-CAP-IND, 8-81

CUR-NET.ADJ
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET.ADJ-CNT
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET.CR
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET.CR-CNT
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET.DB
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET.DB-CNT
PTDD1-CORE, 8-37
PTDF, 8-37

CUR-NET-DC.ADJ
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-NET-DC.ADJ-CNT
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-NET-DC.CR
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-NET-DC.CR-CNT
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-NET-DC.DB
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-NET-DC.DB-CNT
PTDD1-CORE, 8-38
PTDF, 8-38

CUR-POST-DAT, 7-10

CUST-BAL-DSPY, 8-19

D

DAILY.ADJ
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY.ADJ-CNT
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY.CR
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY.CR-CNT
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY.DB
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY.DB-CNT
PTDD1-CORE, 8-35
PTDF, 8-35

DAILY-DC.ADJ
PTDD1-CORE, 8-36
PTDF, 8-36

DAILY-DC.ADJ-CNT
PTDD1-CORE, 8-36
PTDF, 8-36

DAILY-DC.CR
PTDD1-CORE, 8-36
PTDF, 8-36

DAILY-DC.CR-CNT
PTDD1-CORE, 8-36
PTDF, 8-36

DAILY-DC.DB
PTDD1-CORE, 8-36
PTDF, 8-36

DAILY-DC.DB-CNT
PTDD1-CORE, 8-36
PTDF, 8-36

DATA-ENCRYPT-TYP
PTDD1-CORE, 8-60

DEACTIVATE-FLG
PTDD1-CORE, 8-13
PTDF, 8-13

DEBIT-SUPPORT-FLG, 7-18

DELINQ-TBL.A.CYCLE-1, 4-8

DELINQ-TBL.A.CYCLE-2, 4-8

DELINQ-TBL.A.CYCLE-3, 4-9

DELINQ-TBL.A.DAYS-DELINQ, 4-7

DELINQ-TBL.A.MONTHS-ACTIVE, 4-8

DELINQ-TBL.A.RESP, 4-9

DELINQ-TBL.B.CYCLE-1, 4-8

DELINQ-TBL.B.CYCLE-2, 4-8

DELINQ-TBL.B.CYCLE-3, 4-9

DELINQ-TBL.B.DAYS-DELINQ, 4-7

DELINQ-TBL.B.MONTHS-ACTIVE, 4-8

DELINQ-TBL.B.RESP, 4-9

DELINQ-TBL.C.CYCLE-1, 4-8

DELINQ-TBL.C.CYCLE-2, 4-8

DELINQ-TBL.C.CYCLE-3, 4-9

DELINQ-TBL.C.DAYS-DELINQ, 4-7

DELINQ-TBL.C.MONTHS-ACTIVE, 4-8

DELINQ-TBL.C.RESP, 4-9

DESCR, 10-8

DFLT-CHK-ID
PTDF, 8-15
PTDS1-CORE, 8-15

DFLT-TC
PTDF, 8-54
PTDS1-CORE, 8-48
DH-PRO-NAM
PTDD1, 8-14
PTDF, 8-14
DPC-NUM, 8-52
DUAL-SITE-IND
PTDD1-CORE, 8-15

E

EBT-VOUCHER-NUM-TKN.VOUCHER-NUM, 9-48
EMV-DELAYED-AUTH-SPPT, 7-19
ENCR-PIN.ENCR-KEYS.M-KEY
PTDD1-CORE, 8-57
PTDF, 8-57
ENCR-PIN.PIN-ENCRYPT-TYP
PTDD1-CORE, 8-56
PTDF, 8-56
ENCR-PIN.PIN-VAL-TERM
PTDD1-CORE, 8-57
PTDF, 8-57
END-TRAN-CNTL-NUM, 8-42
ENHNC-PRE-AUTH-FLG, 8-50

F

FIID
ADMN, 2-3
CART, 5-4

H

HEAD.CRD.CARD.CRD-NUM, 9-6, 9-19, 9-23, 9-27,
9-37, 9-38, 9-62
HEAD.CRD.CARD.MBR-NUM, 9-6, 9-19, 9-37, 9-38
HEAD.CRD.FIID, 9-5, 9-19, 9-62
HEAD.CRD.LN, 9-6, 9-19, 9-62
HEAD.RETL.BATCH-NUM, 9-31, 9-39, 9-58, 9-63
HEAD.RETL.KY.RDFKEY.ID, 9-63
HEAD.RETL.SHIFT-NUM, 9-32, 9-39, 9-58, 9-64
HEAD.RETL.TERM-ID, 9-19, 9-37, 9-39, 9-62
HEAD.TERM.FIID, 9-7, 9-23, 9-37, 9-56
HEAD.TERM.LN, 9-7, 9-23, 9-37, 9-56
HEAD.TERM.TERM-ID, 9-7, 9-23, 9-57
HEAD.TERM.TIM, 9-8
HEAD.TKEY.REC-FRMT, 9-8
HEAD.TKEY.RKEY.CLERK-ID, 9-9, 9-10, 9-12,
9-14, 9-27, 9-31, 9-38, 9-57
HEAD.TKEY.RKEY.REC-FRMT, 9-10, 9-12, 9-13,
9-22, 9-26, 9-30, 9-36, 9-56, 9-62
HEAD.TKEY.RKEY.RETAILER-ID, 9-9, 9-10, 9-12,
9-13, 9-26, 9-31, 9-38, 9-56

HEAD.TKEY.TERM-ID, 9-9, 9-12, 9-23, 9-57, 9-62

I

INST-ID-NUM
CART, 5-4

K

KEYD-GRP
PTDS1-CORE, 8-58

L

LANGUAGE-IND
PTDF, 8-14
PTDS1-CORE, 8-14
LAST-RESET-DATE, 2-3
LAST-SETL-DATPOST-DAT
PTDD1-CORE, 8-42
PTDF, 8-42
LAST-SETL-TIM
PTDD1-CORE, 8-42
PTDF, 8-42
LAST-USED-DATE, 2-4
LOAD-FIL-NAME
PTDF, 8-16
PTDS1-CORE, 8-16
LOG-RT-CDE
PTDF, 8-18
PTDS1-CORE, 8-18
LOG-TOTALS
PTDD1-CORE, 8-28, 8-29
PTDF, 8-28, 8-29

M

MAC-DATA.ENCR-KEYS.MAS-KEY
PTDD1-CORE, 8-59
PTDF, 8-59
MAC-DATA.MAC-ENCRYPT-TYP
PTDD1-CORE, 8-58
PTDF, 8-58
MAIL-DATA.MAIL-MSG.INBOUND.CATEGORY-
NAM
PTDD1-CORE, 8-74
PTDF, 8-74
MAIL-DATA.MAIL-MSG.INBOUND.COMPL-CDE
PTDD1-CORE, 8-73
PTDF, 8-73
MAIL-DATA.MAIL-MSG.INBOUND.DELIVERY-
MDE
PTDD1-CORE, 8-73
PTDF, 8-73
MAIL-DATA.MAIL-MSG.INBOUND.STATUS-FLG
PTDD1-CORE, 8-75
PTDF, 8-75

- MAIL-DATA.MAIL-MSG.INBOUND.TXT-ID.MSG-DAT
PTDD1-CORE, [8-74](#)
PTDF, [8-74](#)
- MAIL-DATA.MAIL-MSG.INBOUND.TXT-ID.MSG-ID
PTDD1-CORE, [8-74](#)
PTDF, [8-74](#)
- MAIL-DATA.MAIL-MSG.OUTBOUND.CATEGORY-NAM
PTDD1-CORE, [8-74](#)
PTDF, [8-74](#)
- MAIL-DATA.MAIL-MSG.OUTBOUND.COMPL-CDE
PTDD1-CORE, [8-73](#)
PTDF, [8-73](#)
- MAIL-DATA.MAIL-MSG.OUTBOUND.DELIVERY-MDE
PTDD1-CORE, [8-73](#)
PTDF, [8-73](#)
- MAIL-DATA.MAIL-MSG.OUTBOUND.TXT-ID.MSG-DAT
PTDD1-CORE, [8-74](#)
PTDF, [8-74](#)
- MAIL-DATA.MAIL-MSG.OUTBOUND.TXT-ID.MSG-ID
PTDD1-CORE, [8-74](#)
PTDF, [8-74](#)
- MAIL-DATA.MAIL-PRO-NAM
PTDD1-CORE, [8-70](#)
PTDF, [8-70](#)
- MAIL-DATA.OPTION-FLAGS.OFST-RESET
PTDD1-CORE, [8-73](#)
PTDF, [8-73](#)
- MAIL-DATA.OPTION-FLAGS.POS-NEG-CONFIRMATIONS
PTDD1-CORE, [8-71](#)
PTDF, [8-71](#)
- MAIL-DATA.OPTION-FLAGS.SCROLL-THRU
PTDD1-CORE, [8-71](#)
PTDF, [8-71](#)
- MAIL-DATA.OPTION-FLAGS.TERM-COMPL-STORED-MSG
PTDD1-CORE, [8-72](#)
PTDF, [8-72](#)
- MAIL-DATA.OPTION-FLAGS.TERM-COMPL-UNSOLICITED-MSG
PTDD1-CORE, [8-72](#)
PTDF, [8-72](#)
- MAIL-DATA.OPTION-FLAGS.TIMOUT-RESP-TO-TERM
PTDD1-CORE, [8-71](#)
PTDF, [8-71](#)
- MAIL-DATA.OPTION-FLAGS.UNSOLICITED-MSG
PTDD1-CORE, [8-72](#)
PTDF, [8-72](#)
- MAIL-PO-SIC-CDE, [7-6](#)
PTDF, [8-12](#)
PTDS1-CORE, [8-12](#)
- MAS-KEY-CHK-VALUE
PTDD1-CORE, [8-59](#)
PTDF, [8-59](#)
- MAX-PIN-TRY, [2-5](#)
- MERCH-ACTIVITY-RPT.PERIODIC-FILE-RET, [7-17](#)
- MERCH-ACTIVITY-RPT.PRNT-LOC, [7-17](#)
- MERCH-ACTIVITY-RPT.RPT-CREATION-FLG, [7-17](#)
- M-KEY-CHK-VALUE
PTDD1-CORE, [8-57](#)
PTDF, [8-57](#)
- MULT-CRNCY-TTL
PTDF, [8-20](#)
PTDS1-CORE, [8-20](#)
- MULT-LN-TKN.SITE-IND, [9-45](#)
- MULT-THREAD-SPDH.REC-TYP
PTDD1, [8-7](#)
- MULT-THREAD-SPDH.SITE-ID
PTDD1, [8-6](#)
- ## N
- NUM-BATCHES
PTDD1-CORE, [8-25](#)
PTDF, [8-25](#)
- NUM-SHIFTS
PTDD1-CORE, [8-26](#)
PTDF, [8-26](#)
- NUM-USES-RESP, [4-3](#)
- NXT-POST-DAT, [7-11](#)
- ## O
- OVLIM-TBL.A.CYCLE-1, [4-13](#)
- OVLIM-TBL.A.CYCLE-2, [4-13](#)
- OVLIM-TBL.A.CYCLE-3, [4-14](#)
- OVLIM-TBL.A.MONTHS-ACTIVE, [4-12](#)
- OVLIM-TBL.A.PERCENT-OVR, [4-12](#)
- OVLIM-TBL.A.RESP, [4-14](#)
- OVLIM-TBL.B.CYCLE-1, [4-13](#)
- OVLIM-TBL.B.CYCLE-2, [4-13](#)
- OVLIM-TBL.B.CYCLE-3, [4-14](#)
- OVLIM-TBL.B.MONTHS-ACTIVE, [4-12](#)
- OVLIM-TBL.B.PERCENT-OVR, [4-12](#)
- OVLIM-TBL.B.RESP, [4-14](#)
- OVLIM-TBL.C.CYCLE-1, [4-13](#)
- OVLIM-TBL.C.CYCLE-2, [4-13](#)
- OVLIM-TBL.C.CYCLE-3, [4-14](#)
- OVLIM-TBL.C.MONTHS-ACTIVE, [4-12](#)
- OVLIM-TBL.C.PERCENT-OVR, [4-12](#)

OVRLIM-TBL.C.RESP, [4-14](#)

P

PIN-OFST, [2-3](#)

PIN-PAD-CHAR
PTDD1-CORE, [8-56](#)
PTDF, [8-56](#)

POSTAL-CDE
PTDF, [8-8](#)
PTDS1-CORE, [8-8](#)

POST-COMM-FLR-LMT
PTDF, [8-77](#)
PTDS1-CORE, [8-77](#)

POST-COMM-LMT-FLG
PTDF, [8-79](#)
PTDS1-CORE, [8-79](#), [8-80](#), [8-81](#), [8-82](#)

POST-DAT
PTDD1-CORE, [8-42](#)
PTDF, [8-42](#)

PRE-AUTH-CHRGBCK-FLG, [8-51](#)

PRE-AUTH-DFT-AMT
PTDF, [8-22](#)
PTDS1-CORE, [8-22](#)

PRE-AUTH-HLD
PTDF, [8-23](#)
PTDS1-CORE, [8-23](#)

PRE-AUTH-LESS-AMT-FLG, [8-50](#)

PRE-COMM-FLR-LMT
PTDF, [8-77](#)
PTDS1-CORE, [8-77](#)

PRE-COMM-LMT-FLG
PTDF, [8-77](#)
PTDS1-CORE, [8-77](#)

PRE-NET.ADJ
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET.ADJ-CNT
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET.CR
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET.CR-CNT
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET.DB
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET.DB-CNT
PTDD1-CORE, [8-39](#)
PTDF, [8-39](#)

PRE-NET-DC.ADJ
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-NET-DC.ADJ-CNT
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-NET-DC.CR
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-NET-DC.CR-CNT
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-NET-DC.DB
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-NET-DC.DB-CNT
PTDD1-CORE, [8-40](#)
PTDF, [8-40](#)

PRE-POST-DAT, [7-10](#)

PRIKEY.ACCT-TYP, [10-7](#)

PRIKEY.CARD-NUM, [2-2](#)

PRI-KEY.CRD-TYP, [4-3](#)

PRI-KEY.FIID
AST, [3-6](#)
CAPF, [4-2](#)

PRIKEY.FIID, [10-4](#), [10-6](#)

PRI-KEY.ISS, [4-3](#)

PRIKEY.LANG-IND, [10-4](#), [10-7](#)

PRIKEY.REC-TYP, [10-4](#), [10-7](#)

PRIKEY.RESP-CDE, [10-7](#)

PRI-KEY.RETAILER-ID, [3-7](#)

PRIKEY.RETAILER-ID, [2-3](#)

PRIKEY.TERM-GRP, [10-3](#), [10-6](#)

PS50-TKN.ERR-FLG, [9-40](#)

PSEUDO-CRD-NUM-TKN.EXP-DAT, [9-53](#)

PSEUDO-CRD-NUM-TKN.PSEUDO-CRD-
NUM, [9-52](#)

PTLF.TXN-SUBTYP-TKN.ACQ-PROC-CDE, [9-45](#)

PTLF.TXN-SUBTYP-TKN.ISS-PROC-CDE, [9-45](#)

R

RCNCL-ENT, [8-53](#)

RECONCILE-MODE, [8-20](#)

REL-NUM
PTDF, [8-11](#)
PTDS1-CORE, [8-11](#)

RETAILER.ACCT, [7-5](#)

RETAILER.ACH-COMPANY-ID, [7-6](#)

RETAILER.ADDR, [7-3](#)

RETAILER.ADDR-EXT, [7-3](#)

RETAILER.AFT-HRS-PHONE, [7-5](#)

RETAILER.CITY, [7-3](#)

RETAILER.CNTRY, [7-4](#)

RETAILER.CNTY, [7-4](#)

RETAILER.NAME, 7-3
 RETAILER.PHONE, 7-5
 RETAILER.POSTAL-CDE, 7-4
 RETAILER.RFRL-PHONE, 7-7
 RETAILER.RTTN, 7-5
 RETAILER.SIC-CDE, 7-6
 RETAILER.SRV-EST-NUM, 7-6
 RETAILER.ST, 7-4
 RETAILER-BAL-AND-CUTVR-END, 7-10
 RETAILER-BAL-AND-CUTVR-STRT, 7-9
 RETAILER-PROG, 7-7
 RETURN-LMT-AMT
 PTDF, 8-24
 PTDS1-CORE, 8-24
 RETURN-LMT-CNT
 PTDF, 8-24
 PTDS1-CORE, 8-24
 RKEY.FIID, 7-2
 RKEY.GRP, 7-3
 RKEY.REGN, 7-3
 RKEY.RETAILER-ID, 7-2
 RTE-GRP
 PTDF, 8-15
 PTDS1-CORE, 8-15
 RTE-TBL.AUTH-LVL, 5-8
 RTE-TBL.AUTH-TYP, 5-7
 RTE-TBL.CHK-ID-TYP, 5-5
 RTE-TBL.CHK-PROVIDER, 5-6
 RTE-TBL.CHK-SPF, 5-8
 RTE-TBL.DPC, 5-6
 RTE-TBL.FIID, 5-6
 RTE-TBL.SYM-NAME, 5-6
 RTE-TBL.TRAN-CDE, 5-4
 RTG-GRP, 5-3
 RTL-R-TXN-PRFL, 7-18
 RTTN
 PTDD1-CORE, 8-12
 PTDF, 8-12

S

SALES-DFT-FLG, 8-49
 SEQ-NUM
 PTDD1-CORE, 8-25
 PTDF, 8-25
 SETL, 7-7
 SET-REC.SET-REC1.BAL-FLG, 9-64
 SET-REC.SET-REC1.SETL-TYP, 9-32
 SET-REC.SET-REC1.TERM-TIM-OFST, 9-64
 SET-REC.SET-REC1.TRAN-DAT, 9-32, 9-63
 SET-REC.SET-REC1.TRAN-TIM, 9-33, 9-63, 9-64

SET-REC.SET-REC2.STL.DC-TOT.ADJ, 9-66
 SET-REC.SET-REC2.STL.DC-TOT.CR, 9-66
 SET-REC.SET-REC2.STL.DC-TOT.CR-CNT, 9-66
 SET-REC.SET-REC2.STL.DC-TOT.DB, 9-66
 SET-REC.SET-REC2.STL.DC-TOT.DB-CNT, 9-66
 SET-REC.SET-REC2.STL.TOT.ADJ, 9-65
 SET-REC.SET-REC2.STL.TOT.ADJ-CNT, 9-65
 SET-REC.SET-REC2.STL.TOT.CR, 9-65
 SET-REC.SET-REC2.STL.TOT.CR-CNT, 9-65
 SET-REC.SET-REC2.STL.TOT.DB, 9-64
 SET-REC.SET-REC2.STL.TOT.DB-CNT, 9-65
 SFTWR-REL
 PTDF, 8-21
 PTDS1-CORE, 8-21
 SGL-ADV.ADV-RESP, 4-5
 SGL-ADV.LMT, 4-5
 SGL-ADV.PERCENT, 4-5
 SGL-PUR.LMT, 4-4
 SGL-PUR.PERCENT, 4-4
 SGL-PUR.PUR-RESP, 4-4
 SHIFT.ADJ
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT.ADJ-CNT
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT.CR
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT.CR-CNT
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT.DB
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT.DB-CNT
 PTDD1-CORE, 8-33
 PTDF, 8-33
 SHIFT-DC.ADJ
 PTDD1-CORE, 8-34
 PTDF, 8-34
 SHIFT-DC.ADJ-CNT
 PTDD1-CORE, 8-34
 PTDF, 8-34
 SHIFT-DC.CR
 PTDD1-CORE, 8-34
 PTDF, 8-34
 SHIFT-DC.CR-CNT
 PTDD1-CORE, 8-34
 PTDF, 8-34
 SHIFT-DC.DB
 PTDD1-CORE, 8-34
 PTDF, 8-34

SHIFT-DC.DB-CNT
PTDD1-CORE, [8-34](#)
PTDF, [8-34](#)

SHIFT-NUM
PTDD1-CORE, [8-26](#)
PTDF, [8-26](#)

SRV.ADJ
PTDD1-CORE, [8-68](#)
PTDF, [8-68](#)

SRV.ADJ-CNT
PTDD1-CORE, [8-67](#)
PTDF, [8-67](#)

SRV.CA-FLR-LMT
PTDD1-CORE, [8-63](#)
PTDF, [8-63](#)

SRV.CR
PTDD1-CORE, [8-67](#)
PTDF, [8-67](#)

SRV.CR-CNT
PTDD1-CORE, [8-67](#)
PTDF, [8-67](#)

SRV.DB
PTDD1-CORE, [8-66](#)
PTDF, [8-66](#)

SRV.DB-CNT
PTDD1-CORE, [8-66](#)
PTDF, [8-66](#)

SRV.ELEC-FOLLOWUP
PTDD1-CORE, [8-62](#)
PTDF, [8-62](#)

SRV.MO-FLR-LMT
PTDD1-CORE, [8-64](#)
PTDF, [8-64](#)

SRV.NP-FLR-LMT
PTDD1-CORE, [8-63](#)
PTDF, [8-63](#)

SRV.TRAN-LMT
PTDD1-CORE, [8-64](#)
PTDF, [8-64](#)

SRV.TRAN-PROFILE
PTDD1-CORE, [8-63](#)
PTDF, [8-63](#)

SRV.TYP
PTDD1-CORE, [8-62](#), [8-66](#)
PTDF, [8-62](#), [8-66](#)

SRVCS-1.SET-REC1.AUTH-CRNCY-CDE, [9-57](#)

SRVCS-1.SET-REC1.BAL-FLG, [9-59](#)

SRVCS-1.SET-REC1.RETL-ACCT, [9-58](#)

SRVCS-1.SET-REC1.SETL-TYP, [9-32](#)

SRVCS-1.SET-REC1.TERM-TIM-OFST, [9-58](#)

SRVCS-1.SET-REC1.TRAN-DAT, [9-32](#), [9-57](#)

SRVCS-1.SET-REC1.TRAN-TIM, [9-33](#), [9-58](#)

SRVCS-1.SET-REC3.SRV.ADJ, [9-60](#)

SRVCS-1.SET-REC3.SRV.ADJ-CNT, [9-60](#)

SRVCS-1.SET-REC3.SRV.CR-CNT, [9-60](#)

SRVCS-1.SET-REC3.SRV.DB, [9-59](#)

SRVCS-1.SET-REC3.SRV.DB-CNT, [9-59](#)

SRVCS-1.SET-REC3.SRV.TYP, [9-59](#)

SRVCS-2.SET-REC1.AUTH-CRNCY-CDE, [9-57](#)

SRVCS-2.SET-REC1.BAL-FLG, [9-59](#)

SRVCS-2.SET-REC1.RETL-ACCT, [9-58](#)

SRVCS-2.SET-REC1.SETL-TYP, [9-32](#)

SRVCS-2.SET-REC1.TERM-TIM-OFST, [9-58](#)

SRVCS-2.SET-REC1.TRAN-DAT, [9-32](#), [9-57](#)

SRVCS-2.SET-REC1.TRAN-TIM, [9-33](#), [9-58](#)

SRVCS-2.SET-REC4.SRV.ADJ, [9-60](#)

SRVCS-2.SET-REC4.SRV.ADJ-CNT, [9-60](#)

SRVCS-2.SET-REC4.SRV.CR, [9-60](#)

SRVCS-2.SET-REC4.SRV.CR-CNT, [9-60](#)

SRVCS-2.SET-REC4.SRV.DB, [9-59](#)

SRVCS-2.SET-REC4.SRV.DB-CNT, [9-59](#)

SRVCS-2.SET-REC4.SRV.TYP, [9-59](#)

SRV-EST-NUM-CHK, [7-19](#)

SRV-INFO.SRV-INFO-DATA, [7-13](#), [7-14](#), [7-15](#)

SRV-REP.ADDR
PTDF, [8-17](#)
PTDS1-CORE, [8-17](#)

SRV-REP.CITY-ST
PTDF, [8-17](#)
PTDS1-CORE, [8-17](#)

SRV-REP.CNTRY
PTDF, [8-18](#)
PTDS1-CORE, [8-18](#)

SRV-REP.NAM
PTDF, [8-17](#)
PTDS1-CORE, [8-17](#)

SRV-REP.PHONE
PTDF, [8-18](#)
PTDS1-CORE, [8-18](#)

T

TERM-ATTEND-IND, [8-79](#)

TERM-CITY-ST.CITY
PTDF, [8-7](#)
PTDS1-CORE, [8-7](#)

TERM-CITY-ST.ST
PTDF, [8-7](#)
PTDS1-CORE, [8-7](#)

TERM-CUTOVER-TC
PTDD1-CORE, [8-26](#)
PTDF, [8-26](#)

TERM-GRP
PTDD1-CORE, [8-11](#)
PTDF, [8-11](#)

TERM-ID
 PTDD1, [8-4](#)
 PTDF, [8-4](#)
 PTDS1, [8-4](#)
TERM-INPUT-CAP-IND, [8-81](#)
TERM-LOC-IND, [8-79](#)
TERM-NAM-LOC
 PTDF, [8-7](#)
 PTDS1-CORE, [8-7](#)
TERM-OUTPUT-CAP-IND, [8-82](#)
TERM-OWNER.FIID
 PTDD1, [8-5](#)
 PTDF, [8-5](#)
TERM-OWNER.LN
 PTDD1, [8-5](#)
 PTDF, [8-5](#)
TERM-OWNER.RETAILER-GRP
 PTDD1, [8-5](#)
 PTDF, [8-5](#)
TERM-OWNER.RETAILER-ID
 PTDD1, [8-12](#)
 PTDF, [8-12](#)
TERM-OWNER.RETAILER-REGN
 PTDD1, [8-5](#)
 PTDF, [8-5](#)
TERM-OWNER-NAM
 PTDF, [8-10](#)
 PTDS1-CORE, [8-10](#)
TERM-PHONE.BAUD-RATE
 PTDF, [8-10](#)
 PTDS1-CORE, [8-10](#)
TERM-PHONE.NUM
 PTDF, [8-9](#)
 PTDS1-CORE, [8-9](#)
TERM-PROTO
 PTDF, [8-9](#)
 PTDS1-CORE, [8-9](#)
TERM-SIC-CDE
 PTDF, [8-12](#)
 PTDS1-CORE, [8-12](#)
TERM-TYP
 PTDD1-CORE, [8-9](#)
 PTDF, [8-9](#)
 PTDS1-CORE, [8-9](#)
TIM-OFST
 PTDD1-CORE, [8-11](#)
 PTDF, [8-11](#)
TKN-RETRV-OPT, [8-52](#)
TLF.PRE.PAY-RESP-TKN.TAX-AMT, [9-50](#)
TLF.PRE.PAY-TOP-UP-TKN.APPRV-CDE, [9-49](#)
TLF.PRE.PAY-TOP-UP-TKN.PHN-NUM, [9-49](#)
TLF.PRE.PAY-TOP-UP-TKN.REF, [9-49](#)
TLF.PRE.PAY-TOP-UP-TKN.RESP-CDE, [9-50](#)

ACI Worldwide, Inc.