



BASE24-billpayTM

Tables Maintenance Manual

© 2000 by ACI Worldwide Inc. All rights reserved.

All information contained in this document is confidential and proprietary to ACI Worldwide Inc. This material is a trade secret and its confidentiality is strictly maintained. Use of any copyright notice does not imply unrestricted or public access to these materials. No part of this document may be photocopied, electronically transferred, modified, or reproduced in any manner without the prior written consent of ACI Worldwide Inc.

BASE24, BASE24 Remote Banking, BASE24-billpay, and BASE24-telebanking are trademarks or registered trademarks of ACI Worldwide Inc., Transaction Systems Architects, Inc., or their subsidiaries.

Other companies' trademarks, service marks, or registered trademarks and service marks are trademarks, service marks, or registered trademarks and service marks of their respective companies.

Print Record

10/2000, Version 3 (Reissue)

11/1998, Version 2 (Update)

04/97, Version 1 (New)

Contents

Preface	vii
Conventions Used in this Manual	xiii
Section 1	
Introduction	1-1
BASE24-billpay Tables	1-2
Table Access	1-3
SQL Table Row Access	1-4
Function Keys	1-6
Effective Date Ranges	1-7
Assigns and Params	1-8
OMF Assign	1-8
BP-DATE-FORMAT Param	1-8
LGNT-COUNTRY-ABBR Param	1-9
OMF-AUDIT Param	1-9
Section 2	
Bank Branch Table (BKBR)	2-1
Screen 1	2-3
Section 3	
Bank Notice Table (BKNT)	3-1
Screen 1	3-2
Section 4	
Bank Transaction Advice Table (BKAV)	4-1
Screen 1	4-2

Section 5

Cleanup Configuration Table (CLPT)	5-1
Archive Program	5-2
Cleanup Program	5-3
Screen 1 Function Keys	5-6
Screen 1	5-7

Section 6

Customer Billpay Table (CBPT)	6-1
Screen 1	6-2

Section 7

Customer Vendor Table (CVND)	7-1
Screen 1 Function Keys	7-2
Screen 1	7-3

Section 8

History Table (HIST)	8-1
Screen 1	8-2
Screen 2	8-8

Section 9

Response Text Table (RTXT)	9-1
Screen 1	9-2

Section 10

Retry Table (RTRY)	10-1
Screen 1	10-2

Section 11

Service Provider Table (SVPT)	11-1
Screen 1	11-2

Section 12

Vendor Table (VNDR)	12-1
Screen 1 Function Keys	12-3
Screen 1.....	12-4
Screen 2 Function Keys	12-10
Screen 2.....	12-11
Screen 3.....	12-15

Section 13

Vendor Branch Table (VNDB)	13-1
Screen 1 Function Keys	13-3
Screen 1.....	13-4
Screen 2.....	13-9

Section 14

Vendor Budget Category Table (VBUD)	14-1
Screen 1.....	14-2

Section 15

Vendor Mask Table (VNDM)	15-1
Screen 1.....	15-3

Index	Index-1
--------------------	----------------

ACI Worldwide Inc.

Preface

This manual describes the BASE24 CRT screens that access the BASE24-billpay tables. BASE24-billpay CRT screens are accessed from the BILLPAY entry on the Virtual Menu and consist of the screens that are used exclusively with the BASE24-billpay product.

The information in this manual enables users to enter and update rows in the BASE24-billpay tables. Each screen description in this manual includes an illustration of the screen with default values displayed, an explanation of each function key that operates differently from the standard, and the following information about each field on the screen:

- Purpose
- Codes that can be used, including default values
- Length
- Associated table column name

Audience

ACI prepared this publication for distribution to personnel responsible for updating and maintaining the BASE24-billpay database.

Prerequisites

Persons using this manual should be familiar with the ***BASE24 CRT Access Manual*** before reading this manual. The ***BASE24 CRT Access Manual*** includes information about logging on to the BASE24 CRT access system, accessing the appropriate screens, and using function keys.

Additional Documentation

The BASE24 documentation set is arranged so that each BASE24 manual presents a topic or group of related topics in detail. When one BASE24 manual presents a topic that has already been covered in detail in another BASE24 manual, the topic is summarized and the reader is directed to the other manual for additional information. Information has been arranged in this manner to be more efficient for readers who do not need the additional detail and at the same time provide the source for readers who require the additional information. This manual contains references to the following BASE24 publications:

- The ***BASE24 Base Files Maintenance Manual*** describes the screens used to maintain the files and tables that are shared among several BASE24 products. The Bank Table also is presented in this manual.
- The ***BASE24 Core Files and Tables Maintenance Manual*** describes the screens used to maintain the files and tables that are shared among products that use object-oriented design. Customer-related tables used by the BASE24-billpay product are presented in this manual.
- The ***BASE24 CRT Access Manual*** includes information about logging on to the BASE24 CRT access system, accessing the appropriate screens, and using function keys.
- The ***BASE24-billpay Billing Application Manual*** contains billing application screen formats and field descriptions.
- The ***BASE24 Remote Banking Customer Service Support Manual*** contains customer service representative (CSR) screen formats and field descriptions.
- The ***BASE24 Remote Banking Transaction Processing Manual*** contains transaction processing illustrations and action code descriptions.
- The ***BASE24 Remote Banking End-of-Period Processing and Reporting Manual*** contains information about the use of the Archive and Cleanup programs.

In addition to the above BASE24 publications, the ***BASE24-billpay Tables Maintenance Manual*** contains references to the following International Organization for Standardization (ISO) and American National Standards Institute (ANSI) publications:

- The 1988 ANSI X3.31 standard, ***Structure for the Identification of the Counties and County Equivalents of the United States and its Outlying and Associated Areas for Information Interchange***, contains the standards for U.S. county and county equivalent codes used on BASE24 file and table maintenance screens.
- The 1988 ANSI X3.38 standard, ***Identification of the States, the District of Columbia, and the Outlying and Associated Areas of the United States for Information Interchange***, contains the standards for U.S. state codes used on BASE24 file and table maintenance screens.
- The 1993 ISO 3166 standard, ***Codes for the Representation of Names of Countries***, contains the country codes used on BASE24 file and table maintenance screens.
- The 1990 ISO 4217 standard, ***Codes for the Representation of Currencies and Funds***, contains currency codes used on BASE24 file and table maintenance screens.
- The 1993 ISO 8583 standard, ***Financial Transaction Card Originated Messages—Interchange Message Specification***, contains the codes used on BASE24 file and table maintenance screens for message class, message reason, and point of service.

Software

This manual documents standard processing for BASE24-billpay release 1.3.

BASE24-telebanking release 1.3 is required when BASE24-billpay release 1.3 is installed. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for an explanation of how the BASE24-telebanking and BASE24-billpay products work together.

Customer-specific code modifications (that is, CSMs) may result in processing that differs from the material presented in this manual. The customer is responsible for identifying and noting these changes.

Manual Summary

The following is a summary of the contents of this manual.

“Conventions Used in this Manual” follows this preface and describes notation and documentation conventions necessary to understand the information in the manual.

Section 1, “Introduction,” identifies the tables specific to BASE24-billpay, describes how Structured Query Language (SQL) rows are accessed, and presents options for date field formats and effective date ranges.

Section 2, “Bank Branch Table (BKBR),” describes the screen used to maintain the BKBR. The BKBR contains location information for each bank branch.

Section 3, “Bank Notice Table (BKNT),” describes the screen used to maintain the BKNT. The BKNT identifies action codes for which customer notices must be generated.

Section 4, “Bank Transaction Advice Table (BKAV),” describes the screen used to maintain the BKAV. The BKAV identifies transactions that should be logged to the ITS Transaction Log File (ITLF). The ITLF is the log file used by products that use object-oriented design, such as the BASE24-telebanking product.

Section 5, “Cleanup Configuration Table (CLPT),” describes the screen used to maintain the CLPT. The CLPT contains configuration information used by the Cleanup and Archive programs.

Section 6, “Customer Billpay Table (CBPT),” describes the screen used to display information from the CBPT. The CBPT contains the transaction reference number, miscellaneous billing, and vendor information for each customer.

Section 7, “Customer Vendor Table (CVND),” describes the screen used to maintain the CVND. The CVND contains information that establishes the relationship between a customer and a vendor.

Section 8, “History Table (HIST),” describes the screens used to display information from the HIST. The HIST contains rows for BASE24-billpay completed transactions, failed transactions, and log-only nonfinancial transactions. The HIST does not contain BASE24-telebanking transactions.

Section 9, “Response Text Table (RTXT),” describes the screen used to maintain the RTXT. The RTXT contains text for internal and external messages associated with action codes. Internal messages appear on customer service representative (CSR) and table maintenance screens. External messages appear on reports and customer notices.

Section 10, “Retry Table (RTRY),” describes the screen used to maintain the RTRY. The RTRY contains parameters used by the Scheduled Transaction Initiator process for retrying a transaction when a particular action code is returned.

Section 11, “Service Provider Table (SVPT),” describes the screen used to maintain and display information in the SVPT. The SVPT contains last customer ID information for FIIDs that do not use preloaded customer data.

Section 12, “Vendor Table (VNDR),” describes the screens used to maintain the VNDR. The VNDR defines each vendor.

Section 13, “Vendor Branch Table (VNDB),” describes the screen used to maintain the VNDB. The VNDB contains location and account mask information for each vendor branch.

Section 14, “Vendor Budget Category Table (VBUD),” describes the screen used to maintain the VBUD. The VBUD contains a code and description for each budget category that can be assigned to vendors.

Section 15, “Vendor Mask Table (VNDM),” describes the screen used to maintain the VNDM. The VNDM contains the parameters used for defining the edit checks performed on the account number a customer has with a vendor. These parameters are also known as masks.

Readers can use the index by field name to locate information about a particular screen field and the index by column name to locate information about a particular column from a table.

Publication Identification

Two entries appearing at the bottom of each page uniquely identify this BASE24 publication. The publication number (for example, TB-AE000-03 for the *BASE24-billpay Tables Maintenance Manual*) appears on every page to assist readers in applying updates to the appropriate manual. The publication date (for example, 10/2000 for October, 2000) identifies the last time material on a particular page has been revised. This date can be used to verify that the reader has the most current information and is particularly helpful when dealing with HELP24 to answer operating questions.

The print record, located on the page immediately following the title page, is also helpful when verifying that a manual contains the most current information. An entry is added to the print record each time a *product* publication is modified in any way. Each print record entry includes the date of the change, a unique version number, and the type of change (new, update, reissue, or preliminary). Version 1 is assigned to a *new* manual. Later versions can be updates or reissues, depending on the changes being made. An *update* typically involves changes on a small number of pages throughout the manual. A *reissue* occurs when all pages of the manual are replaced because changes affect a large number of pages. A manual is identified as *preliminary* when it is released to customers on a limited basis, but it has not yet reached final form.

Conventions Used in this Manual

This section explains how Structured Query Language (SQL) table maintenance field descriptions are documented in this manual.

Field Descriptions

Each field appearing on a file maintenance screen is listed by name and then described. Field descriptions briefly summarize the contents, purpose, and permissible values, as shown in the following example taken from the Bank Notice Table (BKNT).

Example

FIID — The financial institution identifier. The value in this field links the notice in this row to the financial institution and must match an FIID that already exists in the Bank Table (BANK).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: BKNT.FIID

Explanation

Each field description is completed by one or more of the following items of information:

Example	Demonstrates a possible entry for the field to further clarify the value or values that can be entered.
---------	---

Field Length	Specifies the size of the field and the type of characters that can be entered. This length refers to the field and valid values for the table maintenance screen, not the SQL column in the table layout. Possible values are alphabetic, alphanumeric, hexadecimal, and numeric. The term <i>alphanumeric</i> includes all alphabetic, numeric, and special characters that can be entered from a keyboard without using a control sequence. The term <i>hexadecimal</i> includes all numbers and the letters A through F. When a field value cannot be modified by the operator, the field length is System-protected.
Occurs	Indicates the number of times the field can be displayed on the screen. This information is provided only when the field can be displayed multiple times.
Required Field	Specifies whether a value has to be entered in the field. Possible values are Yes and No. Some fields are required only under certain conditions. In this case, the entry is Yes, followed by the conditions that determine when the field is required.
Default Value	Specifies the value that is automatically placed in the field when the screen is first displayed or when function key F8 is pressed to clear the screen.
Column Name	Provides the SQL column name associated with the field appearing on the screen. Column names are included in the documentation to assist in communicating screen and field issues to your technical staff. Note that screen data is not always stored in the BASE24 database as it appears on the screen or as it is described in the field description. If you need information on how screen data is actually stored, consult the DDLs or SQL table creation source file.

Section 1

Introduction

This section provides an introduction to the tables specific to the BASE24-billpay product and the table maintenance screens and function keys used to access them.

BASE24-billpay Tables

The following tables are specific to the BASE24-billpay product:

- Bank Table (BANK)
- Bank Branch Table (BKBR)
- Bank Notice Table (BKNT)
- Bank Transaction Advice Table (BKAV)
- Billing Group Table (BLG)
- Billing Rate Table (BLRT)
- Billing Type Table (BLTY)
- Cleanup Configuration Table (CLPT)
- Customer Billpay Table (CBPT)
- Customer Vendor Table (CVND)
- History Table (HIST)
- Rate Table (RATE)
- Rate Group Table (RATG)
- Response Text Table (RTXT)
- Retry Table (RTRY)
- Service Provider Table (SVPT)
- Vendor Table (VNDR)
- Vendor Branch Table (VNDB)
- Vendor Budget Category Table (VBUD)
- Vendor Mask Table (VNDM)

The BANK is a BASE24-billpay table that is accessed from Institution Definition File (IDF) screens instead of the BP Product Menu. Refer to the IDF section of the ***BASE24 Base Files Maintenance Manual*** for the BANK screen.

The BLG, BLRT, BLTY, RATE, and RATG are tables that are used exclusively by the BASE24-billpay Billing Application, which is an add-on to the BASE24-billpay product. Refer to the ***BASE24-billpay Billing Application Manual*** for the screens used to maintain these tables. All other table maintenance screens are described in the sections of this manual.

Table Access

All but one of the BASE24-billpay tables that you can access are listed on the Billpay Product Menu, which you access from the BASE24 Virtual Menu. You only see the tables available to you based on the configuration in your security record. A sample Billpay Product Menu listing all possible tables is shown below. The order in which the tables are displayed for individual users is dependent on the order in which the user received access to the tables.

You can access a table listed on the menu by placing the cursor beside an individual item and pressing the **F1** key. A more detailed explanation for accessing tables is provided in the *BASE24 CRT Access Manual*.

BASE24-ADMN	MENU	LLLL	YY/MM/DD	HH:MM	01 OF 01
B P	P R O D U C T	M E N U			
BKAV	BKBR	BKNT	BLG		
BLRT	BLTY	CBPT	CLPT		
CVND	HIST	RATE	RATG		
RTRY	RTXT	SVPT	VBUD		
VNDB	VNDM	VNDR			
***** BASE24 *****					
FILE DESTINATION:					
F1-ENTER DATA	F9-NEXT PAGE	F11-PREVIOUS PAGE	F10-PRINT	F12-HELP	

SQL Table Row Access

All screens presented in this manual access rows in Structured Query Language (SQL) tables.

Access to SQL table rows is provided through the use of primary keys and indexes. For key-sequenced SQL tables, primary keys define the primary columns for which data must be supplied to read a particular row in a table. For relative SQL tables, the primary key is the relative row number. For entry-sequenced tables, the primary key is the row address maintained by SQL. In addition to primary keys, SQL tables can also use indexes to access table rows. Indexes define an alternative set of columns that can also be used to read a particular row or set of rows in a table.

Although SQL table rows can theoretically be accessed using any table row columns, primary keys and indexes provide the high performance data access capabilities required in an online transaction processing system. There is always only one primary key to a table, while there can be a limited number of indexes to provide alternative means of access. All defined indexes are included in the default configuration of SQL tables. Any unwanted indexes can be disabled when the SQL table database is installed, although this should only be done with extreme caution.

Primary keys and indexes are used both when accessing table rows from a table maintenance screen as well as when accessing table rows from the BASE24 transaction processing software.

For BASE24 transaction processing software, including table maintenance requester and server processes, the column names associated with the primary key and indexes are used to access table rows. On table maintenance screens, the primary key and indexed columns are always identified in the introductory text for the screen exactly as they appear on the screen. Fields on a table maintenance screen map directly to table columns where the data entered in the screen field is stored.

Valid values must be entered in each of the primary or indexed fields when attempting to read a particular row from a table maintenance screen. When attempting to read the next row in a table, no data or only partial data can be entered in the key or indexed fields. If no data is entered in the key or indexed fields, the first row in the table is read. If partial data is entered, the next row in the table is read.

Warning: Although the Nonstop SQL conversational interface (SQLCI) provided with the Tandem NonStop SQL product allows Tandem users to perform ad hoc queries or generate ad hoc reports from SQL tables, such use in a production system may have a detrimental impact on transaction processing performance. Therefore, the improvised use of SQLCI on production SQL tables should be severely restricted or prohibited, and should be used only when required for problem analysis.

Function Keys

The standard BASE24 function keys are used on BASE24-billpay screens. These function keys are described in the ***BASE24 Base Files Maintenance Manual*** and ***BASE24 CRT Access Manual***. When the use of these keys differs for a BASE24-billpay screen, the differences are noted in the section of the manual dealing with the screen grouping to which they apply.

Each BASE24-billpay screen also supplies an online Help screen which lists the function keys that apply on that screen. Press the **F12** key to display the Help screen.

Note: Other BASE24 products use the **F13** key to change to another logical network. This key is defined for the same purpose on BASE24-billpay table maintenance screens. However, pressing the **F13** key results in an error message because BASE24-billpay release 1.3 does not currently support multiple logical networks.

Effective Date Ranges

An effective date range for a table row controls the time frame during which the row is used, and is defined by a beginning date and an ending date. The following tables contain an effective date range:

- Bank Notice Table (BKNT)
- Customer Vendor Table (CVND)
- Vendor Table (VNDR)

When you validate or add a table maintenance screen for one of these tables, the beginning date defaults to the current system date and the ending date defaults to blanks, indicating a nonexpiring date range. For a nonexpiring date range, the Billpay Table Maintenance Server process automatically sets the internal database field for the ending date to be the largest available system date, which is December 31, 3999. The display of this date on table maintenance screens, customer service representative (CSR) screens, and reports is left blank to indicate that it is nonexpiring. You can always enter a specific ending date to make a row expire.

Because of the dependencies in the BASE24-billpay database, you should not delete rows from the CVND or VNDR through table maintenance. Rather, you should take the row out of use by entering an appropriate ending date and updating the row. This allows the row to remain in the system for reporting purposes without being used by the online software for transactions. The BASE24-billpay product includes two database management programs—Cleanup and Archive—to delete or archive expired database rows on a daily, monthly, or annual basis. Refer to the Cleanup Configuration Table (CLPT) section for more information on using the Cleanup and Archive programs.

Note: Database dependencies do not exist for the BKNT, and the Cleanup and Archive programs do not remove BKNT rows that have expired. Therefore, you must actually delete BKNT rows that you are no longer using.

Assigns and Params

The following Logical Network Configuration File (LCONF) assigns and params affect BASE24-billpay table maintenance screens:

- OMF assign
- BP-DATE-FORMAT param
- LGNT-COUNTRY-ABBR param
- OMF-AUDIT param

Refer to the *BASE24 Logical Network Configuration File Manual* for additional information about these assigns and params.

OMF Assign

Activity involving BASE24-billpay table maintenance screens is logged to the Online Maintenance File (OMF). The OMF assign provides the fully qualified file name of the OMF.

BP-DATE-FORMAT Param

The BP-DATE-FORMAT param controls the format of date fields in the body of BASE24-billpay table maintenance screens. The valid values for this param are as follows:

- DDMMYY
- DDMMYYYY
- MMDDYY
- MMDDYYYY
- YYDDMM
- YYMMDD
- YYYYDDMM
- YYYYMMDD (default value)

Table maintenance screens with date fields have the date description string displayed one or more times to show you the proper date format. This string always matches the value of the BP-DATE-FORMAT param. The date description string is represented by the value `yyyymmdd` on screen illustrations in this manual.

The BP-DATE-FORMAT param also controls the order of the date in the RECORD LAST CHANGED field at the bottom of each table maintenance screen; however, the date in this field contains only six digits even if the BP-DATE-FORMAT param is set for eight digits. For example, the date in the RECORD LAST CHANGED field is displayed as `YY/MM/DD` when the value of the BP-DATE-FORMAT param is `YYMMDD` or `YYYYMMDD`.

The header line on each table maintenance screen is displayed as `YY/MM/DD` regardless of the BP-DATE-FORMAT param value.

LGNT-COUNTRY-ABBR Param

The LGNT-COUNTRY-ABBR param contains a code identifying the country in which this logical network is located. This code is used to determine the number of decimal places used when entering and displaying amounts. Valid country code values are defined in the 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*. For example, the country code for the United States is `USA`.

OMF-AUDIT Param

The OMF-AUDIT param controls the extent of table maintenance information logged to the Online Maintenance File (OMF). Valid values are as follows:

- 0 = No OMF auditing.
- 1 = Audit record and MSG-HEADER information (default value).
- 2 = Audit MSG-HEADER information only, do not log the record image.

ACI Worldwide Inc.

Section 2

Bank Branch Table (BKBR)

The Bank Branch Table (BKBR) contains information pertinent to a specific financial institution branch such as street address, city, phone, and contact information. This information is used by customer service representatives (CSRs).

The BKBR must exist for the BASE24-billpay product; however, each financial institution has the following options for using the BKBR:

- Define only one branch location, even if additional locations exist
- Define multiple branch locations, if they exist
- Do not define any branch locations

If a financial institution defines one or more branches, one branch should be designated as the main branch. The main branch is designated in the Bank Table (BANK), which is accessed from Institution Definition File (IDF) screens 40 through 42.

The FIID and Branch Number fields on BKBR screen 1 correspond to the FIID and MAIN BRANCH NUM fields on BANK screen 1. However, the FIID must be defined in a BANK row before it can be used in a BKBR row, and the branch number for the main branch must be defined in a BKBR row before it can be used in a BANK row. This is accomplished by performing the following steps:

1. Complete all fields on BANK screen 1 except the MAIN BRANCH NUM field and add the row to the BANK.
2. Obtain the value from the FIID field on BANK screen 1, place it in the FIID field on BKBR screen 1, complete the remaining fields on BKBR screen 1, and add the row to the BKBR. Repeat this step for each branch.
3. Obtain the value from the Branch Number field on BKBR screen 1 for the main branch, place it in the MAIN BRANCH NUM field on BANK screen 1, and update the BANK row.

A BKBR row must not be deleted as long as it is identified as the main branch in a BANK row. However, the BASE24 system does not prevent an operator from deleting a BKBR row that is still being used.

The key to the BKBR is a combination of the values in the FIID and Branch Number fields. This key must be unique when a row is added and cannot be changed when a row is updated. An index is defined for the FIID, City, and State fields.

Screen 1

BKBR screen 1 contains information for each financial institution location. BKBR screen 1 is shown below, followed by descriptions of its fields.

BASE24-BILLPAY
BANK BRANCH
LLLL
YY/MM/DD
HH:MM
01 of 01

FIID
Branch Number
Address
City
State
Postal Code
Contact
Phone
Fax Phone

RECORD LAST CHANGED:
BY USER:

BASE24

NEW PAGE:
FILE DESTINATION:
NEW LOGICAL NETWORK ID:
F12-HELP

FIID — The financial institution identifier. The value in this field links the branch in this row to the financial institution and must match an FIID that already exists in the Bank Table (BANK).

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: BKBR.FIID

Branch Number — The number that identifies the branch. This value must be unique for the FIID and cannot be zero.

One branch must be designated as the main branch. The value from this field on the BKBR screen for the main branch must be placed in the MAIN BRANCH NUM field on BANK screen 1.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: BKBR.BR_NUM

Address — The mailing or street address of the branch.

Field Length: 2 fields of 1–30 alphanumeric characters each
Required Field: No
Default Value: No default value
Column Names: BKBR.ADDR_1
BKBR.ADDR_2

City — The city in which the branch is located.

Field Length: 1–25 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.CITY

State — An ANSI Standard code for the state in which the branch is located.

The U.S. state codes are based on standards described in the 1988 ANSI X3.38 standard, *Identification of the States, the District of Columbia, and the Outlying and Associated Areas of the United States for Information Interchange*.

An operator also can enter a value other than an ANSI code.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.ST

Postal Code — The postal code of the branch.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.POSTAL_CODE

Contact — The name of the contact person at the branch. This is the person to which customers can be referred by customer service representatives for additional information on their BASE24-billpay service.

Field Length: 1–22 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.CONTACT_PERSON

Phone — The business phone number for the branch.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.PHN

Fax Phone — The fax phone number for the branch.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: BKBR.PHN_FAX

ACI Worldwide Inc.

Section 3

Bank Notice Table (BKNT)

The Bank Notice Table (BKNT) is used to identify error conditions that require customer notices to be generated. A notice action is automatically generated and placed in the Report Action Table whenever the Billpay Server process or Scheduled Transaction Initiator process detects an action code that appears in this table.

Each financial institution must add a row to this table for each action code that requires a customer notice. Each row also has an effective date range so financial institutions can control the time frame during which a notice is generated. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for a list of available action codes.

The key to the BKNT is a combination of the values in the FIID, End Date, and Action Code fields. This key must be unique when a row is added and cannot be changed when a row is updated. An index is defined for the FIID, Action Code, and Begin Date fields.

Screen 1

BKNT screen 1 identifies the action codes for which a customer notice must be generated. BKNT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  BANK NOTICE          LLLL      YY/MM/DD  HH:MM      01 of 01

          FIID ____

        Action Code ____

Effective Date Range:
  Begin Date _____ yyyyymmdd
    End Date _____

RECORD LAST CHANGED:                BY USER:      ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                      F12-HELP

```

FIID — The financial institution identifier. The value in this field links the action code in this row to the financial institution and must match an FIID that already exists in the Bank Table (BANK).

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: BKNT.FIID

Action Code — A code used by the transaction authorizer to indicate the processing outcome of a transaction.

While this field accepts one, two, or three alphanumeric characters, BASE24 action codes are three alphanumeric characters in length. Use leading zeros in this field when necessary to match the BASE24 action codes.

A description for the action code appears next to the Action Code field. This description is defined in the Internal Text field on Response Text Table (RTXT) screen 1. The RTXT row used for this description has the same value in the Action Code field and no value in the Reversal Reason field.

Field Length: 1–3 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: BKNT.RSP_CODE

Effective Date Range

The following two fields indicate dates during which this row can be used in processing. Rows for the same FIID and action code cannot have effective date ranges that overlap; however, they can have effective date ranges that omit periods of time. The format used to enter and display the dates in these fields is shown to the right of the Begin Date field.

Begin Date — The first date this row can be used in processing. If the field is left blank, the Billpay Table Maintenance Server process fills in the current date when the row is added or updated.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: BKNT.BEG_DATE

End Date — The last date this row can be used in processing. If the field is left blank, this row does not expire.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: BKNT.END_DATE

ACI Worldwide Inc.

Section 4

Bank Transaction Advice Table (BKAV)

The Bank Transaction Advice Table (BKAV) contains information used by the Bank Advice process to identify additional BASE24-billpay transactions that are logged to the ITS Transaction Log File (ITLF), which can be extracted. Without the Bank Advice process, these transactions are logged only to the BASE24-billpay History Table (HIST), which cannot be extracted.

A subset of BASE24-billpay transactions that are logged to the HIST are also logged to the ITLF. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for a list of BASE24-billpay transactions that are automatically logged to the ITLF. These transactions should not be configured in the BKAV, since this would cause the transactions to be logged to the ITLF twice.

Each row identifies one combination of FIID, transaction source, and transaction type for which the Bank Advice process provides data for a record in the ITLF. Only those combinations to be logged to the ITLF should be added to this table. Also, all Bank Advice processes must be stopped and restarted whenever the BKAV is changed.

The key to the BKAV is a combination of the values in the FIID, Transaction Source, and Transaction Type fields. This key must be unique when a row is added and cannot be changed when a row is updated.

Screen 1

BKAV screen 1 identifies the BASE24-billpay transactions that should be logged to the ITS Transaction Log File (ITLF). BKAV screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  BANK TRAN ADVICE      LLLL      YY/MM/DD  HH:MM      01 of 01

      FIID ____

Transaction Source ____ (AD=Audio DH, IB=Inbound, PC=Personal Computer,
                        SP=Screen Phone, Others Allowed)

Transaction Type ____

Advice Type _ (A=Approved Only, D=Denied Only, B=Both)


RECORD LAST CHANGED:      BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                        F12-HELP

```

FIID — The financial institution identifier. The value in this field links the information in this row to the financial institution and must match an FIID that already exists in the Bank Table (BANK).

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: BKAV.FIID

Transaction Source — A code that identifies the type of device from which the transaction originates. The value in this field is used by the Bank Advice process to check the transaction source field in BASE24-billpay transactions. The code can be a reserved value or be user-defined. The reserved values are as follows:

AD = Audio device (for example, an interactive voice response system)
 BL = BASE24-billpay Billing Application
 IB = Inbound (customer service representative terminal)
 PC = Personal computer
 SP = Screen phone

If a user-defined value is placed in this field, then some originating device or software must generate the user-defined value for its transactions and they must be logged to the HIST; otherwise, no action will be taken by the Bank Advice process based on this row.

Field Length: 2 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Column Name: BKAV.TXN_SRC

Transaction Type — A code that identifies the transaction type. The value in this field is used by the Bank Advice process to check the transaction type field in BASE24-billpay transactions. The code may be a reserved value, user-defined, or for ACI use only. The reserved values are as follows:

3H = Customer vendor list inquiry
 3J = Scheduled payments list inquiry
 3K = Scheduled transfers list inquiry
 3L = History inquiry - payments and transfers
 3M = Scheduled transactions list inquiry
 9A = Schedule payment - immediate
 9B = Schedule payment - future
 9C = Schedule payment - recurring
 9D = Schedule transfer - future
 9E = Schedule transfer - recurring
 9F = Scheduled payment delete
 9G = Scheduled transfer delete
 9H = Scheduled payment update
 9J = Scheduled transfer update
 9K = Customer add
 9L = Customer inquiry
 9M = Customer update
 9N = Customer vendor add

9P = Customer vendor deactivate
 9Q = Customer vendor update
 9R = Master vendor list inquiry (internal transaction)
 9S = Master vendor add
 9T = Customer vendor request mailing
 9V = Loan application
 9W = Miscellaneous request
 9X = History inquiry - all transactions
 B0 = Customer account list inquiry (internal transaction)
 B1 = Bank list inquiry
 B2 = Bank branch list inquiry
 B3 = Cancel immediate payment (internal transaction)
 B4 = Miscellaneous requests inquiry
 B5 = Customer account add
 B6 = Customer account activate
 B7 = Customer account deactivate
 B8 = Customer account delete
 B9 = Customer account update
 BB = Customer activate
 BC = Customer deactivate
 BD = Customer vendor activate
 BE = Customer vendor mask verify inquiry

Caution: The following transaction types cause duplicate transaction entries in the ITS Transaction Log File (ITLF) and are not to be used.

4A = Transfer - future
 4B = Transfer - recurring
 50 = Payment - immediate
 5A = Payment - future
 5B = Payment - recurring

If a user-defined value is placed in this field, then some originating device or software must generate the user-defined or ACI use only value for its transactions and they must be logged to the HIST; otherwise, no action will be taken by the Bank Advice process based on this row.

Field Length: 2 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Column Name: BKAV.TXN_TYP

Advice Type — A code that identifies the conditions under which the Billpay Server process and Scheduled Transaction Initiator process provide data to be logged to the ITLF. Valid values are as follows:

- A = Log approved transactions only
- B = Log both approved and denied transactions
- D = Log denied transactions only

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: No default value
Column Name: BKAV.ADV_TYP

ACI Worldwide Inc.

Section 5

Cleanup Configuration Table (CLPT)

The Cleanup Configuration Table (CLPT) contains configuration information used by the Archive and Cleanup programs. The Archive program copies and removes old rows from the History Table (HIST) and the Cleanup program removes obsolete rows from other tables. The Archive and Cleanup programs remove obsolete information from all tables that need cleaning. A TACL macro purges the old remittance files, which are files (not tables) that are no longer needed. Refer to the ***BASE24 Remote Banking End-of-Period Processing and Reporting Manual*** for more information about the use of the Archive and Cleanup programs.

The key to the CLPT is a combination of the values in the FIID and Parameter Name fields. This key must be unique when a row is added and cannot be changed when a row is updated.

Archive Program

The Archive program archives and removes old rows from the History Table (HIST). This program runs after cutover on a nightly basis, preferably as one of the last steps in the daily cycle.

The Archive program can operate at a system-wide level or an FIID-specific level, depending on the setting of the BP-ARCHIVE-BY-FIID param in the Logical Network Configuration File (LCONF). When the Archive program operates at the system-wide level, it does not use the CLPT. When the Archive program operates at the FIID-specific level, there must be one CLPT row for each FIID that is to have its HIST rows archived. All HIST rows for a given financial institution must be archived after the same length of time.

The group of CLPT rows that define the processing performed by one Archive program is called an archive group. An archive group can have any number of financial institutions; however, all CLPT rows in one archive group must have the same number of retention days for the HIST rows. A separate archive group is required for each retention period value specified in the Parameter Value field on CLPT screen 1.

For example, if five financial institutions use one retention period and five financial institutions use a different retention period, there have to be at least two archive groups (one archive group for each retention period). If necessary, more archive groups can be defined, making each group smaller and reducing the amount of processing time by dividing the work among more Archive programs.

Each archive group must have its own copy of the Archive program, and each Archive program uses its own BP-ARCHIVE-GROUP param in the LCONF to determine which archive group to process. The value in the Cleanup Group field on CLPT screen 1 must match the cleanup group specified in a BP-ARCHIVE-GROUP param. The archive program uses the following Parameter Name and Parameter Value field values on CLPT screen 1 for these rows.

Table	Parameter Name	Parameter Value
History	history	Minimum number of retention days for rows in the HIST

Cleanup Program

The Cleanup program runs after cutover on a nightly basis, preferably as one of the last steps in the daily cycle. This program can remove old rows from 15 BASE24-billpay tables. Some of these tables are accessible from BASE24-billpay tables maintenance screens or customer service representative (CSR) screens, and some are maintained by BASE24-billpay programs only. Regardless of access, each table falls into one of the following groups:

- System-wide tables cleaned daily
- FIID-specific tables cleaned daily
- System-wide tables cleaned annually
- FIID-specific tables cleaned annually

The values used in the Parameter Name and Parameter Value fields on CLPT screen 1 for each group are shown in the following tables. The numeric values in the Parameter Value column are the recommended minimum number of retention days for the parameters.

System-Wide Tables Cleaned Daily		
Table	Parameter Name	Parameter Value
Context	context	0 if the Cleanup program runs after 2:00 a.m.; 1 if the Cleanup program runs between midnight and 2:00 a.m.
Payment Summary	pmtsum	10
Report Action	reportaction	180

FIID-Specific Tables Cleaned Daily		
Table	Parameter Name	Parameter Value
Bank Billing Summary	bankbillsum	60
Bank Transaction Summary	banktxnsum	90
Customer Billing Summary	custbillsum	60

FIID-Specific Tables Cleaned Daily		
Table	Parameter Name	Parameter Value
Loan	loan	2
Miscellaneous Request	miscreq	180

System-Wide Tables Cleaned Annually		
Table	Parameter Name	Parameter Value
Customer Vendor	custvend	Y = Yes, clean table. N = No, do not clean table.
Customer Vendor Summary	custvendsum	Y = Yes, clean table. N = No, do not clean table.
Vendor, Vendor Branch	vend	Y = Yes, clean tables. N = No, do not clean tables.

FIID-Specific Tables Cleaned Annually		
Table	Parameter Name	Parameter Value
Bank Notice	banknotice	Y = Yes, clean table. N = No, do not clean table.
Billing Group	billgrp	Y = Yes, clean table. N = No, do not clean table.
Billing Rate	billrate	Y = Yes, clean table. N = No, do not clean table.

Each financial institution must have its own CLPT row for each FIID-specific table being cleaned. There must be one CLPT row for each system-wide table being cleaned, regardless of the number of financial institutions involved. CLPT rows for FIID-specific tables use an FIID that has been defined in the Bank Table, and CLPT rows for system-wide tables use an FIID value of dashes (----).

The group of CLPT rows that define the processing performed by one Cleanup program is called a cleanup group. The following guidelines must be followed when defining cleanup groups:

- All tables in a group must have the same number of retention days.
- Tables cleaned daily and tables cleaned annually must be in different groups.
- FIID-specific tables and system-wide tables must be in different groups.
- Each Cleanup program uses its own BP-CLEANUP-GROUP param in the Logical Network Configuration File (LCONF) to determine which cleanup group to process.
- The value in the Cleanup Group field on CLPT screen 1 must match the cleanup group specified in a BP-CLEANUP-GROUP param.

Screen 1 Function Keys

The use of two function keys varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column of information below shows the BASE24 keys. The second column describes the function that can be accomplished with these keys.

Key	Description
F2	Read — Cursor position is considered when determining which row is read, as follows: • Rows are accessed according to values in the FIID and Parameter Name fields when the cursor is located in any field other than the Cleanup Group field. • Rows are accessed according to the value in the Cleanup Group field when the cursor is located in the Cleanup Group field.
F6	Read Next — Cursor position is considered when determining which row is read next, as follows: • Rows are accessed according to values in the FIID and Parameter Name fields when the cursor is located in any field other than the Cleanup Group field. • Rows are accessed according to the value in the Cleanup Group field when the cursor is located in the Cleanup Group field.

Cleanup Group — The name of the cleanup group that uses this row. This name must match the cleanup group specified in a BP-CLEANUP-GROUP param or BP-ARCHIVE-GROUP param in the LCONF in order for this row to be used.

Note: This name, when used by the Archive program for FIID-specific processing, must be a valid subvolume name (that is, it must start with a letter, be alphanumeric, and not exceed eight characters in length). The operator is responsible for ensuring that this naming requirement is met.

Field Length: 1–32 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CLPT.CLEANUP_GRP

Parameter Name — The name of the table. For valid values, refer to the Archive Program and Cleanup Program discussions earlier in this section. Other values are accepted, but are not used by the Archive and Cleanup programs.

Field Length: 1–32 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CLPT.PARAM_NAME

Parameter Value — The value for the parameter. For valid values, refer to the Archive Program and Cleanup Program discussions earlier in this section. Other values are accepted, but are not used by the Archive and Cleanup programs.

Field Length: 1–70 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CLPT.PARAM_VAL

Section 6

Customer Billpay Table (CBPT)

The Customer Billpay Table (CBPT) contains information used for online processing of transactions. This table contains one row for each customer allowed access to the BASE24-billpay system.

The Billpay Server process creates a row in this table the first time the Customer Table (CSTT) is used for any BASE24-billpay activity. The Billpay Server process, Customer Billing process, Billpay Table Maintenance Server process, and Scheduled Transaction Initiator process update the information in this table.

The last customer vendor number used for the customer and the next available reference number to use for this customer are displayed on CBPT screen 1.

Other information in the CBPT is provided for the BASE24-billpay Billing Application, which is an add-on to the BASE24-billpay product. Refer to the ***BASE24-billpay Billing Application Manual*** for additional information about this application.

The key to the CBPT is the value in the Cust ID field. All information on CBPT screen 1 is provided for inquiry only.

Screen 1

CBPT screen 1 contains miscellaneous processing information maintained by the BASE24-billpay system for each customer. CBPT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  CUSTOMER BILLPAY      LLLL      YY/MM/DD  HH:MM      1 OF  1

                Cust ID _____

        Billing Type: Current
                  Original

        Billing Group

    Number of Cycles Processed

        Last Cycle End Date      yyyyymmdd

Last Billing Reference Number

        Last Customer Vendor Number
        Next Reference Number

RECORD LAST CHANGED:                BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                  F12-HELP
  
```

Cust ID — The customer ID used to select a CBPT row for display.

Field Length: 1–19 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Column Name: CBPT.CUST_ID

Billing Type

The following two fields contain codes that identify the billing type for a BASE24-billpay customer. If the BASE24-billpay Billing Application is not being used, these fields may be blank.

Current — The billing type that is currently being used.

Field Length: System-protected
Column Name: CBPT.CUR_BILL_TYP

Original — The billing type that existed in the associated Customer Table (CSTT) row when this row was originally created in the CBPT.

Field Length: System-protected
Column Name: CBPT.ORIG_BILL_TYP

Billing Group — The billing group to which this customer currently belongs. If the BASE24-billpay Billing Application is not being used, this field may be blank.

Field Length: System-protected
Column Name: CBPT.BILL_GRP

Number of Cycles Processed — The number of billing cycles that have been processed for this customer using the current billing type. If the BASE24-billpay Billing Application is not being used, this field will display zero.

Field Length: System-protected
Column Name: CBPT.NUM_CYCLES

Last Cycle End Date — The end date of the last billing cycle for this customer. The format used to display the date in this field is shown to the right of the field. If the BASE24-billpay Billing Application is not being used, this field will display zero.

Field Length: System-protected
Column Name: CBPT.LAST_CYCLE_END_DATE

Last Billing Reference Number — The last reference number processed by the BASE24-billpay Billing Application, if used. The Customer Billing process manages the value in this field, which identifies the most recent History Table (HIST) row used for fee calculation purposes.

Field Length: System-protected
Column Name: CBPT.LAST_BILL_REF_NUM

Last Customer Vendor Number — The last customer vendor number used for this customer. The next vendor number for this customer is the value in this field plus 1.

The Billpay Server process and the Billpay Table Maintenance Server process manage the value in this field.

Field Length: System-protected
Column Name: CBPT.LAST_CUST_VEND_NUM

Next Reference Number — The reference number to use for this customer's next billpay transaction. The Billpay Server process and the Scheduled Transaction Initiator process manage the value in this field.

Field Length: System-protected
Column Name: CBPT.NEXT_REF_NUM

Section 7

Customer Vendor Table (CVND)

The Customer Vendor Table (CVND) identifies the vendors to which a given customer is allowed to make payments. A customer has one row in this table for each relationship maintained with a vendor. For example, a customer that has four accounts with the same vendor will have four rows in the CVND.

Each row contains a unique customer vendor number for each customer ID. Different customer IDs can have the same customer vendor numbers. The Billpay Server process and the Billpay Table Maintenance Server process manage the customer vendor numbers, tracking them in the Customer Billpay Table (CBPT).

The key to the CVND is a combination of the values in the Cust ID and Customer Vendor Number fields. This key must be unique when a row is added and cannot be changed when a row is updated. Also, the value in the Vendor Number field cannot be changed when a row is updated since it is associated with the Customer Vendor Number field.

Screen 1 Function Keys

The use of one function key varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of this function key is explained below.

The first column of information below shows the BASE24 key. The second column describes the function that can be accomplished with this key.

Key	Description
F4	Deactivate — Deactivates the row displayed on the screen by altering the value in the Account End Date field to be the current date minus one day. There are dependencies throughout the BASE24-billpay system on CVND rows even after they expire. The Cleanup program is used to remove expired rows from the CVND on an annual basis.

Screen 1

CVND screen 1 contains information that establishes the relationship between a BASE24-billpay customer and a BASE24-billpay vendor. CVND screen 1 is shown below, followed by descriptions of its fields.

BASE24-BILLPAY CUSTOMER VENDOR LLLL YY/MM/DD HH:MM 1 OF 1

Cust ID _____

Customer Vendor Number _____

Vendor Number _____

Vendor Branch Number _____

Account With Vendor _____

Account Verify: Status _ (I=Initial, V=Verified, F=Failed, Others Allowed)

Date _____

Effective Date Range: yyyymmdd Customer Vendor Short Name

Account Begin Date _____ Info 1 _____

Account End Date _____ Info 2 _____

Budget Category _____

RECORD LAST CHANGED: BY USER: _____ ,

***** BASE24 *****

NEW PAGE: FILE DESTINATION: NEW LOGICAL NETWORK ID:

F4-DEACTIVATE F12-HELP

Cust ID — The customer identification number. This value must already exist in the Customer Table (CSTT).

- Field Length: 1–19 alphanumeric characters
- Required Field: Yes, to add or update a row.
- Default Value: No default value
- Column Name: CVND.CUST_ID

Customer Vendor Number — A value that uniquely identifies the relationship between the customer and vendor. The Billpay Table Maintenance Server process and Billpay Server process use the value in the Last Customer Vendor Number field on Customer Billpay Table (CBPT) screen 1 when adding a new customer vendor row, then update the Last Customer Vendor Number field by adding 1 to it.

Field Length: 1–5 numeric characters
Required Field: Yes, to read a row. This field must be set to zero or blanks when a row is added.
Default Value: No default value
Column Name: CVND.CUST_VEND_NUM

Vendor Number — The number used to identify the vendor. This value must already exist in the Vendor Table (VNDR). The name associated with this vendor number in the VNDR is displayed to the right of this field.

Field Length: 1–9 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: CVND.VEND_NUM

Vendor Branch Number — The number that identifies the vendor branch used by the customer. This value must already exist in the Vendor Branch Table (VNDB) row for the vendor identified in the Vendor Number field. The name associated with this branch number in the VNDB is displayed to the right of this field.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: CVND.VEND_BR_NUM

Account With Vendor — The customer account with the vendor that is credited with any customer payments. Any value entered here must conform to the Vendor Mask Table (VNDM) entries for this vendor and vendor branch combination.

Field Length: 1–28 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CVND.ACCT_WITH_VEND

Account Verify

The following two fields indicate when the most recent attempt to verify the vendor information in this row occurred and the result of that attempt. Payments cannot be initiated to an unverified vendor.

Status — A code indicating the result of the last attempt to verify this customer vendor information. Values may be reserved or user-defined; however, any value other than V is considered to be unverified. The reserved values are as follows:

F = Failed. Failed verification.

I = Initial. Customer vendor information has been entered in the table but has not been verified.

V = Verified. Customer vendor information has been verified and may be used for transactions.

Field Length: 1 alphanumeric character

Required Field: No

Default Value: No default value

Column Name: CVND.ACCT_VRFY

Date — The date and time the Status field was initially set or last modified. The format used to display the date in this field is shown above the Account Begin Date field.

Field Length: System-protected

Column Name: CVND.ACCT_VRFY_GMT

Effective Date Range

The following two fields indicate the dates during which this row can be used in processing. The format used to enter and display the dates in these fields is shown above the Account Begin Date field.

Account Begin Date — The first date the associated customer account with the vendor can be used to initiate a payment. If this field is left blank, the Billpay Table Maintenance Server process updates the field with the current date when the row is added or the Status field is updated.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: CVND.ACCT_BEG_DATE

Account End Date — The last date the associated customer account with the vendor can be used to initiate a payment. If this field is left blank when the row is added or updated, this row does not expire.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: CVND.ACCT_END_DATE

Budget Category — A code identifying the budget category to which this vendor is assigned. Any code used in this field must first be defined in the Vendor Budget Category Table (VBUD). The name associated with this budget category in the VBUD is displayed to the right of this field.

If this field is left blank, the Billpay Table Maintenance Server process obtains the value for this field from the Default Budget Category field on Vendor Table (VNDR) screen 2 for the vendor.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CVND.BGT_CAT

Customer Vendor Short Name — The free-format customer short name for the vendor. This field is for information only.

Field Length: 1 to 10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CVND.SHORT_NAME

Info 1 — This field contains customer-specific information about the customer vendor. This field is for information only.

Field Length: 1 to 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CVND.USER_INFO_1

Info 2 — This field contains customer-specific information about the customer vendor. This field is for information only.

Field Length: 1 to 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CVND.USER_INFO_2

ACI Worldwide Inc.

Section 8

History Table (HIST)

The History Table (HIST) contains one row for each BASE24-billpay financial transaction that has been processed, as well as one row for each failed transaction and log-only nonfinancial transaction.

The Archive program removes outdated rows from the HIST. The length of time HIST rows are retained can be controlled at a system-wide level or an FIID-specific level. Rows in the Cleanup Configuration Table (CLPT) control how long HIST rows are retained for each FIID. Refer to the ***BASE24 Remote Banking End-of-Period Processing and Reporting Manual*** for more information about the use of the Archive program.

These screens contain read-only data and are designed for research purposes.

The key to the HIST from these screens is a combination of the values in the Cust ID and Ref Number fields.

Screen 1

HIST screen 1 displays vendor and scheduling information for a transaction. HIST screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  HISTORY                      LLLL          YY/MM/DD  HH:MM          1 OF  2

Cust ID _____ Ref Number _____

Tran Type                                           BP Entry
                                           yyyymmdd

          FIID Account Number          Type Code

From Account:                                           Amt
                                           Scheduled As
To Account:                                           Orig Ref Num
OR
To Vendor: Num
          Name
Acct with Vend

Tran Source: Type
          Number
          Date                                           yyyymmdd

RECORD LAST CHANGED:          BY USER:          ,
*****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
          F12-HELP

```

Cust ID — The customer ID associated with the entry. The Cust ID field, Ref Number field, or both fields can be used to select an entry.

Field Length:	1–19 alphanumeric characters
Required Field:	No
Default Value:	No default value
Column Name:	HIST.CUST_ID

Ref Number — The unique reference number assigned to the transaction. The Cust ID field, Ref Number field, or both fields can be used to select an entry.

Field Length:	1–6 numeric characters
Required Field:	No
Default Value:	No default value
Column Name:	HIST.REF NUM

Tran Type — A code identifying the type of transaction performed. The code can be reserved, user-defined, or for ACI use only. The reserved values are as follows:

3H	=	Customer vendor list inquiry
3J	=	Scheduled payments list inquiry
3K	=	Scheduled transfers list inquiry
3L	=	History inquiry - payments and transfers
3M	=	Scheduled transactions list inquiry
4A	=	Transfer - future
4B	=	Transfer - recurring
50	=	Payment - immediate
5A	=	Payment - future
5B	=	Payment - recurring
9A	=	Schedule payment - immediate
9B	=	Schedule payment - future
9C	=	Schedule payment - recurring
9D	=	Schedule transfer - future
9E	=	Schedule transfer - recurring
9F	=	Scheduled payment delete
9G	=	Scheduled transfer delete
9H	=	Scheduled payment update
9J	=	Scheduled transfer update
9K	=	Customer add
9L	=	Customer inquiry
9M	=	Customer update
9N	=	Customer vendor add
9P	=	Customer vendor deactivate
9Q	=	Customer vendor update
9R	=	Master vendor list inquiry
9S	=	Master vendor add (internal transaction)
9T	=	Customer vendor request mailing
9V	=	Loan application
9W	=	Miscellaneous request
9X	=	History inquiry - all transactions
B0	=	Customer account list inquiry (internal transaction)
B1	=	Bank list inquiry
B2	=	Bank branch list inquiry
B3	=	Cancel immediate payment (internal transaction)
B4	=	Miscellaneous requests inquiry
B5	=	Customer account add
B6	=	Customer account activate
B7	=	Customer account deactivate
B8	=	Customer account delete
B9	=	Customer account update
BB	=	Customer activate

BC = Customer deactivate
BD = Customer vendor activate
BE = Customer vendor mask verify inquiry

Field Length: System-protected
Column Name: HIST.TXN_TYP

BP Entry — The date and time the BASE24-billpay system began processing the transaction. The format used to display the date is shown below this field.

Field Length: System-protected
Column Name: HIST.BP_GMT

From Account

The following three fields contain account data associated with the inquiry or debit side of any transaction. These values existed in the customer-related tables at the time the transaction was entered into the system. These fields may be blank for nonfinancial transactions.

FIID — The financial institution identifier.

Field Length: System-protected
Column Name: HIST.FROM_FIID

Account Number — The number that identifies the account, which may or may not reside on the BASE24 system.

Field Length: System-protected
Column Name: HIST.FROM_ACCT_NUM

Type Code — A code identifying the type of account. The code can be reserved or user-defined. The reserved values are as follows:

10, 1A–1F = Savings
20, 2A–2H = Checking or DDA
30, 3A–3G = Credit
38 = Line of credit
58 = Certificate
59 = Retirement account
90 = Interest-bearing checking account

9A = Commercial loan
9B = Installment loan
9C = Mortgage loan

Field Length: System-protected
Column Name: HIST.FROM_ACCT_TYP

Amount — The amount involved in a financial transaction. This field will be blank if this is a nonfinancial transaction.

Field Length: System-protected
Column Name: HIST.AMT

Scheduled As — A code used for scheduled (future and recurring) payment, scheduled transfer, and immediate payment transactions. Valid values for these types of transactions are as follows:

F = Future financial transaction
I = Immediate financial transaction
R = Recurring financial transaction
b = Nonfinancial transaction, where b indicates blank

Field Length: System-protected
Column Name: HIST.SCHD_TYP

Orig Ref Num — The reference number for the original transaction.

Field Length: System-protected
Column Name: HIST.ORIG_HIST_NUM

To Account

The following three fields contain account data associated with the credit side of a transfer transaction. These values existed in the customer-related tables at the time the transaction was entered into the system. These fields are blank for nonfinancial transactions and transactions that do not involve a *to* account.

FIID — The financial institution identifier.

Field Length: System-protected
Column Name: HIST.TO_FIID

Account Number — The number that identifies the account, which may or may not reside on the BASE24 system.

Field Length: System-protected
Column Name: HIST.TO_ACCT_NUM

Type Code — A code identifying the type of account. The code can be reserved or user-defined. The reserved values are as follows:

10, 1A–1F = Savings
20, 2A–2H = Checking or DDA
30, 3A–3G = Credit
38 = Line of credit
58 = Certificate
59 = Retirement account
90 = Interest-bearing checking account
9A = Commercial loan
9B = Installment loan
9C = Mortgage loan

Field Length: System-protected
Column Name: HIST.TO_ACCT_TYP

To Vendor

The following three fields contain vendor data associated with a payment transaction. These values existed in the Customer Vendor Table (CVND) at the time the transaction was entered into the system. These fields are blank for transactions that do not involve a vendor.

Num — The number that uniquely identifies the vendor.

Field Length: System-protected
Column Name: HIST.VEND_NUM

Name — The name of the vendor identified by the number in the Num field.

Field Length: System-protected
Column Name: VNDR.VEND_NAME

Acct with Vend — The customer account with the vendor that is credited with the payment.

Field Length: System-protected
Column Name: HIST.ACCT_WITH_VEND

Tran Source

The following three fields identify the source of the transaction.

Type — A code identifying the type of device or program that originated the transaction. The code can be reserved or user-defined. The reserved values are as follows:

AD = Audio device (for example, an interactive voice response system)
BL = BASE24-billpay Customer Billing process
IB = Inbound (customer service representative)
PC = Personal computer
SP = Screen phone

Field Length: System-protected
Column Name: HIST.TXN_SRC

Number — A unique number assigned to this transaction by the transaction source device or program.

Field Length: System-protected
Column Name: HIST.TXN_SRC_NUM

Date — The date and time the transaction source originally handled this transaction. The format used to display the date is shown next to this field.

Field Length: System-protected
Column Name: HIST.TXN_SRC_LCT

Screen 2

HIST screen 2 displays status information for a transaction. HIST screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  HISTORY                      LLLL      YY/MM/DD  HH:MM      2 OF  2

Cust ID _____ Ref Number _____

Collection Status                               Partition Num
  Completion
  Action Code
Auth Action Code                               yyyyymmdd
  Approval Code                               Business Date
  Reversal Reason                           History Date
                                           Rqstd Tran Date

Remitted: Date                               Remit Ack:   Paid Date
      Status                                     Number
      Type                                       Rcvd Ack Date

Vendor Specific Data
Billing Text

RECORD LAST CHANGED:                          BY USER:  ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                        F12-HELP

```

Collection Status — A code identifying the status of funds collection from the customer's *from* account, if applicable for this transaction. Valid values are as follows:

C = Completion
 F = Failed
 I = Initial
 P = Pending
 ␣ = Nonfinancial transaction, where ␣ indicates blank

Field Length: System-protected
 Column Name: HIST.COLL_STAT

Partition Num — The HIST partition number managed by the BASE24-billpay system. This number identifies the HIST partition in which this transaction resides. It is displayed for system management research purposes only.

Field Length: System-protected
Column Name: HIST.HIST_PARTITION_NUM

Completion — A description of the completion status of the transaction, based on values in the Action Code and Reversal Reason fields. This description is defined in the Internal Text field on Response Text Table (RTXT) screen 1.

Field Length: System-protected
Column Name: RTXT.INTRN_TXT

Action Code — A code identifying the outcome of transaction processing by BASE24-billpay. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for action codes used by the BASE24-billpay and BASE24-telebanking products.

Field Length: System-protected
Column Name: HIST.RSP_CODE

Auth Action Code — A code identifying the outcome of financial transaction processing by BASE24-telebanking or another authorizer. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for action codes used by the BASE24-billpay and BASE24-telebanking products. This field is blank for a nonfinancial transaction.

Field Length: System-protected
Column Name: HIST.AUTH_ACT_CODE

Approval Code — A random number generated by the authorizer for an approved financial transaction. This field is blank for a nonfinancial transaction.

Field Length: System-protected
Column Name: HIST.AUTH_APPRV_CODE

Business Date — The business date when this transaction was started. For financial transactions, this is the date on which the customer's funds were collected. The format used to display the date is shown above this field.

Field Length: System-protected
Column Name: HIST.BUS_DATE

Reversal Reason — A code used by the transaction authorizer to indicate the reason a transaction was reversed. If the transaction was not reversed, this field is blank.

Field Length: System-protected
Column Name: HIST.RVSL_RSN

History Date — The date and time when the transaction was first placed in the HIST. The format used to display the date is shown above the Business Date field.

Field Length: System-protected
Column Name: HIST.HIST_GMT

Rqstd Tran Date — The date the customer requested that the transaction be performed. For a future payment, future transfer, recurring payment, or recurring transfer, the transaction can be requested on one date and performed on another date. The format used to display the date is shown above the Business Date field.

Field Length: System-protected
Column Name: HIST.PMT_DATE

Remitted

The following three fields contain remittance information about payments to vendors.

Date — The date when the vendor remittance was initiated. The format used to display the date is shown above the Business Date field.

Field Length: System-protected
Column Name: HIST.REMIT_BUS_DATE

Status — The current remittance status. Valid values are as follows:

- C = Completed. Payment has been sent to the vendor.
- F = Failed. Payment could not be initiated.
- I = Initial. Funds have been collected from the customer account.
- L = Cleared. Payment made to the vendor has cleared the account from which it was issued.
- S = Sent out. The transaction has been placed in a remit table.
- ␣ = Nonpayment transaction, where ␣ indicates blank.

Field Length: System-protected
Column Name: HIST.REMIT_STAT

Type — A code indicating how the vendor was paid for payment transactions. The code can be reserved or user-defined. The reserved values are as follows:

ACH = Automated clearing house (ACH) remittance.

CGP = Group-item check. Payments for all customers belonging to the same financial institution are combined on one check per vendor.

CIT = Single-item check. One payment from one customer per check.

Field Length: System-protected
Column Name: HIST.REMIT_TYP

Remit Ack

The following three fields contain vendor remittance processing information provided by a third party, if such information is available.

Paid Date — The date the payment (of whatever type) was sent to the vendor. For example, if the vendor is paid by check and a third party does check generation, this would be the date the third party generated the check for this transaction. The format used to display the date is shown above the Business Date field.

Field Length: System-protected
Column Name: HIST.REMIT_ACK_GMT

Number — The serial number that the payment (of whatever type) carried. For example, if the vendor is paid by check and a third party does check generation, this would be the check number the third party put on the check for this transaction.

Field Length: System-protected
Column Name: HIST.REMIT_ACK_NUM

Rcvd Ack Date — The date the BASE24-billpay system received the information for the Paid Date and Number fields. The format used to display the date is shown above the Business Date field.

Field Length: System-protected
Column Name: HIST.REMIT_ACK_RCVD_GMT

Vendor Specific Data — The vendor-specific data, if any, associated with the transaction. This is data required by certain vendors in addition to information in the Account With Vendor field on HIST screen 1.

Field Length: System-protected
Column Name: HIST.VEND_SPECIFIC_DATA

Billing Text — The billing text, if any, associated with the transaction. This is normally the text shown on the customer's statement from the financial institution.

Field Length: System-protected
Column Name: HIST.BILL_TXT

Section 9

Response Text Table (RTXT)

The Response Text Table (RTXT) contains one row for each action code and reversal reason pair for which either internally displayed or externally displayed text is required. Internally displayed text appears on customer service representative (CSR) and table maintenance screens, primarily as descriptions for action codes. Externally displayed text appears on reports and customer notices.

This table is used by the BASE24-billpay product for descriptions of all action codes; therefore, this table should contain all defined action codes for both the BASE24-billpay and BASE24-telebanking products. Each of these descriptions should be entered by defining the action code value with an associated reversal reason of blanks.

If an action code can have reversal reason codes used with it, additional RTXT rows must be defined for each possible action code and reversal reason pair. For example, an action code that can have three reversal reason codes used with it must have four RTXT rows—one row for the action code only and one row for each of the three action code and reversal reason code pairs.

The description for the Reversal Reason field includes a list of all valid reversal reason codes. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for a complete list of action codes.

The key to the RTXT is a combination of the values in the Action Code and Reversal Reason fields. This key must be unique when a row is added and cannot be changed when a row is updated.

Screen 1

RTXT screen 1 contains internal and external text associated with an action code and reversal reason code. RTXT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  RESPONSE TEXT          LLLL          YY/MM/DD  HH:MM      1 OF  1

  Action Code  ____
Reversal Reason  ____
                  1          2          3
                123456789012345678901234567890
Internal Text:  _____

External Text:
                1          2          3          4          5          6          7
12345678901234567890123456789012345678901234567890123456789012345678
____
____
____
____
____

RECORD LAST CHANGED:          BY USER:          ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                      F12-HELP

```

Action Code — A code used by the transaction authorizer to indicate the processing outcome of a transaction.

While this field accepts one, two, or three alphanumeric characters, BASE24 action codes are three alphanumeric characters in length. Use leading zeros in this field when necessary to match the BASE24 action codes.

A description for the action code appears next to the Action Code field. This description is defined in the Internal Text field.

Field Length:	1–3 alphanumeric characters
Required Field:	Yes
Default Value:	No default value
Column Name:	RTXT.RSP_CODE

Reversal Reason — A code used by the transaction authorizer to indicate why a transaction is reversed. Codes can be reserved or user-defined. Reserved values are as follows:

4000 = Customer cancellation
4001 = No action taken
4002 = Suspected malfunction
4003 = Format error
4005 = Original amount incorrect
4006 = Response received too late
4007 = Card acceptor device unable to complete transaction
4010 = Payment out of balance
4012 = Payment out of balance, applied contents
4013 = Unable to deliver message to point of service
4014 = Suspected malfunction, card retained
4015 = Suspected malfunction, card returned
4016 = Suspected malfunction, Track 3 not updated
4017 = Suspected malfunction, no cash dispensed
4020 = Invalid response, no action taken
4021 = Timeout waiting for response

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: RTXT.RVSL_RSN

Internal Text — User-defined text that is displayed on CSR and table maintenance screens in conjunction with the codes in the Action Code and Reversal Reason fields.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: RTXT.INTRN_TXT

External Text — User-defined text that appears on reports and customer notices in conjunction with the codes in the Action Code and Reversal Reason fields. Note that the entry of data on one line does not automatically wrap to the next line.

Field Length: 6 lines of 1–78 alphanumeric characters each
Required Field: No
Default Value: No default value
Column Name: RTXT.EXTRN_TXT

Section 10

Retry Table (RTRY)

The Retry Table (RTRY) is used by the Scheduled Transaction Initiator process to determine whether transactions in the Future Table that are declined with specific action codes can be retried. Financial institutions must place one entry in this table for each action code that can be retried. No retries are executed for an action code that a financial institution has not placed in this table.

Each RTRY row includes the number of times an action code can be retried and how much time should elapse between retry attempts, as well as whether an action code identifies a transient condition. A transient condition is one that typically can be resolved in a short period of time and without any operator intervention, while a nontransient condition is one that typically takes a longer period of time or operator intervention to resolve. Two possible RTRY entries are shown in the following table.

Action Code	Description	Transient	Retries Allowed	Time to Delay
116	Funds unavailable	No	2	24 hours
911	Issuer timeout	Yes	4	15 minutes

Each Future Table row contains separate counters for transient and nontransient errors. Each time the transaction is declined with an action code defined in the RTRY, the Scheduled Transaction Initiator process adds one to the appropriate error counter and compares the counter with the number of retries specified in the RTRY row for the action code. If the number of errors exceeds the number of retries specified, the Scheduled Transaction Initiator process declines the transaction. The Scheduled Transaction Initiator process resets the error counters if the transaction is authorized successfully.

The key to the RTRY is a combination of the values in the FIID and Action Code fields. This key must be unique when a row is added and cannot be changed when a row is updated.

Screen 1

RTRY screen 1 contains parameters used by the Scheduled Transaction Initiator process to retry transactions. RTRY screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  RTRY                LLLL      YY/MM/DD  HH:MM      1 OF  1

                FIID  ____

                Action Code  ____

Is this a Transient Condition? _ (Y/N)

Number of Retries Allowed ____

Length of Time to Delay  ____ Hours ____ Minutes ____ Seconds

RECORD LAST CHANGED:                BY USER:                ,
***** BASE24 *****
NEW PAGE:                FILE DESTINATION:                NEW LOGICAL NETWORK ID:
                        F12-HELP

```

FIID — The financial institution identifier. The value in this field links the information in this row to the financial institution and must match an FIID that already exists in the Bank Table (BANK).

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: RTRY.FIID

Action Code — A code used by the transaction authorizer to indicate the processing outcome of a transaction. Refer to the ***BASE24 Remote Banking Transaction Processing Manual*** for a list of valid values.

While this field accepts one, two, or three alphanumeric characters, BASE24 action codes are three alphanumeric characters in length. Use leading zeros in this field when necessary to match the BASE24 action codes.

A description for the action code appears next to the Action Code field. This description is defined in the Internal Text field on Response Text Table (RTXT) screen 1.

Field Length: 1–3 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: RTRY.RSP_CODE

Is this a Transient Condition — A flag identifying whether the specified action code represents a transient condition. Valid values are as follows:

Y = Yes, the specified action code identifies a transient condition.

N = No, the specified action code does not identify a transient condition.

The specified action code can be retried regardless of the value in this field.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: No default value
Column Name: RTRY.TRANSIENT

Number of Retries Allowed — The number of times a transaction with the specified action code can be retried.

Field Length: 1–2 numeric characters
Required Field: No
Default Value: No default value
Column Name: RTRY.RETRY_CNT

Length of Time to Delay

The following three fields identify the length of time the Scheduled Transaction Initiator process waits before retrying a transaction with the specified action code. The Scheduled Transaction Initiator process uses the values in these fields to calculate the next time to attempt to complete the transaction.

Hours — The number of hours to wait before retrying the transaction. Valid values are 0 through 99.

Field Length: 1–2 numeric characters
 Required Field: No
 Default Value: No default value
 Column Name: RTRY.RETRY_DELAY

Minutes — The number of minutes to wait before retrying the transaction. Valid values are 0 through 59.

Field Length: 1–2 numeric characters
 Required Field: No
 Default Value: No default value
 Column Name: RTRY.RETRY_DELAY

Seconds — The number of seconds to wait before retrying the transaction. Valid values are 0 through 59.

Field Length: 1–2 numeric characters
 Required Field: No
 Default Value: No default value
 Column Name: RTRY.RETRY_DELAY

Section 11

Service Provider Table (SVPT)

The Service Provider Table (SVPT) contains the last customer ID assigned by the service provider. The Billpay Server process uses this table to automatically generate customer IDs for financial institutions that do not use preloaded customer data. This table should contain only one row.

SVPT screen 1 is provided for the purpose of building an initial row and for viewing its data. You can indicate the customer ID value for the system to use as a starting point. The first customer ID value generated will be one number larger than the value you specify. Once the row has been added, no updates or deletes are allowed.

The key to the SVPT is the value in the Service Provider Name field. This key must match the name specified in the BP-SERVICE-PROVIDER param in the Logical Network Configuration File (LCONF). The row with this name is the only one used by the online software.

Screen 1

SVPT screen 1 contains system information for the service provider. SVPT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  SERVICE PROVIDER      LLLL      YY/MM/DD  HH:MM      1 OF  1

Service Provider Name _____

      Last Customer ID

For the initial creation of the service provider, fill in

      Initial Last Customer ID _____

and add the row.      This row cannot be updated or deleted.

RECORD LAST CHANGED:      BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                        F12-HELP

```

Service Provider Name — The name of the service provider.

The value in this field must match the name specified in the BP-SERVICE-PROVIDER param in the LCONF. The row with this name is the only one used by the online software.

Field Length: 1–10 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: SVPT.SVC_PROVIDER_NAME

Last Customer ID — The last customer ID used when the Billpay Server process is automatically generating customer IDs for a logical network.

Field Length: System-protected
 Column Name: SVPT.LAST_CUST_ID

Initial Last Customer ID — The value to be used as a starting point when the BASE24-billpay system generates customer ID numbers. This field is used when the row is added. The value entered in this field becomes the value in the Last Customer ID field when the row is added.

Field Length: 1–19 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: Not applicable

ACI Worldwide Inc.

Section 12

Vendor Table (VNDR)

The Vendor Table (VNDR) is the master vendor list for the logical network, containing one row for each vendor in the system. Each row contains information specific to a particular vendor such as name, number, remittance information, and parameters for verifying customer account numbers.

Each vendor must have at least one branch defined in the Vendor Branch Table (VNDB). Vendors with multiple branches have the option of defining a VNDB row for each branch. Whether a vendor defines one branch or several, one branch must be designated as the main branch and one branch must be designated as the remittance branch; however, both designations can be given to the same branch. The main branch and remittance branch are designated in the VNDR.

A vendor branch number must be defined in a VNDB row before it can be used in a VNDR row. This is accomplished by performing the following steps:

1. Complete all necessary fields on VNDR screens 1 and 2 except the Main Branch Number and Remit Branch Number fields and add the row to the VNDR.
2. Obtain the value from the Vendor Number field on VNDR screen 1, place it in the Vendor Number field on VNDB screen 1, complete the remaining fields on VNDB screen 1, and add the row to the VNDB. Repeat this step for each vendor branch.
3. Obtain the value from the Branch Number field on VNDB screen 1 for the main branch and place it in the Main Branch Number field on VNDR screen 1. (The VNDR row is updated in step 4.)
4. Obtain the value from the Branch Number field on VNDB screen 1 for the remittance branch, place it in the Remit Branch Number field on VNDR screen 1, and update the VNDR row.

A VNDR row must not be deleted as long as it is identified in any of the following tables. However, the BASE24 system does not prevent an operator from deleting a VNDR row that is still being used.

- The Bank Table identifies the VNDR row used with the BASE24-billpay Billing Application, which is an add-on to the BASE24-billpay product for online extraction of customer service fees.
- The Customer Vendor Table identifies each VNDR row used by a customer.
- The Customer Vendor Summary Table contains the total payments paid to each vendor by a customer during a calendar year.
- The Future Table is used to warehouse future transactions for vendors.
- The History Table contains BASE24-billpay vendor payments processed by the Billpay Server process or the Scheduled Transaction Initiator process.
- The Payment Summary Table contains the total amount and number of payments to each vendor by remittance type.
- The Recurring Table is used to warehouse recurring payments for vendors.
- The Vendor Branch Table identifies the branches associated with a VNDR row.

The key to the VNDR is the value in the Vendor Number field. This key must be unique when a row is added and cannot be changed when a row is updated. One index is defined for the Vendor Name and another index is defined for the Status and Prenote Date fields.

Screen 1 Function Keys

The use of two function keys varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column of information below shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys.

Key	Description
F2	Read — Cursor position is considered when determining which row is read, as follows: • Rows are accessed according to the value in the Vendor Number field when the cursor is located in any field other than the Vendor Name field. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field.
F6	Read Next — Cursor position is considered when determining which row is read next, as follows: • Rows are accessed according to the value in the Vendor Number field when the cursor is located in any field other than the Vendor Name field. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field.

Screen 1

VNDR screen 1 contains remittance and verification status information for the vendor. VNDR screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  VENDOR                      LLLL      YY/MM/DD  HH:MM      1 OF  2

      Vendor Name _____
      Vendor Number _____
      Vendor Type P (P=Public, L=Limited)
      Main Branch Number _____

      Remit: Branch Number _____
              Contact _____ yyymmdd
              Type ____ (ACH, CIT, CGP, Others) Prenote Date
              Report Type ____ (User-Defined)

      Effective Date Range:
              Begin Date _____ yyymmdd
              End Date _____

      Verify: Status I (I=Initial,V=Verified,F=Failed,P=Pend ACH,Others)
              Last Change _____ yyymmdd

RECORD LAST CHANGED:                      BY USER: _____,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP

```

Vendor Name — The name of the vendor. This value must be unique and cannot be blank.

Field Length: 1–30 alphanumeric characters
 Required Field: Yes, when adding and updating rows.
 Default Value: No default value
 Column Name: VNDR.VEND_NAME

Vendor Number — The number that identifies the vendor. This value is generated by the system and is unique.

Field Length: 1–9 numeric characters
 Required Field: Yes, when reading rows. This field must be set to 0 when adding rows.
 Default Value: No default value
 Column Name: VNDR.VEND_NUM

Vendor Type — A code identifying the type of vendor. Valid values are as follows:

L = Limited
P = Public

A public vendor is a vendor available for all customers and uses. A limited vendor is a vendor available for a limited number of customers and uses. A limited vendor is typically added when a customer wants to pay a person who is not a recognized business.

This field is for information purposes only. It has no impact on transaction processing.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: P
Column Name: VNDR.VEND_TYP

Main Branch Number — The number of the vendor branch considered to be the primary location for this vendor.

A vendor branch with this number must be defined in the Vendor Branch Table (VNDB) before the number can be used here. Refer to the instructions at the beginning of this section for additional information about defining branches.

Field Length: 1–4 numeric characters
Required Field: Yes (zeros are not displayed)
Default Value: No default value
Column Name: VNDR.MAIN_BR_NUM

Remit

The following four fields describe the remittance the vendor receives.

Branch Number — The number of the vendor branch considered to be the location where remittance is expected to be received.

A vendor branch with this number must be defined in the Vendor Branch Table (VNDB) before the number can be used here. Refer to the instructions at the beginning of this section for additional information about defining branches.

Field Length: 1–4 numeric characters
Required Field: Yes (zeros are not displayed)
Default Value: No default value
Column Name: VNDR.REMIT_BR_NUM

Contact — The name of the person responsible for remittance for the vendor. This person is normally at the remit branch.

Field Length: 1–22 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.REMIT_PERSON

Type — A code indicating the form of payment the vendor wants to receive. Valid values are as follows:

- ACH = The vendor receives payment in the form of an automated clearing house (ACH) transaction.
- CGP = The vendor receives payment in the form of a group-item check. A group-item check is one check for multiple payments. The Billpay Table Maintenance Server process uses this value if no value is entered before adding a row.
- CIT = The vendor receives payment in the form of a single-item check. A single-item check is one check for each payment.

User-defined values can be used for other forms of remittance.

The Remittance Generator process uses this code to create various remit files. Specifically, the first character of the code is used as the first letter of the name of the remit file. For check processing, the full remit type is used to determine whether a group-item check or a single-item check is to be produced; however, all check remittances go into the same check remit file.

If the Remit Type field is set to the value ACH, the value in the Verify Status field should be set to I.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.REMIT_TYP

Prenote Date — The date when a prenotification for this vendor was sent for ACH processing. This date is meaningful only for vendors with a remit type of ACH. The format used to display the date in this field is shown directly above the date.

Field Length: System-protected
Column Name: VNDR.PRENOTE_BUS_DATE

Report Type — A user-defined code identifying how the vendor is notified about the customer detail accompanying the actual remittance. Suggested values are as follows:

AA = ACH addenda
DK = Diskette
FX = Facsimile
HD = Hard copy printout

This field is for information only and is not currently used.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.REMIT_RPT_TYP

Effective Date Range

The following two fields define the dates during which this row can be used in processing. The format used to enter and display the dates in these fields is shown to the right of the Begin Date field.

Begin Date — The first date this row can be used in processing. If the field is left blank, the Billpay Table Maintenance Server process fills in the current date when the row is added or updated.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.BEG_DATE

End Date — The last date this row can be used in processing. If the field is left blank, this row does not expire.

If a vendor terminates its association with the service provider, all transactions that have not yet been carried out must be completed before associated VNDR entries can be deleted. In order to allow time for this to happen without additional activity being scheduled, the VNDR row is not normally deleted; however, this field can be set to a date that has already passed to make the row expire.

Field Length: 6–8 numeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.END_DATE

Verify

The following two fields identify the current verification status of a vendor.

Status — A code identifying the current verification status of a vendor. Reserved values are as follows:

- F = Failed. Failed verification; no transactions can be paid to this vendor.
- I = Initial. This value is entered when the vendor row is inserted into the database. No transactions can be paid to this vendor.
- P = Pending ACH. Pending ACH prenotification to complete; this value is used after the vendor's prenotification has been submitted for ACH processing. No transactions can be paid to this vendor.
- V = Verified. Transactions can be paid to this vendor.

The values normally used for table maintenance are I, F, and V. ACH processing uses the value P during prenotification processing of vendors who are paid through ACH processing. Other values may be entered; however, only the value V allows transactions to be initiated by a customer.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: I
Column Name: VNDR.VRFY

Last Change — The date and time of the most recent change to the Status field. The format used to display the date in this field is shown to the right of the field.

Field Length: System-protected
Column Name: VNDR.VRFY_GMT

Screen 2 Function Keys

The use of two function keys varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column of information below shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys.

Key	Description
F2	Read — Cursor position is considered when determining which row is read, as follows: • Rows are accessed according to the value in the Vendor Number field when the cursor is located in any field other than the Vendor Name field. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field.
F6	Read Next — Cursor position is considered when determining which row is read next, as follows: • Rows are accessed according to the value in the Vendor Number field when the cursor is located in any field other than the Vendor Name field. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field.

Screen 2

VNDR screen 2 contains specialized processing information for the vendor. VNDR screen 2 is shown below, followed by descriptions of its fields.

BASE24-BILLPAY
VENDOR
LLLL
YY/MM/DD
HH:MM
2 OF 2

Vendor Name

Vendor Number

Vendor Specific Data: Desc

Type

Warning Payment Limit

Audio Token

Govt ID

Vendor Inst ID

Vendor Account Number

Type

Account Mask Group

Default Budget Category

RECORD LAST CHANGED:

BY USER:

BASE24

NEW PAGE:

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F12-HELP

Vendor Specific Data

The following two fields describe vendor-specific data required by this vendor from a customer whenever a payment is made. The BASE24-billpay product presents the information in these fields to customer service representatives (CSRs) and remote banking endpoint device users when payments are being entered.

Desc — The text that appears on the CSR New Payment screen to describe a vendor-specific data entry field.

If this field contains a value, an entry is required in the Vend Specific Data field on the CSR New Payment screen. If this field is blank, an entry is not accepted in the Vend Specific Data field. The presence of an entry in this field also controls whether vendor-specific data is required from a remote banking endpoint device.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.VEND_SPECIFIC_DATA_DESC

Type — A user-defined code that is displayed on the CSR New Payment screen and is sent to a remote banking endpoint device to identify the type of vendor-specific data required.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.VEND_SPECIFIC_DATA_TYP

Warning Payment Limit — The maximum amount, in whole and fractional currency units, of a customer payment to this vendor. If a customer payment to this vendor exceeds this amount, the online BASE24-billpay software outputs an EMS warning message. A zero value means there is no limit.

Field Length: 1–20 numeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.WRN_PMT_LMT

Audio Token — The value given to a client device to retrieve data that is presented to the customer. The data retrieved is normally the vendor's name. This optional token is intended to allow a remote banking endpoint device to speak a vendor's name, but can be used by other input client devices.

The PIT-NAM-ALGO param in the Logical Network Configuration File (LCONF) must be set to the value Y before the BASE24-billpay product uses the value from this field to generate an audio token.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.AUDIO_TKN

Govt ID — The government identifier for this vendor. It is normally used as a tax identifier.

Field Length: 1–15 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.GOVТ_ID

Vendor Inst ID — The ID of the financial institution owning the vendor’s account to be credited for payments.

Field Length: 1–11 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.INST_ID

Vendor Account Number — The account number credited for payments made to this vendor. This account is located at the financial institution identified in the Vendor Inst ID field.

Field Length: 1–19 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.ACCT_NUM

Type — A code identifying the type of account credited for payments made to this vendor.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.ACCT_TYP

Account Mask Group — The name of the mask used to verify the account numbers customers have with this vendor.

If this field and the Account Mask Group field on Vendor Branch Table (VNDB) screen 1 contain values, the account mask identified in the Account Mask Group field on VNDB screen 1 is used to verify the account numbers of all customers using the vendor branch identified by that VNDB row.

If this field contains a value and the Account Mask Group field on VNDB screen 1 does not contain a value, the account mask identified in this field is used to verify the account numbers of all customers using the vendor branch identified by that VNDB row.

All account mask identifiers must already exist in the Mask Group field on Vendor Mask Table (VNDM) screen 1 before being used in this field or in the Account Mask Group field on VNDB screen 1.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.MASK_GRP

Default Budget Category — A code identifying the budget category to which this vendor is assigned. Any code used in this field must first be defined in the Vendor Budget Category Table (VBUD).

If the Budget Category field on Customer Vendor Table (CVND) screen 1 is left blank, the Billpay Table Maintenance Server process places the value from this field in the Budget Category field.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.DFLT_BGT_CAT

```

BASE24-BILLPAY  VENDOR                                LLLL          YY/MM/DD  HH:MM          3 OF  3

      Vendor Name _____
      Vendor Number _____

      Remit Information 1: _____
      Remit Information 2: _____

      Category Code: _____

      Vendor Information 1: _____
      Vendor Information 2: _____


RECORD LAST CHANGED:                                BY USER:          ,
*****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                  F12-HELP

```

Field Length:	1 – 20 alphanumeric characters
Required Field:	No
Default Value:	No default value
Column Name:	VNDR.USER REMIT INFO 1

Field Length:	1 – 20 alphanumeric characters
Required Field:	No
Default Value:	No default value
Column Name:	VNDR.USER_REMIT_INFO_2

Category Code — A code used to classify the industry in which the vendor is involved.

Field Length: 1 – 4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.CATEGORY_CODE

Vendor Information 1 — A field used to provide any additional information about the vendor.

Field Length: 1 – 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.USER_INFO_1

Vendor Information 2 — A field used to provide any additional information about the vendor.

Field Length: 1 – 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDR.USER_INFO_2

Section 13

Vendor Branch Table (VNDB)

The Vendor Branch Table (VNDB) contains information pertinent to a specific vendor branch such as street address, city, phone, contact information, and parameters for verifying customer account numbers.

Each vendor must have at least one branch defined in the VNDB. Vendors with multiple branches have the option of defining a VNDB row for each branch. Whether a vendor defines one branch or several, one branch must be designated as the main branch and one branch must be designated as the remit branch; however, both designations can be given to the same branch. The main branch and remit branch are designated in the Vendor Table (VNDR).

A vendor branch number must be defined in a VNDB row before it can be used in a VNDR row. This is accomplished by performing the following steps:

1. Complete all necessary fields on VNDR screens 1 and 2 except the Main Branch Number and Remit Branch Number fields and add the row to the VNDR.
2. Obtain the value from the Vendor Number field on VNDR screen 1, place it in the Vendor Number field on VNDB screen 1, complete the remaining fields on VNDB screen 1, and add the row to the VNDB. Repeat this step for each vendor branch.
3. Obtain the value from the Branch Number field on VNDB screen 1 for the main branch, place it in the Main Branch Number field on VNDR screen 1. (The VNDR row is updated in step 4.)
4. Obtain the value from the Branch Number field on VNDB screen 1 for the remittance branch, place it in the Remit Branch Number field on VNDR screen 1, and update the VNDR row.

A VNDB row must not be deleted as long as it is identified as a branch in a VNDR row or the vendor branch number in a Customer Vendor Table (CVND) row.

The key to the VNDB is a combination of the values in the Vendor Number and Branch Number fields. This key must be unique when a row is added and cannot be changed when a row is updated. An index is defined for the Vendor Number, Vendor Branch Name, Address, City, and State fields.

Screen 1 Function Keys

The use of two function keys varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column of information below shows the BASE24 keys. The second column describes the function that can be accomplished with these keys.

Key	Description
F2	Read — Cursor position is considered when determining which row is read, as follows: • Rows are accessed according to values in the Vendor Number and Branch Number fields when the cursor is located in any field other than the Vendor Name field. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field. The first branch is displayed for the vendor.
F6	Read Next — Cursor position is considered when determining which row is read next, as follows: • Rows are accessed according to values in the Vendor Number and Branch Number fields when the cursor is located in any field other than the Vendor Name field. Additional branches are displayed for the current vendor. • Rows are accessed according to the value in the Vendor Name field when the cursor is located in the Vendor Name field. The first branch is displayed for each vendor.

Screen 1

VNDB screen 1 contains information for each vendor branch location. VNDB screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  VENDOR BRANCH          LLLL          YY/MM/DD  HH:MM      1 OF  1

Vendor Number _____ or Vendor Name _____
Branch Number _____

Vendor Branch Name _____
Address _____
City _____
State __ Postal Code _____
Country ____ County ____

Contact _____
Phone _____
Fax Phone _____
Data Comm Phone _____

Account Mask Group _____

RECORD LAST CHANGED:                BY USER:                ,
***** BASE24 *****
NEW PAGE:                FILE DESTINATION:                NEW LOGICAL NETWORK ID:
                                F12-HELP

```

Vendor Number — The number that identifies the vendor. The value in this field links the branch in this row to the vendor and must match a vendor number that already exists in the Vendor Table (VNDR).

The Vendor Number field or Vendor Name field must be used for reading a VNDB row.

Field Length: 1–9 numeric characters
 Required Field: Yes, if the Vendor Name field is blank.
 Default Value: No default value
 Column Name: VNDB.VEND_NUM

Vendor Name — The name of the vendor. The value in this field links the branch in this row to the vendor and must match a vendor name that already exists in the VNDR.

This field is for perusal purposes only and can be used instead of the Vendor Number field for reading the VNDB. The value in this field is used to display the first branch row for the vendor. Subsequent reads will display the first branch for the next vendor, skipping over any additional branches for the current vendor. Refer to the “Screen 1 Function Keys” discussion earlier in this section for additional information.

Field Length: 1–30 alphanumeric characters
Required Field: Yes, if the Vendor Number field is blank.
Default Value: No default value
Column Name: VNDR.VEND_NAME

Branch Number — A number that identifies the branch. This value must be unique for the vendor and cannot be zero.

Leading zeros are not displayed in this field; so, a field that appears to be blank actually contains an invalid value.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: VNDB.BR_NUM

Vendor Branch Name — A free-format field displayed on customer support representative (CSR) screens to identify the name of the vendor branch.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.VEND_BR_NAME

Address — The mailing address or street address of the vendor branch.

Field Length: 2 fields of 1–30 alphanumeric characters each
Required Field: No
Default Value: No default value
Column Names: VNDB.ADDR_1
VNDB.ADDR_2

City — The city in which the vendor branch is located.

Field Length: 1–25 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.CITY

State — A code for the state in which the vendor branch is located.

The U.S. state codes are based on standards described in the 1988 ANSI X3.38 standard, *Identification of the States, the District of Columbia, and the Outlying and Associated Areas of the United States for Information Interchange*.

An operator also can enter a value other than an ANSI code.

Field Length: 1–2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.ST

Postal Code — The postal code of the vendor branch.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.POSTAL_CODE

Country — A code for the country in which the vendor branch is located.

The country codes are available in the 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*.

An operator also can enter a value other than an ISO code.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.CNTRY

County — A code indicating the county in which the vendor branch is located.

The U.S. county and county equivalent codes are based on standards described in the 1988 ANSI X3.31 standard, *Structure for the Identification of the Counties and County Equivalents of the United States and its Outlying and Associated Areas for Information Interchange*.

An operator also can enter a value other than an ANSI code.

Field Length: 1–3 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.CNTY

Contact — The name of the contact person at the vendor branch.

Field Length: 1–22 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.CONTACT_PERSON

Phone — The business phone number for the vendor branch.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.PHN

Fax Phone — The fax phone number for the vendor branch.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.PHN_FAX

Data Comm Phone — The data communication phone number for data transmission with the vendor branch, if applicable.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.PHN_COM

Account Mask Group — The name of the mask used to verify the account numbers customers have with this vendor branch.

If this field contains a value, the account mask identified in this field is used to verify the account numbers of all customers using this vendor branch. If this field does not contain a value, the account mask identified in the Account Mask Group field on VNDR screen 1 is used to verify the account numbers of all customers using this vendor branch.

All account mask identifiers must already exist in the Mask Group field on Vendor Mask Table (VNDM) screen 1 before being used in this field or in the Account Mask Group field on VNDR screen 1.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.MASK_GRP

Screen 2

VNDB screen 2 contains remittance information and additional information about the vendor branch location. VNDB screen 2 is shown below, followed by descriptions of its fields.

BASE24-BILLPAY
VENDOR BRANCH
LLLL
YY/MM/DD
HH:MM
2 OF 2

Vendor Number _____ or Vendor Name _____
Branch Number _____

Remit Information 1 _____
Remit Information 2 _____

Vendor Branch Information 1 _____
Vendor Branch Information 2 _____

RECORD LAST CHANGED:
BY USER: ,

BASE24

NEW PAGE:
FILE DESTINATION:
NEW LOGICAL NETWORK ID:

F12-HELP

Remit Information 1 — Specific information about the remittance that is required by the vendor. The information is included in the remittance file produced for the vendor’s remittance type.

Field Length:
1 – 20 alphanumeric characters

Required Field:
No

Default Value:
No default value

Column Name:
VNDB.USER_REMIT_INFO_1

Remit Information 2 — Specific information about the remittance that is required by the vendor. The information is included in the remittance file produced for the vendor’s remittance type.

Field Length: 1 – 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.USER_REMIT_INFO_2

Vendor Information 1 — A field used to provide additional information about the vendor.

Field Length: 1 – 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.USER_INFO_1

Vendor Information 2 — A field used to provide additional information about the vendor.

Field Length: 1 – 20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDB.USER_INFO_2

Section 14

Vendor Budget Category Table (VBUD)

The Vendor Budget Category Table (VBUD) permits BASE24-billpay system owners to associate vendors with a general category for reporting purposes. The description associated with a budget category code appears on table maintenance screens, customer service representative (CSR) screens, and the Customer Vendor Year End Summary report. All budget categories must be defined in the VBUD before they can be used on these screens or report.

A budget category code can be entered in the Customer Vendor Table (CVND) or Vendor Table (VNDR) to group vendors by type or purpose. For example, three groups could be financial institution, utility, and retail. As an alternative, the CVND could have groups that are more specific. For example, electricity, gas, and telephone groups could be used instead of utility.

The key to the VBUD is the value in the Budget Category field. This key must be unique when a row is added and cannot be changed when a row is updated.

A VBUD row must not be deleted as long as its budget category is used in the CVND or VNDR.

Screen 1

VBUD screen 1 contains information that associates vendors with a general category for reporting purposes. VBUD screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-BILLPAY  BUDGET CATEGORY      LLLL      YY/MM/DD  HH:MM      1 OF  1

Budget Category ____
Description _____

RECORD LAST CHANGED:                BY USER:                ,
***** BASE24 *****
NEW PAGE:                FILE DESTINATION:                NEW LOGICAL NETWORK ID:
                                F12-HELP

```

Budget Category — A user-defined code that identifies the budget category. This field cannot be blank.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: VBUD.BGT_CAT

Description — A free-format description of the budget category. This value appears on table maintenance screens, CSR screens, and one report to provide additional descriptive information about the category.

Field Length: 1–30 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Column Name: VBUD.BGT_DESC

Section 15

Vendor Mask Table (VNDM)

The Vendor Mask Table (VNDM) contains edit masks for verifying the account numbers that customers have with vendors. These masks are used when the account numbers are first entered.

The VNDM contains a row for each mask group and account mask combination in the BASE24-billpay system. Any number of vendors or vendor branches can use the same VNDM row.

The edits that can be configured in the VNDM are performed in the following order:

1. Account number minimum and maximum length check
2. Account mask matching
3. User-defined algorithm check

All edits are performed; however, the account mask and algorithm edits are considered optional because they can be configured to always be successful. If any edit is performed unsuccessfully, the remaining edits are not performed and the account number is rejected. If all edits are successful, the account number is accepted.

The masks defined in the VNDM can be used at the vendor level, the vendor branch level, or a combination of the two levels. The mask for a vendor is defined in the Account Mask Group field on Vendor Table (VNDR) screen 2 and the mask for a vendor branch is defined in the Account Mask Group field on Vendor Branch Table (VNDB) screen 1. When a vendor has a mask defined, a vendor branch without its own mask defined uses the mask defined for the vendor. If a vendor branch has its own mask defined, the vendor branch uses its own mask instead of the mask defined for the vendor. If all branches for a vendor use the same mask, only the vendor mask needs to be defined.

A VNDM row must not be deleted as long as it is identified as the mask in a VNDR row or VNDB row.

The key to the VNDM is a combination of the values in the Mask Group and Account Mask fields. This key must be unique when a row is added and cannot be changed when a row is updated.

Screen 1

VNDM screen 1 is used to define the edit checks performed on a customer account number when it is first entered. VNDM screen 1 is shown below, followed by descriptions of its fields.

BASE24-BILLPAY
VENDOR MASK
LLLL
YY/MM/DD
HH:MM
1 OF 1

Mask Group

User Check Number

Minimum Account Length

Maximum Account Length

Account Mask:

1

2

3

4

5

6

7

123456789012345678901234567890123456789012345678901234567890

Comment:

Help Text:

RECORD LAST CHANGED:

BY USER:

***** BASE24 *****

NEW PAGE:

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F12-HELP

Mask Group — The name of the mask that is used to verify customer account numbers. The combination of values in the Mask Group and Account Mask fields must be unique.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Column Name: VNDM.MASK_GRP

Minimum Account Length — The smallest number of characters the account number can contain. This value cannot be zero and must be less than or equal to the value in the Maximum Account Length field. The edit that uses this value is performed before the account masking or user-defined algorithms are checked.

Field Length: 1–2 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: VNDM.MIN_LEN

Maximum Account Length — The greatest number of characters the account number can contain. This value cannot be zero and must be greater than or equal to the value in the Minimum Account Length field. The edit that uses this value is performed before the account masking or user-defined algorithms are checked.

Field Length: 1–2 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: VNDM.MAX_LEN

User Check Number — A number that identifies a user-defined algorithm used to analyze the account number a customer has with a vendor. The edit that uses this value is performed after account number lengths or account masking are checked. Valid values are as follows:

0 = The account number is considered valid without being analyzed (default value).

Note: This value does not appear in the User Check Number field.

1–50 = The account number is analyzed with the user-defined algorithm identified by this value. The value in this field represents the numeric value in a CASE statement in the software into which the user-defined algorithm is inserted. The standard BASE24-billpay product does not have any account number algorithms.

51–9999 = The account number is considered invalid without being analyzed.

Note: Numbers between 51 and 9999 can be used if the CASE statement is changed to recognize them.

Field Length: 1–4 numeric characters
Required Field: No
Default Value: No default value
Column Name: VNDM.USER_CK_NUM

Account Mask — An edit mask that is used to analyze the account number a customer has with a vendor. The combination of values in the Mask Group and Account Mask fields must be unique. The edit that uses this value is performed after account lengths are checked and before a user-defined algorithm is checked.

The edit mask may contain combinations of the following characters to represent the valid format of an account number:

- A = Matches any alphabetic character (A through Z).
- X = Matches any alphanumeric character (A through Z, 0 through 9).
- 9 = Matches any digit (0 through 9).
- ? = Matches any single character.
- * = Matches any number of characters (including none).
- “text” = Matches *text*, where *text* is the group of characters being matched. Since single quotation marks indicate where the text being matched begins and ends, use two quotation marks together to represent a quotation mark that appears in the text being matched.

The following table contains examples of possible account masks and account numbers that match each mask:

Example	Account Masks	Matching Account Numbers
1	“AX”AA999??*	AXZZ123/-15 AXPQ921(Q) AXAB45689
2	“ABC”“DE”9	ABC”DE0 through ABC”DE9
3	A9A99	X1B23 R5T76
4	All blanks	All account numbers

In example 1, the characters in the first nine positions of the account number must be AX, two alphabetic characters, three numeric characters, and two characters of any kind. The asterisk (*) in the mask permits the remaining positions of the account number to contain any number of additional characters. The account number must have at least nine characters.

In example 2, the characters in the first six positions of the account number must be ABC”DE and the seventh position of the account number must contain a number. The two quotation marks between the C and D in the account mask indicate a single quotation mark in the text. Since the account mask does not contain an asterisk (*), the account number must be seven characters in length.

In example 3, the characters in the first and third positions of the account number must be letters and the characters in the second, fourth, and fifth positions of the account number must be numbers. Since the account mask does not contain an asterisk (*), the account number must be five characters in length.

In example 4, all account numbers match because the account mask is all blanks.

Field Length: 1–70 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDM.ACCT_MASK

Comment — An information-only field that can be used to describe the purpose of the account mask.

Field Length: 1–78 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: VNDM.CMNT

Help Text — A free-format, information-only field that can be used to provide additional information.

Field Length: 4 lines of 1–78 alphanumeric characters each
Required Field: No
Default Value: No default value
Column Name: VNDM.HELP_TEXT

Index

A

Access to BASE24-billpay tables, [1-3](#)

Action codes

Bank Notice Table (BKNT), [3-1](#)

Response Text Table (RTXT), [9-1](#)

Retry Table (RTRY), [10-1](#)

Archive program

effective date ranges, [1-7](#)

History Table (HIST), [5-2](#)

B

BANK

see Bank Table (BANK)

Bank Branch Table (BKBR)

introduction, [2-1](#)

screen 1, [2-3](#)

setup guidelines, [2-1](#)

Bank Notice Table (BKNT)

introduction, [3-1](#)

screen 1, [3-2](#)

Bank Table (BANK)

screen 1, [1-2](#)

setup guidelines, [2-1](#)

Bank Transaction Advice Table (BKAV)

introduction, [4-1](#)

screen 1, [4-2](#)

BASE24 Virtual Menu, [1-3](#)

BASE24-billpay Billing Application, [1-2](#), [6-1](#)

BASE24-billpay tables, [1-2](#)

Billpay Product Menu, [1-3](#)

BKAV

see Bank Transaction Advice Table (BKAV)

BKBR

see Bank Branch Table (BKBR)

BKNT

see Bank Notice Table (BKNT)

Budget categories

Customer Vendor Table (CVND), [7-6](#)

introduction, [14-1](#)

Vendor Budget Category Table (VBUD), [14-2](#)

Vendor Table (VNDR), [12-14](#)

C

CBPT

see Customer Billpay Table (CBPT)

Cleanup Configuration Table (CLPT)

introduction, [5-1](#)

screen 1, [5-7](#)

screen 1 function keys, [5-6](#)

Cleanup program

BASE24-billpay tables, [5-3](#)

effective date ranges, [1-7](#)

CLPT

see Cleanup Configuration Table (CLPT)

Configuration guidelines

see Setup guidelines

Cursor position for reading rows

Cleanup Configuration Table (CLPT), [5-6](#)

Vendor Branch Table (VNDB), [13-3](#)

Vendor Table (VNDR), [12-3](#), [12-10](#)

Customer Billpay Table (CBPT)

introduction, [6-1](#)

screen 1, [6-2](#)

Customer Vendor Table (CVND)

introduction, [7-1](#)

screen 1, [7-3](#)

screen 1 function keys, [7-2](#)

CVND

see Customer Vendor Table (CVND)

E

Edit masks

see Masks

Effective date range

Bank Notice Table (BKNT), [3-3](#)

Customer Vendor Table (CVND), [7-5](#)

description of, [1-7](#)

Vendor Table (VNDR), [12-7](#)

F

File access, [1-3](#)

Function keys

- Cleanup Configuration Table (CLPT) screen 1, [5-6](#)
- Customer Vendor Table (CVND) screen 1, [7-2](#)
- F13 use, [1-6](#)
- standard use, [1-6](#)
- Vendor Branch Table (VNDB) screen 1, [13-3](#)
- Vendor Table (VNDR) screen 1, [12-3](#)
- Vendor Table (VNDR) screen 2, [12-10](#)

H

HIST

- see* History Table (HIST)

History Table (HIST)

- introduction, [8-1](#)
- screen 1, [8-2](#)
- screen 2, [8-8](#)

I

IDF

- see* Institution Definition File (IDF)

Institution Definition File (IDF), [2-1](#)

ITLF

- see* ITS Transaction Log File (ITLF)

ITS Transaction Log File (ITLF), [4-1](#)**L**

LCONF

- see* Logical Network Configuration File (LCONF)

Logical Network Configuration File (LCONF)

- BP-ARCHIVE-GROUP param, [5-2](#), [5-8](#)
- BP-CLEANUP-GROUP param, [5-5](#), [5-8](#)
- BP-DATE-FORMAT param, [1-8](#)
- BP-SERVICE-PROVIDER param, [11-1](#)
- LGNT-COUNTRY-ABBR param, [1-9](#)
- OMF assign, [1-8](#)
- OMF-AUDIT param, [1-9](#)
- PIT-NAM-ALGO param, [12-12](#)

M

Masks

- introduction, [15-1](#)
- Vendor Branch Table (VNDB), [13-8](#)
- Vendor Mask Table (VNDM), [15-5](#)
- Vendor Table (VNDR), [12-13](#)

R

Response Text Table (RTXT)

- introduction, [9-1](#)
- screen 1, [9-2](#)

Retry Table (RTRY)

- introduction, [10-1](#)
- screen 1, [10-2](#)

RTRY

- see* Retry Table (RTRY)

RTXT

- see* Response Text Table (RTXT)

S

Service Provider Table (SVPT)

- introduction, [11-1](#)
- screen 1, [11-2](#)

Setup guidelines

- Bank Branch Table (BKBR), [2-1](#)
- Bank Table (BANK), [2-1](#)
- Vendor Branch Table (VNDB), [13-1](#)
- Vendor Table (VNDR), [12-1](#)

Structured Query Language (SQL), [1-4](#)

SVPT

- see* Service Provider Table (SVPT)

TTransient condition, [10-3](#)**V**

VBUD

- see* Vendor Budget Category Table (VBUD)

Vendor Branch Table (VNDB)

- introduction, [13-1](#)
- screen 1, [13-4](#)
- screen 1 function keys, [13-3](#)
- screen 2, [13-9](#)
- setup guidelines, [13-1](#)

Vendor Budget Category Table (VBUD)

- introduction, [14-1](#)
- screen 1, [14-2](#)

Vendor Mask Table (VNDM)

- introduction, [15-1](#)
- screen 1, [15-3](#)

Vendor Table (VNDR)

- introduction, [12-1](#)
- screen 1, [12-4](#)
- screen 1 function keys, [12-3](#)
- screen 2, [12-11](#)
- screen 2 function keys, [12-10](#)
- screen 3, [12-15](#)
- setup guidelines, [12-1](#)

VNDB

- see* Vendor Branch Table (VNDB)

VNDM

- see* Vendor Mask Table (VNDM)

VNDR

- see* Vendor Table (VNDR)