



BASE24[®]

Core Files and Tables Maintenance Manual

© 2000 by ACI Worldwide Inc. All rights reserved.

All information contained in this document is confidential and proprietary to ACI Worldwide Inc. This material is a trade secret and its confidentiality is strictly maintained. Use of any copyright notice does not imply unrestricted or public access to these materials. No part of this document may be photocopied, electronically transferred, modified, or reproduced in any manner without the prior written consent of ACI Worldwide Inc.

ACI, BASE24, BASE24 Remote Banking, BASE24-atm, BASE24-billpay, BASE24-from host maintenance, BASE24-telebanking, and NET24-XPNET are trademarks or registered trademarks of ACI Worldwide Inc., Transaction Systems Architects, Inc., or their subsidiaries.

Other companies' trademarks, service marks, or registered trademarks and service marks are trademarks, service marks, or registered trademarks and service marks of their respective companies.

Print Record

07/2000, Version 4 (Reissue)

11/1998, Version 3 (Reissue)

07/1997, Version 2 (Reissue)

01/95, Version 1 (New)

Contents

Preface	ix
Conventions Used in this Manual	xv
Section 1	
Introduction	1-1
BASE24 Core Files, Tables, and Functions	1-2
BASE24 Base Files and Tables	1-4
File and Table Access	1-5
Enscribe File Record Access	1-6
SQL Table Row Access	1-7
Full-File SQL Table Refresh	1-9
Function Keys	1-10
Help Screens	1-11
Section 2	
Account Type Table File (ATT)	2-1
Naming Account Types	2-2
Screen 1	2-3
Section 3	
Customer Allowed Transaction Table (CATT)	3-1
Default CATT Rows	3-2
Customized CATT Rows	3-2
Transaction Dependencies	3-3
Inquiry Transactions	3-4
Default CATT Table	3-5
Screen 1 Function Keys	3-25
Screen 1	3-27

Section 4

Customer Service Representative Control (CSRC)	4-1
---	------------

Section 5

Customer Table (CSTT)	5-1
Customer/Account Relation Table (CACT)	5-2
Customer/Personal ID Relation Table (CPIT)	5-4
Default Financial Institution Rows	5-5
Screen 1 Function Keys	5-6
Screen 1	5-8
Screen 2 Function Keys	5-18
Screen 2	5-22
Screen 3 Function Keys	5-28
Screen 3	5-31

Section 6

File Control File (FCF)	6-1
Screen 1	6-2

Section 7

Institution Routing Configuration File (IRCF)	7-1
Screen 1	7-3

Section 8

Interface Security File (ISF)	8-1
Field Naming Conventions	8-3
Screen 1	8-4
Screen 2	8-13
Screen 3	8-19
Screen 4	8-24

Section 9

Internal Message Translation File (IMTF)	9-1
Authorization Destination Configuration	9-2
Source Validation Configuration	9-3
Screen 1	9-4

Section 10

ITS Transaction Log File (ITLF)	10-1
Summary Screen Function Keys	10-3
Paging Forward or Backward	10-5
ITLF Summary Screen	10-6
Perusing the ITLF by Customer ID	10-6
Perusing the ITLF by Account Number	10-10
Detail Screen Function Keys	10-11
Detail Screen Fields	10-13
Transaction Identification Information	10-15
Acquirer and Issuer General Information	10-20
Issuer Advice and Routing Information	10-25
Reason Codes, Original Data, and PIN Change Information	10-29
Performance Timer Information	10-35
Point of Service Information	10-37
Backup Account Information	10-44
Transaction Amounts and Currency Conversion Fee Information	10-46
Refresh Information	10-51
Miscellaneous Additional Data	10-54
Acquirer-Dependent Data	10-55
Authorization-Dependent Data	10-56
Advice 1-Dependent Data	10-57
Advice 2-Dependent Data	10-58
BASE24-billpay Transaction Data	10-59
External Acquirer Dependent Data	10-63
External Authorizer Dependent Data	10-64

Section 11

Log Configuration File (LCF)	11-1
Screen 1 Function Keys	11-2
Screen 1	11-3
Screen 2 Function Keys	11-5
Screen 2	11-6

Section 12

Personal Information Table (PIT)	12-1
Default Financial Institution Rows	12-3
Screen 1 Function Keys	12-4
Screen 1	12-6
Screen 2 Function Keys	12-13
Screen 2	12-16

Section 13

Processing Code Definition File (PCDF)	13-1
Default PCDF Records	13-3
Common Field Values	13-4
Routing Restrictions	13-4
Transaction Dependencies	13-6
Default PCDF Table	13-7
Screen 1 Function Keys	13-30
Screen 1	13-31

Section 14

Transaction History Configuration File (THCF)	14-1
Screen 1 Function Keys	14-2
Screen 1	14-3
Screen 2 Function Keys	14-6
Screen 2	14-7

Section 15

Transaction Type By Source Code Table (TTSC)	15-1
Default TTSC Rows	15-2
Screen 1 Function Keys	15-6
Screen 1.	15-9

Section 16

VRU Configuration Data (VCD)	16-1
Screen 1.	16-3
Screen 2.	16-12
Screen 4.	16-19
Screen 9 Function Keys	16-27
Screen 9.	16-28
Screen 18.	16-30

Index	Index-1
------------------------	----------------

Index by Field Name.	Index-5
-------------------------------------	----------------

Index by Data and Column Name	Index-11
--	-----------------

ACI Worldwide Inc.

Preface

This manual describes the BASE24 CRT screens that access the BASE24 core files and tables. BASE24 core files and tables are accessed from the CORE entry on the Virtual Menu and consist of the files and tables that are used with BASE24 core objects. The BASE24-telebanking and BASE24-billpay products are the only integrated transaction services (ITS) core applications at the present time. ITS is ACI's implementation of an object-oriented programming environment. Integrated servers are object-oriented processes running in the ITS environment that perform application functions. Core objects are those objects that specifically perform application functions. Additional objects exist in the ITS environment that perform functions generic to all object-oriented processes or specific to integrated endpoints.

The information in this manual enables users to enter and update records and rows in the BASE24 core files and tables, respectively. The screen descriptions include information about the purpose of the fields on the screen, the codes that can be placed in these fields, and the default values and lengths.

Audience

ACI prepared this publication for distribution to institution personnel responsible for updating and maintaining the BASE24-telebanking and BASE24-billpay databases.

Prerequisites

Persons using this manual should be familiar with the ***BASE24 CRT Access Manual*** before reading this manual. The ***BASE24 CRT Access Manual*** includes information about logging on to BASE24, accessing the appropriate screens, and using function keys.

Additional Documentation

The BASE24 documentation set is arranged so that each manual presents a topic or group of related topics in detail. When one manual presents a topic that has already been covered in detail in another manual, the topic is summarized and the reader is directed to the other manual for additional information. Information has been arranged in this manner to be more efficient for readers who do not need the additional detail and at the same time provide the source for readers who require the additional information. This manual contains references to the following BASE24 publications:

- The ***BASE24 Base Files Maintenance Manual*** describes the screens used to maintain the files and tables that are shared among several BASE24 products.
- The ***BASE24 CRT Access Manual*** includes information about logging on to BASE24, accessing the appropriate screens, and using function keys.
- The ***BASE24 IEP Configuration Manual*** contains information on how message-based routing is configured for an Integrated Endpoint process.
- The ***BASE24 ITS Kernel Configuration Manual*** contains information on how large messages are configured for a system.
- The ***BASE24 Refresh and Extract Operators Manual*** provides procedures for performing full-file refreshes of SQL tables.
- The ***BASE24 Remote Banking Transaction Processing Manual*** provides additional information on using alternate keys with the Customer Account Relation Table (CACT) and how the system differentiates among duplicate account numbers.
- The ***BASE24 Remote Banking Customer Service Support Manual*** contains customer service representative (CSR) screen formats and field descriptions.
- The ***BASE24-billpay Tables Maintenance Manual*** describes the screen used to maintain the Bank Transaction Advice Table (BKAV), which determines which BASE24-billpay transactions are optionally logged to the ITS Transaction Log File (ITLF).

In addition to the BASE24 publications, the manual contains references to the ***BASE24-XPNET Network Control Operations Guide*** for information on service-based routing.

The manual also contains references to the following American National Standards Institute (ANSI) and International Organization for Standardization (ISO) publications:

- The 1988 ANSI X3.38 standard, *Identification of the States, the District of Columbia, and the Outlying and Associated Areas of the United States for Information Interchange*, contains the U.S. state codes used on BASE24 file maintenance screens.
- The 1986 ANSI X9.19 standard, *Financial Institution Retail Message Authentication* contains a code identifying the algorithm used to generate message authentication codes (MACs).
- The 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*, contains the country codes used on BASE24 file maintenance screens.
- The ISO 4217 (1990) standard, *Codes for the Representation of Currencies and Funds*, contains the currency codes used on BASE24 file maintenance screens.
- The ISO 8583 (1993) standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*, contains the codes used on BASE24 file maintenance screens for message class, message reason, and point of service.

Software

This manual documents standard processing for release 1.3 of the BASE24-telebanking, BASE24-billpay, and BASE24-customer service/fraud control products.

Customer-specific code modifications (that is, CSMs) may result in processing that differs from the material presented in this manual. The customer is responsible for identifying and noting these changes.

Manual Summary

The following is a summary of the contents of this manual.

“Conventions Used in this Manual” follows this preface and describes notation and documentation conventions necessary to understand the information in the manual.

Section 1, “Introduction,” presents the files, tables, and functions specific to the BASE24-telebanking, BASE24-billpay, and BASE24-customer service/fraud control products, and to the file maintenance screens used to access them.

Section 2, “Account Type Table File (ATT),” describes the screen used to maintain the ATT. The ATT contains a record for each valid account type in the BASE24 integrated transaction services (ITS) network.

Section 3, “Customer Allowed Transaction Table (CATT),” describes the screen used to maintain the CATT. The CATT contains one row for each supported combination of FIID, customer profile, and processing code.

Section 4, “Customer Service Representative Control (CSRC),” introduces the function of the customer service representative (CSR) screens accessed from the CSRC entry on the Core Product Menu. Refer to the *BASE24 Remote Banking Customer Service Support Manual* for CSR screen and field descriptions.

Section 5, “Customer Table (CSTT),” describes the screens used to maintain the CSTT, the Customer/Account Relation Table (CACT), and optionally, the Customer/Personal ID Relation Table (CPIT).

Section 6, “File Control File (FCF),” describes the screen used to maintain the FCF. The FCF contains a version indicator that is used to identify the newest version of a file for refresh purposes when files are audited by the Tandem Transaction Monitoring Facility (TMF).

Section 7, “Institution Routing Configuration File (IRCF),” describes the screen used to maintain the IRCF. The IRCF is used by institutions to define the routing and authorization parameters for their transactions.

Section 8, “Interface Security File (ISF),” describes the screens used to maintain the ISF. The ISF contains the information and parameters required by integrated transaction services (ITS) interfaces for PIN encryption, PIN translation, message authentication, and dynamic key management.

Section 9, “Internal Message Translation File (IMTF),” describes the screen used to maintain the IMTF. The IMTF is used by the Internal Message Translation Interface object to map authorization destinations to symbolic process names and DPC numbers and to validate stations and processes from which messages are received.

Section 10, “ITS Transaction Log File (ITLF),” describes the screens used to access the ITLF. The ITLF contains a record for each transaction posted by a BASE24 Integrated Server process during a given business day.

Section 11, “Log Configuration File (LCF),” describes the screens used to access the LCF. The LCF controls the logging destination for each ITS object that logs information to the ITS Transaction Log File (ITLF).

Section 12, “Personal Information Table (PIT),” describes the screens used to maintain the PIT and, optionally, the Customer/Personal ID Relation Table (CPIT). The PIT contains one row for each customer associated with a primary customer account row in the Customer Table (CSTT).

Section 13, “Processing Code Definition File (PCDF),” describes the screens used to maintain the PCDF. The PCDF defines processing codes at the institution level.

Section 14, “Transaction History Configuration File (THCF),” describes the screens used to maintain the THCF. The THCF is used by the BASE24-telebanking product to determine which Transaction History File (THF) contains the information needed to authorize a transaction history inquiry.

Section 15, “Transaction Type By Source Code Table (TTSC),” describes the screen used to maintain the TTSC. The TTSC contains one row for each unique combination of source code and BASE24-telebanking or BASE24-billpay transaction type allowed at an inbound customer service representative (CSR) terminal.

Section 16, “VRU Configuration Data (VCD),” describes the screens used to configure the Remote Banking Standard Interface and the Customer Service Interface. The VCD screens are used to maintain the ITS Interface Configuration File (IFCF), Interface Station Table File (IST), and Address Table File (ADRT).

Readers can use the index by field name to locate information about a particular screen field and the index by data and column name to locate information about a particular field from a file or record structure or information about a particular column from a table.

Publication Identification

Two entries appearing at the bottom of each page uniquely identify this BASE24 publication. The publication number (for example, TB-AE000-02 for the ***BASE24 Core Files and Tables Maintenance Manual***) appears on every page to assist readers in applying updates to the appropriate manual. The publication date (for example, 07/2000 for July, 2000) identifies the last time material on a particular

page has been revised. This date can be used to verify that the reader has the most current information and is particularly helpful when dealing with HELP24 to answer operating questions.

The print record, located on the page immediately following the title page, is also helpful when verifying that a manual contains the most current information. An entry is added to the print record each time a BASE24 publication is modified in any way. Each print record entry includes the date of the change, a unique version number, and the type of change (new, update, reissue, or preliminary). Version 1 is assigned to a *new* manual. Later versions can be updates or reissues, depending on the changes being made. An *update* typically involves changes on a small number of pages throughout the manual. A *reissue* occurs when all pages of the manual are replaced because changes affect a large number of pages. A manual is identified as *preliminary* when it is released to customers on a limited basis, but it has not yet reached final form.

Conventions Used in this Manual

This section explains the different terminology used to describe remote banking devices and the screens used to maintain Enscribe files and Structured Query Language (SQL) tables. It also explains how field descriptions, unlabeled fields, and required blank characters are documented in this manual.

Remote Banking Endpoint Devices

This manual uses the term *remote banking endpoint device* to describe any device that acquires BASE24 Remote Banking transactions using the Remote Banking Standard Interface or the Customer Service Interface. The Customer Service Interface supports Pathway-based CSR terminals only. The Remote Banking Standard Interface supports any of the following devices: interactive voice response system (IVR), call center, screen phone, personal computer, third-party processor, kiosk, personal digital assistant, or the Internet.

When this manual refers to a device that communicates with BASE24 Remote Banking using message formats that conform to a particular interface standard, the term *<interface>-compliant device* is used, where *<interface>* is an acronym for the interface standard (e.g., RBSI for the Remote Banking Standard Interface). For example, dynamic key management is only supported for RBSI-compliant devices.

Enscribe Files and SQL Tables

Throughout this manual, specific terminology is used when discussing screens that access Enscribe files or SQL tables. For Enscribe files, the terms field, record, and file are used. For SQL tables, the analogous terms of column, row, and table are used, respectively.

Field Descriptions

Each field appearing on an Enscribe file maintenance screen or SQL table maintenance screen is listed by name and then described. Field descriptions briefly summarize the contents, purpose, and permissible values, as shown in the following examples taken from the Internal Message Translation File (IMTF) and the Personal Information Table (PIT).

Enscribe File Example

PROCESS NAME — The symbolic name of the nonobject-oriented process that communicates with the specified DPC. The symbolic name is assigned to a process in the XPNET environment.

Each pair of values in the PROCESS NAME and DPC NUMBER fields on this screen must have a matching pair of values in the HISF NAME and DPC NUMBER fields on screen 1 of a record in the Host Configuration File (HCF). Refer to the ***BASE24 Base Files Maintenance Manual*** for additional information regarding HCF screens.

For routing transactions to the XPNET Billpay Server process, this field must contain the symbolic name of the XPNET Billpay Server process or the name of a service if XPNET Billpay Server processes are defined to a service for service-based routing. For more information on service-based routing, refer to the ***NET24-XPNET Network Control Operations Guide***.

Wildcard characters can also be used in this field. A wildcard character (*) can be substituted in certain positions of the symbolic name. This enables the Integrated Authorization Server process to replace the asterisks with corresponding positions of its own symbolic name when selecting the ISO Host Interface process or XPNET Billpay Server process to which a message is to be forwarded. This feature allows for matching multiple Integrated Authorization Server processes to multiple ISO Host Interface processes or XPNET Billpay Server processes using a single record for each type of process. When wildcard characters are used, the symbolic name can have any number of leading asterisks, but can have no more than one trailing asterisk. If there are any asterisks in the process name, then the process name must start with an asterisk.

Examples: P1A^HISO1
***^HISO*
P1A^BPSV1
***^BPSV*
***^STI*

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: IMTF.PRO-NAM

SQL Table Example

PERSONAL ID — The identifier for this PIT row. The identifier can be prescribed by the service provider or chosen by the customer, but must be unique within the PIT. For example, this field could contain an employee number for a business customer. For an individual customer, this field could contain the individual's social security number or the customer ID.

When a new customer is added using the customer add transaction from the CSR Customer Signup screen or an RBSI-compliant device, the personal ID is always set to the value of the customer ID.

Field Length: 1–19 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: PIT.PRSNL_ID

Explanation

Each field description is completed by one or more of the following items of information:

Item	Description
Example	Illustrates a possible entry for the field to further clarify the value or values that can be entered.

Item	Description
Field Length	Specifies the size of the field and the type of characters that can be entered. This length refers to the field and valid values for the file maintenance screen, not the field in the DDLs. Possible values are alphabetic, alphanumeric, hexadecimal, and numeric. The term <i>alphanumeric</i> includes all alphabetic, numeric, and special characters that can be entered from a keyboard without using a control sequence. The term <i>hexadecimal</i> includes all numbers and the letters A through F. When a field value cannot be modified by the operator, the field length is System-protected.
Occurs	Indicates the number of times the field can be displayed on the screen. This information is provided only when the field can be displayed multiple times.
Required Field	Specifies whether a value has to be entered in the field. Possible values are Yes and No. Some fields are required only under certain conditions. In this case, the entry is Yes, followed by the conditions that determine when the field is required.
Default Value	Specifies the value that is automatically placed in the field when the screen is first displayed or when the F8 key is pressed to clear the screen.
Data Name	Provides the DDL name associated with the field appearing on the screen. Data names are included in the documentation to assist in communicating screen and field issues to your technical staff. Note that screen data is not always stored in the BASE24 database as it appears on the screen or as it is described in the field description. If you need information on how screen data is actually stored, consult the DDLs.

Item	Description
Column Name	Provides the SQL column name associated with the field appearing on the screen. Column names are included in the documentation to assist in communicating screen and field issues to your technical staff. Note that screen data is not always stored in the BASE24 database as it appears on the screen or as it is described in the field description. If you need information on how screen data is actually stored, consult the DDLs or SQL table creation source file.

Unlabeled Fields on Screens

Angle brackets (< >) indicate an unlabeled field on a screen. An unlabeled field is a field that is present on a screen but is not preceded by an identifying literal label. For the purposes of documenting the field, a label has been assigned and appears inside the angle brackets. A multiple line unlabeled field is displayed as a shaded area and also has a label in angle brackets.

In the field descriptions for the screen, the unlabeled field appears according to its place on the screen and is identified by the same label.

Unlabeled fields are not included in the index by field name; they appear by subject in the main index.

Required Blank Spaces

Throughout this manual when discussing the impact of required blanks or spaces in entered field data, the ¢ symbol is used to denote a required blank character or space.

ACI Worldwide Inc.

Section 1

Introduction

This section provides an introduction to the files, tables, and functions specific to BASE24 core objects, and to the file and table maintenance screens and function keys used to access them.

Currently there are three object-oriented products that run in the integrated transaction services (ITS) environment and use core objects—BASE24-telebanking, BASE24-billpay, and BASE24-customer service/fraud control. While the BASE24-telebanking and BASE24-billpay products use the core files and tables extensively, the BASE24-customer service/fraud control product uses only the Internal Message Translation File (IMTF).

BASE24 Core Files, Tables, and Functions

The following BASE24 core files, tables, and functions can be accessed using file or table maintenance screens:

- Account Type Table File (ATT)
- Address Table File (ADRT)
- Customer/Account Relation Table (CACT)
- Customer Allowed Transaction Table (CATT)
- Customer/Personal ID Relation Table (CPIT)
- Customer Service Representative Control (CSRC)
- Customer Table (CSTT)
- File Control File (FCF)
- Institution Routing Configuration File (IRCF)
- Interface Security File (ISF)
- Interface Station Table File (IST)
- Internal Message Translation File (IMTF)
- ITS Interface Configuration File (IFCF)
- ITS Transaction Log File (ITLF)
- Log Configuration File (LCF)
- Personal Information Table (PIT)
- Processing Code Definition File (PCDF)
- Transaction History Configuration File (THCF)
- Transaction Type By Source Code Table (TTSC)

The Customer Service Representative Control function accesses the customer service representative (CSR) screens described in the ***BASE24 Remote Banking Customer Service Support Manual***. All other screens are described in the sections of this manual. CSR screens are accessed from the CSRC entry on the Core Product menu.

The Customer Table (CSTT) screens are used to maintain data in the CSTT, Customer/Account Relation Table (CACT), and Customer/Personal ID Relation Table (CPIT).

The Personal Information Table (PIT) screens are used to maintain data in the PIT and the CPIT.

Three of the files listed above are maintained from the VRU Configuration Data (VCD) screens. These screens are used to maintain data in the following core files:

- Address Table File (ADRT)
- Interface Station Table File (IST)
- ITS Interface Configuration File (IFCF)

BASE24 Base Files and Tables

The BASE24-telebanking and BASE24-billpay products use the following BASE24 base files and tables:

- Bank Table (BANK). This table is used by the BASE24-billpay product and can only be accessed using a function key from certain IDF screens.
- External Message File (EMF).
- Extract Configuration File (ECF).
- Host Configuration File (HCF).
- Institution Definition File (IDF).
- Key Authorization File (KEYA).
- Key File (KEYF).
- Positive Balance File (PBF).

Screens for base files and tables are described in the ***BASE24 Base Files Maintenance Manual***.

File and Table Access

All integrated transaction services (ITS) application-specific files, tables, and functions accessible to the user are listed on the Core Product Menu, which can be accessed from the BASE24 Virtual Menu. ITS applications are those ACI applications that use object-oriented programming, of which BASE24-telebanking, BASE24-billpay, and BASE24-customer service/fraud control are included. Each operator sees only the files, tables, and functions available to him or her based on the configuration of the BASE24 CRT access security files. A sample Core Product Menu listing all possible files, tables, and functions is shown below. The order that the files, tables, and functions are displayed for individual users is dependent on the order that the user received access to the files, tables, and functions in the security files.

Users can access a file, table, or function listed on the menu by placing the cursor beside an individual item and pressing the **F1** key or by entering the file, table, or function acronym in the FILE DESTINATION field and pressing the **F1** key. A more detailed explanation for accessing files and tables is provided in the ***BASE24 CRT Access Manual***.

Base files used by the BASE24-telebanking and BASE24-billpay products can be accessed from the Base Product Menu, which can also be accessed from the BASE24 Virtual Menu.

```

BASE24-ADMN  MENU                                LLLL      YY/MM/DD  hh:mm  01 OF 01
                                C O R E  P R O D U C T  M E N U

      ATT              CATT              CSRC              CSTT
      FCF              IMTF              IRCF              ISF
      ITLF             LCF              PCDF              PIT
      THCF             TTSC              VCD

```

```

***** BASE24 *****
      FILE DESTINATION:
F1-ENTER DATA  F10-PRINT  F12-HELP  F16-EXIT  SF16-LOGOFF

```

Enscribe File Record Access

Access to Enscribe file records is provided through the use of primary and alternate keys. For all types of Enscribe files, primary keys define the primary fields for which data must be supplied to read a particular record in a file. For key-sequenced Enscribe files, primary key fields are defined by the user or system designer using the Data Definition Language (DDL). For relative Enscribe files, the primary key is the relative record number. For entry-sequenced Enscribe files, the primary key is the record address maintained by Enscribe. In addition to the primary keys, alternate keys can also be used to access Enscribe file records. Alternate keys define an alternative set of fields that can also be used to read a particular record in a file. There is always only one primary key to a file, while there can be a limited number of alternate keys to provide alternative means of access.

Primary and alternate keys are used both when accessing file records from a file maintenance screen as well as when accessing file records from the BASE24 transaction processing software.

On file maintenance screens, the primary and alternate key fields for a file are always identified in the introductory text for the screen exactly as they appear on the screen. Valid values must be entered in each of the primary or alternate key fields when attempting to read a particular record from a file maintenance screen. When attempting to read the next record in a file, no data or only partial data can be entered in the key fields. If no data is entered in the key fields, the first record in the file is read. If partial data is entered, the next record in the file is read.

For BASE24 transaction processing software programs, including file maintenance requesters and servers, the Data Definition Language (DDL) field names associated with the primary and alternate key fields are used to access file records. The DDL field name(s) for each field appearing on a file maintenance screen is provided with the "Data Name(s):" caption in each field description. If a screen field does not have a corresponding Enscribe DDL field name, "Not applicable" appears after this caption.

SQL Table Row Access

Access to Structured Query Language (SQL) table rows is provided through the use of primary keys and indexes. For key-sequenced SQL tables, primary keys define the primary columns for which data must be supplied to read a particular row in a table. For relative SQL tables, the primary key is the relative row number. For entry-sequenced tables, the primary key is the row address maintained by SQL. In addition to primary keys, SQL tables can also use indexes to access table rows. Indexes define an alternative set of columns that can also be used to read a particular row or set of rows in a table.

Although SQL table rows can theoretically be accessed using any table row columns, primary keys and indexes provide the high performance data access capabilities required in an online transaction processing system. There is always only one primary key to a table, while there can be a limited number of indexes to provide alternative means of access. All defined indexes are included in the default configuration of SQL tables. Any unwanted indexes can be disabled when the SQL table database is installed, although this should only be done with extreme caution.

Primary keys and indexes are used both when accessing table rows from a table maintenance screen as well as when accessing table rows from the BASE24 transaction processing software.

On table maintenance screens, the primary key and indexed columns are always identified in the introductory text for the screen exactly as they appear on the screen. On table maintenance screens, fields on the screen map directly to table columns where the data entered in the screen field is stored. Valid values must be entered in each of the primary or indexed fields when attempting to read a particular row from a table maintenance screen. When attempting to read the next row in a table, no data or only partial data can be entered in the key or indexed fields. If no data is entered in the key or indexed fields, the first row in the table is read. If partial data is entered, the next row in the table is read.

For BASE24 transaction processing software programs, including table maintenance requesters and servers, the column names associated with the primary key and indexes are used to access table rows. The column name(s) for each field

appearing on a table maintenance screen is provided with the “Column Name(s):” caption in each field description. If a screen field does not have a corresponding SQL column name, “Not applicable” appears after this caption.

Warning: Although Tandem’s Nonstop SQL conversational interface (SQLCI) provided with the NonStop SQL product allows Tandem users to perform ad hoc queries or generate ad hoc reports from SQL tables, such use in a production system may have a detrimental impact on transaction processing performance. Therefore, the improvised use of SQLCI on production SQL tables should be severely restricted or prohibited, and should only be used when required for problem analysis.

Full-File SQL Table Refresh

Full-file refresh of the CACT, CPIT, CSTT, and PIT cannot be performed without system down-time. Therefore, full-file refresh of these SQL tables is only recommended at system installation.

For detailed procedures on performing full-file refresh of SQL tables, refer to the *BASE24 Refresh and Extract Operators Manual*.

Function Keys

The standard BASE24 function keys are used on core file and table maintenance screens. These function keys are described in the ***BASE24 Base Files Maintenance Manual*** and ***BASE24 CRT Access Manual***. When the use of these keys differs for the BASE24-telebanking, BASE24-billpay or BASE24-customer service/fraud control products, the differences are noted in the section of the manual dealing with the screen grouping to which they apply.

BASE24 products also provide an online Help screen which lists the function keys that apply on each screen. The Help screen is displayed by pressing the **F12** key.

Help Screens

BASE24 products provide online Help screens that list the function keys that apply on each screen. The Help screens are displayed by pressing the **F12** key.

Help screens are not available for the Logon screen or the Virtual Menu. However, the function keys that are available on these screens are listed at the bottom of the screens.

An example of a Help screen is shown below.

```
BASE24-CORE  PROCESSING CODE DEFN      LLLL      YY/MM/DD  hh:mm  01 OF 01
                PRODUCT ID: 14          ROUTE PROFILE: *****
STANDARD FILE MAINTENANCE FUNCTION FOR KEYS 6520/6530 (3270)
      F1 (ENTER) - VALIDATE DATA
      F2 (PF2)   - READ RECORD
      F3 (PF3)   - ADD RECORD
      F4 (PF4)   - DELETE RECORD
      F5 (PF5)   - UPDATE RECORD
      F6 (PF6)   - READ NEXT RECORD
      F7 (PF7)   - LOAD RECORDS
      F8 (PF8)   - CLEAR SCREEN
      F9 (PF9)   - UNLOAD RECORDS
     F10 (PF10)  - PRINT SCREEN
     F11 (PF11)  - PREVIOUS SCREEN
     F12 (PF12)  - DISPLAY HELP SCREEN
     F13 (PF13)  - CHANGE CURRENT LOGICAL NET
     F16 (PF16)  - EXIT OR GOTO FILE
    SF16 (PA2)   - LOGOFF
```

```
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
ANY FUNCTION KEY EXCEPT PF10, PF16, PA2 RETURNS.  PF10 PRINTS AND RETURNS
```

ACI Worldwide Inc.

Section 2

Account Type Table File (ATT)

The Account Type Table File (ATT) contains one record for each valid account type in the BASE24 integrated transaction services (ITS) network. Each ATT record contains an International Organization for Standardization (ISO) code in the ACCOUNT TYPE field and a corresponding description in the ACCOUNT TYPE NAME field.

Screens for BASE24 core object files and tables display the account type names defined in the ATT instead of account type codes. The DEFAULT ACCT TYPE field on Customer Table (CSTT) screen 1 is an example. The default value in this field is the name NONE instead of the code 00. Screens for the following core files and tables also display account type names from the ATT:

- Customer/Account Relation Table (CACT)
- Customer Allowed Transaction Table (CATT)
- Institution Routing Configuration File (IRCF)
- ITS Transaction Log File (ITLF)
- Processing Code Definition File (PCDF)

The value in the ACCOUNT TYPE field is the primary key to the ATT.

Naming Account Types

ACI provides a default set of ATT records with core objects. The ACCOUNT TYPE field description in this section identifies these default records.

Screens for shared BASE24 files such as the Positive Balance File (PBF) do not use the ATT. Instead, these screens use the codes in the PBF column of the table presented with the ACCOUNT TYPE field description in this section. If operators prefer to use the same account type codes on all screens, the values in the PBF column can be used instead of the names provided in the default ATT records.

For example, the savings account entry from the table presented with the ACCOUNT TYPE field description has the following information:

ACCOUNT TYPE		ACCOUNT TYPE NAME	Description
Default ATT	PBF		
10	11	SAV	Savings account

If the value in the ACCOUNT TYPE NAME field on the ATT screen is changed from SAV to 11, operators always use the value 11 to describe a savings account. If the value in the ACCOUNT TYPE NAME field on the ATT screen is SAV, operators use the value 11 in the ACCOUNT TYPE field on a PBF screen and the value SAV on CACT, CATT, CSTT, IRCF, ITLF, and PCDF screens.

With shared BASE24 file values in the ACCOUNT TYPE NAME field, operators use the same code on all screens to identify an account type. The disadvantage is having to use a numeric code for account types on the CACT, CATT, CSTT, IRCF, ITLF, and PCDF screens.

With default ATT values or other alphanumeric values in the ACCOUNT TYPE NAME field, operators can identify the account type without having to learn a numeric code. The disadvantage is having to use one code for account types on the shared BASE24 file screens and another code for account types on the CACT, CATT, CSTT, IRCF, ITLF, and PCDF screens.

```

BASE24-CORE  ACCOUNT TYPE TABLE          LLLL          YY/MM/DD  hh:mm  01 OF 01

ACCOUNT TYPE:                ACCOUNT TYPE NAME:

RECORD LAST CHANGED:                BY USER:                ,
***** BASE24 *****
NEW PAGE:                FILE DESTINATION:                NEW LOGICAL NETWORK ID:
                                F12-HELP

```

On behalf of the BASE24-telebanking and BASE24-billpay products, Integrated Authorization Server processes match each value in the ACCOUNT TYPE field of the ATT with an account type in the Positive Balance File (PBF). The PBF Account Type column in the table on the following page shows the PBF value that corresponds to each ATT value.

ACI provides a default ATT that contains a subset of these records. A check (✓) in the Default ATT column of the following table identifies a record that is included in the default ATT.

ACCOUNT TYPE		Default ATT	ACCOUNT TYPE NAME	Description
ATT	PBF			
00	Not applicable	✓	NONE	
10	11	✓	SAV	Savings accounts
1A	14		SAV1	
1B	15		SAV2	
1C	16		SAV3	
1D	17		SAV4	
1E	18		SAV5	
1F	19		SAV6	
20	01	✓	DDA	Demand deposit accounts
2A	02		DDA1	
2B	03		DDA2	
2C	04		DDA3	
2D	05		DDA4	
2E	06		DDA5	
2F	07		DDA6	
2G	08		DDA7	
2H	09		DDA8	

ACCOUNT TYPE		Default ATT	ACCOUNT TYPE NAME	Description
ATT	PBF			
30	31	✓	CR	Credit accounts
3A	33		CR1	
3B	34		CR2	
3C	35		CR3	
3D	36		CR4	
3E	37		CR5	
3F	38		CR6	
3G	39		CR7	
38	32	✓	LOC	Line of credit
58	13	✓	CD	Certificate
59	12	✓	IRA	Retirement account
90	21	✓	NOW	Interest-bearing checking account
9A	43	✓	CMRCL	Commercial loan
9B	41	✓	INSTL	Installment loan
9C	42	✓	MRTGL	Mortgage loan

Field Length: 2 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: ATT.PRIKEY.ACCT-TYP

ACCOUNT TYPE NAME — An abbreviated description of the account type. Refer to the table in the ACCOUNT TYPE field description for the ACCOUNT TYPE NAME entries in the default ATT and suggestions for additional ACCOUNT TYPE NAME entries.

Note: All entries in the ACCOUNT TYPE NAME field must be unique. If records are added to the ATT, each new record must have a description in the ACCOUNT TYPE NAME field that is not used in any existing ATT record.

Field Length:	1–6 alphanumeric characters
Required Field:	Yes
Default Value:	No default value
Data Name:	ATT.ALTKEY.ACCT-TYP-NAM

Section 3

Customer Allowed Transaction Table (CATT)

The Customer Allowed Transaction Table (CATT) contains one row for each supported combination of FIID, customer profile, and processing code.

Along with the Processing Code Definition File (PCDF), the CATT defines the transactions that can be performed by a customer. The PCDF contains one record for each supported combination of product ID, routing profile, and processing code. Transactions defined in the PCDF can be established at the customer level in the CATT. A transaction must be defined in both the CATT and PCDF before it can be performed by a customer.

The BASE24-telebanking and BASE24-billpay products include a CATT that contains rows for the full set of processing codes that the BASE24-telebanking and BASE24-billpay products support. This set of rows is known as the default CATT. The processing codes in the default CATT are presented in this section.

Information from the CATT is used in the customer extended memory table. Any time a change is made to the CATT, the customer extended memory table should be rebuilt using the Extended Memory Table Build utility and reallocated to objects that access the table using the EMT Warmboot command.

The values used in the ACCOUNT 1 TYPE and ACCOUNT 2 TYPE fields of the CATT must be defined in the ACCOUNT TYPE NAME field of the Account Type Table File (ATT).

The primary key to the CATT is the combination of values in the FIID, CUSTOMER PROFILE, and PROCESSING CODE fields.

Default CATT Rows

The Customer Allowed Transaction Table (CATT) defines the processing codes supported for each combination of FIID and customer profile.

At installation, the BASE24-telebanking and BASE24-billpay products include a full set of CATT rows with asterisks (****) in the FIID field, an entry of DEFAULT in the CUSTOMER PROFILE field, and a nonexpiring date in the END DATE field. A super user (that is, a user with a group number of 255 in his or her CRT access security record) can modify this full set, called the default CATT, by adding or deleting rows with specific processing code information. The rows provided in the default CATT are listed in the default CATT table provided later in this subsection.

Each Customer Table (CSTT) row has FIID and PROFILE fields that correspond with the FIID and CUSTOMER PROFILE fields on CATT screen 1. The FIID field on CSTT screen 1 always contains the FIID of the customer's financial institution.

The FIID field on CATT screen 1 can contain asterisks (****) or the FIID of the customer's financial institution. Asterisks in the FIID field on CATT screen 1 permit multiple financial institutions to use the same CATT rows for a customer profile. An FIID in the FIID field on CATT screen 1 restricts use of the CATT rows to a single financial institution. The BASE24-telebanking and BASE24-billpay products search for a CATT row with an FIID that matches the customer's FIID. If a CATT row with the customer's FIID cannot be found, the BASE24-telebanking and BASE24-billpay products search for a CATT row with an FIID of four asterisks.

Customized CATT Rows

Each customer defined in the CSTT can use the default set of CATT rows or a customized set of CATT rows. For example, if customer A uses all transactions in the default CATT, the PROFILE field on CSTT screen 1 would be set to the value DEFAULT.

If customer B uses a subset of the transactions in the default CATT, a unique customer profile must be specified on CSTT screen 1 for customer B and a new row must be added to the CATT for each transaction that is supported for customer B. The value specified in the CUSTOMER PROFILE field for these new rows must match the value specified for customer B in the PROFILE field in the CSTT.

If customer C uses the same set of transactions as customer B, the value in the PROFILE field on screen 1 of the CSTT record for customer C would match the value used on screen 1 of the CSTT record for customer B and no new rows would be added to the CATT.

Transaction Dependencies

When customers are allowed access to schedule a payment or transfer (9A–9E), they must also be allowed access for each individual scheduled payment or transfer transaction (4A–5B) to be performed as shown in the following table. The 4A–5B transactions are automatically performed by the XPNET Billpay Server or Scheduled Transaction Initiator process.

Access to This Transaction Code:	Requires Access to This Transaction Code:
9A	50
9B	5A
9C	5B
9D	4A
9E	4B

Access to the customer vendor add (9N) and master vendor add (9S) transactions also requires access to the master vendor list inquiry (9R) transaction. The 9R transaction allows customer service representatives (CSRs) to search for an existing vendor before adding a new customer vendor.

Inquiry Transactions

In the default CATT table, *count* refers to the number of transactions, customer vendors, or accounts that can be returned in a single inquiry transaction response message.

Values in the following fields on Host Configuration File (HCF) screen 23 control the number of transactions, customer vendors, or accounts that can be returned in a single inquiry response message to a host.

- CUSTOMER VENDOR MAX COUNT*
- HIST INQ PMNT/XFER MAX COUNT
- LAST TRANSACTION MAX COUNT
- SCHEDULED TRANSFER MAX COUNT
- SCHEDULED PAYMENT MAX COUNT*
- ACCOUNT LIST MAX COUNT

* These fields are not currently used.

Values in the following fields on VRU Configuration Data (VCD) screen 18 control the number of transactions, customer vendors, or accounts that can be returned in a single inquiry response message to an RBSI-compliant device or a customer service representative (CSR) terminal.

- CUSTOMER VENDOR INQ
- HIST INQ PMNT/XFER
- LAST TRANSACTION
- MULTIPLE ACCT BAL *
- SCHEDULED TRANSFERS
- SCHEDULED PAYMENTS
- ACCOUNT LIST

* A maximum count field does not appear on HCF screen 23 for the multiple account balance inquiry transaction, because the number of accounts is controlled in the transaction structure itself. A maximum count is included on VCD screen 18 to ensure that the count in the transaction does not exceed the maximum number of accounts (13) that can be returned in a transaction authorized on a host.

The following fields on VCD screen 18 control the number of items that can be returned in a single inquiry response from an RBSI-compliant device or a CSR terminal. Since these inquiry transactions cannot be acquired from a host, there are no corresponding maximum count fields on HCF screen 23.

- SCHED TRANSACTIONS
- HIST INQ ALL TRANS
- MASTER VENDOR INQ
- BANK LIST INQ
- BANK BRANCH LIST INQ
- MISCELLANEOUS REQ
- CUSTOMER VENDOR MASK
- STATEMENT DOWNLOAD
- STMT CLOS DOWNLOAD

The value in the MAX HISTORY RECORDS field on Customer Table (CSTT) screen 1 controls the total number of Transaction History File (THF) records that can be returned in a last *count* of transaction history inquiry transaction to an RBSI-compliant device for this customer. No limit is imposed on the total number of items that can be returned for any of the other inquiry transactions listed above or for last *count* of transaction history inquiry transactions entered from a customer service representative (CSR) terminal.

Default CATT Table

The table beginning below, referred to as the default CATT table, lists the processing codes in the default CATT rows at the time of installation of the BASE24-telebanking product and BASE24-billpay products. Default processing codes that are available only with the BASE24-billpay product are identified with a check mark (✓) in the BP column of the table. Most transaction codes appear multiple times to accommodate various account type combinations. Values in the

ACCOUNT 1 TYPE and ACCOUNT 2 TYPE columns of the table are defined in the Account Type Table File (ATT). Refer to section 2 for additional information about the ATT.

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Available funds inquiry.		30	NONE	NONE
Available funds inquiry.		30	SAV	NONE
Available funds inquiry.		30	SAV	DDA
Available funds inquiry.		30	DDA	NONE
Available funds inquiry.		30	DDA	SAV
Available funds inquiry.		30	CR	NONE
Available funds inquiry.		30	LOCN	NONE
Available funds inquiry.		30	CD	NONE
Available funds inquiry.		30	IRA	NONE
Available funds inquiry.		30	NOW	NONE
Available funds inquiry.		30	CMRCL	NONE
Available funds inquiry.		30	INSTL	NONE
Available funds inquiry.		30	MRTGL	NONE
Check clearance inquiry.		3A	NONE	NONE
Check clearance inquiry.		3A	DDA	NONE
Check clearance inquiry.		3A	NOW	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Last <i>count</i> of debit/credit transactions inquiry.		3B	NONE	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	SAV	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	DDA	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	CR	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	LOCN	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	CD	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	IRA	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	NOW	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	CMRCL	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	INSTL	NONE
Last <i>count</i> of debit/credit transactions inquiry.		3B	MRTGL	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Last <i>count</i> of account by source transactions inquiry.		3C	NONE	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	SAV	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	DDA	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	CR	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	LOCR	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	CD	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	IRA	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	NOW	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	CMRCL	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	INSTL	NONE
Last <i>count</i> of account by source transactions inquiry.		3C	MRTGL	NONE
Last <i>count</i> of check transactions inquiry.		3D	NONE	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Last <i>count</i> of check transactions inquiry.		3D	DDA	NONE
Last <i>count</i> of check transactions inquiry.		3D	NOW	NONE
Last <i>count</i> of debit transactions inquiry.		3E	NONE	NONE
Last <i>count</i> of debit transactions inquiry.		3E	SAV	NONE
Last <i>count</i> of debit transactions inquiry.		3E	DDA	NONE
Last <i>count</i> of debit transactions inquiry.		3E	CR	NONE
Last <i>count</i> of debit transactions inquiry.		3E	LOCR	NONE
Last <i>count</i> of debit transactions inquiry.		3E	CD	NONE
Last <i>count</i> of debit transactions inquiry.		3E	IRA	NONE
Last <i>count</i> of debit transactions inquiry.		3E	NOW	NONE
Last <i>count</i> of credit transactions inquiry.		3F	NONE	NONE
Last <i>count</i> of credit transactions inquiry.		3F	SAV	NONE
Last <i>count</i> of credit transactions inquiry.		3F	DDA	NONE
Last <i>count</i> of credit transactions inquiry.		3F	CR	NONE
Last <i>count</i> of credit transactions inquiry.		3F	LOCR	NONE
Last <i>count</i> of credit transactions inquiry.		3F	CD	NONE
Last <i>count</i> of credit transactions inquiry.		3F	IRA	NONE
Last <i>count</i> of credit transactions inquiry.		3F	NOW	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Last <i>count</i> of credit transactions inquiry.		3F	CMRCL	NONE
Last <i>count</i> of credit transactions inquiry.		3F	INSTL	NONE
Last <i>count</i> of credit transactions inquiry.		3F	MRTGL	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	NONE	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	SAV	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	DDA	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	CR	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	LOCR	NONE
Last <i>count</i> of account transfer transactions inquiry.		3G	NOW	NONE
Customer vendor list inquiry.	✓	3H	NONE	NONE
Scheduled payments list inquiry.	✓	3J	NONE	NONE
Scheduled transfers list inquiry.	✓	3K	NONE	NONE
History inquiry – payments and transfers.	✓	3L	NONE	NONE
Scheduled transactions list inquiry.	✓	3M	NONE	NONE
Customer account list inquiry.		3N	NONE	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Multiple account balance inquiry.		3P	NONE	NONE
Statement closing download.		3Q	NONE	NONE
Statement closing download.		3Q	SAV	NONE
Statement closing download.		3Q	DDA	NONE
Statement closing download.		3Q	CR	NONE
Statement closing download.		3Q	LOCR	NONE
Statement closing download.		3Q	NOW	NONE
Statement closing download.		3Q	CMRCL	NONE
Statement closing download.		3Q	INSTL	NONE
Statement closing download.		3Q	MRTGL	NONE
Statement download.		3R	NONE	NONE
Statement download.		3R	SAV	NONE
Statement download.		3R	DDA	NONE
Statement download.		3R	CR	NONE
Statement download.		3R	LOCR	NONE
Statement download.		3R	NOW	NONE
Statement download.		3R	CMRCL	NONE
Statement download.		3R	INSTL	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Statement download.		3R	MRTGL	NONE
Transfer – immediate.		40	NONE	NONE
Transfer – immediate.		40	SAV	SAV
Transfer – immediate.		40	SAV	DDA
Transfer – immediate.		40	SAV	CR
Transfer – immediate.		40	SAV	LOCR
Transfer – immediate.		40	SAV	NOW
Transfer – immediate.		40	SAV	CMRCL
Transfer – immediate.		40	SAV	INSTL
Transfer – immediate.		40	SAV	MRTGL
Transfer – immediate.		40	DDA	SAV
Transfer – immediate.		40	DDA	DDA
Transfer – immediate.		40	DDA	CR
Transfer – immediate.		40	DDA	LOCR
Transfer – immediate.		40	DDA	NOW
Transfer – immediate.		40	DDA	CMRCL
Transfer – immediate.		40	DDA	INSTL
Transfer – immediate.		40	DDA	MRTGL

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Transfer – immediate.		40	CR	SAV
Transfer – immediate.		40	CR	DDA
Transfer – immediate.		40	CR	NOW
Transfer – immediate.		40	LOCR	SAV
Transfer – immediate.		40	LOCR	DDA
Transfer – immediate.		40	LOCR	NOW
Transfer – immediate.		40	NOW	SAV
Transfer – immediate.		40	NOW	DDA
Transfer – immediate.		40	NOW	CR
Transfer – immediate.		40	NOW	LOCR
Transfer – immediate.		40	NOW	NOW
Transfer – immediate.		40	NOW	CMRCL
Transfer – immediate.		40	NOW	INSTL
Transfer – immediate.		40	NOW	MRTGL
Transfer – future.	✓	4A	NONE	NONE
Transfer – future.	✓	4A	SAV	SAV
Transfer – future.	✓	4A	SAV	DDA
Transfer – future.	✓	4A	SAV	CR

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Transfer – future.	✓	4A	SAV	LOCR
Transfer – future.	✓	4A	SAV	NOW
Transfer – future.	✓	4A	SAV	CMRCL
Transfer – future.	✓	4A	SAV	INSTL
Transfer – future.	✓	4A	SAV	MRTGL
Transfer – future.	✓	4A	DDA	SAV
Transfer – future.	✓	4A	DDA	DDA
Transfer – future.	✓	4A	DDA	CR
Transfer – future.	✓	4A	DDA	LOCR
Transfer – future.	✓	4A	DDA	NOW
Transfer – future.	✓	4A	DDA	CMRCL
Transfer – future.	✓	4A	DDA	INSTL
Transfer – future.	✓	4A	DDA	MRTGL
Transfer – future.	✓	4A	CR	SAV
Transfer – future.	✓	4A	CR	DDA
Transfer – future.	✓	4A	CR	NOW
Transfer – future.	✓	4A	LOCR	SAV
Transfer – future.	✓	4A	LOCR	DDA

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Transfer – future.	✓	4A	LOCR	NOW
Transfer – future.	✓	4A	NOW	SAV
Transfer – future.	✓	4A	NOW	DDA
Transfer – future.	✓	4A	NOW	CR
Transfer – future.	✓	4A	NOW	LOCR
Transfer – future.	✓	4A	NOW	NOW
Transfer – future.	✓	4A	NOW	CMRCL
Transfer – future.	✓	4A	NOW	INSTL
Transfer – future.	✓	4A	NOW	MRTGL
Transfer – recurring.	✓	4B	NONE	NONE
Transfer – recurring.	✓	4B	SAV	SAV
Transfer – recurring.	✓	4B	SAV	DDA
Transfer – recurring.	✓	4B	SAV	CR
Transfer – recurring.	✓	4B	SAV	LOCR
Transfer – recurring.	✓	4B	SAV	NOW
Transfer – recurring.	✓	4B	SAV	CMRCL
Transfer – recurring.	✓	4B	SAV	INSTL
Transfer – recurring.	✓	4B	SAV	MRTGL

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Transfer – recurring.	✓	4B	DDA	SAV
Transfer – recurring.	✓	4B	DDA	DDA
Transfer – recurring.	✓	4B	DDA	CR
Transfer – recurring.	✓	4B	DDA	LOCR
Transfer – recurring.	✓	4B	DDA	NOW
Transfer – recurring.	✓	4B	DDA	CMRCL
Transfer – recurring.	✓	4B	DDA	INSTL
Transfer – recurring.	✓	4B	DDA	MRTGL
Transfer – recurring.	✓	4B	CR	SAV
Transfer – recurring.	✓	4B	CR	DDA
Transfer – recurring.	✓	4B	CR	NOW
Transfer – recurring.	✓	4B	LOCR	SAV
Transfer – recurring.	✓	4B	LOCR	DDA
Transfer – recurring.	✓	4B	LOCR	NOW
Transfer – recurring.	✓	4B	NOW	SAV
Transfer – recurring.	✓	4B	NOW	DDA
Transfer – recurring.	✓	4B	NOW	CR
Transfer – recurring.	✓	4B	NOW	LOCR

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Transfer – recurring.	✓	4B	NOW	NOW
Transfer – recurring.	✓	4B	NOW	CMRCL
Transfer – recurring.	✓	4B	NOW	INSTL
Transfer – recurring.	✓	4B	NOW	MRTGL
Payment – immediate.	✓	50	NONE	NONE
Payment – immediate.	✓	50	SAV	NONE
Payment – immediate.	✓	50	DDA	NONE
Payment – immediate.	✓	50	CR	NONE
Payment – immediate.	✓	50	LOCR	NONE
Payment – immediate.	✓	50	NOW	NONE
Payment – future.	✓	5A	NONE	NONE
Payment – future.	✓	5A	SAV	NONE
Payment – future.	✓	5A	DDA	NONE
Payment – future.	✓	5A	CR	NONE
Payment – future.	✓	5A	LOCR	NONE
Payment – future.	✓	5A	NOW	NONE
Payment – recurring.	✓	5B	NONE	NONE
Payment – recurring.	✓	5B	SAV	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Payment – recurring.	✓	5B	DDA	NONE
Payment – recurring.	✓	5B	CR	NONE
Payment – recurring.	✓	5B	LOCR	NONE
Payment – recurring.	✓	5B	NOW	NONE
PIN change.		90	NONE	NONE
PIN verify.		91	NONE	NONE
Schedule payment – immediate.	✓	9A	NONE	NONE
Schedule payment – immediate.	✓	9A	SAV	NONE
Schedule payment – immediate.	✓	9A	DDA	NONE
Schedule payment – immediate.	✓	9A	CR	NONE
Schedule payment – immediate.	✓	9A	LOCR	NONE
Schedule payment – immediate.	✓	9A	NOW	NONE
Schedule payment – future.	✓	9B	NONE	NONE
Schedule payment – future.	✓	9B	SAV	NONE
Schedule payment – future.	✓	9B	DDA	NONE
Schedule payment – future.	✓	9B	CR	NONE
Schedule payment – future.	✓	9B	LOCR	NONE
Schedule payment – future.	✓	9B	NOW	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Schedule payment – recurring.	✓	9C	NONE	NONE
Schedule payment – recurring.	✓	9C	SAV	NONE
Schedule payment – recurring.	✓	9C	DDA	NONE
Schedule payment – recurring.	✓	9C	CR	NONE
Schedule payment – recurring.	✓	9C	LOCR	NONE
Schedule payment – recurring.	✓	9C	NOW	NONE
Schedule transfer – future.	✓	9D	NONE	NONE
Schedule transfer – future.	✓	9D	SAV	SAV
Schedule transfer – future.	✓	9D	SAV	DDA
Schedule transfer – future.	✓	9D	SAV	CR
Schedule transfer – future.	✓	9D	SAV	LOCR
Schedule transfer – future.	✓	9D	SAV	NOW
Schedule transfer – future.	✓	9D	SAV	CMRCL
Schedule transfer – future.	✓	9D	SAV	INSTL
Schedule transfer – future.	✓	9D	SAV	MRTGL
Schedule transfer – future.	✓	9D	DDA	SAV
Schedule transfer – future.	✓	9D	DDA	DDA
Schedule transfer – future.	✓	9D	DDA	CR

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Schedule transfer – future.	✓	9D	DDA	LOCR
Schedule transfer – future.	✓	9D	DDA	NOW
Schedule transfer – future.	✓	9D	DDA	CMRCL
Schedule transfer – future.	✓	9D	DDA	INSTL
Schedule transfer – future.	✓	9D	DDA	MRTGL
Schedule transfer – future.	✓	9D	CR	SAV
Schedule transfer – future.	✓	9D	CR	DDA
Schedule transfer – future.	✓	9D	CR	NOW
Schedule transfer – future.	✓	9D	LOCR	SAV
Schedule transfer – future.	✓	9D	LOCR	DDA
Schedule transfer – future.	✓	9D	LOCR	NOW
Schedule transfer – future.	✓	9D	NOW	SAV
Schedule transfer – future.	✓	9D	NOW	DDA
Schedule transfer – future.	✓	9D	NOW	CR
Schedule transfer – future.	✓	9D	NOW	LOCR
Schedule transfer – future.	✓	9D	NOW	NOW
Schedule transfer – future.	✓	9D	NOW	CMRCL
Schedule transfer – future.	✓	9D	NOW	INSTL

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Schedule transfer – future.	✓	9D	NOW	MRTGL
Schedule transfer – recurring.	✓	9E	NONE	NONE
Schedule transfer – recurring.	✓	9E	SAV	SAV
Schedule transfer – recurring.	✓	9E	SAV	DDA
Schedule transfer – recurring.	✓	9E	SAV	CR
Schedule transfer – recurring.	✓	9E	SAV	LOCR
Schedule transfer – recurring.	✓	9E	SAV	NOW
Schedule transfer – recurring.	✓	9E	SAV	CMCRL
Schedule transfer – recurring.	✓	9E	SAV	INSTL
Schedule transfer – recurring.	✓	9E	SAV	MRTGL
Schedule transfer – recurring.	✓	9E	DDA	SAV
Schedule transfer – recurring.	✓	9E	DDA	DDA
Schedule transfer – recurring.	✓	9E	DDA	CR
Schedule transfer – recurring.	✓	9E	DDA	LOCR
Schedule transfer – recurring.	✓	9E	DDA	NOW
Schedule transfer – recurring.	✓	9E	DDA	CMCRL
Schedule transfer – recurring.	✓	9E	DDA	INSTL
Schedule transfer – recurring.	✓	9E	DDA	MRTGL

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Schedule transfer – recurring.	✓	9E	CR	SAV
Schedule transfer – recurring.	✓	9E	CR	DDA
Schedule transfer – recurring.	✓	9E	CR	NOW
Schedule transfer – recurring.	✓	9E	LOCR	SAV
Schedule transfer – recurring.	✓	9E	LOCR	DDA
Schedule transfer – recurring.	✓	9E	LOCR	NOW
Schedule transfer – recurring.	✓	9E	NOW	SAV
Schedule transfer – recurring.	✓	9E	NOW	DDA
Schedule transfer – recurring.	✓	9E	NOW	CR
Schedule transfer – recurring.	✓	9E	NOW	LOCR
Schedule transfer – recurring.	✓	9E	NOW	NOW
Schedule transfer – recurring.	✓	9E	NOW	CMCRL
Schedule transfer – recurring.	✓	9E	NOW	INSTL
Schedule transfer – recurring.	✓	9E	NOW	MRTGL
Scheduled payment delete.	✓	9F	NONE	NONE
Scheduled transfer delete.	✓	9G	NONE	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Scheduled payment update. Allows customers to change the date, amount, period type, number of periods, or to skip the next payment.	✓	9H	NONE	NONE
Scheduled transfer update. Allows customers to change the date, amount, period type, number of periods, or to skip the next transfer.	✓	9J	NONE	NONE
Customer add.	✓	9K	NONE	NONE
Customer inquiry.	✓	9L	NONE	NONE
Customer update.	✓	9M	NONE	NONE
Customer vendor add.	✓	9N	NONE	NONE
Customer vendor deactivate.	✓	9P	NONE	NONE
Customer vendor update.	✓	9Q	NONE	NONE
Master vendor list inquiry.	✓	9R	NONE	NONE
Master vendor add.	✓	9S	NONE	NONE
Customer vendor request mailing.	✓	9T	NONE	NONE
Loan application.	✓	9V	NONE	NONE
Miscellaneous request.	✓	9W	NONE	NONE
History inquiry – all transactions.	✓	9X	NONE	NONE
Check stop payment add.		A0	DDA	NONE

Transaction Description	BP	PROCESSING CODE		
		TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE
Check stop payment add.		A0	LOCR	NONE
Check stop payment add.		A0	NOW	NONE
Check stop payment add.		A0	CMRCL	NONE
Check stop payment add.		A0	INSTL	NONE
Check stop payment add.		A0	MRTGL	NONE
Bank list inquiry.	✓	B1	NONE	NONE
Bank branch list inquiry.	✓	B2	NONE	NONE
Miscellaneous requests inquiry.	✓	B4	NONE	NONE
Customer account add.	✓	B5	NONE	NONE
Customer account activate.	✓	B6	NONE	NONE
Customer account deactivate.	✓	B7	NONE	NONE
Customer account delete.	✓	B8	NONE	NONE
Customer account update.	✓	B9	NONE	NONE
Customer activate.	✓	BB	NONE	NONE
Customer deactivate.	✓	BC	NONE	NONE
Customer vendor activate.	✓	BD	NONE	NONE
Customer vendor mask verify inquiry.	✓	BE	NONE	NONE

Screen 1 Function Keys

The use of four function keys on CATT screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on CATT screen 1.

Key	Description
F5	Update Record — Allows only the BEGIN DATE and END DATE fields to be updated. To update other fields in a CATT row, the user must first delete the row using the F4 key, make the desired changes, and then add the row using the F3 key. Only users in the super user group are allowed to update CATT rows.
F7	Load — Copies all of the default CATT rows to the combination of values specified in the FIID and CUSTOMER PROFILE fields. This key allows the user to add multiple rows simultaneously instead of adding the rows individually. Once the user has pressed the F7 key, the system generates a message indicating the number of rows added to the CATT for the combination of values entered in the FIID and CUSTOMER PROFILE fields. Only a super user can perform this function. You cannot reload the default CATT rows. When loading the default CATT rows, you must change the PROFILE field to a value other than DEFAULT.
F9	Unload — Deletes all of the CATT rows for the combination of values specified in the FIID and CUSTOMER PROFILE fields. This key allows the user to delete multiple rows simultaneously instead of deleting the rows individually. Once the user has pressed the F9 key, the system generates a message indicating that all rows were successfully deleted from the CATT for the combination of values specified in the FIID and CUSTOMER PROFILE fields. Only a super user can perform this function. You cannot unload the default CATT rows.

Key	Description
F11	Display Previous Screen — This function is disabled on this screen because there is only one screen.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.

In addition, only a super user (that is, a user with a group number of 255 in his or her CRT access security record) can add default CATT rows using the **F3** key, delete default CATT rows using the **F4** key, or update default CATT rows using the **F5** key.

Screen 1

CATT screen 1 allows you to associate allowed transactions with financial institutions and customer profiles. Screen 1 of the CATT is shown below, followed by descriptions of its fields.

BASE24-CORE
CUSTOMER ALLOWED TRAN
LLLL
YY/MM/DD
hh:mm
01 OF 01

FIID: ****
CUSTOMER PROFILE: DEFAULT

TRANSACTION CODE:

PROCESSING CODE
ACCOUNT 1 TYPE: NONE
ACCOUNT 2 TYPE: NONE

BEGIN DATE:
(YYYYMMDD)
END DATE:
(YYYYMMDD)

RECORD LAST CHANGED:

BY USER:

BASE24

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F7-LOAD
F9-UNLOAD
F12-HELP

FIID — A code identifying the issuing institution or institutions associated with this profile. All customers are assigned an FIID and customer profile. This field must contain a wildcard entry of four asterisks (****) or a value that matches a value in the FIID field on Customer Table (CSTT) screen 1. A value of all spaces is not allowed in this field.

The BASE24-telebanking and BASE24-billpay products search for a CATT row with an FIID that matches the customer’s FIID. If a CATT row with the customer’s FIID cannot be found, the BASE24-telebanking and BASE24-billpay products search for a CATT row with an FIID of four asterisks.

Field Length:

1–4 alphanumeric characters

Required Field:

Yes

Default Value:

Column Name:

CATT.FIID

CUSTOMER PROFILE — An identifier used to group customers together for transaction processing. All customers are assigned an FIID and a customer profile. The value in this field must contain the entry DEFAULT or an entry that matches a value in the PROFILE field on Customer Table (CSTT) screen 1. A value of all spaces cannot be entered in this field.

If you attempt to load the default CATT rows, this field must contain a value other than DEFAULT.

Field Length: 1–8 alphanumeric characters
Required Field: Yes
Default Value: DEFAULT
Column Name: CATT.PRFL

PROCESSING CODE

The following fields identify the processing code defined by this CATT row.

TRANSACTION CODE — A code identifying the type of transaction being defined. Valid TRANSACTION CODE values for ACI-supplied default records are shown in the Transaction Code column of the default CATT table provided earlier in this section.

The transaction code is stored in the first two positions of the PROC_CDE column.

Field Length: 2 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CATT.PROC_CDE[0:1]

ACCOUNT 1 TYPE — A name identifying the account 1 type for the transaction being defined. Valid ACCOUNT 1 TYPE names for ACI-supplied default rows are shown in the ACCOUNT 1 TYPE column of the default CATT table provided earlier in this section. A name must be defined for the account 1 type in the Account Type Table File (ATT) before it is used in this field.

For transfer transactions, this value always identifies the *from* account.

The account 1 type is stored in the third and fourth positions of the PROC_CDE column.

Spaces are not allowed in this field.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: NONE
Column Name: CATT.PROC_CDE[2:3]

ACCOUNT 2 TYPE — A name identifying the account 2 type for the transaction being defined. Valid ACCOUNT 2 TYPE names for ACI-supplied default rows are shown in the ACCOUNT 2 TYPE column of the default CATT table provided earlier in this section. A name must be defined for the account 2 type in the Account Type Table File (ATT) before it can be used in this field.

For transfer transactions, this value always identifies the *to* account.

The account 2 type is stored in the fifth and sixth positions of the PROC_CDE column.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: NONE
Column Name: CATT.PROC_CDE[4:5]

BEGIN DATE — The date (YYYYMMDD) on which this allowed transaction will become available for use in processing. Valid values range from any valid date up to a maximum value of 20741231. When validating data, updating a row, or adding a row, a value of all spaces in this field indicates that the current Tandem system date be used.

This field, along with the END DATE field, allow users to predefine allowed transactions prior to their actual use in processing. These fields could also be used to define a trial or contracted usage period for an allowed transaction.

Field Length: 8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CATT.BEG_DAT

END DATE — The date (YYYYMMDD) on which this allowed transaction will no longer be available for use in processing. If this field is left blank, it defaults to a value of 20741231.

This field, along with the BEGIN DATE field, allow users to predefine allowed transactions prior to their actual use in processing. These fields could also be used to define a trial or contracted usage period for an allowed transaction.

The date entered in this field must be greater than the date entered in the BEGIN DATE field.

Field Length: 8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CATT.END_DAT

Section 4

Customer Service Representative Control (CSRC)

The customer service representative (CSR) screens, accessed from the Customer Service Representative Control (CSRC) entry on the Core Product Menu, enable a customer service representative to initiate transactions on behalf of customers. Transaction requests are routed by BASE24 products and are authorized by a BASE24 product or a host. Response information is displayed to the customer service representative for return to the customer. A series of request and response screen formats exists. The screen formats used for a particular transaction depend on the type of transaction being performed.

Customer Service Representative functionality is an add-on product to the BASE24-telebanking and BASE24-billpay products. Refer to the ***BASE24 Remote Banking Customer Service Support Manual*** for CSR screen formats and field descriptions.

ACI Worldwide Inc.

Section 5

Customer Table (CSTT)

The Customer Table (CSTT) screens provide access to three SQL tables: the Customer Table (CSTT), the Customer Account Relation Table (CACT), and the Customer/Personal ID Relation Table (CPIT). CSTT screen 1 accesses the CSTT, CSTT screen 2 accesses the CACT, and CSTT screen 3 accesses the CPIT.

The Customer Table (CSTT) contains one row for each customer allowed to perform customer ID-based services. A customer can be an individual or a business. This row contains authorization parameters and usage accumulation information for the specified customer. The primary key to CSTT rows is the CUSTOMER ID field on CSTT screen 1.

The CACT and the CPIT are described on the following pages, followed by descriptions of the screens that access the CSTT, CACT, and CPIT.

Customer/Account Relation Table (CACT)

The Customer/Account Relation Table (CACT) contains one row for each account that is associated with a customer ID. This table is used in conjunction with the Positive Customer with Accounts Authorization method (PCAA) or the Positive Customer with Balances/History Authorization method (PCBA). There is no limit to the number of accounts (CACT rows) that can be associated with a customer ID. Four accounts can be displayed at a time on CSTT screen 2.

If you are using the PCBA authorization method to authorize transactions on the BASE24 system, all accounts defined in the CACT must also be defined in the Positive Balance File (PBF). For more information on the PBF, refer to the *BASE24 Base Files Maintenance Manual*.

The primary key to CACT rows is a combination of the value in the CUSTOMER ID field on CSTT screen 1 and the values in the ACCOUNT TYPE and ACCOUNT NUMBER fields on CSTT screen 2. Two indexes provide alternate key access to CACT rows. These indexes allow customer accounts to be accessed in different ways. The two indexes described in the following table are included when the CACT is installed. Either of these indexes may be disabled, however, when the software is installed, according to the access requirements of your organization. If an index is disabled, it cannot be used to access accounts. The first column of this table names each index. The second column of this table lists the fields included in the index.

Index	Indexed Fields
Account number	ACCOUNT NUMBER field on CSTT screen 2 ACCOUNT TYPE field on CSTT screen 2
Multiple account select	CUSTOMER ID field on CSTT screen 1 ACCOUNT TYPE field on CSTT screen 2 ACCOUNT NUMBER field on CSTT screen 2

When the account number index is enabled, a customer can initiate a transaction by entering an account number and an account type without entering a customer ID. When this method is used, multiple CACT rows cannot have the same account number and account type.

When the multiple account select index is enabled, multiple account selection processing can be supported. Multiple account selection allows customers to select from multiple accounts returned for a particular customer ID and account type. The number of accounts returned in a single response is limited by the remote banking endpoint device. When the accounts are returned, the customer can select an individual account or request that more accounts be returned.

Using the primary keys to CSTT and CACT rows, as well as the enabled indexes to the CACT, individual rows in the CACT can be accessed using any of the following field combinations:

- CUSTOMER ID field on CSTT screen 1 *
- CUSTOMER ID field on CSTT screen 1 and ACCOUNT TYPE field on CSTT screen 2 *
- CUSTOMER ID field on CSTT screen 1 and ACCOUNT NUMBER field on CSTT screen 2 *
- CUSTOMER ID field on CSTT screen 1 and ACCOUNT TYPE and ACCOUNT NUMBER fields on CSTT screen 2

* This access method may result in multiple CACT rows being displayed.

Customer/Personal ID Relation Table (CPIT)

The Customer/Personal ID Relation Table (CPIT) contains one row for each personal ID associated with a CSTT row. This table provides a link between the CSTT and the Personal Information Table (PIT) and allows you to associate a single customer ID with multiple personal IDs or associate multiple customer IDs with a single personal ID. Data from the CPIT is displayed on the CSTT screen 3 and PIT screen 2.

Although the CPIT must always be physically present, use of the CPIT is optional for all BASE24 Remote Banking product options.

CSTT screen 3 allows you to associate multiple personal IDs with a single customer ID. PIT screen 2 allows you to associate multiple customer IDs with a single personal ID. All personal IDs used in the CPIT must also be defined in the Personal Information Table (PIT). The CPIT-PRESENT param in the LCONF must be set to a value of Y to be able to use these screens.

The primary key to rows in the CPIT is a combination of the value entered in the CUSTOMER ID field on CSTT screen 1 and the value entered in the PERSONAL ID field on CSTT screen 3. Rows in the CPIT are also indexed by personal ID for alternate access.

Note: The ID TYP field on Personal Information Table (PIT) screen 2 is also part of the primary key to CPIT rows, however, it is not displayed on CSTT screen 3. A value of CU (Customer Table) is always assumed for this field when reading CPIT rows from the CSTT.

Default Financial Institution Rows

After the Customer Table, Customer/Account Relation Table, and Customer/Personal ID Relation Table (CPIT) are installed, BASE24-billpay users must set up a default CSTT row for each financial institution in the logical network. This row is used for any transaction request (e.g., bank list inquiry transaction) received that does not contain or require a customer ID (i.e., the customer ID is blank or is set to all zeros). The customer ID from the default row is passed back in the transaction response and is logged to the ITS Transaction Log File (ITLF). This CSTT row is identified in the DEFAULT CUST ID field on the Bank Table (BANK) screen.

The same default CSTT row, along with a default CACT and CPIT row, are used to retrieve default customer data when signing up new customers for an institution that does not use preloaded customer data. These CSTT, CPIT, and CACT rows are identified in the DEFAULT CUST ID and DEFAULT ACCT NUM fields on the Bank Table (BANK) screen.

Note: Since the CPIT is an optional table, default financial institution rows are only required in this table if it is installed.

For more information on the BANK, refer to the ***BASE24 Base Files Maintenance Manual***.

For more information on how default data in CSTT, CACT, and CPIT rows is used when adding new BASE24-billpay customers using the CSR screens, refer to the ***BASE24 Remote Banking Customer Service Support Manual***.

Screen 1 Function Keys

The use of six function keys on CSTT screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on CSTT screen 1.

Key	Description
F2	Read Record — Reads one row from the Customer Table (CSTT), the first four account rows from the Customer Account Relation Table (CACT), and the first 30 rows from the Customer/Personal ID Relation Table (CPIT) for the specified customer ID. Records are read based on the value entered in the CUSTOMER ID field on CSTT screen 1. Note: You must have security access to the FIID in the CSTT row to be read.
F3	Add Record — Writes the row information from screen 1 to the CSTT, the row information for selected accounts from screen 2 to the CACT, and the row information for selected personal IDs from screen 3 to the CPIT. Rows can be added from screen 1, 2, or 3. Note: You must have security access to the FIID in the CSTT row to be added.
F4	Delete Record — Deletes the currently displayed row from the CSTT and all CACT and CPIT rows with a customer ID matching the CUSTOMER ID on CSTT screen 1.
F5	Update Record — Updates the CSTT row with information from screen 1 and updates CACT rows with information from accounts selected on CSTT screen 2. Rows currently displayed in both the CSTT and the CACT tables are updated from either CSTT screen 1 or 2. This function key is not valid on CSTT screen 3. Note: You must have security access to the FIID in the CSTT row to be updated.

Key	Description
F6	Read Next Record — Reads the next row in the CSTT, the first four account rows from the CACT, and the first 30 personal ID rows from the CPIT for the specified customer. Note: You must have security access to the FIID in the next CSTT row to be read.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.

Screen 1

CSTT screen 1 defines authorization parameters and usage accumulation information for BASE24-telebanking and BASE24-billpay customers. CSTT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-CORE CUSTOMER CONFIGURATION  LLLL      YY/MM/DD  hh:mm  01 OF 03
CUSTOMER ID:

      FIID:      BRANCH ID:      PROFILE:      TYPE: C
      BEGIN DATE:      (YYYYMMDD)      END DATE:      (YYYYMMDD)
VERIFY STATUS: V      (LAST UPDATE:      )
      PIN VERIFICATION DIGITS:      (LAST UPDATE:      )
      PIN VERIFICATION KEY INDEX:      BAD PIN COUNT: 0000
      PIN CHANGE REQUIRED: N (Y/N/S)      LAST RESET DATE:
      MAX HISTORY RECORDS: 0
      DEFAULT ACCT TYPE: NONE      DEFAULT ACCT NUM:

CUST INFO:
      ALTERNATE CONTACT:
      PAYMENT HIGH LIMIT:      BILLPAY BILLING GROUP:
      PACKET STATUS:      (LAST UPDATE: 00000000000000 )
      BILLPAY BILLING TYPE:      (LAST UPDATE: 00000000000000 )
      SERVICE FEE ACCT TYPE: NONE      SERVICE FEE ACCT NUM:

RECORD LAST CHANGED:      BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F12-HELP

```

CUSTOMER ID — The unique identification number assigned to this CSTT row. An unlimited number of individual accounts and persons (each identified by a unique personal ID) can be associated with one customer ID number.

A customer ID number can also be known as a primary account number (PAN). Other BASE24 products use the PAN to identify information on a plastic card. If customers have already been issued plastic cards, existing PANs could be conveniently used as customer IDs; however, the PAN used by the BASE24-telebanking and BASE24-billpay products does not have to be associated with a plastic card. The PAN field on Personal Information Table (PIT) screen 2 maps directly to the CUSTOMER ID field displayed on CSTT screen 3. The PAN field on PIT screen 2 allows one person to be associated with multiple customer IDs. Multiple persons can be associated with a single customer ID using CSTT screen 3. Multiple accounts can be associated with a single customer ID using CSTT screen 2.

The customer ID is also used by the BASE24-billpay product to index transaction activity recorded in the History Table (HIST).

Field Length: 1–19 numeric characters
Required Field: Yes
Default Value: No default value
Column Name: CSTT.PAN

FIID — The FIID of the financial institution for this CSTT row. The FIID is an identifier that must be unique within the logical network. It is used throughout BASE24 products to identify each BASE24 institution and to secure file record and table row access by financial institution. The value entered in this field should match the value of the FIID in an Institution Definition File (IDF) record.

For more information on the IDF and restrictions regarding the use of FIID values, refer to the ***BASE24 Base Files Maintenance Manual***.

For more information on how the FIID is used to restrict access to file records and table rows, refer to the ***BASE24 CRT Access Manual***.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CSTT.FIID

BRANCH ID — The number for the main branch of the financial institution where this CSTT row is serviced. This is the branch customers are referred to by customer service representatives for additional information on this CSTT row. For a BASE24-billpay customer account, the number in this field must be defined in a Bank Branch Table (BKBR) row.

For additional information on the BKBR, refer to the ***BASE24-billpay Tables Maintenance Manual***.

Field Length: 4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.BRCH_ID

PROFILE — An identifier used to group primary customer IDs together for transaction processing. The value in this field must match a value in the CUSTOMER PROFILE field on Customer Allowed Transaction Table (CATT) screen 1. The default rows in the CATT have the value DEFAULT in the CUSTOMER PROFILE field.

Field Length: 1–8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CSTT.PRFL

TYPE — A code identifying the type of customer associated with this customer ID. This is an information-only field that is not used in processing. Valid values are as follows:

B = Business customer
C = Individual customer

This field may also contain a user-defined type code.

A description of the code entered is displayed immediately to the right of the value in the TYPE field.

Field Length: 1–2 alphanumeric characters
Required Field: Yes
Default Value: C
Column Name: CSTT.TYP

BEGIN DATE — The first date (YYYYMMDD) this customer ID row can be used in processing. If the field is left blank, the Customer Table Maintenance Server process fills in the current date when the row is added or updated, or when a customer activate transaction is processed.

Field Length: 8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CSTT.BEG_DAT

END DATE — The last date (YYYYMMDD) this row can be used in processing. If the field is left blank, this row does not expire.

When a customer activate transaction is processed for this customer, the value of this field is set to the value of the END DATE field in the default CSTT row for the customer's financial institution.

When a customer deactivate transaction is processed for this customer, this field is set to a value one less than the current date.

Field Length: 8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CSTT.END_DAT

VERIFY STATUS — A code identifying the status of the customer relationship. Valid values are as follows:

C = Closed
I = Issued but inactive
V = Verified

Additional user-defined codes may be entered; however, all user-defined codes are treated the same as closed accounts.

Customer service representatives (CSRs) can add accounts for the customer as long as this field displays a value of I or V. CSRs can delete accounts for the customer only when this field displays a value of I.

This CSTT row cannot be used in processing unless this field displays a value of V.

When a customer activate transaction is processed, the value of this field is changed from an I to a V.

A description of the code entered is displayed immediately to the right of the value in the VERIFY STATUS field. For all user-defined codes, the phrase CLOSED, USER DEF is displayed.

Field Length: 2 alphanumeric characters
Required Field: Yes
Default Value: V
Column Name: CSTT.VRFY_FLG

LAST UPDATE — The date and time (YYYYMMDDhhmmss) the VERIFY STATUS field was last updated for this CSTT row.

Field Length: System-protected
Column Name: CSTT.LAST_VRFY_FLG_UPDT_TS

PIN VERIFICATION DIGITS — The PIN offset value, PIN verification number (PVN), or the PIN verification value (PVV) used in PIN verification processing. The information in this field depends on the PIN verification parameters specified in the PIN CHECK TYPE and POFST/PVV LOC fields on Institution Definition File (IDF) screen 2. This field is required if the PIN verification digits are to be maintained in the CSTT.

For more information on the IDF, refer to the ***BASE24 Base Files Maintenance Manual***.

If one zero is entered, at least four zeros must be entered. Although spaces are allowed in this field and spaces can trail an entry, spaces cannot be entered before a numeric entry or be embedded in an entry.

Field Length: 1–16 hexadecimal characters
Required Field: No
Default Value: No default value
Column Name: CSTT.PVD

LAST UPDATE — The date and time (YYYYMMDDhhmmss) the PIN VERIFICATION DIGITS field was last updated.

Field Length: System-protected
Column Name: CSTT.LAST_PVD_UPDT_TS

PIN VERIFICATION KEY INDEX — Identifies the location of the PIN verification value (PVV) when the Visa PVV PIN verification method is specified in the PIN CHECK TYPE field on Institution Definition File (IDF) screen 2. Valid values are 1 through 6 for the Visa PVV verification method and blank for other PIN verification methods.

For more information on the IDF, refer to the ***BASE24 Base Files Maintenance Manual***.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: No default value
Column Name: CSTT.PVK_IDX

BAD PIN COUNT — The number of times an incorrect PIN has been entered for this CSTT row during the current usage accumulation period.

Each institution defines the maximum number of incorrect PIN tries allowed for the customer in the MAX PIN TRIES field on Institution Definition File (IDF) screen 2. When this number of incorrect PIN tries is exceeded, subsequent transactions for the customer are rejected according to the setting in the BAD PIN ACTION field on IDF screen 2.

For more information on the IDF, refer to the ***BASE24 Base Files Maintenance Manual***.

Field Length: System-protected
Column Name: CSTT.BAD_PIN_CNT

PIN CHANGE REQUIRED — A flag that indicates whether a customer needs to initiate a PIN change transaction. If the institution wants the customer to initiate a PIN change transaction to change the current PIN, this field must be set to the value Y. If the institution wants to define a customer before the initial PIN has been selected, this field must be set to the value S. When this field is set to the value S or Y, the only transaction the customer can perform is a PIN change transaction. This field is set to the value N after a successful PIN change transaction is performed. Valid values are as follows:

Y = Yes, a PIN change is required. The customer must change the current PIN; the only transaction allowed is the PIN change transaction.
N = No, a PIN change is not required; the current PIN can be used.
S = Customer select. The customer must select the initial PIN; the only transaction allowed is the PIN change transaction.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Column Name: CSTT.PIN_CHNG_REQ

LAST RESET DATE — The date and time (YYYYMMDDhhmmss) the BAD PIN COUNT field was last cleared. The BAD PIN COUNT field is cleared when the customer performs the first transaction of a business day or enters a correct PIN, based on the value in the PIN TRIES RESET OPTION field on Institution Definition File (IDF) screen 2.

A transaction is considered to be the first one of the day when the date in this field is less than the date in the BEGINNING DATE field on IDF screen 4. After the BAD PIN COUNT field is cleared, the date in this field is replaced with the date from the BEGINNING DATE field on IDF screen 4. For more information on the IDF, refer to the ***BASE24 Base Files Maintenance Manual***.

Field Length: System-protected
Column Name: CSTT.LAST_RESET_DAT_TS

MAX HISTORY RECORDS — The maximum number of Transaction History File (THF) records that can be returned in historical inquiry transactions to a remote banking endpoint device for this customer. This field specifies the total number of items that can be returned for the transaction, not just for each response message included in the transaction. This maximum does not apply to historical inquiries requested by a customer service representative (CSR) using the BASE24 CSR terminal screens. Valid values are as follows:

0 = No maximum is enforced.
1–9999 = Maximum number of THF records that can be returned.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Column Name: CSTT.MAX_HIST_RECS

DEFAULT ACCT TYPE — A code identifying the default account type for which balance information is returned to the customer with PIN verify transactions. The code must be defined in the Account Type Table File (ATT) before it can be entered in this field.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: NONE
Column Name: CSTT.DFLT_ACCT_TYP

DEFAULT ACCT NUM — The number of the account for which balance information is returned to the customer with PIN verify transactions.

Field Length: 1–19 numeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.DFLT_ACCT

CUST INFO — User-defined customer account information. This information is displayed on Customer Service Representative (CSR) screens and can be used for customer verification purposes if the Personal Information Table (PIT) is not used. For example, these fields could be used to contain the customer's government ID, birth date, and mother's maiden name. Information from the CUST INFO fields is also included in the response to customer verify transactions.

Field Length: 3 fields of 1–20 alphanumeric characters each
Required Field: No
Default Value: No default value
Column Names: CSTT.CUST_INFO_1
CSTT.CUST_INFO_2
CSTT.CUST_INFO_3

ALTERNATE CONTACT — The name and phone number of the alternate contact associated with this customer ID. The primary contact is defined using one or more personal IDs associated with this customer ID on CSTT screen 3. The value in the PERSONAL ID field on CSTT screen 3 is the key to rows defined in the Personal Information Table (PIT).

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.ALT_CONTACT

PAYMENT HIGH LIMIT — The maximum amount, in whole and fractional currency units, that can be requested in an individual BASE24-billpay schedule payment transaction for this CSTT row.

If this field is set to a nonzero value, this limit overrides the customer's financial institution payment limit specified in the Bank Table (BANK). For more information on the BANK, refer to the *BASE24 Base Files Maintenance Manual*.

Field Length: 1–15 numeric characters
Required Field: No
Default Value: 0
Column Name: CSTT.BP_TXN_LMT

BILLPAY BILLING GROUP — A code identifying the billing group, which is an arbitrary value used to assign BASE24-billpay customers to a particular date for customer billing.

A row for this billing group must first exist in the Billing Group Table (BLG). For additional information on the BLG, refer to the ***BASE24-billpay Billing Application Manual***.

Field Length: 4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.BP_BILL_GRP

PACKET STATUS — A user-defined code indicating whether an informational packet explaining the billpay service has been sent for this customer ID. Any alphanumeric value is supported and all values are user defined.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: No default value
Column Name: CSTT.PCKT_STAT

LAST UPDATE — The date and time (YYYYMMDDhhmmss) the PACKET STATUS field was last updated.

Field Length: System-protected
Column Name: CSTT.LAST_PCKT_STAT_UPDT_TS

BILLPAY BILLING TYPE — A code that identifies a group of customers for billing purposes throughout the BASE24-billpay database. This code also defines the service level and fee structure for the billpay service. Any alphanumeric values are supported and all values are user-defined.

A row for this billing type must first exist in the Billing Type Table (BLTY). For additional information on the BLTY, refer to the ***BASE24-billpay Billing Application Manual***.

Field Length: 2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.BP_BILL_TYP

LAST UPDATE — The date and time (YYYYMMDDhhmmss) the BILLPAY BILLING TYPE field was last updated.

Field Length: System-protected
Column Name: CSTT.LAST_BP_BILL_TYP_UPDT_TS

SERVICE FEE ACCT TYPE — The account type associated with the service fee account number (SERVICE FEE ACCT NUM) for this customer ID. This field identifies the type of account charged by the customer's financial institution using the automatic debit feature for the billpay service. The account type entered in this field must already be defined in the Account Type Table File (ATT).

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: NONE
Column Name: CSTT.SVC_FEE_ACCT_TYP

SERVICE FEE ACCT NUM — The account number charged by the customer's financial institution using the automatic debit feature for the billpay service. The SERVICE FEE ACCT TYP field indicates the type of account associated with this account number.

Field Length: 1–19 numeric characters
Required Field: No
Default Value: No default value
Column Name: CSTT.SVC_FEE_ACCT

Screen 2 Function Keys

The use of nine function keys on CSTT screen 2 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these function keys on CSTT screen 2.

Key	Description
F2	Read Record — Reads one row from the Customer Table (CSTT), the first four account rows from the Customer Account Relation Table (CACT), and the first 30 rows from the Customer/Personal ID Relation Table (CPIT) for the specified customer ID. Rows in the CACT can be read based on values in the following field combinations: • CUSTOMER ID field on screen 1 • CUSTOMER ID field on screen 1 and ACCOUNT TYPE field on screen 2 • CUSTOMER ID field on screen 1 and ACCOUNT NUMBER field on screen 2 • CUSTOMER ID field on screen 1, and ACCOUNT TYPE and ACCOUNT NUMBER fields on screen 2 CSTT screen 2 can have an unlimited number of pages with four accounts per page. Press the Shift-F7 or Shift-F8 keys as needed to read and display the previous or next four CACT rows associated with the same customer ID.

Key	Description
F3	Add Record — Writes the current information from CSTT screen 1 to the CSTT, writes the currently displayed and selected account information from CSTT screen 2 to the CACT, and writes the currently selected personal ID information from CSTT screen 3 to the CPIT. Rows can be added from CSTT screen 1, 2, or 3. CSTT screen 2 can have an unlimited number of pages with four accounts per page. Each account being added must be selected by setting the flag in column 1 to the value Y before pressing the F3 key. Only one page with a maximum of four accounts can be added with the F3 key. Press the F3 key to add the CSTT row, up to four CACT rows, and up to 30 CPIT rows, then use the Shift-F3 keys to add more CACT rows.
F5	Update Record — Updates the CSTT row with information from CSTT screen 1 and updates selected CACT rows with information from accounts selected on CSTT screen 2. Rows in both the CSTT and CACT are updated from either CSTT screen 1 or 2. CSTT screen 2 can have an unlimited number of pages with four accounts per page. Each account being updated must be identified by setting the flag in column 1 to the value Y before pressing the F5 key. The F5 key must be used to update accounts on the current screen page before you display another CSTT screen 2 page. If you do not press the F5 key before displaying another page, the selected accounts will not be updated in the table. Note: You must have security access to the FIID in the CSTT row to be updated.

Key	Description
F6	Read Next Record — Reads the next row in the CSTT, the first four associated account rows from the CACT, and the first 30 associated personal ID rows from the CPIT for the next CSTT row. CSTT screen 2 can have an unlimited number of pages with four accounts per page. Press the Shift-F7 or Shift-F8 keys as needed to read and display the previous or next four CACT rows associated with the same customer ID. Using this function key, you can read CACT rows using any of the following field combinations: • CUSTOMER ID field on screen 1 • CUSTOMER ID field on screen 1 and ACCOUNT TYPE field on screen 2 • CUSTOMER ID field on screen 1 and ACCOUNT NUMBER field on screen 2 • CUSTOMER ID field on screen 1, and ACCOUNT TYPE and ACCOUNT NUMBER fields on screen 2 Note: You must have security access to the FIID in the next CSTT row to be read.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.
Shift-F3	Add Account Record — Adds the information for selected accounts from the current page of CSTT screen 2 to the CACT. This function is valid only on CSTT screen 2 and a CSTT row must already exist. CSTT screen 2 can have an unlimited number of pages with four accounts per page. Each account being added must be selected by setting the flag in column 1 to the value Y before pressing the Shift-F3 keys. The Shift-F3 keys must be used to add accounts on the current screen page before you display another CSTT screen 2 page. If you do not press the Shift-F3 keys before displaying another page, the selected accounts will not be added to the table.

Key	Description
Shift-F4	Delete Account Record — Deletes rows for selected accounts from the CACT. Rows being deleted must be selected on CSTT screen 2. These keys are valid only on CSTT screen 2. CSTT screen 2 can have an unlimited number of pages with four accounts per page. Each account being deleted must be selected by setting the flag in column 1 to the value Y before pressing the Shift-F4 keys. The Shift-F4 keys must be used to delete accounts on the current screen page before you display another CSTT screen 2 page. If you do not press the Shift-F4 keys before displaying another page, the selected accounts will not be deleted from the table.
Shift-F7	View Previous Page of Multi-Page Entry — Reads and displays the previous four CACT rows that are associated with the current CSTT row.
Shift-F8	View Next Page of Multi-Page Entry — Reads and displays the next four CACT rows that are associated with the current CSTT row.

Screen 2

CSTT screen 2 defines each application account belonging to a particular CSTT row. This screen maintains rows in the Customer/Account Relation Table (CACT). Accounts are associated with a CSTT row using the unique customer ID defined on CSTT screen 1. CSTT screen 2 is shown below, followed by descriptions of its fields.

```
BASE24-CORE  CUSTOMER CONFIGURATION  LLLL          YY/MM/DD  hh:mm  02 OF 03
CUSTOMER ID:
ACCOUNT TYPE:          ACCOUNT NUMBER:

TYPE    ACCOUNT NUMBER/  FIID/    QUALIFIER/  STATUS    ACT ALWD
        DESCRIPTION      BEG DATE  END DATE
<1>

RECORD LAST CHANGED:          BY USER:          ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
SF3-ADD ACCOUNT RECORDS    SF4-DELETE ACCOUNT RECORDS    F12-HELP
```

CUSTOMER ID — The unique identification number assigned to this CSTT row on CSTT screen 1.

Field Length: System-protected
Column Name: CACT.PAN

ACCOUNT TYPE — A code identifying the type of application account to be read when the **F2** or **F6** key is pressed. The code entered here must already be defined in the Account Type Table File (ATT). Use of this field is optional. Refer to the topic “Screen 2 Function Keys” earlier in this section for inquiry options.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: Not applicable

ACCOUNT NUMBER — The account number of an existing application account to be read when the **F2** or **F6** key is pressed. Use of this field is optional. Refer to the topic “Screen 2 Function Keys” earlier in this section for inquiry options.

Field Length: 1–19 numeric characters
Required Field: No
Default Value: No default value
Column Name: Not applicable

<1> — A code indicating whether the application account on a particular line is to be included when an add, delete, or update function is performed. This code also identifies accounts with errors when information is being added or updated. Valid values are as follows:

Y = Yes, add, delete, or update customer account information for this account.
N = No, do not add, delete, or update customer account information for this account.
E = Information on this line contains one or more errors.

You can set this field to the value Y or N. This field is set to the value E when an error is found through system validation after an attempt to add or update an account.

Field Length: 1 alphabetic character
Required Field: Yes, if the line contains an account.
Default Value: N
Column Name: Not applicable

TYPE — A code indicating the type of application account. The code must already be defined in the Account Type Table File (ATT).

Field Length: 1–6 alphanumeric characters
Required Field: Yes, if the line contains an account.
Default Value: No default value
Column Name: CACT.ACCT_TYP

ACCOUNT NUMBER — The application account number.

When an Integrated Authorization Server process encounters duplicate account numbers in the CACT, it uses different search strategies to select an account for the transaction. For detailed information on the specific search strategies used by an Integrated Authorization Server process to differentiate duplicate accounts, refer to the *BASE24 Remote Banking Transaction Processing Manual*.

Field Length: 1–19 numeric characters
Required Field: Yes, if the line contains an account.
Default Value: No default value
Column Name: CACT.ACCT

FIID — The FIID of the customer's financial institution for this application account.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: The FIID entered on CSTT screen 1.
Column Name: CACT.FIID

QUALIFIER — A user-defined code that can be used in place of the application account number and account type to identify and access this account. This field contains the qualifier of an existing account to be read when the **F2** or **F6** key is pressed.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CACT.ACCT_QUAL

STATUS — A code indicating the current status of the application account and the action to be taken by the Integrated Authorization Server process if this account status is encountered during transaction processing. Valid values are as follows:

Value	Status	Action
0, A, B, C	No relationship (inactive account)	Deny transactions.
1, D, E, F, G, H, I	Open	Accept transactions.

Value	Status	Action
2, J, K, L	Restricted to deposits	Accept all transactions except transfers and payments from this account.
3, M, N, O, P, Q, R	Open primary account	Accept transactions.
4, S, T, U	Primary account restricted to deposits	Accept all transactions except transfers and payments from this account.
9, V, W, X, Y, Z	Closed	Deny transactions.

BASE24 products do not distinguish between the alphabetic and numeric values grouped together above. The alphabetic values are intended to give institutions a wider range of values for assigning account statuses.

A description of the current status is displayed immediately to the right of the value in the STATUS field.

Field Length: 1 alphanumeric character
 Required Field: Yes, if the line contains an account.
 Default Value: 0
 Column Name: CACT.STAT

ACT ALWD

The following fields contain codes indicating whether the customer can perform specific types of transactions on an application account.

DB — A code indicating whether the customer can perform debit transactions on the account. Debit transactions include transfers and payments from this account. Valid values are as follows:

Y = Yes, allow debit transactions.
 N = No, do not allow debit transactions.

Field Length: 1 alphabetic character
Required Field: Yes, if the line contains an account.
Default Value: N
Column Name: CACT.ACT_ALWD_DB

CR — A code indicating whether the customer can perform credit transactions on the account. Credit transactions include transfers to this account. Valid values are as follows:

Y = Yes, allow credit transactions.
N = No, do not allow credit transactions.

Field Length: 1 alphabetic character
Required Field: Yes, if the line contains an account.
Default Value: N
Column Name: CACT.ACT_ALWD_CR

INQ — A code indicating whether the customer can perform inquiry transactions (for example, available funds inquiry and scheduled transfers list inquiry) on the account. Valid values are as follows:

Y = Yes, allow inquiry transactions.
N = No, do not allow inquiry transactions.

Field Length: 1 alphabetic character
Required Field: Yes, if the line contains an account.
Default Value: N
Column Name: CACT.ACT_ALWD_INQ

DESCRIPTION — A text description for the application account.

Field Length: 1–15 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CACT.DESCR

BEG DATE — The first date (YYYYMMDD) this account can be used in processing. If the field is left blank, the Customer/Account Relation Table Maintenance Server process fills in the current date when the row is added or updated.

Field Length: 8 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: CACT.BEG_DAT

END DATE — The last date (YYYYMMDD) this account can be used in processing. If the field is left blank, this row does not expire.

When a customer account activate transaction is processed for this customer account, the value of this field is set to the value of the END DATE field in the default CACT row for the customer's financial institution.

When a customer account deactivate transaction is processed for this customer account, this field is set to a value one less than the current date.

Field Length: 8 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: CACT.END_DAT

Screen 3 Function Keys

The use of nine function keys on CSTT screen 3 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on CSTT screen 3.

Key	Description
F2	Read Record — Reads one row from the Customer Table (CSTT), the first four account rows from the Customer Account Relation Table (CACT), and the first 30 rows from the Customer/Personal ID Relation Table (CPIT) for the specified customer ID. Rows in the CPIT are read based on the value in the CUSTOMER ID field on CSTT screen 1. CSTT screen 3 can have an unlimited number of pages with 30 personal IDs per page. Press the Shift-F7 or Shift-F8 keys as needed to read and display the previous or next 30 CPIT rows associated with the same customer ID.
F3	Add Record — Writes the current information from CSTT screen 1 to the CSTT, writes the information for currently selected accounts from CSTT screen 2 to the CACT, and writes the information for currently displayed and selected personal IDs from CSTT screen 3 to the CPIT. Rows can be added from CSTT screen 1, 2, or 3. CSTT screen 3 can have an unlimited number of pages with 30 personal IDs per page. Each personal ID being added must be selected by setting the flag in column 1 to the value Y before pressing the F3 key. Only one page with a maximum of 30 personal IDs can be added with the F3 key. Press the F3 key to add the CSTT row, up to four CACT rows, and up to 30 CPIT rows, then use the Shift-F3 keys to add more CPIT rows.
F5	Update Record — This key is not valid on CSTT screen 3. To update CPIT rows, you must first delete the rows using the Shift-F4 keys and then add rows containing the desired changes using the Shift-F3 keys.

Key	Description
F6	Read Next Record — Reads the next row in the CSTT, the first four associated account rows from the CACT, and the first 30 associated personal ID rows from the CPIT associated with the next CSTT row. CSTT screen 3 can have an unlimited number of pages with 30 personal IDs per page. Press the Shift-F7 or Shift-F8 keys as needed to read and display the next or previous 30 CPIT rows associated with the same CSTT row.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.
Shift-F3	Add Customer/Personal ID Record — Adds the information for selected personal IDs from the current page of CSTT screen 3 to the CPIT. These keys are valid only on CSTT screen 3 and a CSTT row must already exist. CSTT screen 3 can have an unlimited number of pages with 30 personal IDs per page. Each personal ID being added must be selected by setting the flag in column 1 to the value Y before pressing the Shift-F3 keys. The Shift-F3 keys must be used to add personal IDs on the current screen page before you display another CSTT screen 3 page. If you do not press the Shift-F3 keys before displaying another page, the selected personal IDs will not be added to the table.
Shift-F4	Delete Customer/Personal ID Record — Deletes rows for selected personal IDs from the CPIT. Rows being deleted must be selected on CSTT screen 3. CSTT screen 3 can have an unlimited number of pages with 30 personal IDs per page. Each personal ID being deleted must be selected by setting the flag in column 1 to the value Y before pressing the Shift-F4 keys. The Shift-F4 keys must be used to delete personal IDs on the current screen page before you display another screen 3 page. If you do not press the Shift-F4 keys before displaying another page, the selected personal IDs will not be deleted from the table.

Key	Description
Shift-F7	View Previous Page of Multi-Page Entry — Reads and displays the previous 30 CPIT rows associated with the current CSTT row.
Shift-F8	View Next Page of Multi-Page Entry — Reads and displays the next 30 CPIT rows that are associated with the current CSTT row.

Screen 3

CSTT screen 3 defines each of the valid personal IDs associated with a customer ID in the Customer/Personal ID Relation Table (CPIT). This screen enables a single customer ID to be associated with multiple persons. Personal Information Table (PIT) screen 2 allows a single person to be associated with multiple customer IDs. Both screens maintain data in the CPIT. Personal IDs entered on CSTT screen 3 should first be defined to the Personal Information Table (PIT). CSTT screen 3 is shown below, followed by descriptions of its fields.

BASE24-CORE
CUSTOMER CONFIGURATION
LLLL
YY/MM/DD
hh:mm
03 OF 03

CUSTOMER ID:
PERSONAL ID
PERSONAL ID

<2>
<2>

RECORD LAST CHANGED:
BY USER:

BASE24

NEW PAGE:
FILE DESTINATION:
NEW LOGICAL NETWORK ID:

SF3-ADD CUST/PRSNL ID RECORDS
SF4-DELETE CUST/PRSNL ID RECORDS
F12-HELP

CUSTOMER ID — The unique identification number assigned to this CSTT row on CSTT screen 1.

Field Length: System-protected
Column Name: CPIT.PAN

PERSONAL ID — A code identifying a row in the Personal Information Table (PIT). Each personal ID associates a different person with access to the CSTT row identified in the CUSTOMER ID field. The code entered here should already be defined in the PERSONAL ID field of a PIT row.

Note: Personal IDs should not be confused with the personal identification number (PIN) used in PIN verification processing. The PIN offset for a CSTT row is specified in the PIN VERIFICATION DIGITS field on CSTT screen 1.

Field Length: 30 fields of 1–19 alphanumeric characters each
Required Field: Yes, if this line is selected.
Default Value: No default value
Column Name: CPIT.PRSNL_ID

<2> — A code indicating whether the personal ID on a particular line and column is to be included when an add, delete, or update function is performed. This code also identifies personal IDs with errors when information is being added or updated. Valid values are as follows:

Y = Yes, add, delete, or update the personal ID for this customer ID.
N = No, do not add, delete, or update the personal ID for this customer ID.
E = An error was found while attempting to add or update the personal ID for this customer ID.

You can set this field to the value Y or N. This field is set to the value E when an error is found through system validation after an attempt to add or update a personal ID.

Field Length: 1 alphabetic character
Required Field: Yes, if the line contains an account.
Default Value: N
Column Name: Not applicable

Section 6

File Control File (FCF)

The File Control File (FCF) contains version records of Enscribe files for full-file refresh purposes. Each FCF record contains a version indicator that is used to identify the newest version of a file. Currently, version records are maintained in the FCF for the Transaction History File (THF) only.

For most BASE24 files, the BASE24 Enscribe Refresh process renames the existing file and builds a new file with the name originally assigned to the old file when performing full-file refreshes. However, the THF is audited by the Tandem Transaction Monitoring Facility (TMF). A file that is audited by TMF cannot be renamed.

When performing a full-file refresh of the THF, the BASE24 Enscribe Refresh process develops a new name for each file it builds instead of renaming the old file. The BASE24 Enscribe Refresh process creates the new file names by appending a one-character version indicator to the end of the file name defined in the Logical Network Configuration File (LCONF). The BASE24 Enscribe Refresh process then updates the FCF with the version indicator of the new file.

The key to the FCF is a combination of values in the FILE and GROUP fields.

Screen 1

FCF screen 1 allows you to establish version indicators for new versions of files created during full-file refresh processing. The FCF screen is shown below, followed by descriptions of its fields.

```

BASE24-CORE  FILE CONTROL          LLLL          YY/MM/DD  hh:mm  01 OF 01

          FILE:                     GROUP:

VERSION INDICATOR:

RECORD LAST CHANGED:                BY USER:      ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                      F12-HELP

```

FILE — A code identifying the type of file controlled by this FCF record. Currently, the only valid value is THF for the Transaction History File.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: FCF.PRIKEY.TYP

GROUP — The Logical Network Configuration File (LCONF) assign name associated with the Transaction History File (THF) controlled by this FCF record. Valid values are entries that start with THF- and have no embedded spaces.

Multiple THFs can exist in a logical network and each THF must have its own version indicator. The value in the GROUP field uniquely identifies which THF is controlled.

A File Control File (FCF) record with a value of THF in the FILE field should exist for each record in the Transaction History Configuration File (THCF). The value in this field should match the value in the ASSIGN field on screens 1 and 2 of the corresponding THCF record.

Field Length: 1–32 alphanumeric characters
Required Field: Yes, if the FILE field contains a value of THF.
Default Value: No default value
Data Name: FCF.PRIKEY.GRP

VERSION INDICATOR — A code identifying the version of the file controlled by this FCF record. Valid values are A through Z. When all valid values have been used, the values wrap from Z back to A.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: No default value
Data Name: FCF.IND

ACI Worldwide Inc.

Section 7

Institution Routing Configuration File (IRCF)

The Institution Routing Configuration File (IRCF) contains one record for each possible combination of product ID, route profile, route code, and account type in the system. Through configuration of IRCF records, institutions define the routing and authorization parameters for their transactions. Institutions can share common routing and authorization configurations through the specification of a common route profile. Processing codes share common routing and authorization configurations through the specification of a common route code.

A one-sided transaction uses one IRCF record and a two-sided transaction (for example, a transfer) uses two IRCF records. When two IRCF records are required, one record is read based on the *from* account and the other is read based on the *to* account.

A wildcard value of asterisks is supported for the route profile, route code, and account type. The following hierarchy is used when searching for an IRCF record. The fields in the following table also serve as the key to the IRCF:

Selection Hierarchy	PROD ID	ROUTE PROFILE	ROUTE CODE	ACCOUNT TYPE
1	Match	Match	Match	Match
2	Match	Match	Match	*****
3	Match	Match	****	Match
4	Match	*****	Match	Match
5	Match	Match	****	*****
6	Match	*****	Match	*****

Selection Hierarchy	PROD ID	ROUTE PROFILE	ROUTE CODE	ACCOUNT TYPE
7	Match	*****	****	Match
8	Match	*****	****	*****

Information from the IRCF is used in the institution routing extended memory table. Any time a change is made to the IRCF, the institution routing extended memory table should be rebuilt using the Extended Memory Table Build utility and reallocated to objects that access the table using the EMT Warmboot command.

Screen 1

IRCF screen 1 enables you to define routing and authorization configurations on behalf of financial institutions. The IRCF screen is shown below, followed by descriptions of its fields.

BASE24-CORE

INST RTE CNFG FILE

LLLL

YY/MM/DD hh:mm 01 OF 01

PROD ID: 14

ROUTE PROFILE: *****

ROUTE CODE: ****

ACCOUNT TYPE: *****

AUTH LEVEL: 0 (*****)

OVER FLOOR LIMIT

AUTH DESTINATION NAME:

AUTH DESTINATION TYPE:

AUTH METHOD:

DEFAULT AUTH ACTION: (*****)

UNDER FLOOR LIMIT

AUTH DESTINATION NAME:

AUTH DESTINATION TYPE:

AUTH METHOD:

DEFAULT AUTH ACTION: (*****)

DEFAULT AUTH CEILING LIMIT: 0

RECORD LAST CHANGED:

BY USER: ,

***** BASE24 *****

NEW PAGE: FILE DESTINATION: NEW LOGICAL NETWORK ID:

F12-HELP

PROD ID — A code identifying the BASE24 product using the information in this record. The valid value is 14 for the BASE24-telebanking and BASE24-billpay products.

Field Length: 2 numeric characters
 Required Field: Yes
 Default Value: 14
 Data Name: IRCF.PRIKEY.PROD-ID

ROUTE PROFILE — A code identifying the route profile for this configuration. The route profile is defined at the institution level in the ROUTE PROFILE field on Institution Definition File (IDF) screen 40 and permits institutions to share routing and authorization configurations. Valid values are alphanumeric characters or eight asterisks.

Field Length: 1–8 alphanumeric characters
Required Field: Yes
Default Value: *****
Data Name: IRCF.PRIKEY.RTE-PRFL

ROUTE CODE — A value used to group transactions for routing and authorization purposes when multiple destinations must be defined for an institution. The route code is defined at the processing code level in the ROUTE CODE field on Processing Code Definition File (PCDF) screen 1. Valid values are alphanumeric characters or four asterisks.

For institutions that route BASE24-billpay transactions to the XPNET Billpay Server process, the reserved value of BP~~00~~ must be used in this field. If your system uses large messages, some BASE24-billpay transactions cannot be routed to a host. These transactions must always be routed to the XPNET Billpay Server process as described under “Routing Restrictions” in section 13 of this manual.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: ****
Data Name: IRCF.PRIKEY.RTE-CDE

ACCOUNT TYPE — A code identifying the account type for this configuration. Valid values are alphanumeric characters or six asterisks. Values other than six asterisks must be defined in the Account Type Table File (ATT).

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: *****
Data Name: IRCF.PRIKEY.ACCT-TYP

AUTH LEVEL — A code identifying the authorization level for transactions meeting this configuration. Valid values are as follows:

- 1 = Online
- 2 = Offline
- 3 = Online/offline

This field must be set to the value 1 when the ROUTE CODE field is set to the value BP~~00~~ for the BASE24-billpay product.

A description of the code entered is displayed immediately to the right of the value in the AUTH LEVEL field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: No default value
Data Name: IRCF.AUTH-LVL

OVER FLOOR LIMIT

The following fields are used when the transaction amount is over the floor limit. All BASE24-telebanking and BASE24-billpay transactions are considered to be over the floor limit.

AUTH DESTINATION NAME — The symbolic name of the authorization destination.

The BASE24-telebanking and BASE24-billpay products can authorize transactions or send transactions to a data processing center (DPC) for authorization. Both the BASE24-telebanking and BASE24-billpay products use the BASE24 ISO Host Interface process to communicate with DPCs. This field is required when the BASE24 ISO Host Interface process is used (AUTH LEVEL field set to the values 1 or 3). This field is optional when the BASE24 ISO Host Interface process is not used (AUTH LEVEL field set to the value 2). This field is also required if advices are to be sent to the DPC for transactions authorized by the Integrated Authorization Server process.

For institutions that route BASE24-billpay transactions to the XPNET Billpay Server process, the reserved value of BPSRV must be used in this field.

The value in this field must match the value in the INTERFACE DESTINATION field in the Internal Message Translation File (IMTF).

Field Length: 1–16 alphanumeric characters
Required Field: Yes, if the value in the AUTH LEVEL field is 1 or 3 and optional if the value in the AUTH LEVEL field is 2. This field is also required if advices are sent to the DPC.
Default Value: No default value
Data Name: IRCF.OVER-FLR.AUTH-NAM

AUTH DESTINATION TYPE — The name of the object responsible for communicating with the DPC. The only valid value is IMTT for the Internal Message Translation Interface object. The Internal Message Translation Interface object creates an internal message that is recognized by the BASE24 ISO Host Interface process.

A description of the object name entered is displayed immediately to the right of the value in the AUTH DESTINATION TYPE field.

Field Length: 1–4 alphanumeric characters
Required Field: Yes, if the OVER FLOOR LIMIT AUTH DESTINATION NAME field contains an entry.
Default Value: No default value
Data Name: IRCF.OVER-FLR.AUTH-OBJ-NAM

AUTH METHOD — A code identifying the authorization method for transactions meeting this configuration. Valid values are as follows:

PCA = Positive Customer Authorization
PCAA = Positive Customer with Accounts Authorization
PCBA = Positive Customer with Balances/History Authorization

A description of the code entered is displayed immediately to the right of the value in the AUTH METHOD field.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: IRCF.OVER-FLR.AUTH-TYP-OBJ-NAM

DEFAULT AUTH ACTION — A code identifying the default authorization method to take for transactions meeting this configuration if the authorizer specified in the AUTH DESTINATION NAME field is unavailable. Valid values include the following:

A = Approve
D = Decline
R = Refer
␣ = Not applicable

The BASE24-telebanking product requires a setting of ␣ in this field, where ␣ indicates a blank.

A description of the code entered is displayed immediately to the right of the value in the DEFAULT AUTH ACTION field.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: No default value
Data Name: IRCF.OVER-FLR.DFLT-AUTH-ACT

UNDER FLOOR LIMIT

The following fields are used when the transaction amount is under the floor limit.

The BASE24-telebanking and BASE24-billpay products do not use these fields because all BASE24-telebanking and BASE24-billpay transactions are considered to be over the floor limit.

AUTH DESTINATION NAME — The symbolic name of the authorization destination.

The value in this field must match the value in the INTERFACE DESTINATION field in the Internal Message Translation File (IMTF).

Field Length: 1–16 alphanumeric characters
Required Field: Yes, if the value in the AUTH LEVEL field is 1 or 3 and optional if the value in the AUTH LEVEL field is 2. This field is also required if advices are sent to the DPC.
Default Value: No default value
Data Name: IRCF.UNDER-FLR.AUTH-NAM

AUTH DESTINATION TYPE — The name of the object responsible for communicating with the DPC. The only valid value is IMTT for the Internal Message Translation Interface object. The Internal Message Translation Interface object creates an internal message that is recognized by the BASE24 ISO Host Interface process.

A description of the object entered is displayed immediately to the right of the value in the AUTH DESTINATION TYPE field.

Field Length: 1–4 alphanumeric characters
Required Field: Yes, if the UNDER FLOOR LIMIT AUTH DESTINATION NAME field contains an entry.
Default Value: No default value
Data Name: IRCF.UNDER-FLR.AUTH-OBJ-NAM

AUTH METHOD — A code identifying the authorization method for transactions meeting this configuration. Valid values are as follows:

PCA = Positive Customer Authorization
PCAA = Positive Customer with Accounts Authorization
PCBA = Positive Customer with Balances/History Authorization

A description of the code entered is displayed immediately to the right of the value in the AUTH METHOD field.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: IRCF.UNDER-FLR.AUTH-TYP-OBJ-NAM

DEFAULT AUTH ACTION — A code identifying the default authorization method to take for transactions meeting this configuration if the authorizer specified in the AUTH DESTINATION NAME field is unavailable. Valid values include the following:

A = Approve
D = Decline
R = Refer
b = Not applicable

A description of the code entered is displayed immediately to the right of the value in the DEFAULT AUTH ACTION field.

Field Length: 1 alphanumeric character
Required Field: No
Default Value: No default value
Data Name: IRCF.UNDER-FLR.DFLT-AUTH-ACT

DEFAULT AUTH CEILING LIMIT — The maximum amount, in whole currency units (for example, dollars), of a transaction authorized using the action specified in either of the DEFAULT AUTH ACTION fields on this screen. If the transaction amount exceeds the amount in this field, the transaction is referred to a live operator for further review.

The BASE24-telebanking and BASE24-billpay products do not use this field.

Field Length:	1–15 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IRCF.DFLT-AUTH-CEIL-LMT

ACI Worldwide Inc.

Section 8

Interface Security File (ISF)

The Interface Security File (ISF) contains the information and parameters required by integrated transaction services (ITS) interfaces for PIN encryption, PIN translation, message authentication, and dynamic key management. The Customer Service Interface and Remote Banking Standard Interface are the only ITS interfaces available at the present time. Message authentication currently is not used by any of these interfaces. Dynamic key management is supported for PIN encryption keys by the Remote Banking Standard Interface only.

The ISF contains information for issuer and acquirer interfaces. The Customer Service Interface and Remote Banking Standard Interface are acquirer interfaces. The Internal Message Translation Interface is an issuer interface, but it currently does not use the ISF because it does not perform PIN translation.

The ISF contains one record for each record in the ITS Interface Configuration File (IFCF). The IFCF contains one record for all customer service representative (CSR) terminals and one record for each group of up to 90 remote banking endpoint stations. Having one ISF record for each IFCF record enables an institution to configure security parameters for the CSR terminals and each group of remote banking endpoint stations. The VRU Configuration Data (VCD) screens are used to maintain the IFCF.

Procedural BASE24 processes such as the BASE24 ISO Host Interface process use the Key File (KEYF) instead of the ISF for transaction security parameters. Institutions using the BASE24-telebanking and BASE24-billpay products and authorizing transactions on a host must define transaction security parameters in both the KEYF and the ISF.

Information from the ISF is used in the Interface Security File extended memory table. Any time a change is made to the ISF, the Interface Security File extended memory table should be rebuilt by the Transaction Security object using the EMT Warmboot or LCONF Warmboot commands.

The key to records in the ISF is the value in the INTERFACE NAME field.

This section contains documentation for all of the screens used to access records in the ISF, as follows:

- Screen 1 contains PIN encryption parameters, message authentication parameters, and key transport key information.
- Screen 2 contains PIN transport key information.
- Screen 3 contains message authentication key information.
- Screen 4 contains data transport key information.

Field Naming Conventions

Interface Security File (ISF) screens use the following acronyms in field names for keys :

Acronym	Description
KAM	Key used to authenticate message data.
KDT	Key used to encrypt data for transport. This key also is used with a PIN transport key (KPT) to encrypt PINs for transport.
KKT-AM	Key used to encrypt message authentication keys (KAMs) for transport.
KKT-DT	Key used to encrypt data transport keys (KDTs) for transport.
KKT-PT	Key used to encrypt PIN transport keys (KPTs) for transport.
KPT	Key to encrypt PINs for transport.
VVK	Verification value (that is, check digits) associated with a key.

Screen 1

Interface Security File (ISF) screen 1 contains PIN encryption parameters, message authentication parameters, and key transport key information. ISF screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-CORE  INTERFACE SECURITY FILE  LLLL          YY/MM/DD  hh:mm  01 OF 04
                INTERFACE NAME:

EXTRN PIN ENCRYPT TYPE: H HARDWARE          INTRN PIN ENCRYPT TYPE: H HARDWARE
    PIN BLOCK FORMAT: 1 (ANSI)              PIN PAD CHARACTER: F
    PIN ENCRYPT LEVEL: 1 (SINGLE)            OLD KEY TIMER LIMIT:      0 (SEC)
        MAC ALGO: 0 (ANSI X9.19)          MAC ENCRYPT TYPE: N (NONE)

                                KEY TRANSPORT KEY INFORMATION
KEY LENGTH: 1 (SINGLE)
KKT-PT: 0000000000000000 0000000000000000  VVK: 0000  VARIANT: 0 (KKT)
KKT-AM: 0000000000000000 0000000000000000  VVK: 0000  VARIANT: 0 (KKT)
KKT-DT: 0000000000000000 0000000000000000  VVK: 0000  VARIANT: 0 (KKT)

RECORD LAST CHANGED:          BY USER:          ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                                F12-HELP

```

INTERFACE NAME — The name of the interface instance using the information in this ISF record. An interface instance provides a means of dividing interface processing according to specific business relationships and purposes. Interface processing is divided according to groups of stations, with up to 90 stations per each interface instance. For example, a separate interface instance could be used for each financial institution using the interface. One interface instance is used to define interface processing for all customer service representative (CSR) terminals. The value in this field must match the value in the INTERFACE NAME field on VRU Configuration Data (VCD) screen 1 for the same interface instance.

Field Length: 1–16 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: ISF.PRIKEY.INTF-NAM

EXTRN PIN ENCRYPT TYPE — Specifies the type of PIN encryption used or expected by the external entity. Valid values are as follows:

H = Hardware PIN encryption
N = None (clear PINs)
S = Software PIN encryption

If dynamic key management is used for this interface instance, this field must be set to a value of H.

A description of the code entered is displayed immediately to the right of the value in the EXTRN PIN ENCRYPT TYPE field.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: H
Data Name: ISF.PIN-ENCRYPT-TYP-EXTRN

INTRN PIN ENCRYPT TYPE — Specifies the type of PIN encryption used by BASE24 products. Valid values are as follows:

H = Hardware PIN encryption
N = None (clear PINs)
S = Software PIN encryption

If the value in the EXTRN PIN ENCRYPT TYPE field is S, the value in this field must be N or S. If the value in the EXTRN PIN ENCRYPT TYPE field is H or N, the value in this field can be H, N, or S.

A description of the code entered is displayed immediately to the right of the value in the INTRN PIN ENCRYPT TYPE field.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: H
Data Name: ISF.PIN-ENCRYPT-TYP-INTRN

PIN BLOCK FORMAT — Specifies the PIN block format of the PIN in external messages. Valid values are as follows:

0 = Clear PINs
1 = ANSI (PIN/PAN) PIN block
3 = PIN/PAD PIN block

If the value in the EXTRN PIN ENCRYPT TYPE field is N, the value in this field must be 0. If the value in the EXTRN PIN ENCRYPT TYPE field is H or S, the value in this field must be 1 or 3.

A description of the code entered is displayed immediately to the right of the value in the PIN BLOCK FORMAT field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 1
Data Name: ISF.PBT

PIN PAD CHARACTER — If the value in the PIN BLOCK FORMAT field is 3 (PIN/PAD), the value in this field specifies the pad character used in the formation of the external message PIN block. Valid values are A through F.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: F
Data Name: ISF.PINPAD-CHAR

PIN ENCRYPT LEVEL — A code identifying the level of encryption used for PINs exchanged between an external entity and BASE24 interfaces. The valid value is 1 (single).

A description of the code entered is displayed immediately to the right of the value in the PIN ENCRYPT LEVEL field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 1
Data Name: ISF.PIN-ENCRYPT-LVL

OLD KEY TIMER LIMIT — The maximum length of time, in seconds, that an old key can be used before it is automatically cleared by the interface when dynamic key management is enabled. The keys in the KPT1 and KPT2 fields on ISF screen 2, KAM1 and KAM2 fields on ISF screen 3, and KDT1 and KDT2 fields on ISF screen 4 permit information for two keys. The values in the CURRENT INDEX fields on each screen identify whether key number 1 or key number 2 is in use.

At the time a new key is placed in service, the other key becomes the old key. For example, if inbound PIN transport key (KPT) number 1 is currently in use when the BASE24 interface receives a new key, the new key is stored as KPT number 2. KPT number 2 becomes the current key and KPT number 1 becomes the old key. (If KPT number 2 is the current key, it becomes the old key and the new key is stored as KPT number 1.)

When processing a transaction, BASE24 interfaces use the new key for PIN processing or message authentication. If the security device used by a BASE24 interface detects an error because the external entity is still using the old key, it can repeat the PIN processing or message authentication using the old key before the BASE24 interface declines the transaction. The value in this field determines how long the old key is available. If the old key is not available, a second PIN processing or message authentication attempt is not made.

Message authentication is not currently supported by any acquirer interfaces.

If dynamic key management is not enabled for the interface instance, this field should be set to 0.

Valid values are as follows:

- 0 = The old key is not cleared.
- 1–99999 = The maximum length of time, in seconds, that an old key can be used before being cleared.

Field Length:	1–5 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	ISF.OLD-KEY-TIMER-LMT

MAC ALGO — A code identifying the algorithm used to generate message authentication codes (MACs). The only valid value is 0, based on the 1986 ANSI X9.19 standard, *Financial Institution Retail Message Authentication*.

A description of the code entered is displayed immediately to the right of the value in the MAC ALGO field.

This field currently is not used by any acquirer interfaces.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.MAC-ALGO

MAC ENCRYPT TYPE — A code specifying how message authentication is performed for messages exchanged between the external entity and the interface. Valid values are as follows:

H = Hardware MAC encryption
N = No message authentication code (MAC) encryption
S = Software MAC encryption

A description of the code entered is displayed immediately to the right of the value in the MAC ENCRYPT TYPE field.

This field is not currently used by any acquirer interfaces.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: ISF.MAC-TYP

KEY TRANSPORT KEY INFORMATION

When PIN, MAC, or data keys are transported between the interface and the external entity, they are encrypted under this key for the external entity. PIN, MAC, or data keys that an interface receives from an external entity also are encrypted under this key. The key transport keys must be manually exchanged between the two entities.

KEY LENGTH — A code identifying whether single- or double-length key transport keys (KKTs) are being used with this interface. Valid values are as follows:

1 = Single-length key transport keys
2 = Double-length key transport keys

This field is used by the Remote Banking Standard Interface only.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 1
Data Name: ISF.KKT-KEY-LGTH

KKT-PT — The security module-encrypted form of the key used to encrypt PIN transport keys (KPTs). There are two sets of 16 hexadecimal characters. The first set is used for single-length keys and both sets are used for double-length keys. Valid values for each position in this field are 0 through 9 and A through F. Both sets must contain 16 valid characters. If the value in the KEY LENGTH field is 1 (single-length keys), the second set of characters must be spaces.

This field is used by the Remote Banking Standard Interface only.

Field Length: 2 sets of 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.KKT.PT.KEYX

VVK — The verification value associated with the value in the KKT-PT field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

This field is used by the Remote Banking Standard Interface only.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.KKT.PT.VVK

VARIANT — A code that specifies the key variant to be applied to the KKT-PT key when translating PIN transport keys (KPTs). Valid values are as follows:

- 0 = Key transport key (KKT)
- 1 = PIN transport key (KPT)

A description of the code entered is displayed immediately to the right of the value in the VARIANT field.

This field is used by the Remote Banking Standard Interface only.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.KKT.PT-VARIANT

KKT-AM — The security module-encrypted form of the key used to encrypt message authentication keys (KAMs). There are two sets of 16 hexadecimal characters. The first set is used for single-length keys and both sets are used for double-length keys. Valid values for each position in this field are 0 through 9 and A through F. Both sets must contain 16 valid characters. If the value in the KEY LENGTH field is 1 (single-length keys), the second set of characters must be spaces.

This field is not currently used by any acquirer interfaces.

Field Length: 2 sets of 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.KKT.AM.KEYX

VVK — The verification value associated with the value in the KKT-AM field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

This field is not currently used by any acquirer interfaces.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.KKT.AM.VVK

VARIANT — A code that specifies the key variant to be applied to the KKT-AM key when translating message authentication keys (KAMs). Valid values are as follows:

- 0 = Key transport key (KKT)
- 3 = Message authentication key (KAM)

A description of the code entered is displayed immediately to the right of the value in the VARIANT field.

This field is not currently used by any acquirer interfaces.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.KKT.AM-VARIANT

KKT-DT — The security module-encrypted form of the key used to encrypt data transport keys (KDTs). There are two sets of 16 hexadecimal characters. The first set is used for single-length keys and both sets are used for double-length keys. Valid values for each position in this field are 0 through 9 and A through F. Both sets must contain 16 valid characters. If the value in the KEY LENGTH field is 1 (single-length keys), the second set of characters must be spaces.

This field is not currently used by any acquirer interfaces.

Field Length: 2 sets of 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.KKT.DT.KEYX

VVK — The verification value associated with the value in the KKT-DT field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

This field is not currently used by any acquirer interfaces.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.KKT.DT.VVK

VARIANT — A code that specifies the key variant to be applied to the KKT-DT key when translating data transport keys (KDTs). Valid values are as follows:

- 0 = Key transport key (KKT)
- 2 = Data transport key (KDT)

A description of the code entered is displayed immediately to the right of the value in the VARIANT field.

This field is not currently used by any acquirer interfaces.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.KKT.DT-VARIANT

Screen 2

ISF screen 2 contains PIN transport key information. ISF screen 2 is shown below, followed by descriptions of its fields.

BASE24-CORE
INTERFACE SECURITY FILE LLLL
YY/MM/DD hh:mm
02 OF 04

INTERFACE NAME:

PIN TRANSPORT KEY INFORMATION

INTERM SFTWR KEY: 0000000000000000
INTERM HDWR KEY: 0000000000000000

VVK: 0000

INBOUND KEYS:

KPT1: 0000000000000000
KPT2: 0000000000000000

VVK1: 0000
VVK2: 0000

CURRENT INDEX: 0
KEY COUNTER: 000000

OUTBOUND KEYS:

KPT1: 0000000000000000
KPT2: 0000000000000000

VVK1: 0000
VVK2: 0000

CURRENT INDEX: 0
KEY COUNTER: 000000

RECORD LAST CHANGED:
BY USER:

***** BASE24 *****

NEW PAGE:
FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F12-HELP

PIN TRANSPORT KEY INFORMATION

The following fields contain information for keys used to transport PINs between an external entity and BASE24.

Intermediate keys are used whenever a PIN that has been encrypted under a secure key (hardware PIN encryption) must be decrypted into the clear or when a PIN is in the clear and needs to be encrypted under a secure key.

INTERM SFTWR KEY — The clear version of the intermediate key. The key is encrypted in software for storage. A PIN that has been encrypted under the intermediate key at the security module is decrypted in software using the value in this field. A PIN that is in the clear is encrypted in software using the value in this field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INTERM.KPT-SFTWR

INTERM HDWR KEY — The hardware-encrypted intermediate key. A PIN that has been encrypted under a secure key is translated using the intermediate hardware key at the security module. A PIN that has been encrypted using the intermediate software key is translated to be encrypted under a secure key at the security module. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INTERM.KPT-HDWR.KEYX

VVK — The verification value associated with the value in the INTERM HDWR KEY field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INTERM.KPT-HDWR.VVK

INBOUND KEYS

The following fields contain the PIN keys used for inbound transactions (that is, transactions sent by the external entity to the BASE24 interface).

If external PIN management is performed in hardware, security module-encrypted keys are entered in these fields. If external PIN management is performed in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If external PIN management is performed in the clear, keys entered in these fields are not used.

KPT1 — The key used by the external entity to encrypt PINs in transactions sent to the BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KPT[0].KEYX

VVK1 — The verification value associated with the value in the KPT1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KPT[0].VVK

KPT2 — The key used by the external entity to encrypt PINs in transactions sent to the BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KPT[1].KEYX

VVK2 — The verification value associated with the value in the KPT2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KPT[1].VVK

CURRENT INDEX — Identifies the key the interface is currently using. Valid values are as follows:

- 0 = Value in the KPT1 field
- 1 = Value in the KPT2 field

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.INBND.KPT-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by a BASE24 interface. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

This field is used by the Remote Banking Standard Interface only.

Field Length: 6 hexadecimal characters
Required Field: Yes
Default Value: 000000
Data Name: ISF.INBND.KPT-CNTR

OUTBOUND KEYS

The following fields contain the PIN keys used for outbound transactions (that is, transactions sent to the external entity by the BASE24 interface).

If external PINs are encrypted in hardware, security module-encrypted keys are entered in these fields. If external PINs are encrypted in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If external PINs are not encrypted, the keys entered in these fields are not used.

Note: The Customer Service Interface and Remote Banking Standard Interface are acquirer-only interfaces, which do not use the outbound key fields on this screen.

KPT1 — The key used by BASE24 interfaces to encrypt PINs in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KPT[0].KEYX

VVK1 — The verification value associated with the value in the KPT1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KPT[0].VVK

KPT2 — The key used by BASE24 interfaces to encrypt PINs in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KPT[1].KEYX

VVK2 — The verification value associated with the value in the KPT2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KPT[1].VVK

CURRENT INDEX — Identifies the key that the interface is currently using.

Valid values are as follows:

0 = Value in the KPT1 field

1 = Value in the KPT2 field

Field Length: 1 numeric character

Required Field: Yes

Default Value: 0

Data Name: ISF.OUTBND.KPT-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by a BASE24 interface or the external entity. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Otherwise, the interface updates it automatically and attempts to resynchronize it with the external entity. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

Field Length: 6 hexadecimal characters

Required Field: Yes

Default Value: 000000

Data Name: ISF.OUTBND.KPT-CNTR

Screen 3

ISF screen 3 contains message authentication key information.

Note: The Customer Service Interface and Remote Banking Standard Interface do not support message authentication. Therefore, the fields on this screen are not used.

ISF screen 3 is shown below, followed by descriptions of its fields.

BASE24-CORE
INTERFACE SECURITY FILE
LLLL
YY/MM/DD
hh:mm
03 OF 04

INTERFACE NAME:

MESSAGE AUTHENTICATION KEY INFORMATION

INBOUND KEYS:

KAM1: 0000000000000000
VVK1: 0000

KAM2: 0000000000000000
VVK2: 0000

CURRENT INDEX: 0
KEY COUNTER: 000000

OUTBOUND KEYS:

KAM1: 0000000000000000
VVK1: 0000

KAM2: 0000000000000000
VVK2: 0000

CURRENT INDEX: 0
KEY COUNTER: 000000

RECORD LAST CHANGED:
BY USER:

***** BASE24 *****

NEW PAGE:
FILE DESTINATION:
NEW LOGICAL NETWORK ID:

F12-HELP

MESSAGE AUTHENTICATION KEY INFORMATION

The following fields contain information for keys used to authenticate messages exchanged between an external entity and the BASE24 interface.

INBOUND KEYS

The following fields contain the message authentication keys used for inbound transactions (that is, transactions sent by the external entity to the BASE24 interface).

If external message authentication is performed in hardware, security module-encrypted keys are entered in these fields. If external message authentication is performed in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If message authentication is not performed, the keys entered in these fields are not used.

KAM1 — The key used by the external entity to generate message authentication codes (MACs) in transactions sent to a BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KAM[0].KEYX

VVK1 — The verification value associated with the value in the KAM1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KAM[0].VVK

KAM2 — The key used by the external entity to generate MACs in transactions sent to a BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KAM[1].KEYX

VVK2 — The verification value associated with the value in the KAM2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KAM[1].VVK

CURRENT INDEX — Identifies the key the interface is currently using. Valid values are as follows:

0 = Value in the KAM1 field
1 = Value in the KAM2 field

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.INBND.KAM-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by a BASE24 interface or the external entity. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Otherwise, the interface updates it automatically and attempts to resynchronize it with the external entity. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

Field Length: 6 hexadecimal characters
Required Field: Yes
Default Value: 000000
Data Name: ISF.INBND.KAM-CNTR

OUTBOUND KEYS

The following fields contain the message authentication keys used for outbound transactions (that is, transactions sent to the external entity by the BASE24 interface).

If external message authentication is performed in hardware, security module-encrypted keys are entered in these fields. If external message authentication is performed in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If message authentication is not performed, the keys entered in these fields are not used.

KAM1 — The key used by BASE24 interfaces to encrypt message authentication codes (MACs) in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KAM[0].KEYX

VVK1 — The verification value associated with the value in the KAM1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KAM[0].VVK

KAM2 — The key used by BASE24 interfaces to encrypt MACs in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KAM[1].KEYX

VVK2 — The verification value associated with the value in the KAM2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KAM[1].VVK

CURRENT INDEX — Identifies the key the interface is currently using. Valid values are as follows:

0 = Value in the KAM1 field
1 = Value in the KAM2 field

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.OUTBND.KAM-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by a BASE24 interface or the external entity. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Otherwise, the interface updates it automatically and attempts to resynchronize it with the external entity. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

Field Length: 6 hexadecimal characters
Required Field: Yes
Default Value: 000000
Data Name: ISF.OUTBND.KAM-CNTR

Screen 4

ISF screen 4 contains data transport key information. Data transport keys are used for the encryption of data and with PIN transport keys (KPTs) to encrypt PINs for transportation.

Note: The Customer Service Interface and Remote Banking Standard Interface do not support the encryption of data or the encryption of PINs with two keys. Therefore, the fields on this screen are not used.

ISF screen 4 is shown below, followed by descriptions of its fields.

```
BASE24-CORE  INTERFACE SECURITY FILE  LLLL          YY/MM/DD  hh:mm  04 OF 04
                                INTERFACE NAME:

                                DATA TRANSPORT KEY INFORMATION

INBOUND KEYS:
      KDT1: 00000000000000000          VVK1: 0000
      KDT2: 00000000000000000          VVK2: 0000
      CURRENT INDEX: 0                  KEY COUNTER: 000000

OUTBOUND KEYS:
      KDT1: 00000000000000000          VVK1: 0000
      KDT2: 00000000000000000          VVK2: 0000
      CURRENT INDEX: 0                  KEY COUNTER: 000000

RECORD LAST CHANGED:                BY USER: ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                                F12-HELP
```

DATA TRANSPORT KEY INFORMATION

The following fields contain information for data transport keys.

INBOUND KEYS

The following fields contain the data transport keys used for inbound transactions (that is, transactions sent by the external entity to the BASE24 interface).

If external data is encrypted in hardware, security module-encrypted keys are entered in these fields. If external data is encrypted in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If external data is not encrypted, the keys entered in these fields are not used.

KDT1 — The key used by the external entity to encrypt data in transactions sent to the BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KDT[0].KEYX

VVK1 — The verification value associated with the value in the KDT1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KDT[0].VVK

KDT2 — The key used by the external entity to encrypt data in transactions sent to the BASE24 interface. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.INBND.KDT[1].KEYX

VVK2 — The verification value associated with the value in the KDT2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.INBND.KDT[1].VVK

CURRENT INDEX — Identifies the key the interface is currently using. Valid values are as follows:

0 = Value in the KDT1 field
1 = Value in the KDT2 field

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: ISF.INBND.KDT-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by a BASE24 interface or the external entity. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Otherwise, the interface updates it automatically and attempts to resynchronize it with the external entity. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

Field Length: 6 hexadecimal characters
Required Field: Yes
Default Value: 000000
Data Name: ISF.INBND.KDT-CNTR

OUTBOUND KEYS

The following fields contain the data transport keys used for outbound transactions (that is, transactions sent to the external entity by the BASE24 interface).

If external data is encrypted in hardware, security module-encrypted keys are entered in these fields. If external data is encrypted in software, clear keys are entered in these fields. However, they are encrypted in software for storage. If external data is not encrypted, the keys entered in these fields are not used.

KDT1 — The key used by the BASE24 interface to encrypt data in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 0. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KDT[0].KEYX

VVK1 — The verification value associated with the value in the KDT1 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KDT[0].VVK

KDT2 — The key used by the BASE24 interface to encrypt data in transactions sent to the external entity. The interface uses the key in this field when the CURRENT INDEX field contains a value of 1. Valid values for each position in this field are 0 through 9 and A through F. This field must contain 16 valid characters.

Field Length: 16 hexadecimal characters
Required Field: Yes
Default Value: 0000000000000000
Data Name: ISF.OUTBND.KDT[1].KEYX

VVK2 — The verification value associated with the value in the KDT2 field. Valid values for each position in this field are 0 through 9 and A through F. This field must contain four valid characters.

Field Length: 4 hexadecimal characters
Required Field: Yes
Default Value: 0000
Data Name: ISF.OUTBND.KDT[1].VVK

CURRENT INDEX — Identifies the key the interface is currently using. Valid values are as follows:

0 = Value in the KDT1 field

1 = Value in the KDT2 field

Field Length: 1 numeric character

Required Field: Yes

Default Value: 0

Data Name: ISF.OUTBND.KPT-IDX

KEY COUNTER — The number of times the key has been changed by dynamic key management processing.

This counter is updated whenever the key is changed by the BASE24 interface or the external entity. This value should require adjustment using file maintenance only if the external entity expects a value other than zero when dynamic key management is established. Otherwise, the interface updates it automatically and attempts to resynchronize it with the external entity. Valid values for each position in this field are 0 through 9 and A through F. This field must contain six valid characters.

Field Length: 6 hexadecimal characters

Required Field: Yes

Default Value: 000000

Data Name: ISF.OUTBND.KPT-CNTR

Section 9

Internal Message Translation File (IMTF)

The Internal Message Translation File (IMTF) is used by the Internal Message Translation Interface object in the Integrated Authorization Server process to map authorization destinations to symbolic process names and data processing center (DPC) numbers. The IMTF is used any time the Integrated Authorization Server process needs to communicate with an external authorizer or interface process destination that is not object-oriented. It is also used by the Internal Message Translation Interface object in the Integrated Authorization Server process or a Fraud Control process to validate a station or process when an inbound message is received from a source that is not object-oriented.

Information from the IMTF is used in the Internal Message Translation File extended memory table. Any time a change is made to the IMTF, the Internal Message Translation File extended memory table should be rebuilt using the Extended Memory Table Build utility and reallocated to objects that access the table using the EMT Warmboot command.

The value in the INTERFACE DESTINATION field is the key to the IMTF.

Authorization Destination Configuration

Currently, the Integrated Authorization Server process can communicate with the BASE24 ISO Host Interface process to communicate with an institution's DPC for both the BASE24-telebanking and BASE24-billpay applications. The BASE24 ISO Host Interface process is used to communicate with an institution's DPC.

Each pair of values in the PROCESS NAME and DPC NUMBER fields on the IMTF screen must have a matching pair of values in the HISF NAME and DPC NUMBER fields on screen 1 of a record in the Host Configuration File (HCF).

For the BASE24-billpay application, the Integrated Authorization Server communicates with the XPNET Billpay Server process to authorize certain BASE24-billpay transactions.

A separate IMTF record must be configured for each BASE24 ISO Host Interface and XPNET Billpay Server process to which the Integrated Authorization Server process can send messages. For each of these records, the value entered in the INTERFACE DESTINATION field on the IMTF screen must have a matching value in the AUTH DESTINATION NAME field of the Institution Routing Configuration File (IRCF). In addition, the value in the PROCESS NAME field must match a symbolic process name in the XPNET environment.

Source Validation Configuration

For all messages sent to the Integrated Authorization Server process in BASE24 Standard Internal Message format (BSTM), the Internal Message Translation Interface in the Integrated Authorization Server process or Fraud Control process reads the IMTF to validate the message source.

When a message is received from one of the following sources for the BASE24-telebanking or BASE24-billpay products, the Internal Message Translation Interface object in the Integrated Authorization Server process reads the IMTF, searching for a match using the symbolic name of the station or process from which the message originated:

- Customer service representative (CSR) stations
- XPNET Billpay Server process
- Scheduled Transaction Initiator process

When a message is received from one of the following sources for the BASE24-customer service/fraud control product, the Internal Message Translation Interface object in the Fraud Control process reads the IMTF, searching for the symbolic name of the process from which the message originated:

- BASE24-atm Authorization process
- BASE24-pos Device Handler/Router/Authorization process

If the object finds a record with the value of the INTERFACE DESTINATION field set to the symbolic name of the sending station or process, the station or process is considered to be valid. Therefore, an IMTF record must be configured for each BASE24-billpay CSR station, XPNET Billpay Server process, Scheduled Transaction Initiator process, BASE24-atm Authorization process, and BASE24-pos Device Handler/Router/Authorization process configured in the XPNET environment. Although the other required fields in these IMTF records are not used for validation, they must still contain valid values.

Note: For messages sent to the Integrated Authorization Server process in formats other than BSTM (for example, International Organization for Standardization or Internal Transaction Data format), the IMTF is not used for station or process validation. The interface objects (that is, Customer Service Interface and Voice Response Unit Interface) for these message sources use other means to validate the sending station or process.

Screen 1

IMTF screen 1 contains processing controls for the interface from an Integrated Authorization Server process to any process that is not object-oriented. This screen also contains valid process and station symbolic names for certain message sources. IMTF screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-CORE  INT MSG TRANSLATION FILE LLLL          YY/MM/DD  hh:mm  01 OF 01

      INTERFACE DESTINATION:

                PROCESS NAME:                      DPC NUMBER: 0000

DISCARD NON-FINANCIAL REVERSALS: Y (Y/N)             LOG ID: 0000
      CURRENCY CONVERSION GROUP:                     CURRENCY CODE: 840

                TIMER LIMITS
                OUTBOUND LIMIT:    20 (SEC)
      MINIMUM REQUEST LIMIT:      5 (SEC)


RECORD LAST CHANGED:                BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                F12-HELP

```

INTERFACE DESTINATION — The symbolic name of the authorization destination or the symbolic name of a valid process or station message source.

For authorization destinations, the value in this field must match the value in the AUTH DESTINATION NAME field in the Institution Routing Configuration File (IRCF). An IMTF record is required when the BASE24 ISO Host Interface process is used to communicate with an institution's data processing center (DPC). An IMTF record is also required to communicate with the XPNET Billpay Server process for the BASE24-billpay product.

For message sources, the value in this field must match the symbolic process name of the station or process from which a message is received as configured in the XPNET environment.

Each IMTF record must have a unique value in this field.

Field Length: 1–16 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: IMTF.PRIKEY.DEST

PROCESS NAME — The symbolic name of the nonobject-oriented process that communicates with the specified DPC. The symbolic name is assigned to a process in the XPNET environment.

Each pair of values in the PROCESS NAME and DPC NUMBER fields on this screen must have a matching pair of values in the HISF NAME and DPC NUMBER fields on screen 1 of a record in the Host Configuration File (HCF). Refer to the *BASE24 Base Files Maintenance Manual* for additional information regarding HCF screens.

For routing transactions to the XPNET Billpay Server process, this field must contain the symbolic name of the XPNET Billpay Server process or the name of a service if XPNET Billpay Server processes are defined to a service for service-based routing. For more information on service-based routing, refer to the *BASE24-XPNET Network Control Operations Guide*.

Wildcard characters can also be used in this field. A wildcard character (*) can be substituted in certain positions of the symbolic name. This enables the Integrated Authorization Server process to replace the asterisks with corresponding positions of its own symbolic name when selecting the ISO Host Interface process or XPNET Billpay Server process to which a message is to be forwarded. This feature allows for matching multiple Integrated Authorization Server processes to multiple ISO Host Interface processes or XPNET Billpay Server processes using a single record for each type of process. When wildcard characters are used, the symbolic name can have any number of leading asterisks, but can have no more than one trailing asterisk. If there are any asterisks in the process name, then the process name must start with an asterisk.

Examples: P1A^HISO1
 ***^HISO*
 P1A^BPSV1
 ***^BPSV*
 ***^STI*

Field Length: 1–16 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: IMTF.PRO-NAM

DPC NUMBER — The number of the institution's data processing center (DPC). This is the host computer that processes messages received from the BASE24 ISO Host Interface process. Valid values are 0000 through 9999.

Each pair of values in the PROCESS NAME and DPC NUMBER fields on this screen must have a matching pair of values in the HISF NAME and DPC NUMBER fields on screen 1 of a record in the Host Configuration File (HCF). Refer to the ***BASE24 Base Files Maintenance Manual*** for additional information regarding HCF screens.

Note: This field is not used by external processes that do not send messages to a host computer (for example, the XPNET Billpay Server process).

Field Length: 4 numeric characters
Required Field: No
Default Value: 0000
Data Name: IMTF.DPC-NUM

DISCARD NON-FINANCIAL REVERSALS — A code that identifies whether reversals of approved nonfinancial transactions should be discarded. Discarding reversals of nonfinancial transactions prevents unneeded message traffic to the destination for transactions that cannot really be reversed (for example, balance inquiry transactions). Valid values are as follows:

Y = Yes, discard reversals of nonfinancial transactions. Do not log them or forward them to the issuer.
N = No, do not discard reversals of nonfinancial transactions. Log them and forward them to the issuer.

Note: Some reversals for approved nonfinancial BASE24-billpay transactions (for example, scheduled payment and scheduled payment update transactions) may never be discarded—regardless of the value in this field—depending upon whether they were authorized by the BASE24-billpay product, a host, or a third-party processor. For detailed information on the processing performed for reversals of approved nonfinancial BASE24-billpay transactions, refer to the ***BASE24 Remote Banking Transaction Processing Manual***.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: IMTF.DISCRD-NON-FNCL-RVSL

LOG ID — A code identifying the log group for the ITS Transaction Log File (ITLF). Valid values are 0000 through 9999.

The log group defined in this field must fall within the range of groups defined in the START RANGE and END RANGE fields on Log Configuration File (LCF) screen 1.

Field Length: 4 numeric characters
Required Field: Yes
Default Value: 0000
Data Name: IMTF.LOG-GRP-ID

CURRENCY CONVERSION GROUP — This field identifies the group used to access the appropriate currency conversion rates. It is not used in processing.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IMTF.CC-GRP

CURRENCY CODE — A code indicating the currency used by the external authorizer. Currency code values are based on the 1990 ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: 3 numeric characters
Required Field: Yes
Default Value: Based on value of the LGNT-COUNTRY-ABBR param in the Logical Network Configuration File (LCONF).
Data Name: IMTF.CRNCY-CDE

TIMER LIMITS

The following fields contain limits for timers that can be used with a DPC, interchange, or external authorizer process.

OUTBOUND LIMIT — The number of seconds that the Internal Message Translation Interface object waits for a response from the external authorizer or interface process. This defines the maximum time a message can be queued by the XPNET process before it is delivered to the external authorizer or interface process. If the message is queued longer than the time specified in this field, it is

not delivered to the external authorizer or interface process. This option is designed to circumvent processing when it becomes apparent that sending the message does not give the external authorizer or interface process enough time to respond before the BASE24 product times out.

This field is also used to determine the amount of time remaining to process a transaction. If the actual transaction elapsed time subtracted from the authorization time limit established by the message acquirer is greater than the value of this field, the value of this field is used as the amount of time remaining to process a transaction. This amount is then compared against the value in the MINIMUM REQUEST LIMIT field to determine whether the message is sent. Refer to the MINIMUM REQUEST LIMIT field description for details. Valid values are 0 through 99999.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 20
Data Name: IMTF.TIMER-LMT.OUTBND-RQST

MINIMUM REQUEST LIMIT — The minimum number of seconds the external authorizer needs to authorize a transaction and return a response. Valid values are 0 through 99999. The value in this field must be less than the value in the OUTBOUND LIMIT field.

If the amount of time remaining to process a transaction (the actual transaction elapsed time subtracted from the authorization time limit established by the message acquirer or the value from the OUTBOUND LIMIT field, whichever is less) is less than the value in this field, the BASE24 product does not send the message to the host or authorizing process. The BASE24 product either attempts to stand in for the host/external authorizer process or declines the transaction, depending on the value in the AUTH LEVEL field on Institution Routing Configuration File (IRCF) screen 1.

The value in the AUTH REQUEST field on Voice Response Unit Configuration Data (VCD) screen 18 is the authorization time limit for the only message acquirer currently supported by an integrated server application.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 5
Data Name: IMTF.TIMER-LMT.MIN-RQST-TIM

Section 10

ITS Transaction Log File (ITLF)

The ITS Transaction Log File (ITLF) contains one record for each transaction processed by a BASE24 integrated server application during the business day. The BASE24-telebanking and BASE24-billpay products currently are the only integrated server applications. The ITLF records are extracted daily to provide detailed transaction data to participating institutions for processing at their host computer systems.

Note: Certain BASE24-billpay transactions are automatically logged to the ITLF, depending on the source of the transaction. Other BASE24-billpay transactions are optionally logged to the ITLF, depending on the configuration of the Bank Transaction Advice Table (BKAV). For a detailed discussion of which BASE24-billpay transactions are logged to the ITLF, refer to the ***BASE24 Remote Banking End-of-Period Processing and Reporting Manual***.

The ITLF is written sequentially. Records in the ITLF can be perused by reading the file both forward and backward. Reading the ITLF forward displays records in the order they were logged to the file. Reading the ITLF backward allows an operator to display the most recent records logged to the file without having to peruse all of the older transactions first.

The ITLF perusal function uses two types of screen formats—a summary format and a detail format. ITLF screen 1, referred to as the ITLF Summary screen throughout this section, displays summary information for 12 ITLF transactions at one time. The ITLF can be perused by customer ID or account number, depending on the key entered by the operator. There are two summary screen formats—account number and customer ID.

ITLF screen 2, referred to as the ITLF Detail screen throughout this section, displays detail information for any transaction appearing on ITLF screen 1. Seventeen detail screens are necessary to display all of the information that an ITLF record can contain. The first nine detail screens are displayed for each ITLF record. The last eight detail screens are displayed only when the ITLF record

contains information that is not displayed on one of the first nine detail screens. The detail screens are listed in the following table in the order in which they are displayed on ITLF screen 2.

Relative Order	Description
1	Transaction identification information
2	Acquirer and issuer general information
3	Issuer advice and routing information
4	Reason codes, original data information, and personal identification number (PIN) change information
5	Performance timer information
6	Point of service information
7	Backup account information
8	Transaction amounts and currency conversion fee information
9	Refresh impact information and refresh file indicators
10	Additional data
11	Acquirer dependent data
12	Authorization dependent data
13	Advice 1 dependent data
14	Advice 2 dependent data
15	BASE24-billpay transaction data
16	External acquirer dependent data
17	External authorizer dependent data

This section describes the ITLF Summary and Detail screens. It shows an illustration of each screen format and describes the information each screen format provides. The ITLF Summary screen is shown first, followed by the ITLF Detail screens. The ITLF Detail screens are presented in the relative order shown in the preceding table.

Summary Screen Function Keys

Using function keys, operators can perform the following tasks from the ITLF Summary screen:

- Display the first or last 12 records in the ITLF.
- Page forward or backward through the ITLF.
- Switch to the ITLF Detail screens and display the details of a particular record.

The function keys explained in the table below enable operators to perform these tasks. The use of these six function keys on the ITLF Summary screen varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on the ITLF Summary screen.

Key	Description
F1	First Page, Read Forward — Displays the first 12 transaction records in the ITLF and indicates the ITLF should be read from first record to last record. Refer to the topic “Paging Forward or Backward” later in this section for further explanation.
F2	Last Page, Read Backward — Displays the last 12 transaction records in the ITLF and indicates the ITLF should be read from last record to first record. Refer to the topic “Paging Forward or Backward” later in this section for further explanation.
F4	Goto Detail Screen — Switches to the ITLF Detail screens and displays the details for the selected record. A transaction record is selected by positioning the cursor on the same line as the summarized transaction when the F4 key is pressed.
F8	Clear Screen — Clears all the fields on the current screen except the logical network and date.

Key	Description
F9	Next Page — Reads the next 12 records in the ITLF and displays them on the ITLF Summary screen. The direction in which the file is being read determines the records read when this key is pressed. Refer to the topic “Paging Forward or Backward” later in this section for further explanation.
F11	Previous Page — Reads the previous 12 records in the ITLF and displays them on the ITLF Summary screen. The direction in which the file is being read determines the records read when this key is pressed. Refer to the topic “Paging Forward or Backward” later in this section for further explanation.

Paging Forward or Backward

Four function keys—**F1**, **F2**, **F9**, and **F11**—work together to control which records are read and displayed on the ITLF Summary screen. The **F1** and **F2** keys determine the direction in which the ITLF will be read, which in turn affects which records are read when the **F9** and **F11** keys are pressed.

Using an ITLF containing 60 records as an example, the following table illustrates how these function keys operate.

Paging Forward		Paging Backward	
Function Key Pressed	ITLF Records Displayed	Function Key Pressed	ITLF Records Displayed
F1	1–12	F2	49–60
F9	13–24	F9	37–48
F9	25–36	F9	25–36
F11	13–24	F11	37–48
F9	25–36	F9	25–36

Once the ITLF Summary screen is displayed and the operator has chosen a specific ITLF record to display on one of the ITLF Detail screen formats, the operator can read other detail records within the ITLF by perusing forward and backward through the file. However, the only detail records that can be accessed by perusing forward or backward in the file are those records that were displayed on the ITLF Summary screen.

For example, when records 13 through 24 are displayed on the ITLF Summary screen, an operator can choose to display detail for record number 15. When the detail for record number 15 is displayed, the operator can peruse back to the detail for record number 13 or forward to the detail for record number 24. The operator cannot access detail for records out of that range. To do so, the operator must return to the ITLF Summary screen and request a new range of records.

ITLF Summary Screen

The ITLF Summary screen formats display summary information about the records requested. Twelve ITLF records are displayed on the ITLF Summary screen at one time. There are two ITLF Summary screen formats, with the format displayed depending on the key requested. ITLF records can be perused by customer ID or by account number, but not by both.

Perusing the ITLF by Customer ID

When a value is entered in the CUSTOMER ID field, the ITLF Summary screen displays records for transactions initiated by the specified customer. Since the customer ID does not change, the summary fields displayed do not include the customer ID. The ITLF Summary screen displayed when a value is entered in the CUSTOMER ID field is shown below, followed by descriptions of its fields.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    01 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
ACCOUNT NUMBER                        TRANSACTION      RESP  TXN   TXN
<1>                                  DESCRIPTION      <m>  CODE  DATE   TIME

RECORD LAST CHANGED:                  BY USER: ,
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

CUSTOMER ID — The customer ID number involved in the transaction. When a customer ID number is entered, all transactions initiated by the specified customer are displayed for the date selected. The customer ID number entered must belong to the financial institution specified in the FIID field and the logical network specified in the LNET field.

Perusal can be done by customer ID or by account number. If a value is entered in the CUSTOMER ID field, the ACCT NUM field must be left blank. If a value is entered in the ACCT NUM field, the CUSTOMER ID field must be left blank.

Field Length: 1–19 alphanumeric characters
Required Field: Yes, if perusing by customer ID.
Default Value: No default value
Data Name: TLF.BUS-MLF.ALT-KEY2.PAN

FIID — The FIID of the institution that issued the customer ID or account number.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: TLF.BUS-MLF.ALT-KEY2.ISS.FIID for perusal by customer ID or TLF.BUS-MLF.ALT-KEY3.ISS.FIID for perusal by account number

ACCT NUM — The application account number involved in the transaction. When an account number is entered, all transactions performed on the specified account are displayed for the date selected. The account number entered must belong to the financial institution specified in the FIID field and the logical network specified in the LNET field.

Perusal can be done by customer ID or by account number. If a value is entered in the CUSTOMER ID field, the ACCT NUM field must be left blank. If a value is entered in the ACCT NUM field, the CUSTOMER ID field must be left blank.

Field Length: 1–19 numeric characters
Required Field: Yes, if perusing by account number.
Default Value: No default value
Data Name: TLF.BUS-MLF.ALT-KEY3.ACCT.NUM-BCD

LGNT — The logical network associated with the record.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: Current logical network
Data Name: TLF.BUS-MLF.ALT-KEY2.ISS.LGNT for perusal by customer ID or TLF.BUS-MLF.ALT-KEY3.ISS.LGNT for perusal by account number

DATE — The date (YYMMDD) of the ITLF used in selecting records to be displayed. The current system date is used if this field contains zeros or blanks.

Field Length: 6 numeric characters
Required Field: No
Default Value: Current system date
Data Name: Not applicable

ACCOUNT NUMBER — The application account number involved in the transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ALT-KEY3.ACCT.NUM-BCD

TRANSACTION DESCRIPTION — The type of transaction associated with this ITLF record. The information displayed in this field is obtained from the TXN-DESCR field in the Processing Code Definition File (PCDF) record associated with the processing code contained in the internal message.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.PROC-CDE

<m> — A code that indicates the type of message. Valid values are as follows:

F = Forced post (message type 1130 or 1230)
R = Reversal (message type 1430)
b = Response

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.MTI

RESP CODE — The response code associated with this transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ACT.CDE

TXN DATE — The calendar date on which the transaction was performed. The format of the date, MM/DD or DD/MM, is determined by the value of the DATE-DISPLAY-TYPE parameter in the Logical Network Configuration File (LCONF).

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.LOCAL-TXN.DAT

TXN TIME — The time (hh:mm) at which the transaction was performed.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.LOCAL-TXN.TIM

<1> — A field for selecting individual summarized ITLF records to display detailed transaction data. A transaction record is selected by positioning the cursor in this field on the same line as the summarized transaction when the **F4** key is pressed.

Field Length: 12 fields of 1 character each (cursor position only)
Required Field: No
Default Value: None
Data Name: Not applicable

Perusing the ITLF by Account Number

When a value is entered in the ACCT NUM field, the ITLF Summary screen displays records for transactions that affected that account. Since the account number does not change, the summary fields displayed do not include the account number. The ITLF Summary screen displayed when a value is entered in the ACCT NUM field is shown below, followed by descriptions of its fields.

The illustration is followed by a description of the CUSTOMER ID field. Refer to the topic “Perusing the ITLF by Customer ID” presented earlier in this section for descriptions of the remaining fields on this screen.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    01 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                     TRANSACTION      RESP  TXN    TXN
                                     DESCRIPTION        <m> CODE  DATE   TIME
<1>

RECORD LAST CHANGED:                  BY USER:      ,
***** BASE24 *****
FILE DESTINATION:                      NEW LOGICAL NETWORK ID:
F1-FIRST PAGE  F2-LAST PAGE  F4-DETAIL  F9-NEXT PAGE  F11-PREV PAGE  F12-HELP

```

CUSTOMER ID — The customer ID for the customer who initiated the transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ALT-KEY2.PAN

Detail Screen Function Keys

Using function keys from the ITLF Detail screens, operators can perform the following tasks:

- Page backward and forward through the ITLF Detail screens for the 12 transactions previously displayed on the ITLF Summary screen.
- Return to the ITLF Summary screen displayed previously.

The function keys explained in the table below enable operators to perform these tasks. The use of these five function keys on the ITLF Detail screens varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on the ITLF Detail screens.

Key	Description
F4	Go To Summary Screen — Returns to the ITLF Summary screen that was previously displayed.
F6	Next Record — Reads the next record for the transactions on the ITLF Summary screen that were previously displayed. Information continues to be displayed on the ITLF Detail screens. Pressing this key provides information for only those ITLF records that were listed on the ITLF Summary screen. Records listed on the ITLF Summary screen are selected from the top of that screen to the bottom of that screen.
F7	Prev Record — Reads the previous record for the transactions on the ITLF Summary screen that were previously displayed. Information continues to be displayed on the ITLF Detail screens. Pressing this key provides information for only those ITLF records that were listed on the ITLF Summary screen. Records listed on the ITLF Summary screen are selected from the bottom of that screen to the top of that screen.

Key	Description
F9	Next Page — Displays the next ITLF Detail screen for the current transaction. The detail screens available for a particular transaction depend on the information contained in the ITLF record. On ITLF Detail screen 11, this key displays subsequent pages of acquirer-dependent data until there is no more data. Then it displays ITLF Detail screen 12. On the last ITLF Detail screen available for a particular transaction, this key displays ITLF Detail screen 1.
F11	Previous Page — Displays the previous ITLF Detail screen for the current transaction. The detail screens available for a particular transaction depend on the information contained in the ITLF record. On ITLF Detail screen 11, this key displays previous pages of acquirer-dependent data until there is no more data. Then it displays ITLF Detail screen 10. On ITLF Detail screen 1, this key displays the last ITLF Detail screen available for a particular transaction.

One of the following messages appears at the bottom of each ITLF Detail screen to indicate whether additional detail screens exist for the current transaction:

- MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
- NO MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION

Detail Screen Fields

The screen illustrations for the ITLF Detail screens include all of the fields that can appear on each screen. However, all of the fields that can be displayed on a particular screen may not be needed to display the information in the ITLF record. Screen fields for which there is no data in the record are not displayed.

Each field on an ITLF detail screen is mandatory or optional. Mandatory fields have data names that start with TLF.BUS-MLF. Optional fields have data names that start with TLF.BUS-OLF. The type of field and presence of data in the field determine whether the label for the field appears on the screen. If a field is mandatory, it is always logged to the ITLF and its label always appears on the screen. A mandatory field is processed the same way with or without data. If a field is optional, it is logged to the ITLF and its label appears on the screen only when the field contains data.

Fields that contain data always appear in their original position on the screen. For example, the following illustration shows the detail screen for reason codes, original transaction data, and personal identification number (PIN) change information when only the mandatory fields are displayed.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                     TRANSACTION DETAIL

                                     *** ORIGINAL DATA INFO ***

MESSAGE SUBSTATE:  0

          POSTING DATE: 941117          ORIGINAL MESSAGE TYPE:

*** EXCEPTION REASON CODES ***          PRODUCT ID: 14

                                     DISCRIMINANT: 2

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
***** BASE24 *****
          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

As a comparison, all of the fields for this detail screen are shown below.
Descriptions for all fields on this detail screen are shown later in this section.

```
BASE24-CORE LOG FILE PERUSAL          LLLL      YY/MM/DD hh:mm      02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE (YYMMDD):  YYMMDD
                                     TRANSACTION DETAIL

      FUNCTION CODE:                   *** ORIGINAL DATA INFO ***
MESSAGE SUBSTATE:                     MESSAGE TYPE:
MESSAGE RSN CODE:                     STAN:
NEGATIVE RSN CODE:                   LOCAL TXN DAT/TIM:
      POSTING DATE:                   ACQ INST ID CODE:
      CVV STATUS:                     ORIGINAL MESSAGE TYPE:

*** EXCEPTION REASON CODES ***        PRODUCT ID:
      CODE:                          PVD OLD:
POST FLAG:                           PVD NEW:
OBJ NAME:                            PIN CHANGE REQUIRED:
REC TYPE:                            DISCRIMINANT:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
***** BASE24 *****
      FILE DESTINATION:                NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

Transaction Identification Information

Detail screen 1 contains transaction identification information. Detail screen 1 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                     TRANSACTION DETAIL

TXN DESCRIPTION:                      MESSAGE TYPE:
TXN DATE:                            TXN TIME:
ACCOUNT NUM 1:                       ACCOUNT TYPE 1:
ACCOUNT NUM 2:                       ACCOUNT TYPE 2:
CUSTOMER ID:                         SEQUENCE NUM:

TXN AMOUNT:                          CURRENCY CODE:
ORIGINATOR:                          APPROVAL CODE:
RESPONDER:
RESP CODE:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

TXN DESCRIPTION — A description of the transaction. This description is defined in the Processing Code Definition File (PCDF).

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.PROC-CDE

MESSAGE TYPE — The type of message that was logged to the ITLF. Requests are logged to the ITLF when an exception occurs. Valid values are as follows:

1100 = Authorization request to an integrated server process
1110 = Authorization request response from an integrated server process
1120 = Authorization advice to an integrated server process
1130 = Authorization advice response from an integrated server process
1200 = Financial request to an integrated server process

1210 = Financial response from an integrated server process
1220 = Financial advice to an integrated server process
1230 = Financial advice response from an integrated server process
1420 = Reversal advice to an integrated server process
1430 = Reversal advice response from an integrated server process

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.MTI

TXN DATE — The calendar date on which the transaction was performed. The format of the date (DD/MM or MM/DD) is specified by the DATE-DISPLAY-TYPE param in the LCONF.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.LOCAL-TXN.DAT

TXN TIME — The time (hh:mm:ss) at which the transaction was performed.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.LOCAL-TXN.TIM

ACCOUNT NUM 1 — The account number associated with the first account involved in transactions other than transfers. This account number is associated with the *from* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.ACCT1.NUM-BCD

ACCOUNT TYPE 1 — A code identifying the type of the first account involved in transactions other than transfers. This code identifies the *from* account involved in a transfer transaction. The code in this field is obtained from the Account Type Table File (ATT).

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.ACCT1.TYP

ACCOUNT NUM 2 — The account number associated with the second account involved in transactions other than transfers. This account number is associated with the *to* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.ACCT2.NUM-BCD

ACCOUNT TYPE 2 — A code identifying the type of the second account involved in transactions other than transfers. This code identifies the *to* account involved in a transfer transaction. The code in this field is obtained from the Account Type Table File (ATT).

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.ACCT2.TYP

CUSTOMER ID — The unique identification number associated with the customer who initiated the transaction.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ALT-KEY1.PAN

SEQUENCE NUM — The sequence number assigned to the transaction by a BASE24 product.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.SEQ-NUM

TXN AMOUNT — The amount of the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.TXN.AMT

CURRENCY CODE — A code that identifies the currency of the transaction acquirer. Currency code values are based on the 1990 ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.TXN.CRNCY-CDE

ORIGINATOR — A code indicating where the transaction originated. Valid values are as follows:

- 0 = Terminal
- 1 = Terminal object
- 2 = Switch or remote banking endpoint device
- 3 = Switch or VRU Interface object
- 4 = Host
- 5 = Host Interface object
- 6 = Authorization object
- 7 = Billpay Server process
- 8 = Scheduled Transaction Initiator process

The code is followed by a description.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.TXN-ORIGINATOR.FLG

APPROVAL CODE — The approval code assigned to the transaction by the transaction authorizer.

Field Length: System-protected
Data Name: TLF.BUS-OLF.APPRV.CDE

RESPONDER — A code indicating where the transaction was authorized. Valid values are as follows:

- 0 = Terminal
- 1 = Terminal object
- 2 = Switch or remote banking endpoint device
- 3 = Switch or VRU Interface object
- 4 = Host
- 5 = Host Interface object
- 6 = Authorization object
- 7 = Billpay Server process
- 8 = Scheduled Transaction Initiator process

The code is followed by a description.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.TXN-RESPONDER.FLG

RESP CODE — The response code associated with this transaction. The response code is followed by an action indicator code and a response code description.

Valid response codes are defined in the ***BASE24 Remote Banking Transaction Processing Manual***.

Field Length:	System-protected
Data Names:	TLF.BUS-MLF.ASCII.ACT.CDE TLF.BUS-MLF.ASCII.ACT.IND

Acquirer and Issuer General Information

Detail screen 2 contains acquirer and issuer general information. Detail screen 2 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                     TRANSACTION DETAIL

*** ACQUIRER INFORMATION ***          *** ISSUER INFORMATION ***
INST CNTRY CODE:                     INST ID CODE:
INST ID CODE:                        FIID:
FIID:                                LGNT:
LGNT:                                AUTH OBJECT:
ACQUIRER OBJECT:                     IMPACT 1 OBJECT:
TERMINAL ID:                         IMPACT 2 OBJECT:
                                     AUTH AGENT:
                                     AUTHORIZER:
                                     STAN:
DISCARD NON-FINANCIAL REVERSAL:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

ACQUIRER INFORMATION

The fields in this column contain information provided by the transaction acquirer.

INST CNTRY CODE — A code identifying the country where the acquiring institution is located. Country codes are based on the 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ACQ.INST-CNTRY-CDE

INST ID CODE — A code identifying the acquiring institution (for example, merchant bank) or its agent.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ACQ.ID-CDE

FIID — The FIID of financial institution that owns or sponsors the BASE24 terminal where the transaction was performed.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ACQ.FIID

LGNT — The logical network associated with the terminal where the transaction was performed.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ACQ.LGNT

ACQUIRER OBJECT — The type of object that acquired the transaction from an outside entity. Valid values are as follows:

CSI = Customer Service Interface object (used for transactions acquired from a Customer Service Representative terminal)
IMTT = Internal Message Translation Interface object (used for transactions acquired from a procedural process such as the Billpay Server process)
VRUT = Voice Response Unit Interface object (used for transactions acquired from an RBSI-compliant device or host)

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.ACQ-OBJ-ID

TERMINAL ID — The terminal ID of the terminal where the transaction was performed.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.TERM-ID

ISSUER INFORMATION

The fields in this column contain information pertaining to the transaction authorizer.

INST ID CODE — A code identifying the institution that issued the account.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ISS.ID-CDE

FIID — The FIID of the financial institution that issued the account.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ISS.FIID

LGNT — The logical network associated with the institution that issued the account.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ISS.LGNT

AUTH OBJECT — The type of object that authorized the transaction. Valid values are as follows:

DENA = Denial Authorization object (part of the Combined Utility Authorization object)
IMTT = Internal Message Translation Interface object
PCA = Positive Customer Authorization method performed by the Authorization—Combined Positive Customer object
PCAA = Positive Customer with Accounts Authorization method performed by the Authorization—Combined Positive Customer object
PCBA = Positive Customer with Balances/History Authorization method performed by the Authorization—Combined Positive Customer object

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.AUTH-OBJ-ID

IMPACT 1 OBJECT — A code identifying the authorization method used to update the BASE24 database for the first account in a transaction when BASE24 is not the primary authorizer. BASE24 could be preauthorizing the transaction, standing in for the primary authorizer, or receiving a force post from an issuer. Valid values are as follows:

PCA = Positive Customer Authorization
PCAA = Positive Customer with Accounts Authorization
PCBA = Positive Customer with Balances/History Authorization

Field Length: System-protected
Data Name: TLF.BUS-OLF.IMPACT1-OBJ-ID

IMPACT 2 OBJECT — A code identifying the authorization method used to update the BASE24 database for the second account in the transaction when BASE24 is not the primary authorizer. BASE24 could be preauthorizing the transaction, standing in for the primary authorizer, or receiving a force post from an issuer. Valid values are as follows:

PCA = Positive Customer Authorization
PCAA = Positive Customer with Accounts Authorization
PCBA = Positive Customer with Balances/History Authorization

Field Length: System-protected
Data Name: TLF.BUS-OLF.IMPACT2-OBJ-ID

AUTH AGENT — A code identifying the authorizing agent institution. The authorizing agent is used in the response message to indicate that an agent stands in for the issuer. It is used when the institution that authorized the transaction is not the same institution identified in the PAN.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AUTH-AGENT.ID-CDE

AUTHORIZER — The symbolic name of the authorization destination that identifies the Internal Message Translation File (IMTF) record used to route the message.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.AUTH.NAM

STAN — The system trace audit number (STAN) assigned by the message initiator to uniquely identify the message.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.AUTH.STAN

DISCARD NON-FINANCIAL REVERSALS — A code that identifies whether reversals of nonfinancial inquiry transactions are discarded or processed. Valid values are as follows:

- Y = Yes, discard reversals of nonfinancial inquiry transactions. Do not log them or forward them to the issuer.
N = No, do not discard reversals of nonfinancial inquiry transactions. Log them and forward them to the issuer.

Note: Reversals for approved nonfinancial transactions with transaction code 90 (PIN change) are never discarded, regardless of the value in this field. For the BASE24-billpay product, this code also applies to all inquiry transactions as well as some reversals for approved nonfinancial BASE24-billpay transactions. For example, schedule payment and scheduled payment update transactions may also never be discarded—regardless of the value in this field—depending upon whether they were authorized by the BASE24-billpay product, a host, or a third-party processor. For detailed information on the processing performed for reversals of approved nonfinancial BASE24-billpay transactions, refer to the ***BASE24 Remote Banking Transaction Processing Manual***.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.ISS.DISCRD-NON-FNCL-RVSL

Issuer Advice and Routing Information

Detail screen 3 contains issuer advice and routing information. Detail screen 3 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(YYMMDD): YYMMDD

                                TRANSACTION DETAIL
                                *** ISSUER INFORMATION ***
                                ** ADVICE 1 REQUIRED **

OBJECT:
NAME:
FLAG:

                                ** ADVICE 2 REQUIRED **

OBJECT:
NAME:
FLAG:

                                *** ROUTING INFORMATION ***
AUTH INDICATOR:                      ROUTING CODE:
ROUTING FLOOR FLAG:                  ROUTE TYPE FLAG:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

ISSUER INFORMATION

The following fields provide additional information about the issuer.

ADVICE 1 REQUIRED

The following fields contain the name and type of the primary authorizer for the first account involved in the transaction, if the primary authorizer requires an advice because a BASE24 product performs stand-in authorization.

OBJECT — The type of object for the primary authorizer. The valid value is IMTT (Internal Message Translation Interface object).

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC1-REQ.OBJ-ID

NAME — The name of the primary authorizer.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC1-REQ.NAM

FLAG — A code identifying when advices are necessary. Valid values are as follows:

- A = Send advices for approved transactions only.
- B = Send advices for approved and denied transactions.
- D = Send advices for denied transactions only.
- N = Do not send advices.

A description of the code is displayed immediately to the right of the value in the FLAG field.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC1-REQ.FLG

ADVICE 2 REQUIRED

The following fields contain the name and type of the primary authorizer for the second account involved in the transaction, if the primary authorizer requires an advice because a BASE24 product performs stand-in authorization.

OBJECT — The type of object for the primary authorizer. The valid value is IMTT (Internal Message Translation Interface object).

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC2-REQ.OBJ-ID

NAME — The name of the primary authorizer.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC2-REQ.NAM

FLAG — A code identifying when advices are necessary. Valid values are as follows:

- A = Send advices for approved transactions only.
- B = Send advices for approved and denied transactions.
- D = Send advices for denied transactions only.
- N = Do not send advices.

A description of the code is displayed immediately to the right of the value in the FLAG field.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC2-REQ.FLG

ROUTING INFORMATION

The following fields identify the source of information used to route the transaction.

AUTH INDICATOR — A code indicating which authorizer authorized the transaction. Valid values are as follows:

- 1 = Alternate 1
- 2 = Alternate 2
- D = Default or denial authorization
- P = Primary

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.AUTH-IND.FLG

ROUTING CODE — The routing code used to route the transaction. This value is used to group transactions for routing and authorization purposes when multiple destinations or authorization methods must be defined for an institution in the Institution Routing Configuration File (IRCF).

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.RTE-CDE

ROUTING FLOOR FLAG — A code indicating the set of destinations used to route the transaction. Valid values are as follows:

- O = Over-the-floor destinations were used.
- U = Under-the-floor destinations were used.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.RTE-FLR.FLG

ROUTE TYPE FLAG — A code indicating the routing table used to route the transaction. The valid value is P (Institution Routing Configuration File).

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.RTE-TYP.FLG

Reason Codes, Original Data, and PIN Change Information

Detail screen 4 contains reason codes, original transaction data, and security information. Detail screen 4 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL DATE (YYMMDD):  YYMMDD
                                     TRANSACTION DETAIL

      FUNCTION CODE:                   *** ORIGINAL DATA INFO ***
      MESSAGE SUBSTATE:                MESSAGE TYPE:
      MESSAGE RSN CODE:                STAN:
      NEGATIVE RSN CODE:              LOCAL TXN DAT/TIM:
      POSTING DATE:                   ACQ INST ID CODE:
      CARD VERIFY STATUS:             ORIGINAL MESSAGE TYPE:

*** EXCEPTION REASON CODES ***          PRODUCT ID:
      CODE:                          PVD OLD:
POST FLAG:                          PVD NEW:
      OBJ NAME:                      PIN CHANGE REQUIRED:
      REC TYPE:                      DISCRIMINANT:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
      FILE DESTINATION:              NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

FUNCTION CODE — A code indicating the specific purpose of the message within its message class. Function codes are based on the 1993 ISO 8583 standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*.

Field Length: System-protected
Data Name: TLF.BUS-OLF.FNCT.CDE

MESSAGE SUBSTATE — A code used by interface objects to identify message processing results. Valid values are as follows:

- 0 = Normal
- 1 = Duplicate transaction
- 2 = Not sent to authorizer
- 3 = Timeout
- 4 = System error
- 5 = Format error
- 6 = Failed preauthorization
- 7 = Reversal not found
- 8 = Responder down
- 9 = Advice 1 not sent
- 10 = Advice 2 not sent

Field Length: System-protected

Data Name: TLF.BUS-MLF.BCD.MSG-SUBSTATE

MESSAGE RSN CODE — A code providing the receiver of a request, advice, or notification message with the reason for that message. For original authorizations and financial transactions, it identifies why the type of message was sent (that is, why an advice versus a request). If the transaction is a reversal or adjustment, this indicates the reason the reversal or adjustment was generated. Message reason codes are based on the 1993 ISO 8583 standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*.

Field Length: System-protected

Data Name: TLF.BUS-OLF.RSN-CDE-MSG

NEGATIVE RSN CODE — A code identifying the reason this customer could not perform this transaction. Valid values are as follows:

- 00 = Inactive
- 02 = Closed

Field Length: System-protected

Data Name: TLF.BUS-OLF.RSN-CDE-NEG

POSTING DATE — The date (YYMMDD) the transaction was processed by a BASE24 product.

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.CAPTR-DAT

CARD VERIFY STATUS — A code indicating the status of the card verification processing performed. Valid values are as follows:

- C = Card verification processing was performed and the card verification digits (CVD) were invalid. The error was noted and transaction processing continued.
- D = Card verification processing was performed and the CVD was invalid. The transaction was denied.
- J = Card verification processing was not performed. The track length was in error. The transaction was denied.
- K = Card verification processing was not performed. The track length was in error. The transaction was referred.
- L = Card verification processing was not performed. The track length was in error. Transaction processing continued.
- N, Ø, 0 = Card verification processing has not yet been attempted or a security device error occurred.
- O = Card verification processing was not performed because the CVD was not on the card. Not all cards have an encoded CVD value. The card expiration date must be equal to or greater than an expiration date defined for the card prefix to ensure that the CVD field has been encoded. If the card expiration date is equal to or greater than the card prefix date, the CVD checks are performed.
- R = Card verification was performed and the CVD was invalid. The transaction was referred.
- Y = Card verification processing was performed and the CVD was valid.

Field Length: System-protected
Data Name: TLF.BUS-OLF.CVV.STAT

EXCEPTION REASON CODES

If an exception condition exists that indicates the transaction should not have been approved, or that does not allow the transaction to be fully posted to the database, information in the following fields indicates the problem within a BASE24 product. Each of the following fields can occur five times. If more than five exception conditions exist, the first five that occur are displayed in these fields.

CODE — The response code that would have been returned as a result of the transaction posting attempt.

Field Length: System-protected
Data Name: TLF.BUS-OLF.RSN-CDE-EXCPT.CDE

POST FLAG — A code identifying the results of the transaction posting attempt. Valid values are as follows:

- N = The transaction was not posted to the BASE24 authorization database.
- P = The transaction was partially posted to the BASE24 authorization database.
- Y = The transaction was posted to the BASE24 authorization database or was not applicable (that is, the code is used for a condition that does not involve updating the database).

Field Length: System-protected
Data Name: TLF.BUS-OLF.RSN-CDE-EXCPT.POST-FLG

OBJ NAME — The name of the object that encountered the exception condition.

Field Length: System-protected
Data Name: TLF.BUS-OLF.RSN-CDE-EXCPT.OBJ-ID

REC TYPE — A code indicating the PBF record or Customer Table (CSTT) row being updated when the posting error occurred. Valid values are as follows:

- 1 = PBF record for account 1 (single account or *from* account)
- 2 = PBF record for account 2 (*to* account)
- B = PBF record for the backup account
- C = Customer Table (CSTT) row for the customer

Field Length: System-protected
Data Name: TLF.BUS-OLF.RSN-CDE-EXCPT.INFO.REC-TYP

ORIGINAL DATA INFO

The next four fields contain the original transaction information for a reversal transaction. Otherwise, they are blank.

The remaining fields in this column (beginning with the ORIGINAL MESSAGE TYPE field) contain information that is not limited to reversal transactions.

MESSAGE TYPE — The type of message that was reversed. Valid values are as follows:

- 1110 = Authorization request response from an integrated server process
- 1210 = Financial request response from an integrated server process

Field Length: System-protected
Data Name: TLF.BUS-OLF.ORIG-DATA.MTI

STAN — The system trace audit number (STAN) originally assigned by the message initiator to uniquely identify the message.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ORIG-DATA.STAN

LOCAL TXN DAT/TIM — The date (YYMMDD) and time (hh:mm:ss) the original transaction was processed by a BASE24 product.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ORIG-DATA.LOCAL-TXN-DAT-TIM

ACQ INST ID CODE — A code identifying the acquiring institution (for example, merchant bank) or its agent.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ORIG-DATA.ACQ-INST-ID-CDE

ORIGINAL MESSAGE TYPE — The type of message that was originally received by a BASE24 product. Valid values are as follows:

- 1100 = Authorization request to an integrated server process
- 1101 = Authorization request repeat to an integrated server process
- 1200 = Financial request to an integrated server process
- 1201 = Financial request repeat to an integrated server process

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.MTI-ORIG

PRODUCT ID — A code identifying the BASE24 product involved in the transaction. A value of 14 identifies the BASE24-telebanking and BASE24-billpay products.

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.PROD-ID

PVD OLD — The old PIN verification digits (PVD) for a PIN change transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.PVD.OLD

PVD NEW — The new PIN verification digits (PVD) for a PIN change transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.PVD.NEW

PIN CHANGE REQUIRED — A code indicating whether a PIN change transaction must be performed.

Field Length: System-protected
Data Name: TLF.BUS-OLF.PIN-CHNG-REQ.FLG

DISCRIMINANT — A value used by interface objects to check for duplicate transactions.

Field Length: System-protected
Data Name: TLF.BUS-MLF.ALT-KEY1.DISCIM

Performance Timer Information

Detail screen 5 contains performance timer information. Detail screen 5 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

BASE24-CORE LOG FILE PERUSAL

LLLL

YY/MM/DD hh:mm

02 OF 02

CUSTOMER ID:

FIID:

ACCT NUM:

LGNT: LLLL

DATE (YYMMDD): YYMMDD

TRANSACTION DETAIL

*** PERFORMANCE TIMERS ***

ENTRY TIME:

EXTERNAL ACQUIRER TIME:

EXTERNAL ISSUER TIME:

LOG TIME:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.

***** BASE24 *****

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F4-GOTO LISTING

F6-NXT REC

F7-PRV REC

F9-NXT PAGE

F11-PRV PAGE

F12-HELP

PERFORMANCE TIMERS

The following fields contain information that can be used to measure the time a transaction takes to pass through the system.

ENTRY TIME — The date (YY/MM/DD) and time (hh:mm:ss:tt) that the transaction entered a BASE24 product.

Field Length: System-protected

Data Name: TLF.BUS-MLF.BCD.TIM-ENTRY-TS

EXTERNAL ACQUIRER TIME — The amount of time, in microseconds, taken outside of a BASE24 product to gather information from the customer for an interactive transaction (for example, multiple account selection).

Field Length: System-protected
Data Name: TLF.BUS-OLF.TIM-EXTRN-ACQ

EXTERNAL ISSUER TIME — The amount of time, in microseconds, taken by an external issuer to authorize the transaction and return it to a BASE24 product.

Field Length: System-protected
Data Name: TLF.BUS-OLF.TIM-EXTRN-ISS

LOG TIME — The date (YY/MM/DD) and time (hh:mm:ss:tt) the transaction was logged to the ITLF.

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.TIM-LOG-TS

Point of Service Information

Detail screen 6 contains point of service information. Detail screen 6 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(YYMMDD): YYMMDD

                                TRANSACTION DETAIL

                                *** POINT OF SERVICE INFORMATION ***
                                CARD DATA INPUT CAPABILITY:
CARDHOLDER AUTHENTICATION CAPABILITY:
                                CARD CAPTURE CAPABILITY:
                                OPERATING ENVIRONMENT:
                                CARDHOLDER PRESENT:
                                CARD PRESENT:
                                CARD DATA INPUT MODE:
                                CARDHOLDER AUTHENTICATION METHOD:
                                CARDHOLDER AUTHENTICATION ENTITY:
                                CARD DATA OUTPUT CAPABILITY:
                                TERMINAL OUTPUT CAPABILITY:
                                PIN CAPTURE CAPABILITY:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
                                FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

POINT OF SERVICE INFORMATION

The following fields contain a series of codes intended to identify terminal capability, terminal environment, and presentation of security data. These fields are used to indicate specific conditions that are present at the time a transaction occurs. These codes are based on the 1993 ISO 8583 standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*.

Note: The BASE24-telebanking and BASE24-billpay products currently use the OPERATING ENVIRONMENT and PIN CAPTURE CAPABILITY fields in processing and pass the value in the CARD DATA INPUT MODE field to the host. The remaining fields are for information only.

CARD DATA INPUT CAPABILITY — A code indicating the primary means of getting the information on the card into the terminal. Valid values are as follows:

- 0 = Unknown
- 1 = Manual, no terminal
- 2 = Magnetic stripe reader
- 3 = Bar code reader
- 4 = Optical character reader (OCR)
- 5 = Integrated circuit card (ICC)
- 6 = Key entered
- 7 = Reserved for ISO use
- 8 = Reserved for national use
- 9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRD-DATA-INPUT-CAP

CARDHOLDER AUTHENTICATION CAPABILITY — A code indicating the primary means of verifying the cardholder at this terminal. Valid values are as follows:

- 0 = No electronic authentication
- 1 = Personal identification number (PIN)
- 2 = Electronic signature analysis
- 3 = Biometrics
- 4 = Biographic
- 5 = Electronic authentication inoperative
- 6 = Other, including no order of priorities
- 7 = Reserved for ISO use
- 8 = Reserved for national use
- 9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-CAP

CARD CAPTURE CAPABILITY — A code indicating whether the terminal has the ability to capture a card. Valid values are as follows:

- 0 = Card capture capability does not exist
- 1 = Card capture capability does exist
- 2–4 = Reserved for ISO use
- 5–7 = Reserved for national use
- 8–9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRD-CAPTR-CAP

OPERATING ENVIRONMENT — A code indicating whether the terminal is attended by the transaction acceptor and where the terminal is located. The BASE24-telebanking and BASE24-billpay products use this code to indicate whether the transaction is initiated through a remote banking endpoint device or a customer service representative (CSR) terminal. Valid values are as follows:

- 0 = No terminal used.
- 1 = Attended terminal located on the premises of the transaction acceptor. For the BASE24-telebanking and BASE24-billpay products, this code identifies a customer service representative (CSR) terminal.
- 2 = Unattended terminal located on the premises of the transaction acceptor.
- 3 = Attended terminal located off the premises of the transaction acceptor.
- 4 = Unattended terminal located off the premises of the transaction acceptor.
- 5 = Unattended terminal located on the premises of the accountholder. For the BASE24-telebanking and BASE24-billpay products, this code identifies a remote banking endpoint device (for example, an interactive voice response system).
- 6–7 = Reserved for ISO use.
- 8 = Reserved for national use.
- 9 = Reserved for private use.
- A–I = Reserved for ISO use.
- J–R = Reserved for national use.
- S–Z = Reserved for private use.

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.OPER-ENVIRON

CARDHOLDER PRESENT — A code indicating whether the cardholder is present at the point of service and, if not, why not. Valid values are as follows:

- 0 = Cardholder present
- 1 = Cardholder not present, unspecified reason
- 2 = Cardholder not present, mail order
- 3 = Cardholder not present, telephone order
- 4 = Cardholder not present, standing authorization
- 5–6 = Reserved for ISO use
- 7–8 = Reserved for national use
- 9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRDHLDR-PRSN

CARD PRESENT — A code indicating whether the card is present at the point of service. Valid values are as follows:

- 0 = Card not present
- 1 = Card present
- 2–4 = Reserved for ISO use
- 5–7 = Reserved for national use
- 8–9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRD-PRSN

CARD DATA INPUT MODE — A code indicating the method used to input the information from the card to the terminal. The BASE24 ISO Host Interface process passes this value to the host. Valid values are as follows:

- 0 = Unspecified
- 1 = Manual, no terminal
- 2 = Magnetic stripe reader
- 3 = Bar code reader
- 4 = Optical character reader (OCR)
- 5 = Integrated circuit card (ICC)
- 6 = Key entered

- 7 = Reserved for ISO use
- 8 = Reserved for national use
- 9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRD-DATA-INPUT-MDE

CARDHOLDER AUTHENTICATION METHOD — A code indicating the method used for verifying the identity of the cardholder. Valid values are as follows:

- 0 = Not authenticated
- 1 = Personal identification number (PIN)
- 2 = Electronic signature analysis
- 3 = Biometrics
- 4 = Biographic
- 5 = Manual signature verification
- 6 = Other manual verification (for example, driver's license)
- 7 = Reserved for ISO use
- 8 = Reserved for national use
- 9 = Reserved for private use
- A–I = Reserved for ISO use
- J–R = Reserved for national use
- S–Z = Reserved for private use

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-METHOD

CARDHOLDER AUTHENTICATION ENTITY — A code indicating the entity verifying the identity of the cardholder. Valid values are as follows:

- 0 = Not authenticated
- 1 = Integrated circuit card (ICC)
- 2 = Card accepting device (CAD)
- 3 = Authorizing agent
- 4 = Merchant
- 5 = Other
- 6 = Reserved for ISO use
- 7 = Reserved for national use
- 8–9 = Reserved for private use

A–I = Reserved for ISO use
J–R = Reserved for national use
S–Z = Reserved for private use

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-ENTITY

CARD DATA OUTPUT CAPABILITY — A code indicating the ability of the terminal to update the card. Valid values are as follows:

0 = Unknown
1 = None
2 = Magnetic stripe write
3 = Integrated circuit card (ICC)
4–5 = Reserved for ISO use
6–7 = Reserved for national use
8–9 = Reserved for private use
A–I = Reserved for ISO use
J–R = Reserved for national use
S–Z = Reserved for private use

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.PT-SVC.CRD-DATA-OUTPUT-CAP

TERMINAL OUTPUT CAPABILITY — A code indicating the ability of the terminal to print or display messages. Valid values are as follows:

0 = Unknown
1 = None
2 = Printing
3 = Display
4 = Printing and display
5–6 = Reserved for ISO use
7–8 = Reserved for national use
9 = Reserved for private use
A–I = Reserved for ISO use
J–R = Reserved for national use
S–Z = Reserved for private use

Field Length: System-protected
Data Name: TLF.BUS-MLF.ASCII.PT-SVC.TERM-OUTPUT-CAP

PIN CAPTURE CAPABILITY — A code indicating the length of personal identification number (PIN) that the acquirer endpoint is capable of capturing and whether PIN verification is necessary. The BASE24-telebanking and BASE24-billpay products use the values C and S in this field during PIN verification. Valid values are as follows:

- 0 = No PIN capture capability exists.
- 1 = PIN capture capability for device is unknown.
- 2–3 = Reserved for ISO use.
- 4 = Terminal can capture a four-character PIN.
- 5 = Terminal can capture a five-character PIN.
- 6 = Terminal can capture a six-character PIN.
- 7 = Terminal can capture a seven-character PIN.
- 8 = Terminal can capture an eight-character PIN.
- 9 = Terminal can capture a nine-character PIN.
- A = Terminal can capture a 10-character PIN.
- B = Terminal can capture an 11-character PIN.
- C = Terminal can capture a 12-character PIN. For the BASE24-telebanking and BASE24-billpay products, this value means PIN verification has not been performed.
- D–I = Reserved for ISO use.
- J–R = Reserved for national use.
- S = Reserved for private use. For the BASE24-telebanking and BASE24-billpay products, this value means PIN verification has already been performed.
- T–Z = Reserved for private use.

Field Length: System-protected

Data Name: TLF.BUS-MLF.ASCII.PT-SVC.PIN-CAPTR-CAP

Backup Account Information

Detail screen 7 contains backup account information. Detail screen 7 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section. If no backup account exists for the transaction, none of the BACKUP ACCOUNT INFORMATION fields will be displayed.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                     TRANSACTION DETAIL

          *** BACKUP ACCOUNT INFORMATION ***
          ACCT NUM:
          ACCT TYPE:
          TRANSFER AMT:
          CHB TRANSFER AMT:
          CRNCY CDE:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

BACKUP ACCOUNT INFORMATION

If a backup account was used because sufficient funds were not available in Account 1, the following fields contain information concerning the backup account portion of the transaction.

ACCT NUM — The account number assigned to the backup account.

Field Length: System-protected
Data Name: TLF.BUS-OLF.BACKUP.ACCT-NUM

ACCT TYPE — A code identifying the type of backup account.

Field Length: System-protected
Data Name: TLF.BUS-OLF.BACKUP.ACCT.TYP

TRANSFER AMT — The amount of funds transferred from the backup account to Account 1, expressed in the currency of the backup account.

Field Length: System-protected
Data Name: TLF.BUS-OLF.BACKUP.AMT-XFER

CHB TRANSFER AMT — The amount of funds transferred from the backup account to Account 1, expressed in the currency of Account 1.

Field Length: System-protected
Data Name: TLF.BUS-OLF.BACKUP.AMT-XFER-CHB

CRNCY CDE — The currency code of the backup account. Currency codes are based on the 1990 ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: System-protected
Data Name: TLF.BUS-OLF.BACKUP.CRNCY-CDE

Transaction Amounts and Currency Conversion Fee Information

Detail screen 8 contains transaction amounts and currency conversion fee information. Detail screen 8 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                TRANSACTION DETAIL

    *** TRANSACTION AMOUNTS ***          *** ORIGINAL TRANSACTION AMOUNTS ***
      ACQ AMT:                          ACQ AMT:
ACQ CRNCY CDE:                         CHB AMT:
      ISS AMT:                          ISS AMT:
ISS CRNCY CDE:                         LGNT AMT:
      LGNT AMT:                         TXN AMT:
LGNT CRNCY CDE:
      CHB AMT:
CHB CRNCY CDE:
      CHB 2 AMT:
CHB 2 CRNCY CDE:                      CC FEE IMPACT FLG:
                                         ACQ FEE AMT:
                                         ISS FEE AMT:

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
      FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

TRANSACTION AMOUNTS

On a request, the following fields contain the funds requested by the customer, expressed in various currencies. On a response, these fields contain the funds approved by the issuer (that is, unchanged from request if approved, zero if denied). On a reversal, these fields contain the amount reversed. Currency codes are based on the 1990 ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

ACQ AMT — The amount of funds requested by the customer, expressed in the currency of the financial institution that acquired the transaction. The acquiring institution is the terminal owner.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.ACQ.AMT

ACQ CRNCY CDE — A code identifying the currency of the financial institution that acquired the transaction. The acquiring institution is the terminal owner.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.ACQ.CRNCY-CDE

ISS AMT — The amount of funds requested by the customer, expressed in the currency of the financial institution that authorized the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.ISS.AMT

ISS CRNCY CDE — A code identifying the currency of the financial institution that authorized the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.ISS.CRNCY-CDE

LGNT AMT — The amount of funds requested by the customer, expressed in the currency of the logical network that acquired the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.LGNT.AMT

LGNT CRNCY CDE — A code identifying the currency of the logical network that acquired the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN.LGNT.CRNCY-CDE

CHB AMT — The amount of funds requested by the customer, expressed in the currency of the customer's account. The information in the CHB AMT and CHB CRNCY CDE fields applies to the account involved in transactions other than transfers. This information applies to the *from* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-CHB.AMT

CHB CRNCY CDE — A code identifying the currency of the customer's account. The information in the CHB AMT and CHB CRNCY CDE fields applies to the account involved in transactions other than transfers. This information applies to the *from* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-CHB.CRNCY-CDE

CHB 2 AMT — The amount of funds requested by the customer, expressed in the currency of the customer's account. The information in the CHB2 AMT and CHB2 CRNCY CDE fields applies to the *to* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-CHB2.AMT

CHB 2 CRNCY CDE — A code identifying the currency of the customer's account. The information in the CHB2 AMT and CHB2 CRNCY CDE fields applies to the *to* account involved in a transfer transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-CHB2.CRNCY-CDE

ORIGINAL TRANSACTION AMOUNTS

The following five fields contain the original amount of the transaction, expressed in various currencies. This information may be present in authorization, financial, or reversal transactions.

ACQ AMT — The original amount of the transaction, expressed in the currency of the financial institution that acquired the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-ORIG.ACQ

CHB AMT — The original amount of the transaction, expressed in the currency of the customer's account.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-ORIG.CHB

ISS AMT — The original amount of the transaction, expressed in the currency of the financial institution that authorized the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-ORIG.ISS

LGNT AMT — The original amount of the transaction, expressed in the currency of the logical network that acquired the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-ORIG.LGNT

TXN AMT — The original amount of the transaction, expressed in the currency of the terminal where the transaction was initiated.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-TXN-ORIG-TXN

CC FEE IMPACT FLG — A code indicating which fees (acquirer, issuer, or both) impact the account balance.

Field Length: System-protected
Data Name: TLF.BUS-OLF.CC-FEE-IMPACT.FLG

ACQ FEE AMT — The fee assessed by the acquirer for currency conversion, expressed in the local currency of the acquirer or of the source location of the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-FEE-ACQ

ISS FEE AMT — The fee assessed by the issuer for currency conversion, expressed in the local currency of the acquirer or of the source location of the transaction.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AMT-FEE-ISS

Refresh Information

Detail screen 9 contains refresh impact information and refresh file indicators. Detail screen 9 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                TRANSACTION DETAIL

*** REFRESH IMPACT INFO ***          *** REFRESH FILE INDICATORS ***
AMT TYPE  ACCT IND          AMT          FILE TYPE  FILE IN

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

REFRESH IMPACT INFO

The following fields contain information the Enscribe Refresh process uses to impact the database for a financial transaction. These fields can occur up to ten times.

For example, the following table contains the values that would appear in these fields for a transfer of \$50.00 from a savings account to a credit account.

AMT TYPE	ACCT IND	AMT
A	1	-0000000000000005000

AMT TYPE	ACCT IND	AMT
L	1	-0000000000000005000
A	2	0000000000000005000
H	2	0000000000000005000

In this example, the available balance (amount type A) and ledger balance (amount type L) of the *from* account (account indicator 1) are reduced by \$50.00. The available credit (amount type A) and credit balance (amount type H) of the *to* account (account indicator 2) are increased by \$50.00.

AMT TYPE — A code identifying which balance the Enscribe Refresh process is to impact. Valid values are as follows:

A = Available balance/available credit
H = Amount on hold/credit balance
I = Cash in
L = Ledger balance
O = Cash out

Field Length: System-protected
Data Name: TLF.BUS-OLF.REFR-IMPACT.INFO.AMT-TYP

ACCT IND — A code identifying which account the Enscribe Refresh process is to impact. Valid values are as follows:

1 = Account 1
2 = Account 2
B = Backup account

Field Length: System-protected
Data Name: TLF.BUS-OLF.REFR-IMPACT.INFO.ACCT-IND

AMT — The amount the Enscribe Refresh process uses to impact the database.

Field Length: System-protected
Data Name: TLF.BUS-OLF.REFR-IMPACT.INFO.AMT

REFRESH FILE INDICATORS

The following fields indicate the BASE24-telebanking and BASE24-billpay files that can be refreshed and what the current refresh indicator is for each file. The following fields can occur up to ten times.

FILE TYPE — A code indicating to the Enscribe Refresh process the type of file associated with the value in the FILE IND field. Valid values are as follows:

- 1 = Positive Balance File 1 (DDA)
- 2 = Positive Balance File 2 (Savings)
- 3 = Positive Balance File 3 (Credit)

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.REFR.FILE.TYP

FILE IND — A code indicating to the Enscribe Refresh process the version of the file when this transaction occurred. For the Positive Balance File, this field contains the value from the REFRESH GROUP field of the IDF, since the PBF does not have a version.

Field Length: System-protected
Data Name: TLF.BUS-MLF.BCD.REFR.FILE.IND

Miscellaneous Additional Data

Detail screen 10 contains miscellaneous additional data. Detail screen 10 is shown below, followed by a description of its field.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(Yymmdd): Yymmdd
                                TRANSACTION DETAIL
                                *** ADDITIONAL DATA ***
```

```
MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F4-GOTO LISTING   F6-NXT REC   F7-PRV REC   F9-NXT PAGE   F11-PRV PAGE   F12-HELP
```

ADDITIONAL DATA — A variable-length area containing additional data that needs to accompany the transaction, but is not stored in a specific field. This field contains the check number on transactions involving a check. It contains the key data required to reposition on transactions such as *last count of inquiry* transactions. It may also be used for user-defined or ACI use only transactions. Up to four lines of data may be displayed.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADNL-DATA.FDATA

Acquirer-Dependent Data

Detail screen 11 contains acquirer-dependent data. Detail screen 11 is shown below, followed by a description of its field. This screen may contain as many virtual pages as needed to display all the acquirer dependent data. Use the **F9** and **F11** keys to move forward and backward through these pages, respectively.

BASE24-CORE LOG FILE PERUSAL

LLLL

YY/MM/DD hh:mm

02 OF 02

CUSTOMER ID:

FIID:

ACCT NUM:

LGNT: LLLL

DATE(YMMDD): YMMDD

TRANSACTION DETAIL

*** ACQUIRER DEPENDENT DATA ***

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.

***** BASE24 *****

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F4-GOTO LISTING

F6-NXT REC

F7-PRV REC

F9-NXT PAGE

F11-PRV PAGE

F12-HELP

ACQUIRER DEPENDENT DATA — A variable-length area containing fields specific to the acquirer object of this transaction. The structure and content of this field is defined by the acquirer.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ACQ-DPNT.FDATA

Authorization-Dependent Data

Detail screen 12 contains authorization-dependent data. Detail screen 12 is shown below, followed by a description of its field.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(YMMDD) : YMMDD
                                TRANSACTION DETAIL
                                *** AUTH DEPENDENT DATA ***
```

```
MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
                                FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING   F6-NXT REC   F7-PRV REC   F9-NXT PAGE   F11-PRV PAGE   F12-HELP
```

AUTH DEPENDENT DATA — A variable-length area containing fields specific to the authorizer object of this transaction. The structure and content of this field is defined by the authorizer.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AUTH-DPNT.FDATA

Advice 1-Dependent Data

Detail screen 13 contains advice 1-dependent data. Detail screen 13 is shown below, followed by a description of its field.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(YMMDD): YMMDD
                                TRANSACTION DETAIL
                                *** ADVICE 1 DEPENDENT DATA ***

MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
                                FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

ADVICE 1 DEPENDENT DATA — A variable-length area containing fields specific to the object that received an advice for this transaction. This field is used if the primary authorizer of the first account involved in this transaction requires an advice because a BASE24 product performs stand-in authorization. The structure and content of this field is defined by the object receiving the advice.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADVC1-DPNT.FDATA

Advice 2-Dependent Data

Detail screen 14 contains advice 2-dependent data. Detail screen 14 is shown below, followed by a description of its field.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(YYMMDD): YYMMDD
                                TRANSACTION DETAIL
                                *** ADVICE 2 DEPENDENT DATA ***
```

```
MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
FILE DESTINATION:                     NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

ADVICE 2 DEPENDENT DATA — A variable-length area containing fields specific to the object that received an advice for this transaction. This field is used if the primary authorizer of the second account involved in this transaction requires an advice because a BASE24 product performs stand-in authorization. The structure and content of this field is defined by the object receiving the advice.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ADV2-DPNT.FDATA

BASE24-billpay Transaction Data

Detail screen 15 contains data specific to BASE24-billpay scheduled payment, scheduled transfer, and nonfinancial transactions that are automatically logged to the ITLF. BASE24-billpay nonfinancial transactions are automatically logged to the ITLF only when they originate from a remote banking endpoint device or host. This screen also contains the customer reference number and customer vendor information for BASE24-billpay transactions that can be optionally logged to the ITLF. The Bank Transaction Advice Table (BKAV) determines which BASE24-billpay transactions are optionally logged to the ITLF. For more information on the BKAV, refer to the ***BASE24-billpay Tables Maintenance Manual***. Detail screen 15 is shown below, followed by descriptions of its fields.

Some fields shown on the sample screen below may not appear for every transaction that is displayed. For more information on why fields are not displayed, see the topic “Detail Screen Fields” presented earlier in this section.

```

BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL   DATE(Yymmdd): Yymmdd
                                     TRANSACTION DETAIL

      TRANSACTION SOURCE:
CUSTOMER REFERENCE NUMBER:

*** VENDOR INFORMATION ***
VENDOR NAME:
CUSTOMER VENDOR ACCOUNT:
PAYEE:

*** RECURRING TRANSACTION DATA ***      *** SCHEDULED TRANSACTION DATA ***
PERIOD TYPE:                             PAYMENT DATE:
NUMBER OF PERIODS:                       ACTION DATE:
NUMBER OF PAYMENTS TO SKIP:

NO MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F4-GOTO LISTING      F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP

```

TRANSACTION SOURCE — A code indicating the type of client that originated this scheduled payment, scheduled transfer, or inquiry transaction. This code is included in all BASE24-billpay scheduled payment and scheduled transfer transaction requests. Valid values include any two-character user-defined codes as well as the following codes reserved for BASE24 products:

AD = Audio device (for example, an interactive voice response system)
BL = Billpay Server process (considered the source for all scheduled payment and transfer transactions that have been previously warehoused and are initiated by the Scheduled Transaction Initiator process)
IB = Inbound customer service representative (CSR)
PC = Personal computer
SP = Screen phone

A description of the code is displayed immediately to the right of the value in the TRANSACTION SOURCE field.

Field Length: System-protected
Data Name: TLF.BUS-OLF.SRC-CDE

CUSTOMER REFERENCE NUMBER — A unique reference number assigned by the Billpay Server process for every transaction processed.

Field Length: System-protected
Data Name: TLF.BUS-OLF.CUST-REF-NUM

VENDOR INFORMATION

The following fields identify the vendor in a payment transaction or a customer vendor transaction.

VENDOR NAME — The name of the vendor paid in a schedule payment – immediate, schedule payment – future, or schedule payment – recurring transaction. The vendor name is defined in the Vendor Table (VNDR).

Field Length: System-protected
Data Name: TLF.BUS-OLF.PAYEE-DESCR.VNDR-NAM

CUSTOMER VENDOR ACCOUNT — The customer account number with the vendor to be credited for this scheduled payment transaction.

Field Length: System-protected

Data Name: TLF.BUS-OLF.PAYEE-DESCR.CUST-ACCT-NUM-VNDR

PAYEE — The customer vendor number from the Customer Vendor Table (CVND) that uniquely identifies each vendor associated with a customer ID. The customer vendor number is a 1- to 5-digit code generated by the system.

This field conforms to the Payee field defined in the 1993 ISO 8583 standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*.

For more information on the customer vendor number, refer to the *BASE24-billpay Tables Maintenance Manual*.

Field Length: System-protected

Data Name: TLF.BUS-OLF.PAYEE

RECURRING TRANSACTION DATA

The following fields provide information for schedule payment – recurring and schedule transfer – recurring transactions.

PERIOD TYPE — A code indicating the frequency of a schedule payment – recurring transaction or schedule transfer – recurring transaction. This field is optionally logged for scheduled payment update and scheduled transfer update transactions. Valid codes are as follows:

WK	= Weekly
2W	= Every two weeks
MN	= Monthly
Q	= Quarterly (every three months)
S	= Semi-annually (every six months)
A	= Annually (once a year)
All others	= *****

Field Length: System-protected

Data Name: TLF.BUS-OLF.RECUR-TXN-DATA.PRD-TYP

NUMBER OF PERIODS — The number of periods for a schedule payment – recurring transaction or a schedule transfer – recurring transaction. This field is optionally logged for scheduled payment update and scheduled transfer update transactions.

Field Length: System-protected
Data Name: TLF.BUS-OLF.RECUR-TXN-DATA.NUM-PRD

SCHEDULED TRANSACTION DATA

The following fields are logged for all scheduled payment and scheduled transfer transactions.

PAYMENT DATE — The date (YYYYMMDD) on which the customer has scheduled this payment or transfer transaction to be performed. For recurring payment and transfer transactions, this is the date on which the first payment or transfer is scheduled to be performed.

Field Length: System-protected
Data Name: TLF.BUS-OLF.PMNT-DAT

ACTION DATE — The date (YYMMDD) on which a scheduled payment or transfer transaction was actually performed. For scheduled recurring payment and transfer transactions, this is the date on which the first scheduled payment or transfer transaction was actually performed.

In most cases, the PAYMENT DATE and the ACTION DATE fields will contain the same date. The dates could be different, however, if the payment or transfer is scheduled to be performed on a weekend or financial institution holiday, but is not actually performed until the next business day.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ACT-DAT

NUMBER OF PAYMENTS TO SKIP — The number of periods to skip for a scheduled recurring payment or transfer transaction. This field is logged for scheduled payment update and scheduled transfer update transactions. Valid values are 0 or 1.

Field Length: System-protected
Data Name: TLF.BUS-OLF.RECUR-TXN-DATA.SKIP-NXT-PMNT-IND

External Acquirer Dependent Data

Detail screen 16 contains external acquirer dependent data. Detail screen 16 is shown below, followed by a description of its field.

BASE24-CORE LOG FILE PERUSAL

LLLL

YY/MM/DD hh:mm

02 OF 02

CUSTOMER ID:

FIID:

ACCT NUM:

LGNT: LLLL

DATE(YMMDD): YMMDD

TRANSACTION DETAIL

*** EXTERNAL ACQUIRER DEPENDENT DATA ***

NO MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.

***** BASE24 *****

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F4-GOTO LISTING

F6-NXT REC

F7-PRV REC

F9-NXT PAGE

F11-PRV PAGE

F12-HELP

EXTERNAL ACQUIRER DEPENDENT DATA — A variable-length area containing fields specific to an external process (that is, external to the Integrated Authorization Server process) acquiring this transaction such as the ISO Host Interface process or the Scheduled Transaction Initiator process. The structure and content of this field is defined by the external acquirer process.

Field Length: System-protected
Data Name: TLF.BUS-OLF.ACQ-DPNT-EXTRN.FDATA

External Authorizer Dependent Data

Detail screen 17 contains external authorizer dependent data. Detail screen 17 is shown below, followed by a description of its field.

```
BASE24-CORE LOG FILE PERUSAL          LLLL          YY/MM/DD hh:mm    02 OF 02
CUSTOMER ID:                          FIID:
ACCT NUM:                             LGNT: LLLL  DATE(Yymmdd): Yymmdd
                                TRANSACTION DETAIL
                                *** EXTERNAL AUTH DEPENDENT DATA ***
```

```
NO MORE DETAIL INFORMATION IS AVAILABLE FOR THIS TRANSACTION.
***** BASE24 *****
                                FILE DESTINATION:          NEW LOGICAL NETWORK ID:
F4-GOTO LISTING  F6-NXT REC  F7-PRV REC  F9-NXT PAGE  F11-PRV PAGE  F12-HELP
```

EXTERNAL AUTH DEPENDENT DATA — A variable-length area containing fields specific to an external process (that is, external to the Integrated Authorization Server process) acquiring this transaction such as the Billpay Server process. The structure and content of this field is defined by the external authorizer process.

Field Length: System-protected
Data Name: TLF.BUS-OLF.AUTH-DPNT-EXTRN.FDATA

Section 11

Log Configuration File (LCF)

The Log Configuration File (LCF) controls the logging destination for each ITS object that logs information to the ITS Transaction Log File (ITLF). The LCF contains one record for each group of ITS objects that logs information to the ITLF.

Log groups are defined in the LOG ID field on Internal Message Translation File (IMTF) screen 1 and the LOG ID field on VRU Configuration Data (VCD) screen 18. All log groups defined on the IMTF and VCD screens must be included in an LCF record.

The LCF has limited use at the present time because all ITS objects must use a common logging destination. As a result, the LCF must contain only one record that applies to all log groups.

The OBJECT NAME and END RANGE fields make up the primary key to the LCF.

Screen 1 Function Keys

The use of one function key on LCF screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of this function key is explained below.

The first column shows the BASE24 key. The second column describes the functions that can be accomplished with this key on LCF screen 1.

Key	Description
Shift-F2	Display Summary — Retrieves the first summary page of LCF records for the object specified on LCF screen 1 and displays the information on LCF screen 2. Note: The END RANGE field must contain a zero when this function is performed.

Screen 1

LCF screen 1 defines the logging destination for each ITS object that logs information to the ITS Transaction Log File (ITLF). Currently, all ITS objects must use a common logging destination. Screen 1 of the LCF is shown below, followed by descriptions of its fields.

BASE24-CORE
LOG CONFIGURATION FILE
LLLL
YY/MM/DD
hh:mm
01 OF 02

OBJECT NAME:

START RANGE:0

END RANGE:0

ASSIGN:

COMMENT:

RECORD LAST CHANGED:

BY USER:

*****BASE24*****

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F12-HELP

OBJECT NAME — The name of the object to which this LCF record applies or all asterisks to represent all objects. The value in this field must match a value in the OBJECT NAME field on Object File (OBJ) screen 1 or contain all asterisks. The OBJ is accessed from the Kernel Product Menu. For more information on the OBJ, refer to the *BASE24 ITS Kernel Files Maintenance Manual*.

A description of the object is displayed immediately to the right of the OBJECT NAME field.

Note: The LCF can contain only one record at the present time. Asterisks (****) must be used because all objects currently use the same logging destination.

Field Length:

1–4 alphanumeric characters

Required Field:

Yes

Default Value:

No default value

Data Name:

LCF.PRIKEY.OBJ-NAM

START RANGE — An integer that identifies the first log group that uses the ITS Transaction Log File (ITLF) associated with this LCF record. The value in this field is always zero since the LCF can contain only one record at the present time.

Field Length: System-protected
Data Name: Not applicable

END RANGE — An integer that identifies the last log group that uses the ITLF associated with this LCF record. Valid values are as follows:

0 = Display LCF screen 2
1–999999 = Last log group that uses the ITLF associated with this LCF record

The value in this field must be set to zero before the **Shift-F2** keys are pressed to display LCF screen 2.

Note: When adding or updating the LCF record, the value in this field must be set to 999999 because all objects currently use a single logging destination.

Field Length: 1–6 numeric characters
Required Field: Yes
Default Value: 0
Data Name: LCF.PRIKEY.END-RANGE

ASSIGN — The Logical Network Configuration File (LCONF) assign name used to locate the ITLF for the object and log groups specified in this LCF record. The assign name must begin with TLF-.

Field Length: 1–32 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: LCF.TLF-ASGN

COMMENT — A description of how this LCF entry is used.

Field Length: 1–50 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: LCF.COMMENT

Screen 2 Function Keys

The use of three function keys on LCF screen 2 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on LCF screen 2.

Key	Description
F4	Select Record — Selects a specific LCF record and displays the information on LCF screen 1. Place the cursor in the SEL column of the desired LCF record and press the F4 key.
F9	Next Page — Retrieves the next summary page of LCF records for the specified object.
F11	Previous Page — Retrieves the previous summary page of LCF records for the specified object.

Screen 2

LCF screen 2 displays all log groups defined for a specified object. Screen 2 of the LCF is shown below, followed by descriptions of its fields.

```

BASE24-CORE LOG CONFIGURATION FILE LLLL YY/MM/DD hh:mm 02 OF 02

      OBJECT NAME:

      --- RANGE ---
SEL  START  END      ASSIGN

<NO MORE RECORDS EXIST>
***** BASE24 *****
      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
F4-SELECT RECORD  F9-NEXT PAGE  F11-PREVIOUS PAGE  F12-HELP  F16-EXIT

```

SEL — Selects an LCF record to be displayed on LCF screen 1. Place the cursor in this field and press the **F4** key to select the record range displayed on the same line of the screen. The selected record is then displayed on screen 1.

Field Length: Cursor placement only

Data Name: Not applicable

RANGE

The START and END fields identify the log groups that use a particular ITS Transaction Log File (ITLF).

START — An integer that identifies the first log group using the ITLF associated with this LCF record. The first LCF record for an object contains a zero in this field.

Field Length: System-protected
Data Name: Not applicable

END — An integer that identifies the last log group using the ITLF associated with this LCF record.

Field Length: System-protected
Data Name: LCF.PRIKEY.END-RANGE

ASSIGN — The Logical Network Configuration File (LCONF) assign name used to locate the ITLF template for the object and log groups specified in this LCF record.

Field Length: System-protected
Data Name: LCF.TLF-ASGN

ACI Worldwide Inc.

Section 12

Personal Information Table (PIT)

The Personal Information Table (PIT) screens provide access to the Personal Information Table (PIT) and, optionally, to the Customer/Personal ID Relation Table (CPIT). The PIT and CPIT are both SQL tables.

The PIT contains one row for each person (customer) associated with a row in the Customer Table (CSTT). Each PIT row contains personal information used to uniquely identify the person such as name, address, phone number, government ID, and date of birth. Rows in the PIT are identified through a personal ID. The personal ID is any string of 1–19 alphanumeric characters prescribed by the customer's financial institution or service provider or chosen by the customer. The personal ID used for any particular row must be unique within the entire PIT.

Rows in the PIT are associated with CSTT rows through the CPIT. The CPIT links CSTT rows to PIT rows by associating customer IDs with personal IDs. Customer Table (CSTT) screen 3 allows you to associate a single customer ID with multiple personal IDs. PIT screen 2 allows you to associate a single personal ID with multiple customer IDs. The PAN field on PIT screen 2 maps directly to the CUSTOMER ID field in the CSTT. A customer ID must be defined to the CSTT and a personal ID must be defined to the PIT before they can be related in the CPIT.

Although the CPIT must always be physically present, use of the CPIT is optional for all BASE24 product options. The CPIT-PRESENT param in the LCONF must be set to the value Y to be able to use PIT screen 2.

Information in the PIT can be used by customer service representatives when verifying the identity of a calling customer. The PIT is also used by the BASE24-billpay product during vendor remittance processing to obtain customer information needed to produce remittance files. Data from the PIT is also displayed on various BASE24-billpay reports.

Rows in the PIT can be maintained using this table maintenance screen, the Customer Information screen and the Customer Signup screen from a CSR terminal, or the customer update and customer add transactions from an RBSI-

compliant device. PIT information on the Customer Information screen is updated using the customer update transaction. PIT information on the Customer Signup screen is updated using the customer add or the customer update transaction. For more information on CSR screens and transactions, refer to the ***BASE24 Remote Banking Customer Service Support Manual***.

The primary key to rows in the PIT is the PERSONAL ID field on PIT screen 1. Rows in the PIT are also indexed by the customer's full name (FAMILY, GIVEN, M/I fields) to provide alternate key access.

The PIT is an optional table when only BASE24-telebanking is installed. The PIT is always required when BASE24-billpay is installed.

Default Financial Institution Rows

After the PIT and CPIT are installed, BASE24-billpay users must set up a default PIT and CPIT row for each financial institution in the logical network that does not preload their customer database from an existing database or tape. These PIT and CPIT rows are identified by the value in the DEFAULT CUST ID field on the Bank Table (BANK) screen. These rows are used to display the initial default data for customer service representatives (CSRs) when adding a new customer for the BASE24-billpay service from a CSR terminal screen or an RBSI-compliant device. The BANK screen is accessed using a function key from Institution Definition File (IDF) screens 40 through 42.

Note: Since the CPIT is an optional table, default financial institution rows are only required in this table if it is installed.

For more information on the BANK, refer to the *BASE24 Base Files Maintenance Manual*.

Screen 1 Function Keys

The use of eight function keys on PIT screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on PIT screen 1.

Key	Description
F2	Read Record — Reads the first row from the Personal Information Table (PIT) and the first 30 rows from the Customer/Personal ID Relation Table (CPIT) for the specified personal ID. Rows in the PIT and CPIT are read based on the value in the PERSONAL ID field on screen 1. Note: You must have security access to the FIID in the PIT row to be read.
F3	Add Record — Writes the currently displayed information on PIT screen 1 to the PIT and up to 30 selected CPIT rows from PIT screen 2 to the CPIT. Note: You must have security access to the FIID in the PIT row to be added.
F4	Delete Record — Deletes the currently displayed row on screen 1 from the PIT and all rows associated with the personal ID on PIT screen 1 from the CPIT.
F5	Update Record — Updates the PIT row with information from PIT screen 1. This function does not update any CPIT rows currently accessed on PIT screen 2. To update rows on PIT screen 2 you must first delete the row and then add it. Note: You must have security access to the FIID in the PIT row to be updated.

Key	Description
F6	Read Next Record — Reads the next row from the PIT and up to 30 corresponding rows from the CPIT for the specified personal ID on PIT screen 1. If the cursor is currently in the GIVEN NAME, FAMILY NAME, or M/I fields on PIT screen 1 when the F6 key is pressed, the next PIT row and associated CPIT rows are read by the full customer name rather than by the value in the PERSONAL ID field. If the cursor is in any other field on PIT screen 1 when the F6 key is pressed, the next PIT row and associated CPIT rows are read by PERSONAL ID.
F9	Next Screen — Displays PIT screen 2 if the CPIT is configured.
F11	Previous Screen — Displays PIT screen 2 if the CPIT is configured.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.

Screen 1

PIT screen 1 defines personal information for each customer who can access a customer ID. PIT screen 1 is shown below, followed by descriptions of its fields.

```

BASE24-CORE PERSONAL INFORMATION LLLL YY/MM/DD hh:mm 01 OF 02

PERSONAL ID: FIID: 0000

NAME- FAMILY: GIVEN: M/I: TITLE:

ADDRESS 1:
ADDRESS 2:
ADDRESS 3:

CITY: STATE: POSTAL CODE: CNTRY:

HOME PHONE: WORK PHONE:
OTHER PHONE: DESCR:
OTHER PHONE: DESCR:

BIRTH DATE : (YYYYMMDD) GOVERNMENT ID:
LANGUAGE IND: 00 MOTHER'S MAIDEN NAME:

RECORD LAST CHANGED: BY USER: ,
***** BASE24 *****
NEW PAGE: FILE DESTINATION: NEW LOGICAL NETWORK ID:
F12-HELP

```

PERSONAL ID — The identifier for this PIT row. The identifier can be prescribed by the service provider or chosen by the customer, but must be unique within the PIT. For example, this field could contain an employee number for a business customer. For an individual customer, this field could contain the individual's social security number or the customer ID.

When a new customer is added using the customer add transaction from the CSR Customer Signup screen or an RBSI-compliant device, the personal ID is always set to the value of the customer ID.

Field Length:	1–19 alphanumeric characters
Required Field:	Yes
Default Value:	No default value
Column Name:	PIT.PRSNL_ID

FIID — The FIID of the financial institution associated with this personal ID.

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Column Name: PIT.FIID

NAME

The following four fields define a customer's name.

FAMILY — The family name or last name of this customer.

This field accepts special characters required for languages other than U.S. English.

If the cursor is located in this field when the **F6** key is pressed, the entire name (that is, the values in the FAMILY, GIVEN, and M/I fields) is used to read the next table row.

Field Length: 1–20 alphanumeric or special characters
Required Field: Yes
Default Value: No default value
Column Name: PIT.NAM_FMLY

GIVEN — The given name or first name of this customer.

This field accepts special characters required for languages other than U.S. English.

If the cursor is located in this field when the **F6** key is pressed, the entire name (that is, the values in the FAMILY, GIVEN, and M/I fields) is used to read the next table row.

Field Length: 1–10 alphanumeric or special characters
Required Field: Yes
Default Value: No default value
Column Name: PIT.NAM_GIVEN

M/I — The initial of this customer's middle name.

If the cursor is located in this field when the **F6** key is pressed, the entire name (that is, the values in the FAMILY, GIVEN, and M/I fields) is used to read the next table row.

Field Length: 1 alphabetic character
Required Field: No
Default Value: No default value
Column Name: PIT.NAM_M_I

TITLE — The social title (for example, Mr., Mrs., Ms., Dr., Rev.), civil and military title (for example, Gen., Gov., Prof.), or any other title used to address this customer.

Field Length: 1–6 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.NAM_TITLE

ADDRESS 1 — The first line of the street or mailing address for this customer.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.STR_ADDR_1

ADDRESS 2 — The second line of the street or mailing address for this customer.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.STR_ADDR_2

ADDRESS 3 — The third line of the street or mailing address for this customer.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.STR_ADDR_3

CITY — The name of the city for this customer's residence or mailing address.

Field Length: 1–25 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.CITY

STATE — The two-letter U.S. state or Canadian province abbreviation for this customer's residence or mailing address. State codes are based on the 1988 ANSI X3.38 standard, *Identification of the States, the District of Columbia, and the Outlying and Associated Areas of the United States for Information Interchange*.

Field Length: 2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.ST_CDE

POSTAL CODE — The postal code of this customer's residence or mailing address.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.POSTAL_CDE

CNTRY — The country code associated with this customer's residence or mailing address. Country codes are based on the 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*.

Field Length: 3 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.CNTRY_CDE

HOME PHONE — The home telephone number for this customer.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.PHN_HOME

WORK PHONE — The work telephone number for this customer.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.PHN_WRK

OTHER PHONE — Any other telephone number (for example, cellular, paging, or fax) that can be used to reach this customer. The DESCR field on the same line of the screen describes this phone number.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Names: PIT.PHN_OTHER_1

DESCR — A description (for example, CELLULAR, PAGER, or FAX) of the telephone number provided in the OTHER PHONE field on the same line of the screen.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.PHN_OTHER_1_DESCR

OTHER PHONE — Any other telephone number (for example, cellular, paging, or fax) that can be used to reach this customer. The DESCR field on the same line of the screen describes this phone number.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Names: PIT.PHN_OTHER_2

DESCR — A description (for example, CELLULAR, PAGER, or FAX) of the telephone number provided in the OTHER PHONE field on the same line of the screen.

Field Length: 1–10 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.PHN_OTHER_2_DESCR

BIRTH DATE — The date of birth (YYYYMMDD) for this customer.

Field Length: 8 numeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.DOB

GOVERNMENT ID — The government ID (for example, U.S. social security number) assigned to this customer. The government ID can be used by customer service representatives to verify the identity of a calling customer.

Field Length: 1–15 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.GOV_T_ID

LANGUAGE IND — A user-defined code indicating the primary language spoken by this customer. Valid values are 00–99.

Field Length: 2 numeric characters
Required Field: No
Default Value: 00
Column Name: PIT.LANG_IND

MOTHER'S MAIDEN NAME — The maiden name of this customer's mother. This name can be used by customer service representatives to verify the identity of a calling customer.

This field accepts special characters required for languages other than U.S. English.

Field Length: 1–20 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: PIT.MTHR_MDN_NAM

Screen 2 Function Keys

The use of ten function keys on PIT screen 2 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on PIT screen 2.

Key	Description
F2	Read Record — This key does not work on PIT screen 2. To read rows on this screen, use the F2 key on PIT screen 1 or the F6 key on PIT screen 2.
F3	Add Record — Writes the currently accessed row from screen 1 to the PIT and the currently displayed and selected CPIT rows from PIT screen 2 to the CPIT. PIT screen 2 can have an unlimited number of pages with 30 primary account numbers (PANs) per page. Each PAN being added must be selected by setting the flag in column 1 or 4 on the same line of the screen to the value Y before pressing the F3 key. On this screen, PAN is an alternate term for a customer ID. Only one page with a maximum of 30 PANs can be added with the F3 key. Press the F3 key to add the associated PIT row and up to 30 CPIT rows, then use the Shift-F3 keys to add more CPIT rows associated with the same PIT row.
F4	Delete Record — This key is not valid on PIT screen 2. To delete CPIT rows on PIT screen 2, use the Shift-F4 keys.
F5	Update Record — This key is not valid on PIT screen 2. To update rows on PIT screen 2, you must first delete the rows using the Shift-F4 keys and then add the rows containing the desired changes using the Shift-F3 keys.

Key	Description
F6	Read Next Record — Reads the next row from the Personal Information Table (PIT) and the first 30 corresponding rows from the Customer/Personal ID Relation Table (CPIT) associated with the next PIT row. PIT screen 2 can have an unlimited number of pages with 30 PANs displayed per page. Press the Shift-F8 keys to read and display the next 30 CPIT rows associated with the same PIT row.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.
Shift-F3	Add Customer/Personal ID Record — Adds the information for the personal ID and selected PANs from the current page of PIT screen 2 to the CPIT. These keys are valid only on PIT screen 2 and a PIT row for the personal ID must already exist. PIT screen 2 can have an unlimited number of pages with 30 PANs per page. Each PAN being added must be selected by setting the flag in column 1 or 4 to the value Y before pressing the Shift-F3 keys. The Shift-F3 keys must be used to add CPIT rows on the current screen page before you display another screen 2 page. If you do not press the Shift-F3 keys before displaying another page, the selected PANs will not be added to the CPIT.
Shift-F4	Delete Customer/Personal ID Record — Deletes rows for the personal ID and selected PANs from the CPIT. These keys are valid only on PIT screen 2 and a PIT row for the personal ID must already exist. PIT screen 2 can have an unlimited number of pages with 30 PANs per page. Each PAN being deleted must be selected by setting the flag in column 1 or 4 to the value Y before pressing the Shift-F4 keys. The Shift-F4 keys must be used to delete CPIT rows on the current screen page before you display another PIT screen 2 page. If you do not press the Shift-F4 keys before displaying another page, the selected PANs will not be deleted from the CPIT.

Key	Description
Shift-F7	View Previous Page of Multi-Page Entry — Reads and displays the previous 30 CPIT rows associated with the current PIT row (identified by the PERSONAL ID field).
Shift-F8	View Next Page of Mutli-Page Entry — Reads and displays the next 30 CPIT rows associated with the current PIT row (identified by the PERSONAL ID field).

Screen 2

PIT screen 2 allows you to associate a single customer with multiple customer IDs, which are also referred to as primary account numbers (PANs). Conversely, Customer Table (CSTT) screen 3 allows you to associate multiple customers to a single customer ID. Data entered on either of these screens is stored in the Customer/Personal ID Relation Table (CPIT). PIT screen 2 is shown below, followed by descriptions of its fields.

```

BASE24-CORE PERSONAL INFORMATION LLLL YY/MM/DD hh:mm 02 OF 02
PERSONAL ID:

      PAN          ID TYP          PAN          ID TYP
<1>                                <1>

RECORD LAST CHANGED:                BY USER:
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:    NEW LOGICAL NETWORK ID:
SF3-ADD CUST/PRSNL ID RECORDS  SF4-DELETE CUST/PRSNL ID RECORDS  F12-HELP

```

PERSONAL ID — The identifier assigned to this PIT row on PIT screen 1.

Field Length: System-protected

Column Name: CPIT.PRSNL_ID

PAN — The customer ID of a Customer Table (CSTT) row this customer is allowed to access. This field maps to the CUSTOMER ID field displayed on CSTT screen 1. A row for this customer ID must exist in the Customer Table (CSTT) before it can be related here.

This field can be used by customer service representatives to verify the identity of a calling customer.

Field Length: 1–19 alphanumeric characters
Required Field: Yes, if the corresponding <1> field contains the value Y.
Default Value: No default value
Column Name: CPIT.PAN

ID TYP — A code indicating the type of table to which the PAN on the same line and column pertains. Currently, the only valid value is CU for the Customer Table (CSTT).

Field Length: 1–2 alphanumeric characters
Required Field: Yes, if the corresponding <1> field contains the value Y.
Default Value: No default value
Column Name: CPIT.ID_TYP

<1> — A code indicating whether the PAN on a particular line and column is to be included when an add or delete function is performed. Valid values are as follows:

Y = Yes, add or delete the PAN for this personal ID.

N = No, do not add or delete the PAN for this personal ID.

Field Length: 1 alphabetic character
Required Field: Yes, if the corresponding PAN field contains a value.
Default Value: N
Column Name: Not applicable

ACI Worldwide Inc.

Section 13

Processing Code Definition File (PCDF)

The Processing Code Definition File (PCDF) contains one record for each combination of product ID, routing profile, and processing code that is supported by an institution. PCDF records control the following at the institution level for each transaction:

- Whether the transaction is supported
- The type of account or accounts that are affected by the transaction
- The routing code for the transaction
- Whether an advice is required for the transaction
- The description associated with the transaction that is displayed on various screens and reports

Subsets of the transactions defined in the PCDF can be established at the customer level in the Customer Allowed Transaction Table (CATT). A transaction must be defined in the CATT and PCDF before it can be performed by a customer.

ACI provides a PCDF containing records for the full set of processing codes that the BASE24-telebanking and BASE24-billpay products support. This set of records is known as the default PCDF. The processing codes in this default PCDF are presented in this section. Default PCDF records are used for display on Customer Service Representative (CSR) screens, ITS Transaction Log File (ITLF) screens, and customer activity reports.

Information from the PCDF is used in the institution routing extended memory table. Any time a change is made to the PCDF, the institution routing extended memory table should be rebuilt using the Extended Memory Table Build utility and reallocated to objects that access the table using the EMT Warmboot command.

The values used in the ACCOUNT 1 TYPE and ACCOUNT 2 TYPE fields must first be defined in the ACCOUNT TYPE NAME field of the Account Type Table File (ATT).

The key to PCDF records is a combination of the data entered in the PRODUCT ID, ROUTE PROFILE, TRANSACTION CODE, ACCOUNT 1 TYPE, and ACCOUNT 2 TYPE fields.

Default PCDF Records

The PCDF defines the processing codes supported for each routing profile.

When ACI installs the BASE24-telebanking product with or without the BASE24-billpay product, a full set of records is placed in the PCDF with a value of 14 (BASE24-telebanking and BASE24-billpay products) in the PRODUCT ID field and asterisks (*****) in the ROUTE PROFILE field. A super user (that is, a user with a group number of 255 in his or her CRT access security record) can modify this full set, called the default PCDF, by adding, modifying, or deleting records with specific processing code information.

The value in the ROUTE PROFILE field on Institution Definition File (IDF) screen 40 identifies the set of PCDF records used by an institution. Each institution defined in the IDF can use an existing set of PCDF records or customize its own set of PCDF records.

The value in the TRANSACTION ALLOWED field of the default PCDF records determines whether the default PCDF can be specified in the ROUTE PROFILE field on IDF screen 40. The value in the TRANSACTION ALLOWED field of each default PCDF record provided by ACI is N (not allowed). This value is used to ensure that unwanted processing codes are not approved in error.

Institutions can use the default PCDF if a super user has changed the value in the TRANSACTION ALLOWED field of the default PCDF records for a usable set of transactions to Y (allowed). If the default PCDF provided by ACI has not been changed, an institution must create a copy of the default PCDF records and change the value in the TRANSACTION ALLOWED field of the copied records to Y (allowed) for each transaction that is allowed.

For example, institution A establishes a set of PCDF records for its transaction set. If institution B uses a subset of the transactions set up by institution A, another set of PCDF records must be added for institution B. If institution C uses the same set of transactions as institution B, the value in the ROUTE PROFILE field on screen 40 of the IDF record for institution C could match the value used on screen 40 of the IDF record for institution B and no new records would be added to the PCDF.

Common Field Values

The default records table on the following page lists the processing codes in the default PCDF records at the time of installation. All PCDF records have the following entries, with the exception of records for certain BASE24-billpay transactions as described in the footnote:

PRODUCT ID	14
ROUTE PROFILE	*****
TRANSACTION ALLOWED	N
ROUTE CODE	0000*
ADVICE REQUIRED	N

- * All BASE24-billpay transactions routed from the Integrated Authorization Server process to the XPNET Billpay Server process must use a value of BP in the ROUTE CODE field, where denotes two blank spaces. You may need to change the value of the ROUTE CODE field in the default PCDF from 0000 to BP for these transactions. BASE24-billpay transactions with a value of 4A, 4B, 50, 5A, and 5B in the TRANSACTION CODE field are routed from the XPNET Billpay Server or Scheduled Transaction Initiator process to the Integrated Authorization Server process, and, therefore, use a value of 0000 in the ROUTE CODE field.

Routing Restrictions

The following BASE24-telebanking transactions must always be routed to a host for authorization. They cannot be authorized on the BASE24 system.

TRANSACTION CODE	TRANSACTION DESCRIPTION
3Q	STATEMENT CLOSING DOWNLOAD
3R	STATEMENT DOWNLOAD
A0	CHECK STOP PAYMENT ADD

The following BASE24-billpay transactions cannot be routed to a host for authorization. These transactions must be authorized by the XPNET Billpay Server process, and therefore, must use the reserved value of BP00 in the ROUTE CODE field.

TRANSACTION CODE	TRANSACTION DESCRIPTION
3H	CUSTOMER VENDOR LIST INQUIRY
3J	SCHEDULED PAYMENTS LIST INQUIRY
3M	SCHEDULED TRANSACTIONS LIST INQUIRY
9K	CUSTOMER ADD
9L	CUSTOMER INQUIRY
9M	CUSTOMER UPDATE
9N	CUSTOMER VENDOR ADD
9P	CUSTOMER VENDOR DEACTIVATE
9Q	CUSTOMER VENDOR UPDATE
9R	MASTER VENDOR LIST INQUIRY
9T	CUSTOMER VENDOR REQUEST MAIL
9V	LOAN APPLICATION
9W	MISCELLANEOUS REQUEST
9X	HISTORY INQUIRY – ALL TRANS
B1	BANK LIST INQUIRY
B2	BANK BRANCH LIST INQUIRY
B4	MISCELLANEOUS REQUEST INQUIRY
B5	CUSTOMER ACCOUNT ADD
B6	CUSTOMER ACCOUNT ACTIVATE
B7	CUSTOMER ACCOUNT DEACTIVATE

TRANSACTION CODE	TRANSACTION DESCRIPTION
B8	CUSTOMER ACCOUNT DELETE
B9	CUSTOMER ACCOUNT UPDATE
BB	CUSTOMER ACTIVATE
BC	CUSTOMER DEACTIVATE
BD	CUSTOMER VENDOR ACTIVATE
BE	CUSTOMER VENDOR MASK VRFY INQ

* Even if your system uses small messages, the loan application transaction cannot be routed to a host.

Transaction Dependencies

When a schedule payment or transfer transaction (9A–9E) is supported for an institution, the corresponding transaction to execute each payment or transfer (4A–5B) must also be supported for the institution as shown in the following table. The 4A–5B transactions are automatically generated by the Scheduled Transaction Initiator or XPNET Billpay Server process.

Support for This Transaction Code:	Requires Support for This Transaction Code:
9A	50
9B	5A
9C	5B
9D	4A
9E	4B

Access to customer vendor add (9N) and master vendor add (9S) transactions also requires access to the master vendor list inquiry (9R) transaction code. The 9R transaction allows customer service representatives (CSRs) to search for an existing vendor before adding a new customer vendor.

Default PCDF Table

Each PCDF record has unique information in the PROCESSING CODE and TRANSACTION DESCRIPTION fields, as shown in the following table. Values in the ACCOUNT 1 TYPE and ACCOUNT 2 TYPE columns of the table are defined in the Account Type Table File (ATT). Refer to section 2 for additional information about the ATT.

The default records included when the BASE24-billpay product is installed along with the BASE24-telebanking product are identified with a check mark (✓) in the BP column of the table.

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
30	NONE	NONE		AVAIL FUNDS INQUIRY
30	SAV	NONE		AVAIL FUNDS INQUIRY SAV
30	SAV	DDA		AVAIL FUNDS INQUIRY SAV/DDA
30	DDA	NONE		AVAIL FUNDS INQUIRY DDA
30	DDA	SAV		AVAIL FUNDS INQUIRY DDA/SAV
30	CR	NONE		AVAIL FUNDS INQUIRY CR
30	LOCR	NONE		AVAIL FUNDS INQUIRY LOCR
30	CD	NONE		AVAIL FUNDS INQUIRY CD
30	IRA	NONE		AVAIL FUNDS INQUIRY IRA
30	NOW	NONE		AVAIL FUNDS INQUIRY NOW
30	CMRCL	NONE		AVAIL FUNDS INQUIRY CMRCL

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
30	INSTL	NONE		AVAIL FUNDS INQUIRY INSTL
30	MRTGL	NONE		AVAIL FUNDS INQUIRY MRTGL
3A	NONE	NONE		CHECK CLEARANCE INQUIRY
3A	DDA	NONE		CHECK CLEARANCE INQUIRY DDA
3A	NOW	NONE		CHECK CLEARANCE INQUIRY NOW
3B	NONE	NONE		LAST COUNT DB/CR INQUIRY
3B	SAV	NONE		LAST COUNT DB/CR SAV
3B	DDA	NONE		LAST COUNT DB/CR DDA
3B	CR	NONE		LAST COUNT DB/CR CR
3B	LOCR	NONE		LAST COUNT DB/CR LOCR
3B	CD	NONE		LAST COUNT DB/CR CD
3B	IRA	NONE		LAST COUNT DB/CR IRA
3B	NOW	NONE		LAST COUNT DB/CR NOW
3B	CMRCL	NONE		LAST COUNT DB/CR CMRCL
3B	INSTL	NONE		LAST COUNT DB/CR INSTL
3B	MRTGL	NONE		LAST COUNT DB/CR MRTGL
3C	NONE	NONE		LAST COUNT SOURCE

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
3C	SAV	NONE		LAST COUNT SOURCE SAV
3C	DDA	NONE		LAST COUNT SOURCE DDA
3C	CR	NONE		LAST COUNT SOURCE CR
3C	LOCR	NONE		LAST COUNT SOURCE LOCR
3C	CD	NONE		LAST COUNT SOURCE CD
3C	IRA	NONE		LAST COUNT SOURCE IRA
3C	NOW	NONE		LAST COUNT SOURCE NOW
3C	CMRCL	NONE		LAST COUNT SOURCE CMRCL
3C	INSTL	NONE		LAST COUNT SOURCE INSTL
3C	MRTGL	NONE		LAST COUNT SOURCE MRTGL
3D	NONE	NONE		LAST COUNT CHECK
3D	DDA	NONE		LAST COUNT CHECK DDA
3D	NOW	NONE		LAST COUNT CHECK NOW
3E	NONE	NONE		LAST COUNT DEBIT
3E	SAV	NONE		LAST COUNT DEBIT SAV
3E	DDA	NONE		LAST COUNT DEBIT DDA
3E	CR	NONE		LAST COUNT DEBIT CR
3E	LOCR	NONE		LAST COUNT DEBIT LOCR

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
3E	CD	NONE		LAST COUNT DEBIT CD
3E	IRA	NONE		LAST COUNT DEBIT IRA
3E	NOW	NONE		LAST COUNT DEBIT NOW
3F	NONE	NONE		LAST COUNT CREDIT
3F	SAV	NONE		LAST COUNT CREDIT SAV
3F	DDA	NONE		LAST COUNT CREDIT DDA
3F	CR	NONE		LAST COUNT CREDIT CR
3F	LOCR	NONE		LAST COUNT CREDIT LOCR
3F	CD	NONE		LAST COUNT CREDIT CD
3F	IRA	NONE		LAST COUNT CREDIT IRA
3F	NOW	NONE		LAST COUNT CREDIT NOW
3F	CMRCL	NONE		LAST COUNT CREDIT CMRCL
3F	INSTL	NONE		LAST COUNT CREDIT INSTL
3F	MRTGL	NONE		LAST COUNT CREDIT MRTGL
3G	NONE	NONE		LAST COUNT TRANSFER
3G	SAV	NONE		LAST COUNT TRANSFER SAV
3G	DDA	NONE		LAST COUNT TRANSFER DDA
3G	CR	NONE		LAST COUNT TRANSFER CR

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
3G	LOCR	NONE		LAST COUNT TRANSFER LOCR
3G	NOW	NONE		LAST COUNT TRANSFER NOW
3H	NONE	NONE	✓	CUSTOMER VENDOR LIST INQUIRY
3J	NONE	NONE	✓	SCHEDULED PAYMENTS LIST INQUIRY
3K	NONE	NONE	✓	SCHEDULED TRANSFERS LIST INQUIRY
3L	NONE	NONE	✓	HISTORY INQUIRY – PMNTS/ XFERS
3M	NONE	NONE	✓	SCHEDULED TRANSACTIONS LIST INQUIRY
3N	NONE	NONE		ACCOUNT LIST INQUIRY
3P	NONE	NONE		MULTIPLE ACCTS BALANCE INQUIRY
3Q	NONE	NONE		STATEMENT CLOSING DOWNLOAD
3Q	SAV	NONE		STATEMENT CLOSING DOWNLOAD SAV
3Q	DDA	NONE		STATEMENT CLOSING DOWNLOAD DDA

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
3Q	CR	NONE		STATEMENT CLOSING DOWNLOAD CR
3Q	LOCR	NONE		STATEMENT CLOSING DOWNLOAD LOCR
3Q	NOW	NONE		STATEMENT CLOSING DOWNLOAD NOW
3Q	CMRCL	NONE		STATEMENT CLOSING DOWNLOAD CMRCL
3Q	INSTL	NONE		STATEMENT CLOSING DOWNLOAD INSTL
3Q	MRTGL	NONE		STATEMENT CLOSING DOWNLOAD MRTGL
3R	NONE	NONE		STATEMENT DOWNLOAD
3R	SAV	NONE		STATEMENT DOWNLOAD SAV
3R	DDA	NONE		STATEMENT DOWNLOAD DDA
3R	CR	NONE		STATEMENT DOWNLOAD CR
3R	LOCR	NONE		STATEMENT DOWNLOAD LOCR
3R	NOW	NONE		STATEMENT DOWNLOAD NOW
3R	CMRCL	NONE		STATEMENT DOWNLOAD CMRCL
3R	INSTL	NONE		STATEMENT DOWNLOAD INSTL
3R	MRTGL	NONE		STATEMENT DOWNLOAD MRTGL

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
40	NONE	NONE		TRANSFER IMMED
40	SAV	SAV		TRANSFER IMMED SAV, SAV
40	SAV	DDA		TRANSFER IMMED SAV, DDA
40	SAV	CR		TRANSFER IMMED SAV, CR
40	SAV	LOCR		TRANSFER IMMED SAV, LOCR
40	SAV	NOW		TRANSFER IMMED SAV, NOW
40	SAV	CMRCL		TRANSFER IMMED SAV, CMRCL
40	SAV	INSTL		TRANSFER IMMED SAV, INSTL
40	SAV	MRTGL		TRANSFER IMMED SAV, MRTGL
40	DDA	SAV		TRANSFER IMMED DDA, SAV
40	DDA	DDA		TRANSFER IMMED DDA, DDA
40	DDA	CR		TRANSFER IMMED DDA, CR
40	DDA	LOCR		TRANSFER IMMED DDA, LOCR
40	DDA	NOW		TRANSFER IMMED DDA, NOW
40	DDA	CMRCL		TRANSFER IMMED DDA, CMRCL
40	DDA	INSTL		TRANSFER IMMED DDA, INSTL
40	DDA	MRTGL		TRANSFER IMMED DDA, MRTGL
40	CR	SAV		TRANSFER IMMED CR, SAV

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
40	CR	DDA		TRANSFER IMMED CR, DDA
40	CR	NOW		TRANSFER IMMED CR, NOW
40	LOCR	SAV		TRANSFER IMMED LOCR, SAV
40	LOCR	DDA		TRANSFER IMMED LOCR, DDA
40	LOCR	NOW		TRANSFER IMMED LOCR, NOW
40	NOW	SAV		TRANSFER IMMED NOW, SAV
40	NOW	DDA		TRANSFER IMMED NOW, DDA
40	NOW	CR		TRANSFER IMMED NOW, CR
40	NOW	LOCR		TRANSFER IMMED NOW, LOCR
40	NOW	NOW		TRANSFER IMMED NOW, NOW
40	NOW	CMRCL		TRANSFER IMMED NOW, CMRCL
40	NOW	INSTL		TRANSFER IMMED NOW, INSTL
40	NOW	MRTGL		TRANSFER IMMED NOW, MRTGL
4A	NONE	NONE	✓	TRANSFER FUTURE
4A	SAV	SAV	✓	TRANSFER FUTURE SAV, SAV
4A	SAV	DDA	✓	TRANSFER FUTURE SAV, DDA
4A	SAV	CR	✓	TRANSFER FUTURE SAV, CR
4A	SAV	LOCR	✓	TRANSFER FUTURE SAV, LOCR

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
4A	SAV	NOW	✓	TRANSFER FUTURE SAV, NOW
4A	SAV	CMRCL	✓	TRANSFER FUTURE SAV, CMRCL
4A	SAV	INSTL	✓	TRANSFER FUTURE SAV, INSTL
4A	SAV	MRTGL	✓	TRANSFER FUTURE SAV, MRTGL
4A	DDA	SAV	✓	TRANSFER FUTURE DDA, SAV
4A	DDA	DDA	✓	TRANSFER FUTURE DDA, DDA
4A	DDA	CR	✓	TRANSFER FUTURE DDA, CR
4A	DDA	LOCR	✓	TRANSFER FUTURE DDA, LOCR
4A	DDA	NOW	✓	TRANSFER FUTURE DDA, NOW
4A	DDA	CMRCL	✓	TRANSFER FUTURE DDA, CMRCL
4A	DDA	INSTL	✓	TRANSFER FUTURE DDA, INSTL
4A	DDA	MRTGL	✓	TRANSFER FUTURE DDA, MRTGL
4A	CR	SAV	✓	TRANSFER FUTURE CR, SAV
4A	CR	DDA	✓	TRANSFER FUTURE CR, DDA
4A	CR	NOW	✓	TRANSFER FUTURE CR, NOW
4A	LOCR	SAV	✓	TRANSFER FUTURE LOCR, SAV
4A	LOCR	DDA	✓	TRANSFER FUTURE LOCR, DDA
4A	LOCR	NOW	✓	TRANSFER FUTURE LOCR, NOW

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
4A	NOW	SAV	✓	TRANSFER FUTURE NOW, SAV
4A	NOW	DDA	✓	TRANSFER FUTURE NOW, DDA
4A	NOW	CR	✓	TRANSFER FUTURE NOW, CR
4A	NOW	LOCR	✓	TRANSFER FUTURE NOW, LOCR
4A	NOW	NOW	✓	TRANSFER FUTURE NOW, NOW
4A	NOW	CMRCL	✓	TRANSFER FUTURE NOW, CMRCL
4A	NOW	INSTL	✓	TRANSFER FUTURE NOW, INSTL
4A	NOW	MRTGL	✓	TRANSFER FUTURE NOW, MRTGL
4B	NONE	NONE	✓	TRANSFER RECURRING
4B	SAV	SAV	✓	TRANSFER RECURRING SAV, SAV
4B	SAV	DDA	✓	TRANSFER RECURRING SAV, DDA
4B	SAV	CR	✓	TRANSFER RECURRING SAV, CR
4B	SAV	LOCR	✓	TRANSFER RECURRING SAV, LOCR
4B	SAV	NOW	✓	TRANSFER RECURRING SAV, NOW
4B	SAV	CMRCL	✓	TRANSFER RECURRING SAV, CMRCL

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
4B	SAV	INSTL	✓	TRANSFER RECURRING SAV, INSTL
4B	SAV	MRTGL	✓	TRANSFER RECURRING SAV, MRTGL
4B	DDA	SAV	✓	TRANSFER RECURRING DDA, SAV
4B	DDA	DDA	✓	TRANSFER RECURRING DDA, DDA
4B	DDA	CR	✓	TRANSFER RECURRING DDA, CR
4B	DDA	LOCR	✓	TRANSFER RECURRING DDA, LOCR
4B	DDA	NOW	✓	TRANSFER RECURRING DDA, NOW
4B	DDA	CMRCL	✓	TRANSFER RECURRING DDA, CMRCL
4B	DDA	INSTL	✓	TRANSFER RECURRING DDA, INSTL
4B	DDA	MRTGL	✓	TRANSFER RECURRING DDA, MRTGL
4B	CR	SAV	✓	TRANSFER RECURRING CR, SAV
4B	CR	DDA	✓	TRANSFER RECURRING CR, DDA
4B	CR	NOW	✓	TRANSFER RECURRING CR, NOW

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
4B	LOCR	SAV	✓	TRANSFER RECURRING LOCR, SAV
4B	LOCR	DDA	✓	TRANSFER RECURRING LOCR, DDA
4B	LOCR	NOW	✓	TRANSFER RECURRING LOCR, NOW
4B	NOW	SAV	✓	TRANSFER RECURRING NOW, SAV
4B	NOW	DDA	✓	TRANSFER RECURRING NOW, DDA
4B	NOW	CR	✓	TRANSFER RECURRING NOW, CR
4B	NOW	LOCR	✓	TRANSFER RECURRING NOW, LOCR
4B	NOW	NOW	✓	TRANSFER RECURRING NOW, NOW
4B	NOW	CMCRL	✓	TRANSFER RECURRING NOW, CMCRL
4B	NOW	INSTL	✓	TRANSFER RECURRING NOW, INSTL
4B	NOW	MRTGL	✓	TRANSFER RECURRING NOW, MRTGL
50	NONE	NONE	✓	PAYMENT IMMED

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
50	SAV	NONE	✓	PAYMENT IMMED SAV
50	DDA	NONE	✓	PAYMENT IMMED DDA
50	CR	NONE	✓	PAYMENT IMMED CR
50	LOCR	NONE	✓	PAYMENT IMMED LOCR
50	NOW	NONE	✓	PAYMENT IMMED NOW
5A	NONE	NONE	✓	PAYMENT FUTURE
5A	SAV	NONE	✓	PAYMENT FUTURE SAV
5A	DDA	NONE	✓	PAYMENT FUTURE DDA
5A	CR	NONE	✓	PAYMENT FUTURE CR
5A	LOCR	NONE	✓	PAYMENT FUTURE LOCR
5A	NOW	NONE	✓	PAYMENT FUTURE NOW
5B	NONE	NONE	✓	PAYMENT RECURRING
5B	SAV	NONE	✓	PAYMENT RECURRING SAV
5B	DDA	NONE	✓	PAYMENT RECURRING DDA
5B	CR	NONE	✓	PAYMENT RECURRING CR
5B	LOCR	NONE	✓	PAYMENT RECURRING LOCR
5B	NOW	NONE	✓	PAYMENT RECURRING NOW
90	NONE	NONE		PIN CHANGE

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
91	NONE	NONE		PIN VERIFY
9A	NONE	NONE	✓	SCHEDULE PAYMENT IMMED
9A	SAV	NONE	✓	SCHEDULE PAYMENT IMMED SAV
9A	DDA	NONE	✓	SCHEDULE PAYMENT IMMED DDA
9A	CR	NONE	✓	SCHEDULE PAYMENT IMMED CR
9A	LOCR	NONE	✓	SCHEDULE PAYMENT IMMED LOCR
9A	NOW	NONE	✓	SCHEDULE PAYMENT IMMED NOW
9B	NONE	NONE	✓	SCHEDULE PAYMENT FUTURE
9B	SAV	NONE	✓	SCHEDULE PAYMENT FUTURE SAV
9B	DDA	NONE	✓	SCHEDULE PAYMENT FUTURE DDA
9B	CR	NONE	✓	SCHEDULE PAYMENT FUTURE CR
9B	LOCR	NONE	✓	SCHEDULE PAYMENT FUTURE LOCR
9B	NOW	NONE	✓	SCHEDULE PAYMENT FUTURE NOW

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9C	NONE	NONE	✓	SCHEDULE PAYMENT RECUR
9C	SAV	NONE	✓	SCHEDULE PAYMENT RECUR SAV
9C	DDA	NONE	✓	SCHEDULE PAYMENT RECUR DDA
9C	CR	NONE	✓	SCHEDULE PAYMENT RECUR CR
9C	LOCR	NONE	✓	SCHEDULE PAYMENT RECUR LOCR
9C	NOW	NONE	✓	SCHEDULE PAYMENT RECUR NOW
9D	NONE	NONE	✓	SCHEDULE XFER FUTURE
9D	SAV	SAV	✓	SCHEDULE XFER FUTURE SAV, SAV
9D	SAV	DDA	✓	SCHEDULE XFER FUTURE SAV, DDA
9D	SAV	CR	✓	SCHEDULE XFER FUTURE SAV, CR
9D	SAV	LOCR	✓	SCHEDULE XFER FUTURE SAV, LOCR
9D	SAV	NOW	✓	SCHEDULE XFER FUTURE SAV, NOW

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9D	SAV	CMCRL	✓	SCHEDULE XFER FUTURE SAV, CMCRL
9D	SAV	INSTL	✓	SCHEDULE XFER FUTURE SAV, INSTL
9D	SAV	MRTGL	✓	SCHEDULE XFER FUTURE SAV, MRTGL
9D	DDA	SAV	✓	SCHEDULE XFER FUTURE DDA, SAV
9D	DDA	DDA	✓	SCHEDULE XFER FUTURE DDA, DDA
9D	DDA	CR	✓	SCHEDULE XFER FUTURE DDA, CR
9D	DDA	LOCR	✓	SCHEDULE XFER FUTURE DDA, LOCR
9D	DDA	NOW	✓	SCHEDULE XFER FUTURE DDA, NOW
9D	DDA	CMCRL	✓	SCHEDULE XFER FUTURE DDA, CMCRL
9D	DDA	INSTL	✓	SCHEDULE XFER FUTURE DDA, INSTL
9D	DDA	MRTGL	✓	SCHEDULE XFER FUTURE DDA, MRTGL

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9D	CR	SAV	✓	SCHEDULE XFER FUTURE CR, SAV
9D	CR	DDA	✓	SCHEDULE XFER FUTURE CR, DDA
9D	CR	NOW	✓	SCHEDULE XFER FUTURE CR, NOW
9D	LOCR	SAV	✓	SCHEDULE XFER FUTURE LOCR, SAV
9D	LOCR	DDA	✓	SCHEDULE XFER FUTURE LOCR, DDA
9D	LOCR	NOW	✓	SCHEDULE XFER FUTURE LOCR, NOW
9D	NOW	SAV	✓	SCHEDULE XFER FUTURE NOW, SAV
9D	NOW	DDA	✓	SCHEDULE XFER FUTURE NOW, DDA
9D	NOW	CR	✓	SCHEDULE XFER FUTURE NOW, CR
9D	NOW	LOCR	✓	SCHEDULE XFER FUTURE NOW, LOCR
9D	NOW	NOW	✓	SCHEDULE XFER FUTURE NOW, NOW

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9D	NOW	CMCRL	✓	SCHEDULE XFER FUTURE NOW, CMCRL
9D	NOW	INSTL	✓	SCHEDULE XFER FUTURE NOW, INSTL
9D	NOW	MRTGL	✓	SCHEDULE XFER FUTURE NOW, MRTGL
9E	NONE	NONE	✓	SCHEDULE XFER RECUR
9E	SAV	SAV	✓	SCHEDULE XFER RECUR SAV, SAV
9E	SAV	DDA	✓	SCHEDULE XFER RECUR SAV, DDA
9E	SAV	CR	✓	SCHEDULE XFER RECUR SAV, CR
9E	SAV	LOCR	✓	SCHEDULE XFER RECUR SAV, LOCR
9E	SAV	NOW	✓	SCHEDULE XFER RECUR SAV, NOW
9E	SAV	CMCRL	✓	SCHEDULE XFER RECUR SAV, CMCRL
9E	SAV	INSTL	✓	SCHEDULE XFER RECUR SAV, INSTL
9E	SAV	MRTGL	✓	SCHEDULE XFER RECUR SAV, MRTGL

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9E	DDA	SAV	✓	SCHEDULE XFER RECUR DDA, SAV
9E	DDA	DDA	✓	SCHEDULE XFER RECUR DDA, DDA
9E	DDA	CR	✓	SCHEDULE XFER RECUR DDA, CR
9E	DDA	LOCR	✓	SCHEDULE XFER RECUR DDA, LOCR
9E	DDA	NOW	✓	SCHEDULE XFER RECUR DDA, NOW
9E	DDA	CMCRL	✓	SCHEDULE XFER RECUR DDA, CMCRL
9E	DDA	INSTL	✓	SCHEDULE XFER RECUR DDA, INSTL
9E	DDA	MRTGL	✓	SCHEDULE XFER RECUR DDA, MRTGL
9E	CR	SAV	✓	SCHEDULE XFER RECUR CR, SAV
9E	CR	DDA	✓	SCHEDULE XFER RECUR CR, DDA
9E	CR	NOW	✓	SCHEDULE XFER RECUR CR, NOW
9E	LOCR	SAV	✓	SCHEDULE XFER RECUR LOCR, SAV

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9E	LOCR	DDA	✓	SCHEDULE XFER RECUR LOCR, DDA
9E	LOCR	NOW	✓	SCHEDULE XFER RECUR LOCR, NOW
9E	NOW	SAV	✓	SCHEDULE XFER RECUR NOW, SAV
9E	NOW	DDA	✓	SCHEDULE XFER RECUR NOW, DDA
9E	NOW	CR	✓	SCHEDULE XFER RECUR NOW, CR
9E	NOW	LOCR	✓	SCHEDULE XFER RECUR NOW, LOCR
9E	NOW	NOW	✓	SCHEDULE XFER RECUR NOW, NOW
9E	NOW	CMCRL	✓	SCHEDULE XFER RECUR NOW, CMCRL
9E	NOW	INSTL	✓	SCHEDULE XFER RECUR NOW, INSTL
9E	NOW	MRTGL	✓	SCHEDULE XFER RECUR NOW, MRTGL
9F	NONE	NONE	✓	SCHEDULED PAYMENT DELETE
9G	NONE	NONE	✓	SCHEDULED TRANSFER DELETE

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
9H	NONE	NONE	✓	SCHEDULED PAYMENT UPDATE
9J	NONE	NONE	✓	SCHEDULED TRANSFER UPDATE
9K	NONE	NONE	✓	CUSTOMER ADD
9L	NONE	NONE	✓	CUSTOMER INQUIRY
9M	NONE	NONE	✓	CUSTOMER UPDATE
9N	NONE	NONE	✓	CUSTOMER VENDOR ADD
9P	NONE	NONE	✓	CUSTOMER VENDOR DEACTIVATE
9Q	NONE	NONE	✓	CUSTOMER VENDOR UPDATE
9R	NONE	NONE	✓	MASTER VENDOR LIST INQUIRY
9S	NONE	NONE	✓	MASTER VENDOR ADD
9T	NONE	NONE	✓	CUSTOMER VENDOR REQ MAILING
9V	NONE	NONE	✓	LOAN APPLICATION
9W	NONE	NONE	✓	MISCELLANEOUS REQUEST
9X	NONE	NONE	✓	HISTORY INQUIRY – ALL TRANS
A0	DDA	NONE		CHECK STOP PAYMENT ADD DDA
A0	LOCR	NONE		CHECK STOP PAYMENT ADD LOCR

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
A0	NOW	NONE		CHECK STOP PAYMENT ADD NOW
A0	CMRCL	NONE		CHECK STOP PAYMENT ADD CMRCL
A0	INSTL	NONE		CHECK STOP PAYMENT ADD INSTL
A0	MRTGL	NONE		CHECK STOP PAYMENT ADD MRTGL
B1	NONE	NONE	✓	BANK LIST INQUIRY
B2	NONE	NONE	✓	BANK BRANCH LIST INQUIRY
B4	NONE	NONE	✓	MISCELLANEOUS REQUEST INQUIRY
B5	NONE	NONE	✓	CUSTOMER ACCOUNT ADD
B6	NONE	NONE	✓	CUSTOMER ACCOUNT ACTIVATE
B7	NONE	NONE	✓	CUSTOMER ACCOUNT DEACTIVATE
B8	NONE	NONE	✓	CUSTOMER ACCOUNT DELETE
B9	NONE	NONE	✓	CUSTOMER ACCOUNT UPDATE
BB	NONE	NONE	✓	CUSTOMER ACTIVATE
BC	NONE	NONE	✓	CUSTOMER DEACTIVATE
BD	NONE	NONE	✓	CUSTOMER VENDOR ACTIVATE

PROCESSING CODE			BP	TRANSACTION DESCRIPTION
TRANSACTION CODE	ACCOUNT 1 TYPE	ACCOUNT 2 TYPE		
BE	NONE	NONE	✓	CUSTOMER VENDOR MASK VRFY INQ

Screen 1 Function Keys

The use of two function keys on PCDF screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on PCDF screen 1.

Key	Description
F7	Load Records — Copies all of the default PCDF records to the combination of values specified in the PRODUCT ID and ROUTE PROFILE fields. This key allows the user to add multiple records simultaneously instead of adding the records individually. Once the user has pressed the F7 key, the system generates a message when the load is successfully completed or an error is encountered. Only a super user can perform this function.
F9	Unload Records — Deletes all of the PCDF records for the combination of values specified in the PRODUCT ID and ROUTE PROFILE fields. This key allows the user to delete multiple records simultaneously instead of deleting the records individually. Once the user has pressed the F9 key, the system generates a message indicating that all records were successfully deleted from the PCDF for the combination of values specified in the PRODUCT ID and ROUTE PROFILE fields. Only a super user can perform this function.

In addition, only a super user (that is, a user with a group number of 255 in his or her CRT access security record) can add default PCDF rows using the **F3** key, delete PCDF default rows using the **F4** key, or update PCDF default rows using the **F5** key.

Screen 1

PCDF screen 1 allows you to specify the processing codes supported for a product ID and routing profile combination. The PCDF screen is shown below, followed by descriptions of its fields.

BASE24-CORE
PROCESSING CODE DEFN
LLLL
YY/MM/DD
hh:mm
01 OF 01

PRODUCT ID: 14
ROUTE PROFILE: *****

PROCESSING CODE

TRANSACTION CODE:
ACCOUNT 1 TYPE: NONE
ACCOUNT 2 TYPE: NONE

TRANSACTION ALLOWED: N (Y/N)
ROUTE CODE: 0000
ADVICE REQUIRED: N NO ADVICES
TRANSACTION DESCRIPTION:

RECORD LAST CHANGED:
BY USER:

***** BASE24 *****

FILE DESTINATION:
NEW LOGICAL NETWORK ID:

F7-LOAD
F9-UNLOAD
F12-HELP

PRODUCT ID — A code identifying the BASE24 product for which this processing code is defined. The valid value is 14 (BASE24-telebanking product with or without the BASE24-billpay product).

Field Length: 2 numeric characters
 Required Field: Yes
 Default Value: 14
 Data Name: PCDF.PRIKEY.PROD-ID

ROUTE PROFILE — A code identifying the institution or institutions using this processing code. The value in this field must match the value in the ROUTE PROFILE field on IDF screen 40. An entry of asterisks in this field indicates this PCDF record can be used by all institutions. Some institutions can be configured to have a specific route profile, while other institutions can use the default route profile.

The BASE24-telebanking and BASE24-billpay products search for a PCDF record with a value in the ROUTE PROFILE field that matches the value in the ROUTE PROFILE field on IDF screen 40 for the customer's financial institution. If a PCDF record with a value in the ROUTE PROFILE field matching the customer's financial institution route profile cannot be found, the BASE24-telebanking and BASE24-billpay products search for a PCDF record with a value in the ROUTE PROFILE field of all asterisks.

Field Length: 1–8 alphanumeric characters
Required Field: Yes
Default Value: *****
Data Name: PCDF.PRIKEY.RTE-PRFL

PROCESSING CODE

The following fields identify the processing code defined by this PCDF record.

TRANSACTION CODE — A code identifying the type of transaction being defined. Valid default values are shown in the TRANSACTION CODE column of the default PCDF table presented earlier in this section.

Field Length: 2 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: PCDF.PRIKEY.PROC-CDE.TXN-CDE

ACCOUNT 1 TYPE — A code identifying the account 1 type for the transaction being defined. Valid default values are shown in the ACCOUNT 1 TYPE column of the default PCDF table presented earlier in this section. A value must be defined in the Account Type Table File (ATT) before it can be used in this field.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: NONE
Data Name: PCDF.PRIKEY.PROC-CDE.ACCT1-TYP

ACCOUNT 2 TYPE — A code identifying the account 2 type for the transaction being defined. Valid default values are shown in the ACCOUNT 2 TYPE column of the default PCDF table presented earlier in this section. A value must be defined in the Account Type Table File (ATT) before it can be used in this field.

Field Length: 1–6 alphanumeric characters
Required Field: Yes
Default Value: NONE
Data Name: PCDF.PRIKEY.PROC-CDE.ACCT2-TYP

TRANSACTION ALLOWED — A code indicating whether the transaction being defined is allowed. Valid values are as follows:

Y = Yes, the transaction is allowed.
N = No, the transaction is not allowed.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: PCDF.TXN-ALWD-FLG

ROUTE CODE — A value used to group transactions for routing and authorization purposes when multiple destinations must be defined for an institution in the Institution Routing Configuration File (IRCF).

All BASE24-billpay transactions routed from the Integrated Authorization Server process to the XPNET Billpay Server process must use a value of BP00 in this field.

The value in this field must match the value in the ROUTE CODE field in the Institution Routing Configuration File (IRCF).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: 0000
Data Name: PCDF.RTE-CDE

ADVICE REQUIRED — A code identifying the type of transactions for which BASE24 products send an advice to the host after authorizing the transaction. Valid values are as follows:

A = Send advices for approved transactions only.
B = Send advices for approved and denied transactions.
D = Send advices for denied transactions only.
N = Do not send advices.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: PCDF.ADVC-REQ

TRANSACTION DESCRIPTION — The description of the transaction. This description should identify the purpose of the transaction and the type of accounts involved. Refer to the “Default PCDF Records” discussion presented earlier in this section for examples.

The information in this field is displayed on ITS Transaction Log File (ITLF) screens, Customer Service Representative (CSR) screens, and on BASE24-telebanking reports.

Field Length: 1–30 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: PCDF.TXN-DESCR

Section 14

Transaction History Configuration File (THCF)

The Transaction History Configuration File (THCF) is used with the Positive Customer with Balances/History Authorization method (PCBA).

The BASE24-telebanking product uses the Transaction History File (THF) to authorize transaction history inquiries. The THF is updated only by the Enscribe Refresh process. The BASE24-telebanking product does not update the THF when it authorizes financial transactions.

The BASE24-telebanking product permits a processor to maintain multiple THFs. The BASE24-telebanking product uses the THCF to determine which THF contains the information needed to authorize a transaction history inquiry. The refresh group, FIID, and application account number can be used to determine which THF is accessed.

The REFRESH GROUP, FIID, and ACCOUNT NUMBER END RANGE fields make up the key to the THCF.

Screen 1 Function Keys

The use of one function key on THCF screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of this function key is explained below.

The first column shows the BASE24 key. The second column describes the functions that can be accomplished with this key on THCF screen 1.

Key	Description
Shift-F2	Display Summary — Retrieves the first summary page of THCF records for the refresh group and FIID specified on THCF screen 1 and displays the information on THCF screen 2. Note: The END RANGE field must contain a zero when this function is performed.

Screen 1

THCF screen 1 allows you to associate a refresh group, FIID, and account number range with specific Transaction History Files (THFs). Screen 1 of the THCF is shown below, followed by descriptions of its fields.

BASE24-CORE
TRAN HIST CONFIG FILE
LLLL
YY/MM/DD
hh:mm
01 OF 02

REFRESH GROUP:
FIID:

ACCOUNT NUMBER START RANGE: 000000000000000000

ACCOUNT NUMBER END RANGE: 000000000000000000

ASSIGN:

COMMENT:

RECORD LAST CHANGED:
BY USER:
,

BASE24

FILE DESTINATION:
NEW LOGICAL NETWORK ID:

F12-HELP

REFRESH GROUP — The refresh group to which this record applies.

Field Length: 1–4 alphanumeric characters
 Required Field: Yes
 Default Value: No default value
 Data Name: THCF.PRIKEY.REFR-FIID.REFR-GRP

FIID — An identifier for the institution to which this record applies.

Asterisks (****) can be used in this field when all institutions in a refresh group use the same Transaction History File (THF).

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: THCF.PRIKEY.REFR-FIID.FIID

ACCOUNT NUMBER START RANGE — An integer that identifies the first application account for the refresh group and FIID combination that uses the Transaction History File (THF) associated with this THCF record. The first THCF record for a given refresh group and FIID contains a zero in this field.

Field Length: System-protected
Data Name: Not applicable

ACCOUNT NUMBER END RANGE — An integer that identifies the last application account for the refresh group and FIID combination that uses the THF associated with this THCF record. Valid values are as follows:

00000000000000000000 = Display THCF screen 2
1–999999999999999999 = Last application account that uses the THF
associated with this THCF record

The value in this field must be set to all zeros before the **Shift-F2** keys are pressed to display THCF screen 2.

The value in this field should be set to 99999999999999999999 when there is a single THCF record for a given refresh group and FIID.

Field Length: 19 numeric characters
Required Field: Yes
Default Value: 00000000000000000000
Data Name: THCF.PRIKEY.END-RANGE

ASSIGN — The Logical Network Configuration File (LCONF) assign name used to locate the THF template for the accounts specified in this THCF record. The assign name must begin with THF-.

Field Length: 1–32 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: THCF.THF-ASGN

COMMENT — A description of how this THCF entry is used.

Field Length:	1–50 alphanumeric characters
Required Field:	No
Default Value:	No default value
Data Name:	THCF.COMMENT

Screen 2 Function Keys

The use of three function keys on THCF screen 2 varies from the standard function keys explained in the ***BASE24 Base Files Maintenance Manual*** and the ***BASE24 CRT Access Manual***. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on THCF screen 2.

Key	Description
F4	Select Record — Selects a specific THCF record and displays the information on THCF screen 1. To select a record, place the cursor in the SEL column of the desired THCF record and press the F4 key.
F9	Next Page — Retrieves the next summary page of THCF records for the specified refresh group and FIID.
F11	Previous Page — Retrieves the previous summary page of THCF records for the specified refresh group and FIID.

Screen 2

THCF screen 2 allows you to select individual THCF records for a refresh group and FIID specified on THCF screen 1. The selected record is then displayed on THCF screen 1. Screen 2 of the THCF is shown below, followed by descriptions of its fields.

BASE24-CORE

TRAN HIST CONFIG FILE

LLLL

YY/MM/DD

hh:mm

02 OF 02

REFRESH GROUP:

FIID: ****

----- RANGE -----

SEL

START

END

ASSIGN

<NO MORE RECORDS EXIST>

***** BASE24 *****

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F4-SELECT RECORD

F9-NEXT PAGE

F11-PREVIOUS PAGE

F12-HELP

F16-EXIT

SEL — Identifies one of the THCF records displayed on this screen before the **F4** key is pressed. This field is used to select a record to be displayed on THCF screen 1.

Field Length: Cursor position only
Data Name: Not applicable

RANGE

The START and END fields identify the accounts that use the Transaction History File (THF) associated with this THCF record.

START — An integer that identifies the first application account that uses the THF associated with this THCF record. The first THCF record for a given refresh group and FIID contains a zero in this field.

Field Length: System-protected

Data Name: Not applicable

END — An integer that identifies the last application account that uses the THF associated with this THCF record.

Field Length: System-protected

Data Name: THCF.PRIKEY.END-RANGE

ASSIGN — The Logical Network Configuration File (LCONF) assign name used to locate the THF template for the accounts specified in this THCF record.

Field Length: System-protected

Data Name: THCF.THF-ASGN

Section 15

Transaction Type By Source Code Table (TTSC)

The Transaction Type By Source Code Table (TTSC) is an SQL table that contains one row for each unique combination of source code and BASE24-telebanking or BASE24-billpay transaction allowed at an inbound customer service representative (CSR) terminal. Currently, the TTSC is used only to restrict the transactions that can be performed at an inbound CSR terminal. It is not currently used to restrict transactions performed at a remote banking endpoint device.

TTSC rows are also used to display the transactions available to CSRs on the Transaction Menu, which is one of the screens accessed from the CSR Control (CSRC) entry on the Core Product Menu. If a transaction is not configured in the TTSC, it is not displayed on this menu and cannot be performed by the CSR. The value defined in the TRANSACTION DESCRIPTION field on the TTSC is displayed as a transaction selection on the Transaction Menu. Transactions are arranged on this menu in the order specified by the value in the POSITION field on the TTSC. If multiple transactions have the same value in the POSITION field, they are displayed in the order of values in the TRANSACTION TYPE field for that position. For detailed information on the Transaction Menu, refer to the *BASE24 Remote Banking Customer Service Support Manual*.

When a CSR attempts to execute a transaction configured in the TTSC, the customer's institution and profile must also allow access to the transaction before it can be performed by the CSR. Institution access is controlled by the PCDF. Customer access is controlled by the CSTT and CATT.

The BASE24-telebanking and BASE24-billpay products include a TTSC that contains rows for the CSR transactions that the BASE24-telebanking and BASE24-billpay products support. This set of rows is known as the default TTSC. The transactions in the default TTSC are presented in this section.

The primary key to TTSC rows is a combination of the SOURCE CODE and TRANSACTION TYPE fields.

Default TTSC Rows

The default TTSC defines the transactions that can be performed from an inbound customer service representative (CSR) terminal and displayed on the Transaction Menu.

When ACI installs the BASE24-telebanking product with or without the BASE24-billpay product, a full set of rows is placed in the TTSC with the SOURCE CODE field set to a value of IB. The group user who owns the network can modify this full set, called the default TTSC, by adding, modifying, or deleting rows with specific transaction information.

Note: BASE24-billpay transactions automatically generated by the XPNET Billpay Server or Scheduled Transaction Initiator process (that is, transaction types 4A, 4B, 50, 5A, and 5B) should not be configured to the TTSC. Access to these transactions is controlled completely at the institution and customer levels.

CSR access to the 9N (CUSTOMER VENDOR ADD) transaction also requires access to the 9R (MASTER VENDOR LIST INQUIRY) transaction.

The following table, called the default TTSC table, lists each of the rows provided in the default TTSC. Rows required when the BASE24-billpay product is installed along with the BASE24-telebanking product are identified with a check mark (✓) in the BP column of the table. All default TTSC rows have a value of IB in the SOURCE CODE field.

TRANSACTION TYPE	TRANSACTION DESCRIPTION	POSITION	BP
30	AVAILABLE FUNDS INQUIRY	1	
3A	CHECK CLEARANCE INQUIRY	2	
3B	LAST COUNT DB/CR INQUIRY	3	
3C	LAST COUNT SOURCE INQUIRY	4	

TRANSACTION TYPE	TRANSACTION DESCRIPTION	POSITION	BP
3D	LAST COUNT CHECK INQUIRY	5	
3E	LAST COUNT DEBIT INQUIRY	6	
3F	LAST COUNT CREDIT INQUIRY	7	
3G	LAST COUNT TRANSFER INQUIRY	8	
3H	CUSTOMER VENDOR LIST INQUIRY	16	✓
3J	SCHEDULED PAYMENTS LIST INQUIRY	27	✓
3K	SCHEDULED TRANSFERS LIST INQUIRY	28	✓
3L	HISTORY INQUIRY – PMNTS/XFERS	34	✓
3M	SCHEDULED TRANSACTIONS LIST INQUIRY	26	✓
3N	ACCOUNT LIST INQUIRY	9	
3P	ACCOUNT LIST INQ WITH BALANCES	9	
3Q	STATEMENT CLOSING DOWNLOAD INQUIRY	9	
3R	STATEMENT DOWNLOAD INQUIRY	9	
40	TRANSFER IMMEDIATE	10	
90	PIN CHANGE	11	
91	PIN VERIFY	12	
9A	SCHEDULE PAYMENT – IMMEDIATE	21	✓
9B	SCHEDULE PAYMENT – FUTURE	22	✓
9C	SCHEDULE PAYMENT – RECURRING	23	✓

TRANSACTION TYPE	TRANSACTION DESCRIPTION	POSITION	BP
9D	SCHEDULE TRANSFER – FUTURE	24	✓
9E	SCHEDULE TRANSFER – RECURRING	25	✓
9F	SCHEDULED PAYMENT DELETE	29	✓
9G	SCHEDULED TRANSFER DELETE	30	✓
9H	SCHEDULED PAYMENT UPDATE	31	✓
9J	SCHEDULED TRANSFER UPDATE	32	✓
9K	CUSTOMER ADD	15	✓
9L	CUSTOMER INQUIRY	13	✓
9M	CUSTOMER UPDATE	14	✓
9N	CUSTOMER VENDOR ADD	17	✓
9P	CUSTOMER VENDOR DEACTIVATE	18	✓
9Q	CUSTOMER VENDOR UPDATE	19	✓
9R	MASTER VENDOR LIST INQUIRY	19	✓
9S	MASTER VENDOR ADD	19	✓
9T	CUSTOMER VENDOR REQUEST MAIL	20	✓
9V	LOAN APPLICATION	35	✓
9W	MISCELLANEOUS REQUEST	36	✓
9X	HISTORY INQUIRY – ALL TRANS	33	✓
A0	CHECK STOP PAYMENT	12	

TRANSACTION TYPE	TRANSACTION DESCRIPTION	POSITION	BP
B1	BANK LIST INQUIRY	33	✓
B2	BANK BRANCH LIST INQUIRY	33	✓
B4	MISCELLANEOUS REQUEST INQUIRY	33	✓
B5	CUSTOMER ACCOUNT ADD	33	✓
B6	CUSTOMER ACCOUNT ACTIVATE	33	✓
B7	CUSTOMER ACCOUNT DEACTIVATE	33	✓
B8	CUSTOMER ACCOUNT DELETE	33	✓
B9	CUSTOMER ACCOUNT UPDATE	33	✓
BB	CUSTOMER ACTIVATE	33	✓
BC	CUSTOMER DEACTIVATE	33	✓
BD	CUSTOMER VENDOR ACTIVATE	33	✓
BE	CUSTOMER VENDOR MASK VRFY INQ	33	✓

Screen 1 Function Keys

The use of eight function keys on TTSC screen 1 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on TTSC screen 1.

Key	Description
F2	Read by Source Code/Transaction Type — Reads the first 14 rows from the Transaction Type By Source Code Table (TTSC) according to the values entered in the SOURCE CODE and TRANSACTION TYPE fields at the top of the screen. Rows are displayed in order by SOURCE CODE and then by TRANSACTION TYPE within each source code. TTSC screen 1 can have an unlimited number of pages with 14 TTSC rows per page. Press the Shift-F7 or Shift-F8 keys as needed to read and display the next or previous 14 TTSC rows associated with the same SOURCE CODE and TRANSACTION TYPE field values.
F3	Add Record — Writes the currently displayed and selected TTSC rows from TTSC screen 1 to the TTSC. Each row being added on the currently displayed page must be selected by setting the flag in column 1 on the same line of the screen to the value Y before pressing the F3 key. TTSC screen 1 can have an unlimited number of pages with up to 14 selected TTSC rows per page. Only one screen page with a maximum of 14 selected TTSC rows can be added with the F3 key. Rows selected on screen pages that are not currently displayed are not added when the F3 key is pressed. After adding rows for the currently displayed screen page, press the F8 key to clear the screen before adding additional TTSC rows.

Key	Description
F4	Delete Record — Deletes the currently displayed and selected TTSC rows on TTSC screen 1 from the TTSC. Each row being deleted on the currently displayed page must be selected by setting the flag in column 1 on the same line of the screen to the value Y before pressing the F4 key. TTSC screen 1 can have an unlimited number of pages with up to 14 selected TTSC rows per page. Only one screen page with a maximum of 14 selected TTSC rows can be deleted with the F4 key. Rows selected on screen pages that are not currently displayed are not deleted when the F4 key is pressed. After deleting rows for the currently displayed screen page, press the Shift-F7 or Shift-F8 keys as needed to read additional TTSC rows to be deleted.
F5	Update Record — Updates the currently displayed and selected TTSC rows on TTSC screen 1 from the TTSC. Each row being updated on the currently displayed page must be selected by setting the flag in column 1 on the same line of the screen to the value Y before pressing the F5 key. TTSC screen 1 can have an unlimited number of pages with up to 14 selected TTSC rows per page. Only one screen page with a maximum of 14 selected TTSC rows can be updated with the F5 key. Rows selected on screen pages that are not currently displayed are not updated when the F5 key is pressed. After updating rows for the currently displayed screen page, press the Shift-F7 or Shift-F8 keys as needed to read additional TTSC rows to be updated.
F6	Read by Source Code/Position — Reads the first 14 rows from the TTSC according to the value entered in the SOURCE CODE field at the top of the screen and the value stored in the POSITION field of the TTSC rows. Rows are displayed in ascending position order for the selected source code. TTSC screen 1 can have an unlimited number of pages with 14 TTSC rows per page. Press the Shift-F8 keys to read and display the next 14 TTSC rows associated with the same SOURCE CODE in source code/position order.
F13	Change Current Logical Network — This function is not available on screens that access SQL tables.

Key	Description
Shift-F7	View Previous Page of Multi-Page Entry — Reads and displays the previous 14 TTSC rows in the order the rows are being read (that is, by source code and transaction type or by source code and position).
Shift-F8	View Next Page of Mutli-Page Entry — Reads and displays the next 14 TTSC rows in the order the rows are being read (that is, by source code and transaction type or by source code and position).

Screen 1

TTSC screen 1 allows you to specify the allowed transactions for inbound Customer Service Representative (CSR) terminals. Screen 1 of the TTSC is shown below, followed by descriptions of its fields.

BASE24-CORE
TRAN TYPE BY SOURCE
LLLL
YY/MM/DD
hh:mm
01 OF 01

SOURCE CODE:

TRANSACTION TYPE:

SOURCE

TRANSACTION

TRANSACTION

CODE

TYPE

DESCRIPTION

POSITION

<1>

RECORD LAST CHANGED:

BY USER:

***** BASE24 *****

NEW PAGE:

FILE DESTINATION:

NEW LOGICAL NETWORK ID:

F2-READ BY SOURCE/TRAN TYPE

F6-READ BY SOURCE/POSITION

F12-HELP

SOURCE CODE — A code identifying a source code to be read. Valid values include any one- or two-character alphanumeric combination. Valid values reserved for BASE24 products are listed with the next SOURCE CODE field description.

Field Length: 2 alphanumeric characters
 Required Field: No
 Default Value: No default value
 Column Name: Not applicable

TRANSACTION TYPE — A code identifying a transaction type to be read. Valid values include any two-character alphanumeric combination. Valid values reserved for BASE24 products are listed in the default TTSC described earlier in this section. Spaces are not allowed in this field.

Field Length: 2 alphanumeric characters
Required Field: No
Default Value: No default value
Column Name: Not applicable

SOURCE CODE — A code identifying a transaction source. Valid values include any two-character alphanumeric combination. Valid values reserved for BASE24 products are as follows:

AD = Audio device (for example, an interactive voice response system)
IB = Inbound customer service representative
PC = Personal computer
SP = Screen phone

Currently, only the IB value is used.

Field Length: 2 alphanumeric characters
Required Field: Yes, if this line is selected
Default Value: No default value
Column Name: TTSC.SRC_CDE

TRANSACTION TYPE — A code identifying a transaction type allowed from this transaction source. Valid values include any two-character alphanumeric combination; spaces are not allowed. Valid values reserved for BASE24 products are listed in the default TTSC table provided earlier in this section.

Field Length: 2 alphanumeric characters
Required Field: Yes, if this line is selected
Default Value: No default value
Column Name: TTSC.TXN_TYP

TRANSACTION DESCRIPTION — A text description of the transaction type displayed in the TRANSACTION TYPE field on the same line of the screen. This text is displayed as an item on the Transaction Menu.

Field Length: 1–30 alphanumeric characters
Required Field: Yes, if this line is selected
Default Value: No default value
Column Name: TTSC.DESCR

POSITION — A number indicating the relative position of this row when rows are read by source code and position using the **F6** key or when transactions are displayed on the Transaction Menu.

Using the POSITION field, for example, you can position transactions so that the most common transactions are displayed first on this screen and on the Transaction Menu.

The number entered in this field does not have to be unique. If multiple rows have the same value in this field, the rows with the same value are displayed in transaction type order.

Field Length: 1–4 numeric characters
Required Field: Yes, if this line is selected
Default Value: 0
Column Name: TTSC.POSN

<1> — A code indicating whether the TTSC row displayed on a particular line is to be included when an add, delete, or update function is performed. This code also identifies rows with errors when information is being added or updated. If no information is displayed on the same line of the screen, this field will be blank. Valid values are as follows:

Y = Yes, add, delete, or update this row.
N = No, do not add, delete, or update this row.
E = Information on this line contains one or more errors.

You can set this field to the value Y or N. This field is set to the value E when an error is found through system validation after an attempt to add or update a row.

Field Length: 1 alphabetic character
Required Field: Yes, if this line is selected
Default Value: N
Column Name: Not applicable

ACI Worldwide Inc.

Section 16

VRU Configuration Data (VCD)

The VRU Configuration Data (VCD) screens are used to configure the Remote Banking Standard Interface and the Customer Service Interface. These interfaces are responsible for communicating with RBSI-compliant devices and customer service representative (CSR) terminals, respectively. Examples of RBSI-compliant devices include the following: interactive voice response system (IVR), call center, screen phone, personal computer, third-party processor, kiosk, personal digital assistant, or the Internet.

The VCD screens display information from the following files:

- The ITS Interface Configuration File (IFCF) contains most of the configuration information for remote banking endpoint devices and CSR terminals.
- The Interface Station Table File (IST) contains the stations defined for remote banking endpoint devices. The IST is not used for CSR terminals.
- The Address Table File (ADRT) contains the geographic address information associated with the remote banking endpoint devices and CSR terminals.

The value in the INTERFACE NAME field is the key to the VCD screens.

One set of records associated with the VCD screens (that is, one IFCF record, one ADRT record, and one IST record) is required for each interface instance. An interface instance is not a process or a station. Each interface instance provides a means of dividing up interface processing according to specific business relationships and purposes. Interface instances can share one Interface Master process and use multiple Integrated Authorization Server processes. Up to 90 remote banking endpoint stations can be associated with each interface instance. All CSR terminals share one interface instance with no stations defined for the interface instance in the IST.

Information from the ADRT, IFCE, and IST is used in the interface extended memory table. Any time a change is made to one or more of these files, the interface extended memory table should be rebuilt using the Extended Memory Table Build utility and reallocated to objects that access the table using the EMT Warmboot command.

The VCD includes the following screens:

- Screen 1 contains base fields
- Screen 2 contains base fields
- Screen 4 contains dynamic key management information
- Screen 9 contains a station table
- Screen 18 contains BASE24-telebanking and BASE24-billpay interface processing data

Screen 1

VCD screen 1 defines the processing options associated with a particular interface instance. VCD screen 1 is shown below, followed by descriptions of its fields.

Note: Many of the fields on this screen are not used by the BASE24-telebanking and BASE24-billpay products. Each field description indicates whether the field is used by the BASE24-telebanking and BASE24-billpay products and whether the field is required. Required fields must contain a valid value even when they are not used during processing.

```

BASE24-CORE VRU CONFIGURATION          LLLL      YY/MM/DD  hh:mm  01 OF 45
INTERFACE NAME:                        INTERFACE TYPE:
                                     FIID:
                                     NAME:
      PROCESSING OPTIONS
      DE-SAF LIMIT:      1
      MAX SAF RETRY:     0
      NMM ENABLED: Y (Y/N)
      AUTO LOGON: Y (Y/N)
      KEY MGMT TYPE: N (NONE)
      MAC TYPE: N (NONE)
      MAC NMM: N (Y/N)
      MAC DATA TYPE: A (ASCII)
      IMP SYMBOLIC NAME:
      PRODUCT INDICATOR TABLE (Y/N)
      Y BASE
                                     ADDRESS 1:
                                     ADDRESS 2:
      POSTAL CODE:
      UNKNOWN ROUTE CODE:
      SAF GROUP:
      DESTINATION GROUP:
      MEASURE COUNTER NAME:
                                     IAS QUEUE:
      Y TB

RECORD LAST CHANGED:                  BY USER:
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                                     F12-HELP

```

INTERFACE NAME — The name that identifies the interface instance.

An interface instance provides a means of dividing interface processing according to specific business relationships and purposes. Interface processing is divided according to groups of stations, with up to 90 stations per each interface instance. For example, a separate interface instance could be used for each financial institution using the interface. One interface instance is used to define interface processing for all customer service representative (CSR) terminals.

If this interface instance is for the customer service representative (CSR) terminals, this field must contain the value CSI. CSI is the code for the Customer Service Interface object.

If this interface instance is for RBSI-compliant devices, the value in this field must uniquely identify the interface instance and match values entered in fields in other files. The value in this field must match the value in the INTERFACE NAME field on screen 1 of the Interface Security File (ISF) record used by this interface instance. The value in this field must also match the value in the PROCESS NAME field of an External Message File (EMF) record for the interface instance. EMF records for RBSI-compliant device interface instances are identified with a value of VRU in the INTERF TYP field of the EMF record. For detailed information on the EMF, refer to the ***BASE24 Base Files Maintenance Manual***.

There can be between 1 and 90 remote banking endpoint stations associated with each instance of the Remote Banking Standard Interface. The endpoint stations associated with this interface instance are specified on VCD screen 9.

The interface instance specified in this field uses the Interface Master process specified in the IMP SYMBOLIC NAME field on this screen.

Field Length: 1–16 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: IFCF.PRIKEY.INTF-NAM

INTERFACE TYPE — A code identifying the type of interface. Valid values are as follows:

CSI = Customer service
VRU = Remote banking standard

Field Length: 1–4 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: IFCF.ALTKEY.OBJ-NAM

FIID — The FIID of the financial institution that controls this interface instance. The FIID entered in this field should be defined in the Institution Definition File (IDF). However, this is an information-only field and its contents are not used in processing or compared with information in the IDF.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SWI-LGNT

PROCESSING OPTIONS

The following fields are used to configure the processing options used by this interface instance:

DE-SAF LIMIT
MAX SAF RETRY
NMM ENABLED
AUTO LOGON
KEY MGMT TYPE
MAC TYPE
MAC NMM
MAC DATA TYPE

These fields appear in a column on the screen. However, field descriptions are arranged according to cursor movement (that is, row first instead of column first). Therefore, descriptions for fields in the first column (processing options) and descriptions for fields in the second column are combined.

NAME — An information-only field for this interface instance. This name should be descriptive of the interface instance it represents. For example, an interface instance that supports a financial institution with an FIID of BK16 could be “BK16 Interface.”

Field Length: 1–22 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: ADRT.NAM

DE-SAF LIMIT — The maximum number of Store-and-Forward File (SAF) records that can be sent at one time. Valid values are 0 through 9999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 1
Data Name: IFCF.SEG0000.PROC-LMT.DE-SAF

ADDRESS 1 — An information-only field for this interface instance. For example, this field could contain the street address of a financial institution processed by this interface instance.

Field Length: 1–25 alphanumeric characters
Required Field: Yes
Default Value: No default value
Data Name: ADRT.ADDR1

MAX SAF RETRY — The maximum number of times a record in the Store-and-Forward File (SAF) can be transmitted before being deleted from the SAF.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0000.PROC-LMT.MAX-SAF-RETRY

ADDRESS 2 — An information-only field for this interface instance. For example, this field could contain the city and state of a financial institution processed by this interface instance.

Field Length: 1–25 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: ADRT.ADDR2

NMM ENABLED — A code indicating whether BASE24 products can send network management messages to this interface instance. Valid values are as follows:

Y = Yes, BASE24 products can send network management messages to this interface instance.

N = No, BASE24 products cannot send network management messages to this interface instance.

Field Length: 1 alphanumeric character

Required Field: Yes

Default Value: Y

Data Name: IFCF.SEG0000.PROC-FLG.NMM-ENABLED

POSTAL CODE — An information-only field for this interface instance. For example, this field could contain the postal code of a financial institution processed by this interface instance.

Field Length: 1–10 alphanumeric characters

Required Field: No

Default Value: No default value

Data Name: ADRT.POSTAL-CDE

COUNTRY — An information-only field for this interface instance. For example, this field could contain the country code associated with a financial institution processed by this interface instance. Country codes are based on the 1993 ISO 3166 standard, *Codes for the Representation of Names of Countries*.

Field Length: 2 alphanumeric characters

Required Field: Yes

Default Value: No default value

Data Name: ADRT.CNTRY-ABBR

AUTO LOGON — A code identifying whether the interface instance automatically sends a logon message as part of its initialization. Valid values are as follows:

Y = Yes, the interface instance sends a logon message as part of its initialization.

N = No, the interface instance does not send a logon message as part of its initialization.

This field is not used in processing, but must contain a valid entry.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: IFCF.SEG0000.PROC-FLG.AUTO-LOGON

UNKNOWN ROUTE CODE — This field is not used in processing.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0000.UNKN-CRD-RTE-CDE

KEY MGMT TYPE — A code identifying the type of key management processing this interface instance can perform. Currently, dynamic key management is only supported for the Remote Banking Standard Interface. Valid values are as follows:

M = Dynamic key management with the BASE24 product as the main processor.
N = No dynamic key management.

The values C (co-network) and S (BASE24 product as the secondary processor) also are valid entries, but are not supported by the BASE24-telebanking product.

The value in this field determines whether VCD screen 4 is displayed. VCD screen 4 is displayed when this field contains the value C, M, or S.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.PROC-FLG.KEY-MGMT-TYP

SAF GROUP — A code that identifies which Store-and-Forward File (SAF) is used by this interface instance. Valid values are 0 through 9999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–4 alphanumeric characters
Required Field: No, if the INTERFACE TYPE field is set to the value VRUT or CSI
Default Value: No default values
Data Name: IFCF.SEG0000.SAF-GRP-ID

MAC TYPE — A code specifying whether selected data elements or the entire message is considered when computing the message authentication code (MAC). Valid values are as follows:

F = Full message authentication
N = No message authentication
S = Selected field message authentication

This field is not used in processing, but must contain a valid entry.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.PROC-FLG.MAC-IND

DESTINATION GROUP — This field is not used in processing.

Field Length: 1–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0000.DEST-GRP-NAM

MAC NMM — A code specifying whether messages to and from this interface instance have message authentication codes (MACs) generated for network management messages other than echo tests. Valid values are as follows:

Y = Yes, generate MACs for network management messages.
N = No, do not generate MACs for network management messages.

This field is not used in processing, but must contain a valid entry.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.PROC-FLG.MAC-NMM-TYP

MEASURE COUNTER NAME — The name of the counter used by the Integrated Endpoint process and the Tandem Measure product to accumulate statistics for this interface instance.

For detailed information on how the Integrated Endpoint process uses Measure counters, refer to the *BASE24 IEP Configuration Manual*.

Field Length: 1–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0000.MEASURE-CNTR-NAM

MAC DATA TYPE — A code specifying the character set in which messages are being transmitted between the endpoint device and this interface instance. Valid values are as follows:

A = ASCII
E = EBCDIC

This field is not used in processing, but must contain a valid entry.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: A
Data Name: IFCF.SEG0000.PROC-FLG.MAC-DATA-TYP

IMP SYMBOLIC NAME — The symbolic name of the Interface Master process that performs station management and dynamic key management for this RBSI-compliant device interface instance.

Field Length: 1–16 alphanumeric characters
Required Field: Yes, if the INTERFACE TYPE field contains a value other than CSI.
Default Value: No default value
Data Name: IFCF.IMP-SYM-NAM

IAS QUEUE — This field is not used in processing.

Field Length: 1–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0000.IAS-QUEUE

PRODUCT INDICATOR TABLE

A series of flags that indicate the BASE24 products supported by this interface instance. The Product Indicator Table (PITABLE) identifies which product indicators can be displayed.

BASE – A code indicating whether this interface instance supports BASE24 products. The valid value is Y (yes).

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: IFCF.SEG0000.PROD-IND

TB – A code indicating whether this interface instance supports the BASE24-telebanking product. Valid values are as follows:

Y = Yes, this interface instance supports the BASE24-telebanking product.
N = No, this interface instance does not support the BASE24-telebanking product.

Note: The BASE24-telebanking product must be supported when the BASE24-billpay product is used.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: IFCF.SEG0000.PROD-IND

Screen 2

VCD screen 2 defines additional processing options associated with an interface instance. It also includes the message class wildcard options used to route messages for this interface instance by the Integrated Endpoint process. VCD screen 2 is shown below, followed by descriptions of its fields.

Note: Many of the fields on this screen are not used by the BASE24-telebanking and BASE24-billpay products. Each field description indicates whether the field is used by the BASE24-telebanking and BASE24-billpay products and whether the field is required. Required fields must contain a valid value even when they are not used during processing.

```

BASE24-CORE VRU CONFIGURATION          LLLL          YY/MM/DD hh:mm 02 OF 45
INTERFACE NAME:                        INTERFACE TYPE:

                                TIMER LIMITS
NETWORK MANAGEMENT:    30 (SEC)      EXTENDED NETWORK:    60 (SEC)
STORE AND FORWARD:    60 (SEC)      WAIT FOR TRAFFIC:    120 (SEC)
OVERLOAD:              30 (SEC)

THRESHOLD MAX OUTSTANDING REQUESTS:    0          MAX TIMEOUTS:    0
STAN UPDATE INTERVAL:    5000          STATION SELECT METHOD: R (ROTARY)
STAN UNIQUE INDICATOR: D (DESTINATION GROUP)
CURRENCY CODE: 840
CURRENCY CONVERSION GROUP:
BALANCE INFO OPTION: 1 (LEDGER BALANCE ONLY)

                                MESSAGE CLASS WILD CARD OPTIONS (Y/N)
SUB FIELD 1: N          SUB FIELD 2: N          SUB FIELD 3: N          SUB FIELD 4: N

RECORD LAST CHANGED:                BY USER:          ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                                F12-HELP

```

TIMER LIMITS

The following five fields contain timer limits. The BASE24-telebanking and BASE24-billpay products use only the limit specified in the NETWORK MANAGEMENT field.

NETWORK MANAGEMENT — The number of seconds that a BASE24 product waits for a response after transmitting a network management message to a remote banking endpoint station. Network management messages include echo tests and dynamic key management messages. Valid values are 0 through 99999.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 30
Data Name: IFCF.SEG0000.TIMER-LMT.NMM

EXTENDED NETWORK — The number of seconds to set the extended network management message timer. Valid values are 0 through 99999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 60
Data Name: IFCF.SEG0000.TIMER-LMT.XNMM

STORE AND FORWARD — The number of seconds the interface waits for an acknowledgment after transmitting a store-and-forward message. Valid values are 0 through 99999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 60
Data Name: IFCF.SEG0000.TIMER-LMT.SAF

WAIT FOR TRAFFIC — The number of seconds the interface waits for traffic on the line to a station before initiating an echo test. Valid values are 0 through 99999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 120
Data Name: IFCF.SEG0000.TIMER-LMT.WFT

OVERLOAD — The number of seconds the interface waits when the number of outstanding requests specified in the THRESHOLD MAX OUTSTANDING REQUESTS field has been reached. Valid values are 0 through 99999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 30
Data Name: IFCF.SEG0000.TIMER-LMT.OVERLOAD

THRESHOLD MAX OUTSTANDING REQUESTS — The maximum number of transactions that can be outbound to this interface instance. Valid values are 0 through 9999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0000.PROC-LMT.THRSHLD-OUTSTND-RQST

MAX TIMEOUTS — The maximum consecutive number of messages to a station that can time out before the interface marks the station down. Network management messages are excluded from this count. Valid values are 0 through 9999.

This field is not used in processing, but must contain a valid entry.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0000.PROC-LMT.MAX-TIMEOUT

STAN UPDATE INTERVAL — This field is not used in processing, but must contain an entry between 0 and 99999.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 5000
Data Name: IFCF.SEG0000.PROC-LMT.STAN-UPDT-INTERVAL

STATION SELECT METHOD — A code indicating the method used for selecting stations in a resource node. Valid values are as follows:

B = Bias
R = Rotary

This field is not used in processing, but must contain a valid entry.

A description of the code entered is displayed immediately to the right of the value in the STATION SELECT METHOD field.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: R
Data Name: IFCF.SEG0000.PROC-FLG.STA-SELECT-METHOD

STAN UNIQUE INDICATOR — This field is not used in processing, but must contain one of the following values:

D = Destination group
I = Interface instance

A description of the code entered is displayed immediately to the right of the value in the STAN UNIQUE INDICATOR field.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: D
Data Name: IFCF.SEG0000.PROC-FLG.STAN-UNIQUE-IND

CURRENCY CODE — A code indicating the currency used by the remote banking endpoint device. Currency codes are based on the 1990 ISO 4217 standard, *Codes for the Representation of Currencies and Funds*.

Field Length: 3 numeric characters
Required Field: Yes
Default Value: Based on value of the LGNT-COUNTRY-ABBR param in the Logical Network Configuration File (LCONF).
Data Name: IFCF.SEG0000.CRNCY-CDE

CURRENCY CONVERSION GROUP — This field identifies the group used to access the appropriate currency conversion rates. It is not used in processing.

Field Length: 1–4 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0000.CC-GRP

BALANCE INFO OPTION — This field is not used in processing, but must contain one of the following values:

- 1 = Ledger balance only
- 2 = Available balance only
- 5 = Ledger and available balances

Note: The value in the CUSTOMER BALANCE INFO field on Institution Definition File (IDF) screen 40 identifies which balances, if any, the institution prefers to have reported to the customer upon completion of a transaction.

A description of the code entered is displayed immediately to the right of the value in the BALANCE INFO OPTION field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 1
Data Name: IFCF.SEG0000.BAL-OPT-ACQ-INFO

MESSAGE CLASS WILD CARD OPTIONS

The following fields indicate whether certain subfields of the message class must be considered before the Integrated Endpoint process routes the message. For more information on configuring message-based routing for the Integrated Endpoint process, refer to the *BASE24 IEP Configuration Manual*.

The message class is one of the elements the Integrated Endpoint process uses for routing messages. The message class is specified in the MESSAGE CLASS field on screen 1 of the Destination File (DEST) as *pptttvv*, where *pp* is the product ID, *tttt* is the message type, and *vv* is the message variant. The message class is divided into four subfields, as shown in the following table:

Subfield	Message Class Information
1	Product ID
2	First two characters of message type

Subfield	Message Class Information
3	Last two characters of message type
4	Message variant

As an example, if the last two characters of the message type do not affect the routing destination, the value in the SUB FIELD 3 field can be set to Y. The other subfields do affect the routing destination. Therefore, the values in the SUB FIELD 1, SUB FIELD 2, and SUB FIELD 4 fields must be set to N.

SUB FIELD 1 — A code indicating whether wildcard values can be used in place of the product ID in the message class. Valid values are as follows:

Y = Yes, wildcard values can be used.
N = No, wildcard values cannot be used.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.MSG-CLAS-WILDCARD-FLG[0]

SUB FIELD 2 — A code indicating whether wildcard values can be used in place of the first two characters of the message type in the message class. Valid values are as follows:

Y = Yes, wildcard values can be used.
N = No, wildcard values cannot be used.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.MSG-CLAS-WILDCARD-FLG[1]

SUB FIELD 3 — A code indicating whether wildcard values can be used in place of the last two characters of the message type in the message class. Valid values are as follows:

Y = Yes, wildcard values can be used.
N = No, wildcard values cannot be used.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.MSG-CLAS-WILDCARD-FLG[2]

SUB FIELD 4 — A code indicating whether wildcard values can be used in place of the message variant in the message class. Valid values are as follows:

Y = Yes, wildcard values can be used.
N = No, wildcard values cannot be used.

Field Length: 1 alphanumeric character
Required Field: Yes
Default Value: N
Data Name: IFCF.SEG0000.MSG-CLAS-WILDCARD-FLG[3]

Screen 4

The BASE24-telebanking and BASE24-billpay products use the fields on VCD screen 4 for dynamic key management. This screen appears only when the KEY MGMT TYPE field on VCD screen 1 contains a valid value other than N.

Three types of keys are displayed on VCD screen 4. These keys are identified by the following abbreviations:

KAM = This key is used to authenticate message data.

KDT = This key is used to encrypt data. This key also is used with a PIN transport key (KPT) to encrypt PINs for transport.

KPT = This key is used to encrypt PINs.

Only the KPT keys are currently used for dynamic key management.

VCD screen 4 is shown below, followed by descriptions of its fields.

Note: Many of the fields on this screen are not used by the BASE24-telebanking and BASE24-billpay products. Each field description indicates whether the field is used by the BASE24-telebanking and BASE24-billpay products and whether the field is required. Required fields must contain a valid value even when they are not used during processing.

```

BASE24-CORE VRU CONFIGURATION          LLLL          YY/MM/DD  hh:mm  04 OF 45
INTERFACE NAME:                        INTERFACE TYPE:

                                LIMITS
                                KPT          KAM          KDT
KEY SYNC ERRORS:                  0
TIMER VALUE:                      0 (MIN)      0 (MIN)      0 (MIN)
TRANSACTIONS:                     0              0              0
ERRORS:                           0              0              0
CONSECUTIVE ERRORS:               0              0              0
SYNC ERRORS:                      0              0

KEY SYNC ERROR ACTION: 0 (EXCHANGE KEYS AND CONTINUE)
KPT CONSECUTIVE ERROR ACTION: 0 (EXCHANGE KEYS AND CONTINUE)
KAM CONSECUTIVE ERROR ACTION: 0 (EXCHANGE KEYS AND CONTINUE)
KDT CONSECUTIVE ERROR ACTION: 0 (EXCHANGE KEYS AND CONTINUE)
NUMBER OF KEYS: 1 (COMBINED)
ORIGINATING ID:                   RECEIVING ID:

RECORD LAST CHANGED:              BY USER: ,
***** BASE24 *****
NEW PAGE:          FILE DESTINATION:          NEW LOGICAL NETWORK ID:
                                F12-HELP

```

LIMITS

The following fields are used to set the dynamic key management parameters for this interface instance. Keys can be changed based on time intervals, transaction activity, the number of errors since the last key change, or the number of consecutive errors. These limits can be used individually or in any combination. At least one PIN transport key (KPT) limit on this screen must be set to a nonzero value for the interface instance using this record to initiate dynamic key management for PINs, unless you are initiating key changes using the KPT NEW command only. For more information on the KPT NEW command, refer to the *BASE24 Remote Banking Transaction Processing Manual* and the *BASE24 Integrated Server Transaction Security Manual*.

The counters and timers for the key are reset when any one of the configured count or time limits is reached, the KPT NEW command is received for the interface instance, or the Interface Master process is initialized. The time limit is also reset when the Interface Master Services object in the process receives an LCONF Warmboot command.

Each limit can be set for one or more of the following keys:

- PIN transport key (KPT)
- Data transport key (KDT)
- Message authentication key (KAM)

The field description for each limit identifies the key or keys for which it can be set.

Note: The BASE24-telebanking and BASE24-billpay products currently do not support dynamic key management for message authentication keys (KAMs) or data transport keys (KDTs).

KEY SYNC ERRORS — The number of sanity check errors allowed before the BASE24 product generates a new key. Sanity check errors can occur when decrypting the PIN block. Valid values are 0 through 9999.

This limit can be set for PIN transport keys (KPTs).

Field Length:	1–4 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG0400.KPT-LMT.KEY-SYNC-ERR

TIMER VALUE — The maximum length of time, in minutes, before a new key should be generated. Valid values are 0 through 99999 minutes.

This limit can be set for PIN transport keys (KPTs), message authentication keys (KAMs), and data transport keys (KDTs). The limits for KAMs and KDTs are not used in processing. However, the fields for all three keys must contain valid entries.

Field Length:	1–5 numeric characters for each limit
Required Field:	Yes
Default Value:	0
Data Names:	IFCF.SEG0400.KPT-LMT.TIMER IFCF.SEG0400.KAM-LMT.TIMER IFCF.SEG0400.KDT-LMT.TIMER

TRANSACTIONS — The maximum number of transactions containing a PIN that can be performed with the current key before it must be changed. Valid values are as follows:

0 = This parameter is not used.
1–99999 = The maximum number of transactions.

This limit can be set for PIN transport keys (KPTs), message authentication keys (KAMs), and data transport keys (KDTs). The limits for KAMs and KDTs are not used in processing. However, the fields for all three keys must contain valid entries.

Field Length:	1–5 numeric characters for each limit
Required Field:	Yes
Default Value:	0
Data Names:	IFCF.SEG0400.KPT-LMT.TXN IFCF.SEG0400.KAM-LMT.TXN IFCF.SEG0400.KDT-LMT.TXN

ERRORS — The maximum number of translation errors that can occur with the current key before it must be changed. Translation errors include both PIN length errors and sanity check errors. Valid values are as follows:

0 = This parameter is not used.
1–9999 = The maximum number of errors.

This limit can be set for PIN transport keys (KPTs), message authentication keys (KAMs), and data transport keys (KDTs). The limits for KAMs and KDTs are not used in processing. However, the fields for all three keys must contain valid entries.

Field Length: 1–4 numeric characters for each limit
Required Field: Yes
Default Value: 0
Data Names: IFCF.SEG0400.KPT-LMT.ERR
IFCF.SEG0400.KAM-LMT.ERR
IFCF.SEG0400.KDT-LMT.ERR

CONSECUTIVE ERRORS — The maximum number of consecutive translation errors that can occur with the current key. When this number is reached, BASE24 products generate a new key. Translation errors include both PIN length errors and sanity check errors. Valid values are as follows:

0 = This parameter is not used.
1–9999 = The maximum number of errors.

This limit can be set for KPTs, KAMs, and KDTs. The limits for KAMs and KDTs are not used in processing. However, the fields for all three keys must contain valid entries.

Changing a key or using it successfully resets the counter associated with this limit.

Field Length: 1–4 numeric characters for each limit
Required Field: Yes
Default Value: 0
Data Names: IFCF.SEG0400.KPT-LMT.ERR-CONS
IFCF.SEG0400.KAM-LMT.ERR-CONS
IFCF.SEG0400.KDT-LMT.ERR-CONS

SYNC ERRORS — The maximum number of key synchronization errors that can occur with the current key before it must be changed.

Key synchronization is comparing the verification value returned from a security module for the current key with the verification value stored in the Interface Security File (ISF) record for the current key. Valid values are as follows:

0 = This parameter is not used.
1–9999 = The maximum number of errors.

This limit can be set for message authentication keys (KAMs). This limit is not used in processing; however, the field must contain a valid entry.

Field Length: 1–4 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0400.KAM-LMT.SYNC-ERR

KEY SYNC ERROR ACTION — A code indicating the action BASE24 products perform when the number of sanity check errors exceeds the limit set in the KEY SYNC ERRORS field for the PIN transport key (KPT). Valid values are as follows:

- 0 = Exchange keys and continue
- 1 = Exchange keys once and shut the interface down if the limit is reached again
- 2 = Shut the interface down
- 3 = Raise exception and wait

This field is not currently used by BASE24 Remote Banking for dynamic key management. The action is always to perform a key change and continue.

A description of the code entered is displayed immediately to the right of the value in the KEY SYNC ERROR ACTION field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0400.KPT-LMT.KEY-SYNC-ERR-ACT

KPT CONSECUTIVE ERROR ACTION — A code indicating the action BASE24 products perform when the number of consecutive PIN translation errors exceeds the limit set in the CONSECUTIVE ERRORS field for the PIN transport key (KPT). Valid values are as follows:

- 0 = Exchange keys and continue
- 1 = Exchange keys once and shut the interface down if the limit is reached again
- 2 = Shut the interface down
- 3 = Raise exception and wait

This field is not currently used by BASE24 Remote Banking for dynamic key management. The action is always to perform a key change and continue.

A description of the code entered is displayed immediately to the right of the value in the KPT CONSECUTIVE ERROR ACTION field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0400.KPT-LMT.ERR-ACT

KAM CONSECUTIVE ERROR ACTION — A code indicating the action BASE24 products perform when the number of consecutive message authentication errors exceeds the limit set in the KEY SYNC ERRORS field for the message authentication key (KAM). Valid values are as follows:

- 0 = Exchange keys and continue
- 1 = Exchange keys once and shut the interface down if the limit is reached again
- 2 = Shut the interface down
- 3 = Raise exception and wait

This field is not used in processing, but must contain a valid entry.

A description of the code entered is displayed immediately to the right of the value in the KAM CONSECUTIVE ERROR ACTION field.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG0400.KAM-LMT.ERR-ACT

KDT CONSECUTIVE ERROR ACTION — A code indicating the action BASE24 products perform when the number of consecutive data translation errors exceeds the limit set in the KEY SYNC ERRORS field for the data transport key (KDT). Valid values are as follows:

- 0 = Exchange keys and continue
- 1 = Exchange keys once and shut the interface down if the limit is reached again
- 2 = Shut the interface down
- 3 = Raise exception and wait

This field is not used in processing, but must contain a valid entry.

A description of the code entered is displayed immediately to the right of the value in the KDT CONSECUTIVE ERROR ACTION field.

Field Length: 1 numeric character
 Required Field: Yes
 Default Value: 0
 Data Name: IFCF.SEG0400.KDT-LMT.ERR-ACT

NUMBER OF KEYS — A code indicating whether the inbound and outbound keys are combined or separate. Valid values are as follows:

- 1 = Combined. The inbound and outbound PIN transport keys (KPTs) are the same, the inbound and outbound message authentication keys (KAMs) are the same, and the inbound and outbound data transport keys (KDTs) are the same.
- 2 = Separate. The inbound and outbound KPTs are different, the inbound and outbound KAMs are different, and the inbound and outbound KDTs are different.

This field must be set to a value of 1 for dynamic key management.

Field Length: 1 numeric character
 Required Field: Yes
 Default Value: 1
 Data Name: IFCF.SEG0400.KEY-CNT

ORIGINATING ID — Indicates the sender of dynamic key management messages.

The values in the RECEIVING ID and ORIGINATING ID fields need to be agreed upon by the sender and receiver. The sender's originating ID is the receiver's receiving ID and the sender's receiving ID is the receiver's originating ID. For example, if you have agreed on the IDs AAAA for the remote banking endpoint and BBBB for the BASE24 transaction processing system, this field would contain the value BBBB (BASE24 system's originating ID) and the RECEIVING ID field would contain the value AAAA. These values do not need to match any specific values in the BASE24 database.

BASE24 products place the originating ID and receiving ID in the dynamic key management messages that they send to an RBSI-compliant device. These IDs can provide the RBSI-compliant device another way of checking that a message has been routed properly. For example, assume you use the IDs AAAA and BBBB described above. A message from the BASE24 system to the RBSI-compliant

device has an originating ID of BBBB and a receiving ID of AAAA. The RBSI-compliant device can check the receiving ID, accepting the message only if it contains a receiving ID of AAAA. The message returned from the RBSI-compliant device has an originating ID of AAAA and a receiving ID of BBBB; however, BASE24 products do not verify these IDs in the messages that they receive from the RBSI-compliant device.

Field Length: 4–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0400.ORIG-ID

RECEIVING ID — Indicates the receiver of dynamic key management messages.

Refer to the ORIGINATING ID field description for an example of how this field is used.

Field Length: 4–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG0400.RCV-ID

Screen 9 Function Keys

The use of three function keys on VCD screen 9 varies from the standard function keys explained in the *BASE24 Base Files Maintenance Manual* and the *BASE24 CRT Access Manual*. The use of these function keys is explained below.

The first column shows the BASE24 keys. The second column describes the functions that can be accomplished with these keys on VCD screen 9.

Key	Description
Shift-F6	First Page — Displays the first page of station entries.
Shift-F7	Previous Page — Displays the previous page of station entries.
Shift-F8	Next Page — Displays the next page of station entries.

Screen 9

VCD screen 9 defines all the stations (up to 90) associated with a Remote Banking Standard Interface instance. This screen can have up to nine pages with 10 stations on each page. VCD screen 9 is shown below, followed by descriptions of its fields.

```

BASE24-CORE VRU CONFIGURATION      LLLL      YY/MM/DD  hh:mm  09 OF 45
INTERFACE NAME:                     INTERFACE TYPE:

                                     STATION NAME      TYPE              MAX OUT
                                     STATION NAME      TYPE              REQUESTS

RECORD LAST CHANGED:                BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
SF6 - FIRST PAGE  SF7 - PREVIOUS PAGE  SF8 - NEXT PAGE

```

STATION NAME — The symbolic name of the station associated with a remote banking endpoint device. The entry in this field must match a symbolic station name in the XPNET environment and be unique within the logical network.

Field Length: 1–16 alphanumeric characters
Occurs: Up to 90 times
Required Field: At least one entry is required if the INTERFACE TYPE field contains a value other than CSI.
Default Value: No default value
Data Name: IST.STA-TBL.STA-NAM

TYPE — A code defining the type of station named in the STATION NAME field on the same line of the table. The type determines whether the Remote Banking Standard Interface can send messages to this station, receive messages from this station, or send and receive messages involving this station. Valid values are as follows:

- 0 = Send and receive
- 1 = Receive with no output
- 2 = Send with no input

Note: Each station entry with a value of 1 in the TYPE field must be followed immediately by a station entry with a value of 2 in the TYPE field.

A description of the code entered is displayed immediately to the right of the value in the TYPE field.

Field Length:	1 numeric character
Occurs:	Up to 90 times
Required Field:	Yes, if the corresponding STATION NAME field contains an entry.
Default Value:	No default value
Data Name:	IST.STA-TBL.STA-TYP

MAX OUT REQUESTS — The maximum number of requests that can be waiting for a response from this station at any time. Valid values are 0 through 9999.

Field Length:	1–4 numeric characters
Occurs:	Up to 90 times
Required Field:	Yes, if the corresponding STATION NAME field contains an entry.
Default Value:	No default value
Data Name:	IST.STA-TBL.MAX-OUTSTND-RQST

Screen 18

VCD screen 18 defines various BASE24-telebanking and BASE24-billpay processing controls associated with an interface instance. VCD screen 18 is shown below, followed by descriptions of its fields.

```
BASE24-CORE VRU CONFIGURATION      LLLL      YY/MM/DD  hh:mm  18 OF 45
INTERFACE NAME:                     INTERFACE TYPE:

                                TELEBANKING INFORMATION
                                TIMER LIMITS
                                AUTH REQUEST:      15
                                MULTIPLE ACCOUNT SELECT: 60
                                QUEUE LIMIT:      5
                                DEFAULT SOURCE CODE:
                                DEFAULT POINT OF SVC DATA CODE: 61050061510C
                                MULTIPLE ACCOUNT SELECT MAX COUNT: 0
                                MAXIMUM COUNTS:
                                LAST TRANSACTION:   SCHEDULED TRANSFERS:   CUSTOMER VENDOR INQ:
                                STATEMENT DOWNLOAD: SCHEDULED PAYMENTS:   CUSTOMER VENDOR MASK:
                                STMT CLOS DOWNLOAD: SCHED TRANSACTIONS:   MASTER VENDOR INQ:
                                HIST INQ PMNT/XFER: ACCOUNT LIST:         BANK LIST INQ:
                                HIST INQ ALL TRANS: MULTIPLE ACCT BAL:   BANK BRANCH LIST INQ:
                                MISCELLANEOUS REQ:

RECORD LAST CHANGED:               BY USER:      ,
***** BASE24 *****
NEW PAGE:      FILE DESTINATION:      NEW LOGICAL NETWORK ID:
                                F12-HELP
```

TELEBANKING INFORMATION

The following fields contain information that is specific to the BASE24-telebanking and BASE24-billpay products.

TIMER LIMITS

The following fields contain timer limits used by this interface instance:

AUTH REQUEST
MULTIPLE ACCOUNT SELECT
QUEUE LIMIT

These fields appear in a column on the screen. However, field descriptions are arranged according to cursor movement (that is, row first instead of column first). Therefore, descriptions for fields in the first column (timer limits) and descriptions for fields in the second column are combined.

APPROVAL CODE LENGTH — The length of approval code required by the remote banking endpoint device or customer service representative (CSR) terminal. Valid values are 2 through 9.

Field Length: 1 numeric character
Required Field: Yes
Default Value: 6
Data Name: IFCF.SEG1400.APPRV-CDE-LGTH

AUTH REQUEST — The number of seconds that the remote banking endpoint device waits for a response from a BASE24 product after transmitting a request for authorization. Valid values are 0 through 99999.

For more information on transaction timers used by the BASE24-telebanking product, refer to the *BASE24 Remote Banking Transaction Processing Manual*.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 15
Data Name: IFCF.SEG1400.TIMER-LMT.AUTH-RQST

LOCAL PIN VERIFICATION — A code indicating whether the remote banking endpoint device can perform local PIN verification. Valid values are as follows:

Y = Yes, local PIN verification is supported.
N = No, local PIN verification is not supported.

Field Length: 1 alphabetic character
Required Field: Yes
Default Value: Y
Data Name: IFCF.SEG1400.LOCAL-PIN-VRFY-ALWD

MULTIPLE ACCOUNT SELECT — The number of seconds a BASE24 product waits for follow-up requests after returning multiple account information to the remote banking endpoint device. Valid values are 0 through 99999 seconds.

For more information on transaction timers used by the BASE24-telebanking product, refer to the ***BASE24 Remote Banking Transaction Processing Manual***.

Field Length: 1–5 numeric characters
Required Field: Yes
Default Value: 60
Data Name: IFCF.SEG1400.TIMER-LMT.MAS

DEFAULT TERMINAL ID — The terminal ID that will be logged to the ITS Transaction Log File (ITLF) for transactions that do not include a terminal ID.

Field Length: 1–16 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG1400.DFLT-TERM-ID

QUEUE LIMIT — The maximum time a message can be queued before it is delivered to the remote banking endpoint device. If the message is queued longer than the time specified in this field, it is not delivered to the endpoint device. This option is designed to circumvent processing when it becomes apparent that sending the message does not give the endpoint device enough time to respond before the BASE24 product times out.

This time limit is used when the BASE24 product is sending a new key and is waiting for an acknowledgment or when the BASE24 product has returned multiple accounts to the endpoint device and is waiting for a follow-up request. Valid values are 0 through 99 seconds.

For more information on transaction timers used by the BASE24-telebanking product, refer to the ***BASE24 Remote Banking Transaction Processing Manual***.

Field Length: 1–2 numeric characters
Required Field: Yes
Default Value: 5
Data Name: IFCF.SEG1400.TIMER-LMT.QUEUE-TIM

DEFAULT ACQUIRER ID — The acquirer ID that will be logged to the ITLF for transactions that do not include an acquirer ID.

Field Length: 1–11 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG1400.DFLT-ACQ-ID-CDE

DEFAULT SOURCE CODE — A code identifying the default transaction source (remote banking endpoint device or customer service representative terminal) for this interface instance. This field is used for billing purposes as well as for researching problems and for collecting interface instance statistics. Valid values include any two-character alphanumeric combination. Valid values reserved for BASE24 products are as follows:

AD = Audio device (for example, an interactive voice response system)
BL = BASE24-billpay Billing application
IB = Inbound customer service representative terminal
PC = Personal computer
SP = Screen phone

Field Length: 2 alphanumeric characters
Required Field: No
Default Value: No default value
Data Name: IFCF.SEG1400.DFLT-SRC-CDE

LOG ID — The log group used to read the Log Configuration File (LCF). Valid values are 0 through 9999.

The log group defined in this field must fall within the range of groups defined in the START RANGE and END RANGE fields on LCF screen 1.

Field Length: 4 numeric characters
Required Field: Yes
Default Value: 0000
Data Name: IFCF.SEG1400.LOG-GRP-ID

DEFAULT POINT OF SVC DATA CODE — The value that is mapped to the internal transaction data (ITD) by the interface instance if the remote banking endpoint device or customer service representative (CSR) terminal does not send a point of service data code in the external message.

The point of service data code contains 12 alphanumeric characters that are defined as follows:

Position	Description
1	Card data input capability
2	Cardholder authentication capability
3	Card capture capability
4	Operating environment
5	Cardholder present
6	Card present
7	Card data input mode
8	Cardholder authentication method
9	Cardholder authentication entity
10	Card data output capability
11	Terminal output capability
12	PIN capture capability

The BASE24-telebanking product performs specific processing based on the values in the fourth and twelfth positions of the point of service data code. Fourth position values used by the BASE24-telebanking product are as follows:

- 1 = Transaction initiated at a CSR terminal.
- 5 = Transaction initiated at a remote banking endpoint device. This is the default value.

Twelfth position values used by the BASE24-telebanking product are as follows:

- C = The PIN cannot be verified locally and must be included in the external message. This is the default value.
- S = The PIN can be verified locally and is not included in the external message.

The BASE24 ISO Host Interface process passes the value in the seventh position to the host in the external message.

The remaining positions are for information only. Refer to the ITS Transaction Log File (ITLF) Point of Service Information Detail screen in section 10 of this manual for the valid values for all positions.

Field Length: 12 alphanumeric characters
Required Field: No
Default Value: 61050061510C
Data Name: IFCF.SEG1400.DFLT-PT-SVC

MULTIPLE ACCOUNT SELECT MAX COUNT — The maximum number of accounts that can be returned to the remote banking endpoint device or customer service representative (CSR) terminal in a single response. Valid values are 0 and 2 through 15.

Field Length: 1–2 numeric characters
 Required Field: Yes
 Default Value: 0
 Data Name: IFCF.SEG1400.MAS-ALWD-CNT

MAXIMUM COUNTS

The following fields contain maximum counts for the number of transaction items that can be returned in each response message for inquiry transactions acquired from this interface instance.

LAST TRANSACTION — The maximum number of transaction items that can be returned in each response message for a last count of transactions inquiry transaction acquired from this interface instance. Valid values are 0 through 15. A value of 0 in this field indicates that last count of transactions inquiry transactions are not supported from this interface instance.

Transaction information returned in a last count of transactions inquiry transaction is retrieved from the Transaction History File (THF).

The value in the LAST TRANSACTION MAX COUNT field on Host Configuration File (HCF) screen 23 controls the maximum number of transactions contained in each response message for a last count of transactions inquiry transaction acquired from a host. For additional information on the HCF, refer to the *BASE24 Base Files Maintenance Manual*.

While this field controls the maximum number of transactions returned in each response message, the MAX HISTORY RECORDS field in the Customer Table (CSTT) indicates the total number of transactions that can be retrieved in a last count of transactions inquiry transaction acquired from an endpoint device. For last count of transactions inquiry transactions acquired from a CSR terminal, there is no maximum limit.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.LAST-TXN

SCHEDULED TRANSFERS — The maximum number of scheduled transfer transaction items that can be returned in each response message for a scheduled transfers list inquiry transaction acquired from this interface instance. Valid values are 0 through 2 for small messages and 0 through 10 for large messages. A value of 0 in this field indicates that scheduled transfers list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Scheduled transfer information returned in a scheduled transfers list inquiry transaction is retrieved from the Future Table (FUTR) or Recurring Table (RCUR).

The SCHEDULED TRANSFER MAX COUNT field on Host Configuration File (HCF) screen 23 controls the maximum number of transactions contained in each response message for a scheduled transfers list inquiry transaction acquired from a host. For additional information on the HCF, refer to the *BASE24 Base Files Maintenance Manual*.

There is no limit to the total number of scheduled transaction items that can be retrieved in a scheduled transfers list inquiry transaction. The customer or CSR can continue to request more items until there are no more applicable rows in the FUTR or RCUR.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.SCHED-XFER-INQ

CUSTOMER VENDOR INQ — The maximum number of customer vendor transaction items that can be returned in each response message for a customer vendor list inquiry transaction acquired from this interface instance. Valid values are 0 through 1 for small messages and 0 through 4 for large messages. A value of 0 in this field indicates that customer vendor list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Customer vendor transaction information returned in a customer vendor inquiry transaction is retrieved from the Customer Vendor Table (CVND), Vendor Table (VNDR), and Vendor Branch Table (VNDB).

There is no limit to the total number of customer vendor transaction items that can be retrieved in a customer vendor list inquiry transaction. The customer or CSR can continue to request more items until there are no more applicable customer vendor rows in the CVND.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length:	2 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG1400.TXN-CNT.CUST-VNDR-INQ

STATEMENT DOWNLOAD — The maximum number of transaction items that can be returned in each response message for a statement download transaction acquired from this interface instance. Valid values are 0 through 3. A value of 0 in this field indicates that statement download transactions are not supported from this interface instance.

Transaction information returned in a statement download transaction is retrieved from the host.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.STMT-DWNLD

SCHEDULED PAYMENTS — The maximum number of scheduled payment transaction items that can be returned in each response message for a scheduled payments list inquiry transaction acquired from this interface instance. Valid values are 0 through 2 for small messages and 0 through 9 for large messages. A value of 0 in this field indicates that scheduled payments list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Scheduled payment transaction information returned in a scheduled payments list inquiry transaction is retrieved from the Future Table (FUTR), Recurring Table (RCUR), and Vendor Table (VNDR).

There is no limit to the total number of scheduled payment transaction items that can be retrieved in a scheduled payments list inquiry transaction. The customer or CSR can continue to request more items until there are no more applicable rows in the FUTR or RCUR.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.SCHED-PMNT-INQ

CUSTOMER VENDOR MASK — The maximum number of customer vendor account masks that can be returned in each response message for a customer vendor mask verify inquiry transaction acquired from this interface instance. Valid values are 0 through 2 for small messages and 0 through 8 for large messages. A value of 0 in this field indicates that customer vendor mask verify inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Customer vendor account mask information returned in a customer vendor mask verify inquiry transaction is retrieved from the Vendor Mask Table (VNDM).

There is no limit to the total number of customer vendor account masks that can be retrieved in a customer vendor mask verify inquiry transaction. The CSR can continue to request more items until there are no more applicable rows in the VNDM.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.CVND-MASK-INQ

STMT CLOS DOWNLOAD — The maximum number of transaction items that can be returned in each response message for a statement closing download transaction acquired from this interface instance. Valid values are 0 through 16. A value of 0 in this field indicates that statement closing download transactions are not supported from this interface instance.

Transaction information returned in a statement download transaction is retrieved from the host.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.STMT-CLOS-DWNLD

SCHED TRANSACTIONS — The maximum number of scheduled transaction items that can be returned in each response message for a scheduled transactions list inquiry transaction acquired from this interface instance. Valid values are 0

through 2 for small messages and 0 through 8 for large messages. A value of 0 in this field indicates that scheduled transactions list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Scheduled transactions information returned in a scheduled transactions list inquiry transaction is retrieved from the Future Table (FUTR), Recurring Table (RCUR), and Vendor Table (VNDR).

There is no limit to the total number of scheduled transaction items that can be retrieved in a scheduled transactions list inquiry transaction. The customer or CSR can continue to request more items until there are no more applicable rows in the FUTR or RCUR.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length:	2 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG1400.TXN-CNT.SCHED-TXN-INQ

MASTER VENDOR INQ — The maximum number of vendors that can be returned in each response message for a master vendor list inquiry transaction acquired from this interface instance. Valid values are 0 through 1 for small messages and 0 through 5 for large messages. A value of 0 in this field indicates that master vendor list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Vendor information returned in a master vendor list inquiry transaction transaction is retrieved from the Vendor Table (VNDR) and Vendor Branch Table (VNDB).

There is no limit to the total number of vendors that can be retrieved in a master vendor list inquiry transaction. The CSR can continue to request more items until there are no more applicable rows in the VNDR.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.MSTR-VNDR-INQ

HIST INQ PMNT/XFER — The maximum number of payment and transfer transaction items that can be returned in each response message for a history inquiry – payments and transfers transaction acquired from this interface instance. Valid values are 0 through 1 for small messages and 0 through 7 for large messages. A value of 0 in this field indicates that history inquiry – payments and transfers transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the ***BASE24 ITS Kernel Configuration Manual***.

Payment and transfer transaction information returned in a history inquiry – payments and transfers transaction is retrieved from the History Table (HIST).

The HIST INQ PMNT/XFER MAX COUNT field on Host Configuration File (HCF) screen 23 controls the maximum number of transactions contained in each response message for a history inquiry – payments and transfers transaction acquired from a host. For additional information on the HCF, refer to the ***BASE24 Base Files Maintenance Manual***.

While this field controls the maximum number of transactions returned in each response message, the MAX HISTORY RECORDS field in the Customer Table (CSTT) indicates the total number of transactions that can be retrieved in a history inquiry – payments and transfers transaction.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.LAST-PMNT-INQ

ACCOUNT LIST — The maximum number of accounts that can be returned in each response message for a customer account list inquiry transaction acquired from this interface instance. Valid values are 0 through 15. A value of 0 in this field indicates that customer account list inquiry transactions are not supported from this interface instance.

Customer account list information returned in an account list inquiry transaction is retrieved from the Customer/Account Relation Table (CACT) and the Customer Table (CSTT).

If the value of this field is less than 5 for the CSR interface record, then the value from this field determines how many customer accounts are displayed on the List All Accounts Response screen when a customer account list inquiry transaction is performed. No more than 5 customer accounts can be displayed on this screen, even if this field contains a value greater than 5.

The ACCOUNT LIST MAX COUNT field on Host Configuration File (HCF) screen 23 controls the maximum number of customer accounts that can be contained in each response message for a customer account list inquiry transaction acquired from a host. For additional information on the HCF, refer to the ***BASE24 Base Files Maintenance Manual***.

There is no limit to the total number of customer accounts that can be listed in a customer account list inquiry transaction. The customer or CSR can continue to request to list accounts until there are no more applicable rows in the CACT or CSTT.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.ACCT-LIST-INQ

BANK LIST INQ — The maximum number of financial institution items that can be returned in each response message for a bank list inquiry transaction acquired from this interface instance. Valid values are 0 through 4 for small messages and 0 through 19 for large messages. A value of 0 in this field indicates that bank list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Financial institution information returned in a bank list inquiry transaction is retrieved from the Bank Table (BANK).

There is no limit to the total number of financial institutions that can be retrieved in a bank list inquiry transaction. The CSR can continue to request more items until there are no more applicable rows in the BANK.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length:	2 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG1400.TXN-CNT.BANK-INQ

HIST INQ ALL TRANS — The maximum number of BASE24-billpay transaction items that can be returned in each response message for a history inquiry – all transactions acquired from this interface instance. Valid values are 0 through 1 for small messages and 0 through 7 for large messages. A value of 0 in this field indicates that history inquiries – all transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

All BASE24-billpay transaction information returned in a history inquiry – all transactions is retrieved from the History Table (HIST).

While this field controls the maximum number of transactions returned in each response message, the MAX HISTORY RECORDS field in the Customer Table (CSTT) indicates the total number of transactions that can be retrieved in a history inquiry – all transactions.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.TXN-HIST-INQ

MULTIPLE ACCT BAL — The maximum number of account balances that can be returned in each response message for a multiple account balance inquiry transaction acquired from this interface instance. Valid values are 0 through 13. A value of 0 in this field indicates that multiple account balance inquiry transactions are not supported from this interface instance.

Account balance information returned in a multiple account balance inquiry transaction is retrieved from the Customer/Account Relation Table (CACT) and the Positive Balance File (PBF).

If the value of this field is less than 3 for the CSR interface record, then the value from this field determines how many accounts are displayed on the Multiple Account Balance Inquiry Response screen when a multiple account balance inquiry transaction is performed. No more than 3 accounts can be displayed on this screen, even if this field contains a value greater than 3.

There is no limit to the total number of account balances that can be displayed in a multiple account balance inquiry transaction. The customer or CSR can continue to request to display account balances until there are no more applicable rows in the CACT.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length: 2 numeric characters
Required Field: Yes
Default Value: 0
Data Name: IFCF.SEG1400.TXN-CNT.MULT-ACCT-BAL-INQ

BANK BRANCH LIST INQ — The maximum number of financial institution branches that can be returned in each response message for a bank branch list inquiry transaction acquired from this interface instance. Valid values are 0 through 4 for small messages and 0 through 16 for large messages. A value of 0 in this field indicates that bank branch list inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Financial institution branch information returned in a bank branch list inquiry transaction is retrieved from the Bank Branch Table (BKBR).

There is no limit to the total number of financial institution branches that can be retrieved in a bank branch list inquiry transaction. The CSR can continue to request more items until there are no more applicable rows in the BKBR.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length:	2 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG1400.TXN-CNT.BKBR-INQ

MISCELLANEOUS REQ — The maximum number of miscellaneous request items that can be returned in each response message for a miscellaneous requests inquiry transaction acquired from this interface instance. Valid values are 0 through 1 for small messages and 0 through 5 for large messages. A value of 0 in this field indicates that miscellaneous requests inquiry transactions are not supported from this interface instance.

A large-memory model toggle set when the Application Network Services object is compiled, determines whether small messages or large messages are used in your system. If the toggle is set, large messages are used. If the toggle is not set, small messages are used. For more information on this toggle and its impact on message size, refer to the *BASE24 ITS Kernel Configuration Manual*.

Miscellaneous request information returned in a miscellaneous requests inquiry transaction is retrieved from the Miscellaneous Request Table (MISC).

There is no limit to the total number of miscellaneous requests that can be retrieved in a miscellaneous requests inquiry transaction. The CSR can continue to request more items until there are no more applicable rows in the MISC.

The value from this field is placed in the Last Transaction Allowed Count field in the Internal Transaction Data (ITD).

Field Length:	2 numeric characters
Required Field:	Yes
Default Value:	0
Data Name:	IFCF.SEG1400.TXN-CNT.MISC-RQST-INQ

Index

A

Account Type Table File (ATT)

- introduction, [2-1](#)
- naming account types, [2-2](#)
- screen 1, [2-3](#)
- usage in CATT, [3-6](#)

Address Table File (ADRT), [16-1](#)

ADRT

- see* Address Table File (ADRT)

ATT

- see* Account Type Table File (ATT)

B

Bank Transaction Advice Table (BKAV), [10-1](#)

Base files and tables, [1-4](#)

BASE24-customer service/fraud control, [1-1](#), [9-3](#)

C

CACT

- see* Customer/Account Relation Table (CACT)

CATT

- see* Customer Allowed Transaction Table (CATT)

Core Product Menu, [1-5](#)

CPIT

- see* Customer/Personal ID Relation Table (CPIT)

CPIT-PRESENT LCONF param, [12-1](#)

CSR

- see* Customer service representative (CSR) screens

CSTT

- see* Customer Table (CSTT)

Customer Allowed Transaction Table (CATT)

- default CATT rows, [3-2](#)
- introduction, [3-1](#)
- screen 1, [3-27](#)
- screen 1 function keys, [3-25](#)

Customer extended memory table, [3-1](#)

Customer ID, definition of, [5-8](#)

Customer Service Interface (CSI), [8-1](#)

Customer service representative (CSR) screens, [4-1](#)

Customer service representative (CSR) terminal

- Interface Security File (ISF), [8-1](#)
- VRU Configuration Data (VCD), [16-1](#)

Customer Table (CSTT)

- default rows, [5-5](#)
- introduction, [5-1](#)
- screen 1, [5-8](#)
- screen 1 function keys, [5-6](#)
- screen 2, [5-22](#)
- screen 2 function keys, [5-18](#)
- screen 3, [5-31](#)
- screen 3 function keys, [5-28](#)
- usage in CATT, [3-2](#)

Customer/Account Relation Table (CACT)

- CSTT screen 2, [5-22](#)
- default rows, [5-5](#)
- introduction, [5-2](#)
- usage in CSTT, [5-1](#)

Customer/Personal ID Relation Table (CPIT)

- default rows, [5-5](#), [12-3](#)
- introduction, [5-4](#)
- usage in CSTT, [5-1](#), [5-31](#)
- usage in PIT, [12-1](#), [12-16](#)

D

DATE-DISPLAY-TYPE LCONF param, [10-8](#)

Default records

- ATT, [2-2](#), [2-4](#)
- PCDF, [13-3](#)

Default rows

- CACT, [5-5](#)
- CATT, [3-2](#)
- CPIT, [5-5](#), [12-3](#)
- CSTT, [5-5](#)
- PIT, [12-3](#)
- TTSC, [15-2](#)

E

EMT warmboot command

- customer extended memory table, [3-1](#)
- institution routing extended memory table, [7-2](#), [13-1](#)
- interface extended memory table, [16-2](#)
- Interface Security File extended memory table, [8-1](#)
- Internal Message Translation File extended memory table, [9-1](#)

Enscribe file record access, [1-6](#)

Extended Memory Table Build utility
 customer extended memory table, [3-1](#)
 institution routing extended memory table, [7-2](#), [13-1](#)
 interface extended memory table, [16-2](#)
 Internal Message Translation File extended memory table, [9-1](#)

F

FCF
 see File Control File (FCF)
File and table access, [1-5](#)
File Control File (FCF)
 introduction, [6-1](#)
 screen 1, [6-2](#)
Fraud Control process, [9-3](#)
Full-file refresh, [1-9](#)
Function keys
 CATT screen 1, [3-25](#)
 CSTT screen 1, [5-6](#)
 CSTT screen 2, [5-18](#)
 CSTT screen 3, [5-28](#)
 ITLF Detail screen, [10-11](#)
 ITLF Summary screen, [10-3](#)
 LCF screen 1, [11-2](#)
 LCF screen 2, [11-5](#)
 PCDF screen 1, [13-30](#)
 PIT screen 1, [12-4](#)
 PIT screen 2, [12-13](#)
 standard, [1-10](#)
 THCF screen 1, [14-2](#)
 THCF screen 2, [14-6](#)
 TTSC screen 1, [15-6](#)
 VCD screen 9, [16-27](#)

H

Help screens, [1-11](#)

I

IFCF
 see ITS Interface Configuration File (IFCF)
IMTF
 see Internal Message Translation File (IMTF)
Institution Routing Configuration File (IRCF)
 introduction, [7-1](#)
 screen 1, [7-3](#)
Institution routing extended memory table
 IRCF, [7-2](#)
 PCDF, [13-1](#)
Interface extended memory table, [16-2](#)
Interface instance, definition of, [16-1](#)
Interface Security File (ISF)
 field naming conventions, [8-3](#)
 introduction, [8-1](#)
 screen 1, [8-4](#)
 screen 2, [8-13](#)
 screen 3, [8-19](#)
 screen 4, [8-24](#)
Interface Security File extended memory table, [8-1](#)
Interface Station Table File (IST), [16-1](#)
Internal Message Translation File (IMTF)
 introduction, [9-1](#)
 screen 1, [9-4](#)
Internal Message Translation File extended memory table, [9-1](#)
IRCF
 see Institution Routing Configuration File (IRCF)
ISF
 see Interface Security File (ISF)
ISO codes
 account type, [2-1](#)
 country, [10-20](#), [12-10](#)
 currency, [9-7](#), [10-17](#), [10-45](#), [10-46](#)
 message functions, [10-29](#)
 message reason codes, [10-30](#)
 point of service information, [10-37](#)
IST
 see Interface Station Table File (IST)
ITLF
 see ITS Transaction Log File (ITLF)
ITS Interface Configuration File (IFCF), [16-1](#)
ITS Transaction Log File (ITLF)
 acquirer and issuer general information, [10-20](#)
 acquirer-dependent data, [10-55](#)
 advice 1-dependent data, [10-57](#)
 advice 2-dependent data, [10-58](#)
 authorization-dependent data, [10-56](#)
 backup account information, [10-44](#)
 BASE24-billpay transaction data, [10-59](#)
 currency conversion fee information, [10-46](#)
 detail screen 1, [10-15](#)
 detail screen 10, [10-54](#)
 detail screen 11, [10-55](#)
 detail screen 12, [10-56](#)
 detail screen 13, [10-57](#)
 detail screen 14, [10-58](#)
 detail screen 15, [10-59](#)
 detail screen 16, [10-63](#)
 detail screen 17, [10-64](#)
 detail screen 2, [10-20](#)
 detail screen 3, [10-25](#)
 detail screen 4, [10-29](#)
 detail screen 5, [10-35](#)
 detail screen 6, [10-37](#)
 detail screen 7, [10-44](#)
 detail screen 8, [10-46](#)
 detail screen 9, [10-51](#)
 detail screen fields, [10-13](#)
 detail screen function keys, [10-11](#)
 external acquirer dependent data, [10-63](#)
 external authorizer dependent data, [10-64](#)
 introduction, [10-1](#)
 issuer advice information, [10-25](#)
 logging destination, [11-3](#)
 logging to, [11-1](#)

ITS Transaction Log File (ITLF) *continued*
 miscellaneous additional information, [10-54](#)
 original transaction data, [10-29](#)
 paging forward or backward, [10-5](#)
 performance timer information, [10-35](#)
 PIN change information, [10-29](#)
 point of service information, [10-37](#)
 reason codes, [10-29](#)
 refresh information, [10-51](#)
 routing information, [10-25](#)
 summary screen, [10-6](#)
 summary screen function keys, [10-3](#)
 summary screen, perusing by account number, [10-10](#)
 summary screen, perusing by customer ID, [10-6](#)
 transaction amounts, [10-46](#)
 transaction identification information, [10-15](#)

K

KPT NEW command, [16-20](#)

L

Large message impacts
 bank branch list inquiry, [16-45](#)
 bank list inquiry, [16-43](#)
 customer vendor list inquiry, [16-37](#)
 customer vendor mask verify inquiry, [16-39](#)
 history inquiry – all transactions, [16-43](#)
 history inquiry – payments and transfers, [16-41](#)
 master vendor list inquiry, [16-40](#)
 miscellaneous requests inquiry, [16-45](#)
 scheduled payments list inquiry, [16-38](#)
 scheduled transactions list inquiry, [16-40](#)
 scheduled transfers list inquiry, [16-36](#)

LCF

see Log Configuration File (LCF)

LCONF warmboot command, ISECEMT, [8-1](#)

Log Configuration File (LCF)

introduction, [11-1](#)
 screen 1, [11-3](#)
 screen 1 function keys, [11-2](#)
 screen 2, [11-6](#)
 screen 2 function keys, [11-5](#)

Logical Network Configuration File (LCONF) params

CPIT-PRESENT, [12-1](#)
 DATE-DISPLAY-TYPE, [10-8](#)

M

Message type field, on ITLF Summary screen, [10-8](#)

P

PCDF

see Processing Code Definition File (PCDF)

Personal Information Table (PIT)

default rows, [12-3](#)
 introduction, [12-1](#)
 screen 1, [12-6](#)
 screen 1 function keys, [12-4](#)
 screen 2, [5-31](#), [12-16](#)
 screen 2 function keys, [12-13](#)

PIT

see Personal Information Table (PIT)

Positive Customer with Accounts Authorization method (PCAA), [5-2](#)

Positive Customer with Balances/History Authorization method (PCBA), [5-2](#), [14-1](#)

Primary account number (PAN), [5-8](#), [12-16](#)

Processing Code Definition File (PCDF)

default records, [13-3](#)
 introduction, [13-1](#)
 screen 1, [13-31](#)
 screen 1 function keys, [13-30](#)

R

RBSI-compliant device, definition of, [xv](#)

Remote banking endpoint device, definition of, [xv](#)

Remote Banking Standard Interface, [8-1](#), [16-1](#)

S

Selection field

on CSTT screen 2, [5-23](#)
 on CSTT screen 3, [5-32](#)
 on ITLF Summary screen, [10-9](#)
 on PIT screen 2, [12-17](#)
 on TTSC screen 1, [15-11](#)

Small message impacts

bank branch list inquiry, [16-45](#)
 bank list inquiry, [16-43](#)
 customer vendor list inquiry, [16-37](#)
 customer vendor mask verify inquiry, [16-39](#)
 history inquiry – all transactions, [16-43](#)
 history inquiry – payments and transfers, [16-41](#)
 master vendor list inquiry, [16-40](#)
 miscellaneous requests inquiry, [16-45](#)
 scheduled payments list inquiry, [16-38](#)
 scheduled transactions list inquiry, [16-40](#)
 scheduled transfers list inquiry, [16-36](#)

SQL table row access, [1-7](#)

SQL tables, full-file refresh, [1-9](#)

T

Table access, [1-5](#)

THCF

see Transaction History Configuration File (THCF)

THF

see Transaction History File (THF)

Transaction History Configuration File (THCF)

- introduction, [14-1](#)
- screen 1, [14-3](#)
- screen 1 function keys, [14-2](#)
- screen 2, [14-7](#)
- screen 2 function keys, [14-6](#)

Transaction History File (THF)

- usage in FCF, [6-1](#)
- usage in THCF, [14-1](#)

Transaction Security object, [8-1](#)

Transaction Type By Source Code Table (TTSC)

- default records, [15-2](#)
- introduction, [15-1](#)
- screen 1, [15-9](#)
- screen 1 function keys, [15-6](#)

TTSC

- see* Transaction Type By Source Code Table (TTSC)

V

VCD

- see* VRU Configuration Data (VCD)

VRU Configuration Data (VCD)

- introduction, [16-1](#)
- screen 1, [16-3](#)
- screen 18, [16-30](#)
- screen 2, [16-12](#)
- screen 4, [16-19](#)
- screen 9, [16-28](#)
- screen 9 function keys, [16-27](#)

Index by Field Name

Note: Unlabeled fields are not included in this index; they appear by subject in the main index.

A

ACCOUNT 1 TYPE

CATT, [3-28](#)
PCDF, [13-32](#)

ACCOUNT 2 TYPE

CATT, [3-29](#)
PCDF, [13-32](#)

ACCOUNT LIST, [16-42](#)

ACCOUNT NUM 1, [10-16](#)

ACCOUNT NUM 2, [10-17](#)

ACCOUNT NUMBER

CSTT screen 2, entry field, [5-24](#)
CSTT screen 2, search field, [5-23](#)
ITLF, [10-8](#)

ACCOUNT NUMBER END RANGE, [14-4](#)

ACCOUNT NUMBER START RANGE, [14-4](#)

ACCOUNT TYPE

ATT, [2-3](#)
CSTT, [5-22](#)
IRCF, [7-4](#)

ACCOUNT TYPE 1, [10-16](#)

ACCOUNT TYPE 2, [10-17](#)

ACCOUNT TYPE NAME, [2-6](#)

ACCT IND, [10-52](#)

ACCT NUM

ITLF Detail screen 6, [10-44](#)
ITLF Summary screen, [10-7](#)

ACCT TYPE, [10-45](#)

ACQ AMT

ITLF Detail screen 8, original transaction amounts, [10-48](#)
ITLF Detail screen 8, transaction amounts, [10-46](#)

ACQ CRNCY CDE, [10-47](#)

ACQ FEE AMT, [10-49](#)

ACQ INST ID CODE, [10-33](#)

ACQUIRER DEPENDENT DATA, [10-55](#)

ACQUIRER INFORMATION, [10-20](#)

ACQUIRER OBJECT, [10-21](#)

ACTION ALLOWED, [5-25](#)

ACTION DATE, [10-62](#)

ADDITIONAL DATA, [10-54](#)

ADDRESS 1

PIT, [12-8](#)
VCD, [16-6](#)

ADDRESS 2

PIT, [12-8](#)
VCD, [16-6](#)

ADDRESS 3, [12-9](#)

ADVICE 1 DEPENDENT DATA, [10-57](#)

ADVICE 1 REQUIRED, [10-25](#)

ADVICE 2 DEPENDENT DATA, [10-58](#)

ADVICE 2 REQUIRED, [10-26](#)

ADVICE REQUIRED, [13-33](#)

ALTERNATE CONTACT, [5-15](#)

AMT, [10-52](#)

AMT TYPE, [10-52](#)

APPROVAL CODE, [10-18](#)

APPROVAL CODE LENGTH, [16-31](#)

ASSIGN

LCF screen 1, [11-4](#)
LCF screen 2, [11-7](#)
THCF screen 1, [14-4](#)
THCF screen 2, [14-8](#)

AUTH AGENT, [10-23](#)

AUTH DEPENDENT DATA, [10-56](#)

AUTH DESTINATION NAME

IRCF screen 1, over floor limit, [7-5](#)
IRCF screen 1, under floor limit, [7-7](#)

AUTH DESTINATION TYPE

IRCF screen 1, over floor limit, [7-6](#)
IRCF screen 1, under floor limit, [7-7](#)

AUTH INDICATOR, [10-27](#)

AUTH LEVEL, [7-4](#)

AUTH METHOD

IRCF screen 1, over floor limit, [7-6](#)
IRCF screen 1, under floor limit, [7-8](#)

AUTH OBJECT, [10-22](#)

AUTH REQUEST, [16-31](#)

AUTHORIZER, [10-23](#)

AUTO LOGON, [16-7](#)

B

BACKUP ACCOUNT INFORMATION, [10-44](#)
BAD PIN COUNT, [5-13](#)
BALANCE INFO OPTION, [16-16](#)
BANK BRANCH LIST INQ, [16-45](#)
BANK LIST INQ, [16-43](#)
BEG DATE, [5-26](#)
BEGIN DATE
 CATT, [3-29](#)
 CSTT, [5-10](#)
BILLPAY BILLING GROUP, [5-15](#)
BILLPAY BILLING TYPE, [5-16](#)
BIRTH DATE, [12-11](#)
BRANCH ID, [5-9](#)

C

CARD CAPTURE CAPABILITY, [10-39](#)
CARD DATA INPUT CAPABILITY, [10-38](#)
CARD DATA INPUT MODE, [10-40](#)
CARD DATA OUTPUT CAPABILITY, [10-42](#)
CARD PRESENT, [10-40](#)
CARD VERIFY STATUS, [10-31](#)
CARDHOLDER AUTHENTICATION
 CAPABILITY, [10-38](#)
CARDHOLDER AUTHENTICATION ENTITY, [10-41](#)
CARDHOLDER AUTHENTICATION
 METHOD, [10-41](#)
CARDHOLDER PRESENT, [10-40](#)
CC FEE IMPACT FLG, [10-49](#)
CHB 2 AMT, [10-48](#)
CHB 2 CRNCY CDE, [10-48](#)
CHB AMT
 ITLF Detail screen 8, original transaction
 amounts, [10-49](#)
 ITLF Detail screen 8, transaction amounts, [10-47](#)
CHB CRNCY CDE, [10-48](#)
CHB TRANSFER AMT, [10-45](#)
CITY, [12-9](#)
CNTRY, [12-10](#)
CODE, [10-31](#)
COMMENT
 LCF, [11-4](#)
 THCF, [14-5](#)
CONSECUTIVE ERRORS, [16-22](#)
COUNTRY, [16-7](#)
CR, [5-26](#)
CRNCY CDE, [10-45](#)

CURRENCY CODE

IMTF, [9-7](#)
ITLF, [10-17](#)
VCD, [16-15](#)

CURRENCY CONVERSION GROUP

IMTF, [9-7](#)
VCD, [16-15](#)

CURRENT INDEX

ISF screen 2, PIN transport keys, inbound, [8-16](#)
ISF screen 2, PIN transport keys, outbound, [8-18](#)
ISF screen 3, message authentication keys,
 inbound, [8-21](#)
ISF screen 3, message authentication keys,
 outbound, [8-23](#)
ISF screen 4, data transport keys, inbound, [8-26](#)
ISF screen 4, data transport keys, outbound, [8-28](#)

CUST INFO, [5-15](#)**CUSTOMER ID**

CSTT screen 1, [5-8](#)
CSTT screen 2, [5-22](#)
CSTT screen 3, [5-31](#)
ITLF Detail screen 1, [10-17](#)
ITLF Summary screen, perusing the ITLF by account
 number, [10-10](#)
ITLF Summary screen, perusing the ITLF by customer
 ID, [10-6](#)

CUSTOMER PROFILE, [3-28](#)**CUSTOMER REFERENCE NUMBER, [10-60](#)****CUSTOMER VENDOR ACCOUNT, [10-61](#)****CUSTOMER VENDOR INQ, [16-37](#)****CUSTOMER VENDOR MASK, [16-38](#)****D****DATA TRANSPORT KEY INFORMATION, [8-24](#)****DATE, [10-8](#)****DB, [5-25](#)****DEFAULT ACCT NUM, [5-14](#)****DEFAULT ACCT TYPE, [5-14](#)****DEFAULT ACQUIRER ID, [16-32](#)****DEFAULT AUTH ACTION**

IRCF screen 1, over floor limit, [7-6](#)
IRCF screen 1, under floor limit, [7-8](#)

DEFAULT AUTH CEILING LIMIT, [7-9](#)**DEFAULT POINT OF SVC DATA CODE, [16-33](#)****DEFAULT SOURCE CODE, [16-33](#)****DEFAULT TERMINAL ID, [16-32](#)****DE-SAF LIMIT, [16-6](#)****DESCR**

PIT screen 1, first other phone, [12-10](#)
PIT screen 1, second other phone, [12-11](#)

DESCRIPTION, [5-26](#)**DESTINATION GROUP, [16-9](#)**

DISCARD NON-FINANCIAL REVERSALSIMTF screen 1, [9-6](#)ITLF Detail screen 4, [10-24](#)**DISCRIMINANT, [10-34](#)****DPC NUMBER, [9-6](#)****E****END**LCF, [11-7](#)THCF, [14-8](#)**END DATE**CATT, [3-29](#)CSTT screen 1, [5-10](#)CSTT screen 2, [5-27](#)**END RANGE, [11-4](#)****ENTRY TIME, [10-35](#)****ERRORS, [16-21](#)****EXCEPTION REASON CODES, [10-31](#)****EXTENDED NETWORK, [16-13](#)****EXTERNAL ACQUIRER DEPENDENT DATA, [10-63](#)****EXTERNAL ACQUIRER TIME, [10-36](#)****EXTERNAL AUTH DEPENDENT DATA, [10-64](#)****EXTERNAL ISSUER TIME, [10-36](#)****EXTRN PIN ENCRYPT TYPE, [8-5](#)****F****FAMILY, [12-7](#)****FIID**CATT, [3-27](#)CSTT screen 1, [5-9](#)CSTT screen 2, [5-24](#)ITLF Detail screen 2, acquirer information, [10-21](#)ITLF Detail screen 2, issuer information, [10-22](#)ITLF Summary screen, [10-7](#)PIT, [12-7](#)THCF, [14-3](#)VCD, [16-5](#)**FILE, [6-2](#)****FILE IND, [10-53](#)****FILE TYPE, [10-53](#)****FLAG**ITLF Detail screen 3, issuer information, advice 1 required, [10-26](#)ITLF Detail screen 3, issuer information, advice 2 required, [10-27](#)**FUNCTION CODE, [10-29](#)****G****GIVEN, [12-7](#)****GOVERNMENT ID, [12-11](#)****GROUP, [6-2](#)****H****HIST INQ ALL TRANS, [16-43](#)****HIST INQ PMNT/XFER, [16-41](#)****HOME PHONE, [12-10](#)****I****IAS QUEUE, [16-10](#)****ID TYP, [12-17](#)****IMP SYMBOLIC NAME, [16-10](#)****IMPACT 1 OBJECT, [10-23](#)****IMPACT 2 OBJECT, [10-23](#)****INBOUND KEYS**ISF screen 2, [8-14](#)ISF screen 3, [8-19](#)ISF screen 4, [8-24](#)**INQ, [5-26](#)****INST CNTRY CODE, [10-20](#)****INST ID CODE**ITLF Detail screen 2, acquirer information, [10-21](#)ITLF Detail screen 2, issuer information, [10-22](#)**INTERFACE DESTINATION, [9-4](#)****INTERFACE NAME**ISF, [8-4](#)VCD, [16-3](#)**INTERFACE TYPE, [16-4](#)****INTERM HDWR KEY, [8-14](#)****INTERM SFTWR KEY, [8-13](#)****INTRN PIN ENCRYPT TYPE, [8-5](#)****ISS AMT**ITLF Detail screen 8, original transaction amounts, [10-49](#)ITLF Detail screen 8, transaction amounts, [10-47](#)**ISS CRNCY CDE, [10-47](#)****ISS FEE AMT, [10-50](#)****ISSUER INFORMATION**ITLF Detail screen 2, [10-22](#)ITLF Detail screen 3, [10-25](#)**K****KAM CONSECUTIVE ERROR ACTION, [16-24](#)****KAM1**ISF screen 3, message authentication keys, inbound, [8-20](#)ISF screen 3, message authentication keys, outbound, [8-22](#)**KAM2**ISF screen 3, message authentication keys, inbound, [8-20](#)ISF screen 3, message authentication keys, outbound, [8-22](#)**KDT CONSECUTIVE ERROR ACTION, [16-24](#)**

KDT1
ISF screen 4, data transport keys, inbound, [8-25](#)
ISF screen 4, data transport keys, outbound, [8-27](#)

KDT2
ISF screen 4, data transport keys, inbound, [8-25](#)
ISF screen 4, data transport keys, outbound, [8-27](#)

KEY COUNTER
ISF screen 2, PIN transport keys, inbound, [8-16](#)
ISF screen 2, PIN transport keys, outbound, [8-18](#)
ISF screen 3, message authentication keys,
inbound, [8-21](#)
ISF screen 3, message authentication keys,
outbound, [8-23](#)
ISF screen 4, data transport keys, inbound, [8-26](#)
ISF screen 4, data transport keys, outbound, [8-28](#)

KEY LENGTH, [8-8](#)

KEY MGMT TYPE, [16-8](#)

KEY SYNC ERROR ACTION, [16-23](#)

KEY SYNC ERRORS, [16-20](#)

KEY TRANSPORT KEY INFORMATION, [8-8](#)

KKT-AM, [8-10](#)

KKT-DT, [8-11](#)

KKT-PT, [8-9](#)

KPT CONSECUTIVE ERROR ACTION, [16-23](#)

KPT1
ISF screen 2, PIN transport keys, inbound, [8-15](#)
ISF screen 2, PIN transport keys, outbound, [8-17](#)

KPT2
ISF screen 2, PIN transport keys, inbound, [8-15](#)
ISF screen 2, PIN transport keys, outbound, [8-17](#)

L

LANGUAGE IND, [12-12](#)

LAST RESET DATE, [5-13](#)

LAST TRANSACTION, [16-35](#)

LAST UPDATE, [5-16](#)
CSTT screen 1, packet status, [5-16](#)
CSTT screen 1, PIN verification digits, [5-12](#)
CSTT screen 1, verification status, [5-11](#)

LGNT
ITLF Detail screen 2, acquirer information, [10-21](#)
ITLF Detail screen 2, issuer information, [10-22](#)
ITLF Summary screen, [10-7](#)

LGNT AMT
ITLF Detail screen 8, original transaction
amounts, [10-49](#)
ITLF Detail screen 8, transaction amounts, [10-47](#)

LGNT CRNCY CDE, [10-47](#)

LIMITS, [16-20](#)

LOCAL PIN VERIFICATION, [16-31](#)

LOCAL TXN DAT/TIM, [10-33](#)

LOG ID
IMTF, [9-7](#)
VCD, [16-33](#)

LOG TIME, [10-36](#)

M

MAC ALGO, [8-7](#)

MAC DATA TYPE, [16-10](#)

MAC ENCRYPT TYPE, [8-8](#)

MAC NMM, [16-9](#)

MAC TYPE, [16-9](#)

MASTER VENDOR INQ, [16-40](#)

MAX HISTORY RECORDS, [5-14](#)

MAX OUT REQUESTS, [16-29](#)

MAX SAF RETRY, [16-6](#)

MAX TIMEOUTS, [16-14](#)

MAXIMUM COUNTS, [16-35](#)

MEASURE COUNTER NAME, [16-10](#)

MESSAGE AUTHENTICATION KEY
INFORMATION, [8-19](#)

MESSAGE CLASS WILD CARD OPTIONS, [16-16](#)

MESSAGE RSN CODE, [10-30](#)

MESSAGE SUBSTATE, [10-30](#)

MESSAGE TYPE
ITLF Detail screen 1, [10-15](#)
ITLF Detail screen 4, [10-32](#)

M/I, [12-8](#)

MINIMUM REQUEST LIMIT, [9-8](#)

MISCELLANEOUS REQ, [16-45](#)

MOTHER'S MAIDEN NAME, [12-12](#)

MULTIPLE ACCOUNT SELECT, [16-31](#)

MULTIPLE ACCOUNT SELECT MAX
COUNT, [16-35](#)

MULTIPLE ACCT BAL, [16-44](#)

N

NAME
ITLF, [10-26](#)
VCD, [16-5](#)

NEGATIVE RSN CODE, [10-30](#)

NETWORK MANAGEMENT, [16-13](#)

NMM ENABLED, [16-7](#)

NUMBER OF KEYS, [16-25](#)

NUMBER OF PAYMENTS TO SKIP, [10-62](#)

NUMBER OF PERIODS, [10-62](#)

O

OBJ NAME, [10-32](#)

OBJECT, [10-26](#)

OBJECT NAME, [11-3](#)

OLD KEY TIMER LIMIT, [8-6](#)

OPERATING ENVIRONMENT, [10-39](#)
ORIGINAL DATA INFO, [10-32](#)
ORIGINAL MESSAGE TYPE, [10-33](#)
ORIGINAL TRANSACTION AMOUNTS, [10-48](#)
ORIGINATING ID, [16-25](#)
ORIGINATOR, [10-18](#)
OTHER PHONE
 PIT screen 1, first other phone, [12-10](#)
 PIT screen 1, second other phone, [12-11](#)
OUTBOUND KEYS
 ISF screen 2, [8-16](#)
 ISF screen 3, [8-21](#)
 ISF screen 4, [8-26](#)
OUTBOUND LIMIT, [9-7](#)
OVER FLOOR LIMIT, [7-5](#)
OVERLOAD, [16-14](#)

P

PACKET STATUS, [5-16](#)
PAN, [12-16](#)
PAYEE, [10-61](#)
PAYMENT DATE, [10-62](#)
PAYMENT HIGH LIMIT, [5-15](#)
PERFORMANCE TIMERS, [10-35](#)
PERIOD TYPE, [10-61](#)
PERSONAL ID
 CSTT, [5-31](#)
 PIT screen 1, [12-6](#)
 PIT screen 2, [12-16](#)
PIN BLOCK FORMAT, [8-5](#)
PIN CAPTURE CAPABILITY, [10-43](#)
PIN CHANGE REQUIRED
 CSTT, [5-13](#)
 ITLF, [10-34](#)
PIN ENCRYPT LEVEL, [8-6](#)
PIN PAD CHARACTER, [8-6](#)
PIN TRANSPORT KEY INFORMATION, [8-13](#)
PIN VERIFICATION DIGITS, [5-12](#)
PIN VERIFICATION KEY INDEX, [5-12](#)
POINT OF SERVICE INFORMATION, [10-37](#)
POSITION, [15-11](#)
POST FLAG, [10-32](#)
POSTAL CODE
 PIT, [12-9](#)
 VCD, [16-7](#)
POSTING DATE, [10-30](#)
PROCESS NAME, [9-5](#)
PROCESSING CODE
 CATT, [3-28](#)
 PCDF, [13-32](#)
PROCESSING OPTIONS, [16-5](#)

PROD ID, [7-3](#)
PRODUCT ID
 ITLF, [10-33](#)
 PCDF, [13-31](#)
PRODUCT INDICATOR TABLE, [16-11](#)
PROFILE, [5-10](#)
PVD NEW, [10-34](#)
PVD OLD, [10-34](#)

Q

QUALIFIER, [5-24](#)
QUEUE LIMIT, [16-32](#)

R

RANGE
 LCF, [11-6](#)
 THCF, [14-7](#)
RECEIVING ID, [16-26](#)
REFRESH FILE INDICATORS, [10-53](#)
REFRESH GROUP, [14-3](#)
REFRESH IMPACT INFO, [10-51](#)
RESP CODE
 ITLF Detail screen 1, [10-19](#)
 ITLF Summary screen, [10-8](#)
RESPONDER, [10-18](#)
ROUTE CODE
 IRCF, [7-4](#)
 PCDF, [13-33](#)
ROUTE PROFILE
 IRCF, [7-3](#)
 PCDF, [13-31](#)
ROUTE TYPE FLAG, [10-28](#)
ROUTING CODE, [10-27](#)
ROUTING FLOOR FLAG, [10-28](#)
ROUTING INFORMATION, [10-27](#)

S

SAF GROUP, [16-8](#)
SCHED TRANSACTIONS, [16-39](#)
SCHEDULED PAYMENTS, [16-38](#)
SCHEDULED TRANSFERS, [16-36](#)
SEL
 LCF, [11-6](#)
 THCF, [14-7](#)
SEQUENCE NUM, [10-17](#)
SERVICE FEE ACCT NUM, [5-17](#)
SERVICE FEE ACCT TYPE, [5-17](#)
SOURCE CODE
 TTSC screen 1, entry field, [15-10](#)
 TTSC screen 1, search field, [15-9](#)

STAN

- ITLF Detail screen 2, [10-23](#)
- ITLF Detail screen 4, [10-33](#)

STAN UNIQUE INDICATOR, [16-15](#)STAN UPDATE INTERVAL, [16-14](#)

START

- LCF, [11-7](#)
- THCF, [14-8](#)

START RANGE, [11-4](#)STATE, [12-9](#)STATEMENT DOWNLOAD, [16-37](#)STATION NAME, [16-28](#)STATION SELECT METHOD, [16-15](#)STATUS, [5-24](#)STMT CLOS DOWNLOAD, [16-39](#)STORE AND FORWARD, [16-13](#)SUB FIELD 1, [16-17](#)SUB FIELD 2, [16-17](#)SUB FIELD 3, [16-17](#)SUB FIELD 4, [16-18](#)SYNC ERRORS, [16-22](#)

T

TELEBANKING INFORMATION, [16-30](#)TERMINAL ID, [10-21](#)TERMINAL OUTPUT CAPABILITY, [10-42](#)THRESHOLD MAX OUTSTANDING
REQUESTS, [16-14](#)

TIMER LIMITS

- VCD screen 18, [16-30](#)
- VCD screen 2, [16-12](#)

TIMER VALUE, [16-21](#)TITLE, [12-8](#)TRANSACTION ALLOWED, [13-33](#)TRANSACTION AMOUNTS, [10-46](#)

TRANSACTION CODE

- CATT, [3-28](#)
- PCDF, [13-32](#)

TRANSACTION DESCRIPTION

- ITLF, [10-8](#)
- PCDF, [13-34](#)
- TTSC, [15-10](#)

TRANSACTION SOURCE, [10-60](#)

TRANSACTION TYPE

- TTSC screen 1, entry field, [15-10](#)
- TTSC screen 1, search field, [15-9](#)

TRANSACTIONS, [16-21](#)TRANSFER AMT, [10-45](#)TXN AMOUNT, [10-17](#)TXN AMT, [10-49](#)

TXN DATE

- ITLF Detail screen 1, [10-16](#)
- ITLF Summary screen, [10-8](#)

TXN DESCRIPTION, [10-15](#)

TXN TIME

- ITLF Detail screen 1, [10-16](#)
- ITLF Summary screen, [10-9](#)

TYPE

- CSTT screen 1, [5-10](#)
- CSTT screen 2, [5-23](#)
- VCD, [16-29](#)

U

UNDER FLOOR LIMIT, [7-7](#)UNKNOWN ROUTE CODE, [16-8](#)

V

VARIANT

- ISF screen 1, key transport keys, KKT-AM, [8-10](#)
- ISF screen 1, key transport keys, KKT-DT, [8-11](#)
- ISF screen 1, key transport keys, KKT-PT, [8-9](#)

VENDOR NAME, [10-60](#)VERIFY STATUS, [5-11](#)VERSION INDICATOR, [6-3](#)

VVK

- ISF screen 1, key transport keys, KKT-AM, [8-10](#)
- ISF screen 1, key transport keys, KKT-DT, [8-11](#)
- ISF screen 1, key transport keys, KKT-PT, [8-9](#)
- ISF screen 2, [8-14](#)

VVK1

- ISF screen 2, PIN transport keys, inbound, [8-15](#)
- ISF screen 2, PIN transport keys, outbound, [8-17](#)
- ISF screen 3, message authentication keys,
inbound, [8-20](#)
- ISF screen 3, message authentication keys,
outbound, [8-22](#)
- ISF screen 4, data transport keys, inbound, [8-25](#)
- ISF screen 4, data transport keys, outbound, [8-27](#)

VVK2

- ISF screen 2, PIN transport keys, inbound, [8-15](#)
- ISF screen 2, PIN transport keys, outbound, [8-17](#)
- ISF screen 3, message authentication keys,
inbound, [8-20](#)
- ISF screen 3, message authentication keys,
outbound, [8-22](#)
- ISF screen 4, data transport keys, inbound, [8-25](#)
- ISF screen 4, data transport keys, outbound, [8-27](#)

W

WAIT FOR TRAFFIC, [16-13](#)WORK PHONE, [12-10](#)

Index by Data and Column Name

A

ACCT, [5-24](#)
ACCT_QUAL, [5-24](#)
ACCT_TYP, [5-23](#)
ACT_ALWD_CR, [5-26](#)
ACT_ALWD_DB, [5-26](#)
ACT_ALWD_INQ, [5-26](#)
ADDR1, [16-6](#)
ADDR2, [16-6](#)
ADVC-REQ, [13-34](#)
ALT_CONTACT, [5-15](#)
ALTKEY.ACCT-TYP-NAM, [2-6](#)
ALTKEY.OBJ-ID, [16-4](#)
APPRV-CDE-LGTH, [16-31](#)
AUTH-LVL, [7-5](#)

B

BAD_PIN_CNT, [5-13](#)
BAL-OPT-ACQ-INFO, [16-16](#)
BEG_DAT
 CACT, [5-27](#)
 CATT, [3-29](#)
 CSTT, [5-10](#)
BP_BILL_GRP, [5-16](#)
BP_BILL_TYP, [5-16](#)
BP_TXN_LMT, [5-15](#)
BRCH_ID, [5-9](#)
BUS-MLF.ALT-KEY1.DISCIM, [10-34](#)
BUS-MLF.ALT-KEY1.PAN, [10-17](#)
BUS-MLF.ALT-KEY2.ISS.FIID, [10-7](#)
BUS-MLF.ALT-KEY2.ISS.LGNT, [10-7](#)
BUS-MLF.ALT-KEY2.PAN, [10-7](#), [10-10](#)
BUS-MLF.ALT-KEY3.ACCT.NUM-BCD, [10-7](#), [10-8](#)
BUS-MLF.ALT-KEY3.ISS.FIID, [10-7](#)
BUS-MLF.ALT-KEY3.ISS.LGNT, [10-7](#)
BUS-MLF.ASCII.ACQ.FIID, [10-21](#)
BUS-MLF.ASCII.ACQ.ID-CDE, [10-21](#)
BUS-MLF.ASCII.ACQ.INST-CNTRY-CDE, [10-20](#)
BUS-MLF.ASCII.ACQ.LGNT, [10-21](#)
BUS-MLF.ASCII.ACT.CDE, [10-8](#), [10-19](#)

BUS-MLF.ASCII.ACT.IND, [10-19](#)
BUS-MLF.ASCII.AUTH.NAM, [10-23](#)
BUS-MLF.ASCII.AUTH.STAN, [10-24](#)
BUS-MLF.ASCII.AUTH-IND.FLG, [10-27](#)
BUS-MLF.ASCII.CAPTR-DAT, [10-30](#)
BUS-MLF.ASCII.ISS.DISCARD-NON-FNCL-RVSL, [10-24](#)
BUS-MLF.ASCII.ISS.FIID, [10-22](#)
BUS-MLF.ASCII.ISS.ID-CDE, [10-22](#)
BUS-MLF.ASCII.ISS.LGNT, [10-22](#)
BUS-MLF.ASCII.LOCAL-TXN.DAT, [10-9](#), [10-16](#)
BUS-MLF.ASCII.LOCAL-TXN.TIM, [10-9](#), [10-16](#)
BUS-MLF.ASCII.MTI, [10-8](#), [10-16](#)
BUS-MLF.ASCII.MTI-ORIG, [10-33](#)
BUS-MLF.ASCII.PROC-CDE, [10-8](#), [10-15](#)
BUS-MLF.ASCII.PT-SVC.CRD-CAPTR-CAP, [10-39](#)
BUS-MLF.ASCII.PT-SVC.CRD-DATA-INPUT-CAP, [10-38](#)
BUS-MLF.ASCII.PT-SVC.CRD-DATA-INPUT-MDE, [10-41](#)
BUS-MLF.ASCII.PT-SVC.CRD-DATA-OUTPUT-CAP, [10-42](#)
BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-CAP, [10-38](#)
BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-ENTITY, [10-42](#)
BUS-MLF.ASCII.PT-SVC.CRDHLDR-AUTH-METHOD, [10-41](#)
BUS-MLF.ASCII.PT-SVC.CRDHLDR-PRSN, [10-40](#)
BUS-MLF.ASCII.PT-SVC.CRD-PRSN, [10-40](#)
BUS-MLF.ASCII.PT-SVC.OPER-ENVIRON, [10-39](#)
BUS-MLF.ASCII.PT-SVC.PIN-CAPTR-CAP, [10-43](#)
BUS-MLF.ASCII.PT-SVC.TERM-OUTPUT-CAP, [10-42](#)
BUS-MLF.ASCII.RTE-CDE, [10-27](#)
BUS-MLF.ASCII.RTE-FLR.FLG, [10-28](#)
BUS-MLF.ASCII.RTE-TYP.FLG, [10-28](#)
BUS-MLF.ASCII.SEQ-NUM, [10-17](#)
BUS-MLF.ASCII.TERM-ID, [10-21](#)
BUS-MLF.ASCII.TXN-ORIGINATOR.FLG, [10-18](#)
BUS-MLF.ASCII.TXN-RESPONDER.FLG, [10-18](#)

BUS-MLF.BCD.ACCT1.NUM-BCD, [10-16](#)
BUS-MLF.BCD.ACCT1.TYP, [10-16](#)
BUS-MLF.BCD.ACCT2.NUM-BCD, [10-17](#)
BUS-MLF.BCD.ACCT2.TYP, [10-17](#)
BUS-MLF.BCD.ACQ-OBJ-ID, [10-21](#)
BUS-MLF.BCD.AUTH-OBJ-ID, [10-22](#)
BUS-MLF.BCD.MSG-SUBSTATE, [10-30](#)
BUS-MLF.BCD.PROD-ID, [10-33](#)
BUS-MLF.BCD.REFR.FILE.IND, [10-53](#)
BUS-MLF.BCD.REFR.FILE.TYP, [10-53](#)
BUS-MLF.BCD.TIM-ENTRY-TS, [10-35](#)
BUS-MLF.BCD.TIM-LOG-TS, [10-36](#)
BUS-OLF.ACQ-DPNT.FDATA, [10-55](#)
BUS-OLF.ACQ-DPNT-EXTRN.FDATA, [10-63](#), [10-64](#)
BUS-OLF.ACT-DAT, [10-62](#)
BUS-OLF.ADNL-DATA.FDATA, [10-54](#)
BUS-OLF.ADVC1-DPNT.FDATA, [10-57](#)
BUS-OLF.ADVC1-REQ.FLG, [10-26](#)
BUS-OLF.ADVC1-REQ.NAM, [10-26](#)
BUS-OLF.ADVC1-REQ.OBJ-ID, [10-26](#)
BUS-OLF.ADVC2-DPNT.FDATA, [10-58](#)
BUS-OLF.ADVC2-REQ.FLG, [10-27](#)
BUS-OLF.ADVC2-REQ.NAM, [10-26](#)
BUS-OLF.ADVC2-REQ.OBJ-ID, [10-26](#)
BUS-OLF.AMT-FEE-ACQ, [10-49](#)
BUS-OLF.AMT-FEE-ISS, [10-50](#)
BUS-OLF.AMT-TXN.ACQ.AMT, [10-47](#)
BUS-OLF.AMT-TXN.ACQ.CRNCY-CDE, [10-47](#)
BUS-OLF.AMT-TXN.ISS.AMT, [10-47](#)
BUS-OLF.AMT-TXN.ISS.CRNCY-CDE, [10-47](#)
BUS-OLF.AMT-TXN.LGNT.AMT, [10-47](#)
BUS-OLF.AMT-TXN.LGNT.CRNCY-CDE, [10-47](#)
BUS-OLF.AMT-TXN.TXN.AMT, [10-17](#)
BUS-OLF.AMT-TXN.TXN.CRNCY-CDE, [10-17](#)
BUS-OLF.AMT-TXN-CHB.AMT, [10-48](#)
BUS-OLF.AMT-TXN-CHB.CRNCY-CDE, [10-48](#)
BUS-OLF.AMT-TXN-CHB2.AMT, [10-48](#)
BUS-OLF.AMT-TXN-CHB2.CRNCY-CDE, [10-48](#)
BUS-OLF.AMT-TXN-ORIG.ACQ, [10-48](#)
BUS-OLF.AMT-TXN-ORIG.CHB, [10-49](#)
BUS-OLF.AMT-TXN-ORIG.ISS, [10-49](#)
BUS-OLF.AMT-TXN-ORIG.LGNT, [10-49](#)
BUS-OLF.AMT-TXN-ORIG-TXN, [10-49](#)
BUS-OLF.APPRV.CDE, [10-18](#)
BUS-OLF.AUTH-AGENT.ID-CDE, [10-23](#)
BUS-OLF.AUTH-DPNT.FDATA, [10-56](#)
BUS-OLF.BACKUP.ACCT.TYP, [10-45](#)
BUS-OLF.BACKUP.ACCT-NUM, [10-44](#)

BUS-OLF.BACKUP.AMT-XFER, [10-45](#)
BUS-OLF.BACKUP.AMT-XFER-CHB, [10-45](#)
BUS-OLF.BACKUP.CRNCY-CDE, [10-45](#)
BUS-OLF.CC-FEE-IMPACT.FLG, [10-49](#)
BUS-OLF.CUST-REF-NUM, [10-60](#)
BUS-OLF.CVV.STAT, [10-31](#)
BUS-OLF.FNCT.CDE, [10-29](#)
BUS-OLF.IMPACT1-OBJ-ID, [10-23](#)
BUS-OLF.IMPACT2-OBJ-ID, [10-23](#)
BUS-OLF.ORIG-DATA.ACQ-INST-ID-CDE, [10-33](#)
BUS-OLF.ORIG-DATA.LOCAL-TXN-DAT-TIM, [10-33](#)
BUS-OLF.ORIG-DATA.MTI, [10-33](#)
BUS-OLF.ORIG-DATA.STAN, [10-33](#)
BUS-OLF.PAYEE, [10-61](#)
BUS-OLF.PAYEE-DESCR.CUST-ACCT-NUM-VNDR, [10-61](#)
BUS-OLF.PAYEE-DESCR.VNDR-NAM, [10-60](#)
BUS-OLF.PIN-CHNG-REQ.FLG, [10-34](#)
BUS-OLF.PMNT-DAT, [10-62](#)
BUS-OLF.PVD.NEW, [10-34](#)
BUS-OLF.PVD.OLD, [10-34](#)
BUS-OLF.RECUR-TXN-DATA.NUM-PRD, [10-62](#)
BUS-OLF.RECUR-TXN-DATA.PRD-TYP, [10-61](#)
BUS-OLF.RECUR-TXN-DATA.SKIP-NXT-PMNT-IND, [10-62](#)
BUS-OLF.REFR-IMPACT.INFO.ACCT-IND, [10-52](#)
BUS-OLF.REFR-IMPACT.INFO.AMT, [10-52](#)
BUS-OLF.REFR-IMPACT.INFO.AMT-TYP, [10-52](#)
BUS-OLF.RSN-CDE-EXCPT.CDE, [10-31](#)
BUS-OLF.RSN-CDE-EXCPT.OBJ-ID, [10-32](#)
BUS-OLF.RSN-CDE-EXCPT.POST-FLG, [10-32](#)
BUS-OLF.RSN-CDE-MSG, [10-30](#)
BUS-OLF.RSN-CDE-NEG, [10-30](#)
BUS-OLF.SRC-CDE, [10-60](#)
BUS-OLF.TIM-EXTRN-ACQ, [10-36](#)
BUS-OLF.TIM-EXTRN-ISS, [10-36](#)

C

CC-GRP
 IFCF, [16-16](#)
 IMTF, [9-7](#)
CITY, [12-9](#)
CNTRY-ABBR, [16-7](#)
CNTRY_CDE, [12-10](#)
COMMENT
 LCF, [11-4](#)
 THCF, [14-5](#)
CRNCY-CDE, [16-15](#)

CUST_INFO_1, [5-15](#)
 CUST_INFO_2, [5-15](#)
 CUST_INFO_3, [5-15](#)

D

DESCR
 CACT, [5-26](#)
 TTSC, [15-10](#)
 DEST-GRP-NAM, [16-9](#)
 DFLT_ACCT, [5-14](#)
 DFLT_ACCT_TYP, [5-14](#)
 DFLT-ACQ-ID-CDE, [16-33](#)
 DFLT-AUTH-CEIL-LMT, [7-9](#)
 DFLT-PT-SVC, [16-34](#)
 DFLT-SRC-CDE, [16-33](#)
 DFLT-TERM-ID, [16-32](#)
 DISCRD-NON-FNCL-RVSL, [9-6](#)
 DOB, [12-11](#)
 DPC-NUM, [9-6](#)

E

END_DAT
 CACT, [5-27](#)
 CATT, [3-30](#)
 CSTT, [5-11](#)

F

FIID
 CACT, [5-24](#)
 CATT, [3-27](#)
 CSTT, [5-9](#)
 PIT, [12-7](#)

G

GOVT_ID, [12-11](#)

I

IAS-QUEUE, [16-10](#)
 ID_TYP, [12-17](#)
 IMP-SYM-NAM, [16-10](#)
 INBND.KAM[0].KEYX, [8-20](#)
 INBND.KAM[0].VVK, [8-20](#)
 INBND.KAM[1].KEYX, [8-20](#)
 INBND.KAM[1].VVK, [8-21](#)
 INBND.KAM-CNTR, [8-21](#)
 INBND.KAM-IDX, [8-21](#)
 INBND.KDT[0].KEYX, [8-25](#)
 INBND.KDT[0].VVK, [8-25](#)
 INBND.KDT[1].KEYX, [8-25](#)

INBND.KDT[1].VVK, [8-26](#)
 INBND.KDT-CNTR, [8-26](#)
 INBND.KDT-IDX, [8-26](#)
 INBND.KPT[0].KEYX, [8-15](#)
 INBND.KPT[0].VVK, [8-15](#)
 INBND.KPT[1].KEYX, [8-15](#)
 INBND.KPT[1].VVK, [8-15](#)
 INBND.KPT-CNTR, [8-16](#)
 INBND.KPT-IDX, [8-16](#)
 IND, [6-3](#)
 INTERM.KPT-HDWR.KEYX, [8-14](#)
 INTERM.KPT-HDWR.VVK, [8-14](#)
 INTERM.KPT-SFTWR, [8-14](#)

K

KAM-LMT.ERR, [16-22](#)
 KAM-LMT.ERR-ACT, [16-24](#)
 KAM-LMT.ERR-CONS, [16-22](#)
 KAM-LMT.SYNC-ERR, [16-23](#)
 KAM-LMT.TIMER, [16-21](#)
 KAM-LMT.TXN, [16-21](#)
 KDT-LMT.ERR, [16-22](#)
 KDT-LMT.ERR-ACT, [16-25](#)
 KDT-LMT.ERR-CONS, [16-22](#)
 KDT-LMT.TIMER, [16-21](#)
 KDT-LMT.TXN, [16-21](#)
 KEY-CNT, [16-25](#)
 KKT.AM.KEYX, [8-10](#)
 KKT.AM.VVK, [8-10](#)
 KKT.AM-VARIANT, [8-11](#)
 KKT.DT.KEYX, [8-11](#)
 KKT.DT.VVK, [8-11](#)
 KKT.DT-VARIANT, [8-12](#)
 KKT.PT.KEYX, [8-9](#)
 KKT.PT.VVK, [8-9](#)
 KKT.PT-VARIANT, [8-10](#)
 KKT-KEY-LGTH, [8-9](#)
 KPT-LMT.ERR, [16-22](#)
 KPT-LMT.ERR-ACT, [16-24](#)
 KPT-LMT.ERR-CONS, [16-22](#)
 KPT-LMT.KEY-SYNC-ERR, [16-20](#)
 KPT-LMT.KEY-SYNC-ERR-ACT, [16-23](#)
 KPT-LMT.TIMER, [16-21](#)
 KPT-LMT.TXN, [16-21](#)

L

LANG_IND, [12-12](#)

LAST_BP_BILL_TYP_UPDT_TS, [5-17](#)
LAST_PCKT_STAT_UPDT_TS, [5-16](#)
LAST_PVD_UPDT_TS, [5-12](#)
LAST_RESET_DAT_TS, [5-14](#)
LAST_VRFY_FLG_UPDT_TS, [5-12](#)
LOCAL-PIN-VRFY-ALWD, [16-31](#)
LOG-GRP-ID
 IFCF, [16-33](#)
 IMTF, [9-7](#)

M

MAC-ALGO, [8-8](#)
MAC-TYP, [8-8](#)
MAS-ALWD-CNT, [16-35](#)
MAX_HIST_RECS, [5-14](#)
MEASURE-CNTR-NAM, [16-10](#)
MSG-CLAS-WILDCARD-FLG[0], [16-17](#)
MSG-CLAS-WILDCARD-FLG[1], [16-17](#)
MSG-CLAS-WILDCARD-FLG[2], [16-18](#)
MSG-CLAS-WILDCARD-FLG[3], [16-18](#)
MTHR_MDN_NAM, [12-12](#)

N

NAM, [16-5](#)
NAM_FMLY, [12-7](#)
NAM_GIVEN, [12-7](#)
NAM_M_I, [12-8](#)
NAM_TITLE, [12-8](#)

O

OLD-KEY-TIMER-LMT, [8-7](#)
ORIG-ID, [16-26](#)
OUTBND.KAM[0].KEYX, [8-22](#)
OUTBND.KAM[0].VVK, [8-22](#)
OUTBND.KAM[1].KEYX, [8-22](#)
OUTBND.KAM[1].VVK, [8-23](#)
OUTBND.KAM-CNTR, [8-23](#)
OUTBND.KAM-IDX, [8-23](#)
OUTBND.KDT[0].KEYX, [8-27](#)
OUTBND.KDT[0].VVK, [8-27](#)
OUTBND.KDT[1].KEYX, [8-27](#)
OUTBND.KDT[1].VVK, [8-27](#)
OUTBND.KPT[0].KEYX, [8-17](#)
OUTBND.KPT[0].VVK, [8-17](#)
OUTBND.KPT[1].KEYX, [8-17](#)
OUTBND.KPT[1].VVK, [8-17](#)
OUTBND.KPT-CNTR, [8-18](#), [8-28](#)
OUTBND.KPT-IDX, [8-18](#), [8-28](#)

OVER-FLR.AUTH-NAM, [7-5](#)
OVER-FLR.AUTH-OBJ-NAM, [7-6](#)
OVER-FLR.AUTH-TYP-OBJ-NAM, [7-6](#)
OVER-FLR.DFLT-AUTH-ACT, [7-7](#)

P

PAN
 CACT, [5-22](#)
 CPIT, [5-31](#), [12-17](#)
 CSTT, [5-9](#)
PBT, [8-6](#)
PCKT_STAT, [5-16](#)
PHN_HOME, [12-10](#)
PHN_OTHER_1, [12-10](#)
PHN_OTHER_1_DESCR, [12-10](#)
PHN_OTHER_2, [12-11](#)
PHN_OTHER_2_DESCR, [12-11](#)
PHN_WRK, [12-10](#)
PIN_CHNG_REQ, [5-13](#)
PIN-ENCRYPT-LVL, [8-6](#)
PIN-ENCRYPT-TYP-EXTRN, [8-5](#)
PIN-ENCRYPT-TYP-INTRN, [8-5](#)
PINPAD-CHAR, [8-6](#)
POSN, [15-11](#)
POSTAL-CDE, [16-7](#)
POSTAL_CDE, [12-9](#)
PRFL
 CATT, [3-28](#)
 CSTT, [5-10](#)
PRIKEY.ACCT-TYP
 ATT, [2-5](#)
 IRCF, [7-4](#)
PRIKEY.DEST, [9-5](#)
PRIKEY.END-RANGE
 LCF, [11-4](#), [11-7](#)
 THCF, [14-4](#), [14-8](#)
PRIKEY.GRP, [6-3](#)
PRIKEY.INTF-NAM
 IFCF, [16-4](#)
 ISF, [8-4](#)
PRIKEY.OBJ-NAM, [11-3](#)
PRIKEY.PROC-CDE.ACCT1-TYP, [13-32](#)
PRIKEY.PROC-CDE.ACCT2-TYP, [13-33](#)
PRIKEY.PROC-CDE.TXN-CDE, [13-32](#)
PRIKEY.PROD-ID
 IRCF, [7-3](#)
 PCDF, [13-31](#)
PRIKEY.REFR-FIID.FIID, [14-4](#)
PRIKEY.REFR-FIID.REFR-GRP, [14-3](#)
PRIKEY.RTE-CDE, [7-4](#)

PRIKEY.RTE-PRFL
 IRCF, 7-4
 PCDF, 13-32
 PRIKEY.TYP, 6-2
 PROC_CDE, 3-28, 3-29
 PROC-FLG.AUTO-LOGON, 16-8
 PROC-FLG.KEY-MGMT-TYP, 16-8
 PROC-FLG.MAC-DATA-TYP, 16-10
 PROC-FLG.MAC-IND, 16-9
 PROC-FLG.MAC-NMM-TYP, 16-9
 PROC-FLG.NMM-ENABLED, 16-7
 PROC-FLG.STAN-UNIQUE-IND, 16-15
 PROC-FLG.STA-SELECT-METHOD, 16-15
 PROC-LMT.DE-SAF, 16-6
 PROC-LMT.MAX-SAF-RETRY, 16-6
 PROC-LMT.MAX-TIMEOUT, 16-14
 PROC-LMT.STAN-UPDT-INTERVAL, 16-14
 PROC-LMT.THRSHLD-OUTSTND-RQST, 16-14
 PROD-IND, 16-11
 PRO-NAM, 9-5
 PRSNL_ID
 CPIT, 5-32, 12-16
 PIT, 12-6
 PVD, 5-12
 PVK_IDX, 5-12

R

RCV-ID, 16-26
 RTE-CDE, 13-33

S

SAF-GRP-ID, 16-9
 SRC_CDE, 15-10
 STAT, 5-25
 STA-TBL.MAX-OUTSTND-RQST, 16-29
 STA-TBL.STA-NAM, 16-28
 STA-TBL.STA-TYP, 16-29
 ST_CDE, 12-9
 STR_ADDR_1, 12-8
 STR_ADDR_2, 12-8
 STR_ADDR_3, 12-9
 SVC_FEE_ACCT, 5-17
 SVC_FEE_ACCT_TYP, 5-17
 SWI-LGNT, 16-5

T

THF-ASGN, 14-4, 14-8
 TIMER-LMT.AUTH-RQST, 16-31

TIMER-LMT.MAS, 16-32
 TIMER-LMT.MIN-RQST-TIM, 9-8
 TIMER-LMT.NMM, 16-13
 TIMER-LMT.OUTBND-RQST, 9-8
 TIMER-LMT.OVERLOAD, 16-14
 TIMER-LMT.QUEUE-TIM, 16-32
 TIMER-LMT.SAF, 16-13
 TIMER-LMT.WFT, 16-13
 TIMER-LMT.XNMM, 16-13
 TLF-ASGN, 11-4, 11-7
 TXN-ALWD-FLG, 13-33
 TXN-CNT.ACCT-LIST-INQ, 16-42
 TXN-CNT.BANK-INQ, 16-43
 TXN-CNT.BKBR-INQ, 16-45
 TXN-CNT.CUST-VNDR-INQ, 16-37
 TXN-CNT.CVND-MASK-INQ, 16-39
 TXN-CNT.LAST-PMNT-INQ, 16-42
 TXN-CNT.LAST-TXN, 16-36
 TXN-CNT.MISC-RQST-INQ, 16-46
 TXN-CNT.MSTR-VNDR-INQ, 16-41
 TXN-CNT.MULT-ACCT-BAL-INQ, 16-44
 TXN-CNT.SCHED-PMNT-INQ, 16-38
 TXN-CNT.SCHED-TXN-INQ, 16-40
 TXN-CNT.SCHED-XFER-INQ, 16-36
 TXN-CNT.STMT-CLOS-DWNLD, 16-39
 TXN-CNT.STMT-DWNLD, 16-38
 TXN-CNT.TXN-HIST-INQ, 16-44
 TXN-DESCR, 13-34
 TXN_TYP, 15-10
 TYP, 5-10

U

UNDER-FLR.AUTH-NAM, 7-7
 UNDER-FLR.AUTH-OBJ-NAM, 7-8
 UNDER-FLR.AUTH-TYP-OBJ-NAM, 7-8
 UNDER-FLR.DFLT-AUTH-ACT, 7-8
 UNKN-CRD-RTE-CDE, 16-8

V

VRFY_FLG, 5-11

ACI Worldwide Inc.