



BASE24 Remote BankingTM

Standard Interface Message Specifications

© 2000 by ACI Worldwide Inc. All rights reserved.

All information contained in this document is confidential and proprietary to ACI Worldwide Inc. This material is a trade secret and its confidentiality is strictly maintained. Use of any copyright notice does not imply unrestricted or public access to these materials. No part of this document may be photocopied, electronically transferred, modified, or reproduced in any manner without the prior written consent of ACI Worldwide Inc.

ACI, BASE24, BASE24 Remote Banking, BASE24-billpay, and BASE24-telebanking are trademarks or registered trademarks of ACI Worldwide Inc., Transaction Systems Architects, Inc., or their subsidiaries.

Other companies' trademarks, service marks, or registered trademarks and service marks are trademarks, service marks, or registered trademarks and service marks of their respective companies.

Print Record

09/2000, Version 1 (New)

Contents

Preface	vii
Conventions Used in This Manual	xi
1. Payment Messages	1-1
1.1. Schedule Payment – Immediate (9A)	1-1
1.2. Schedule Payment – Future (9B)	1-10
1.3. Schedule Payment – Recurring (9C)	1-18
1.4. Scheduled Payment Update (9H).....	1-27
1.5. Scheduled Payment Delete (9F)	1-35
2. Transfer Messages	2-1
2.1. Transfer – Immediate (40)	2-1
2.2. Schedule Transfer – Future (9D)	2-9
2.3. Schedule Transfer – Recurring (9E)	2-17
2.4. Scheduled Transfer Update (9J)	2-25
2.5. Scheduled Transfer Delete (9G)	2-32
3. Inquiry Messages	3-1
3.1. Available Funds Inquiry (30).....	3-1
3.2. Check Clearance Inquiry (3A).....	3-8
3.3. Last Count of Debit/Credit Transactions Inquiry (3B)	3-17
3.4. Last Count of Account by Source Transactions Inquiry (3C).....	3-26
3.5. Last Count of Check Transactions Inquiry (3D).....	3-35
3.6. Last Count of Debit Transactions Inquiry (3E)	3-44
3.7. Last Count of Credit Transactions Inquiry (3F)	3-53
3.8. Last Count of Account Transfer Transactions Inquiry (3G).....	3-62
3.9. Customer Vendor List Inquiry (3H)	3-71
3.10. Scheduled Payments List Inquiry (3J).....	3-81
3.11. Scheduled Transfers List Inquiry (3K)	3-90
3.12. History Inquiry – Payments and Transfers (3L)	3-99
3.13. History Inquiry – All Transactions (9X)	3-109
3.14. Scheduled Transactions List Inquiry (3M).....	3-119

3.15.	Customer Account List Inquiry (3N)	3-128
3.16.	Multiple Account Balance Inquiry (3P)	3-136
3.17.	Bank List Inquiry (B1)	3-144
3.18.	Bank Branch List Inquiry (B2).....	3-152
3.19.	Statement Download (3R).....	3-160
3.20.	Statement Closing Download (3Q).....	3-169
4.	Customer Management Messages	4-1
4.1.	Customer Add (9K)	4-1
4.2.	Customer Inquiry (9L)	4-12
4.3.	Customer Update (9M).....	4-22
4.4.	Customer Activate (BB)	4-33
4.5.	Customer Deactivate (BC)	4-42
4.6.	Customer Account Add (B5).....	4-52
4.7.	Customer Account Activate (B6)	4-60
4.8.	Customer Account Deactivate (B7).....	4-67
4.9.	Customer Account Delete (B8)	4-75
4.10.	Customer Account Update (B9).....	4-82
4.11.	Customer Verify (BF)	4-89
4.12.	Customer Select (BG)	4-92
5.	Vendor Management Messages	5-1
5.1.	Customer Vendor Add (9N)	5-1
5.2.	Customer Vendor Update (9Q)	5-12
5.3.	Customer Vendor Activate (BD).....	5-23
5.4.	Customer Vendor Deactivate (9P).....	5-33
5.5.	Customer Vendor Mask Verify Inquiry (BE)	5-43
5.6.	Master Vendor List Inquiry (9R).....	5-51
6.	Customer Service Management Messages	6-1
6.1.	Loan Application (9V)	6-1
6.2.	Miscellaneous Request (9W).....	6-14
6.3.	Miscellaneous Requests Inquiry (B4).....	6-22
6.4.	Check Stop Payment Add (A0)	6-30

7. PIN Messages.....	7-1
7.1. PIN Change (90)	7-1
7.2. PIN Verify (91).....	7-8
8. Network Management and Administrative Messages	8-1
8.1. Network Management	8-1
8.2. Administrative Notify.....	8-3

ACI Worldwide Inc.

Preface

The *BASE24 Remote Banking Standard Interface Message Specifications* describes the format of every message that can be used by BASE24 Remote Banking for communicating with RBSI-compliant devices.

The message specifications in this manual are based on the International Organization for Standardization (ISO) 8583-1993 standard.

Audience

This manual is intended for BASE24 Remote Banking customers and software application vendors who are responsible for implementing a device that functions with the BASE24 Remote Banking product.

Prerequisites

The structure and content of the BASE24-telebanking Standard External Message is patterned after the standard external message developed by ISO, which is described in the ISO 8583-1993 standard, *Financial Transaction Card Originated Messages—Interchange Message Specification*. The BASE24-telebanking Standard External Message carries both BASE24-telebanking and BASE24-billpay information.

Because of the similarity between the BASE24 external message and the ISO standard, familiarity with the above document, commonly referred to as “ISO 8583,” is recommended.

Additional Documentation

The BASE24 documentation set is arranged so that each BASE24 manual presents a topic or group of related topics in detail. When one BASE24 manual presents a topic that has already been covered in detail in another BASE24 manual, the topic is summarized and the reader is directed to the other manual for additional information. Information has been arranged in this manner to be more efficient for readers who do not need the additional detail and at the same time provide the source for readers who require the additional information. This manual contains references to the following BASE24 publications:

- The *BASE24 Remote Banking Standard Interface Support Manual* provides additional information on particular message fields as well as valid account type.
- The *BASE24 Remote Banking Transaction Processing Manual* lists and describes the valid action codes that can be returned in response messages.

Software

This manual documents standard processing for the following BASE24 Remote Banking product releases:

- BASE24-billpay release 1.3
- BASE24-telebanking release 1.3

Customer-specific code modifications (that is, CSMs) may result in processing that differs from the material presented in this manual. The customer is responsible for identifying and noting these changes.

Manual Summary

The following is a summary of the contents of this manual.

“Conventions Used in this Manual” follows this preface and describes notation and documentation conventions necessary to understand the information in the manual.

Section 1, “Payment Messages,” provides message layouts for scheduling, changing, and deleting payment transactions.

Section 2, “Transfer Messages,” provides message layouts for entering, scheduling, changing, and deleting transfer transactions.

Section 3, “Inquiry Messages,” provides message layouts for inquiry transactions.

Section 4, “Customer Management Messages,” provides message layouts for managing customer information.

Section 5, “Vendor Management Messages,” provides message layouts for managing vendor information.

Section 6, “Customer Service Management Messages,” provides message layouts for various transactions used by customer service representatives.

Section 7, “PIN Messages,” provides message layouts for verifying and changing personal identification numbers (PINs).

Section 8, “Network Management and Administration Messages,” provides message layouts for network management and administration.

Publication Identification

Two entries appearing at the bottom of each page uniquely identify this BASE24 publication. The publication number (for example, TB-DT100-02 for the ***BASE24 Remote Banking Standard Interface Support Manual***) appears on every page to assist readers in applying updates to the appropriate manual. The publication date (for example, 09/2000 for September, 2000) identifies the last time material on a particular page has been revised. This date can be used to verify that the reader has the most current information and is particularly helpful when dealing with HELP24 to answer operating questions.

The print record, located on the page immediately following the title page, is also helpful when verifying that a manual contains the most current information. an entry is added to the print record each time a *product* publication is modified in any way. Each print record entry includes the date of the change, a unique version number, and the type of change (new, update, reissue, or preliminary). Version 1 is assigned to a *new* manual. Later versions can be updates or reissues, depending on the changes being made. an *update* typically involves changes on a small number of pages throughout the manual. A *reissue* occurs when all pages of the manual are replaced because changes affect a large number of pages. A manual is identified as *preliminary* when it is released to customers on a limited basis, but it has not yet reached final form.

ACI Worldwide Inc.

Conventions Used in This Manual

This section explains how message formats are documented in this manual.

Typical ISO Message Format Table

A portion of a typical ISO message format is shown here followed by a description of table column titles:

Transfer (single, immediate)			Reversal Request MTI=1420		
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 8	M	binary	Flags for fields 1–64.
1	Secondary Bit Map	an 8	O	binary	Flags for fields 65–128..
2	Primary Account Number	n ..19	C	LLnnnn...	Customer ID

Description of Table Column Headings

The following table describes the column headings used throughout the tables in this manual to describe the layouts of ISO messages.

Heading Line 1	
Column 1	Descriptive title of the function that the ISO format supports.
Column 2	Specific description of the function that the ISO format supports. Also includes the Message Type Indicator (MTI) field value that precedes the record described by the format.
Heading Line 2	
Bit #	Bit number of the corresponding ISO data element. This number corresponds to positions 1 through 64 of the primary bit map and positions 65 through 128 of the secondary bit map (if present). (See Table A — Bit Maps in the ISO 8583-1993 standard, <i>Financial Transaction Card Originated Messages—Interchange Message Specification</i> for more information.)
Field Description	Describes the corresponding ISO data element.
ISO Format	Standard ISO format code for the ISO data element. (See the ISO Format Codes Table below for possible format codes.)
ISO Sta	ISO Status. Indicates whether the ISO data element must be present, or is optional or conditional. (See the ISO Field Status Table below for possible status values.)
Format	The specific formatting used in the ISO data element for the Remote Banking Standard Interface. (See the ISO Format Codes Table below for possible format codes.)
Comment	More specific information about how the ISO data element is used for the Remote Banking Standard Interface.

ISO Format Codes Table

The following table explains the notation used to describe the format of ISO fields. This notation is used in the ISO Format and Format columns of the message layout tables.

Field Type Notation	Field Description / Usage
a	Alphabetic characters
n	Numeric digits
p	Pad characters [space]
s	Special characters
x	' ' or '+' for positive amounts, '-' for negative amounts; always associated with a number amount element (e.g. x + n 14 means "prefix ' ' '+' or '-' and 14 digits of amount").
an	Alphabetic and numeric characters
as	Alphabetic and special characters
np	Numeric and pad (space) characters
ns	Numeric and special characters
anp	Alphabetic, numeric and pad [space] characters
ans	Alphabetic, numeric and special characters
ansp	Alphabetic, numeric, special and pad characters (General Text)
integer value	Fixed length field, where the length of the field in bytes is the integer value indicated
..19	Variable length field of a maximum of 19 characters (in this example). These variable length fields always contain two positions prior to the actual data, indicating the number of bytes of actual data. The integer value specified does not account for the two positions indicating the length. The integer value following the two dots can range from 0 to 99.
...104	Variable length field of a maximum of 104 characters (in this example). These variable length fields always contain three positions prior to the actual data, indicating the number of bytes of actual data. The integer value specified does not account for the three positions indicating the length. The integer value following the three dots can range from 0 to 999.
008 + n 8	ISO variable length field (n...999 in this example) that has a length of 8 numeric digits in ISO message
Var -> nnn	Indicates a variable length field up to nnn characters long without a length field at the beginning of the field.
Notes:	- All fixed length 'n' data elements are assumed to be right justified with leading zeros. - All other fixed length data elements are left justified with trailing blanks.

ISO Field Status Table

The following table explains the status values that appear in the ISO Sta column of the message layout tables.

ISO Field Status	Field Description / Usage
M	Mandatory field
ME	Mandatory Echo—the same data as the original message is echoed back. If no data was present in the original message, no data is echoed.
OE	Optional Echo—the same optional data as the original message is echoed back. If no data was present in the original message, no data is echoed.
O	Optional
C	Conditionally Required

ACI Worldwide Inc.

1. Payment Messages

1.1. Schedule Payment – Immediate (9A)

1.1.1. Schedule Payment – Immediate: ISO Request Format

The schedule payment – immediate format requests the scheduling of an immediate payment using the following data:

- A specific vendor): Field 98 contains the payee number assigned by BASE24.
- The amount specified in the Transaction Amount (field 4) and Currency Code (field 49) fields.
- The *from* account specified in field 102.

Schedule Payment – Immediate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ann00	9Ann00 = Schedule payment – immediate. <i>nn</i> = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.

Schedule Payment – Immediate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...30	Vendor-specific payment data. This field is optional for scheduled payments. BASE24-billpay supports a length of 30 bytes for the vendor specific payment data. Third-party bill payment service providers can support other lengths for the data. However, the length of this field cannot exceed 200 bytes.
49	Currency Code	n 3	M	n 3	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains the account type selected by the customer.

1.1.2. Schedule Payment – Immediate: ISO Response Format

Schedule Payment – Immediate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ann00	9Ann00 = Schedule payment – immediate. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8	O	08 + YYYYMM DD	Payment date. This is the business date for the immediate payment. This field is returned in all approved transactions and in a subset of denied transactions.
48	Additional Data, Private	ans...200		ans...30	Additional data. If this field is present in the request, it is echoed in the response.
49	Currency Code	n 3	ME	n 3	
54	Additional Amounts	ans...120	C		Balance information returned if the transaction is approved. See the Account Balance Structure below.

Schedule Payment – Immediate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	This field is returned in all approved transactions and in a subset of denied transactions.
104.1	Customer Account Number with Vendor			an 28	The customer's account number with the vendor.
104.2	Vendor Name			an 32	Vendor name.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, from account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Account Balance Structure The following structure can occur up to 6 times:				
#	Name	ISO Format	Format	Comment
1	Account Type	n 2		ISO account type—Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
2	Amount Type	n 2	01, 02, 03, 04, 05, 16, 17, 20	01 = Amount 1 ledger balance 02 = Amount 1 available balance 03 = Amount owed 04 = Amount due 05 = Available credit 16 = Amount 2 ledger balance 17 = Amount 2 available balance 20 = Amount remaining
3	Currency Code	n 3		

Account Balance Structure The following structure can occur up to 6 times:				
#	Name	ISO Format	Format	Comment
4	Amount	x + n 12		Amount in whole and fractional currency units.

1.1.3. Schedule Payment – Immediate: ISO Reversal Format

Schedule Payment – Immediate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ann00	9Ann00 = Schedule payment – immediate. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
44	Additional Response Data	ans..8	M	08 + YYYYMMDD	Payment date. This is the business date for the immediate payment.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the original response, it should be echoed in the reversal.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			

Schedule Payment – Immediate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	Transaction description. This field is required if it is present in the original response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.1.4. Schedule Payment – Immediate: ISO Reversal Response Format

Schedule Payment – Immediate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ann00	9Ann00 = Schedule payment – immediate. <i>nn</i> = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the reversal request, it is echoed in the reversal response.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Schedule Payment – Immediate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.2. Schedule Payment – Future (9B)

1.2.1. Schedule Payment – Future: ISO Request Format

The schedule payment – future format requests the scheduling of a future payment using the following data:

- A specific vendor: Field 98 contains the payee number assigned by BASE24.
- The amount specified in the Transaction Amount (field 4) and Currency Code (field 49) fields.
- The date the payment is to be made in the Action Date (field 73) field.
- The *from* account specified in field 102.

This payment is a one-time future payment.

Schedule Payment – Future		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Bnn00	9Bnn00 = schedule payment – future nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.

Schedule Payment – Future		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...30	Vendor-specific payment data. This field is optional for scheduled payments. BASE24-billpay supports a length of 30 bytes for the vendor specific payment data. Third-party bill payment service providers can support other lengths for the data. However, the length of this field cannot exceed 200 bytes.
49	Currency Code	n 3	M	n 3	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first payment.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains the account type selected by the customer.

1.2.2. Schedule Payment – Future: ISO Response Format

The schedule payment – future response format is used after a payment is added to the Future Table (FUTR) on the BASE24 system. The customer reference number is returned in field 95. This is a transaction number that uniquely identifies this transaction to BASE24-billpay.

Schedule Payment – Future		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Bnn00	9Bnn00 = schedule payment – future nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8	O	08 + YYYYMM DD	Payment date. This is the business date for the immediate payment. This field is returned in all approved transactions and in a subset of denied transactions.
48	Additional Data, Private	ans...200		ans...30	Additional data. If this field is present in the request, it is echoed in the response.
49	Currency Code	n 3	ME	n 3	

Schedule Payment – Future		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	ME	YYMMDD	The date of the first payment.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	Transaction description. This field is returned in all approved transactions and in a subset of denied transactions.
104.1 Customers Account Number with Vendor				an 28	The customer's account number with the vendor.
104.2 Vendor Name				an 32	Vendor name.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

1.2.3. Schedule Payment – Future: ISO Reversal Format

Schedule Payment – Future		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Bnn00	9Bnn00 = schedule payment – future nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
44	Additional Response Data	ans..8	M	08 + YYYYMMDD	Payment date. This is the business date for the immediate payment.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the original response, it should be echoed in the reversal.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			

Schedule Payment – Future		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first payment.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	Transaction description. This field is required if it is present in the original response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.2.4. Schedule Payment – Future: ISO Reversal Response Format

Schedule Payment – Future		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Bnn00	9Bnn00 = schedule payment – future nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the reversal request, it is echoed in the reversal response.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Schedule Payment – Future		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.3. Schedule Payment – Recurring (9C)

1.3.1. Schedule Payment – Recurring: ISO Request Format

The schedule payment – recurring format requests the scheduling of a recurring payment using the following data:

- A specific vendor (field 98): Field 98 contains the payee number assigned by BASE24.
- The amount specified in the Transaction Amount (field 4) and Currency Code (field 49) fields.
- The period type, number of periods, and skip payment flag in the Recurring Transaction Data (field 62) field.
- The date the first payment is to be made in the Action Date (field 73) field.
- The *from* account specified in field 102.

A recurring payment can be started immediately or can be scheduled to start on a future date.

Schedule Payment – Recurring		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Cnn00	9Cnn00 = schedule payment – recurring. <i>nn</i> = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.

Schedule Payment – Recurring		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...30	Vendor-specific payment data. This field is optional for scheduled payments. BASE24-billpay supports a length of 30 bytes for the vendor specific payment data. Third-party bill payment service providers can support other lengths for the data. However, the length of this field cannot exceed 200 bytes.
49	Currency Code	n 3	M	n 3	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	
62.1 Period Type		a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2 Number of Periods		n 4		n 4	The number of periods.
62.3 Skip Next Payment Flag		n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first payment.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, from account (anp 4). Either field 102 or 123 is required.

Schedule Payment – Recurring		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains the account type selected by the customer.

1.3.2. Schedule Payment – Recurring: ISO Response Format

The schedule payment – recurring response format is used after a payment is added to the Future Table (FUTR) and Recurring Table (RCUR) on the BASE24 system. The customer reference number is returned in field 95. This is a transaction number that uniquely identifies this transaction to BASE24-billpay.

Schedule Payment – Recurring		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Cnn00	9Cnn00 = schedule payment – recurring. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8	O	08 + YYYYMM DD	Payment date. This is the business date for the immediate payment. This field is returned in all approved transactions and in a subset of denied transactions.
48	Additional Data, Private	ans...200		ans...30	Additional data. If this field is present in the request, it is echoed in the response.

Schedule Payment – Recurring		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
49	Currency Code	n 3	ME	n 3	
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	ME	YYMMDD	The date of the first payment.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	Transaction description. This field is returned in all approved transactions and in a subset of denied transactions.
104.1	Customers Account Number with Vendor			an 28	The customer's account number with the vendor.
104.2	Vendor Name			an 32	Vendor name.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

1.3.3. Schedule Payment – Recurring: ISO Reversal Format

Schedule Payment – Recurring		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Cnn00	9Cnn00 = schedule payment – recurring. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
44	Additional Response Data	ans..8	M	08 + YYYYMM DD	Payment date. This is the business date for the immediate payment.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the original response, it should be echoed in the reversal.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			

Schedule Payment – Recurring		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only if it was present in the original response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first payment.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
104	Transaction Description	ans..60		ans..60	Transaction description. This field is required if it is present in the original response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.3.4. Schedule Payment – Recurring: ISO Reversal Response Format

Schedule Payment – Recurring		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Cnn00	9Cnn00 = schedule payment – recurring. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The payment amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...30	Additional data. If this field is present in the reversal request, it is echoed in the reversal response.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Schedule Payment – Recurring		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

1.4. Scheduled Payment Update (9H)

1.4.1. Scheduled Payment Update: ISO Request Format

The scheduled payment update request is used to change a previously scheduled future or recurring payment. Key data returned in a scheduled payment inquiry response is used to identify the scheduled payment to be changed.

Scheduled Payment Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9H0000	9H0000 = scheduled payment update.
4	Transaction Amount	n 12	O	n 12	The payment amount. This field is required only when changing the amount of the payment.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. The value in this field must be set to the value of the key data that was returned in the scheduled payments list inquiry response for the payment that is being changed.
48.1 Customer Reference Number		n 6			
48.2 From Account Number		an 19			

Scheduled Payment Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.3	From Account Type	an 2			
48.4	From Account Type Description	an 6			
48.5	Vendor Specific Data	an 30			
48.6	Reserved	an 1			
49	Currency Code	n 3	O	n 3	Currency code. This field is required only when changing the amount of the payment.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only when changing the period type or the number of periods.
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	O	YYMMDD	Action date. This field is required only when changing the future or next recurring date.
98	Payee	ans 25	O	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.4.2. Scheduled Payment Update: ISO Response Format

Scheduled Payment Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9H0000	9H0000 = scheduled payment update.
4	Transaction Amount	n 12		n 12	The payment amount. If this field is present in the request, it is echoed in the response.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8		08 + YYYYMM DD	This field is returned only if the payment date changed.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. If this field is present in the request, it is echoed in the response.
49	Currency Code	n 3		n 3	Currency code. If this field is present in the request, it is echoed in the response.
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only when changing the period type or the number of periods.

Scheduled Payment Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6		YYMMDD	Action date. This field is required only when changing the future or next recurring date.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.4.3. Scheduled Payment Update: ISO Reversal Format

Scheduled Payment Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9H0000	9H0000 = scheduled payment update.
4	Transaction Amount	n 12	M	n 12	The payment amount. This field must be sent if it was sent in the original request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...30	This field should be echoed from the original response.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Scheduled Payment Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only if it was present in the original response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	Action date. This field is required only if it was present in the original response.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.4.4. Scheduled Payment Update: ISO Reversal Response Format

Scheduled Payment Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9H0000	9H0000 = scheduled payment update.
4	Transaction Amount	n 12		n 12	The payment amount. This field must be sent if it was sent in the original request.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...30	
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.

Scheduled Payment Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.5. Scheduled Payment Delete (9F)

1.5.1. Scheduled Payment Delete: ISO Request Format

The scheduled payment delete request is used to delete a previously scheduled future or recurring payment. Key data returned in a scheduled payment inquiry response is used to identify the scheduled payment to be deleted.

Scheduled Payment Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9F0000	9F0000 = scheduled payment delete.
4	Transaction Amount	n 12	O	n 12	The payment amount. This field is optional in the request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	The value in this field must be set to the value of the key data that was returned in the scheduled payments list inquiry response for the payment that is being deleted.
48.1	Customer Reference Number	n 6			
49	Currency Code	n 3	O	n 3	Currency code. This field is optional in the request.

Scheduled Payment Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	O	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.5.2. Scheduled Payment Delete: ISO Response Format

Scheduled Payment Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9F0000	9F0000 = scheduled payment delete.
4	Transaction Amount	n 12		n 12	The payment amount. If this field is present in the request, it is echoed in the response.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the request, it is echoed in the response.
49	Currency Code	n 3		n 3	Currency code. If this field is present in the request, it is echoed in the response.
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Scheduled Payment Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.

1.5.3. Scheduled Payment Delete: ISO Reversal Format

Scheduled Payment Delete		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9F0000	9F0000 = scheduled payment delete.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...30	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.6 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

Scheduled Payment Delete		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
98	Payee	ans 25	M	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

1.5.4. Scheduled Payment Delete: ISO Reversal Response Format

Scheduled Payment Delete		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9F0000	9F0000 = scheduled payment delete.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...30	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

ACI Worldwide Inc.

2. Transfer Messages

A transfer of funds request can be made immediately or it can be scheduled as a future or recurring event.

2.1. Transfer – Immediate (40)

2.1.1. Transfer – Immediate: ISO Request Format

Transfer – Immediate		Request/Repeat MTI = 1200/1201			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	40nnmm	40nnmm = transfer – immediate. nn, mm = account types. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	Optional for financial requests. Can be used to transport data to a host.
49	Currency Code	n 3	M	n 3	

Transfer – Immediate		Request/Repeat MTI = 1200/1201			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

2.1.2. Transfer – Immediate: ISO Response Format

Transfer – Immediate		Response MTI = 1210			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	40nnmm	40nnmm= transfer – immediate. nn, mm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
30	Original Amounts	n24	C	n 24	Returned if transaction denied.
30.1	Original Transaction Amount	n12		n12	Original transaction amount
30.2	Original Reconciliation Amount	n12		zeros	BASE24 does not use the Reconciliation Amount field.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Optional for financial requests. Can be used to transport data to a host.
49	Currency Code	n 3	ME	n 3	
54	Additional Amounts	ans...120	C		Balance information returned if the transaction is approved. See the Account Balance Structure below.

Transfer – Immediate		Response MTI = 1210			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Account Balance Structure			The following structure can occur up to 6 times:	
#	Name	ISO Format	Format	Comment
1	Account Type	n 2		ISO account type—Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
2	Amount Type	n 2	01, 02, 03, 04, 05, 16, 17, 20	01 = Amount 1 ledger balance 02 = Amount 1 available balance 03 = Amount owed 04 = Amount due 05 = Available credit 16 = Amount 2 ledger balance 17 = Amount 2 available balance 20 = Amount remaining
3	Currency Code	n 3		
4	Amount	x + n 12		Amount in whole and fractional currency units.

2.1.3. Transfer – Immediate: ISO Reversal Format

Transfer – Immediate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	40nnmm	40nnmm= transfer – immediate. nn, mm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			

Transfer – Immediate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.

2.1.4. Transfer – Immediate: ISO Reversal Response Format

Transfer – Immediate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	40nnmm	40nnmm= transfer – immediate. nn,mm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	To account. Either field 103 or 123 is required.

Transfer – Immediate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.

2.2. Schedule Transfer – Future (9D)

2.2.1. Schedule Transfer – Future: ISO Request Format

Schedule Transfer – Future		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Dnnmm	9Dnnmm = schedule transfer – future. nnnm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
49	Currency Code	n 3	M	n 3	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Schedule Transfer – Future		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first transfer.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

2.2.2. Schedule Transfer – Future: ISO Response Format

Schedule Transfer – Future		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Dnnmm	9Dnnmm = schedule transfer – future. nnnm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8	O	08 + YYYYMM DD	Payment date. This is the business date for the transfer. This field is present if the transaction was approved and the data was available.
49	Currency Code	n 3	ME	n 3	
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	ME	YYMMDD	The date of the first transfer.

Schedule Transfer – Future		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

2.2.3. Schedule Transfer – Future: ISO Reversal Format

Schedule Transfer – Future		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Dnnmm	9Dnnmm = schedule transfer – future. nnnm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
44	Additional Response Data	ans..8	M	08 + YYYYMMDD	Payment date. This is the business date for the transfer.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			

Schedule Transfer – Future		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first transfer.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

2.2.4. Schedule Transfer – Future: ISO Reversal Response Format

Schedule Transfer – Future		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Dnnmm	9Dnnmm = schedule transfer – future. nnnm = account types. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Schedule Transfer – Future		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

2.3. Schedule Transfer – Recurring (9E)

2.3.1. Schedule Transfer – Recurring: ISO Request Format

Schedule Transfer – Recurring		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Enmmm	9Enmmm = schedule transfer – recurring. nnmm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
49	Currency Code	n 3	M	n 3	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Schedule Transfer – Recurring		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62	Recurring Transaction Data	ans...7		ans...7	
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first transfer.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

2.3.2. Schedule Transfer – Recurring: ISO Response Format

Schedule Transfer – Recurring		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ennm	9Ennm = schedule transfer – recurring. nm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	ME	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDDhhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
44	Additional Response Data	ans..8	O	08 + YYYYMMDD	Payment date. This is the business date for the transfer. This field is present if the transaction was approved and the data was available.
49	Currency Code	n 3	ME	n 3	
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7	ME	ans...7	

Schedule Transfer – Recurring		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	ME	YYMMDD	The date of the first transfer.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

2.3.3. Schedule Transfer – Recurring: ISO Reversal Format

Schedule Transfer – Recurring		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ennnmm	9Ennnmm = schedule transfer – recurring. nnmm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
44	Additional Response Data	ans..8	M	08 + YYYYMM DD	Payment date. This is the business date for the transfer.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			

Schedule Transfer – Recurring		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only if it was present in the original response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	The date of the first transfer.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

2.3.4. Schedule Transfer – Recurring: ISO Reversal Response Format

Schedule Transfer – Recurring		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Ennmm	9Ennmm = schedule transfer – recurring. nnmm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12	M	n 12	The transfer amount.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Schedule Transfer – Recurring		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

2.4. Scheduled Transfer Update (9J)

2.4.1. Scheduled Transfer Update: ISO Request Format

The scheduled transfer update request is used to change a previously scheduled future or recurring transfer. The key data returned in a scheduled transfer inquiry response is used to identify the scheduled transfer.

Scheduled Transfer Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9J0000	9J0000 = scheduled transfer update. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
4	Transaction Amount	n 12	O	n 12	The transfer amount. This field is required only when changing the amount of the transfer.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	The value in this field must be set to the value of the key data that was returned in the scheduled transfers list inquiry response for the transfer that is being changed.

Scheduled Transfer Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Customer Reference Number	n 6			
48.2	From Account Number	an 19			
48.3	From Account Type	an 2			
48.4	From Account Type Description	an 6			
48.5	To Account Number	an 19			
48.6	To Account Type	an 2			
48.7	To Account Type Description	an 6			
49	Currency Code	n 3	O	n 3	Currency code. This field is required only when changing the amount of the transfer.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only when changing the period type or the number of periods.
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	O	YYMMDD	Action date. This field is required only when changing the future or next recurring date.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

2.4.2. Scheduled Transfer Update: ISO Response Format

Scheduled Transfer Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9J0000	9J0000 = scheduled transfer update. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
4	Transaction Amount	n 12		n 12	The transfer amount. If this field is present in the request, it is echoed in the response.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
44	Additional Response Data	ans..8		08 + YYYYMM DD	This field is returned only if the transfer date changed.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. If this field is present in the request, it is echoed in the response.
49	Currency Code	n 3		n 3	Currency code. If this field is present in the request, it is echoed in the response.
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only when changing the period type or the number of periods.

Scheduled Transfer Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62.1	Period Type	a 2		aa or a (<i>left justified and padded with a space</i>)	A = Annually MN = Monthly Q = Quarterly S = Semi-annually WK = Weekly 2W = Every two weeks
62.2	Number of Periods	n 4		n 4	The number of periods.
62.3	Skip Next Payment Flag	n 1		n 1	0 = Do not skip payment other = Skip next payment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6		YYMMDD	Action date. This field is required only when changing the future or next recurring date.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

2.4.3. Scheduled Transfer Update: ISO Reversal Format

Scheduled Transfer Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9J0000	9J0000 = scheduled transfer update.
4	Transaction Amount	n 12	M	n 12	The transfer amount. This field must be sent if it was sent in the original request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...30	This field should be echoed from the original response.
49	Currency Code	n 3	M	n 3	Currency code. This field must contain the same data as the original request.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Scheduled Transfer Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
62	Recurring Transaction Data	ans...7		ans...7	Recurring transaction data. This field is required only if it was present in the original response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
73	Action Date	n 6	M	YYMMDD	Action date. This field is required only if it was present in the original response.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

2.4.4. Scheduled Transfer Update: ISO Reversal Response Format

Scheduled Payment Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9J0000	9J0000 = scheduled transfer update.
4	Transaction Amount	n 12		n 12	The transfer amount. This field must be sent if it was sent in the original request.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...30	
49	Currency Code	n 3		n 3	Currency code. This field must contain the same data as the original request.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

2.5. Scheduled Transfer Delete (9G)

2.5.1. Scheduled Transfer Delete: ISO Request Format

The scheduled transfer delete request is used to delete a previously scheduled future or recurring transfer. The key data returned in a scheduled transfer inquiry response is used to identify the scheduled transfer.

Scheduled Transfer Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9G0000	9G0000 = scheduled transfer delete. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
4	Transaction Amount	n 12	O	n 12	The transfer amount. This field is optional in the request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	The value in this field must be set to the value of the key data that was returned in the scheduled transfers list inquiry response for the transfer that is being deleted.
48.1	Customer Reference Number	n 6			

Scheduled Transfer Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
49	Currency Code	n 3	O	n 3	Currency code. This field is optional in the request.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
103	Account ID 2	ans..28		ans..28	This field is optional in the request.

2.5.2. Scheduled Transfer Delete: ISO Response Format

Scheduled Transfer Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9G0000	9G0000 = scheduled transfer delete. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
4	Transaction Amount	n 12		n 12	The transfer amount. If this field is present in the request, it is echoed in the response.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	This field is echoed from the request.
49	Currency Code	n 3		n 3	Currency code. If this field is present in the request, it is echoed in the response.
59	Transport Data	ans...30	ME	ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Scheduled Transfer Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
103	Account ID 2	ans..28		ans..28	If this field is present in the request, it is echoed in the response.

2.5.3. Scheduled Transfer Delete: ISO Reversal Format

Scheduled Transfer Delete		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9G0000	9G0000 = scheduled transfer delete.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...30	This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

Scheduled Transfer Delete		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

2.5.4. Scheduled Transfer Delete: ISO Reversal Response Format

Scheduled Transfer Delete		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9G0000	9G0000 = scheduled transfer delete.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...30	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3. Inquiry Messages

3.1. Available Funds Inquiry (30)

3.1.1. Available Funds Inquiry: ISO Request Format

The available funds inquiry requests balances for any accounts that the customer can access.

Available Funds Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	30nnmm	30nnmm= available funds inquiry. nnmm = account types. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Available Funds Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.1.2.Available Funds Inquiry: ISO Response Format

Available Funds Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	30nnmm	30nnmm = available funds inquiry. nnmm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
54	Additional Amounts	ans...120	C		Balance information returned if the transaction is approved. See Account Balance structure below.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Available Funds Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
103	Account ID 2	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifiers.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Account Balance Structure		The following structure can occur up to 6 times:			
#	Name	ISO Format	Format	Comment	
1	Account Type	n 2		ISO account type—Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.	
2	Amount Type	n 2	01, 02, 03, 04, 05, 16, 17, 20	01 = Amount 1 ledger balance 02 = Amount 1 available balance 03 = Amount owed 04 = Amount due 05 = Available credit 16 = Amount 2 ledger balance 17 = Amount 2 available balance 20 = Amount remaining	
3	Currency Code	n 3			
4	Amount	x + n 12		Amount in whole and fractional currency units.	

3.1.3.Available Funds Inquiry: ISO Reversal Format

Available Funds Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	30nnmm	30nnmm = available funds inquiry. nnmm = account types. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Available Funds Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
103	Account ID 2	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.1.4.Available Funds Inquiry: ISO Reversal Response Format

Available Funds Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	30nnmm	30nnmm = available funds inquiry. nnmm = account types. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDDhhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
103	Account ID 2	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.2. Check Clearance Inquiry (3A)

3.2.1. Check Clearance Inquiry: ISO Request Format

Check Clearance Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Ann00	3Ann00 = check clearance inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	On a continuation request, field 48 data must be echoed from the response.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2 Source Type		an 1		Spaces	This field is set to spaces for specific check clearance inquiries.
48.3 Check Number		an 12			The check number, right-justified and zero-filled

Check Clearance Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.2.2. Check Clearance Inquiry: ISO Response Format

Check Clearance Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Ann00	3Ann00 = check clearance inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.

Check Clearance Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12			The check number, right-justified and zero-filled
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1	Count	n 2		0–15	The number of accounts returned in the information block.
125.2	Currency Code	an 3			
125.3	Reserved	an 1			
125.4	Inquiry Response Structure				See Inquiry Response Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Inquiry Response Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.2.3. Check Clearance Inquiry: ISO Reversal Format

Check Clearance Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Ann00	3Ann00 = check clearance inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			

Check Clearance Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.2.4. Check Clearance Inquiry: ISO Reversal Response Format

Check Clearance Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Ann00	3Ann00 = check clearance inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Check Clearance Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.3. Last Count of Debit/Credit Transactions Inquiry (3B)

3.3.1. Last Count of Debit/Credit Transactions Inquiry: ISO Request Format

The last count of debit/credit transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Debit/Credit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Bnn00	3Bnn00 = last count of debit/credit transactions inquiry. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

Last Count of Debit/Credit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is not required on initial requests except for inquiries by amount, when the amount is required. On a continuation request, field 48 data must be echoed from the response.
48.1	Request/Response Indicator	an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	This field is optional for last count of debit/credit transactions inquiries. If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	This field is optional for last count of debit/credit transactions inquiries. The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.3.2. Last Count of Debit/Credit Transactions Inquiry: ISO Response Format

Last Count of Debit/Credit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Bnn00	3Bnn00 = last count of debit/credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.

Last Count of Debit/Credit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	This field is optional for last count of debit/credit transactions inquiry. If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	This field is optional for last count of debit/credit transactions inquiry. The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1	Count	n 2		0–15	The number of transactions being returned in the information block.
125.2	Currency Code	an 3			
125.3	Reserved	an 1			
125.4	Last Transaction Structure				See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.

Last Count of Debit/Credit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.3.3. Last Count of Debit/Credit Transactions Inquiry: ISO Reversal Format

Last Count of Debit/Credit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Bnn00	3Bnn00 = last count of debit/credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date / Time	n 12			

Last Count of Debit/Credit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.3.4. Last Count of Debit/Credit Transactions Inquiry: ISO Reversal Response Format

Last Count of Debit/Credit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Bnn00	3Bnn00 = last count of debit/credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Debit/Credit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.4. Last Count of Account by Source Transactions Inquiry (3C)

3.4.1. Last Count of Account by Source Transactions Inquiry: ISO Request Format

The last count of account by source transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Account by Source Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Cnn00	3Cnn00 = last count of account by source transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, field 48 data must be echoed from the response.

Last Count of Account by Source Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.4.2. Last Count of Account by Source Transactions Inquiry: ISO Response Format

Last Count of Account by Source Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Cnn00	3Cnn00 = last count of account by source transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.
48.1	Request/Response Indicator	an 1		1	1 = Response

Last Count of Account by Source Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2 Source Type		an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3 Check Number		an 12		Spaces	
48.4 Amount		an 18			The amount to retrieve.
48.5 Start Date		an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6 End Date		an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1 Count		n 2		0–15	The number of transactions being returned in the information block.
125.2 Currency Code		an 3			
125.3 Reserved		an 1			
125.4 Last Transaction Structure					See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.4.3. Last Count of Account by Source Transactions Inquiry: ISO Reversal Format

Last Count of Account by Source Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Cnn00	3Cnn00 = last count of account by source transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date / Time		n 12			

Last Count of Account by Source Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.4.4. Last Count of Account by Source Transactions Inquiry: ISO Reversal Response Format

Last Count of Account by Source Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Cnn00	3Cnn00 = last count of account by source transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Account by Source Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.5. Last Count of Check Transactions Inquiry (3D)

3.5.1. Last Count of Check Transactions Inquiry: ISO Request Format

The last count of check transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Check Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Dnn00	3Dnn00 = last count of check transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

Last Count of Check Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is not required on initial requests except for inquiries by amount, when the amount is required. On a continuation request, field 48 data must be echoed from the response.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2 Source Type		an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3 Check Number		an 12		Spaces	
48.4 Amount		an 18			The amount to retrieve.
48.5 Start Date		an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6 End Date		an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.5.2. Last Count of Check Transactions Inquiry: ISO Response Format

Last Count of Check Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Dnn00	3Dnn00 = last count of check transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.
48.1 Request/Response Indicator		an 1		1	1 = Response

Last Count of Check Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1	Count	n 2		0–15	The number of transactions being returned in the information block.
125.2	Currency Code	an 3			
125.3	Reserved	an 1			
125.4	Last Transaction Structure				See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.5.3. Last Count of Check Transactions Inquiry: ISO Reversal Format

Last Count of Check Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Dnn00	3Dnn00 = last count of check transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date / Time	n 12			

Last Count of Check Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.5.4. Last Count of Check Transactions Inquiry: ISO Reversal Response Format

Last Count of Check Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Dnn00	3Dnn00 = last count of check transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Check Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.6. Last Count of Debit Transactions Inquiry (3E)

3.6.1. Last Count of Debit Transactions Inquiry: ISO Request Format

The last count of debit transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Debit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Enn00	3Enn00 = last count of debit transactions inquiry. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

Last Count of Debit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is not required on initial requests except for inquiries by amount, when the amount is required. On a continuation request, field 48 data must be echoed from the response.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2 Source Type		an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3 Check Number		an 12		Spaces	
48.4 Amount		an 18			The amount to retrieve.
48.5 Start Date		an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6 End Date		an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.6.2. Last Count of Debit Transactions Inquiry: ISO Response Format

Last Count of Debit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Enn00	3Enn00 = last count of debit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.
48.1	Request/Response Indicator	an 1		1	1 = Response

Last Count of Debit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1	Count	n 2		0–15	The number of transactions being returned in the information block.
125.2	Currency Code	an 3			
125.3	Reserved	an 1			
125.4	Last Transaction Structure				See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.6.3. Last Count of Debit Transactions Inquiry: ISO Reversal Format

Last Count of Debit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Enn00	3Enn00 = last count of debit transactions inquiry. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date / Time		n 12			

Last Count of Debit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.6.4. Last Count of Debit Transactions Inquiry: ISO Reversal Response Format

Last Count of Debit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Enn00	3Enn00 = last count of debit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Debit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.7. Last Count of Credit Transactions Inquiry (3F)

3.7.1. Last Count of Credit Transactions Inquiry: ISO Request Format

The last count of credit transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Credit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Fnn00	3Fnn00 = last count of credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

Last Count of Credit Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is not required on initial requests except for inquiries by amount, when the amount is required. On a continuation request, field 48 data must be echoed from the response.
48.1	Request/Response Indicator	an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.7.2. Last Count of Credit Transactions Inquiry: ISO Response Format

Last Count of Credit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Fnn00	3Fnn00 = last count of credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.
48.1 Request/Response Indicator		an 1		1	1 = Response

Last Count of Credit Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1	Count	n 2		0–15	The number of transactions being returned in the information block.
125.2	Currency Code	an 3			
125.3	Reserved	an 1			
125.4	Last Transaction Structure				See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.7.3. Last Count of Credit Transactions Inquiry: ISO Reversal Format

Last Count of Credit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Fnn00	3Fnn00 = last count of credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date / Time		n 12			

Last Count of Credit Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.7.4. Last Count of Credit Transactions Inquiry: ISO Reversal Response Format

Last Count of Credit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Fnn00	3Fnn00 = last count of credit transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2	O	ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Credit Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.8. Last Count of Account Transfer Transactions Inquiry (3G)

3.8.1. Last Count of Account Transfer Transactions Inquiry: ISO Request Format

The last count of account transfer transactions inquiry request returns details of up to the last 15 transactions performed for a particular account.

Last Count of Account Transfer Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Gnn00	3Gnn00 = last count of account transfer transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

Last Count of Account Transfer Transactions Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is not required on initial requests except for inquiries by amount, when the amount is required. On a continuation request, field 48 data must be echoed from the response.
48.1	Request/Response Indicator	an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2	Source Type	an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3	Check Number	an 12		Spaces	
48.4	Amount	an 18			The amount to retrieve.
48.5	Start Date	an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6	End Date	an 8		YYYYMMDD	The end date is not required if the start date is specified.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.8.2. Last Count of Account Transfer Transactions Inquiry: ISO Response Format

Last Count of Account Transfer Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
3	Processing Code	an 6	M	3Gnn00	3Gnn00 = last count of account transfer transactions inquiry. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved. The response message from BASE24 contains additional data that BASE24 needs to process continuation requests. Therefore, the length of this field is greater than 48 bytes in the request message.
48.1	Request/Response Indicator	an 1		1	1 = Response

Last Count of Account Transfer Transactions Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2 Source Type		an 1		A, B, P or T	A = ATM B = Remote banking device P = POS device T = Teller
48.3 Check Number		an 12		Spaces	
48.4 Amount		an 18			The amount to retrieve.
48.5 Start Date		an 8		YYYYMMDD	If the end date is specified, the start date is required.
48.6 End Date		an 8		YYYYMMDD	The end date is not required if the start date is specified.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1 Count		n 2		0–15	The number of transactions being returned in the information block.
125.2 Currency Code		an 3			
125.3 Reserved		an 1			
125.4 Last Transaction Structure					See Last Transaction Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Last Transaction Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		

3.8.3. Last Count of Account Transfer Transactions Inquiry: ISO Reversal Format

Last Count of Account Transfer Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Gnn00	3Gnn00 = last count of account transfer transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date / Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			

Last Count of Account Transfer Transactions Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.8.4. Last Count of Account Transfer Transactions Inquiry: ISO Reversal Response Format

Last Count of Account Transfer Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3Gnn00	3Gnn00 = last count of account transfer transactions inquiry. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field is optional for the reversal phase of this transaction. It can be used to transport data to a host.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2	O	ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.

Last Count of Account Transfer Transactions Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.9. Customer Vendor List Inquiry (3H)

3.9.1. Customer Vendor List Inquiry: ISO Request Format

The customer vendor list inquiry transaction is used to request the list of vendors included on a particular customer's vendor list.

Customer Vendor List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3H0000	3H0000 = customer vendor list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. For the initial request, 48.1 must be set to a value of 0, 48.2 to AC, 48.3 to 0, 48.4 to 000, 48.5 to a space, and 48.6 to blanks. Key data fields will contain BASE24-billpay positioning information. On a continuation request, this data must be echoed from the response.
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0 and 48.7 equals spaces)

Customer Vendor List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Search Direction	an 2		AC	AC = Ascending
48.3	Key Data Type	an 1		0 or 1	0 = Vendor name 1 = Customer vendor number
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data: Reserved	an 30		spaces	Not currently used.
48.7	Key Data (1)	Var -> 192 an 30			Vendor name. Depending on the value in 48.3 (Key data type) either 48.7 or 48.8 and 48.9 is present. If 48.1 is not a space, key data (48.7 or 48.8) must not be spaces.
OR 48.8	Key Data (2)	n 5		n 5	Customer vendor number
48.9	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.9.2. Customer Vendor List Inquiry: ISO Response Format

Customer Vendor List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3H0000	3H0000 = customer vendor list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. Must be returned unaltered in subsequent requests. Key data fields will contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC	AC = Ascending
48.3 Key Data Type		an 1		0 or 1	0 = Vendor name 1 = Customer vendor number
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data: Reserved		an 30		spaces	Not currently used.

Customer Vendor List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.7 Key Data (1)		Var -> 192 an 30			Vendor name. Depending on the value in 48.3 (Key data type) either 48.7 or 48.8 and 48.9 is present. If 48.1 is not a space, key data (48.7 or 48.8) must not be spaces.
OR 48.8 Key Data (2)		n 5		n 5	Customer vendor number
48.9 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...936 ans ...1	C	ans...936 Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present. The length must be set to 001.
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–4	Number of occurrences of vendor details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
Inquiry Response Structure		Occurs as specified by the value of the Count field.		
4	Customer Vendor Number	n 5		
5	Account with Vendor	an 28		
6	Account Verify	an 1	I, F, V or other values	I = Initial F = Failed V =Verified All other values are user defined.
7	Account Verify Last Change date	n 20	YYYYMMDDhhmmssmmmmmm	
8	Customer Vendor Begin Date	n 8	YYYYMMDD	
9	Customer Vendor End Date	n 8	YYYYMMDD	
10	Budget Category	an 4		
11	Customer Vendor Short Name	an 10		
12	User Information 1	an 20		
13	User Information 2	an 20		
14	Customer Vendor File Maintenance Tag	an 75		
14.1	Group Number	n 5		
14.2	User Number	n 5		
14.3	Terminal Name	an 24		
14.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
14.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
14.6	Reserved	an 1		
15	Vendor Name	an 3		
16	Main Branch Number	n 4		
17	Remit Branch Number	n 4		
18	Remit Person	an 22		
19	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V =Verified W= Waiting for ACH prenotification All other values are user defined.
20	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
21	Verify Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
22	Vendor Begin Date	n 8	YYYYMMDD	
23	Vendor End Date	n 8	YYYYMMDD	
24	Government ID	an 15		
25	Institution ID	an 11		
26	Account Number	an 19		
27	Account Type	an 2		
28	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
29	Remit Report Type	an 2		
30	Default Budget Type	an 4		
31	Audio Token	an 20		
32	Warning Payment Limit Amount	n 20		
33	Vendor Mask Group	an 4		
34	Vendor Type	an 1	P, or L	P = Public L = Limited
35	Vendor Type Description	an 7	Public Limited	
36	Prenote Date	n 8	YYYYMMDD	
37	Vendor Specific data Type	an 2		
38	Vendor Specific data Description	an 30		
39	Vendor User Remit Information 1	an 20		
40	Vendor User Remit Information 2	an 20		
41	Category Code	an 4		
42	Vendor File Maintenance Tag	an 75		
42.1	Group Number	n 5		
42.2	User Number	n 5		
42.3	Terminal Name	an 24		
42.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
42.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
42.6	Reserved	an 1		
43	Reserved	an 1		
44	Vendor Number	n 9		
45	Vendor Branch Number	n 4		
46	Vendor Branch Name	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
47	Address 1	an 30		
48	Address 2	an 30		
49	City	an 25		
50	State	an 2		
51	Postal Code	an 10		
52	County	an 3		
53	Country	an 3		
54	Phone number	an 20		
55	Contact Person	an 22		
56	Fax Phone	an 20		
57	Company Phone Number	an 20		
58	Mask Group	an 4		
59	Vendor Branch User Remit Information 1	an 20		
60	Vendor Branch User Remit Information 2	an 20		
61	Vendor Branch File Maintenance Tag	an 75		
61.1	Group Number	n 5		
61.2	User Number	n 5		
61.3	Terminal Name	an 24		
61.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
61.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
61.6	Reserved	an 1		
62	Customer Vendor Budget Category Description	an 30		
63	Vendor Default Budget Category Description	an 30		

3.9.3. Customer Vendor List Inquiry: ISO Reversal Format

Customer Vendor List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3H0000	3H0000 = customer vendor list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Vendor List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.9.4. Customer Vendor List Inquiry: ISO Reversal Response Format

Customer Vendor List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3H0000	3H0000 = customer vendor list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.10. Scheduled Payments List Inquiry (3J)

3.10.1. Scheduled Payments List Inquiry: ISO Request Format

The scheduled payments list inquiry transaction provides a list of all scheduled payments for a specified customer ID.

Scheduled Payments List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3J0000	3J0000 = scheduled payments list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. For the initial request, 48.1 must be set to a value of 0, 48.2 to AC, 48.3 to 0, 48.4 to 000, 48.5 to a space, and 48.6 to blanks. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed.

Scheduled Payments List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals AC, and 48.8 equals zeros)
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Next business date
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	n 5		n 5	Customer vendor number.
48.7	Reserved	an 25		an 25	
48.8	Key Data	n 8		YYYYMMDD	Next business date. If key data is present, filter data (48.6 and 48.7) must be present.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.10.2. Scheduled Payments List Inquiry: ISO Response Format

Scheduled Payments List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3J0000	3J0000 = scheduled payments list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDDhhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. Must be returned unaltered in subsequent requests, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Next business date
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	

Scheduled Payments List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.6	Filter Data	n 5		n 5	Customer vendor number.
48.7	Reserved	an 25		an 25	
48.8	Key Data	n 8		YYYYMMDD	Next business date. If key data is present, filter data (48.6 and 48.7) must be present.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...936 ans ...1	C	ans...936 Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present. The length must be set to 001.
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–9	Number of occurrences of history details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	Payments Made	n 4		
2	Total Payments	n 4		
3	Initial Payment Date	n 8	YYYYMMDD	
4	Recur Period	an 2		
5	STI Partition Number	n 5		
6	STI Payment Date	n 8	YYYYMMDD	
7	Retry Processing GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
8	Customer Reference Number	n 6		
9	Customer Vendor Number	n 5		
10	Vendor Number	n 9		
11	Customer Account with Vendor	an 28		
12	Billpay GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
13	Transaction type	an 2		
14	From FIID	an 4		
15	From Account Number	an 19		
16	From Account Type	an 2		
17	To FIID	an 4		
18	To Account Number	an 19		
19	To Account Type	an 2		
20	Amount	n 12		
21	Transaction Source	an 2	AD, BL, IB, PC, SP or other values	AD = Audio BL = Billing IB = Inbound PC = Personal computer SP = Screen phone All other values are user defined.
22	Transaction Source Number	n 6		
23	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmm mssmmmmmm	
24	Vendor Specific data	an 30		
25	Payment Date	n 8	YYYYMMDD	
26	Schedule Type	an 1	I, F, R, or space	I = Immediate F =Future R = Recurring Space = N/A (nonfinancial) All other values are considered to be unknown.
27	Billing Text	an 28		
28	Processing Status	an 2		
29	STI Request GMT	n 20	YYYYMMDDhhmm mssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
30	Retry Count Transient	n 4		
31	Retry Count Nontransient	n 4		
32	Retry Last Response code	n 3		
33	Remit type	n 3		
34	File Maintenance Tag	an 75		
34.1	Group Number	n 5		
34.2	User Number	n 5		
34.3	Terminal Name	an 24		
34.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.6	Reserved	an 1		
35	Vendor Name	an 30		
36	Vendor Token	an 20		
37	Currency Code	n 3		
38	From Account Type Description	an 6		
39	Reserved	an 1		

3.10.3. Scheduled Payments List Inquiry: ISO Reversal Format

Scheduled Payments List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3J0000	3J0000 = scheduled payments list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Scheduled Payments List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.10.4. Scheduled Payments List Inquiry: ISO Reversal Response Format

Scheduled Payments List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3J0000	3J0000 = scheduled payments list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.11. Scheduled Transfers List Inquiry (3K)

3.11.1. Scheduled Transfers List Inquiry: ISO Request Format

The scheduled transfers list inquiry transaction provides a list of all scheduled transfers for a specified customer ID.

Scheduled Transfers List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3K0000	3K0000 = scheduled transfers list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. For the initial request, 48.1 must be set to a value of 0, 48.2 to AC, 48.3 to 0, 48.4 to 000, 48.5 to a space, and 48.6 to blanks. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed.

Scheduled Transfers List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals AC, and 48.7 equals zeros)
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Next business date
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 30		an 30	Spaces
48.7	Key Data	n 8		YYYYMMDD	Next business date. If key data is present, filter data (48.6) must be present.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.11.2. Scheduled Transfers List Inquiry: ISO Response Format

Scheduled Transfers List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3K0000	3K0000 = scheduled transfers list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. Must be returned unaltered in subsequent requests, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Next business date
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 30		an 30	Spaces

Scheduled Transfers List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.7 Key Data		n 8		YYYYMMDD	Next business date. If key data is present, filter data (48.6) must be present.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...936 ans ...1	C	ans...936 Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present. The length must be set to 001.
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–10	Number of occurrences of history details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	Transfers Made	n 4		
2	Total Transfers	n 4		
3	Initial Transfer Date	n 8	YYYYMMDD	
4	Recur Period	an 2		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
5	STI Partition Number	n 5		
6	STI Transfer Date	n 8	YYYYMMDD	
7	Retry Processing GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
8	Customer Reference Number	n 6		
9	Customer Vendor Number	n 5		
10	Vendor Number	n 9		
11	Customer Account with Vendor	an 28		
12	Billpay GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
13	Transaction type	an 2		
14	From FIID	an 4		
15	From Account Number	an 19		
16	From Account Type	an 2		
17	To FIID	an 4		
18	To Account Number	an 19		
19	To Account Type	an 2		
20	Amount	n 12		
21	Transaction Source	an 2	AD, BL, IB, PC, SP or other values	AD = Audio BL = Billing IB = Inbound PC = Personal computer SP = Screen phone All other values are user defined.
22	Transaction Source Number	n 6		
23	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmm mssmmmmmm	
24	Vendor Specific data	an 30		
25	Transfer Date	n 8	YYYYMMDD	
26	Schedule Type	an 1	I, F, R, or space	I = Immediate F = Future R = Recurring Space = N/A (nonfinancial) All other values are considered to be unknown.
27	Billing Text	an 28		
28	Processing Status	an 2		
29	STI Request GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
30	Retry Count Transient	n 4		
31	Retry Count Nontransient	n 4		
32	Retry Last Response code	n 3		
33	Remit type	n 3		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
34	File Maintenance Tag	an 75		
34.1	Group Number	n 5		
34.2	User Number	n 5		
34.3	Terminal Name	an 24		
34.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.6	Reserved	an 1		
35	Currency Code	n 3		
36	From Account Type Description	an 6		
37	To Account Type Description	an 6		
38	Reserved	an 1		

3.11.3. Scheduled Transfers List Inquiry: ISO Reversal Format

Scheduled Transfers List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3K0000	3K0000 = scheduled transfers list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Scheduled Transfers List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.11.4. Scheduled Transfers List Inquiry: ISO Reversal Response Format

Scheduled Transfers List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3K0000	3K0000 = scheduled transfers list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.12. History Inquiry – Payments and Transfers (3L)

3.12.1. History Inquiry – Payments and Transfers: ISO Request Format

The history inquiry – payments and transfers transaction requests the last set of bill payment and transfer transactions (excluding immediate transfers) for a customer ID (PAN).

Note: Only the scheduling phase of a scheduled payment – immediate is retrieved. The resulting payment is not retrieved.

History Inquiry – Payments and Transfers		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3L0000	3L0000 = history inquiry – payments and transfers.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

History Inquiry – Payments and Transfers		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. For an initial request, 48.1 must be set to a value of 0, 48.2 to AC, 48.3 to 0, 48.4 to 000, 48.5 to a space, and 48.6 to blanks. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals DC, and 48.8 equals the current date)
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0 or 1	0 = Business date 1 = Customer reference number
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data		an 1		A, D or B	A = Approved B = Both D = Denied
48.7 Reserved		an 29		an 29	
48.8 Key Data (1)		n 8		YYYYMMDD	Business date. Depending on the value in 48.3 (Key data type) either 48.8 or 48.9 is present. If key data is present, filter data (48.6 and 48.7) must be present.
OR 48.9 Key Data (2)		n 6		n 5	Customer reference number. If key data is present, filter data (48.6 and 48.7) must be present.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.12.2. History Inquiry – Payments and Transfers: ISO Response Format

The history inquiry – payments and transfers response supplies the last set of bill payment and transfer transactions (excluding immediate transfers) for a customer ID (PAN).

History Inquiry – Payments and Transfers		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3L0000	3L0000 = history inquiry – payments and transfers.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. Must be returned unaltered in subsequent requests, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0 or 1	0 = Business date 1 = Customer reference number
48.4 Cumulative Transaction Count		n 3		n 3	

History Inquiry – Payments and Transfers		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 1		A, D or B	A = Approved B = Both D = Denied
48.7	Reserved	an 29		an 29	
48.8	Key Data (1)	n 8		YYYYMM DD	Business date. Depending on the value in 48.3 (Key data type) either 48.8 or 48.9 is present. If key data is present, filter data (48.6 and 48.7) must be present.
OR 48.9	Key Data (2)	n 6		n 5	Customer reference number. If key data is present, filter data (48.6 and 48.7) must be present.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...936 ans ...1	C	ans...936 Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present. The length must be set to 001.
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–7	Number of occurrences of history details returned.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
Inquiry Response Structure		Occurs as specified by the value of the Count field.		
1	Partition Number	n 5		
2	GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
3	Customer Reference Number	n 6		
4	Customer Vendor Number	n 5		
5	Vendor Number	n 9		
6	Customer Account with Vendor	an 28		
7	Billpay GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
8	Transaction type	an 2		
9	From FIID	an 4		
10	From Account Number	an 19		
11	From Account Type	an 2		
12	To FIID	an 4		
13	To Account Number	an 19		
14	To Account Type	an 2		
15	Amount	n 12		
16	Transaction Source	an 2	AD, BL, IB, PC, SP or other values	AD = Audio BL = Billing IB = Inbound PC = Personal computer SP = Screen phone All other values are user defined.
17	Transaction Source Number	n 6		
18	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmm mssmmmmmm	
19	Vendor Specific data	an 30		
20	Payment Begin Date	n 8	YYYYMMDD	
21	Schedule Type	an 1	I, F, R, or space	I = Immediate F =Future R = Recurring Space = N/A (nonfinancial) All other values are considered to be unknown.
22	Bill Text	an 28		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
23	Original Customer Reference Number	n 6		
24	Response Code	an 3		
25	Reversal Reason Code	an 4		
26	Auth Action Code	an 3		
27	Auth Approve Code	an 9		
28	Collection Status	an 1	C, F, I, P, space	C = Complete F = Failed I = Initial P = Pending Space = Nonfinancial transaction All other values are considered to be unknown.
29	Business Date	n 8	YYYYMMDD	
30	Remit Business Date	n 8	YYYYMMDD	
31	Remit Status	an 1	I, C, F, L, S, space	I = Initial C = Completed F = Failed L = Cleared S = Sent out Space = Nonpayment transaction All other values are considered to be unknown.
32	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
33	Remit ack GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
34	Remit ack number	an 10		
35	Remit ack received GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
36	File Maintenance Tag	an 75		
36.1	Group Number	n 5		
36.2	User Number	n 5		
36.3	Terminal Name	an 24		
36.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
36.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
36.6	Reserved	an 1		
37	From Account Type Description	n 6		
38	To Account Type Description	n 6		
39	Response Code Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
40	Vendor Name	an 30		
41	Vendor Token	an 20		
42	Currency Code	n 3		
43	Reserved	an 1		
44	Transaction Type Financial Description	an 4	BLPY, TRFR or Space	BLPY = Transactions 9A, 9B, 9C, 5A, 5B TRFR = Transactions 9D, 9E, 4A, 4B Space = Aall other transactions

3.12.3. History Inquiry – Payments and Transfers: ISO Reversal Format

History Inquiry – Payments and Transfers		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3L0000	3L0000 = history inquiry – payments and transfers.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

History Inquiry – Payments and Transfers		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.12.4. History Inquiry – Payments and Transfers: ISO Reversal Response Format

History Inquiry – Payments and Transfers		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3L0000	3L0000 = history inquiry – payments and transfers.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.13. History Inquiry – All Transactions (9X)

3.13.1. History Inquiry – All Transactions: ISO Request Format

The history inquiry – all transactions request lists all types of transactions (financial, nonfinancial, or maintenance) logged for a customer ID in the History Table (HIST).

Note: Only the scheduling phase of a scheduled payment – immediate is retrieved. The resulting payment is not retrieved.

History Inquiry – All Transactions		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9X0000	9X0000 = history inquiry – all transactions.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.

History Inquiry – All Transactions		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On the initial request, 48.1 must be set to a value of 0, 48.2 to AC, 48.3 to 0, 48.4 to 000, 48.5 to a space, and 48.6 to blanks. Either 48.8 or 48.9 must be present. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals DC, and 48.8 equals the current date)
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0, 1	0 = Business date 1 = Customer reference number
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data		an 1		A, D or B	A = Approved D = Denied B = Both
48.7 Reserved		an 29		an 29	
48.8 Key Data (1)		n 8		YYYYMMDD	Business date or 48.9 must be present
OR 48.9 Key Data (2)		n 6		n 5	Customer reference number.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.13.2. History Inquiry – All Transactions: ISO Response Format

History Inquiry – All Transactions		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9X0000	9X0000 = history inquiry – all transactions.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. Must be returned unaltered in subsequent requests, except for the search direction, which can be changed. Either 48.8 or 48.9 must be present. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending

History Inquiry – All Transactions		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.3	Key Data Type	an 1		0 or 1	0 = Business date 1 = Customer reference number
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 1		A, D or B	A = Approved D = Denied B = Both
48.7	Reserved	an 29		an 29	
48.8	Key Data (1)	n 8		YYYYMMDD	Business date or 48.9 must be present
OR 48.9	Key Data (2)	n 6		n 5	Customer reference number.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0-7	Number of occurrences of history details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	Partition Number	n 5		
2	GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
3	Customer Reference Number	n 6		
4	Customer Vendor Number	n 5		
5	Vendor Number	n 9		
6	Customer Account with Vendor	an 28		
7	Billpay GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
8	Transaction type	an 2		
9	From FIID	an 4		
10	From Account Number	an 19		
11	From Account Type	an 2		
12	To FIID	an 4		
13	To Account Number	an 19		
14	To Account Type	an 2		
15	Amount	n 12		
16	Transaction Source	an 2	AD, BL, IB, PC, SP or other values	AD = Audio BL = Billing IB = Inbound PC = Personal computer SP = Screen phone All other values are user defined.
17	Transaction Source Number	n 6		
18	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmm mssmmmmmm	
19	Vendor Specific data	an 30		
20	Payment Begin Date	n 8	YYYYMMDD	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
21	Schedule Type	an 1	I, F, R, or space	I = Immediate F = Future R = Recurring Space = N/A (nonfinancial) All other values are considered to be unknown.
22	Bill Text	an 28		
23	Original Customer Reference Number	n 6		
24	Response Code	an 3		
25	Reversal Reason Code	an 4		
26	Auth Action Code	an 3		
27	Auth Approve Code	an 9		
28	Collection Status	an 1	C, F, I, P, space	C = Complete F = Failed I = Initial P = Pending Space = Nonfinancial transaction All other values are considered to be unknown.
29	Business Date	n 8	YYYYMMDD	
30	Remit Business Date	n 8	YYYYMMDD	
31	Remit Status	an 1	I, C, F, L, S, space	I = Initial C = Completed F = Failed L = Cleared S = Sent out Space = Nonpayment transaction All other values are considered to be unknown.
32	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
33	Remit ack GMT	n 20	YYYYMMDDhhmmssmmmmmm	
34	Remit ack number	an 10		
35	Remit ack received GMT	n 20	YYYYMMDDhhmmssmmmmmm	
36	File Maintenance Tag	an 75		
36.1	Group Number	n 5		
36.2	User Number	n 5		
36.3	Terminal Name	an 24		
36.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
36.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
36.6	Reserved	an 1		
37	From Account Type Description	n 6		
38	To Account Type Description	n 6		
39	Response Code Description	an 30		
40	Vendor Name	an 30		
41	Vendor Token	an 20		
42	Currency Code	n 3		
43	Reserved	an 1		
44	Transaction Type Financial Description	an 4	BLPY, TRFR or Space	BLPY = Transactions 9A, 9B, 9C, 5A, 5B TRFR = Transactions 9D, 9E, 4A, 4B Space = All other transactions

3.13.3. History Inquiry – All Transactions: ISO Reversal Format

History Inquiry – All Transactions		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9X0000	9X0000 = history inquiry – all transactions.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

History Inquiry – All Transactions		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.13.4. History Inquiry – All Transactions: ISO Reversal Response Format

History Inquiry – All Transactions		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9X0000	9X0000 = history inquiry – all transactions.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	M	ans 25	Customer vendor number. If it is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.14. Scheduled Transactions List Inquiry (3M)

3.14.1. Scheduled Transactions List Inquiry: ISO Request Format

The scheduled transactions list inquiry transaction provides a list of all transfer and payment transactions for a specified customer ID that are scheduled to be performed in the future, including both one-time and recurring transactions.

Scheduled Transactions List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3M0000	3M0000 = scheduled transactions list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.

Scheduled Transactions List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, and 48.8 equals zeros)
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0 or 1	0 = Payment Date 1 = Customer reference number
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	n 5		n 5	Customer vendor number.
48.7	Reserved	an 25		an 25	
48.8	Key Data (1)	n 8		YYYYMMDD	Payment date. Depending on the value in 48.3 (Key data type) either 48.8 or 48.9 is present.
OR 48.9	Key Data (2)	n 6		n 6	Customer reference number.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.14.2. Scheduled Transactions List Inquiry: ISO Response Format

Scheduled Transactions List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3M0000	3M0000 = scheduled transactions list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0 or 1	0 = Payment date 1 = Customer reference number

Scheduled Transactions List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	n 5		n 5	Customer vendor number.
48.7	Reserved	an 25		an 25	
48.8	Key Data (1)	n 8		YYYYMMDD	Payment date. Depending on the value in 48.3 (Key data type) either 48.8 or 48.9 is present.
OR 48.9	Key Data (2)	n 6		n 6	Customer reference number.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–8	Number of occurrences of history details returned.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	Payments Made	n 4		
2	Total Payments	n 4		
3	Initial Payment Date	n 8	YYYYMMDD	
4	Recur Period	an 2		
5	STI Partition Number	n 5		
6	STI Payment Date	n 8	YYYYMMDD	
7	Retry Processing GMT	n 20	YYYYMMDDhhmmssmmmmmm	
8	Customer Reference Number	n 6		
9	Customer Vendor Number	n 5		
10	Vendor Number	n 9		
11	Customer Account with Vendor	an 28		
12	Billpay GMT	n 20	YYYYMMDDhhmmssmmmmmm	
13	Transaction type	an 2		
14	From FIID	an 4		
15	From Account Number	an 19		
16	From Account Type	an 2		
17	To FIID	an 4		
18	To Account Number	an 19		
19	To Account Type	an 2		
20	Amount	n 12		
21	Transaction Source	an 2	AD, BL, IB, PC, SP or other values	AD = Audio BL = Billing IB = Inbound PC = Personal computer SP = Screen phone All other values are user defined.
22	Transaction Source Number	n 6		
23	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmmssmmmmmm	
24	Vendor Specific data	an 30		
25	Payment Date	n 8	YYYYMMDD	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
26	Schedule Type	an 1	I, F, R, or space	I = Immediate F =Future R = Recurring Space = N/A (nonfinancial) All other values are considered to be unknown.
27	Billing Text	an 28		
28	Processing Status	an 2		
29	STI Request GMT	n 20	YYYYMMDDhhmm mssmmmmmm	
30	Retry Count Transient	n 4		
31	Retry Count Nontransient	n 4		
32	Retry Last Response code	n 3		
33	Remit type	n 3		
34	File Maintenance Tag	an 75		
34.1	Group Number	n 5		
34.2	User Number	n 5		
34.3	Terminal Name	an 24		
34.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
34.6	Reserved	an 1		
35	Vendor Name	an 30		
36	Vendor Token	an 20		
37	Currency Code	n 3		
38	From Account Type Description	an 6		
39	To Account Type Description	an 6		
40	Reserved	an 1		

3.14.3. Scheduled Transactions List Inquiry: ISO Reversal Format

Scheduled Transactions List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3M0000	3M0000 = scheduled transactions list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Scheduled Transactions List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.14.4. Scheduled Transactions List Inquiry: ISO Reversal Response Format

Scheduled Transactions List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3M0000	3M0000 = scheduled transactions list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.15. Customer Account List Inquiry (3N)

3.15.1. Customer Account List Inquiry: ISO Request Format

The customer account list inquiry request lists all accounts associated with the customer ID (PAN).

Customer Account List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3N0000	3N0000 = customer account list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. On a continuation request, this data must be echoed from the response exactly, except for the search direction, which can be changed. Key data fields contain BASE24-billpay positioning information

Customer Account List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Spaces (indicates to use defaults of 48.1 equals 0, 48.2 equals AC, and 48.8 equals zeros)
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Reserved	an 1			
48.4	Key Data	Var -> 196			
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> Account. Required only if accessing by account.

3.15.2. Customer Account List Inquiry: ISO Response Format

Customer Account List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3N0000	3N0000 = customer account list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field is returned if the transaction is approved.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Reserved		an 1			
48.4 Key Data		Var -> 196			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Account List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Account List Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1 Count		n 2		0–15	The number of accounts returned in the information block.
125.2 Additional Data Flag		an 1		Y or N	Y = More accounts exist. N = No more accounts exist.
125.3 Customer Type		an 2		B, C or others	B = Business. C = Consumer or others (user defined).
125.4 Customer Verify Type		an 2		I, V, C or others	I = Issued, but not active. V = Verified. C = Closed or others (user defined).
125.5 Customer Information Buffer #1		an 20			
125.6 Customer Information Buffer #2		an 20			
125.7 Customer Information Buffer #3		an 20			
125.8 Reserved		an 1			
125.9 Account List Structure					See Account List Structure below. Occurs the number of times specified by the value in the Count field.

Account List Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	an 19		The number for this account.
2	Account Type	an 2		Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
3	Account Qualifier	an 4		Account qualifier.
4	FIID	an 4		Financial institution ID.

Account List Structure				
#	Name	ISO Format	Format	Comment
5	Status	an 1	0-4, 9, A-Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Account Description	an 15		Account Description
7	Debits allowed	an 1	Y or N	Indicates whether debits are allowed. Y= Yes N= No
8	Credits allowed	an 1	Y or N	Indicates whether credits are allowed. Y= Yes N= No
9	Inquiries allowed	an 1	Y or N	Indicates whether inquiries are allowed. Y= Yes N= No

3.15.3. Customer Account List Inquiry: ISO Reversal Format

Customer Account List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3N0000	3N0000 = customer account list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field can be used to transport data to a host.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Account List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	<i>From Account. Required only if accessing by account.</i>

3.15.4. Customer Account List Inquiry: ISO Reversal Response Format

Customer Account List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3N0000	3N0000 = customer account list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. If this field is present in the reversal, it should be echoed in the reversal response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From Account. Required only if accessing by account.

3.16. Multiple Account Balance Inquiry (3P)

3.16.1. Multiple Account Balance Inquiry: ISO Request Format

The multiple account balance inquiry transaction allows a customer to obtain the current balances of all configured accounts for a customer ID. The account number must be provided in the request for each account on which the customer wants to obtain a balance. Therefore, ACI suggests that an account list inquiry transaction be performed prior to this transaction to obtain the customer account numbers.

Multiple Account Balance Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3P0000	3P0000 = multiple account balance inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field can be used to transport data to a host.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Multiple Account Balance Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	<i>To</i> account. Either field 103 or 123 is required.
123	Account Qualifiers	anp...8		anp...8	Account qualifier, <i>from</i> and <i>to</i> accounts (anp 4 each). Either fields 102 and 103 or 123 are required.
125	Multiple Account Balance Request Data	ans ...998	M	ans ...998	
125.1 Count		n 2		0–13	The number of account details returned in the Multiple Account Information Structure.
125.2 Multiple Account Information Structure					See Multiple Account Information Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

Multiple Account Information Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	an 19		The number for this account.
2	Account Type	n 2		Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.

3.16.2. Multiple Account Balance Inquiry: ISO Response Format

Multiple Account Balance Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3P0000	3P0000 = multiple account balance inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the request, it is echoed in the response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Multiple Account Balance Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Multiple Account Balance Inquiry Data	ans ...998	C	ans...998	This field is returned if the transaction is approved and data is available.
125.1 Count		n 2		0–13	The number of account details returned in the Multiple Account Information Structure.
125.2 Multiple Account Information Structure					See Multiple Account Information Structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Multiple Account Information Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	an 19		The number for this account.
2	Account Type	an 2		Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
3	Action Code	an 3		
4	Balance Date	an 8	YYYYMMDD	
5	Currency Code	an 3		
Balance Entry Information The following fields occur twice for each Multiple Account Information entry.				
	Balance Amount Type	an 2		
	Balance Amount Sign	an 1		
	Balance Amount	an 12		

3.16.3. Multiple Account Balance Inquiry: ISO Reversal Format

Multiple Account Balance Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3P0000	3P0000 = multiple account balance inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. If this field is present in the response, it should be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Multiple Account Balance Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	If an account is available, it is sent in the response, otherwise request data is echoed back.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.16.4. Multiple Account Balance Inquiry: ISO Reversal Response Format

Multiple Account Balance Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	3P0000	3P0000 = multiple account balance inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the reversal, it should be echoed in the reversal response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.
103	Account ID 2	ans..28		ans..28	To account. Either field 103 or 123 is required.

Multiple Account Balance Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.17. Bank List Inquiry (B1)

3.17.1. Bank List Inquiry: ISO Request Format

The bank list inquiry transaction returns a list of financial institutions configured in the Bank Table (BANK).

Bank List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used. On a continuation request, this field contains the BASE24-billpay customer ID taken from the response.
3	Processing Code	an 6	M	B10000	B10000 = bank list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not contain zeros, this field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response exactly. Key data fields contain BASE24-billpay positioning information.

Bank List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals AC, and 48.7 equals spaces)
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0 or 1	0 = Bank name 1 = FIID If the PAN is zeros, this field must be set to a value of 1.
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 30		an 30	Not currently used. This field must contain spaces if it is present.
48.7	Key Data (1) – Bank Name	an 22		an 22	This field or 48.8 must be present.
OR 48.8	Key Data (2) - FIID	an 4		an 4	FIID. This field must contain a valid FIID or spaces.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.17.2. Bank List Inquiry: ISO Response Format

Bank List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Contains the BASE24-billpay default customer ID .
3	Processing Code	an 6	M	B10000	B10000 = bank list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field can contain zeros, if not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0 or 1	0 = Bank name 1 = FIID
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data		an 30		an 30	Not currently used. This field must contain spaces if it is present.
48.7 Key Data (1) – Bank Name		an 22		an 22	This field or 48.8 must be present.

Bank List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
OR 48.8 Key Data (2) - FIID		an 4		an 4	FIID.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–19	Number of occurrences of history details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	FIID	an 4		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
2	Institution ID	n 11		
3	Bank Name	an 22		
4	Main Branch Number	an 4		
5	Begin Date	n 8	YYYYMMDD	
6	End date	n 8	YYYYMMDD	
7	Payment High Limit	n 12		
8	Subsequent Transaction Source	an 2		
9	Billing Group	an 4		
10	Billing Type	an 2		
11	Customer Vendor Initial Verify	a 1	I, F or V	I = Initial F = Failed V = Verified
12	Vendor Number	n 9		
13	Default Customer ID	an 28		
14	Default Account Number	an 19		
15	Customer Database Preload	an 1	Y or N	Y = Yes, database is preloaded. N = No, database is not preloaded.
16	Customer ID Generation Allowed	an 1	Y or N	Y = Yes, customer ID generation is allowed. N = No, customer ID generation is not allowed.
17	Reactivation Allowed	an 1	Y or N	Y = Yes, customer reactivation is allowed N = No, customer reactivation is not allowed
18	Reserved	an 1		
19	File Maintenance Tag	an 75		
19.1	Group Number	n 5		
19.2	User Number	n 5		
19.3	Terminal Name	an 24		
19.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
19.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
19.6	Reserved	an 1		

3.17.3. Bank List Inquiry: ISO Reversal Format

Bank List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B10000	B10000 = bank list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Bank List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.17.4. Bank List Inquiry: ISO Reversal Response Format

Bank List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B10000	B10000 = bank list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.18. Bank Branch List Inquiry (B2)

3.18.1. Bank Branch List Inquiry: ISO Request Format

The bank branch list inquiry transaction returns a list of financial institution branches configured in the Bank Branch Table (BKBR).

Bank Branch List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B20000	B20000 = bank branch list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response exactly. Key data fields contain BASE24-billpay positioning information.
48.1	Request/Response Indicator	an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates to use defaults of 48.3 equals 0, 48.2 equals AC, 48.7, and 48.8 equal spaces)

Bank Branch List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Bank Branch
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 30		an 30	Not currently used. This field must contain spaces if it is present.
48.7	Bank Branch Key - FIID	an 4		an 4	Must be present and contain a valid FIID if not using defaults.
48.8	Bank Branch Key – City	an 25		an 25	Optional if not using defaults
48.9	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.18.2. Bank Branch List Inquiry: ISO Response Format

Bank Branch List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B20000	B20000 = bank branch list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0	0 = Bank branch
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data		an 30		an 30	Not currently used. This field must contain spaces if it is present.
48.7 Bank Branch Key - FIID		an 4		an 4	Must be present if not using defaults.
48.8 Bank Branch Key – City		an 25		an 25	Optional if not using defaults.

Bank Branch List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.9 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and BASE24-billpay inquiry data is available. The value Y indicates whether the external data block is present.
	External Data Block	ans4096	C		See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–16	Number of occurrences of history details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Inquiry Response Structure			Occurs as specified by the value of the Count field.	
1	FIID	an 4		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
2	Branch Number	an 4		
3	Address Line 1	an 30		
4	Address Line 1	an 30		
5	City	an 25		
6	State	an 2		
7	Postal Code	an 10		
8	Phone Number	an 20		
9	Contact Name	an 22		
10	Fax	an 20		
11	Reserved	an 1		
12	File Maintenance Tag	an 75		
12.1	Group Number	n 5		
12.2	User Number	n 5		
12.3	Terminal Name	an 24		
12.4	AFT Timestamp	n 20	YYYYMMDDhhm mssmmmmmm	
12.5	OLTP Timestamp	n 20	YYYYMMDDhhm mssmmmmmm	
12.6	Reserved	an 1		

3.18.3. Bank Branch List Inquiry: ISO Reversal Format

Bank Branch List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B20000	B20000 = bank branch list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Bank Branch List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.18.4. Bank Branch List Inquiry: ISO Reversal Response Format

Bank Branch List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	B20000	B20000 = bank branch list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

3.19. Statement Download (3R)

3.19.1. Statement Download: ISO Request Format

The statement download transaction returns the set of transactions for an account over a given period of time.

Statement Download		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Rnn00	3Rnn00 = statement download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2 Source type		an 1			This field is not currently used.

Statement Download		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.3	Check Number	an 12			This field is not currently used.
48.4	Amount	n 12			This field is not currently used.
48.5	Start Posting Date	an 6			
48.6	End Posting date	an 6			
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
123	Account Qualifier	anp...8		anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 are required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.19.2. Statement Download: ISO Response Format

Statement Download		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Rnn00	3Rnn00 = statement download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Source type	an 1			This field is not currently used.
48.3	Check Number	an 12			This field is not currently used.
48.4	Amount	n 12			This field is not currently used.
48.5	Start Posting Date	an 6			
48.6	End Posting date	an 6			

Statement Download		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
123	Account Qualifier	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1 Count		n 2		0–3	The number of transactions being returned in the information block.
125.2 Currency Code		an 3			
125.3 Additional Data Flag		an 1			
125.4 Last Transaction Structure					See statement download structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Statement Download Structure				
#	Name	ISO Format	Format	Comment
1	Date	n 6	YYMMDD	Date of transaction.
2	Amount	n 12		Amount of transaction.
3	Check Number	an 12		Check number.
4	Debit/Credit Indicator	an 1	C or D	C = Credit D = Debit

Statement Download Structure				
#	Name	ISO Format	Format	Comment
5	Source Type	an 1	A, B, P or T	A code indicating where the transaction originated. Valid values reserved for BASE24 are as follows: A = ATM B = Remote banking device P = POS device T = Teller
6	Funds Indicator	an 1	0 or 1	0 = Sufficient funds 1 = Insufficient funds
7	Reversal Indicator	an 1	0 or 1	0 = Not reversed 1 = Reversed
8	Reserved Transaction Flags	an 14	0	
9	Host Transaction Code	an 8		
10	FI Transaction ID	an 32		Unique for each account.
11	Special Data Type	an 1	P, T or “ ”	P = Payment data present T = Transfer data present “ ” = No special data present
12	Reserved	an 1		
13	Special Data	an 160		This field contains either the PMNT structure (if the special data type is P) or the XFER structure (if the special data type is T) or spaces (if the special data type is “ ”).
13.1 PMNT – Payee Name		an 32		
13.2 PMNT – Payee Address 1		an 32		
13.3 PMNT – Payee Address 2		an 32		
13.4 PMNT – Payee City		an 32		
13.5 PMNT – Payee State		an 2		
13.6 PMNT – Payee Zip		an 10		
13.7 PMNT – Payee Phone		an 20		
OR 13.1 XFER – Other Account		an 19		The other account involved in the transfer (i.e., the one not documented in field 102 or 123).
13.2 XFER – Other Account Type		an 2		
13.3 XFER – Reserved		an 139		

3.19.3. Statement Download: ISO Reversal Format

Statement Download		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Rnn00	3Rnn00 = statement download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			

Statement Download		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.19.4. Statement Download: ISO Reversal Response Format

Statement Download		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Rnn00	3Rnn00 = statement download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

Statement Download		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.20. Statement Closing Download (3Q)

3.20.1. Statement Closing Download: ISO Request Format

The statement closing download transaction returns the closing statement information for an account over a given period of time.

Statement Closing Download		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Qnn00	3Qnn00 = statement closing download. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, this data must be echoed from the response.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request

Statement Closing Download		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Source type	an 1			This field is not currently used.
48.3	Check Number	an 12			This field is not currently used.
48.4	Amount	n 12			This field is not currently used.
48.5	Start Posting Date	an 6			
48.6	End Posting date	an 6			
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
123	Account Qualifier	anp...8		anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

3.20.2. Statement Closing Download: ISO Response Format

Statement Closing Download		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Qnn00	3Qnn00 = statement closing download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Request/Response Indicator	an 1		1	1 = Response
48.2	Source type	an 1			This field is not currently used.
48.3	Check Number	an 12			This field is not currently used.
48.4	Amount	n 12			This field is not currently used.
48.5	Start Posting Date	an 6			
48.6	End Posting date	an 6			

Statement Closing Download		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
123	Account Qualifier	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
125	Transaction History Data	ans...998	C	ans...998	This field is returned if the transaction is approved and history data is available.
125.1 Count		n 2		0–16	The number of transactions being returned in the information block.
125.2 Currency Code		an 3			
125.3 Additional Data Flag		an 1			
125.4 Last Transaction Structure					See Statement Closing Download structure below. Occurs the number of times specified by the value in the Count field.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

Statement Closing Download Structure				
#	Name	ISO Format	Format	Comment
1	FI Transaction ID	an 32		Unique for each account.
2	Closing date	an 6	YYMMDD	
3	Closing Balance	an 12		
4	Begin posting date	an 6	YYMMDD	
5	End posting date	an 6	YYMMDD	

3.20.3. Statement Closing Download: ISO Reversal Format

Statement Closing Download		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Qnn00	3Qnn00 = statement closing download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			

Statement Closing Download		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

3.20.4. Statement Closing Download: ISO Reversal Response Format

Statement Closing Download		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	3Qnn00	3Qnn00 =statement closing download. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Statement Closing Download		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

4. Customer Management Messages

4.1. Customer Add (9K)

4.1.1. Customer Add: ISO Request Format

The customer add transaction adds a customer to the database.

Customer Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used. The value in this field should be nonzero only if BASE24-billpay does not generate the customer ID for the FIID.
3	Processing Code	an 6	M	9K0000	9K0000 = customer add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 FIID		an 4		an 4	FIID for the customer being added.

Customer Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Alternate Contact	an 30		
2	Customer Information: Line1	an 20		
3	Customer Information: Line2	an 20		
4	Customer Information: Line3	an 20		
5	Customer Type	an 2	B or C	C = Consumer B = Business
6	Branch Number	n 4		
7	Default Account Number	an 19		
8	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
9	Default Account Type Description	an 6		If the account type is provided, the account description is not used.
10	Service Fee: Account Number	an 19		
11	Service Fee: Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
12	Service Fee: Account Type Description	an 6		If the account type is provided, the account description is not used.
13	Customer Profile	an 8		
14	Family Name	an 20		
15	Given Name	an 10		
16	Middle Initial	an 1		
17	Title	an 6		
18	Government ID	an 15		
19	Birth Date (YYYYMMDD)	n 8		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
20	Address 1	an 30		
21	Address 2	an 30		
22	Address 3	an 30		
23	City	an 25		
24	State	an 2		
25	Country Code	an 3		
26	Postal Code	an 10		
27	Language Indicator	n 2		
28	Phone: Home	an 20		
29	Phone: Work	an 20		
30	Phone: Other 1	an 20		
31	Phone: Other 1 Description	an 10		
32	Phone: Other 2	an 20		
33	Phone: Other 2 Description	an 10		
34	Mother's Maiden Name	an 20		

4.1.2. Customer Add: ISO Response Format

Customer Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if not, this field is used if field 34 is not used. The value in this field should be nonzero only if BASE24-billpay does not generate the customer ID for the FIID.
3	Processing Code	an 6	M	9K0000	9K0000 = customer add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDDhhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 FIID		an 4		an 4	FIID for the customer being added.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
125	Billpay Inquiry Data	ans ...998	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Version	n 4		
2	FIID	an 4		
3	Customer Profile	an 8		
4	Customer Type	an 2	B or C	C = Consumer B = Business
5	Bad PIN Count	n 4		
6	Customer Verify Flag	an 2	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
7	PIN Offset	an 16		
8	Last Change: Customer Verify Status	n 20	YYYYMMDDhhmm mssmmmmmm	
9	Last Change: PIN Offset	n 20	YYYYMMDDhhmm mssmmmmmm	
10	PVK Index	an 1		
11	Default Account Number	an 19		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
12	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
13	Max Online History Records	n 4		
14	Customer Information: Line1	an 20		
15	Customer Information: Line2	an 20		
16	Customer Information: Line3	an 20		
17	Alternate Contact	an 30		
18	Begin Date	n 8	YYYYMMDD	
19	End Date	n 8	YYYYMMDD	
20	Branch Number	n 4		
21	PIN Change Required	an 1	Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
22	Billing Type	an 2		
23	Packet Status	an 1		
24	Billing Type Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
25	Packet Status Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
26	Billpay Billing Group	an 4		
27	Billpay Transaction Limit	n 12		
28	Customer File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.6	Reserved	an 1		
29	Last Reset Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
30	Service Fee: Account Number	an 19		
31	Service Fee: Account Type	an 2		
32	Reserved	an 1		
33	Number of Cycles	n 5		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
34	Next Customer Reference Number	n 6		
35	Billing Group	an 4		
36	Last Customer Vendor Number	n 5		
37	Last Cycle End Date	n 8	YYYYMMDD	
38	Original Billing Type	an 2		
39	Last Billing Reference Number	n 6		
40	Current Billing Type	an 2		
41	Customer Billpay File Maintenance Tag	an 75		
41.1	Group Number	n 5		
41.2	User Number	n 5		
41.3	Terminal Name	an 24		
41.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.6	Reserved	an 1		
42	Personal ID	an 28		
43	Version	n 4		
44	FIID	an 4		
45	Family Name	an 20		
46	Given Name	an 10		
47	Middle Initial	an 1		
48	Family Name Token	an 16		
49	Given Name Token	an 6		
50	Title	an 6		
51	Government ID	an 15		
52	Birth Date (YYYYMMDD)	n 8		
53	Address 1	an 30		
54	Address 2	an 30		
55	Address 3	an 30		
56	City	an 25		
57	State	an 2		
58	Country Code	an 3		
59	Postal Code	an 10		
60	Language Indicator	n 2		
61	Phone: Home	an 20		
62	Phone: Work	an 20		
63	Phone: Other 1	an 20		
64	Phone: Other 1 Description	an 10		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
65	Phone: Other 2	an 20		
66	Phone: Other 2 Description	an 10		
67	Mother's Maiden Name	an 20		
68	Personal File Maintenance Tag	an 75		
68.1	Group Number	n 5		
68.2	User Number	n 5		
68.3	Terminal Name	an 24		
68.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
68.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
68.6	Reserved	an 1		
69	Default Account Type Description	an 6		
70	Service Fee Account Type Description	an 6		

4.1.3. Customer Add: ISO Reversal Format

Customer Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if not, this field is used if field 34 is not used. The value of this field should be nonzero only if BASE24-billpay does not generate the customer ID for the FIID.
3	Processing Code	an 6	M	9K0000	9K0000 = customer add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.1.4. Customer Add: ISO Reversal Response Format

Customer Add		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if not, this field is used if field 34 is not used. The value of this field should be nonzero only if BASE24-billpay does not generate the customer ID for the FIID.
3	Processing Code	an 6	M	9K0000	9K0000 = customer add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.2. Customer Inquiry (9L)

4.2.1. Customer Inquiry: ISO Request Format

The customer inquiry transaction retrieves customer ID and personal information about a customer from the BASE24 database.

If a customer ID and personal ID are provided, BASE24-billpay retrieves the specific customer information. If the personal ID is not provided in the request, the value of the personal ID is assumed to be the same as the customer ID. If a customer ID and a personal ID are not provided, default customer information is retrieved for signing up new customers.

Customer Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	9L0000	9L0000 = customer inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	
48.1	Personal ID	an 28		an 28	Personal ID. Must be blank if field 2 (or field 34, if used) is zero. If blank, the value in field 2 or field 34 is used.

Customer Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2 FIID		an 4		an 4	FIID. Must be present if field 2 (or field 34 if used) is zero.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	If this field is not sent in the request, a BASE24 default is used.

4.2.2. Customer Inquiry: ISO Response Format

Customer Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9L0000	9L0000 = customer inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the request, it is echoed in the response.
48.1 Personal ID		an 28		an 28	
48.2 FIID		an 4		an 4	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Version	n 4		
2	FIID	an 4		
3	Customer Profile	an 8		
4	Customer Type	an 2	B or C	C = Consumer B = Business
5	Bad PIN Count	n 4		
6	Customer Verify Flag	an 2	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
7	PIN Offset	an 16		
8	Last Change: Customer Verify Status	n 20	YYYYMMDDhhmmssmmmmmm	
9	Last Change: PIN Offset	n 20	YYYYMMDDhhmmssmmmmmm	
10	PVK Index	an 1		
11	Default Account Number	an 19		
12	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
13	Max Online History Records	n 4		
14	Customer Information: Line1	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
15	Customer Information: Line2	an 20		
16	Customer Information: Line3	an 20		
17	Alternate Contact	an 30		
18	Begin Date	n 8	YYYYMMDD	
19	End Date	n 8	YYYYMMDD	
20	Branch Number	n 4		
21	PIN Change Required	an 1	Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
22	Billing Type	an 2		
23	Packet Status	an 1		
24	Billing Type Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
25	Packet Status Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
26	Billpay Billing Group	an 4		
27	Billpay Transaction Limit	n 12		
28	Customer File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.6	Reserved	an 1		
29	Last Reset Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
30	Service Fee: Account Number	an 19		
31	Service Fee: Account Type	an 2		
32	Reserved	an 1		
33	Number of Cycles	n 5		
34	Next Customer Reference Number	n 6		
35	Billing Group	an 4		
36	Last Customer Vendor Number	n 5		
37	Last Cycle End Date	n 8	YYYYMMDD	
38	Original Billing Type	an 2		
39	Last Billing Reference Number	n 6		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
40	Current Billing Type	an 2		
41	Customer Billpay File Maintenance Tag	an 75		
41.1	Group Number	n 5		
41.2	User Number	n 5		
41.3	Terminal Name	an 24		
41.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.6	Reserved	an 1		
42	Personal ID	an 28		
43	Version	n 4		
44	FIID	an 4		
45	Family Name	an 20		
46	Given Name	an 10		
47	Middle Initial	an 1		
48	Family Name Token	an 16		
49	Given Name Token	an 6		
50	Title	an 6		
51	Government ID	an 15		
52	Birth Date (YYYYMMDD)	n 8		
53	Address 1	an 30		
54	Address 2	an 30		
55	Address 3	an 30		
56	City	an 25		
57	State	an 2		
58	Country Code	an 3		
59	Postal Code	an 10		
60	Language Indicator	n 2		
61	Phone: Home	an 20		
62	Phone: Work	an 20		
63	Phone: Other 1	an 20		
64	Phone: Other 1 Description	an 10		
65	Phone: Other 2	an 20		
66	Phone: Other 2 Description	an 10		
67	Mother's Maiden Name	an 20		
68	Personal File Maintenance Tag	an 75		
68.1	Group Number	n 5		
68.2	User Number	n 5		
68.3	Terminal Name	an 24		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
68.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
68.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
68.6	Reserved	an 1		
69	Default Account Type Description	an 6		
70	Service Fee Account Type Description	an 6		

4.2.3. Customer Inquiry: ISO Reversal Format

Customer Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9L0000	9L0000 = customer inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the response, it should be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.2.4. Customer Inquiry: ISO Reversal Response Format

Customer Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9L0000	9L0000 = customer inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the reversal, it should be echoed in the reversal response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.3. Customer Update (9M)

4.3.1. Customer Update: ISO Request Format

The customer update transaction updates customer ID and personal information that resides on the BASE24 database. If the personal ID is not provided in the request, the value of the personal ID is assumed to be the same as the customer ID.

Customer Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9M0000	9M0000 = customer update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	
48.1 Personal ID		an 28		an 28	Personal ID. If blank, the value in field 2 or field 34 is used.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Alternate Contact	an 30		
2	Customer Information: Line1	an 20		
3	Customer Information: Line2	an 20		
4	Customer Information: Line3	an 20		
5	Customer Type	an 2	B or C	C = Consumer B = Business
6	Branch Number	n 4		
7	Default Account Number	an 19		
8	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
9	Default Account Type Description	an 6		If the account type is provided, the account description is not used.
10	Service Fee: Account Number	an 19		
11	Service Fee: Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
12	Service Fee: Account Type Description	an 6		If the account type is provided, the account description is not used.
13	Customer Profile	an 8		
14	Family Name	an 20		
15	Given Name	an 10		
16	Middle Initial	an 1		
17	Title	an 6		
18	Government ID	an 15		
19	Birth Date (YYYYMMDD)	n 8		
20	Address 1	an 30		
21	Address 2	an 30		
22	Address 3	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
23	City	an 25		
24	State	an 2		
25	Country Code	an 3		
26	Postal Code	an 10		
27	Language Indicator	n 2		
28	Phone: Home	an 20		
29	Phone: Work	an 20		
30	Phone: Other 1	an 20		
31	Phone: Other 1 Description	an 10		
32	Phone: Other 2	an 20		
33	Phone: Other 2 Description	an 10		
34	Mother's Maiden Name	an 20		

4.3.2. Customer Update: ISO Response Format

Customer Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9M0000	9M0000 = customer update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the request, it is echoed in the response.
48.1 Personal ID		an 28		an 28	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Version	n 4		
2	FIID	an 4		
3	Customer Profile	an 8		
4	Customer Type	an 2	B or C	C = Consumer B = Business
5	Bad PIN Count	n 4		
6	Customer Verify Flag	an 2	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
7	PIN Offset	an 16		
8	Last Change: Customer Verify Status	n 20	YYYYMMDDhhmmssmmmmmm	
9	Last Change: PIN Offset	n 20	YYYYMMDDhhmmssmmmmmm	
10	PVK Index	an 1		
11	Default Account Number	an 19		
12	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
13	Max Online History Records	n 4		
14	Customer Information: Line1	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
15	Customer Information: Line2	an 20		
16	Customer Information: Line3	an 20		
17	Alternate Contact	an 30		
18	Begin Date	n 8	YYYYMMDD	
19	End Date	n 8	YYYYMMDD	
20	Branch Number	n 4		
21	PIN Change Required	an 1	Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
22	Billing Type	an 2		
23	Packet Status	an 1		
24	Billing Type Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
25	Packet Status Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
26	Billpay Billing Group	an 4		
27	Billpay Transaction Limit	n 12		
28	Customer File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.6	Reserved	an 1		
29	Last Reset Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
30	Service Fee: Account Number	an 19		
31	Service Fee: Account Type	an 2		
32	Reserved	an 1		
33	Number of Cycles	n 5		
34	Next Customer Reference Number	n 6		
35	Billing Group	an 4		
36	Last Customer Vendor Number	n 5		
37	Last Cycle End Date	n 8	YYYYMMDD	
38	Original Billing Type	an 2		
39	Last Billing Reference Number	n 6		
40	Current Billing Type	an 2		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
41	Customer Billpay File Maintenance Tag	an 75		
41.1	Group Number	n 5		
41.2	User Number	n 5		
41.3	Terminal Name	an 24		
41.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.6	Reserved	an 1		
42	Personal ID	an 28		
43	Version	n 4		
44	FIID	an 4		
45	Family Name	an 20		
46	Given Name	an 10		
47	Middle Initial	an 1		
48	Family Name Token	an 16		
49	Given Name Token	an 6		
50	Title	an 6		
51	Government ID	an 15		
52	Birth Date (YYYYMMDD)	n 8		
53	Address 1	an 30		
54	Address 2	an 30		
55	Address 3	an 30		
56	City	an 25		
57	State	an 2		
58	Country Code	an 3		
59	Postal Code	an 10		
60	Language Indicator	n 2		
61	Phone: Home	an 20		
62	Phone: Work	an 20		
63	Phone: Other 1	an 20		
64	Phone: Other 1 Description	an 10		
65	Phone: Other 2	an 20		
66	Phone: Other 2 Description	an 10		
67	Mother's Maiden Name	an 20		
68	Personal File Maintenance Tag	an 75		
68.1	Group Number	n 5		
68.2	User Number	n 5		
68.3	Terminal Name	an 24		
68.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
68.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
68.6	Reserved	an 1		
69	Default Account Type Description	an 6		
70	Service Fee Account Type Description	an 6		

4.3.3. Customer Update: ISO Reversal Format

Customer Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9M0000	9M0000 = customer update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. If this field is present in the original response, it should be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.3.4. Customer Update: ISO Reversal Response Format

Customer Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	9M0000	9M0000 = customer update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. If this field is present in the reversal, it should be echoed in the reversal response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.4. Customer Activate (BB)

4.4.1. Customer Activate: ISO Request Format

The customer activate transaction changes a customer's verify status from initial to verified, sets the begin date for the customer ID to the current calendar date and the end date to the value defined in the default customer data for the customer's financial institution, and sets the timestamp for the customer's verify status to the current calendar date.

Customer Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BB0000	BB0000 = customer activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	Reactivation Allowed by Client	an 1		Y or N	Y = Yes, reactivation is allowed. N = No, reactivation is not allowed.
48.2	Personal ID	an 28		an 28	Optional. If this field is blank, the value in field 2 or field 34 is used.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.4.2. Customer Activate: ISO Response Format

Customer Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BB0000	BB0000 = customer activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field is echoed from the request.
48.1 Reactivation Allowed by Client		an 1		Y or N	Y = Yes, reactivation is allowed. N = No, reactivation is not allowed.
48.2 Personal ID		an 28		an 28	Optional. If this field is blank, the value in field 2 or field 34 is used.
48.3 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Version	n 4		
2	FIID	an 4		
3	Customer Profile	an 8		
4	Customer Type	an 2	B or C	C = Consumer B = Business
5	Bad PIN Count	n 4		
6	Customer Verify Flag	an 2	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
7	PIN Offset	an 16		
8	Last Change: Customer Verify Status	n 20	YYYYMMDDhhmmssmmmmmmmm	
9	Last Change: PIN Offset	n 20	YYYYMMDDhhmmssmmmmmmmm	
10	PVK Index	an 1		
11	Default Account Number	an 19		
12	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13	Max Online History Records	n 4		
14	Customer Information: Line1	an 20		
15	Customer Information: Line2	an 20		
16	Customer Information: Line3	an 20		
17	Alternate Contact	an 30		
18	Begin Date	n 8	YYYYMMDD	
19	End Date	n 8	YYYYMMDD	
20	Branch Number	n 4		
21	PIN Change Required	an 1	Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
22	Billing Type	an 2		
23	Packet Status	an 1		
24	Billing Type Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
25	Packet Status Last Change	n 20	YYYYMMDDhhmmssmmmmmm	
26	Billpay Billing Group	an 4		
27	Billpay Transaction Limit	n 12		
28	Customer File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.6	Reserved	an 1		
29	Last Reset Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
30	Service Fee: Account Number	an 19		
31	Service Fee: Account Type	an 2		
32	Reserved	an 1		
33	Number of Cycles	n 5		
34	Next Customer Reference Number	n 6		
35	Billing Group	an 4		
36	Last Customer Vendor Number	n 5		
37	Last Cycle End Date	n 8	YYYYMMDD	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
38	Original Billing Type	an 2		
39	Last Billing Reference Number	n 6		
40	Current Billing Type	an 2		
41	Customer Billpay File Maintenance Tag	an 75		
41.1	Group Number	n 5		
41.2	User Number	n 5		
41.3	Terminal Name	an 24		
41.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
41.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
41.6	Reserved	an 1		
42	Personal ID	an 28		
43	Version	n 4		
44	FIID	an 4		
45	Family Name	an 20		
46	Given Name	an 10		
47	Middle Initial	an 1		
48	Family Name Token	an 16		
49	Given Name Token	an 6		
50	Title	an 6		
51	Government ID	an 15		
52	Birth Date (YYYYMMDD)	n 8		
53	Address 1	an 30		
54	Address 2	an 30		
55	Address 3	an 30		
56	City	an 25		
57	State	an 2		
58	Country Code	an 3		
59	Postal Code	an 10		
60	Language Indicator	n 2		
61	Phone: Home	an 20		
62	Phone: Work	an 20		
63	Phone: Other 1	an 20		
64	Phone: Other 1 Description	an 10		
65	Phone: Other 2	an 20		
66	Phone: Other 2 Description	an 10		
67	Mother's Maiden Name	an 20		
68	Personal File Maintenance Tag	an 75		
68.1	Group Number	n 5		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
68.2	User Number	n 5		
68.3	Terminal Name	an 24		
68.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
68.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
68.6	Reserved	an 1		
69	Default Account Type Description	an 6		
70	Service Fee Account Type Description	an 6		

4.4.3. Customer Activate: ISO Reversal Format

Customer Activate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BB0000	BB0000 = customer activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.4.4. Customer Activate: ISO Reversal Response Format

Customer Activate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BB0000	BB0000 = customer activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.5. Customer Deactivate (BC)

4.5.1. Customer Deactivate: ISO Request Format

The customer deactivate transaction sets the end date for the customer ID to the current calendar date minus one, thereby effectively removing the customer from service.

Customer Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BC0000	BC0000 = customer deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	O	ans...200	Additional data. If this field is not present, the value in field 2 or field 34 is used.
48.1	Personal ID	an 28		an 28	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.5.2. Customer Deactivate: ISO Response Format

Customer Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BC0000	BC0000 = customer deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the request, it is echoed in the response.
48.1 Personal ID		an 28		an 28	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Version	n 4		
2	FIID	an 4		
3	Customer Profile	an 8		
4	Customer Type	an 2	B or C	C = Consumer B = Business
5	Bad PIN Count	n 4		
6	Customer Verify Flag	an 2	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
7	PIN Offset	an 16		
8	Last Change: Customer Verify Status	n 20	YYYYMMDDhhmmssmmmmmm	
9	Last Change: PIN Offset	n 20	YYYYMMDDhhmmssmmmmmm	
10	PVK Index	an 1		
11	Default Account Number	an 19		
12	Default Account Type	an 2		If an account number is not assigned, the account type fields should be filled in with a value of 00 (i.e., an account type of NONE). Either the account type or the account description can be provided for the account.
13	Max Online History Records	n 4		
14	Customer Information: Line1	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
15	Customer Information: Line2	an 20		
16	Customer Information: Line3	an 20		
17	Alternate Contact	an 30		
18	Begin Date	n 8	YYYYMMDD	
19	End Date	n 8	YYYYMMDD	
20	Branch Number	n 4		
21	PIN Change Required	an 1	Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
22	Billing Type	an 2		
23	Packet Status	an 1		
24	Billing Type Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
25	Packet Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
26	Billpay Billing Group	an 4		
27	Billpay Transaction Limit	n 12		
28	Customer File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
28.6	Reserved	an 1		
29	Last Reset Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
30	Service Fee: Account Number	an 19		
31	Service Fee: Account Type	an 2		
32	Reserved	an 1		
33	Number of Cycles	n 5		
34	Next Customer Reference Number	n 6		
35	Billing Group	an 4		
36	Last Customer Vendor Number	n 5		
37	Last Cycle End Date	n 8	YYYYMMDD	
38	Original Billing Type	an 2		
39	Last Billing Reference Number	n 6		
40	Current Billing Type	an 2		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
41	Customer Billpay File Maintenance Tag	an 75		
41.1	Group Number	n 5		
41.2	User Number	n 5		
41.3	Terminal Name	an 24		
41.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
41.6	Reserved	an 1		
42	Personal ID	an 28		
43	Version	n 4		
44	FIID	an 4		
45	Family Name	an 20		
46	Given Name	an 10		
47	Middle Initial	an 1		
48	Family Name Token	an 16		
49	Given Name Token	an 6		
50	Title	an 6		
51	Government ID	an 15		
52	Birth Date (YYYYMMDD)	n 8		
53	Address 1	an 30		
54	Address 2	an 30		
55	Address 3	an 30		
56	City	an 25		
57	State	an 2		
58	Country Code	an 3		
59	Postal Code	an 10		
60	Language Indicator	n 2		
61	Phone: Home	an 20		
62	Phone: Work	an 20		
63	Phone: Other 1	an 20		
64	Phone: Other 1 Description	an 10		
65	Phone: Other 2	an 20		
66	Phone: Other 2 Description	an 10		
67	Mother's Maiden Name	an 20		
68	Personal File Maintenance Tag	an 75		
68.1	Group Number	n 5		
68.2	User Number	n 5		
68.3	Terminal Name	an 24		
68.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
68.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
68.6	Reserved	an 1		
69	Default Account Type Description	an 6		
70	Service Fee Account Type Description	an 6		

4.5.3. Customer Deactivate: ISO Reversal Format

Customer Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BC0000	BC0000 = customer deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the response, it should be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.5.4. Customer Deactivate: ISO Reversal Response Format

Customer Deactivate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Used if field 34 is not used.
3	Processing Code	an 6	M	BC0000	BC0000 = customer deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200		ans...200	Additional data. If this field is present in the reversal, it should be echoed in the reversal response.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.6. Customer Account Add (B5)

4.6.1. Customer Account Add: ISO Request Format

The customer account add transaction adds a new customer account to the BASE24 Remote Banking database.

Customer Account Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B50000	B50000 = customer account add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	Account Number	an 19		an 19	Account number being added.
48.2	Account Type	an 2		an 2	Account type of account being added.
48.3	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Account Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
2	Account Qualifier	an 4		
3	Account Description	an 15		
4	Allowed: Debit	an 1	Y or N	Y = Yes N = No
5	Allowed: Credit	an 1	Y or N	Y = Yes N = No
6	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No

4.6.2. Customer Account Add: ISO Response Format

Customer Account Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B50000	B50000 = customer account add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Account Number	an 19		an 19	Account number being added.
48.2	Account Type	an 2		an 2	Account type of account being added.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Account Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	n 19		Account number added
2	Account Type	an 2		Account type
3	Account Qualifier	an 4		
4	FIID	an 4		
5	Status	an 1	0-9, A-Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Version	n 4		
7	Account Description	an 15		
8	Allowed: Debit	an 1	Y or N	Y = Yes N = No
9	Allowed: Credit	an 1	Y or N	Y = Yes N = No
10	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No
11	Begin Date	n 8	YYYYMMDD	
12	End Date	n 8	YYYYMMDD	
13	File Maintenance Tag	an 75		
13.1	Group Number	n 5		
13.2	User Number	n 5		
13.3	Terminal Name	an 24		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.6	Reserved	an 1		
14	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
15	Account Status Description	an 8	INACTV OPEN DEPONLY OPENPRI RSTOPRI CLOSED UNKNOWN	INACTV = Inactive OPEN = Open DEPONLY = Restricted to deposits only OPENPRI = Open primary account RSTOPRI = Primary account restricted to deposits CLOSED = Closed UNKNOWN = Unknown

4.6.3. Customer Account Add: ISO Reversal Format

Customer Account Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B50000	B50000 = customer account add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Account Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.6.4. Customer Account Add: ISO Reversal Response Format

Customer Account Add		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B50000	B50000 = customer account add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.7. Customer Account Activate (B6)

4.7.1. Customer Account Activate: ISO Request Format

The customer account activate transaction allows the customer to activate a customer account after it has been configured for a customer ID. Once activated, the account can be used in transaction processing.

Customer Account Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B60000	B60000 = customer account activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	Account Number	an 19		an 19	Account number being activated.
48.2	Account Type	an 2		an 2	Account type of account being activated.
48.3	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Account Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

4.7.2. Customer Account Activate: ISO Response Format

Customer Account Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B60000	B60000 = customer account activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Account Number	an 19		an 19	Account number being activated.
48.2	Account Type	an 2		an 2	Account type of account being activated.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Account Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	n 19		Account number activated
2	Account Type	an 2		Account type
3	Account Qualifier	an 4		
4	FIID	an 4		
5	Status	an 1	0-9, A-Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Version	n 4		
7	Account Description	an 15		
8	Allowed: Debit	an 1	Y or N	Y = Yes N = No
9	Allowed: Credit	an 1	Y or N	Y = Yes N = No
10	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No
11	Begin Date	n 8	YYYYMMDD	
12	End Date	n 8	YYYYMMDD	
13	File Maintenance Tag	an 75		
13.1	Group Number	n 5		
13.2	User Number	n 5		
13.3	Terminal Name	an 24		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.6	Reserved	an 1		
14	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
15	Account Status Description	an 8	INACTV OPEN DEPONLY OPENPRI RSTOPRI CLOSED UNKNOWN	INACTV = Inactive OPEN = Open DEPONLY = Restricted to deposits only OPENPRI = Open primary account RSTOPRI = Primary account restricted to deposits CLOSED = Closed UNKNOWN = Unknown

4.7.3. Customer Account Activate: ISO Reversal Format

Customer Account Activate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B60000	B60000 = customer account activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.7.4. Customer Account Activate: ISO Reversal Response Format

Customer Account Activate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B60000	B60000 = customer account activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.8. Customer Account Deactivate (B7)

4.8.1. Customer Account Deactivate: ISO Request Format

The customer account deactivate transaction allows the customer to deactivate a customer account after it has been configured for a customer ID. Once deactivated, the account cannot be used in transaction processing.

Customer Account Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B70000	B70000 = customer account deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 Account Number		an 19		an 19	Account number being deactivated.
48.2 Account Type		an 2		an 2	Account type of account being deactivated.
48.3 Reserved		an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Account Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

4.8.2. Customer Account Deactivate: ISO Response Format

Customer Account Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B70000	B70000 = customer account deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Account Number	an 19		an 19	Account number being deactivated.
48.2	Account Type	an 2		an 2	Account type of account being deactivated.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Account Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	n 19		Account number activated
2	Account Type	an 2		Account type
3	Account Qualifier	an 4		
4	FIID	an 4		
5	Status	an 1	0–9, A–Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Version	n 4		
7	Account Description	an 15		
8	Allowed: Debit	an 1	Y or N	Y = Yes N = No
9	Allowed: Credit	an 1	Y or N	Y = Yes N = No
10	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No
11	Begin Date	n 8	YYYYMMDD	
12	End Date	n 8	YYYYMMDD	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13	File Maintenance Tag	an 75		
13.1	Group Number	n 5		
13.2	User Number	n 5		
13.3	Terminal Name	an 24		
13.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.6	Reserved	an 1		
14	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
15	Account Status Description	an 8	INACTV OPEN DEPONLY OPENPRI RSTOPRI CLOSED UNKNOWN	INACTV = Inactive OPEN = Open DEPONLY = Restricted to deposits only OPENPRI = Open primary account RSTOPRI = Primary account restricted to deposits CLOSED = Closed UNKNOWN = Unknown

4.8.3. Customer Account Deactivate: ISO Reversal Format

Customer Account Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B70000	B70000 = customer account deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Account Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.8.4. Customer Account Deactivate: ISO Reversal Response Format

Customer Account Deactivate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B70000	B70000 = customer account deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.9. Customer Account Delete (B8)

4.9.1. Customer Account Delete: ISO Request Format

The customer account delete transaction allows the customer to delete a customer account that is associated with a customer ID from the database. Once the account is deleted, it can no longer be used in transaction processing.

Customer Account Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B80000	B80000 = customer account delete.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 Account Number		an 19		an 19	Account number being deleted.
48.2 Account Type		an 2		an 2	Account type of account being deleted.
48.3 Reserved		an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Account Delete		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

4.9.2. Customer Account Delete: ISO Response Format

Customer Account Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B80000	B80000 = customer account delete.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Account Number	an 19		an 19	Account number being deleted.
48.2	Account Type	an 2		an 2	Account type of account being deleted.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Account Delete		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	n 19		Account number activated
2	Account Type	an 2		Account type
3	Account Qualifier	an 4		
4	FIID	an 4		
5	Status	an 1	0-9, A-Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Version	n 4		
7	Account Description	an 15		
8	Allowed: Debit	an 1	Y or N	Y = Yes N = No
9	Allowed: Credit	an 1	Y or N	Y = Yes N = No
10	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No
11	Begin Date	n 8	YYYYMMDD	
12	End Date	n 8	YYYYMMDD	
13	File Maintenance Tag	an 75		
13.1	Group Number	n 5		
13.2	User Number	n 5		
13.3	Terminal Name	an 24		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
13.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
13.6	Reserved	an 1		
14	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
15	Account Status Description	an 8	INACTV OPEN DEPONLY OPENPRI RSTOPRI CLOSED UNKNOWN	INACTV = Inactive OPEN = Open DEPONLY = Restricted to deposits only OPENPRI = Open primary account RSTOPRI = Primary account restricted to deposits CLOSED = Closed UNKNOWN = Unknown

4.9.3. Customer Account Delete: ISO Reversal Format

Customer Account Delete		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B80000	B80000 = customer account delete.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.9.4. Customer Account Delete: ISO Reversal Response Format

Customer Account Delete		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B80000	B80000 = customer account delete.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.10. Customer Account Update (B9)

4.10.1. Customer Account Update: ISO Request Format

The customer account update transaction updates an existing customer account at any time, as long as the customer verify status is verified. The information that can be updated includes the following:

- Account qualifier
- Debit allowed flag
- Credit allowed flag
- Inquiry allowed flag
- Account description

Customer Account Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B90000	B90000 = customer account update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	Account Number	an 19		an 19	Account number being updated.

Customer Account Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2 Account Type		an 2		an 2	Account type of account being updated.
48.3 Reserved		an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Qualifier	an 4		
2	Account Description	an 15		
3	Allowed: Debit	an 1	Y or N	Y = Yes N = No
4	Allowed: Credit	an 1	Y or N	Y = Yes N = No
5	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No

4.10.2. Customer Account Update: ISO Response Format

Customer Account Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B90000	B90000 = customer account update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1	Account Number	an 19		an 19	Account number being updated.
48.2	Account Type	an 2		an 2	Account type of account being updated.
48.3	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Account Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Account Number	n 19		Account number added
2	Account Type	an 2		Account type
3	Account Qualifier	an 4		
4	FIID	an 4		
5	Status	an 1	0–9, A–Z	The current status of the account. 0, A, B, C = Inactive 1, D, E, F, G, H, I = Open 2, J, K, L = Restricted to deposits 3, M, N, O, P, Q, R = Open primary 4, S, T, U = Restricted primary 9, V, W, X, Y, Z = Closed
6	Version	n 4		
7	Account Description	an 15		
8	Allowed: Debit	an 1	Y or N	Y = Yes N = No
9	Allowed: Credit	an 1	Y or N	Y = Yes N = No
10	Allowed: Inquiry	an 1	Y or N	Y = Yes N = No
11	Begin Date	n 8	YYYYMMDD	
12	End Date	n 8	YYYYMMDD	
13	File Maintenance Tag	an 75		
13.1	Group Number	n 5		
13.2	User Number	n 5		
13.3	Terminal Name	an 24		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
13.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
13.6	Reserved	an 1		
14	Account Type Description	an 6		If field 48 contains the account type, this field is not used. If the account type is not included in field 48, this field is used.
15	Account Status Description	an 8	INACTV OPEN DEPONLY OPENPRI RSTOPRI CLOSED UNKNOWN	INACTV = Inactive OPEN = Open DEPONLY = Restricted to deposits only OPENPRI = Open primary account RSTOPRI = Primary account restricted to deposits CLOSED = Closed UNKNOWN = Unknown

4.10.3. Customer Account Update: ISO Reversal Format

Customer Account Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B90000	B90000 = customer account update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

4.10.4. Customer Account Update: ISO Reversal Response Format

Customer Account Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B90000	B90000 = customer account update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

4.11. Customer Verify (BF)

4.11.1. Customer Verify: ISO Request Format

The customer verify transaction provides a customer, customer service representative, or branch employee the ability to review customer specific information to confirm if the customer selected is the correct customer. A customer ID, customer name, or customer account number is required in a customer verification request. If the customer cannot be determined from the information provided in the request because there is more than one customer who fits the criteria provided, or if a customer name is provided, a customer select transaction may be required to select the customer.

Customer Verify		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
3	Processing Code	an 6	M	BF0000	BF0000 = customer verify.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
24	Function Code	n 3	M	n 3	Function code.
125	Customer Verify Request Data	ans ...998	M	ans ...998	
125.1 Search Indicator		an 1		C, A or N	Required field. Valid values are: C = Customer ID A = Account number N = Name
125.2 Reserved		an 1		an 1	
125.3 Search: PAN (Customer ID)		an 28		an 28	
125.4 Search: Account Number		an 28		an 28	
125.5 Search: Family Name		an 20		an 20	If search is by name, Family Name must be entered at a minimum
125.6 Search: Given Name		an 10		an 10	If entered, Family Name must be entered also.
125.7 Search: Middle Initial		an 1		an 1	If entered, Family and Given name must be entered also.
125.8 Reserved		an 1		an 1	

4.11.2. Customer Verify: ISO Response Format

Customer Verify		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
3	Processing Code	an 6	M	BF0000	BF0000 = customer verify.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhhmmss	The BASE24 date and time of transaction initiation.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
39	Action Code	n 3	M	n 3	Action code. Refer to the <i>BASE24 Remote Banking Transaction Processing Manual</i> for valid action codes.
125	Customer Verify Response Data	ans ...998	C	ans ...998	
125.1	FIID Name	an 22			
125.2	Search: PAN (Customer ID)	an 28		an 28	
125.3	Search: Family Name	an 20		an 20	
125.4	Search: Given Name	an 10		an 10	
125.5	Search: Middle Initial	an 1		an 1	
125.6	Reserved	an 1		an 1	
125.7	Customer Information 1	an 20		an 20	
125.8	Customer Information 2	an 20		an 20	
125.9	Customer Information 3	an 20		an 20	
125.10	Personal ID	an 28		an 28	
125.11	Title	an 6		an 6	
125.12	Name: Family	an 20		an 20	
125.13	Name: Given	an 10		an 10	
125.14	Name: Middle Initial	an 1		an 1	
125.15	Government ID	an 15		an 15	
125.16	Date of Birth	n 8		YYYYMMDD	
125.17	Address 1	an 30		an 30	
125.18	Address 2	an 30		an 30	
125.19	Address 3	an 30		an 30	
125.20	City	an 25		an 25	
125.21	State	an 2		an 2	
125.22	Country Code	an 3		an 3	
125.23	Postal Code	an 10		an 10	
125.24	Phone: Home	an 20		an 20	
125.25	Phone: Work	an 20		an 20	

Customer Verify		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
125.26	Phone: Other 1	an 20		an 20	
125.27	Phone: Other 1 Description	an 10		an 10	
125.28	Phone: Other 2	an 20		an 20	
125.29	Phone: Other 2 Description	an 10		an 10	
125.30	Mother's Maiden Name	an 20		an 20	
125.31	Language Indicator	n 2		n 2	
125.32	PIN Required at CSR	an 1		Y or N	Y = Yes N = No
125.33	PIN Change Allowed at CSR	an 1		Y or N	Y = Yes N = No
125.34	PIN Change Required	an 1		Y or N	Y = Yes, PIN change is required. N = No, PIN change is not required.
125.35	Reserved	an 1		an 1	
125.36	Customer Type	an 2		B or C	C = Consumer B = Business
125.37	Verify flag	an 2		I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
125.38	MAS Display Options	n 1		n 1	
125.39	Reserved	an 1		an 1	
125.40	Route Profile	an 8		an 8	
125.41	FIID	an 4		an 4	

4.12. Customer Select (BG)

4.12.1. Customer Select: ISO Request Format

The customer select transaction allows customers to select a particular person or customer ID when more than one person is configured for the customer ID provided in a customer verification request or when the full or partial customer name is provided in the customer verification request.

Customer Select		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
3	Processing Code	an 6	M	BG0000	BG0000 = customer select.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
24	Function Code	n 3	M	n 3	Function code.
125	Customer Select Request Data	ans ...998	M	ans ...998	
125.1 Select Index		an 2		“ ”	“ ” = spaces.
125.2 Private Data 1		an 118		an 118	
125.3 Customer Count		n 2		1–6	
125.4 More Indicator		an 3		972 or 973	972 = No more customer or personal IDs 973 = More customer or personal IDs
125.5 Reserved		an 1		an 1	
125.6 Private Data 1		an 20		an 20	
125.7 Customer Information Structure		Var-> 840		Var -> 840	See Customer Information structure below.

Customer Information Structure		The following structure can occur up to six times:			
#	Name	ISO Format	Format	Comment	
1	Customer ID	an 28			
2	Personal ID	an 28			
3	Name: Family	an 20			
4	Name: Given	an 10			
5	Name: Middle Initial	an 1			
6	ID Type	an 2	CU	CU = Customer Table	
7	Address 1	an 30			
8	Home Phone	an 20			
9	Reserved	an 1			

4.12.2. Customer Select: ISO Response Format

Customer Select		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
3	Processing Code	an 6	M	BG0000	BG0000 = customer select.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
39	Action Code	n 3	M	n 3	Should be set to 000.
125	Customer Verify Response Data	ans ...998	C	ans ...998	
125.1	Select Index	an 2		“ ” or 1–6	“ ” = spaces.
125.2	Private Data 1	an 118		an 118	
125.3	Customer Count	n 2		1–6	
125.4	More Indicator	an 3		972 or 973	972 = No more customer IDs or personal IDs 973 = More customer IDs or personal IDs
125.5	Reserved	an 1		an 1	
125.6	Private Data 1	an 20		an 20	
125.7	Customer Information Structure	Var-> 840		Var -> 840	See Customer Information structure below.

Customer Information Structure		The following structure can occur up to six times:			
#	Name	ISO Format	Format	Comment	
1	Customer ID	an 28			
2	Personal ID	an 28			
3	Name: Family	an 20			
4	Name: Given	an 10			
5	Name: Middle Initial	an 1			
6	ID Type	an 2	CU	CU = Customer Table	
7	Address 1	an 30			
8	Home Phone	an 20			
9	Reserved	an 1			

ACI Worldwide Inc.

.

5. Vendor Management Messages

5.1. Customer Vendor Add (9N)

5.1.1. Customer Vendor Add: ISO Request Format

The customer vendor add transaction adds a customer vendor to a customer's vendor list at any time, regardless of the customer's verify status.

Customer Vendor Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9N0000	9N0000 = customer vendor add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

Customer Vendor Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Vendor Name	an 30		Either the Vendor Name or Vendor Number field should be present, but not both.
2	Vendor Number	n 9		Either the Vendor Name or Vendor Number field should be present, but not both. If the Vendor Number field contains a nonzero value, it is considered present.
3	Vendor User Remit Information 1	an 20		
4	Vendor User Remit Information 2	an 20		
5	Vendor Branch Name	an 30		Either the Vendor Branch Number or Vendor Branch Name fields (Name, Address 1, Address 2, City, State, Postal Code, Phone Number, Customer Account With Vendor) should be present. If the Vendor Branch Name fields are present, the Vendor Branch Table (VNDB) is read by Vendor Branch Name, Address 1, and Address 2 key. If a vendor branch is not found with that key data, it is added.
6	Vendor Branch Number	n 4		Either the Vendor Branch Number or Vendor Branch Name fields (Name, Address 1, Address 2, City, State, Postal Code, Phone Number, Customer Account With Vendor) should be present. If the the Vendor Branch Number field contains a nonzero value, it is considered present.
7	Address 1	an 30		
8	Address 2	an 30		If the Vendor Branch Name fields are present, only the Address 2 and Phone Number fields are optional.
9	City	an 25		
10	State	an 2		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11	Postal Code	an 10		
12	Phone Number	an 20		If the Vendor Branch Name fields are present, only the Address 2 and Phone Number fields are optional.
13	Vendor Branch User Remit Information 1	an 20		
14	Vendor Branch User Remit Information 2	an 20		
15	Customer Account with Vendor	an 28		
16	Customer Vendor Short Name	an 10		
17	Customer Vendor User Information 1	an 20		
18	Customer Vendor User Information 2	an 20		
19	Budget Category	an 4		

5.1.2. Customer Vendor Add: ISO Response Format

Customer Vendor Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9N0000	9N0000 = customer vendor add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Vendor Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Customer Vendor Number	n 5		
2	Account with Vendor	an 28		
3	Account Verify	an 1	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
4	Account Verify Last Change date	n 20	YYYYMMDDhhmm mssmmmmmm	
5	Customer Vendor Begin Date	n 8	YYYYMMDD	
6	Customer Vendor End Date	n 8	YYYYMMDD	
7	Budget Category	an 4		
8	Customer Vendor Short Name	an 10		
9	User Information 1	an 20		
10	User Information 2	an 20		
11	Customer Vendor File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.6	Reserved	an 1		
12	Vendor Name	an 30		
13	Main Branch Number	n 4		
14	Remit Branch Number	n 4		
15	Remit Person	an 22		
16	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V = Verified W = Waiting for ACH prenotification All other values are user defined.
17	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	
18	Verify Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
19	Vendor Begin Date	n 8	YYYYMMDD	
20	Vendor End Date	n 8	YYYYMMDD	
21	Government ID	an 15		
22	Institution ID	an 11		
23	Account Number	an 19		
24	Account Type	an 2		
25	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
26	Remit Report Type	an 2		
27	Default Budget Type	an 4		
28	Audio Token	an 20		
29	Warning Payment Limit Amount	n 20		
30	Vendor Mask Group	an 4		
31	Vendor Type	an 1	P, or L	P = Public L = Limited
32	Vendor Type Description	an 7	Public Limited	
33	Prenote Date	n 8	YYYYMMDD	
34	Vendor Specific data Type	an 2		
35	Vendor Specific data Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
36	Vendor User Remit Information 1	an 20		
37	Vendor User Remit Information 2	an 20		
38	Category Code	an 4		
39	Vendor File Maintenance Tag	an 75		
39.1	Group Number	n 5		
39.2	User Number	n 5		
39.3	Terminal Name	an 24		
39.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.6	Reserved	an 1		
40	Reserved	an 1		
41	Vendor Number	n 9		
42	Vendor Branch Number	n 4		
43	Vendor Branch Name	an 30		
44	Address 1	an 30		
45	Address 2	an 30		
46	City	an 25		
47	State	an 2		
48	Postal Code	an 10		
49	County	an 3		
50	Country	an 3		
51	Phone number	an 20		
52	Contact Person	an 22		
53	Fax Phone	an 20		
54	Company Phone Number	an 20		
55	Mask Group	an 4		
56	Vendor Branch User Remit Information 1	an 20		
57	Vendor Branch User Remit Information 2	an 20		
58	Vendor Branch File Maintenance Tag	an 75		
58.1	Group Number	n 5		
58.2	User Number	n 5		
58.3	Terminal Name	an 24		
58.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.6	Reserved	an 1		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
59	Customer Vendor Budget Category Description	an 30		
60	Vendor Default Budget Category Description	an 30		

5.1.3. Customer Vendor Add: ISO Reversal Format

Customer Vendor Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9N0000	9N0000 = customer vendor add.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

Customer Vendor Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.1.4. Customer Vendor Add: ISO Reversal Response Format

Customer Vendor Add		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9N0000	9N0000 = customer vendor add.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.2. Customer Vendor Update (9Q)

5.2.1. Customer Vendor Update: ISO Request Format

The customer vendor update transaction serves two purposes—updating customer vendor information or updating vendor information. Only one customer vendor relationship can be updated in each transaction. See the ***BASE24 Remote Banking Standard Interface Support Manual*** for details of what fields can be updated for limited or public vendors.

Customer Vendor Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Q0000	9Q0000 = customer vendor update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	Customer Vendor Number	n 5		n 5	The customer vendor number being updated.
48.2	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Vendor Update		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	M	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Vendor Name	an 30		
2	Update Vendor User Info	an 1	Y or N	Y = Yes, update vendor user information. N = No, do not update vendor user information.
3	Vendor User Remit Info 1	an 20		
4	Vendor User Remit Info 2	an 20		
5	Vendor Branch Name	an 30		Either the Vendor Branch Number or Vendor Branch Name fields (Name, Address 1 -> Phone Number, Customer Account with Vendor) should be present. If the Vendor Branch Name fields are present, the Vendor Branch Table is read by a Vendor Branch Name, Address 1, Address 2 key. If a vendor branch is not found with that key data, it is added and Customer Vendor Table is updated with the vendor branch number.
6	Vendor Branch Number	n 4		Either the Vendor Branch Number or Vendor Branch Name fields (Name, Address 1 -> Phone Number, Customer Account with Vendor) should be present. If the Vendor Branch Number field contains a nonzero value, it is present. See the BASE24 Remote Banking Standard Interface Support Manual for more restrictions.
7	Address 1	an 30		
8	Address 2	an 30		If the Vendor Branch Name fields are present, only the Address 2 and Phone Number fields are optional.
9	City	an 25		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
10	State	an 2		
11	Postal Code	an 10		
12	Phone Number	an 20		If the Vendor Branch Name fields are present, only the Address 2 and Phone Number fields are optional.
13	Update Vendor Branch User Information	an 1	Y or N	Y = Yes, update vendor user information. N = No, do not update vendor user information.
14	Vendor Branch User Remit Information 1	an 20		
15	Vendor Branch User Remit Information 2	an 20		
16	Customer Account with Vendor	an 28		
17	Customer Vendor Short Name	an 10		
18	Customer Vendor User Information 1	an 20		
19	Customer Vendor User Information 2	an 20		
20	Budget Category	an 4		

5.2.2. Customer Vendor Update: ISO Response Format

Customer Vendor Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Q0000	9Q0000 = customer vendor update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1 Customer Vendor Number		n 5		n 5	Customer vendor number being updated.
48.2 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Vendor Update		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Customer Vendor Number	n 5		
2	Account with Vendor	an 28		
3	Account Verify	an 1	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
4	Account Verify Last Change date	n 20	YYYYMMDDhhmmssmmmmmm	
5	Customer Vendor Begin Date	n 8	YYYYMMDD	
6	Customer Vendor End Date	n 8	YYYYMMDD	
7	Budget Category	an 4		
8	Customer Vendor Short Name	an 10		
9	User Information 1	an 20		
10	User Information 2	an 20		
11	Customer Vendor File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.6	Reserved	an 1		
12	Vendor Name	an 30		
13	Main Branch Number	n 4		
14	Remit Branch Number	n 4		
15	Remit Person	an 22		
16	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V = Verified W = Waiting for ACH prenotification All other values are user defined.
17	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	
18	Verify Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
19	Vendor Begin Date	n 8	YYYYMMDD	
20	Vendor End Date	n 8	YYYYMMDD	
21	Government ID	an 15		
22	Institution ID	an 11		
23	Account Number	an 19		
24	Account Type	an 2		
25	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
26	Remit Report Type	an 2		
27	Default Budget Type	an 4		
28	Audio Token	an 20		
29	Warning Payment Limit Amount	n 20		
30	Vendor Mask Group	an 4		
31	Vendor Type	an 1	P, or L	P = Public L = Limited
32	Vendor Type Description	an 7	Public Limited	
33	Prenote Date	n 8	YYYYMMDD	
34	Vendor Specific data Type	an 2		
35	Vendor Specific data Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
36	Vendor User Remit Information 1	an 20		
37	Vendor User Remit Information 2	an 20		
38	Category Code	an 4		
39	Vendor File Maintenance Tag	an 75		
39.1	Group Number	n 5		
39.2	User Number	n 5		
39.3	Terminal Name	an 24		
39.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.6	Reserved	an 1		
40	Reserved	an 1		
41	Vendor Number	n 9		
42	Vendor Branch Number	n 4		
43	Vendor Branch Name	an 30		
44	Address 1	an 30		
45	Address 2	an 30		
46	City	an 25		
47	State	an 2		
48	Postal Code	an 10		
49	County	an 3		
50	Country	an 3		
51	Phone number	an 20		
52	Contact Person	an 22		
53	Fax Phone	an 20		
54	Company Phone Number	an 20		
55	Mask Group	an 4		
56	Vendor Branch User Remit Information 1	an 20		
57	Vendor Branch User Remit Information 2	an 20		
58	Vendor Branch File Maintenance Tag	an 75		
58.1	Group Number	n 5		
58.2	User Number	n 5		
58.3	Terminal Name	an 24		
58.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.6	Reserved	an 1		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
59	Customer Vendor Budget Category Description	an 30		
60	Vendor Default Budget Category Description	an 30		

5.2.3. Customer Vendor Update: ISO Reversal Format

Customer Vendor Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Q0000	9Q0000 = customer vendor update.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

Customer Vendor Update		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.2.4. Customer Vendor Update: ISO Reversal Response Format

Customer Vendor Update		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9Q0000	9Q0000 = customer vendor update.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.3. Customer Vendor Activate (BD)

5.3.1. Customer Vendor Activate: ISO Request Format

The customer vendor activate transaction allows the customer to activate a customer vendor after it has been configured for a customer ID. Once activated, the customer vendor can be used in transaction processing. The customer vendor activate transaction can be performed if the customer vendor has a verify status of either verified or initial.

Customer Vendor Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BD0000	BD0000 = customer vendor activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 Customer Vendor Number		n 5		n 5	Customer vendor number being activated.
48.2 Reserved		an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Vendor Activate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.3.2. Customer Vendor Activate: ISO Response Format

Customer Vendor Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BD0000	BD0000 = customer vendor activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1 Customer Vendor Number		n 5		n 5	Customer vendor number being activated.
48.2 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Vendor Activate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Customer Vendor Number	n 5		
2	Account with Vendor	an 28		
3	Account Verify	an 1	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
4	Account Verify Last Change date	n 20	YYYYMMDDhhmmssmmmmmm	
5	Customer Vendor Begin Date	n 8	YYYYMMDD	
6	Customer Vendor End Date	n 8	YYYYMMDD	
7	Budget Category	an 4		
8	Customer Vendor Short Name	an 10		
9	User Information 1	an 20		
10	User Information 2	an 20		
11	Customer Vendor File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
11.6	Reserved	an 1		
12	Vendor Name	an 32		
13	Main Branch Number	n 4		
14	Remit Branch Number	n 4		
15	Remit Person	an 22		
16	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V = Verified W = Waiting for ACH prenotification All other values are user defined.
17	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	
18	Verify Status Last Change	n 20	YYYYMMDDhhmmssmmmmmmmm	
19	Vendor Begin Date	n 8	YYYYMMDD	
20	Vendor End Date	n 8	YYYYMMDD	
21	Government ID	an 15		
22	Institution ID	an 11		
23	Account Number	an 19		
24	Account Type	an 2		
25	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
26	Remit Report Type	an 2		
27	Default Budget Type	an 4		
28	Audio Token	an 20		
29	Warning Payment Limit Amount	n 20		
30	Vendor Mask Group	an 4		
31	Vendor Type	an 1	P, or L	P = Public L = Limited
32	Vendor Type Description	an 7	Public Limited	
33	Prenote Date	n 8	YYYYMMDD	
34	Vendor Specific data Type	an 2		
35	Vendor Specific data Description	an 30		
36	Vendor User Remit Information 1	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
37	Vendor User Remit Information 2	an 20		
38	Category Code	an 4		
39	Vendor File Maintenance Tag	an 75		
39.1	Group Number	n 5		
39.2	User Number	n 5		
39.3	Terminal Name	an 24		
39.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
39.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
39.6	Reserved	an 1		
40	Reserved	an 1		
41	Vendor Number	n 9		
42	Vendor Branch Number	n 4		
43	Vendor Branch Name	an 30		
44	Address 1	an 30		
45	Address 2	an 30		
46	City	an 25		
47	State	an 2		
48	Postal Code	an 10		
49	County	an 3		
50	Country	an 3		
51	Phone number	an 20		
52	Contact Person	an 22		
53	Fax Phone	an 20		
54	Company Phone Number	an 20		
55	Mask Group	an 4		
56	Vendor Branch User Remit Information 1	an 20		
57	Vendor Branch User Remit Information 2	an 20		
58	Vendor Branch File Maintenance Tag	an 75		
58.1	Group Number	n 5		
58.2	User Number	n 5		
58.3	Terminal Name	an 24		
58.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
58.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
58.6	Reserved	an 1		
59	Customer Vendor Budget Category Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
60	Vendor Default Budget Category Description	an 30		

5.3.3. Customer Vendor Activate: ISO Reversal Format

Customer Vendor Activate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BD0000	BD0000 = customer vendor activate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.

Customer Vendor Activate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.3.4. Customer Vendor Activate: ISO Reversal Response Format

Customer Vendor Activate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BD0000	BD0000 = customer vendor activate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.4. Customer Vendor Deactivate (9P)

5.4.1. Customer Vendor Deactivate: ISO Request Format

The customer vendor deactivate transaction sets the end date for a customer vendor to the current calendar date minus one, thereby effectively preventing the customer from sending payments to the vendor.

Customer Vendor Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9P0000	9P0000 = customer vendor deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 Customer Vendor Number		n 5		n 5	Customer vendor number being deactivated.
48.2 Reserved		an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.

Customer Vendor Deactivate		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.4.2. Customer Vendor Deactivate: ISO Response Format

Customer Vendor Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9P0000	9P0000 = customer vendor deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1 Customer Vendor Number		n 5		n 5	Customer vendor number being deactivated.
48.2 Reserved		an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Customer Vendor Deactivate		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Customer Vendor Number	n 5		
2	Account with Vendor	an 28		
3	Account Verify	an 1	I, F, V or other values	I = Initial F = Failed V = Verified All other values are user defined.
4	Account Verify Last Change date	n 20	YYYYMMDDhhmmssmmmmmm	
5	Customer Vendor Begin Date	n 8	YYYYMMDD	
6	Customer Vendor End Date	n 8	YYYYMMDD	
7	Budget Category	an 4		
8	Customer Vendor Short Name	an 10		
9	User Information 1	an 20		
10	User Information 2	an 20		
11	Customer Vendor File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.6	Reserved	an 1		
12	Vendor Name	an 30		
13	Main Branch Number	n 4		
14	Remit Branch Number	n 4		
15	Remit Person	an 22		
16	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V = Verified W = Waiting for ACH prenotification All other values are user defined.
17	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	
18	Verify Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
19	Vendor Begin Date	n 8	YYYYMMDD	
20	Vendor End Date	n 8	YYYYMMDD	
21	Government ID	an 15		
22	Institution ID	an 11		
23	Account Number	an 19		
24	Account Type	an 2		
25	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
26	Remit Report Type	an 2		
27	Default Budget Type	an 4		
28	Audio Token	an 20		
29	Warning Payment Limit Amount	n 20		
30	Vendor Mask Group	an 4		
31	Vendor Type	an 1	P, or L	P = Public L = Limited
32	Vendor Type Description	an 7	Public Limited	
33	Prenote Date	n 8	YYYYMMDD	
34	Vendor Specific data Type	an 2		
35	Vendor Specific data Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
36	Vendor User Remit Information 1	an 20		
37	Vendor User Remit Information 2	an 20		
38	Category Code	an 4		
39	Vendor File Maintenance Tag	an 75		
39.1	Group Number	n 5		
39.2	User Number	n 5		
39.3	Terminal Name	an 24		
39.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
39.6	Reserved	an 1		
40	Reserved	an 1		
41	Vendor Number	n 9		
42	Vendor Branch Number	n 4		
43	Vendor Branch Name	an 30		
44	Address 1	an 30		
45	Address 2	an 30		
46	City	an 25		
47	State	an 2		
48	Postal Code	an 10		
49	County	an 3		
50	Country	an 3		
51	Phone number	an 20		
52	Contact Person	an 22		
53	Fax Phone	an 20		
54	Company Phone Number	an 20		
55	Mask Group	an 4		
56	Vendor Branch User Remit Information 1	an 20		
57	Vendor Branch User Remit Information 2	an 20		
58	Vendor Branch File Maintenance Tag	an 75		
58.1	Group Number	n 5		
58.2	User Number	n 5		
58.3	Terminal Name	an 24		
58.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmmmm	
58.6	Reserved	an 1		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
59	Customer Vendor Budget Category Description	an 30		
60	Vendor Default Budget Category Description	an 30		

5.4.3. Customer Vendor Deactivate: ISO Reversal Format

Customer Vendor Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9P0000	9P0000 = customer vendor deactivate.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Vendor Deactivate		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.4.4. Customer Vendor Deactivate: ISO Reversal Response Format

Customer Vendor Deactivate		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9P0000	9P0000 = customer vendor deactivate.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.5. Customer Vendor Mask Verify Inquiry (BE)

5.5.1. Customer Vendor Mask Verify Inquiry: ISO Request Format

The customer vendor mask verify inquiry transaction provides a list of all the vendor masks associated with a specific vendor and vendor branch.

Customer Vendor Mask Verify Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BE0000	BE0000 = customer vendor mask verify inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	On a continuation request, key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		0 or 1	0 = Initial request 1 = Continuation request
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending

Customer Vendor Mask Verify Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.3	Key Data Type	an 1		0 or 1	0 = Vendor branch by name 1 = Vendor branch by number
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Customer Account with Vendor	an 28		an 28	
48.7	Reserved	an 1		an 1	
48.8	Key Data: Vendor Name	an 30		an 30	Either fields 48.8–48.11 or 48.12–48.14 are present ,depending on the value of field 48. 3 (key data type)
AND 48.9	Key Data: Vendor Branch Name	an 30		an 30	
AND 48.10	Key Data: Address 1	an 30		an 30	
AND 48.11	Key Data: Address 2	an 30		an 30	
OR 48.12	Key Data: Vendor Number	n 9		n 9	
AND 48.13	Key Data: Vendor Branch Number	n 4		n 4	
AND 48.14	Reserved	an 1		an 1	
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.5.2. Customer Vendor Mask Verify Inquiry: ISO Response Format

Customer Vendor Mask Verify Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BE0000	BE0000 = customer vendor mask verify inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. Key data fields will contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0 or 1	0 = Vendor branch by name 1 = Vendor branch by number
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Customer Account with Vendor		an 28		an 28	

Customer Vendor Mask Verify Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.7	Reserved	an 1		an 1	
48.8	Key Data: Vendor Name	an 30		an 30	Either fields 48.8–48.11 or 48.12–48.14 are present ,depending on the value of field 48. 3 (key data type)
AND 48.9	Key Data: Vendor Branch Name	an 30		an 30	
AND 48.10	Key Data: Address 1	an 30		an 30	
AND 48.11	Key Data: Address 2	an 30		an 30	
OR 48.12	Key Data: Vendor Number	n 9		n 9	
AND 48.13	Key Data: Vendor Branch Number	n 4		n 4	
AND 48.14	Reserved	an 1		an 1	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–8	Number of occurrences of vendor mask details returned.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Vendor Mask Response Structure		Occurs as specified by the value of the Count field.		
1	Mask Group	an 4		
2	Account Mask	an 70		
3	User Check Number	n 5		
4	Minimum Length	n 2		
5	Maximum Length	n 2		
6	Help Text	an 312		
7	Comment	an 78		
8	Verification Failed Indicator	n 2	00, 01, 02, 03, 04 or 05	00 = OK 01 = No account 02 = Failed minimum 03 = Failed maximum 04 = Failed mask 05 = Failed user check
9	Reserved	an 1		

5.5.3. Customer Vendor Mask Verify Inquiry: ISO Reversal Format

Customer Vendor Mask Verify Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BE0000	BE0000 = customer vendor mask verify inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Customer Vendor Mask Verify Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25		ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.5.4. Customer Vendor Mask Verify Inquiry: ISO Reversal Response Format

Customer Vendor Mask Verify Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	BE0000	BE0000 = customer vendor mask verify inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.6. Master Vendor List Inquiry (9R)

5.6.1. Master Vendor List Inquiry: ISO Request Format

The master vendor list inquiry is used to determine if a vendor is already included in the BASE24-billpay database.

Master Vendor List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9R0000	9R0000 = master vendor list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, Key data fields will contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates the defaults of 48.2 equals AC, 48.11 equals spaces)
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0	0 = Vendor name

Master Vendor List Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data: List All Branches	an 1		Y or N	Y = Yes N = No
48.7	Filter Data: List Current Vendors	an 1		Y or N	Y = Yes N = No
48.8	Filter Data: List Verified Vendors	an 1		Y or N	Y = Yes N = No
48.9	Filter Data: List Public Vendors	an 1		Y or N	Y = Yes N = No
48.10	Reserved	an 26		an 26	
48.11	Key Data: Vendor Name	an 30		an 30	If key data is present, filter data must be present.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.6.2. Master Vendor List Inquiry: ISO Response Format

Master Vendor List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9R0000	9R0000 = master vendor list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. Key data fields contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0	0 = Vendor name
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data: List All Branches		an 1		Y or N	Y = Yes N = No
48.7 Filter Data: List Current Vendors		an 1		Y or N	Y = Yes N = No
48.8 Filter Data: List Verified Vendors		an 1		Y or N	Y = Yes N = No

Master Vendor List Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.9	Filter Data: List Public Vendors	an 1		Y or N	Y = Yes N = No
48.10	Reserved	an 26		an 26	
48.11	Key Data: Vendor Name	an 30		an 30	If key data is present, filter data must be present.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–5	Number of occurrences of vendor details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
3	Reserved	an 1		
Vendor List Response Structure		Occurs as specified by the value of the Count field.		
1	Vendor Name	an 30		
2	Main Branch Number	n 4		
3	Remit Branch Number	n 4		
4	Remit Person	an 22		
5	Verify Status	an 1	I, F, P, V, W or other values	I = Initial F = Failed verification P = Pending ACH prenotification V = Verified W = Waiting for ACH prenotification All other values are user defined.
6	Verify Status Description	an 10	INITIAL FAILED PEND ACH VERIFIED WAIT ACH USER-DFN	
7	Verify Status Last Change	n 20	YYYYMMDDhhmm mssmmmmmm	
8	Vendor Begin Date	n 8	YYYYMMDD	
9	Vendor End Date	n 8	YYYYMMDD	
10	Government ID	an 15		
11	Institution ID	an 11		
12	Account Number	an 19		
13	Account Type	an 2		
14	Remit Type	an 3	GCP, CIT, ACH or other values	GCP = Group-item check CIT = Single-item check ACH = Automated clearing All other values are user defined.
15	Remit Report Type	an 2		
16	Default Budget Type	an 4		
17	Audio Token	an 20		
18	Warning Payment Limit Amount	n 20		
19	Vendor Mask Group	an 4		
20	Vendor Type	an 1	P, or L	P = Public L = Limited
21	Vendor Type Description	an 7	Public Limited	
22	Prenote Date	n 8	YYYYMMDD	
23	Vendor Specific data Type	an 2		
24	Vendor Specific data Description	an 30		
25	Vendor User Remit Information 1	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
26	Vendor User Remit Information 2	an 20		
27	Category Code	an 4		
28	Vendor File Maintenance Tag	an 75		
28.1	Group Number	n 5		
28.2	User Number	n 5		
28.3	Terminal Name	an 24		
28.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
28.6	Reserved	an 1		
29	Reserved	an 1		
30	Vendor Number	n 9		
31	Vendor Branch Number	n 4		
32	Vendor Branch Name	an 30		
33	Address 1	an 30		
34	Address 2	an 30		
35	City	an 25		
36	State	an 2		
37	Postal Code	an 10		
38	County	an 3		
39	Country	an 3		
40	Phone number	an 20		
41	Contact Person	an 22		
42	Fax Phone	an 20		
43	Company Phone Number	an 20		
44	Mask Group	an 4		
45	Vendor Branch User Remit Information 1	an 20		
46	Vendor Branch User Remit Information 2	an 20		
47	Vendor Branch File Maintenance Tag	an 75		
47.1	Group Number	n 5		
47.2	User Number	n 5		
47.3	Terminal Name	an 24		
47.4	AFT Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
47.5	OLTP Timestamp	n 20	YYYYMMDDhhmmssmmmmmm	
47.6	Reserved	an 1		
48	Customer Vendor Budget Category Description	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
49	Vendor Default Budget Category Description	an 30		

5.6.3. Master Vendor List Inquiry: ISO Reversal Format

Master Vendor List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9R0000	9R0000 = master vendor list inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Master Vendor List Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25		ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

5.6.4. Master Vendor List Inquiry: ISO Reversal Response Format

Master Vendor List Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9R0000	9R0000 = master vendor list inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6. Customer Service Management Messages

6.1. Loan Application (9V)

6.1.1. Loan Application: ISO Request Format

The loan application transaction allows a customer to submit a loan application. The customer does not have to be an existing remote banking customer (i.e., have access to a customer ID).

Loan Application		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	9V0000	9V0000 = loan application.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 FIID		an 4		an 4	

Loan Application		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	Y = External data block present.
	External Data Block	ans4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Family Name	an 20		
2	Given Name	an 10		
3	Middle Initial	an 1		
4	Transaction Source Local Civil Time	n 20		
5	FIID	an 4		
6	Loan Type	an 1		
7	Referred by: Given Name	an 10		
8	Referred by: Family Name	an 20		
9	Amount Requested	n 12		
10	Collateral	an 25		
11	Purpose of Loan	an 60		
12	Number of Dependents	n 2		
13	Ages of Dependents	an 30		
14	Date of Birth	n 8	YYYYMMDD	
15	Government ID	an 15		
16	Home Phone Number	an 20		
17	Married	an 1	Y or N	Y = Yes, married. N = No, not married.
18	Current Address: Line 1	an 30		
19	Current Address: Line 2	an 30		
20	Current Address: City	an 25		
21	Current Address: State	an 2		
22	Current Address: Postal Code	an 10		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
23	Current Address: Years at Address	n 2		
24	Current Address: Own	an 1	Y or N	Y = Yes, own. N = No, do not own.
25	Current Address: Monthly Payment	n 12		
26	Current Address: Name Rent Payments are made to	an 22		
27	Previous Address: Line 1	an 30		
28	Previous Address: Line 2	an 30		
29	Previous Address: City	an 25		
30	Previous Address: State	an 2		
31	Previous Address: Postal Code	an 10		
32	Previous Address: Years at Address	n 2		
33	Previous Address: Own	an 1	Y or N	Y = Yes, own. N = No, do not own.
34	Occupation	an 20		
35	Current Employer: Name	an 22		
36	Current Employer: Address, Line 1	an 30		
37	Current Employer: Address, Line 2	an 30		
38	Current Employer: City	an 25		
39	Current Employer: State	an 2		
40	Current Employer: Postal Code	an 10		
41	Current Employer: Years at	n 2		
42	Current Employer: Monthly Income	n 12		
43	Previous Employer: Name	an 22		
44	Previous Employer: Address, Line 1	an 30		
45	Previous Employer: Address, Line 2	an 30		
46	Previous Employer: City	an 25		
47	Previous Employer: State	an 2		
48	Previous Employer: Postal Code	an 10		
49	Previous Employer: Years at	n 2		
50	Previous Employer: Monthly Income	n 12		
51	Other Source of Income	an 22		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
52	Other Source of Income: Amount	n 12		
53	Judgements	an 1	Y or N	Y = Yes N = No
54	Bankruptcy	an 1	Y or N	Y = Yes N = No
55	Back Taxes	an 1	Y or N	Y = Yes N = No
56	Income reduction	an 1	Y or N	Y = Yes N = No
57	Coapplicant: Given Name	an 10		
58	Coapplicant: Middle Initial	an 1		
59	Coapplicant: Family Name	an 20		
60	Coapplicant: Date of Birth	n 8	YYYYMMDD	
61	Coapplicant: Government ID	an 15		
62	Coapplicant: Home Phone Number	an 20		
63	Coapplicant: Relationship	an 10		
64	Coapplicant: Occupation	an 20		
65	Coapplicant: Current Employer, Name	an 22		
66	Coapplicant: Current Employer, Address, Line 1	an 30		
67	Coapplicant: Current Employer, Address, Line 2	an 30		
68	Coapplicant: Current Employer, City	an 25		
69	Coapplicant: Current Employer, State	an 2		
70	Coapplicant: Current Employer, Postal Code	an 10		
71	Coapplicant: Current Employer, Years at	n 2		
72	Coapplicant: Current Employer, Monthly Income	n 12		
73	Coapplicant: Previous Employer, Name	an 22		
74	Coapplicant: Previous Employer, Address, Line 1	an 30		
75	Coapplicant: Previous Employer, Address, Line 2	an 30		
76	Coapplicant: Previous Employer, City	an 25		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
77	Coapplicant: Previous Employer, State	an 2		
78	Coapplicant: Previous Employer, Postal Code	an 10		
79	Coapplicant: Previous Employer, Years at	n 2		
80	Coapplicant: Previous Employer, Monthly Income	n 12		
81	Coapplicant: Other Source of Income	an 22		
82	Coapplicant: Other Source of Income: Amount	n 12		
83	Institution Info (1): Institution, Name	an 22		
84	Institution Info (2): Institution, Name	an 22		
85	Institution Info (3): Institution, Name	an 22		
86	Institution Info (1): Institution, Account Number	an 19		
87	Institution Info (2): Institution, Account Number	an 19		
88	Institution Info (3): Institution, Account Number	an 19		
89	Institution Info (1): Institution, Account Type	an 2		
90	Institution Info (2): Institution, Account Type	an 2		
91	Institution Info (3): Institution, Account Type	an 2		
92	Institution Info (1): Institution, Account Value	n 12		
93	Institution Info (2): Institution, Account Value	n 12		
94	Institution Info (3): Institution, Account Value	n 12		
95	Institution Info (1): Institution, Address, Line 1	an 30		
96	Institution Info (2): Institution, Address, Line 1	an 30		
97	Institution Info (3): Institution, Address, Line 1	an 30		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
98	Institution Info (1): Institution, Address, Line 2	an 30		
99	Institution Info (2): Institution, Address, Line 2	an 30		
100	Institution Info (3): Institution, Address, Line 2	an 30		
101	Institution Info (1): Institution, City	an 25		
102	Institution Info (2): Institution, City	an 25		
103	Institution Info (3): Institution, City	an 25		
104	Institution Info (1): Institution, State	an 2		
105	Institution Info (2): Institution, State	an 2		
106	Institution Info (3): Institution, State	an 2		
107	Institution Info (1): Institution, Postal Code	an 10		
108	Auto (1): Year	n 4	YYYY	
109	Auto (2): Year	n 4	YYYY	
110	Auto (1): Make	an 20		
111	Auto (2): Make	an 20		
112	Auto (1): Model	an 20		
113	Auto (1): Model	an 20		
114	Residence Purchase Price	n 12		
115	Down Payment	n 12		
116	Life Insurance Value	n 12		
117	Other Property	an 1	Y or N	Y = Yes, other property. N = No, no other property.
118	Other Property Description	an 30		
119	Other assets	an 1	Y or N	Y = Yes, other assets. N = No, no other assets
120	Other Assets Description	an 30		
121	Liability (1): Type	an 20		
122	Liability (2): Type	an 20		
123	Liability (3): Type	an 20		
124	Liability (4): Type	an 20		
125	Liability (5): Type	an 20		
126	Liability (6): Type	an 20		
127	Liability (7): Type	an 20		
128	Liability (8): Type	an 20		
129	Liability (9): Type	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
130	Liability (10): Type	an 20		
131	Liability (11): Type	an 20		
132	Liability (1): Institution Name	an 22		
133	Liability (2): Institution Name	an 22		
134	Liability (3): Institution Name	an 22		
135	Liability (4): Institution Name	an 22		
136	Liability (5): Institution Name	an 22		
137	Liability (6): Institution Name	an 22		
138	Liability (7): Institution Name	an 22		
139	Liability (8): Institution Name	an 22		
140	Liability (9): Institution Name	an 22		
141	Liability (10): Institution Name	an 22		
142	Liability (11): Institution Name	an 22		
143	Liability (1): Amount Owed	n 12		
144	Liability (2): Amount Owed	n 12		
145	Liability (3): Amount Owed	n 12		
146	Liability (4): Amount Owed	n 12		
147	Liability (5): Amount Owed	n 12		
148	Liability (6): Amount Owed	n 12		
149	Liability (7): Amount Owed	n 12		
150	Liability (8): Amount Owed	n 12		
151	Liability (9): Amount Owed	n 12		
152	Liability (10): Amount Owed	n 12		
153	Liability (11): Amount Owed	n 12		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
154	Liability (1): Monthly Payment	n 12		
155	Liability (2): Monthly Payment	n 12		
156	Liability (3): Monthly Payment	n 12		
157	Liability (4): Monthly Payment	n 12		
158	Liability (5): Monthly Payment	n 12		
159	Liability (6): Monthly Payment	n 12		
160	Liability (7): Monthly Payment	n 12		
161	Liability (8): Monthly Payment	n 12		
162	Liability (9): Monthly Payment	n 12		
163	Liability (10): Monthly Payment	n 12		
164	Liability (11): Monthly Payment	n 12		
165	Reserved	an 1		

6.1.2. Loan Application: ISO Response Format

Loan Application		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 34 is not used.
3	Processing Code	an 6	M	9V0000	9V0000 = loan application.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). Can contain zeros, if it does not, this field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	
48.1 FIID		an 4		an 4	
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Loan Application		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.1.3.Loan Application: ISO Reversal Format

Loan Application		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9V0000	9V0000 = loan application.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Loan Application		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.1.4. Loan Application: ISO Reversal Response Format

Loan Application		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9V0000	9V0000 = loan application.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.2. Miscellaneous Request (9W)

6.2.1. Miscellaneous Request: ISO Request Format

The miscellaneous request transaction allows a customer, customer service representative, or branch employee to send a message to a financial institution.

Miscellaneous Request		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9W0000	9W0000 = miscellaneous request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Miscellaneous Request		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	Y = External data block present.
	External Data Block	ans ...4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Family Name	an 20		
2	Given Name	an 10		
3	Phone Number	an 20		
4	Contact Type	an 1	B, C, O or V	B = Bank C = Customer O = Other V = Vendor
5	Priority	n 1	1–5	1 is the highest priority and 5 is the lowest priority.
6	Request Type	an 1	C, Q or A	C = Complaint Q = Question A = Account maintenance
7	Department	an 22		
8	Contact Details	an 624		
9	Reserved	an 1		

6.2.2. Miscellaneous Request: ISO Response Format

Miscellaneous Request		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9W0000	9W0000 = miscellaneous request.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.

Miscellaneous Request		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans ...4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmm mssmmmmmm	
2	Family Name	an 20		
3	Given Name	an 10		
4	Phone Number	an 20		
5	FIID	an 4		
6	Contact Type	an 1	B, C, O or V	B = Bank C = Customer O = Other V = Vendor
7	Priority	n 1	1–5	1 is the highest priority and 5 is the lowest priority.
8	Request Type	an 1	C, Q or A	C = Complaint Q = Question A = Account maintenance
9	Department	an 22		
10	Contact Details	an 624		
11	File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	

External Data Block Structure				
#	Name	ISO Format	Format	Comment
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.6	Reserved	an 1		
12	Reserved	an 1		

6.2.3. Miscellaneous Request: ISO Reversal Format

Miscellaneous Request		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9W0000	9W0000 = miscellaneous request.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Miscellaneous Request		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25		ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.2.4. Miscellaneous Request: ISO Reversal Response Format

Miscellaneous Request		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	9W0000	9W0000 = miscellaneous request.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.3. Miscellaneous Requests Inquiry (B4)

6.3.1. Miscellaneous Requests Inquiry: ISO Request Format

The miscellaneous requests inquiry transaction allows a customer, customer service representative, or branch employee to review any outstanding miscellaneous requests for a given customer.

Miscellaneous Requests Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B40000	B40000 = miscellaneous requests inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. On a continuation request, Key data fields will contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		0 or 1 or “ ”	0 = Initial request 1 = Continuation request “ ” = Space (indicates the defaults of 48.2 equals DC, 48.7 equals current date)

Miscellaneous Requests Inquiry		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.2	Search Direction	an 2		AC or DC	AC = Ascending DC = Descending
48.3	Key Data Type	an 1		0	0 = Transaction source date
48.4	Cumulative Transaction Count	n 3		n 3	
48.5	Reserved	an 1		an 1	
48.6	Filter Data	an 30		an 30	Not currently used . This field must contain spaces if it is present.
48.7	Key Data: Transaction Source Date	n 8		YYYYMMDD	If key data is present, filter data must be present.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.3.2. Miscellaneous Requests Inquiry: ISO Response Format

Miscellaneous Requests Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B40000	B40000 = miscellaneous requests inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. Key data fields will contain BASE24-billpay positioning information.
48.1 Request/Response Indicator		an 1		1	1 = Response
48.2 Search Direction		an 2		AC or DC	AC = Ascending DC = Descending
48.3 Key Data Type		an 1		0	0 = Transaction Source date
48.4 Cumulative Transaction Count		n 3		n 3	
48.5 Reserved		an 1		an 1	
48.6 Filter Data		an 30		an 30	Not currently used. This field must contain spaces if it is present.
48.7 Key Data: Transaction Source Date		n 8		YYYYMMDD	If key data is present, filter data must be present.

Miscellaneous Requests Inquiry		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. This field is returned in all approved transactions and in a subset of denied transactions.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.
125	Billpay Inquiry Data	ans ...1	C	Y	This field is returned if the transaction is approved and data is available. The value Y indicates whether the external data block is present
	External Data Block	ans ...4096	C	ans4096	See External Data Block structure below.

External Data Block Structure				
#	Name	ISO Format	Format	Comment
1	Count	n 2	0–5	Number of occurrences of miscellaneous details returned.
2	Additional Data Flag	an 1	Y or N	Y = Yes, more data possible. N = No, no more data. If the number of occurrences returned is less than the maximum defined in the IFCF, this field will be set to a value of N. Otherwise, it will be set to a value of Y.
3	Reserved	an 1		
Miscellaneous Requests Inquiry Response Structure Occurs as specified by the value of the Count field.				
1	Transaction Source Local Civil Time	n 20	YYYYMMDDhhmmssmmmmmm	
2	Family Name	an 20		

External Data Block Structure				
#	Name	ISO Format	Format	Comment
3	Given Name	an 10		
4	Phone Number	an 20		
5	FIID	an 4		
6	Contact Type	an 1	B, C, O or V	B = Bank C = Customer O = Other V = Vendor
7	Priority	n 1	1–5	1 is the highest priority and 5 is the lowest priority.
8	Request Type	an 1	C, Q or A	C = Complaint Q = Question A = Account maintenance
9	Department	an 22		
10	Contact Details	an 624		
11	File Maintenance Tag	an 75		
11.1	Group Number	n 5		
11.2	User Number	n 5		
11.3	Terminal Name	an 24		
11.4	AFT Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.5	OLTP Timestamp	n 20	YYYYMMDDhhmm mssmmmmmm	
11.6	Reserved	an 1		
12	Reserved	an 1		

6.3.3. Miscellaneous Requests Inquiry: ISO Reversal Format

Miscellaneous Requests Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B40000	B40000 = miscellaneous requests inquiry.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

Miscellaneous Requests Inquiry		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
95	Card Issuer Reference Data	ans..6		ans..6	The customer reference number. If this field is present in the original response, it must be echoed in the reversal.
98	Payee	ans 25		ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.3.4. Miscellaneous Requests Inquiry: ISO Reversal Response Format

Miscellaneous Requests Inquiry		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	B40000	B40000 = miscellaneous requests inquiry.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	ME	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
98	Payee	ans 25	ME	ans 25	Customer vendor number. This field is left-justified and blank-filled.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

6.4. Check Stop Payment Add (A0)

6.4.1. Check Stop Payment Add: ISO Request Format

This transaction request performs a check stop payment add transaction in a host pass-through environment only.

Check Stop Payment Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	A0nn00	A0nn00 = check stop payment add. nn = account type. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1	High Check Number	an 12			Contains the single check number to be stopped or the highest check number of the range.
48.2	Low Check Number	an 12			Spaces if a single check is to be stopped. Otherwise, this field contains the lowest check number of the range.

Check Stop Payment Add		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.3	Amount	an 18			The amount of the check to be stopped.
48.4	Stop Date	an 8		YYYYMMDD	Request should contain data for both 48.4 and 48.5, or optionally send blanks for both. If both are blanks, BASE24 defaults to the current date.
48.5	Stop Time	an 8		hhmmssst	Request should contain data for both 48.4 and 48.5, or optionally send blanks for both. If both are blanks, BASE24 defaults to the current time.
48.6	Expiration date	an 8		YYYYMMDD	The expiration date of the stop.
48.7	Description	an 35			Description for the stop payment that is being added. This field contains any additional information about the stop payment order.
48.8	Check Date	an 8		YYYYMMDD	
48.9	Filler	an 91			
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifier	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains account types selected by the customer.

6.4.2. Check Stop Payment Add: ISO Response Format

Check Stop Payment Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	A0nn00	A0nn00 = check stop payment add. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhhmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Field is sent but not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 High Check Number		an 12			Contains the single check number to be stopped or the highest check number of the range.
48.2 Low Check Number		an 12			Spaces if a single check is to be stopped. Otherwise, this field contains the lowest check number of the range.
48.3 Amount		an 18			The amount of the check to be stopped.
48.4 Stop Date		an 8		YYYYMMDD	Taken from request or provided by BASE24. The customer can also choose to have their host override the contents of the field.

Check Stop Payment Add		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
48.5	Stop Time	an 8		hhmmssstt	Taken from request or provided by BASE24. The customer can also choose to have their host override the contents of the field.
48.6	Expiration date	an 8		YYYYMMDD	The expiration date of the stop payment order.
48.7	Description	an 35			Description for the stop payment that is being added. This field contains any additional information about the stop payment order.
48.8	Check Date	an 8		YYYYMMDD	
48.9	Filler	an 91			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the BASE24 Remote Banking Standard Interface Support Manual for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	If this field is present in the request, it is echoed in the response.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account. Either field 102 or 123 is required.
126	Multiple Account Select Data	ans...757		ans...757	If multiple account selection is performed, this field contains multiple accounts and account descriptions.

6.4.3. Check Stop Payment Add: ISO Reversal Format

Check Stop Payment Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	A0nn00	A0nn00 = check stop payment add. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDDhhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the original response.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date / Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			

Check Stop Payment Add		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	<i>From</i> account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, <i>from</i> account (anp 4). Either field 102 or 123 is required.

6.4.4. Check Stop Payment Add: ISO Reversal Response Format

Check Stop Payment Add		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	A0nn00	A0nn00 = check stop payment add. nn = account type. Refer to the BASE24 Remote Banking Standard Interface Support Manual for valid account types.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
48	Additional Data, Private	ans...200	M	ans...200	Additional data. This field should be echoed from the reversal.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2	O	ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	From account. Either field 102 or 123 is required.
123	Account Qualifiers	anp...8	ME	anp...8	Account qualifier, from account (anp 4). Either field 102 or 123 is required.

7. PIN Messages

7.1. PIN Change (90)

7.1.1. PIN Change: ISO Request Format

The PIN change transaction allows a customer to change his or her PIN.

PIN Change		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	900000	900000 = PIN change.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
48	Additional Data, Private	ans...200	M	ans...200	
48.1 New PIn 1		an 16		an 16	The new PINs sent in a PIN change request have the same PIN block type and use the same verification method as the current PIN.
48.2 New PIn 2		an 16		an 16	The new PINs sent in a PIN change request have the same PIN block type and use the same verification method as the current PIN.

PIN Change		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.1.2. PIN Change: ISO Response Format

PIN Change		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	900000	900000 = PIN change.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

PIN Change		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.1.3. PIN Change: ISO Reversal Format

PIN Change		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	900000	900000 = PIN change.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

PIN Change		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.1.4. PIN Change: ISO Reversal Response Format

PIN Change		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	900000	900000 = PIN change.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.2. PIN Verify (91)

7.2.1. PIN Verify: ISO Request Format

The purpose of the PIN verify message is to verify a customer's PIN.

PIN Verify		Request/Repeat MTI = 1100/1101			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	910000	910000 = PIN verify.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
22	POS Data Code	an 12	O	61050061510S or 61050061510C	POS data code. A value of S in position 12 indicates that the PIN was verified locally, a value of C indicates that it was not verified locally. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	O	In the range of 1500–1999	Informational only, no default.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
52	PIN Data	an 16		b 16	PIN data. This field must be present, or position 12 of field 22 must be set to a value of S.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.2.2. PIN Verify: ISO Response Format

PIN Verify		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	910000	910000 = PIN verify.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
17	Capture Date	n 4	O	MMDD	The date this transaction was processed by the acquirer.
19	Country Code	n 3		n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
24	Function Code	n 3		n 3	Function code. This field is echoed from the request.
32	Acquiring Institution ID Code	n..11		n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28		an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. This field is returned if the transaction is approved.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
54	Additional Amounts	ans...120	C		Balance information returned if balances are configured to be returned in the BASE24 database. See the Account Balance Structure below.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

PIN Verify		Response MTI = 1110			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
96	Key Management Data	ans...114			Key management data. A new key is sent in the response if thresholds have been exceeded. Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

Account Balance Structure		The following structure can occur up to 6 times:			
#	Name	ISO Format	Format	Comment	
1	Account Type	n 2		ISO account type—Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for valid account types.	
2	Amount Type	n 2	01, 02, 03, 04, 05, 16, 17, 20	01 = Amount 1 ledger balance 02 = Amount 1 available balance 03 = Amount owed 04 = Amount due 05 = Available credit 16 = Amount 2 ledger balance 17 = Amount 2 available balance 20 = Amount remaining	
3	Currency Code	n 3			
4	Amount	x + n 12		Amount in whole and fractional currency units.	

7.2.3. PIN Verify: ISO Reversal Format

PIN Verify		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	910000	910000 = PIN verify.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not sent in the request, a BASE24 default is used.
24	Function Code	n 3	M	n 3	Function code.
25	Message Reason Code	n 4	M	In the range of 4000–4499	The reason for the reversal.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not sent in the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
56	Original Data Elements	n..35	M		This field identifies the transaction being reversed.
56.1 Original MTI		n 4			
56.2 Original System Trace Audit Number		n 6			
56.3 Original Local Date/Time		n 12			
56.4 Original Acquiring Inst ID Code Length		n 2			
56.5 Original Acquiring Inst ID Code		n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.

PIN Verify		Reversal/Repeat Reversal MTI = 1420/1421			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

7.2.4. PIN Verify: ISO Reversal Response Format

PIN Verify		Reversal Response MTI = 1430			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	C	b 16	Flags for fields 65–128.
2	Primary Account Number	n..19		n..19	Primary account number (PAN). This field is used if field 34 is not used.
3	Processing Code	an 6	M	910000	910000 = PIN verify.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	The BASE24 date and time of transaction initiation.
19	Country Code	n 3	O	n 3	Country code. If this field is not echoed from the request, a BASE24 default is used.
32	Acquiring Institution ID Code	n..11	O	n..11	Identification number of the acquiring institution. If this field is not echoed from the request, a BASE24 default is used.
34	PAN, Extended	an..28	O	an..28	Primary account number (PAN). This field is used if field 2 is not used.
38	Approval Code	anp 6		anp 6	Approval code. If this field is present in the original response, it must be echoed in the reversal.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
63	Source Code	ans...2		ans...2	Source code. If this field is not sent in the request, a BASE24 default is used.
102	Account ID 1	ans..28		ans..28	This field is not required. It can be used for the account number of a customer whose customer ID is an account number.

ACI Worldwide Inc.

8. Network Management and Administrative Messages

8.1. Network Management

8.1.1. Network Management Message: ISO Request Format

The purpose of the Network Management message is to control the system security. The device sends this message to BASE24 to indicate whether it has accepted or rejected the new key previously sent by BASE24 in a 1110/1210 message. Regardless of whether the device accepted the key, BASE24 responds with a NMM request response (MTI 1814). If the 1804 or 1805 message indicates that the device accepted the new key, the 1814 message marks the point at which BASE24 has put the key into use.

Network Management Message		Request/Repeat MTI = 1804/1805			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
11	System Trace Audit Number	n 6	M	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	M	YYMMDD hhmmss	BASE24 date and time of message initiation
24	Function Code	n 3	M	n 3	Function code.
56	Original Data Elements	n..35	M		
56.1	Original MTI	n 4		n 4	Zeros if the original MTI is not present.
56.2	Original System Trace Audit Number	n 6		n 6	This field must contain the system trace audit number of the message that contained the new key.
56.3	Original Local Date/Time	n 12		n 12	Zeros if the original MTI is not present.
56.4	Original Acquiring Inst ID Code Length	n 2		n 2	Zeros if the original MTI is not present.
56.5	Original Acquiring Inst ID Code	n..11		n..11	Zeros if the original MTI is not present.
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.
96	Key Management Data	ans...114			Refer to the <i>BASE24 Remote Banking Standard Interface Support Manual</i> for detailed information on the format of this field.

8.1.2. Network Management Message: ISO Response Format

Network Management Message		Response MTI = 1814			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
11	System Trace Audit Number	n 6	ME	n 6	A number, assigned by the transaction initiator, that is used to uniquely identify the transaction.
12	Local Date/Time	n 12	ME	YYMMDD hhmmss	BASE24 date and time of message initiation
24	Function Code	n 3	M	n 3	Function code. This field is echoed from the request.
39	Action Code	n 3	M	n 3	Action code. Refer to the BASE24 Remote Banking Transaction Processing Manual for valid action codes.
56	Original Data Elements	n..35	ME		This field is echoed from the request.
56.1	Original MTI	n 4			
56.2	Original System Trace Audit Number	n 6			
56.3	Original Local Date/Time	n 12			
56.4	Original Acquiring Inst ID Code Length	n 2			
56.5	Original Acquiring Inst ID Code	n..11			
59	Transport Data	ans...30		ans...30	Not used by BASE24. If the field is present in the request, it is echoed in the response.

8.2. Administrative Notify

8.2.1. Admin Notify Message: ISO Format

The purpose of the Administrative Notify message is to notify either the issuer or the acquirer that an external ISO message cannot be deciphered. In this case, the message is returned to the sender as a rejected message.

Admin Notify Message		MTI = 1644			
Bit #	Field Description	ISO Format	ISO Sta	Format	Comment
	Primary Bit Map	an 16	M	b 16	Flags for fields 1–64.
1	Secondary Bit Map	an 16	M	b 16	Flags for fields 65–128.
24	Function Code	n 3	M	n 3	Function code.
72	Data Record	ans...999	M		
72.1 Bit in Error		n 3		n 3, 200 or 201	Indicates the field of the message that is in error; set to 200 if the MTI is in error or 201 if the primary bit map is invalid.
72.2 Original Message		Var -> 996			The complete message that is being rejected.

ACI Worldwide Inc.