### **Backend - Appointment Booking**

### 1. POST /api/bookings/add

- **Description**: Add a new booking for a court. Ensures that double-booking for the same time slot is prevented.
- Method: POST
- URL: /api/bookings/add
- Request Body:
  - o courtId (string, required) The ID of the court to be booked.
  - o startTime (string, required) The start time of the booking in ISO 8601 format.
  - o customerName (string, required) The name of the customer booking the court.

### Sample Request:

}

```
json
{
  "courtId": "651234567890abcdef123456",
  "startTime": "2024-10-12T10:00:00Z",
  "customerName": "John Doe"
}
Sample Response (Success):
json
  "message": "Booking created successfully",
  "booking": {
    "_id": "651234567890abcdef123471",
    "court": "651234567890abcdef123456",
    "startTime": "2024-10-12T10:00:00Z",
    "endTime": "2024-10-12T11:00:00Z",
    "customerName": "John Doe",
    "createdAt": "2024-10-10T08:00:00Z"
  }
```

#### Sample Response (Error - Double Booking):

```
json
{
    "error": "Court is already booked for this time slot."
}
```

#### **Response Codes:**

- 201 Created: Booking was successfully created.
- 400 Bad Request: Missing or invalid input fields.
- 409 Conflict: Double booking attempt for the same court and time slot.
- 500 Internal Server Error: Error on the server-side while creating the booking.

## 2. GET /api/bookings/court/

- Description: Retrieve all bookings for a specific court by its ID.
- Method: GET
- URL: /api/bookings/court/:courtId
  - Replace :courtId with the actual ID of the court.

### Sample Request:

GET /api/bookings/court/651234567890abcdef123456

#### Sample Response:

#### **Response Codes:**

- 200 OK: Successfully retrieved all bookings for the court.
- 404 Not Found: The court with the specified ID was not found.
- 500 Internal Server Error: Error on the server-side while retrieving bookings.

## 3. GET /api/bookings/centers

- Description: Retrieve all centers with their sports and courts populated (excluding bookings).
- Method: GET
- URL: /api/bookings/centers

#### Sample Request:

GET /api/bookings/centers

### Sample Response:

```
"_id": "651234567890abcdef123456",
          "name": "Badminton Court 1"
        },
          "_id": "651234567890abcdef123459",
          "name": "Badminton Court 2"
      1
    },
      "_id": "651234567890abcdef123461",
      "name": "Squash",
      "courts": [
          "_id": "651234567890abcdef123460",
          "name": "Squash Court 1"
        },
          "_id": "651234567890abcdef123461",
          "name": "Squash Court 2"
        }
      1
    }
  1
},
  "_id": "651234567890abcdef123464",
  "name": "Koramangala Center",
  "location": "Koramangala, Bangalore",
  "sports": [
    {
      "_id": "651234567890abcdef123463",
      "name": "Tennis",
      "courts": [
          "_id": "651234567890abcdef123462",
         "name": "Tennis Court 1"
        },
```

```
{
        "_id": "651234567890abcdef123463",
        "name": "Tennis Court 2"
        }
        ]
        }
        ]
     }
     ]
}
```

### **Response Codes:**

- 200 OK: Successfully retrieved all centers with sports and courts.
- 404 Not Found: No centers found (if applicable).
- 500 Internal Server Error: Error on the server-side while retrieving centers.

## **API Endpoints Summary:**

Endpoint	Method	Description
/api/bookings/add	POST	Add a new booking (prevents double-booking)
/api/bookings/court/:c ourtId	GET	View all bookings for a specific court
/api/bookings/centers	GET	Retrieve all centers with their sports and courts

# Local Usage (EXAMPLE)

```
[POST]localhost:4000/api/bookings/add
[GET]localhost:4000/api/bookings/court/:courtId
```

[GET]localhost:4000/api/bookings/centers