

Sage Shield API Specification

Complete Endpoint Reference & Integration Guide for Frontend Developers & Administrators

Target Host: shield.sageconsolidated.com **Base Path:** /api/v1 **Auth Type:** Session Cookie (session_id)

1. Security Event Search & Ingestion API

GET /api/v1/events/logs — Unified AST Log Search

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Provides a unified security query engine across all connected enterprise integrations (Okta, Entra ID) and uploaded

file logs (CSV, Syslog, EVTX).

FRONTEND DEVELOPER DIRECTIVE:

Bind to the primary Log Search input. Use query parameter q to pass AST query strings (e.g. q= 'level=ERROR

"failed password").

Parameter	Type	Description
q	query string	AST Search Query (e.g. level=ERROR "unauthorized")
page / page_size	integer	Pagination controls (Default: page=1, page_size=50)
source_id	string (UUID)	Filter results by specific Integration Source ID

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"message": "Logs retrieved successfully",
```

```
"data": {
```

```
"logs": [
```

```
{
```

```
"id": "e4a21098-4c91-4a11-b8d2-109283746501",
```

```
"source_id": "89b12e34-5678-90ab-cdef-1234567890ab",
```

```
"event_type": "user.authentication.failure",
```

```
"severity": "HIGH",
```

```
"actor_email": "admin@company.com",
```

```
"ip_address": "192.168.1.100",
```

```
"created_at": "2026-08-09T10:15:30Z"
```

```
}
```

```
,
```

```
"pagination": {
```

```
"current_page": 1,
```

```
"page_size": 50,
```

```
"total_records": 1240
```

```
}
```

```
}
```

```
}
```

GET /api/v1/events/logs/:id — Get Log Event Detail

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Detailed forensic breakdown of an isolated security event, showing standardized attributes alongside the original raw

unparsed log payload.

FRONTEND DEVELOPER DIRECTIVE:

Call when a log row is clicked in the UI grid. Render normalized attributes in a key-value list and raw log text in a

monospace viewer.

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"data": {
```

```
"id": "e4a21098-4c91-4a11-b8d2-109283746501",
```

```
"source_id": "89b12e34-5678-90ab-cdef-1234567890ab",
```

```
"event_type": "user.authentication.failure",
```

```
"severity": "HIGH",
```

```
"actor_email": "admin@company.com",
```

```
"ip_address": "192.168.1.100",
```

```
"raw_log": "2026-08-09 10:15:30 [WARN] AuthFailed user=admin@company.com
```

```
ip=192.168.1.100",
```

```
"parsed_fields": {
```

```
"user": "admin@company.com",
```

```
"ip": "192.168.1.100",
```

```
"status_code": 401
```

```
}
```

```
}
```

```
}
```

POST /api/v1/events/logs/bulk-ingest — Bulk Log Stream Ingestion

STAKEHOLDER & ADMINISTRATOR PURPOSE:

High-throughput ingestion interface for streaming telemetry from agents, webhooks, and log forwarders.

FRONTEND DEVELOPER DIRECTIVE:

Send up to 500 log items per batch array. Ensure timestamps follow RFC3339 format.

SAMPLE REQUEST OBJECT:

```
{
```

```
  "source_id": "89b12e34-5678-90ab-cdef-1234567890ab",
```

```
  "logs": [
```

```
    {
```

```
      "raw_log": "2026-08-09T10:20:00Z [INFO] User login success
```

```
      user=jane@company.com",
```

```
"timestamp": "2026-08-09T10:20:00Z"
```

```
}
```

```
]
```

```
}
```

SAMPLE RESPONSE OBJECT (201 CREATED):

```
{
```

```
"success": true,
```

```
"message": "Bulk ingestion accepted",
```

```
"data": {
```

```
"ingested_count": 1,
```

```
"rejected_count": 0
```

```
}
```

```
}
```

2. Integrations & Data Sources API

POST /api/v1/integrations/ — Connect Integration Source

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Configures automatic log collection from cloud SaaS providers (Okta, Entra ID) or custom endpoints.

FRONTEND DEVELOPER DIRECTIVE:

Collect provider credentials via a multi-step modal wizard and POST to this endpoint.

SAMPLE REQUEST OBJECT:

```
{
  "name": "Corporate Okta Production",
  "provider": "okta",
  "config": {
    "domain": "company.okta.com",
    "api_token": "00a1b2c3d4e5f6g7h8i9"
  }
}
```

SAMPLE RESPONSE OBJECT (201 CREATED):

{

"success": true,

"message": "Integration source connected",

"data": {

"source_id": "89b12e34-5678-90ab-cdef-1234567890ab",

"name": "Corporate Okta Production",

"status": "ACTIVE"

}

}

GET /api/v1/integrations/logs-data/sources — List Integration Sources

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Provides a complete inventory of all connected security data sources and their operational statuses.

FRONTEND DEVELOPER DIRECTIVE:

Use to populate the Data Sources Table. Display status indicators (ACTIVE, SYNCING, ERROR, DISCONNECTED).

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
  "success": true,
```

```
  "data": [
```

```
    {
```

```
      "id": "89b12e34-5678-90ab-cdef-1234567890ab",
```

```
      "name": "Corporate Okta Production",
```

```
      "provider": "okta",
```

```
      "status": "ACTIVE",
```

```
      "last_sync_at": "2026-08-09T10:00:00Z"
```

```
    }
```

```
  ]
```

```
}
```

POST /api/v1/integrations/logs-data/sources/:id/sync — Trigger Manual Source Sync

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Forces an immediate poll cycle for cloud integrations without waiting for scheduled execution.

FRONTEND DEVELOPER DIRECTIVE:

Bind to a "Sync Now" button on the integration card. Show a loading spinner during execution.

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"message": "Synchronization triggered successfully"
```

```
}
```

3. Ingestion Health & Metrics API

GET /api/v1/integrations/logs-data/ingestion-health — Ingestion Health Overview

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Displays top-level health KPIs including total log throughput, ingestion rate (EPS), and active error rates.

FRONTEND DEVELOPER DIRECTIVE:

Populate top KPI cards on the Monitoring Dashboard. Update periodically or on manual refresh.

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"data": {
```

```
"total_events_ingested": 1450200,
```

```
"events_per_second": 48.5,
```

```
"active_sources_count": 8,
```

```
"error_rate_percentage": 0.02
```

```
}
```

```
}
```

4. Custom Log Parsers API

POST /api/v1/integrations/logs-data/parsers/:id/test — Test Custom Log Parser

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Allows security engineers to validate custom Grok/regex parsing logic against sample log lines before deploying to

production.

FRONTEND DEVELOPER DIRECTIVE:

Provide a side-by-side testing panel in the Parser Editor. Show extracted key-value fields upon test completion.

SAMPLE REQUEST OBJECT:

```
{
```

```
"sample_log": "2026-08-09 10:30:00 [ERROR] Connection refused from 10.0.0.5:8080"
```

```
}
```

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"data": {
```

```
"matched": true,
```

```
"extracted_fields": {
```

```
"timestamp": "2026-08-09 10:30:00",
```

```
"log_level": "ERROR",
```

```
"message": "Connection refused",
```

```
"source_ip": "10.0.0.5",
```

```
"source_port": "8080"
```

```
}
```

```
}
```

```
}
```

5. AI Data Quality & Automated Repair API

GET /api/v1/integrations/logs-data/data-quality — AI Quality Score Overview

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Returns aggregate AI Quality Score (0–100%) measuring log normalization fidelity across all connected sources.

FRONTEND DEVELOPER DIRECTIVE:

Render as a radial progress gauge. Display Green for score >85%, Yellow for 60–85%, Red for <60%.

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"data": {
```

```
"overall_quality_score": 92.5,
```

```
"normalized_fields_percentage": 94.8,
```

```
"unmapped_fields_count": 14,
```

```
"active_parsers_count": 12
```

```
}
```

```
}
```

GET /api/v1/integrations/logs-data/data-quality/ai-analysis — AI Diagnosis & Suggested

Fixes

STAKEHOLDER & ADMINISTRATOR PURPOSE:

AI analyzes unmapped log data and generates recommended Grok/regex parser patches automatically.

FRONTEND DEVELOPER DIRECTIVE:

Display AI Recommendation Cards showing unmapped field names and a "1-Click Fix" button.

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"data": {
```

```
"suggestions": [
```

```
{
```

```
"fix_id": "fix_ai_99182",
```

```
"parser_id": "3a12903c-8821-4d2b-9c12-3210984a1234",
```

```
"unmapped_field": "client_ip",
```

```
"suggested_pattern": "%{IP:client_ip}",
```

```
"confidence_score": 0.98
```

```
}
```

```
]
```

```
}
```

```
}
```

POST /api/v1/integrations/logs-data/data-quality/apply-suggested-fix — Apply AI 1-Click

Fix

STAKEHOLDER & ADMINISTRATOR PURPOSE:

Applies the AI-recommended parser patch directly into production without manual coding.

FRONTEND DEVELOPER DIRECTIVE:

Call when administrator clicks "Apply Fix". Refresh Data Quality Score upon completion.

SAMPLE REQUEST OBJECT:

```
{
```

```
"parser_id": "3a12903c-8821-4d2b-9c12-3210984a1234",
```

```
"fix_id": "fix_ai_99182"
```

```
}
```

SAMPLE RESPONSE OBJECT (200 OK):

```
{
```

```
"success": true,
```

```
"message": "AI parser fix applied successfully",
```

```
"data": {
```

```
"new_version": 2,
```

```
"updated_quality_score": 96.2
```

```
}
```

```
}
```

