Database Modification Problem 2

Language used : MySQL

SQL Statement :

INSERT INTO Location(LocNo,FacNo,LocName)

VALUES ('L107','F104','Door');

Snapshot :

Before :

```
mysql> select * from location;
+-------+-------+----------------+
| LocNo | FacNo | LocName        |
+-------+-------+----------------+
| L100  | F100  | Locker room    |
| L101  | F100  | Plaza          |
| L102  | F100  | Vehicle gate   |
| L103  | F101  | Locker room    |
| L104  | F100  | Ticket Booth   |
| L105  | F101  | Gate           |
| L106  | F100  | Pedestrian gate |
+-------+-------+----------------+
7 rows in set (0.00 sec)

mysql>
```

After :

```
mysql> INSERT INTO Location(LocNo,FacNo,LocName)
    -> VALUES ('L107','F104','Door');
Query OK, 1 row affected (0.05 sec)

mysql> select * from location;
+-------+-------+----------------+
| LocNo | FacNo | LocName        |
+-------+-------+----------------+
| L100  | F100  | Locker room    |
| L101  | F100  | Plaza          |
| L102  | F100  | Vehicle gate   |
| L103  | F101  | Locker room    |
| L104  | F100  | Ticket Booth   |
| L105  | F101  | Gate           |
| L106  | F100  | Pedestrian gate |
| L107  | F104  | Door           |
+-------+-------+----------------+
8 rows in set (0.00 sec)

mysql>
```