

CMS Mock Service - Extended Documentation

Customer Management System Mock Service - Now with Drivers, Clients, and Admins

Port: **3001**

Technology: **Python FastAPI**

Storage: **File-based JSON**

Table of Contents

- [Overview](#)
 - [Entity Types](#)
 - [API Endpoints](#)
 - [Data Models](#)
 - [Quick Start Examples](#)
 - [Advanced Usage](#)
 - [File Storage](#)
-

Overview

The CMS Mock Service now manages **four types of entities**:

1. **Customers** - Organizations or individuals using the logistics service
2. **Drivers** - Delivery personnel with vehicle assignments
3. **Clients** - Business clients with membership tiers
4. **Admins** - System administrators with role-based permissions

Key Features

- ✓ Full CRUD operations for all entity types
 - ✓ Status/role-based filtering
 - ✓ Thread-safe file storage
 - ✓ Automatic data persistence
 - ✓ Input validation with Pydantic
 - ✓ Auto-generated Swagger documentation
 - ✓ RESTful API design
-

Entity Types

1. Customers

Organizations or individuals who use the logistics service.

Fields:

- **id** - Unique identifier (UUID)

- **name** - Customer name
- **email** - Email address (validated)
- **phone** - Phone number (optional)
- **address** - Physical address (optional)
- **company** - Company name (optional)
- **status** - active | inactive | pending
- **created_at** - Creation timestamp
- **updated_at** - Last update timestamp

2. Drivers

Delivery personnel assigned to vehicles.

Fields:

- **id** - Unique identifier (UUID)
- **name** - Driver name
- **email** - Email address (validated)
- **phone** - Phone number (required)
- **license_number** - Driver's license number (required)
- **vehicle_id** - Assigned vehicle ID (optional)
- **status** - available | on_duty | off_duty | inactive
- **created_at** - Creation timestamp
- **updated_at** - Last update timestamp

3. Clients

Business clients with membership levels.

Fields:

- **id** - Unique identifier (UUID)
- **name** - Client/company name
- **email** - Email address (validated)
- **phone** - Phone number (optional)
- **address** - Physical address (optional)
- **membership_level** - basic | silver | gold | platinum
- **created_at** - Creation timestamp
- **updated_at** - Last update timestamp

4. Admins

System administrators with role-based access.

Fields:

- **id** - Unique identifier (UUID)
- **name** - Admin name
- **email** - Email address (validated)
- **phone** - Phone number (optional)

- `role` - super_admin | admin | moderator | support
- `permissions` - Array of permission strings
- `created_at` - Creation timestamp
- `updated_at` - Last update timestamp

API Endpoints

Health Check

GET /health

Returns service status and entity counts.

Response:

```
{
  "status": "healthy",
  "service": "CMS Mock Service",
  "entities": {
    "customers": 3,
    "drivers": 4,
    "clients": 5,
    "admins": 3
  }
}
```

Customers API

Base Path: `/customers`

Method	Endpoint	Description
GET	<code>/customers/</code>	Get all customers
GET	<code>/customers/{id}</code>	Get customer by ID
POST	<code>/customers/</code>	Create new customer
PUT	<code>/customers/{id}</code>	Update customer
DELETE	<code>/customers/{id}</code>	Delete customer

Drivers API

Base Path: `/drivers`

Method	Endpoint	Description
GET	/drivers/	Get all drivers
GET	/drivers/?status={status}	Filter drivers by status
GET	/drivers/{id}	Get driver by ID
POST	/drivers/	Create new driver
PUT	/drivers/{id}	Update driver
DELETE	/drivers/{id}	Delete driver

Status Filter Values: available, on_duty, off_duty, inactive

Clients API

Base Path: /clients

Method	Endpoint	Description
GET	/clients/	Get all clients
GET	/clients/?membership_level={level}	Filter by membership
GET	/clients/{id}	Get client by ID
POST	/clients/	Create new client
PUT	/clients/{id}	Update client
DELETE	/clients/{id}	Delete client

Membership Levels: basic, silver, gold, platinum

Admins API

Base Path: /admins

Method	Endpoint	Description
GET	/admins/	Get all admins
GET	/admins/?role={role}	Filter admins by role
GET	/admins/{id}	Get admin by ID
POST	/admins/	Create new admin
PUT	/admins/{id}	Update admin
DELETE	/admins/{id}	Delete admin

Admin Roles: super_admin, admin, moderator, support

Quick Start Examples

1. Get All Drivers

```
curl http://localhost:3001/drivers/
```

2. Create a New Driver

```
curl -X POST http://localhost:3001/drivers/ \
-H "Content-Type: application/json" \
-d '{
  "name": "John Driver",
  "email": "john@swiftlogistics.com",
  "phone": "+1-555-0100",
  "license_number": "DL12345678"
}'
```

3. Filter Drivers by Status

```
# Get all available drivers
curl "http://localhost:3001/drivers/?status=available"

# Get all drivers on duty
curl "http://localhost:3001/drivers/?status=on_duty"
```

4. Create a New Client

```
curl -X POST http://localhost:3001/clients/ \
-H "Content-Type: application/json" \
-d '{
  "name": "Tech Corp",
  "email": "contact@techcorp.com",
  "phone": "+1-555-0200",
  "address": "123 Business St, San Francisco, CA",
  "membership_level": "gold"
}'
```

5. Update a Driver Status

```
curl -X PUT http://localhost:3001/drivers/{driver_id} \
-H "Content-Type: application/json" \
-d '{
```

```
"status": "on_duty",  
"vehicle_id": "VH-123"  
'}
```

6. Filter Clients by Membership

```
# Get all platinum clients  
curl "http://localhost:3001/clients/?membership_level=platinum"
```

7. Create an Admin User

```
curl -X POST http://localhost:3001/admins/ \  
-H "Content-Type: application/json" \  
-d '{  
  "name": "Support Agent",  
  "email": "support@swiftlogistics.com",  
  "phone": "+1-555-0300",  
  "role": "support",  
  "permissions": ["tickets.read", "tickets.write", "customers.read"]  
'
```

Advanced Usage

Python Example

```
import requests  
  
BASE_URL = "http://localhost:3001"  
  
# Get all available drivers  
response = requests.get(f"{BASE_URL}/drivers/", params={"status":  
"available"})  
available_drivers = response.json()  
  
# Assign a driver to a delivery  
if available_drivers:  
    driver_id = available_drivers[0]["id"]  
    update_data = {  
        "status": "on_duty",  
        "vehicle_id": "VH-001"  
    }  
    requests.put(f"{BASE_URL}/drivers/{driver_id}", json=update_data)  
  
# Create a new client  
new_client = {
```

```
    "name": "Startup Inc",
    "email": "hello@startup.com",
    "membership_level": "silver"
  }
  response = requests.post(f"{BASE_URL}/clients/", json=new_client)
  client = response.json()
  print(f"Created client: {client['id']}")
```

JavaScript Example

```
const BASE_URL = 'http://localhost:3001';

// Get all platinum clients
async function getPlatinumClients() {
  const response = await fetch(`${BASE_URL}/clients/?membership_level=platinum`);
  const clients = await response.json();
  return clients;
}

// Create a new driver
async function createDriver(driverData) {
  const response = await fetch(`${BASE_URL}/drivers/`, {
    method: 'POST',
    headers: { 'Content-Type': 'application/json' },
    body: JSON.stringify(driverData)
  });
  return await response.json();
}

// Usage
const newDriver = {
  name: 'Alice Driver',
  email: 'alice@swiftlogistics.com',
  phone: '+1-555-0150',
  license_number: 'DL99887766'
};

createDriver(newDriver).then(driver => {
  console.log('Created driver:', driver.id);
});
```

File Storage

Each entity type is stored in a separate JSON file:

```
services/mocks/cms-mock/data/
├─ customers.json    # Customer records
```

```
|— drivers.json      # Driver records
|— clients.json     # Client records
|— admins.json      # Admin records
```

Data Persistence

- All changes are **immediately written** to disk
- **Thread-safe** file operations using locks
- **Atomic writes** prevent data corruption
- **JSON format** for easy inspection and backup

Example File Structure

drivers.json:

```
{
  "uuid-1": {
    "id": "uuid-1",
    "name": "Mike Wilson",
    "email": "mike@swiftlogistics.com",
    "phone": "+1-555-0201",
    "license_number": "DL123456789",
    "vehicle_id": "VH-001",
    "status": "available",
    "created_at": "2024-01-15T10:00:00",
    "updated_at": "2024-01-15T10:00:00"
  }
}
```

Swagger Documentation

Interactive API documentation is available at:

<http://localhost:3001/docs>

Features:

- Try out API endpoints directly
- View request/response schemas
- See all available filters and parameters
- Test authentication flows

Error Responses

All endpoints follow consistent error handling:

404 Not Found


```
{
  "detail": "Driver with id {id} not found"
}
```

422 Validation Error

```
{
  "detail": [
    {
      "loc": ["body", "email"],
      "msg": "value is not a valid email address",
      "type": "value_error.email"
    }
  ]
}
```

Architecture

```
cms-mock/
├── app.py                # FastAPI application
├── data/                 # JSON data files
│   ├── customers.json
│   ├── drivers.json
│   ├── clients.json
│   └── admins.json
├── src/
│   ├── config/
│   │   └── settings.py  # Configuration
│   ├── models/
│   │   └── schemas.py   # Pydantic models
│   ├── routes/
│   │   ├── cms_routes.py # Customer endpoints
│   │   ├── driver_routes.py # Driver endpoints
│   │   ├── client_routes.py # Client endpoints
│   │   └── admin_routes.py # Admin endpoints
│   ├── services/
│   │   ├── cms_service.py # Customer business logic
│   │   ├── driver_service.py # Driver business logic
│   │   ├── client_service.py # Client business logic
│   │   └── admin_service.py # Admin business logic
│   └── utils/
│       └── file_storage.py # File storage utility
```

Summary

The **extended CMS Mock Service** now provides comprehensive management for:

- ✓ **Customers** - End users and organizations
- ✓ **Drivers** - Delivery personnel with vehicle tracking
- ✓ **Clients** - Business clients with membership tiers
- ✓ **Admins** - System administrators with role-based access

All entities support:

- Full CRUD operations
- Filtered queries
- Status/role management
- Thread-safe persistence
- RESTful API design

Next Steps:

- Explore the Swagger UI at <http://localhost:3001/docs>
- Try the example requests above
- Integrate with your application
- Check the data files in [data/](#) directory