

# Python Mock Services Migration

---

## Overview

This document outlines the migration of Node.js mock services to Python using FastAPI.

## Services Migrated

### 1. CMS Mock Service (Customer Management System)

- **Port:** 3001
- **Location:** [services/mocks/cms-mock-python/](#)
- **Features:**
  - Customer CRUD operations
  - Customer status management (active, inactive, pending)
  - Email validation
  - Mock data initialization

### 2. ROS Mock Service (Route Optimization System)

- **Port:** 3002
- **Location:** [services/mocks/ros-mock-python/](#)
- **Features:**
  - Route CRUD operations
  - Route optimization algorithm
  - Distance and duration calculation
  - Route status tracking (planned, in\_progress, completed, cancelled)
  - Multiple stop support

### 3. WMS Mock Service (Warehouse Management System)

- **Port:** 3003
- **Location:** [services/mocks/wms-mock-python/](#)
- **Features:**
  - Inventory CRUD operations
  - SKU-based lookup
  - Stock level checking
  - Reorder level management
  - Warehouse location tracking
  - Inventory status management (available, reserved, out\_of\_stock, damaged)

## Technology Stack

- **Framework:** FastAPI 0.109.0
- **Server:** Uvicorn with auto-reload
- **Validation:** Pydantic 2.5.3
- **Configuration:** Pydantic Settings

- **CORS:** FastAPI CORS Middleware

## Project Structure

Each service follows the same structure:

```
service-name-python/
├── app.py                # Main application entry point
├── requirements.txt      # Python dependencies
├── Dockerfile           # Docker configuration
├── README.md            # Service documentation
├── .gitignore           # Git ignore patterns
├── src/
│   ├── __init__.py
│   ├── config/
│   │   ├── __init__.py
│   │   └── settings.py  # Configuration management
│   ├── models/
│   │   ├── __init__.py
│   │   └── schemas.py   # Pydantic models
│   ├── routes/
│   │   ├── __init__.py
│   │   └── *_routes.py  # API endpoints
│   ├── services/        # Business logic (CMS, ROS)
│   │   ├── __init__.py
│   │   └── *_service.py
│   ├── handlers/        # Business logic (WMS)
│   │   ├── __init__.py
│   │   └── *_handlers.py
│   └── utils/           # Helper functions (ROS)
│       ├── __init__.py
│       └── helpers.py
```

## Setup Instructions

### Option 1: Using Setup Script (Recommended)

```
# Run the setup script
./scripts/setup-python-mocks.sh

# Start all services
./scripts/start-python-mocks.sh

# Stop all services
./scripts/stop-python-mocks.sh
```

### Option 2: Manual Setup

For each service:

```
cd services/mocks/<service-name>-python

# Create virtual environment
python3 -m venv venv

# Activate virtual environment
source venv/bin/activate

# Install dependencies
pip install -r requirements.txt

# Run the service
python app.py

# Deactivate when done
deactivate
```

### Option 3: Using Docker

For each service:

```
cd services/mocks/<service-name>-python

# Build the image
docker build -t <service-name>-python .

# Run the container
docker run -p <port>:<port> <service-name>-python
```

## API Documentation

Each service provides automatic API documentation:

- **Swagger UI:** <http://localhost:<port>/docs>
- **ReDoc:** <http://localhost:<port>/redoc>

### CMS Mock Service (Port 3001)

- GET [/api/customers](#) - List all customers
- GET [/api/customers/{id}](#) - Get customer by ID
- POST [/api/customers](#) - Create customer
- PUT [/api/customers/{id}](#) - Update customer
- DELETE [/api/customers/{id}](#) - Delete customer

### ROS Mock Service (Port 3002)

- GET [/api/routes](#) - List all routes
- GET [/api/routes/{id}](#) - Get route by ID

- POST `/api/routes` - Create route
- PUT `/api/routes/{id}` - Update route
- DELETE `/api/routes/{id}` - Delete route
- POST `/api/routes/{id}/optimize` - Optimize route

## WMS Mock Service (Port 3003)

- GET `/api/inventory` - List all inventory items
- GET `/api/inventory/{id}` - Get item by ID
- GET `/api/inventory/sku/{sku}` - Get item by SKU
- POST `/api/inventory` - Create inventory item
- PUT `/api/inventory/{id}` - Update inventory item
- DELETE `/api/inventory/{id}` - Delete inventory item
- GET `/api/inventory/check-stock/{sku}` - Check stock level

## Testing

### Health Check

```
# CMS Mock
curl http://localhost:3001/health

# ROS Mock
curl http://localhost:3002/health

# WMS Mock
curl http://localhost:3003/health
```

### Sample API Calls

#### Create Customer (CMS)

```
curl -X POST http://localhost:3001/api/customers \
-H "Content-Type: application/json" \
-d '{
  "name": "Test Customer",
  "email": "test@example.com",
  "phone": "+1-555-0100",
  "address": "123 Test St",
  "company": "Test Corp"
}'
```

#### Create Route (ROS)

```
curl -X POST http://localhost:3002/api/routes \
-H "Content-Type: application/json" \
-d '{
  "origin": "New York, NY",
  "destination": "Boston, MA",
  "vehicle_id": "VEH-001",
  "driver_id": "DRV-001"
}'
```

### Create Inventory Item (WMS)

```
curl -X POST http://localhost:3003/api/inventory \
-H "Content-Type: application/json" \
-d '{
  "sku": "PROD-999",
  "name": "Test Product",
  "quantity": 100,
  "unit_price": 49.99,
  "reorder_level": 20
}'
```

## Key Features

### 1. Type Safety with Pydantic

All data models use Pydantic for automatic validation and serialization.

### 2. Automatic API Documentation

FastAPI generates interactive API documentation automatically.

### 3. CORS Support

All services have CORS configured to accept requests from any origin.

### 4. In-Memory Storage

Data is stored in memory with pre-populated mock data for testing.

### 5. Error Handling

Proper HTTP status codes and error messages for all operations.

### 6. Configuration Management

Environment-based configuration using Pydantic Settings.

## Migration Notes

Node.js → Python Equivalents

Node.js	Python
Express.js	FastAPI
package.json	requirements.txt
index.js	app.py
JavaScript modules	Python packages
npm/yarn	pip
node_modules/	venv/

Advantages of Python Implementation

- 1. **Type Hints:** Better IDE support and code clarity
- 2. **Automatic Validation:** Pydantic validates all input/output
- 3. **Auto-generated Docs:** Swagger UI and ReDoc out of the box
- 4. **Async Support:** Native async/await with FastAPI
- 5. **Data Models:** Clean separation with Pydantic models
- 6. **Less Boilerplate:** More concise code

Troubleshooting

Port Already in Use

```
# Find process using port
lsof -i :<port>

# Kill the process
kill -9 <PID>
```

Virtual Environment Issues

```
# Remove and recreate venv
rm -rf venv
python3 -m venv venv
source venv/bin/activate
pip install -r requirements.txt
```

Module Import Errors

Make sure you're running from the service root directory and the virtual environment is activated.

Next Steps

1. Update the main `docker-compose.yml` to include Python services
2. Update adapters to connect to Python mock services
3. Create integration tests for Python services
4. Add logging and monitoring
5. Implement persistent storage (optional)

## Support

For issues or questions:

- Check service logs
- Review API documentation at `/docs`
- Ensure all dependencies are installed
- Verify ports are not in use