

BAO Setup Notes

Docker command worked for me personally

```
docker run -p 127.0.0.1:5432:5432/tcp --add-host host.docker.inter
docker exec -it --user root <container_id> bash
```

Manual PSQL setup:

1. Install postgres@12: `brew install postgresql@12`
2. Add it to your PATH: `echo 'export PATH="/opt/homebrew/opt/postgresql@12/bin:$PATH"' >> ~/.bash_profile`
3. Restart terminal and check `postgres --version`
4. Create a role imdb (for modifying imdb database) `$ psql postgres`
→ `CREATE ROLE imdb;` **OR** `psql -U imdb`
Role imdb being used to add the rows to the database.
5. Add the data to your database: `pg_restore -U saharshbarve -d imdb <../../imdb_pg11>`
6. Verify

```
(base) Saharshs-Laptop-4:project-bao saharshbarve$ psql -U saharshbarve -d imdb
psql (12.22)
Type "help" for help.

imdb=# select count(*) from title;
 count
-----
2528312
(1 row)
```

7. Brew install gcc (check `gcc --version` check `clang --version` find clang path `which clang`)
8. Install bao extension: `make CC=/usr/bin/clang USE_PGXS=1 install`

```
(base) Saharshs-Laptop-4:pg_extension saharshbarve$ make CC=/usr/bin/clang USE_PGXS=1 install
/usr/bin/clang -Wall -Wmissing-prototypes -Wpointer-arith -Wdeclaration-after-statement -Werror=vla -Wendif-labels -Wmissing-format-attribute -Wformat-security -fno-strict-aliasing -fwrapv -fexcess-precision=standard -Wno-unused-command-line-argument -Wno-compound-token-split-by-macro -Wno-deprecated-non-prototype -O2 -I. -I./ -I/opt/homebrew/opt/postgresql@12/include/postgresql/server -I/opt/homebrew/opt/postgresql@12/include/postgresql/internal -I/opt/homebrew/Cellar/icu4c@76.1.1/include -isysroot /Library/Developer/CommandLineTools/SDKs/MacOSX15.sdk -I/opt/homebrew/opt/openssl@3/include -I/opt/homebrew/opt/readline/include -c -o main.o main.c
/usr/bin/clang -Wall -Wmissing-prototypes -Wpointer-arith -Wdeclaration-after-statement -Werror=vla -Wendif-labels -Wmissing-format-attribute -Wformat-security -fno-strict-aliasing -fwrapv -fexcess-precision=standard -Wno-unused-command-line-argument -Wno-compound-token-split-by-macro -Wno-deprecated-non-prototype -O2 -bundle -o pg_bao.so main.o -L/opt/homebrew/opt/postgresql@12/lib -isysroot /Library/Developer/CommandLineTools/SDKs/MacOSX15.sdk -L/opt/homebrew/opt/openssl@3/lib -L/opt/homebrew/opt/readline/lib -L/usr/lib -Wl,-dead_strip_dylibs -bundle_loader /opt/homebrew/Cellar/postgresql@12/12.22/bin/postgres
/bin/sh /opt/homebrew/opt/postgresql@12/lib/postgresql/pgxs/src/makefiles/../../config/install-sh -c -d '/opt/homebrew/opt/postgresql@12/lib/postgresql'
/bin/sh /opt/homebrew/opt/postgresql@12/lib/postgresql/pgxs/src/makefiles/../../config/install-sh -c -d '/opt/homebrew/opt/postgresql@12/share/postgresql@12/extension'
/bin/sh /opt/homebrew/opt/postgresql@12/lib/postgresql/pgxs/src/makefiles/../../config/install-sh -c -d '/opt/homebrew/opt/postgresql@12/share/postgresql@12/extension'
/usr/bin/install -c -m 755 pg_bao.so '/opt/homebrew/opt/postgresql@12/lib/postgresql/pg_bao.so'
/usr/bin/install -c -m 644 ./pg_bao.control '/opt/homebrew/opt/postgresql@12/share/postgresql@12/extension/'
/usr/bin/install -c -m 644 ./pg_bao--0.0.1.sql '/opt/homebrew/opt/postgresql@12/share/postgresql@12/extension/'
```

9. Postgresql update the conf file (uncomment and add `shared_preload_libraries = 'pg_bao'`)

```
#-----
# RESOURCE USAGE (except WAL)
#-----

# - Memory -

shared_buffers = 4GB                # min 128kB
                                     # (change requires restart)
#huge_pages = try                    # on, off, or try
                                     # (change requires restart)
#temp_buffers = 8MB                 # min 800kB
#max_prepared_transactions = 0      # zero disables the feature
                                     # (change requires restart)

# Caution: it is not advisable to set max_prepared_transactions nonzero unless
# you actively intend to use prepared transactions.
#work_mem = 4MB                     # min 64kB
#maintenance_work_mem = 64MB       # min 1MB
#autovacuum_work_mem = -1           # min 1MB, or -1 to use maintenance_work_mem
#max_stack_depth = 2MB              # min 100kB
#shared_memory_type = mmap          # the default is the first option
                                     # supported by the operating system:
                                     #   mmap
                                     #   sysv
                                     #   windows
                                     # (change requires restart)
dynamic_shared_memory_type = posix  # the default is the first option
                                     # supported by the operating system:
                                     #   posix
                                     #   sysv
                                     #   windows
                                     #   mmap
                                     # (change requires restart)

# - Disk -

#temp_file_limit = -1                # limits per-process temp file space
                                     # in kB, or -1 for no limit

# - Kernel Resources -

#max_files_per_process = 1000        # min 25
                                     # (change requires restart)
#shared_preload_libraries = 'pg_bao' # (change requires restart)
```

10. Restart postgresSQL: `brew services stop/start/restart postgresql@12`
11. Verify: `SHOW shared_preload_libraries;`
12. Verify: `imdb=# SHOW enable_bao;`

```
(base) Saharshs-Laptop-4:pg_extension saharshbarve$ psql postgres -U saharshbarve -d imdb
psql: warning: extra command-line argument "postgres" ignored
psql (12.22)
Type "help" for help.

imdb=# SHOW shared_preload_libraries;
shared_preload_libraries
-----
pg_bao
(1 row)

imdb=# SHOW enable_bao;
enable_bao
-----
off
(1 row)
```

- 13.